

DRILL HOLE # BGC02-13

Page 3 of 3

Date Drilled: Sept. 28, 2002

Contractor & Rig: Mine's Diamond Drill

Drill Method: Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.3 m

Co-ord: 13558.6N, 17448.6E (Mine Grid)

Logged by: G. Claypool

Project No. 0255-006-07

Reviewed by: J. Cassie

Notes: Brine Temp. = -3.5C, Thermocouple

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
21										21
	@ 21.3 to 24.4 m drill rate increase to 1.5 m/ min. No pump pressure. Minimal recovery.									
22										22
23										23
24										24
	@ 24.4 to 30.0 m: Drilling rate slows.									
25										25
	@ 26.0 m grades to: SAND, trace Silt, brown. 91.4% Sand 8.6% Silt and Clay									
26										26
27										27
28										28
29										29
30										30



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 30 m

DRILL HOLE # BGC03-01

Date Drilled: May 5, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 386.5 m

Co-ord: 13415.2N, 17369.7E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: No installation due to water pump failure.

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %		Installation / Backfill		Depth (m)
				Wp	WI			
				10	20	30	40	
0	Ground Surface 386.5							0
	SHALE (FILL) 0.0							0
	Cobble and gravel size, angular. 385.9							0
	TAILINGS 0.6							0
1	Frozen, no visible ice (unless noted), bonded, silt, some fine sand, layered	1						1
	@ 1.8 m: 25 mm thick ice lense in core run 1							1
2	@ 1.9 m: 39 mm thick zone with 50% ice.							2
								2
3		2						3
								3
4	@ 3.9 m fine sand, some silt							4
								4
5		3						5
								5
6	@ 6.0 m silt and fine sand	4						6
								6
7	@ 7.2 m: drill advanced with almost no applied head pressure.	5						7
								7
8								8
								8
9	@ 8.9 m: friable, Silt with some-trace sand, dilatant	6						9
								9
10	376.5							10
	10.0							10



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mines Ltd.

PROJECT: May 2003 Drill Program

Final Depth: 10.1 m

DRILL HOLE # BGC03-02

Date Drilled: May 6, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 386.5 m

Co-ord: 13409.1N, 17369.7E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: No installation due to pump failure.

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
0	Ground Surface 386.5									0
	SHALE (FILL) 386.2									
	Cobble and gravel sized. 0.3									
1	TAILINGS Frozen, no visible ice (unless noted), bonded, interbedded silt and coarse sand	1		x						1
2		2		x						2
3	@ 3.0 m interbedded light grey and gold colours, grades to silty fine sand, 10 mm thick interbeds of silt, some fine sand	3								3
4		4		x						4
5	@ 5.0 m silt with some sand	5		x						5
6		6								6
7	@ 7.3 m friable, fine sand, silty to some silt	7								7
8		8								8
9	@ 8.5 m: Almost no head pressure required to advance drill rods.	9		x						9
10		10								10



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 16.2 m

DRILL HOLE # BGC03-02

Page 2 of 2

Date Drilled: May 6, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 386.5 m

Co-ord: 13409.1N, 17369.7E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: No installation due to pump failure.

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %		Installation / Backfill		Depth (m)
				Wp	WI			
				10	20	30	40	
11								11
12	@ 11.6 m: Drill string sinks into tailings under self weight.							12
13								13
14	@ 14.3 m: Driller noted that head pressure was needed to advance drill string.							14
15	@ 15.4 m: Drill progress slows, rough drilling progress.							15
16	End of Borehole	370.3	16.2					16
17								17
18								18
19								19
20								20

Notes on drilling: Core catcher was removed after advancing to 16.2 m. No recovery. Could not re-seat the catcher. Casing was run down in an attempt to re-establish drill progress. However, the casing broke. The borehole was abandoned.



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 16.2 m

DRILL HOLE # BGC03-03

Date Drilled: May 7, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.3 m

Co-ord: 13292.2N, 17346.3E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: Thermocouple Installed

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %		Installation / Backfill		Depth (m)
				Wp	WI			
0	Ground Surface 387.3							0
0	SHALE (FILL) 387.1							0
0.2	Reddish stained, cobble and gravel sizes						Stick-up of 0.84 m Metal surface protector.	0
1	TAILINGS	1		x			T/C node @ -0.22 m	1
2	Frozen, no visible ice (unless noted), bonded. Sand, some silt with some 0.025 m thick interbeds of silt, trace sand.						T/C node @ 1.8 m	2
3	@ 2.5 m to 3.5 m: thinly banded (5-10mm) silt with trace sand	2		x			25 mm solid PVC pipe.	3
4	@ 3.5 m to 4.0 m: light grey, sand, trace silt						Backfilled with slough and crusher reject.	4
5	@ 5.0 m to 5.5 m: interbedded, with 10 mm thick silt zones.	3		x			T/C node @ 3.8 m	5
6	@ 5.2 m to 6.7 m: some thin (> 1 mm) ice lenses. Silt with trace clay, trace sand			x	x			6
7	@ 6.7 m to 7.0 m: ice lenses every 10 mm (1 mm thick), increase to 10 mm thick @ 7.0 m 380.3	4		x			T/C node @ 6.3 m	7
7	TILL 7.0	5						8
8	Frozen, visible ice, near larger clasts (3 mm thick), bonded, Cobbles and gravel, sandy, some silt, non plastic with fragments of frost shattered dolostone bedrock.							9
9	@ 9.2 m to 9.5 m: 30% visible ice as lenses (> 1 mm), sand and silt sediments, broken cobble sized rock with ice lenses around the large clasts.	6		x	x		T/C node @ 8.8 m	9
10	@ 9.45 m: 10 mm thick ice lens. 377.3			x				10
	10.0							


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 10.0 m

DRILL HOLE # BGC03-07

Page 1 of 3

Date Drilled: May 9, 2003

Location: Surface Cell

Project No. 0255-008-03

Contractor & Rig: BQ Mine's Diamond Drill

Elevation: 388.0 m

Reviewed by: J. Cassie

Drill Method: Chilled Brine Coring

Co-ord: 13724.9N, 17567.7E (Mine Grid)

Notes: Thermistor Installed, Tag #25-1

Hammer Type: N/A

Logged by: G. Ferris

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
0	Ground Surface 388.0									0
	SHALE (FILL) 0.0									
	Gravel and sand, angular.									
1	TAILINGS 387.2	1								1
	0.8									
	Frozen, no visible ice (unless noted), bonded. Sand, some silt, fine to medium grained.									
2		2								2
	@ 2.9 m: Interbedded sand and silt.									
3		3								3
	@ 3.0 m - 3.35 m: Silt, trace sand, 1 mm thick lenses, 1.5 mm thick lenses at 3.28 m.	4								
4		5								4
	@ 4.6 m - 5.9 m: Silt and sand, fine sand, 10%-30% visible ice as lenses, 1 mm thick, spaced 5 -6 mm, ice lenses thickness increases with depth.	6								
5		7								5
	@ 5.9 m: Ice lenses 10 -12 mm thick.									
6		8								6
	@ 7.2 m: 2 mm thick ice lenses, 50% visible ice.									
7	ICE 380.7	9								7
	7.3									
8		10								8
	@ 8.8 m to 9.4 m 40% soil.									
9										9
	378.6									
	9.4									
	378.3									
	9.8									
10										10



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 25.6 m

DRILL HOLE # BGC03-07

Date Drilled: May 9, 2003

Location: Surface Cell

Project No. 0255-008-03

Contractor & Rig: BQ Mine's Diamond Drill

Elevation: 388.0 m

Reviewed by: J. Cassie

Drill Method: Chilled Brine Coring

Co-ord: 13724.9N, 17567.7E (Mine Grid)

Notes: Thermistor Installed, Tag #25-1

Hammer Type: N/A

Logged by: G. Ferris

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
11	TAILINGS SAND, silty, medium, bonded, no visible ice.									11
	ICE estimated 5% soil	376.7	11							
	TAILINGS SILT, trace sand, 40% visible	11.3								
12	ice as lenses, 5mm thick ice lenses, bonded.	376.3				x				12
	ICE estimated 3% soil	11.7								
		375.8	12						T/M node @ 12.3 m	
		12.2								
13	TAILINGS SAND, trace silt, bonded, no visible ice (unless noted).					x				13
	@ 12.8 m: Silt, trace sand, 30% visible ice as 1 - 5 mm thick lenses.									
14	@ 13.25 m: Ice lenses increase to 10 mm thick, 50% visible ice.		13							14
	@ 13.4 m: 20% ice as lenses.									
		373.1								
15	ICE estimated 2 - 5% soil	14.9	14						T/M node @ 14.8 m	15
16										16
		371.6	15			x				
17	TAILINGS SILT, some sand, fine grained, 15% visible ice as 1 - 2 mm thick lenses.	16.4	16			x			T/M node @ 17.3 m	17
18										18
19			17							19
20	@ 19.5 m: Artesian pressure encountered, drill advanced with almost no head pressure.								T/M node @ 19.8 m	20


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 25.6 m

DRILL HOLE # BGC03-07

Date Drilled: May 9, 2003

Location: Surface Cell

Project No. 0255-008-03

Contractor & Rig: BQ Mine's Diamond Drill

Elevation: 388.0 m

Reviewed by: J. Cassie


Drill Method: Chilled Brine Coring

Co-ord: 13724.9N, 17567.7E (Mine Grid)

Notes: Thermistor Installed, Tag #25-1

Hammer Type: N/A

Logged by: G. Ferris


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 25.6 m

DRILL HOLE # BGC03-08

Date Drilled: May 10, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.0 m

Co-ord: 13620.9N, 17486.6E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: Borehole abandoned

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
0	Ground Surface 387.0									0
0	SHALE 0.0 Gravel, some cobbles, some sand, angular.								No installation.	0
1	TAILINGS 385.9 SAND, some silt, fine to medium grained, frozen, no visible ice (unless noted), bonded.	1							Backfilled with slough and fine shale.	1
2	@ 2.07 m: 62 mm thick zone of silt, 3% visible ice.	2								2
3	@ 2.57 m: 100 mm thick zone of shale, gravel and sand sized.	3								3
4	@ 3.05 m: Thick interbedded zone of silt, trace sand with sand, trace silt.	4								4
5	@ 4.01 m: 0.28 m long piece of metal encountered.	5								5
6	@ 4.19 m: 100 mm thick zone of gravel sized shale fragments.	6								6
7	@ 4.29 m: 25 mm thick zone with 50% ice.	7								7
8	@ 4.57 m: 25 mm thick interbedded silt, trace sand and sand, some silt, frozen, bonded, no visible ice.									8
9	End of Borehole 379.4 7.6									9
10	Core barrel was damaged. Hole abandoned.									10


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 7.6 m

DRILL HOLE # BGC03-09

Date Drilled: May 12, 2003

Location: Surface Cell

Project No. 0255-0008-03

Contractor & Rig: Mine's Diamond Drill

Elevation: 388.4 m

Reviewed by: J. Cassie

Drill Method: BQ Chilled Brine Coring

Co-ord: 13599.1N, 17478.4E (Mine Grid)

Notes: Thermistor Installed, Tag #25-2

Hammer Type: N/A

Logged by: G.Ferris

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
0	Ground Surface 388.4									0
	SHALE (FILL) 388.1									
	Gravel, sandy. 0.3									
1	TAILINGS SAND, some silt, medium, frozen, friable, no visible ice (unless noted).	1							Metal surface protector. Stick-up of 0.8 m	1
2	@ 1.52 m: 0.2 m of interbedded sand and silt sized material.	2							T/M node @ 1.2 m	2
3	@ 2.9 m: 0.3 m zone of silt, trace sand, 5% visible ice as lenses up to 3 mm thick,	3							T/M node @ 2.2 m	3
4	@ 4.57 m: Sand, and silt, fine.	4							25 mm solid PVC pipe.	4
5		5							T/M node @ 5.2 m	5
6		6							Backfilled using crusher reject and slough.	6
7		7							T/M node @ 7.7 m	7
8	@ 7.62 m: 0.31 m zone of silt, with 10% visible ice as lenses, ranging from 1 mm - 3 mm in thickness.	8								8
9	@ 9.14 m: 200 mm thick beds of alternating sand, some silt with silt, trace sand. Silt zones contain 5% visible ice as lenses, up to 3 mm thick.	9								9
10		10								10


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 27.4 m

DRILL HOLE # BGC03-09

Date Drilled: May 12, 2003

Location: Surface Cell

Project No. 0255-0008-03

Contractor & Rig: Mine's Diamond Drill

Elevation: 388.4 m

Reviewed by: J. Cassie

Drill Method: BQ Chilled Brine Coring

Co-ord: 13599.1N, 17478.4E (Mine Grid)

Notes: Thermistor Installed, Tag #25-2

Hammer Type: N/A

Logged by: G.Ferris

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
11	TAILINGS Thawed @ 10.67 m: Artesian pressure and running silt encountered. @ 12 m: Almost no head pressure required to advance drill rods. @ 16.76 m: Lost surface water return.	377.8 10.6	8		x					11
12										12
13										13
14										14
15										15
16										16
17										17
18										18
19										19
20			9							20


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 27.4 m

DRILL HOLE # BGC03-09

Page 3 of 3

Date Drilled: May 12, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 388.4 m

Co-ord: 13599.1N, 17478.4E (Mine Grid)

Logged by: G.Ferris

Project No. 0255-0008-03

Reviewed by: J. Cassie

Notes: Thermistor Installed, Tag #25-2

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
21	TAILINGS Thawed									21
22										22
23										23
24										24
25										25
26										26
27										27
28										28
29										29
30										30
	End of Borehole	361.0	27.4							



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 27.4 m

DRILL HOLE # BGC03-10

Date Drilled: May 13, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.9 m

Co-ord: 13639.5N, 17456.7E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: Thermistor Installed, Tag #30-1

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %		Installation / Backfill		Depth (m)
				Wp	WI			
0	Ground Surface 387.9							0
	SHALE (FILL) 387.07							
	Gravel, some sand, frozen, bonded, no visible ice. 0.2	1					Metal surface protector.	
1	TAILINGS							
	SAND, some silt, fine, frozen, bonded, no visible ice (unless noted).			x			Stick-up 0.9 m	1
2	@ 1.2 - 1.3 m: 40% visible ice.	2						
	@ 1.4 - 1.6 m: 3% visible ice.			x				2
	@ 1.7 - 1.9 m: Silt, sandy.							
	@ 2.2 - 3.0 m: Sand, some silt, medium to fine.						25 mm solid PVC pipe	
3	@ 2.56 - 2.59 m: 5% visible ice.			x			T/M node @ 2.2 m	3
	@ 3.2 - 3.4 m: 3 - 5% visible ice, SILT, some sand.	3						
4	@ 3.4 - 4.1 m: 5 - 7% visible ice, SILT, some sand.						Backfilled with crusher reject and slough.	4
	@ 4.2 - 4.4 m: Silt, and sand.	4						
5	@ 4.9 m: Shale fragments sloughed into hole and blocked core recovery from Core Run 3.	5					T/M node @ 4.7 m	5
6								
7		6						
8								
9		7					T/M node @ 7.2 m	7
10								


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 28.3 m

DRILL HOLE # BGC03-10

Date Drilled: May 13, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.9 m

Co-ord: 13639.5N, 17456.7E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: Thermistor Installed, Tag #30-1

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
				10	20	30	40			
11	@ 11.3 m: Lost surface return.	8								11
12		9								12
13										13
14										14
15										15
16										16
17										17
18										18
19	@ 18.9 m: Artesian pressure encountered.									19
20										20

T/M node @ 12.2 m

T/M node @ 17.2 m


BGC ENGINEERING INC.
 AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 28.3 m

Logged by: G. Ferris



Final Depth: 28.3 m

DRILL HOLE # BGC03-11

Page 1 of 3

Date Drilled: May 13, 2003

Contractor & Rig: Mine's Diamond Drill

Drill Method: BQ Chilled Brine Coring

Hammer Type: N/A

Location: Surface Cell

Elevation: 387.1 m

Co-ord: 13529.6N, 17371.1E (Mine Grid)

Logged by: G. Ferris

Project No. 0255-008-03

Reviewed by: J. Cassie

Notes: Thermistor Installed, Tag #25-3

Depth (m)	SOIL DESCRIPTION	Core Run	Recovery	Moisture Content %				Installation / Backfill		Depth (m)
				Wp	X	WI				
0	Ground Surface 387.1									0
	SHALE (FILL) 0.0									
	Gravel, and sand, frozen, friable. 386.7									
	0.4	1							T/M node @ 0.2 m	
									Metal surface protector.	
1	TAILINGS									1
	SAND, some silt, coarse, frozen, friable, visible ice as noted.	2							T/M node @ 1.2 m	
	@ 1.5 m: SAND, trace silt, coarse, bonded.			x						
2									Stick-up of 0.8 m	2
	@ 2.6 - 2.9 m: 25 mm thick interbedded coarse sand and silt layers, silt beds have 5% visible ice, one silt bed had 20% visible ice.	3							25 mm solid PVC pipe.	
				x						3
3										
		4							T/M node @ 4.2 m	4
4				x						
	ICE 382.8									
	4.3								Backfilled with slough and crusher rejects.	5
5		5								
6									T/M node @ 6.7 m	6
	TAILINGS 381.0									
	No recovery between 6.1 m - 19.8 m. 6.1									7
7										
8										
9									T/M node @ 9.2 m	9
10										10



BGC ENGINEERING INC.
AN APPLIED EARTH SCIENCES COMPANY

Calgary, AB

Phone (403) 250-5185

CLIENT: Nanisivik Mine, a Division of CanZinco Ltd.

PROJECT: Geotechnical Investigation

Final Depth: 24.5 m

Logged by: G. Ferris



Final Depth: 24.5 m