

Environmental Protection Operations Directorate
Suite 301, 5204 - 50th Avenue
Yellowknife, NT, X1A 1E2

June 1, 2007

Our file:

Manager of Licensing
Nunavut Water Board
PO Box 119
Gjoa Haven, Nunavut
X0B 1J0

Via Email: licensing@nunavutwaterboard.org

**RE: 1BR-ROB – Type “B” Water License Application (NIRB 07CN007), Remediation of Roberts Bay and Ida Bay
Proponent – Indian and Northern Affairs Canada (INAC)**

INAC has applied for a Type “B” Water License to support their work in remediating the Roberts Bay and Ida Bay abandoned silver mine sites in eastern Nunavut. These sites are located approximately 115 kilometres southwest of Cambridge Bay and are connected by a rough ATV trail. Summer air access is limited to float plane or helicopter and there is open water access between approximately June 15-September 15. Previous on-site assessments have identified the following issues to be remediated at these sites:

Roberts Bay

- Remaining infrastructure
- Tailings pond
- Waste rock
- Non-hazardous waste
- Hazardous waste
- Petroleum and metals impacted soil
- Mine openings

Ida Bay

- Remaining infrastructure
- Waste rock
- Mine openings
- Marine sediments

Environment Canada has the following general comments relative to this file:

1. Meeting the requirements of the *Fisheries Act* is mandatory, irrespective of any other regulatory or permitting system. Section 36(3) of the *Fisheries Act* specifies that unless authorized by federal regulation, no person shall deposit or permit the deposit of deleterious substances of any type in water frequented by fish, or in any place under any conditions where the deleterious substance, or any other deleterious substance that results from the deposit of the deleterious substance, may enter any such water. The legal definition of deleterious substance provided in subsection 34(1) of the *Fisheries Act*, in conjunction with court rulings, provides a very broad interpretation of deleterious and includes any substance with a potentially harmful chemical, physical or biological effect on fish or fish habitat.
2. The proponent shall not store materials on the surface ice of lakes or streams, except that which is for immediate use.

With respect to the transport, handling and storage of fuels and hazardous materials, Environment Canada has the following recommendations.

3. All sumps, pits, spill basins and fuel caches shall be located above the high water mark of any waterbody and in such a manner as to prevent the contents from entering any waterbody frequented by fish. Therefore, please note that maintaining a buffer of 30 m may not always be an adequate preventative measure.
4. Environment Canada recommends the use of secondary containment with an impervious liner, such as self-supporting insta-berms, for storage of all barreled fuel rather than relying on natural depressions to contain spills.
5. Secondary containment or a surface liner (drip pans, fold-a-tanks, etc) should be placed under all container or vehicle fuel tank inlet and outlet points, hose connections and hose ends during fuel or hazardous substance transfers. Secondary containment should be of adequate size and volume to contain and hold fluids for the purpose of preventing spills (the worst-case scenario).
6. The proponent shall have a Spill Contingency Plan in place prior to establishing any fuel caches.
7. Spill kits should be located along all transportation routes. Vehicles used in transporting fuel and chemicals should also be equipped with portable spill kits to allow for the efficient and expeditious response to spills.
8. The proponent shall ensure that any fuel or hazardous wastes associated with the proposed project are properly handled, transported and disposed of.
9. A supply of spill kits, shovels, barrels, sorbents, pumps, etc. shall be consistently maintained and readily available at all project locations.
10. Please note that fuels or hazardous materials cached for this study must be removed at the end of the project.
11. All releases of fuel or hazardous materials, **regardless of quantity**, are immediately reportable where the release is near or into a water body;
 - is near or into a designated sensitive environment or sensitive wildlife habitat;
 - poses an imminent threat to human health or safety; or
 - poses an imminent threat to a listed species at risk or its critical habitat.

The Spill Contingency Plan should include Jimmy Noble, Environment Canada's Enforcement Officer. Mr. Noble can be contacted at (867) 975-4644.

 - Please note that any spill of, regardless **of quantity**, shall be reported immediately to the NWT 24-hour Spill Line, (867) 920-8130.
12. Environment Canada's contact number is (867) 920-5131, a 24-hour emergency pager monitored by Emergency and Enforcement Officers.

If road construction/maintenance and quarrying activities are to be carried out, please note the following:

13. The proponent shall not deposit, nor permit the deposit of sediment into any water body. It is recommended that an undisturbed buffer zone of at least 100 metres be maintained between any proposed quarry operation and the normal high water mark of any water body.
14. Any stream crossings shall be located to minimize approach grades. Bank disturbance is to be avoided, and mechanized clearing should not be done immediately adjacent to any watercourse.

With respect to waste management at this site, please note the following:

15. All equipment and material brought to site for this project should be packed out on project completion.

16. All non-combustible solid wastes (e.g., potable water bottles) shall be disposed of at an appropriate facility. The proponent is encouraged to make use of recycling facilities for all recyclable materials.
17. Environment Canada recognizes that timely disposal of camp waste - specifically food waste - is of critical importance to minimize safety risks associated with wildlife attraction. Timely disposal is usually achieved through burning. However, burning of waste products releases numerous contaminants to the air, many of them persistent, bioaccumulative and toxic (e.g. polycyclic aromatic hydrocarbons - PAH's - heavy metals, chlorinated organics – dioxins and furans). These contaminants can result in serious impacts to human and wildlife health through direct inhalation and they can also be deposited to land and water, where they bioaccumulate through food chains affecting wildlife and country foods. Therefore, burning should only be considered after all other alternatives for waste disposal have been explored.
18. A variety of incineration devices are available and selection of the most appropriate will depend on considerations of technical and economical feasibility for each situation. For large, permanent camps and/or operational facilities (e.g. diamond mines), installation of an incineration device capable of meeting the emission limits established under the Canada-wide Standards (CWS) for Dioxins and Furans and the CWS for Mercury Emissions is required (both the Government of Canada and the Government of the Nunavut are signatories to these Standards and are required to implement them according to their respective jurisdictional responsibility). For small, temporary camps the use of a modified burn barrel may be acceptable. The proponent should review the incineration options available and provide justification for the selected device to the regulatory authority.
19. If burning is the only alternative available, the proponent should ensure that the waste is burned in a device that promotes efficient combustion and reduction of emissions, and that the amount of waste burned is reduced as much as possible. The use of appropriate waste incineration technology should be combined with a comprehensive waste management strategy (especially waste segregation) that is designed to reduce and control the volumes of wastes produced, transported, and disposed of.
20. Any **Waste Management Plan** should consider and include the following:
 - Purchasing policies that focus on reduced packaging;
 - On-site diversion and segregation programs (i.e. the separation of non-food waste items suitable for storage and subsequent transport and disposal or recycling);
 - If incineration is required, ensure diligent operation and maintenance of the incineration device and ensure appropriate training is provided to the personnel operating and maintaining the incinerator.
 - The objective should be to ensure that only food waste and food-contaminated waste is burned (the use of paper, cardboard and clean wood as supplementary fuel is acceptable).
 - Used absorbent materials, oily or greasy rags, and equipment servicing wastes (such as used engine oil, antifreeze, hydraulic oil, lead acid batteries, brake fluid and other lubricants) should be safely stored and transported in sealed containers (odor free to prevent animal attraction) and safely transported to a facility that is authorized for the treatment and disposal of industrial hazardous wastes.
21. Some past site assessments for the Roberts Bay site noted the potential for some of the waste rock to be acid generating. Environment Canada urges the proponent to only utilize waste rock in remediation works that are considered non acid generating.
22. Also, please note that any discharges from the tailings pond must be protective of the receiving environment. The proponent should ensure that adequate testing is carried out to ensure that if tailings water is pumped underground, the arsenic levels will not be harmful to the receiving environment.
23. Previous site investigations identified between 225-325 m³ of PHC impacted soil as well as elevated metals concentrations (arsenic, barium, chromium, copper, lead, nickel, silver and zinc) in some soil and waste rock piles. Please review the comments below with respect to landfarming PHC soils and please note the levels at which metal contaminated soils should not be landfarmed.

crude oils, hydraulic fluids									
waste petroleum products									

Please note that if any of the levels detected exceed these maximums, the contaminated soil should be considered hazardous waste and handled accordingly. Landfarming is not recommended for such contaminated soils.

- Total petroleum hydrocarbon (TPH) or total extractable hydrocarbons (TEH) < 3% (Yukon, 2004a and 2004b);
- total heavy metal concentrations < 2500 mg/L (USEPA, 1994)¹;
- electrical conductivity (EC) < 4 dS/m; and
- sodium adsorption ratio (SAR) < 6 (Alberta EUB, 1996).

Site Characterization

Given the circumstances of landfarm construction (i.e., an immediate reaction to a spill), no site characterization was carried out. This is important in order to determine the following parameters:

- groundwater flow, direction and baseline chemical analysis;
- native soil hydraulic conductivity determination;
- Microbial identification determination and population.
- A landfarm should be sited greater than 500 m from a permanent surface water body. This restriction applies to both potable and non-potable surface waters. The full nature of surface water flow at the site should be known.
- A landfarm should be sited greater than 500 m from a potable groundwater well.
- The geology of the site needs to be considered (e.g. thickness of underlying soil, the presence of bedrock, degree of fracturing) to determine the need a liner/barrier. It is recommended that at landfarm sites with less than 5 m of low hydraulic conductivity ($<10^{-6}$ cm/s) native underlying soil, a liner/barrier be used. It is important to determine if there is fractured bedrock at this site as fractured bedrock could make the investigation of groundwater flow, direction etc very problematic.
- The landfarm should be sited at a location with a natural slope of less than 5 %; otherwise the site will require grading.
- The landfarm should be sited where the groundwater table is greater than 3 m from the surface. When there is a need to excavate during landfarm construction, cultivation no closer than 3 m above the groundwater table must be ensured. Using groundwater flow direction and rate data, the landfarm should be sited such that groundwater contamination is avoided (otherwise, a barrier to groundwater flow is necessary).
- A landfarm should not be sited on land within a 50 year floodplain.
- Environment Canada has some concerns relative to the availability of adequate volumes of topsoil at the site that may be required to effectively manage and operate this facility.

Prior to landfarm design, an evaluation of the soil characteristics provided in **Table 2** will ensure that the contaminated soil is well-suited to landfarming.

Table 2: Optimal Soil Characteristics for Landfarming

Landfarming Parameter	Optimal Characteristics
Microbial population density:	For landfarming to be effective, the minimum heterotrophic plate count should be 10^3 CFU/g (colony forming units/gram). Below this minimum, landfarming may still be effective provided the existing bacteria are stimulated using nutrients or the soil is amended to increase the bacteria population (USEPA. 1994) In the latter case, adding non-indigenous bacteria to a site has had limited success in enhancing degradation of petroleum hydrocarbons. There are also

Landfarming Parameter	Optimal Characteristics
	regulatory restrictions associated with the addition of bacteria to sites.
Soil pH:	To support bacterial growth, soil pH should be between 6 and 8. Outside this range, landfarming may still be effective through soil amendments.
Moisture content:	Bacterial growth requires moisture, optimally between 40-85% of field capacity ² (USEPA, 1994). Periodically, moisture may be added to landfarmed soil to maintain this moisture level. Excess moisture due to periods of high precipitation, during spring thaw or due to poor site drainage may need to be addressed. Site drainage may be improved through landfarm design, but uncontrollable influx of moisture may simply mean that longer operating times will be required for the landfarm.
Nutrient concentration:	For proper growth, micro-organisms require inorganic nutrients that may be naturally-occurring in the soil. Nitrogen and phosphorous may be added in the form of commercial fertilizer. For effective biodegradation, carbon:nitrogen:phosphorus ratios need to be between 100:10:1 and 100:1:0.5 (USEPA, 1994). This ratio may be calculated from the soil bulk density and the total hydrocarbon concentration.
Soil Type:	Clayey soils hamper biodegradation because of difficulties in aeration and the distribution of nutrients and moisture. Soil amendments such as gypsum and bulking agents such as sawdust, may be required. Clumpy soils may also require pre-treatment in the form of shredding, in order for landfarming to be effective. Very coarse soils are not suitable to landfarming as they do not retain moisture and nutrients (University of Saskatchewan, 2002). Volatile compounds will also volatilize more readily from coarse-grain soils than from fine grain soils. Typically, large diameter soil particles have a low contamination concentration due to their low surface area. As such, these particles can be screened out prior to placing soils in the landfarm.

Once a landfarm is operating, generic or site-specific remediation limits as per the CCME Environmental Quality Guidelines (EQGs) or CWS-PHC should be used to monitor the extent to which the soil has been remediated to acceptable levels. The parameters analyzed during the environmental site assessment should be evaluated using these guidelines to determine chemicals of concern (CoCs) and those identified should be tracked during the remediation process.

Leachate Control

Groundwater sampling and analysis should adhere to the CCME sampling procedures (CCME 1993). Leachate monitoring performed during the landfarm operations is primarily for characterization purposes only, as leachate is often recirculated over the landfarm as a means of irrigation (or stored in a tank in the event that irrigation may be required at some point in the landfarming season). If this tank is discharged into the environment, the CCME EQGs apply as a standard.

A means to collect and treat run-off from the landfarm may be necessary. A leachate control system capable of handling a 24 hour duration, 1:10 year frequency storm is required in such a case. Leachate may be recirculated

² The most reliable measure of moisture content is expressed as a percent of field capacity (also referred to as "soil capacity"). Field capacity itself is the maximum %-weight of moisture the unconfined, gravity-drained soil can retain. An example would be a sandy soil with a field capacity of 25%, meaning a maximum of 250 grams of water retained in 1,000 grams (dry wt.) of unconfined soil. Typically the target moisture content is expressed as a percent of the field capacity; for example, 50% of field capacity for the above sandy soil would be 125 grams water per 1,000 grams dry soil.

over the landfarm soil surface as a means of irrigation to maintain optimal biodegradation rates, or discharged if surface water analyses indicate contaminant levels are within CCME EQGs. **Environment Canada strongly recommends a containment system where all leachate from the facility is fully controlled.**

Barriers/Liners

When native soils at the landfarm site have high conductivity, a barrier or liner having a maximum seepage rate equivalent to clay liner under 0.3 m head of water or a 10^{-7} cm/s hydraulic conductivity at a thickness of 0.6 m, should be used beneath the soil to be treated.

Placement of Soil in Landfarm

A contaminated soil depth less than 0.5 m within cell(s) or in windrows is recommended. However, the type of equipment available for tilling, as well as the land availability, will dictate soil depth. Typically, landfarming is practiced with soil depths between 0.30 and 0.45 m. Contaminated soil should not be applied on a continuous layer of snow or ice or when the existing soil base is saturated with moisture.

Landfarm Design/Operational Requirements

Land Availability

Please note that the expected landfarm soil depth of between 0.30 and 0.45 m and a maximum soil thickness of 0.5 m is recommended. Therefore, a single plot or multiple plots may be required. Additional area surrounding the plot(s) for berms and leachate control should be considered.

Microbial Population Density Monitoring

If microbial amendments are being considered, the user should be aware that products containing microorganisms, biochemicals (such as enzymes) or biopolymers, are "biotechnology products" and may be subject to the New Substances Notification (NSN) Regulations, pursuant to the Canadian Environmental Protection Act, 1999 (CEPA, 1999). (Contact the New Substances Division of Environment Canada and http://www.ec.gc.ca/substances/nsb/eng/index_e.htm for more information.)

Although a few petroleum hydrocarbon-degradable micro-organisms have been found to be active at temperatures below 0°C (Whyte and Greer, 1999; Whyte, *et al.* 2001 and 2003; Rike, *et al.* (2003)), most biodegradation occurs above freezing. Research has shown appreciable biodegradation may occur after one summer season, additional biodegradation over a second season is usually required. Therefore, it is recommended that the landfarm should operate for a minimum between 6 months to 2 years. This operation period assumes optimal conditions are maintained (i.e. regular tilling; moisture control; nutrient amendment, if required). Please note that soil sampling and analyses are required to confirm remediation progress and completion.

pH Maintenance

The optimal pH for landfarming operations is between 6 and 8. The soil pH may be increased with the addition of lime and decreased with the addition of elemental sulphur.

Moisture Content Monitoring

The amount of moisture in the landfarm soil impacts biodegradation and, therefore, should be monitored and adjusted if possible and necessary. If moisture levels are too high, the movement of air through the soil is restricted thereby reducing oxygen availability. Effective moisture levels are 40 - 85 % of water-holding capacity in the soil, but 20 - 85 % will support microbes. Water spraying is often needed during summer months, particularly prior to tilling, in order to reduce wind erosion. Soil may be amended with organic matter to increase moisture retention. A rule of thumb is the soil should be moist, not dry and dusty or dripping wet.

Nutrient Amendments Requirements

Biodegradation requires that micro-organisms are meeting nutritional requirements. The optimal range of carbon:nitrogen:phosphorus (C:N:P) is 100:10:1 to 100:1:0.5. If the available nutrients are not sufficient, soil amendment in the form of commercial fertilizers, is required. Note that the addition of nitrogen may inadvertently lower the pH. Nutrients can be supplied to the soil in either liquid or solid form. Solid nutrients can be added directly to the soil when the soil is mixed prior to placement in the landfarm or during tilling events once the landfarm is operational. Liquid nutrient can be added to watering or irrigation systems. The frequency of nutrient addition can be reduced by using slow release nutrients.

Tilling

Tilling, with a rototiller or turning over the soil with a backhoe or other similar equipment, is a means of aerating the soil. This provides oxygen for the micro-organisms as well as distributes nutrients and moisture in the soil, thereby aiding biodegradation. Tilling is recommended once per month during the operating season of the landfarm, provided the soil is uniformly moist but not saturated. Tilling when soil is excessively wet is unproductive, whereas tilling while the soil is excessively dry may erode the soil and cause wind-blown dust problems. Tilling must be carefully carried-out by an experienced operator, since it is possible to disturb or damage the liner placed under the contaminated soil.

System Maintenance

Maintenance of the landfarm is essential in ensuring its effectiveness. At some appropriate point during landfarm construction, inspection of the synthetic liner(s) should be conducted to ensure that the seams and joints are tight, and that there is an absence of punctures, blisters or tears. Imperfections (e.g. lenses, cracks, channels) can occur in soil and clay liners. Weekly, during landfarm operations, and immediately after a major storm or catastrophic event, inspections should be conducted on the:

- (i) drainage control systems for evidence of deterioration, malfunction, leaks or improper operation, and
- (ii) leachate collection systems to ensure proper functioning and to determine if leachate is being generated or is accumulating.

If any defects or malfunctioning works are detected, immediate repair is required to maintain the integrity of all works.

The drainage control system should be inspected as necessary/required during periods of precipitation or spring thaw to ensure control measures are taken if the system is approaching its capacity.

Closure Procedures

During the system design phase, it is important to determine the requirements for closing the site once remediation is complete. By laying out the closure procedures at this time, the responsible party or site sponsor can review and endorse them prior to proceeding with the system construction. This closure plan should be consistent with the current land use and will need to recognize how future land use changes or ownership will be taken into consideration after landfarm closure.

Monitoring and Record Keeping Requirements

For the purpose of monitoring the performance of the land treatment process, soil samples should be taken no less frequently than once every four months, during the period of active land treatment to monitor contamination levels until analytical results are below acceptable levels as set forth in the CCME's Canadian Soil Quality Guidelines (CSQG). The once a month sampling program as described by MHBL is adequate.

For the purpose of monitoring for potential impact of the facility on groundwater quality in the active layer, groundwater samples should be taken from the down gradient monitoring wells no less frequently than twice per year and analyzed for indicators of petroleum hydrocarbon contamination. Should analytical results indicate

groundwater contamination associated with the land treatment facility, corrective action should be taken as soon as possible.

A sampling plan should include sampling methods (grid, composite) and frequency (number of samples per surface area). Since the landfarmed material is relatively thinly applied and homogenized through tilling, only one depth of sample collection is required. The samples should then be analyzed for the contaminants of interest and compared with the remediation guidelines presented in the CCME EQG and the CWS-PHC documentation. These protocols are recommended for the landfarm soils to determine at which point the soils have been remediated and the landfarm can be closed. Monitoring of contaminant levels in the leachate is only required prior to discharge to the environment; during recirculation, testing may be done for purposes of tracking remediation progress. It is also recommended that groundwater on-site be monitored and compared to the appropriate CCME EQGs. **Table 3** summarizes the criteria that should be used for the various media involved in landfarming operations.

The landfarm soils may be considered remediated once analyses confirms these soils are within the CCME EQGs or CWS-PHC for the particular land use of the property. The remediated soil may then be used in a manner that is consistent and appropriate with the site use. If other contaminant levels (such as heavy metals, PCBs, etc.) exceed CCME EQGs, the landfarmed materials should be then further remediated using an alternative remediation technique.

Accurate records should be maintained by the owner/operator which contain the following information:

- A detailed description of the size and location of the land treatment facility
- Quantitative and qualitative data on the soil treated at the site
- Monitoring data as set forth above
- The final destination of the treated soil and its intended use.

Table 3: Summary of Landfarming Standards for Federal Contaminated Sites

Media Monitored	Criteria
Landfarm soil and soil remaining at the delineated (excavation) site	Canada Wide Standard for Petroleum Hydrocarbons (CWS-PHC) (CCME, 2003)
	Canadian Soil Quality Guidelines for the Protection of Environmental and Human Health (CCME, 2003)
Groundwater	Non-potable - none; as per <i>A Federal Approach to Contaminated Sites</i> (CSMWG, 1999) whereby provincial/territorial guidelines are recommended. Potable - Guidelines for Canadian Drinking Water Quality (Health Canada, 1996)
Leachate	For recirculation – none (operations monitoring only) For discharge to environment ▪ Into surface water: CCME Environmental Quality Standard (EQS) for Freshwater Aquatic Life (CCME, 2003) for surface water reception; and ▪ Into groundwater: none, as per <i>A Federal Approach to Contaminated Sites</i> (CSMWG, 1999) whereby provincial/territorial guidelines are recommended
Surface Water	CCME Environmental Quality Standard (EQS) for Freshwater Aquatic Life (CCME, 2003) or, for potable water, the Guidelines for Canadian Drinking Water Quality (Health Canada, 1996)
Ambient Air	Canadian National Ambient Air Quality Objectives: Process and Status (CCME, 2003)

The Canadian Wildlife Service (CWS) of Environment Canada has reviewed the above-mentioned submission and makes the following comments and recommendations pursuant to the *Migratory Birds Convention Act* (the *Act*) and *Migratory Birds Regulations* (the *Regulations*), and the *Species at Risk Act* (SARA).

26. Details on what to do if the case of a wildlife encounter was contained in the "Spill Contingency Plan". This is potentially confusing to have this information imbedded within the spill information. Environment Canada recommends that only relevant spill information be contained in the Spill Contingency Plan and that information on wildlife encounters be put in a separate section or report.
27. Section 6 (a) of the *Migratory Birds Regulations* states that no one shall disturb or destroy the nests or eggs of migratory birds. The Environmental Assessment report prepared by AMEC (16 February 2007) states that activities will be scheduled around breeding times to avoid effects on breeding birds and that facilities will not be demolished in the immediate vicinity of nests while birds are nesting. Although it appears that the proponent has been able to schedule some activities outside of the breeding bird season, there still are some activities scheduled for June and July that will overlap with the nesting season. The Environmental Assessment report also states that a qualified environmental professional will conduct a field assessment of the area encompassing the Ida Bay barge loading site and mine site prior to commencing the proposed remediation activities. In addition or as part of the field assessment, Environment Canada recommends that the proponent confirm that there are no active nests (i.e. nests containing eggs or young) in the vicinity of their operations before activities during the nesting season commence. This confirmation of no active nests should be done each year immediately prior to any activities in a specific area. If active nests of migratory birds are discovered, the proponent should halt all activities in the nesting area until nesting is completed (i.e. the young have left the vicinity of the nest).
28. If the remediation activities could result in the removal of a nest with eggs or young (despite the mitigation measures listed above), Environment Canada recommends that the proponent contact Canadian Wildlife Service of Environment Canada to determine the appropriate action(s).
29. The Environmental Assessment report prepared by AMEC (16 February 2007) referred to past discussions with Canadian Wildlife Service of Environment Canada regarding the importance of the coastal areas of Melville Sound, Elu Inlet and Bathurst Inlet for Common Eiders for nesting, molting and rearing their young. These areas are considered to be core breeding areas to eiders based on surveys conducted throughout the central arctic in 1995 and 1996. Canadian Wildlife Service does not have specific data for Ida Bay, although the general area is known to be important to eiders from mid-June to late October. Environment Canada again recommends that a field investigation be conducted prior to remedial activities to determine whether eiders use the coastal area proximate to the Ida Bay mine site and, if so, at what times of the year. If these areas are being used by Common Eiders, Environment Canada recommends that the timing of barging activities and remediation activities near the coast be adjusted to minimize disturbance to eiders using the area at this time.
30. In order to reduce disturbance to nesting birds, Environment Canada recommends that aircraft used in conducting project activities maintain a flight altitude of at least 610 m during horizontal (point to point) flight unless safety or cloud ceiling do not permit.
31. In order to reduce disturbance to resting, feeding, or moulting birds, Environment Canada recommends that aircraft used in conducting project activities maintain a vertical distance of 1000 m and minimum horizontal distance of 1500 m from any observed concentrations (flocks / groups) of birds.
32. Environment Canada recommends that camp waste be made inaccessible to wildlife at all times. Camp waste can attract predators of migratory birds (e.g., foxes and ravens) to an area if not disposed of properly.
33. Section 35 of the *Migratory Birds Regulations* states that no person shall deposit or permit to be deposited, oil, oil wastes or any other substance harmful to migratory birds in any waters or any area frequented by migratory birds.
34. All mitigation measures identified by the proponent, and the additional measures suggested herein, should be strictly adhered to in conducting project activities. This will require awareness on the part of the proponents' representatives (including contractors) conducting operations in the field. Environment Canada

recommends that all field operations staff be made aware of the proponents' commitments to these mitigation measures and provided with appropriate advice / training on how to implement these measures.

35. Implementation of these measures may help to reduce or eliminate some effects of the project on migratory birds, but will not necessarily ensure that the proponent remains in compliance with the *Migratory Birds Convention Act* (the *Act*) and *Migratory Birds Regulations* (the *Regulations*). The proponent must ensure they remain in compliance with the *Act* and *Regulations* during all phases and in all undertakings related to the project.
36. The following comments are pursuant to the Species at Risk Act (SARA), which came into full effect on June 1, 2004. Section 79 (2) of SARA, states that during an assessment of effects of a project, the adverse effects of the project on listed wildlife species and its critical habitat must be identified, that measures are taken to avoid or lessen those effects, and that the effects need to be monitored. This section applies to all species listed on Schedule 1 of SARA. However, as a matter of best practice, Environment Canada suggests that species on other Schedules of SARA and under consideration for listing on SARA, including those designated as at risk by the Committee on the Status of Endangered Wildlife in Canada (COSEWIC), be considered during an environmental assessment in a similar manner.

Species at Risk that may be encountered	COSEWIC Designation	Schedule of SARA	Government Organization with Primary Management Responsibility ¹
Short-eared Owl	Special Concern	Schedule 3	Government of Nunavut
Peregrine Falcon (subspecies tundrius)	Special Concern	Schedule 3	Government of Nunavut
Barren-ground Caribou (Dolphin and Union population)	Special Concern	Pending	Government of Nunavut
Grizzly Bear	Special Concern	Pending	Government of Nunavut
Wolverine (Western Population)	Special Concern	Pending	Government of Nunavut
Polar Bear	Special Concern	Pending	Government of Nunavut

¹ Environment Canada has a national role to play in the conservation and recovery of Species at Risk in Canada, as well as responsibility for management of birds described in the *Migratory Birds Convention Act* (MBCA). Day-to-day management of terrestrial species not covered in the MBCA is the responsibility of the Territorial Government. Thus, for species within their responsibility, the Territorial Government is best suited to provide detailed advice and information on potential adverse effects, mitigation measures, and monitoring.

Impacts could be disturbance and attraction to operations.

Environment Canada recommends:

- Species at Risk that could be encountered or affected by the project should be identified and any potential adverse effects of the project to the species, its habitat, and/or its residence noted. Refer to the Species at Risk registry at www.sararegistry.gc.ca for information on specific species.
- If Species at Risk are encountered or affected, the primary mitigation measure should be avoidance. The proponent should avoid contact with or disturbance to each species, its habitat and/or its residence.
- The proponent should record the locations and frequency of any observations of Species at Risk and note any actions taken to avoid contact or disturbance to the species.
- For species under the responsibility of the Territorial Government, the Territorial Government should be consulted to identify other appropriate mitigation and/or monitoring measures to minimize effects to these species from the project.
- Mitigation and monitoring measures must be taken in a way that is consistent with applicable recovery strategies and action/management plans.

If there are any changes in the proposed project, EC should be notified, as further review may be necessary. Please do not hesitate to contact me with any questions or comments with regards to the foregoing at (867) 669-4708 or by email at ivy.stone@ec.gc.ca.

Sincerely,

Original signed by

Ivy Stone
Environmental Assessment / Contaminated Sites

CC: Mike Fournier (Northern EA Coordinator, EPOD, Environment Canada, Yellowknife, NT)
Miles Constable (Risk Assessment Specialist, EPOD, Environment Canada, Edmonton, AB)
Myra Robertson (EA Coordinator, CWS, Environmental Stewardship Branch)

ⁱ Modified from: Environment Canada. 1993. "Appendix 3: Guidelines on the Ex-Situ Bioremediation of Petroleum Hydrocarbon Contaminated Soils on Federal Crown Land" in the *Study on the Use of Landfarming and Surface Impoundments in the Management of Hazardous and Non-Hazardous Waste*. Conservation and Protection. June 23, 1993.

ⁱⁱ Heavy metal analyses required to determine if constituents are not present at levels toxic to micro-organisms (>2500 mg/L) (USEPA. 1994). (Soils with heavy metal concentrations below this level but above remediation criteria, will have to undergo further treatment following landfarming to reduce heavy metal concentrations.)