

# Product Information



15640 Mountainview Dr., White Rock, BC V4P 2W9 • Tel: (604) 535-6699 Fax: (604) 535-5493

## ***Extreme Number One***

### **Granular Drilling Mud Polymer**

#### ***Description***

Ultra High Grade, Anionic, Acrylamide Copolymer in the form of a free flowing coarse white powder.

#### ***Principle Use***

The Number One choice for demanding hole conditions when Bentonite is unavailable or unwanted. A one product drilling fluid. Excellent for winter. Product does not freeze in container. Economical. Ultra High Grade means less product required on jobs and less product to fly into remote sites. Lifts cuttings and stabilizes the hole. Reduces torque and drag in the hole. Greatly reduces swelling of clays and shales. Can be used to make stiff foam for air drilling. Environment Friendly. Extremely Effective.

#### ***Mixing***

Add a small amount of Extreme Number One to water in the mixing tank. Sprinkle slowly into turbulent water when mixer is on high. Increase the quantity added of Extreme Number One if hole conditions are difficult. For fast mixing, add Extreme Number One to a small amount of vegetable oil first and then pour quickly into turbulent water.

#### ***Packaging***

Extreme Number One comes in 5 gallon, high impact plastic pails with a snap-on lid. 24 pails per pallet.

# MATERIAL SAFETY DATA SHEET



5540 Mountainview Dr., White Rock, BC V4P 2W9 • Tel: (604) 535-6699 Fax: (604) 535-5497

**EMERGENCY PHONE NO. (604) 535-6699**

PAGE 1 OF 5

## WHMIS HAZARD INDEX:

### DEGREE OF HAZARD:

HEALTH 1  
FIRE 0  
REACTIVITY 0  
OTHER: B (GLASSES & GLOVES)

### HAZARD RATING:

0 LEAST  
1 SLIGHT  
2 MODERATE  
3 HIGH  
4 EXTREME

## SECTION 1

## PRODUCT IDENTIFICATION

PRODUCT NAME:	EXTREME NUMBER ONE
CHEMICAL IDENTIFICATION:	Acrylamide, Acrylate Copolymer
MATERIAL USE:	Drilling Fluid Additive
WHMIS CLASSIFICATION:	Not Regulated
WORK PLACE HAZARD:	Not Applicable

## TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION:	Not Dangerous Goods
PACKAGE GROUP:	Not Applicable
CAS NUMBER:	Not Applicable
MSDS CODE:	Not Applicable

## SECTION 2

## HAZARDOUS INGREDIENTS

INGREDIENT:	None Considered Hazardous
PERCENTAGE:	Not Available
CAS NUMBER:	Not Available
LD (50):	Not Available
LC (50):	Not Available

## EXTREME NUMBER ONE

## MATERIAL SAFETY DATA SHEET

## SECTION 3

## PHYSICAL DATA

APPEARANCE AND ODOUR	Slight, mild odour, white, granular solid
DENSITY (SPECIFIC GRAVITY)	.80
BOILING POINT:	Not Available
MELTING POINT:	Not Available
SOLUBILITY:	Soluble
EVAPORATION RATE: (EE=1):	Not Available
VAPOUR PRESSURE: (MM HG):	Not Available
VAPOUR DENSITY: (AIR = 1):	Not Available

## SECTION 4

## FIRE AND EXPLOSION

FLASHPOINT:	Not Applicable
FLAMMABLE LIMIT:	Not Available
AUTO IGNITION TEMP:	No Data
EXTINGUISHING MEDIA	Dry Chemical, Carbon Dioxide, Foam
SPECIAL FIRE FIGHTING PROCEDURES:	Self-Contained Respirators For Fire Fighting Personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Products of incomplete combustion and oxides of nitrogen and carbon.

## SECTION 5

## REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.):	Stable
INCOMPATIBILITY (CONDITIONS TO AVOID):	Strong oxidizing agents and highly alkaline solutions
HAZARDOUS POLYMERIZATION:	Will not occur
HAZARDOUS DECOMPOSITION PRODUCTS:	None

## MATERIAL SAFETY DATA SHEET

EXTREME NUMBER ON

## SECTION 6

## HEALTH HAZARDS

ROUTE OF ENTRY:

(X) SKIN

(X) EYE CONTACT

(X) INHALATION

(X) INGESTION

SKIN CONTACT:

May be minimally irritating to sensitive skin upon prolonged direct contact.

EYE CONTACT:

May be minimally irritating to eyes upon direct contact.

INHALATION:

May cause irritation to nose and throat.

## SECTION 7

## PREVENTATIVE MEASURES

SKIN PROTECTION:

Impervious gloves, protective clothing as required Goggles.

EYE PROTECTION:

General mechanical; 10 changes per hour.

VENTILATION:

Approved dust mask; MESA type

RESPIRATORY PROTECTION:

Ventilate area, wear rubber boots, gloves and a self-contained respirator if ventilation inadequate.

LEAK &amp; SPILL PROCEDURE:

Collect into waste container. wash site after pick up. Water solutions extremely slippery.

WASTE DISPOSAL:

Dispose in compliance with government regulations and local requirements.

STORAGE REQUIREMENTS:

Cool, dry area, away from oxidizing and reducing agents. Keep containers closed when not in use. Avoid prolonged contact when handling. Do not inhale dust.

## EXTREME NUMBER ONE

## MATERIAL SAFETY DATA SHEET

SECTION 8FIRST AID MEASURES

SKIN:

Wash thoroughly with soap and warm water

EYE:

Flush with water for at least 15 minutes. Seek medical attention.

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.

INGESTION:

Do not induce vomiting. If conscious, dilute by giving two glasses of water. Seek medical attention.

SECTION 9PREPARATION DATE

DATE ISSUED:

AUGUST 20, 1996

BY:

PRODUCT SAFETY COMMITTEE

THE DATA REPRESENTED HEREIN IS BELIEVED ACCURATE AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.

DATE REVISED:

## MATERIAL SAFETY DATA SHEET

EXTREME NUMBER ON

## ADDENDUM

## SECTION 10

## ECOLOGICAL INFORMATION

## ACUTE TOXICITY:

- Oral:
- Dermal:
- Inhalation:

LD50/oral/rat &gt; 5000 mg/kg

The results of lab testing showed this material to be non-toxic even at high dose levels.

The product is not expected to be toxic by inhalation.

## IRRITATION:

- Skin:
- Eyes:

The results of lab testing showed this material to be non-irritating to the skin.

Testing conducted according to the Draize technique showed the material produces no corneal or iridial effects and only slight transitory conjunctival effects similar to those which all granular materials have no conjunctivae.

## SENSITIZATION:

The results of lab testing showed this material to be non-sensitizing.

## CHRONIC TOXICITY:

The results of extensive lab testing did not reveal adverse health effects.

ECOTOXICITY

- Fish:
- Algae:

LC50 / Fathead minnows / 96 hours > 1000 mg/l  
EC50 / Selenastrum capricornutum > 96 hours > 500 mg/l

## Bioaccumulation:

The product is not expected to bioaccumulate.

## Persistence / degradability:

Not readily biodegradable.