








**MATERIAL SAFETY DATA SHEETS  
(MSDS)**

*(Attached in Hard Copy)*

**FUELS, FUEL ADDITIVES, OIL**  
**Knife Lake Project – Spring 2004 Drill Programme**



WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
 	B-3, D-2B	   	

**Section 1. Chemical Product and Company Identification**

<b>Product Name</b>	<b>DIESEL FUEL</b>	<b>Code</b>	W104 SAP: 120, 121, 122, 287
<b>Synonym</b>	Diesel 50, Diesel 50 LS, #1 Diesel, #1 Diesel LS, Diesel LC, Seasonal Diesel, Seasonal Diesel LS, Diesel AA, Domestic Marine Diesel, International marine Diesel, Seasonal Diesel Locomotive, Domestic Marine diesel LS, diesel -20°C (LS), LSD, Low Sulphur Diesel, dyed diesel, marked diesel, coloured diesel, Naval Distillate, Ultra Low Sulphur Diesel, ULS Diesel.	<b>Validated on</b>	3/2/2001.
<b>Manufacturer</b>	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	<b>In case of Emergency</b>	Petro-Canada: 403-296-3000 Canutec Transportation: 813-995-8888 Poison Control Centre; Consult local telephone directory for emergency number(s).
<b>Material Uses</b>	Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type.		

**Section 2. Composition and Information on Ingredients**

			<i>Exposure Limits (ACGIH)</i>		
Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
1) Diesel oil.	68334-30-5	>99.9	100 mg/m <sup>3</sup> (as total hydrocarbons) *	Not established	Not established
2) Proprietary additives.	Not available	<0.1	Not established	Not established	Not established
Aromatic content is 50% maximum (benzene: nil).					
<b>Manufacturer Recommendation</b>	* Avoid prolonged or repeated skin contact to diesel fuels which can lead to dermal irritation and may be associated with an increased risk of skin cancer.				
<b>Other Exposure Limits</b>	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

**Section 3. Hazards Identification.**

<b>Potential Health Effects</b>	Eye contact may cause mild eye irritation. Skin contact can cause moderate to severe irritation and produce drying, cracking, or defatting dermatitis. Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat. Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure. For more information, refer to Section 11.
---------------------------------	--

**Section 4. First Aid Measures**

<b>Eye Contact</b>	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
<b>Skin Contact</b>	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
<b>Inhalation</b>	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
<b>Ingestion</b>	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
<b>Note to Physician</b>	Not available

**Section 5. Fire-fighting Measures**

<b>Flammability</b>	Class II - combustible liquid (NFPA).	<b>Flammable Limits</b>	LOWER: 0.7%, UPPER: 6%
<b>Flash Points</b>	Diesel Fuel: Closed Cup: >40°C (>104°F) Marine Diesel Fuel: Closed Cup: >60°C (>140°F)	<b>Auto-ignition Temperature</b>	225°C (437°F)
<b>Fire Hazards in Presence of Various Substances</b>	Flammable in presence of open flames, sparks, or heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.	<b>Explosion Hazards in Presence of Various Substances</b>	Containers may explode in heat of fire. Do not cut, weld, heat, drill or pressurize empty container. Vapour explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.

<b>Products of Combustion</b>	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), sulphur compounds (H <sub>2</sub> S), water vapour (H <sub>2</sub> O), smoke and irritating vapours as products of incomplete combustion.
<b>Fire Fighting Media and Instructions</b>	<p>NAERG96, GUIDE 128, Flammable liquids (Non-polar/Water-Immiscible).</p> <p>CAUTION: This product has a moderate flash point above 40°C; Use of water spray when fighting fire may be inefficient.</p> <p>If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.</p> <p>SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam.</p> <p>LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk.</p> <p>Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.</p> <p>Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.</p>

### Section 6. Accidental Release Measures

<b>Material Release or Spill</b>	<p>NAERG96, GUIDE 128, Flammable Liquids (Non-polar/ Water-immiscible).</p> <p>ELIMINATE ALL IGNITION SOURCES. Avoid contact. Stop leak if without risk. Contain spill. Absorb with inert absorbents, dry clay, or diatomaceous earth. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.</p>
----------------------------------	---

### Section 7. Handling and Storage

<b>Handling</b>	Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. DO NOT reuse empty containers without commercial cleaning or reconditioning. Ground/bond line and equipment during pumping or transfer to avoid accumulation of static charge. DO NOT ingest. Do not breathe gas/vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately. Avoid contact with skin and eyes. Practice good personal hygiene. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.
<b>Storage</b>	Store in tightly closed containers in cool, dry, isolated, well-ventilated area, and away from incompatibles. Ground all equipment containing material.

### Section 8. Exposure Controls/Personal Protection

<b>Engineering Controls</b>	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.
<b>Personal Protection</b>	<b>The selection of personal protective equipment varies, depending upon conditions of use.</b>
<b>Eyes</b>	Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.
<b>Body</b>	Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.
<b>Respiratory</b>	Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.
<b>Hands</b>	Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.
<b>Feet</b>	Wear appropriate footwear to prevent product from coming in contact with feet and skin.

### Section 9. Physical and Chemical Properties

<b>Physical State and Appearance</b>	Bright oily liquid.	<b>Viscosity</b>	1.3-4.1 cSt @ 40°C (104°F)
<b>Colour</b>	Clear to yellow / brown. Low sulphur diesel fuels (<0.05 wt % sulphur) are colourless to light yellow (and may be dyed red for taxation purposes). Regular sulphur diesel fuels (0.05-0.50 % sulphur) may be colourless to yellow / brown and are usually dyed red for taxation purposes.	<b>Pour Point</b>	Variable, 0°C to -50°C (32°F to -58°F)
<b>Odour</b>	Petroleum oil like.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available	<b>Dropping Point</b>	Not applicable.



DIESEL FUEL		Page Number: 3	
<b>Boiling Point</b>	150-371°C (302-700°F)	<b>Penetration</b>	Not applicable.
<b>Density</b>	0.85 kg/L @ 15°C (Water = 1).	<b>Oil / Water Dist. Coefficient</b>	Not available
<b>Vapour Density</b>	4.5 (Air = 1)	<b>Ionicity (in water)</b>	Not applicable.
<b>Vapour Pressure</b>	1.0 kPa @ 20°C (7.5 mmHg @ 68°F).	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	<0.1 (Butyl acetate = 1), less than gasoline.	<b>Solubility</b>	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

Section 10. Stability and Reactivity			
<b>Corrosivity</b>	Not available		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents and acids.	<b>Decomposition Products</b>	May release COx, NOx, SOx, H2S, H2O, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information	
<b>Routes of Entry</b>	Skin contact, eye contact, inhalation, and ingestion.
<b>Acute Lethality</b>	Acute oral toxicity (LD50): 7500 mg/kg (rat).
<b>Chronic or Other Toxic Effects</b>	
Dermal Route:	Skin contact may cause moderate to severe irritation. Repeated exposure would produce drying and cracking or defatting dermatitis. (See Other Considerations)
Inhalation Route:	Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat.
Oral Route:	Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	Eye contact may cause mild irritation, but no permanent damage.
Immunotoxicity:	Not available
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.
Mutagenic:	This product is not expected to be a mutagen, based on the available data and the known hazards of the components.
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.
Carcinogenicity (ACGIH):	ACGIH A3: animal carcinogen. [Diesel oil] (See Other Considerations)
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	Not available
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
<b>Other Considerations</b>	Avoid prolonged or repeated skin contact to diesel fuels which can lead to dermal irritation and may be associated with an increased risk of skin cancer.

Section 12. Ecological Information			
<b>Environmental Fate</b>	Not available	<b>Persistence/ Bioaccumulation Potential</b>	Not available
<b>BOD5 and COD</b>	Not available	<b>Products of Biodegradation</b>	Not available
<b>Additional Remarks</b>	No additional remark.		





**Section 13. Disposal Considerations**

<b>Waste Disposal</b>	Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations. Consult your local or regional authorities.
-----------------------	--

**Section 14. Transport Information**

<b>TDG Classification</b>	Currently: Diesel Fuel, 3, UN1202, PGIII As of August 15, 2002: DIESEL FUEL, 3, UN1202, PGIII	<b>Special Provisions for Transport</b>	Not applicable.
---------------------------	--	---	-----------------

**Section 15. Regulatory Information**

<b>Other Regulations</b>		This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).																																				
		All components of this formulation are listed on the US EPA-TSCA inventory.																																				
		All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).																																				
		This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.																																				
		Please contact Product Safety for more information.																																				
<b>DSD/DPD (Europe)</b>		Not evaluated.	<b>HCS (U.S.A.)</b>		CLASS: Irritating substance. CLASS: Target organ effects. CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).																																	
<b>ADR (Europe) (Pictograms)</b>		NOT EVALUATED FOR EUROPEAN TRANSPORT  NON EVALUÉ POUR LE TRANSPORT EUROPÉEN.	<b>DOT (U.S.A) (Pictograms)</b>																																			
<b>HMIS (U.S.A.)</b>		<table><tr><td>Health Hazard</td><td>(2)</td></tr><tr><td>Fire Hazard</td><td>(2)</td></tr><tr><td>Reactivity</td><td>(0)</td></tr><tr><td>Personal Protection</td><td>(H)</td></tr></table>	Health Hazard	(2)	Fire Hazard	(2)	Reactivity	(0)	Personal Protection	(H)	<b>NFPA (U.S.A.)</b>		<table><tr><td>Health</td><td></td><td>Fire Hazard</td><td>Rating</td><td>0 Insignificant</td></tr><tr><td></td><td></td><td>Reactivity</td><td></td><td>1 Slight</td></tr><tr><td></td><td></td><td>Specific hazard</td><td></td><td>2 Moderate</td></tr><tr><td></td><td></td><td></td><td></td><td>3 High</td></tr><tr><td></td><td></td><td></td><td></td><td>4 Extreme</td></tr></table>	Health		Fire Hazard	Rating	0 Insignificant			Reactivity		1 Slight			Specific hazard		2 Moderate					3 High					4 Extreme
Health Hazard	(2)																																					
Fire Hazard	(2)																																					
Reactivity	(0)																																					
Personal Protection	(H)																																					
Health		Fire Hazard	Rating	0 Insignificant																																		
		Reactivity		1 Slight																																		
		Specific hazard		2 Moderate																																		
				3 High																																		
				4 Extreme																																		

**Section 16. Other Information**

<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark
<b>Glossary</b>	<p>ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials ( ) BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemicals Hazard Information and Packaging Approved Supply List COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSOL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning and Community Right to Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer</p> <p>IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NAERG'95 - North American Emergency Response Guide Book (1998) NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety &amp; Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety &amp; Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act SD - Single Dose STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLM - Median Tolerance Limit TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System</p>

<b>For Copy of MSDS</b>	<b>Prepared by Product Safety - TAR on 3/2/2001.</b>
<b>Fuels &amp; Solvents:</b> <b>Western Canada, telephone: 403-296-4158; fax: 403-296-6551</b> <b>Ontario &amp; Central Canada, telephone: 1-800-668-0220; fax: 1-800-837-1228</b> <b>Quebec &amp; Eastern Canada, telephone: 514-840-8308; fax: 514-840-8385</b>	<b>Data entry by Product Safety - JDW.</b>
<b>For Product Safety Information: (905) 804-4752</b>	

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

**Shell Canada Limited**  
**Material Safety Data Sheet**Effective Date: 2002-08-14  
Supersedes: 2001-01-08Class B2 Flammable  
LiquidClass D2A Other Toxic  
Effects - Carcinogen**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT: **REGULAR UNLEADED GASOLINE**  
SYNONYMS: Automotive Fuel  
Petrol  
PRODUCT USE: Fuel  
MSDS Number: 211-001

**MANUFACTURER**  
**Shell Canada Limited**  
P.O. Box 100, Station M  
400-4th Ave. S.W.  
Calgary, AB Canada  
T2P 2H5

**TELEPHONE NUMBERS**  
**Shell Emergency Number** 1-800-661-7378  
**CANUTEC 24 HOUR EMERGENCY NUMBER** 613-996-6666  
For general information: 1-800-661-1600  
For MSDS information: 403-691-3982  
(From 7:30 to 4:30 Mountain Time) 403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

\*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Component Name	CAS Number	% Range	WHMIS Controlled
Gasoline, Natural	8006-61-9	80 - 100	Yes
Benzene	71-43-2	<1.5	Yes

See Section 8 for Occupational Exposure Guidelines.

**3. HAZARDS IDENTIFICATION**

**Physical Description:** Liquid Clear Typical Gasoline Odour

**Routes of Exposure:** Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

<b>Hazards:</b>	Flammable Liquid. May cause cancer. Vapours are moderately irritating to the eyes. Ingestion may result in vomiting. Avoid aspiration of vomitus into lungs as small quantities may result in aspiration pneumonitis. May be absorbed by skin contact. Prolonged immersion in liquid may lead to chemical burns. Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung. Excessive exposure to benzene may cause leukemia in man.
<b>Handling:</b>	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

#### 4. FIRST AID

<b>Eyes:</b>	Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.
<b>Skin:</b>	Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.
<b>Ingestion:</b>	DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.
<b>Inhalation:</b>	Remove victim from further exposure and restore breathing, if required. Obtain medical attention.
<b>Notes to Physician:</b>	The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media:</b>	Dry Chemical Carbon Dioxide Foam Water Fog
-----------------------------	---

**Firefighting Instructions:** Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Product will float and can be reignited on surface of water. Do not use water except as a fog. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.

**Hazardous Combustion Products:** Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

## 6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations.

## 7. HANDLING AND STORAGE

**Handling:** Extremely flammable. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Avoid all direct contact with this material. Avoid prolonged or repeated inhalation of vapours. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Do not use as a cleaning solvent. Never siphon by mouth. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Launder contaminated clothing prior to reuse. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities.

**Storage:** Store in a cool, dry, well ventilated area, away from heat and ignition sources. Protect against physical damage to containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

### OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Gasoline: 300 ppm (STEL: 500 ppm)

Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)

Skin Notation: The occupational exposure limit is based on the fact that skin and/or eye is a major route of exposure through absorption.

**Mechanical Ventilation:** Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

**PERSONAL PROTECTIVE EQUIPMENT:**

**Eye Protection:** Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

**Skin Protection:** Impervious gloves should be worn at all times when handling this product. PVC or nitrile rubber gloves are recommended. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

**Respiratory Protection:** If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

**9. PHYSICAL DATA**

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Clear
<b>Odour:</b>	Typical Gasoline Odour
<b>Odour Threshold:</b>	<0.25 ppm
<b>Freezing/Pour Point:</b>	Not available
<b>Boiling Point:</b>	35 - 220 degrees C
<b>Density:</b>	720 - 730 kg/m <sup>3</sup> @ 15 degrees C
<b>Vapour Density (Air = 1):</b>	3.5
<b>Vapour Pressure (absolute):</b>	Not available
<b>pH:</b>	Not applicable
<b>Flash Point:</b>	Method Tag Closed Cup -30 degrees C
<b>Lower Explosion Limit:</b>	1.4 % (vol.)
<b>Upper Explosion Limit:</b>	7.6 % (vol.)
<b>Autoignition Temperature:</b>	280 degrees C
<b>Viscosity:</b>	<1 cSt @ 38 degrees C
<b>Evaporation Rate (n-BuAc = 1):</b>	Not available
<b>Partition Coefficient (K<sub>ow</sub>):</b>	200
<b>Water Solubility:</b>	Insoluble
<b>Other Solvents:</b>	Hydrocarbon Solvents

**10. STABILITY AND REACTIVITY**

<b>Chemically Stable:</b>	Yes
<b>Hazardous Polymerization:</b>	No
<b>Sensitive to Mechanical Impact:</b>	No
<b>Sensitive to Static Discharge:</b>	Yes
<b>Incompatible Materials:</b>	Avoid strong oxidizing agents.



**Conditions of Reactivity:**

Avoid excessive heat, formation of vapours or mists.

**11. TOXICOLOGICAL INFORMATION**

<b>Ingredient (or Product if not specified)</b>	<b>Toxicological Data</b>
Gasoline, Natural	LD50 Oral Rat = 18800 mg/kg LD50 Dermal Rabbit >8000 mg/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
<b>Routes of Exposure:</b>	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
<b>Irritancy:</b>	Based on testing with similar materials, this product is not expected to be a primary skin irritant after exposure of short duration, would not be a skin sensitizer and would not be irritating to the eye.
<b>Chronic Effects:</b>	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
<b>Carcinogenicity and Mutagenicity:</b>	According to the International Agency for Research on Cancer (IARC) this product is considered to be possibly carcinogenic to humans. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes.

**12. ECOLOGICAL INFORMATION**

<b>Environmental Effects:</b>	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. Fish Toxicity: 5 to 40 ppm   96 hr TLm   Rainbow Trout   Freshwater
<b>Biodegradability:</b>	Not readily biodegradable. Potential for bioaccumulation. Rapid volatilization.

**13. DISPOSAL CONSIDERATIONS**

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

**14. TRANSPORTATION INFORMATION****Canadian Road and Rail Shipping Classification:**

UN Number

UN1203



Proper Shipping Name	GASOLINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Additional Information	Marine Pollutant
Shipping Description	GASOLINE Class 3 UN1203 PG II Marine Pollutant

## 15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)* and the MSDS contains all the information required by the CPR.

WHMIS Class:	Class B2 Flammable Liquid Class D2A Other Toxic Effects - Carcinogen
DSL/NDSL Status:	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.
Other Regulatory Status:	No Canadian federal standards.

## 16. ADDITIONAL INFORMATION

### LABEL STATEMENTS

Hazard Statement :	Flammable Liquid. May cause cancer.
Handling Statement:	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.
First Aid Statement :	Wash contaminated skin with soap and water. Flush eyes with water. If overcome by vapours remove to fresh air. Do not induce vomiting. Obtain medical attention.
Revisions:	This MSDS has been reviewed and updated. Changes have been made to: Section 1 Section 2 Section 14

KLEEN-FLO TUMBLER INDUSTRIES LIMITED		MATERIAL SAFETY DATA SHEET		PAGE 1
<b>SECTION I-MATERIAL IDENTIFICATION AND USE</b>				
Material Name/Identifier:	Diesel Fuel Oil Conditioner	Stock No.	991/992/993/994/995/998	
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd	Street Address:	75 Advance Blvd.	
City:	Brampton	Province:	Ontario	
Postal Code:	L6T 4N1	Emergency Phone #:	(905) 793-4311	
Chemical Name:	N/A (mixture)	Chemical Family:	Blend of aliphatic alcohol & aromatic hydrocarbons.	
Chemical Formula:	N/A (Mixture)	Trade Names & Synonyms:	No	
Material Use:	Conditioner/Cleaner	Molecular Weight:	N/A (Mixture)	
<b>SECTION II-HAZARDOUS INGREDIENTS OF MATERIAL</b>				
Hazardous Ingredients	C.A.S.	Approximate Concentration	LD50 Species & Route	LC50 Species & Route
2-propanol	67-63-0	60-90%	5 g/kg rat-oral	12000 ppm (8hr) rat-inh.
Dimethyl benzene	1330-20-7	10-30%	4.3 g/kg rat-oral	5000 ppm (4hr) rat-inh.
Ethyl benzene	100-41-4	1 - 5%	3.5 g/kg rat-oral	N/A
<b>SECTION III-PHYSICAL DATA FOR MATERIAL</b>				
Physical State:	Liquid	Odour/Appearance:	Colourless, water white liquid, alcohol odour	
Specific Gravity:	0.8 @ 15°C	Odour Threshold(p.p.m.):	N/E	
Boiling Point:	82-137°C	Evaporation Rate:	N/E	
Freezing Point:	N/A	Solubility in Water:	87%	
% Volatile(by volume):	100%	Vapour Pressure(mm)Hg:	4.4 kPa at 20°C	
Vapour Density(Air=1):	2.2	Coefficient of Water/Oil Distribut:	3.5	
pH	N.Ap.			
<b>SECTION IV-FIRE AND EXPLOSION HAZARD OF MATERIAL</b>				
Flammability Yes/No	Yes	If yes under which conditions?	Can be ignited under normal temp. conditions.	
Auto Ignition Temperature	N/E	Means of Extinction:	Alcohol Foam, carbon dioxide	
Flashpoint and Method:	11°C	Hazardous Combustion Products:	Carbon monoxide,	
	Tag closed cup		carbon dioxide, hydrocarbon fumes & smoke	
Upper Flammable limit		Lower Flammable Limit(% by volume):	2%	
(% by volume):	12%			
Explosion Data:	Sensitivity to Mech. Impact: Use only	Sensitivity to Static Discharge:	Yes	
	non-sparking tool		use grounded equipment	
<b>SECTION V-REACTIVITY DATA</b>				
Chemical Stability Yes/No:	Yes	If NO under which conditions?	N.Ap.	
Incompatibility to Other Substances Yes/No:	Yes	If so which ones?	Avoid contact with strong oxidizing	
			materials, it may react with aluminum at high temp.	
Reactivity and under what conditions?	Normally stable but can become unstable at elevated temp. and pressure.			
Hazardous Decomposition Products:	Carbon monoxide, carbon dioxide produced on combustion.			
N/E: not established				
N.Ap.: not applicable				
N/A: not available				

Material Name/Identifier: Diesel Fuel Oil Conditioner		Stock No. 991/992/993/994/995/998		PAGE 2
<b>SECTION VI-TOXICOLOGICAL PROPERTIES OF PRODUCT</b>				
Route of Entry:	-SKIN CONTACT -X-SKIN ABSORPTION -X-EYE CONTACT -X-INHALATION -X-INGESTION			
Effects of Acute Exposure:	May cause slight eye irritation, headaches, nausea, dizziness, drowsiness and central nervous system depression.			
Effects of chronic exposure:	High exposure to dimethylbenzene to some animal studies have been reported to cause health effects on developing embryo/fetus. These effects were often at levels toxic to mother. The significance of these findings has not been determined.			
LD 50 of Product:	5gm/kg rat-oral	LC 50 of Product:	>12000 ppm rat-inh.	
Irritancy of Product:	skin and eye irritant	Exposure limits of products: 2-propanol- 400 ppm,		
Sensitization of Product:	N/A	ethyl benzene- 100 ppm, xylene- 100 ppm		
Toxicologically Synergistic Materials:				N/A
-CARCINOGENICITY -REPRODUCTIVE EFFECTS -TERATOGENICITY -MUTAGENICITY				none known
<b>SECTION VII-PREVENTIVE MEASURES</b>				
Personal Protective Equipment to be used:				
Gloves(specify):	Nitrile, viton & polyethylene	Eye(specify):	Chemical safety glasses	
Respiratory(specify):	Organic canister mask	Clothing:	Plastic apron Footwear: Oil resistant soles.	
Respiratory Protection:	If used indoors or on a continuous basis, use of cartridge type respirator is recommended			
<b>SECTION VII-PREVENTIVE MEASURES</b>				
Personal Protective Equipment to be used:				
Gloves(specify):	Nitrile, viton & polyethylene	Eye(specify):	Chemical safety glasses	
Respiratory(specify):	Organic canister mask	Clothing:	Plastic apron Footwear: Oil resistant soles.	
Respiratory Protection:	If used indoors or on a continuous basis, use of cartridge type respirator is recommended			
Handling procedure & Equip.	Use spark resistant tools and equipment for transfers.			
Leak and Spill Procedure:	Dyke and contain land spill. Soak residue with natural absorbent.			
Waste Disposal:	Incineration or dispose at an approved waste disposal facility.			
Storage Requirements:	Keep in a cool place.			
CEPA & DSL	All ingredients in the product are included in the DSL and are exempted from CEPA requirements.			
TDG Classification	991/992/993 : Consumer Commodity, 994/995/996/998 as follows: Flammable liquids, N.O.S.* (2-propanol/Xylene), Class 3, UN 1993, Pkg.Gr.II			
WHMIS Classification:	991/992/993 - Consumer Commodity, #994/995/998 - Class B2, D2B & D2A			
<b>SECTION VIII-FIRST AID MEASURES</b>				
Eye:	Flush with water for at least 15 minutes.			
Skin:	Wash with soap and water			
Inhalation:	Remove to fresh air and restore breathing if required.			
Ingestion:	Contains petroleum distillate. Do not induce vomiting. Guard against aspiration into lungs.			
<b>SECTION IX-PREPARATION DATE OF M.S.D.S.</b>				
Additional Info/Comments:	Sources Used: NOISH Registry of Toxic Effects of Chemical Substances Shell Data			
Phone Number:	(905) 793-4311	Prepared By: Quality Control Laboratory		
Date:	March 3rd. 2003	Kleen-Flo Tumbler Industries Limited		
THIS SHEET SUPERSEDES ANY OTHER M.S.D.S. PREVIOUSLY PREPARED				
N/A: not available		N/E: not established		

**Shell Canada Limited**  
**Material Safety Data Sheet**Effective Date: 2002-08-14  
Supersedes: 2001-01-08Class B2 Flammable  
LiquidClass D2B Other Toxic  
Effects - Skin IrritantClass D2A Other Toxic  
Effects - Carcinogen**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT: **SHELL JET B**  
SYNONYMS: WIDE BOILING RANGE AVIATION TURBINE FUEL  
PRODUCT USE: Fuel  
MSDS Number: 141-012

**MANUFACTURER**  
**Shell Canada Limited**  
P.O. Box 100, Station M  
400-4th Ave. S.W.  
Calgary, AB Canada  
T2P 2H5

**TELEPHONE NUMBERS**  
**Shell Emergency Number** 1-800-661-7378  
**CANUTEC 24 HOUR EMERGENCY NUMBER** 613-996-6666  
  
For general information: 1-800-661-1600  
For MSDS information: 403-691-3982  
(From 7:30 to 4:30 Mountain Time) 403-691-2220

This MSDS was prepared by the Toxicology and Material Safety Section of Shell Canada Limited.

\*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Component Name	CAS Number	% Range	WHMIS Controlled	CBI Claim No. CBI Date
Naphtha (Petroleum), Full-range Reformed	68919-37-9	>95	Yes	
Benzene	71-43-2	0.5 - 1.5	Yes	

See Section 8 for Occupational Exposure Guidelines.

**3. HAZARDS IDENTIFICATION**

**Physical Description:** Liquid Bright Clear Typical Gasoline Odour

<b>Routes of Exposure:</b>	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
<b>Hazards:</b>	Flammable Liquid. Irritating to skin. Contains Benzene. May cause cancer. Vapours are moderately irritating to the eyes. Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung. Excessive exposure to benzene may cause leukemia in man.
<b>Handling:</b>	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

#### 4. FIRST AID

<b>Eyes</b>	Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.
<b>Skin</b>	Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.
<b>Ingestion</b>	DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.
<b>Inhalation</b>	Remove victim from further exposure and restore breathing, if required. Obtain medical attention.
<b>Notes to Physician</b>	The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media</b>	Dry Chemical Carbon Dioxide Foam Water Fog
----------------------------	---

<b>Firefighting Instructions</b>	Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Do not use water except as a fog. Use water to cool fire exposed containers. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Always stay away from ends of containers due to explosive potential. Fight fire from maximum distance. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.
<b>Hazardous Combustion Products</b>	A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

## 6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Handling equipment must be grounded. Isolate hazard area and restrict access. Try to work upwind of spill. Avoid direct contact with material. Saturated clothing should be immediately removed to avoid flammability hazard. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Extremely flammable. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Never siphon by mouth. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.
<b>Storage:</b>	Use explosion-proof ventilation to prevent vapour accumulation. Keep container tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON

**THE CONDITIONS OF USE.**

<b>Occupational Exposure Limits (2000) :</b>	North American exposure limits have not been established for the product. Consult local authorities for acceptable provincial values. Gasoline: 300 ppm (STEL: 500 ppm) Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)
<b>Mechanical Ventilation:</b>	Make up air should always be supplied to balance air exhausted (either generally or locally). Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere. Use explosion-proof ventilation as required to control vapour concentrations.

**PERSONAL PROTECTIVE EQUIPMENT:**

<b>Eye Protection:</b>	Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.
<b>Skin Protection:</b>	Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.
<b>Respiratory Protection:</b>	If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

**9. PHYSICAL DATA**

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Bright Clear
<b>Odour:</b>	Typical Gasoline Odour
<b>Odour Threshold:</b>	Not available
<b>Freezing/Pour Point:</b>	<-51 degrees C
<b>Boiling Point:</b>	60 - 270 degrees C
<b>Density:</b>	750 - 801 kg/m <sup>3</sup> @ 15 degrees C
<b>Vapour Density (Air = 1):</b>	Not available
<b>Vapour Pressure:</b>	>42 mm Hg @ 38 degrees C
<b>Specific Gravity (Water = 1):</b>	0.000
<b>pH:</b>	Not applicable
<b>Flash Point:</b>	Method Tag Closed Cup = -23 - 1 degrees C
<b>Lower Explosion Limit:</b>	1.4 % (vol.)
<b>Upper Explosion Limit:</b>	7.6 % (vol.)
<b>Autoignition Temperature:</b>	Not available
<b>Viscosity:</b>	Not available
<b>Evaporation Rate (n-BuAc = 1):</b>	Not available
<b>Partition Coefficient (K<sub>OW</sub>):</b>	Not available
<b>Water Solubility:</b>	Insoluble
<b>Other Solvents:</b>	Hydrocarbon Solvents



**10. STABILITY AND REACTIVITY**

<b>Chemically Stable:</b>	Yes
<b>Hazardous Polymerization:</b>	No
<b>Sensitive to Mechanical Impact:</b>	No
<b>Sensitive to Static Discharge:</b>	Yes
<b>Hazardous Decomposition Products:</b>	Thermal decomposition products are highly dependent on combustion conditions.
<b>Incompatible Materials:</b>	Avoid contact with strong oxidizing agents and acids.
<b>Conditions of Reactivity:</b>	Avoid excessive heat, open flames and all ignition sources.

**11. TOXICOLOGICAL INFORMATION**

<b>Ingredient (or Product if not specified)</b>	<b>Toxicological Data</b>
Naphtha (Petroleum), Full-range Reformed	LD50 Oral Rat >28 mL/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
<b>Routes of Exposure:</b>	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
<b>Irritancy:</b>	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
<b>Chronic Effects:</b>	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
<b>Pre-existing Conditions:</b>	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
<b>Carcinogenicity and Mutagenicity:</b>	This product contains benzene. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes. Carcinogenic hazard.

**12. ECOLOGICAL INFORMATION**

<b>Environmental Effects</b>	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. May cause physical fouling of aquatic organisms.
<b>Biodegradability</b>	Not readily biodegradable. Potential for bioaccumulation.

**13. DISPOSAL CONSIDERATIONS**



Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

## 14. TRANSPORTATION INFORMATION

### Canadian Road and Rail Shipping Classification:

UN/NA Number	UN1863
Proper Shipping Name	FUEL, AVIATION, TURBINE ENGINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Shipping Description	FUEL, AVIATION, TURBINE ENGINE Class 3 UN1863 PG II

## 15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

<b>WHMIS Class:</b>	Class B2 Flammable Liquid Class D2B Other Toxic Effects - Skin Irritant Class D2A Other Toxic Effects - Carcinogen
<b>DSL/NDL Status:</b>	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.
<b>Other Regulatory Status:</b>	No Canadian federal standards.

## 16. ADDITIONAL INFORMATION

### LABEL STATEMENTS

<b>Hazard Statement :</b>	Flammable Liquid. Irritating to skin. Contains Benzene. May cause cancer.
<b>Handling Statement:</b>	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

**First Aid Statement :** Wash contaminated skin with soap and water.  
Flush eyes with water.  
If overcome by vapours remove to fresh air.  
Do not induce vomiting.  
Obtain medical attention.

**Revisions:** This revision reflects the change of name from Shell Canada Products Limited to Shell Canada Products.  
This MSDS has been reviewed and updated.  
Changes have been made to:  
Section 14



## Material Safety Data Sheets

New Search

Get This Document !

Date Prepared: Decem  
Supersedes: May 31, 1  
MSDS Number: 08524

### 1. PRODUCT INFORMATION

Product Identifier: TURBINE AVIATION, WIDE CUT TYPE

ESSO TURBO FUEL B  
ESSO JET B  
JET B  
TURBO FUEL B  
TURBO FUEL B F40  
TURBO FUEL B JP4  
ESSO TURBO FUEL B (FSII)  
JET B (FSII)  
AVIATION TURBINE FUEL (JP4)  
CAN/CGSB-3.22 GRADE F40  
ESSO JET B (FSII)

Application and Use:  
Aviation turbine fue

Product Description:

ixture of aliphatic and aromatic hydrocarbons and additives.

REGULATOR CLASSIFICATION

Class B, D 2: Flammable Liquids.  
Class D, D 2, Subdivision A: Very Toxic Material.  
2, Subdivision B: Toxic Material

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT  
All components of this product are either on the Domestic  
Substances List (DSL) or are exempt.

TDG INFORMATION (RAIL, ROAD):

Shipping Name: FUEL, AVIATION, TURBINE ENGINES  
Class:  
Packing Gro  
PIN Number:

Marine Pollutant: Not app

Please be aware that regulations may app

## TELEPHONE NUMBERS

Emergency 24 39-  
 Technical In 68-

## MANUFACTURER/SUPPLIER:

IMPERIAL OI  
 Products Division  
 111 St Clair Avenue West  
 Toronto, Ontar.  
 M5W 1K3  
 (416) 968-4441

## 2. REGULATED COMPONENTS

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

NAME	CAS
Kerosene, straight run	-70 V 8008-20-6 LD50:>5g/kg, oral, rat
Napth: ill range	-60 V 64741-42-0
Diethylene glycol monomethyl ether	111-77-3 LD50:7g/kg, oral, rat LD50:>2.0/kg, skn. rbt

## 3. TYPICAL PHYSICAL &amp; CHEMICAL PROPERTIES

Physical State: Liquid  
 Specific gravity: not available  
 Viscosity: 0.60 cSt at 40 deg  
 Vapour Density:  
 Boiling Point: 270 deg C  
 Evaporation rat : n-butylaceta  
 Solubility in water: negligible  
 Freezing/Pour Point: -58 deg C ASTM 2386  
 Odour Threshold: not available  
 Vapour Pressure: 21 kPa at 38 deg C  
 Density: 0.78 g/cc at 15 deg  
 Appearance/odour: White or pale yellow liquid, pet

## 4. HEALTH HAZARD INFORMATION

## NATURE OF HAZARD

## INHALATION:

Negligible hazard at normal temperatures (up to 38 deg C).  
 High vapour concentrations are irritating to the eyes, nose, throat and lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.

vap.

**EYE CONTACT:**

...ing but will not injure eye tissue.

**SKIN CONTACT:**

frequent or prolonged contact may irritate the skin and cause a skin rash

**INGESTION:**

Low toxic

Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

**CHRONIC:**

Contains benzene. Human health studies (epidemiology) indicate that prolonged and/or repeated overexposures to benzene may cause damage to the blood producing system and serious blood disorders, including leukemia.

Animal tests suggest that prolonged and/or repeated overexposures to benzene may damage the embryo/fetus. The relationship of these animal studies to humans has not been fully established.

Contains n-hexane. Prolonged and/or repeated exposures may cause damage to the peripheral nervous system (e.g. fingers, feet, arms etc.).

Contains diethylene glycol monomethyl ether (DIEGME). Prolonged and repeated exposure through inhalation or extensive skin contact with DIEGME may result in toxic effects on the kidneys, the reproductive system and/or the embryo/fetus.

**ACUTE TOXICITY DATA:**

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

Oral : LD50 > 5000 mg/kg (Rat)  
Der : LD50 > 2000 mg/kg (Rab)  
Inhalation : LC50 > 2500 mg/m3 (Rat)

**OCCUPATIONAL EXPOSURE LIMIT:**

Manufacturer Recommends  
100 ppm based on composition

**ACGIH recommends:**

For n-Hexane (skin), 50 ppm (176 mg/m<sup>3</sup>)

For Benzene, ACGIH recommends a TWA of 0.5 ppm (0.5 mg/m<sup>3</sup>) (skin) and confirmed human carcinogen.

Local regulated limits may vary.

## 5. FIRST AID MEASURES

### INHALATION:

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

### EYE CONTACT:

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

### SKIN CONTACT:

Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention.

### INGESTION:

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

### PERSONAL PROTECTION:

The selection of personal protective equipment varies, depending upon conditions of use.  
In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves.  
Where only incidental contact is likely, wear safety goggles, long sleeves and chemical-resistant gloves.  
Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

### ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

### HANDLING, STORAGE AND SHIPPING:

Keep containers closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. In keeping with good personal hygiene practices, wash hands thoroughly after handling the material.  
Store and load at normal (up to 38 deg C) temperature and at atmospheric pressure.

accumulate static charges which may cause a spark. Static discharge could become an ignition source. Use proper relaxation and bonding procedures.  
Containers may contain product residue. Do not pressurize, heat, or weld empty containers. Do not reuse empty containers for commercial cleaning or reconditioning.

**LAND SPILL:**

Eliminate all sources of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Vapours or dust may be harmful or fatal. Warn occupants of downwind areas.

Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof motor or hand pump) using a suitable absorbent.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

**WATER SPILL:**

Eliminate all sources of ignition. Vapours or dust may be harmful or fatal. Warn occupants and shipping in downwind areas. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

**7. FIRE AND EXPLOSION HAZARD**

Flash point and method: -18 deg C COC ASTM D92

Autoignition: NA Flammable Limits: LEL: 0.6% UE :

**GENERAL HAZARDS:**

Extremely flammable; material will readily ignite at normal temperatures. Flammable Liquid; may release vapours that form flammable mixtures at or above the flash point.

Decomposes; flammable/toxic form at elevated temperatures (thermal decomposition).

Toxic gases will form upon combustion.

Static Discharge; material may accumulate static charges which may cause

**FIRE FIGHTING:**

water spray	fire exposed surfaces and to protect personnel.
oil fuel	possible to do so without hazard. If a leak or
has	water spray to disperse the vapours.

fire to burn out under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Respiratory and eye protection required for fire fighting personnel. Avoid spraying water directly into storage containers due to danger of boilover. A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an extinguisher

**HAZARDOUS COMBUSTION PRODUCTS:**

Smoke, carbon monoxide, carbon dioxide and traces of oxides of sulphur. In addition, small amounts of nitrogen oxides will be formed.

**8. REACTIVITY DATA****STABILITY:**

product is stable. Hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:**

Strong oxidizing agents. Use product with caution around heat, sparks, pilot lights, static electricity and open flames.

**HAZARDOUS DECOMPOSITION:**

Hazardous Combustion Product.

**9. NOTES**

All components of this product are listed on the U.S. TSCA inventory.

ON SUMMARY :  
31 May 20 MSDS has been revised in Sect. 10.1

**10. PREPARATION**

Date prepared : December  
Prepared by : Lubricants & Specialties  
IMPERIAL OIL  
Products Division  
111 St. Clair Avenue West  
Toronto, Ont.  
M5W 1K3



CAUTION: " This material and be used in combination or material y p te product is not to be used rpose or under conditions which are normal or reasonably foreseeable, information cannot be relied upon as complete or applicable. For certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers prohibited without the written consent of Imperial Oil."

Call our toll-free customer service center at 1-800-567-ESSO (3776) for information or questions about Material Safety Sheets.

[Français](#) | [Contacts](#) | [Disclaimer](#) | [Privacy](#) | [Sitemap](#) Copyright ©2002-2003, Imperial Oil Limited, Toronto, Canada. All rights reserved.

**Shell Canada Limited**  
**Material Safety Data Sheet**

Effective Date: 2002-08-14

Supersedes: 2001-09-14

Class B3 Combustible  
LiquidClass D2B Other Toxic  
Effects - Skin Irritant**1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT: **SHELL\* JET A-1**  
SYNONYMS: Aviation Turbine Fuel (Kerosene Type)  
May contain anti-icing additive (Diethylene Glycol Monomethyl Ether)  
PRODUCT USE: Fuel Solvent  
MSDS Number: 142-011

**MANUFACTURER**  
**Shell Canada Limited**  
P.O. Box 100, Station M  
400-4th Ave. S.W.  
Calgary, AB Canada  
T2P 2H5

**TELEPHONE NUMBERS**  
**Shell Emergency Number** 1-800-661-7378  
**CANUTEC 24 HOUR EMERGENCY NUMBER** 613-996-6666  
  
For general information: 1-800-661-1600  
For MSDS information: 403-691-3982  
(From 7:30 to 4:30 Mountain Time) 403-691-2220

This MSDS was prepared by the Toxicology and Material Safety Section of Shell Canada Limited.

\*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Component Name	CAS Number	% Range	WHMIS Controlled	CBI Claim No. CBI Date
Kerosene (Petroleum), Hydrodesulfurized	64742-81-0	60 - 100	Yes	

See Section 8 for Occupational Exposure Guidelines.

**3. HAZARDS IDENTIFICATION**

**Physical Description:** Liquid Bright Clear Hydrocarbon Odour

<b>Routes of Exposure:</b>	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
<b>Hazards:</b>	Combustible Liquid. Irritating to skin. Vapours are moderately irritating to the eyes. Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
<b>Handling:</b>	Eliminate all ignition sources. Avoid prolonged exposure to vapours. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

#### 4. FIRST AID

<b>Eyes</b>	Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.
<b>Skin</b>	Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.
<b>Ingestion</b>	DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.
<b>Inhalation</b>	Remove victim from further exposure. Obtain medical attention.
<b>Notes to Physician</b>	The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media</b>	Carbon Dioxide Foam Dry Chemical Water Fog
----------------------------	---

<b>Firefighting Instructions</b>	Caution - Combustible. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Flashback may occur along vapour trail. Do not use water except as a fog. Use water to cool fire exposed containers. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.
<b>Hazardous Combustion Products</b>	A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

## 6. ACCIDENTAL RELEASE MEASURES

Issue warning "Combustible". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.
<b>Storage:</b>	Store in a cool, dry, well ventilated area, away from heat and ignition sources. Keep container tightly closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

<b>Occupational Exposure Limits (2000) :</b>	North American exposure limits have not been established for the product. Consult local authorities for acceptable provincial values. Recommend SHELL guideline of 125 mg/m <sup>3</sup> for vapours (8 hour shift).
<b>Mechanical Ventilation:</b>	Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.
<b>PERSONAL PROTECTIVE EQUIPMENT:</b>	
<b>Eye Protection:</b>	Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.
<b>Skin Protection:</b>	Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.
<b>Respiratory Protection:</b>	If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

## 9. PHYSICAL DATA

<b>Physical State:</b>	Liquid
<b>Appearance:</b>	Bright Clear
<b>Odour:</b>	Hydrocarbon Odour
<b>Odour Threshold:</b>	Not available
<b>Freezing/Pour Point:</b>	Freeze Point <-47 degrees C
<b>Boiling Point:</b>	145 - 300 degrees C
<b>Density:</b>	775 - 840 kg/m <sup>3</sup> @ 15 degrees C
<b>Vapour Density (Air = 1):</b>	Not available
<b>Specific Gravity (Water = 1):</b>	0.81
<b>pH:</b>	Not available
<b>Flash Point:</b>	Method Tag Closed Cup >38 degrees C
<b>Lower Explosion Limit:</b>	0.7 % (vol.)
<b>Upper Explosion Limit:</b>	5 % (vol.)
<b>Autoignition Temperature:</b>	210 degrees C
<b>Viscosity:</b>	<8 cSt @ -20 degrees C
<b>Evaporation Rate (n-BuAc = 1):</b>	Not available
<b>Partition Coefficient (K<sub>OW</sub>):</b>	Not available
<b>Water Solubility:</b>	Insoluble
<b>Other Solvents:</b>	Hydrocarbon Solvents

## 10. STABILITY AND REACTIVITY

<b>Chemically Stable:</b>	Yes
---------------------------	-----

<b>Hazardous Polymerization:</b>	No
<b>Sensitive to Mechanical Impact:</b>	No
<b>Sensitive to Static Discharge:</b>	Yes
<b>Hazardous Decomposition Products:</b>	Thermal decomposition products are highly dependent on combustion conditions.
<b>Incompatible Materials:</b>	Avoid strong oxidizing agents.
<b>Conditions of Reactivity:</b>	Avoid excessive heat, open flames and all ignition sources.

## 11. TOXICOLOGICAL INFORMATION

<b>Ingredient (or Product if not specified)</b>	<b>Toxicological Data</b>
Kerosene (Petroleum), Hydrosulfurized	LD50 Oral Rat >5000 mg/kg LD50 Dermal Rabbit >2000 mg/kg
<b>Routes of Exposure:</b>	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
<b>Irritancy:</b>	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
<b>Chronic Effects:</b>	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression.
<b>Pre-existing Conditions:</b>	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
<b>Carcinogenicity and Mutagenicity:</b>	The International Agency for Research on Cancer (IARC) considers that this product is not classifiable as to its carcinogenicity to humans. Middle distillates have caused skin cancers in laboratory animals when applied repeatedly and left in place between applications. This effect is believed to be caused by the continuous irritation of the skin. Good personal hygiene should be maintained to avoid this risk.

## 12. ECOLOGICAL INFORMATION

<b>Environmental Effects</b>	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May cause physical fouling of aquatic organisms.
<b>Biodegradability</b>	Rapid volatilization. Not readily biodegradable. Potential for bioaccumulation.

## 13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

**14. TRANSPORTATION INFORMATION****Canadian Road and Rail Shipping Classification:**

UN/NA Number	UN1863
Proper Shipping Name	FUEL, AVIATION, TURBINE ENGINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG III
Shipping Description	FUEL, AVIATION, TURBINE ENGINE Class 3 UN1863 PG III

**15. REGULATORY INFORMATION**

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)* and the MSDS contains all the information required by the CPR.

<b>WHMIS Class:</b>	Class B3 Combustible Liquid Class D2B Other Toxic Effects - Skin Irritant
<b>DSL/NDL Status:</b>	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.
<b>Other Regulatory Status:</b>	No Canadian federal standards.

**16. ADDITIONAL INFORMATION****LABEL STATEMENTS**

<b>Hazard Statement :</b>	Combustible Liquid. Irritating to skin.
<b>Handling Statement:</b>	Eliminate all ignition sources. Avoid prolonged exposure to vapours. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.
<b>First Aid Statement :</b>	Wash contaminated skin with soap and water. Flush eyes with water. If overcome by vapours remove to fresh air. Do not induce vomiting. Obtain medical attention.
<b>Revisions:</b>	This revision reflects the change of name from Shell Canada Products Limited to Shell Canada Products. This MSDS has been reviewed and updated. Changes have been made to: Section 14



## Material Safety Data Sheets

New Search

Get This Document

Date Prepared: November 25, 2001  
Supersedes: November 21, 2003  
MSDS Number: 08525

### 1. PRODUCT INFORMATION

Product Identifier: KEROSENE TYPE AVIATION TURBINE FUEL

ESSO TURBO FUEL A  
ESSO TURBO FUEL A-1  
ESSO JET A  
ESSO JET A-1  
JET A  
JET A-1  
TURBO FUEL A  
TURBO FUEL A-1  
TURBO FUEL A-1 F34  
TURBO FUEL A-1 JP8  
JET A-1 (FSII)  
CAN/CGSB-3.23 GRADE F34

Application and Use:  
Aviation turbine fuel.

Product Description:

A mixture of aliphatic and aromatic hydrocarbons and additives.

#### REGULATORY CLASSIFICATION

WHMIS:

Class B, Division 3: Combustible Liquids.

Class D, Division 2, Subdivision A: Very Toxic Material.

Class D, Division 2, Subdivision B: Toxic Material.

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT

All components of this product are either on the Domestic Substances List (DSL), exempt, or have been notified under CEPA.

TDG INFORMATION (RAIL/ROAD):

Shipping Name: FUEL, AVIATION, TURBINE ENGINES

Class: 3

Packing Group: III



PIN Number: UN1863  
Marine Pollutant: Not applicable

In containers of 454 litres capacity or less this product is exempt from TDG regulations.

Please be aware that other regulations may apply.

---

**TELEPHONE NUMBERS**

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3163

**MANUFACTURER/SUPPLIER:**

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

---

## 2. REGULATED COMPONENTS

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

NAME		CAS	
Kerosene, straight run	0-100 V/V	8008-20-6	LD50: >5g/kg, oral, rat
Diethylene glycol monomethyl ether	0-0.15 V/V	111-77-3	LD50: 7g/kg, oral, rat LD50: >2.0/kg, skin, rabbit

---

## 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
Specific gravity: not available  
Viscosity: 8.00 cSt at -20 deg C  
Vapour Density: 4  
Boiling Point: 205 to 300 deg C  
Evaporation rate: not available (1= n-butylacetate)  
Solubility in water: NEGLIGIBLE  
Freezing/Pour Point: -47 deg C ASTM D2386  
Odour Threshold: 0.552mg/m3  
Vapour Pressure: 4 kPa at 38 deg C  
Density: 0.91 g/cc at 15 deg C  
Appearance/odour: White or pale yellow liquid, petroleum odour

---

## 4. HEALTH HAZARD INFORMATION

### NATURE OF HAZARD

#### INHALATION:

Negligible hazard at normal temperatures (up to 38 deg C).  
High vapour concentrations are irritating to the eyes, nose, throat and

lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.  
Avoid breathing vapours or mists.

**EYE CONTACT:**

Slightly irritating, but will not injure eye tissue.

**SKIN CONTACT:**

Irritating.  
Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).  
Low toxicity.

**INGESTION:**

Low toxicity.  
Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

**CHRONIC:**

Lifetime skin painting tests indicate that materials of similar composition have produced skin cancer in experimental animals. The relationship of these results to humans has not been fully established.  
Contains diethylene glycol monomethyl ether (DIEGME). Prolonged and repeated exposure through inhalation or extensive skin contact with DIEGME may result in toxic effects on the kidneys, the reproductive system and/or the embryo/fetus.

**ACUTE TOXICITY DATA:**

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

Oral : LD50 > 5000 mg/kg (Rat)  
Dermal : LD50 > 2000 mg/kg (Rabbit)  
Inhalation : LC50 > 2500 mg/m3 (Rat)

**OCCUPATIONAL EXPOSURE LIMIT:**

Manufacturer Recommends:  
For kerosene and other middle distillate fuels, 500 mg/m3 for total vapour/aerosol exposure and 5 mg/m3 for stable aerosols.

**ACGIH recommends:**

For Kerosene (skin), ACGIH recommends a TWA of 200 mg/m3 and categorizes it as an animal carcinogen.

Local regulated limits may vary.

---

**5. FIRST AID MEASURES****INHALATION:**

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

**EYE CONTACT:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:**

Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention.

**INGESTION:**

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

**6. PREVENTIVE AND CORRECTIVE MEASURES****PERSONAL PROTECTION:**

The selection of personal protective equipment varies, depending upon conditions of use. In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves. Where only incidental contact is likely, wear safety goggles, long sleeves, and chemical-resistant gloves. Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

**ENGINEERING CONTROLS:**

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

**HANDLING, STORAGE AND SHIPPING:**

Keep containers closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. In keeping with good personal hygiene practices, wash hands thoroughly after handling the material. Store and load at normal (up to 38 deg C) temperature and at atmospheric pressure. Material will accumulate static charges which may cause a spark. Static charge build-up could become an ignition source. Use proper relaxation and grounding procedures. Empty containers may contain product residue. Do not pressurize.

cut, heat, or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.

**LAND SPILL:**

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

**WATER SPILL:**

Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

**7. FIRE AND EXPLOSION HAZARD**

Flashpoint and method: 38 deg C TCC ASTM D56

Autoignition: NA Flammable Limits: LEL: NA UEL: NA

**GENERAL HAZARDS:**

Combustible Liquid; may form combustible mixtures at or above the flash point.

Decomposes; flammable/toxic gases will form at elevated temperatures (thermal decomposition).

Toxic gases will form upon combustion.

Static Discharge; material may accumulate static charges which may cause a fire.

**FIRE FIGHTING:**

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire if possible to do so without hazard. If a leak or spill has not ignited use water spray to disperse the vapours.

Use foam or dry chemical to extinguish fire.

Respiratory and eye protection required for fire fighting personnel.

Avoid spraying water directly into storage containers due to danger of rollover.

A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which

may easily be extinguished with a portable fire extinguisher, use of SCBA may not be required.

**HAZARDOUS COMBUSTION PRODUCTS:**

Smoke, carbon monoxide, carbon dioxide, oxides of sulphur.  
In addition, small amounts of nitrogen oxides will be formed.

---

**8. REACTIVITY DATA****STABILITY:**

The product is stable. Hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:**

Strong oxidizing agents. Use product with caution around heat, sparks, pilot lights, static electricity and open flames.

**HAZARDOUS DECOMPOSITION:**

See: Hazardous Combustion Products

---

**9. NOTES**

All components of this product are listed on the U.S. TSCA inventory.

**REVISION SUMMARY:**

Since 21 November 2003, this MSDS has been revised in Section(s):

---

**10. PREPARATION**

Date Prepared: November 25, 2003  
Prepared by: Lubricants & Specialties  
IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the

information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."

**Call our toll-free customer service center at 1-800-567-ESSO (3776) for information or questions about Material Safety Sheets.**

[Français](#) | [Contacts](#) | [Disclaimer](#) | [Privacy](#) | [Sitemap](#) Copyright ©2002-2003, Imperial Oil Limited, Toronto, Canada. All rights reserved.

<b>KLEEN-FLO TUMBLER INDUSTRIES LIMITED</b>	<b>MATERIAL SAFETY DATA SHEET</b>	<b>PAGE 1</b>
---	-----------------------------------	---------------

**SECTION I-MATERIAL IDENTIFICATION AND USE**

Material Name/Identifier:	<b>Kleen-Start Starting Fluid</b>	Stock No.	730
Manufacturer's Name:	Kleen-Flo Tumbler Industries Ltd	Street Address:	75 Advance Blvd.
City:	Brampton	Province:	Ontario
Postal Code:	L6T 4N1	Emergency Phone #:	(905) 793-4311
Chemical Name:	N/A (Mixture)	Chemical Family:	N/A (Mixture)
Chemical Formula:	N/A (Mixture)	Trade Names & Synonyms:	Kleen-Start
Material Use:	Engine Starting Fluid	Molecular Weight:	N/A (Mixture)

**SECTION II-HAZARDOUS INGREDIENTS OF MATERIAL**

Hazardous Ingredients	C.A.S.	Approximate % Concentration	LD50 Species & Route	LC50 Species & Route
Diethyl ether	60-29-7	40-70	N/A	N/A
Heptane	142-82-5	40-70	N/A	N/A
Carbon dioxide	124-38-9	5-10	N/A	N/A
Upper Cylinder Lubricant	64741-89-5	1-5	N/E	N/E

**SECTION III-PHYSICAL DATA FOR MATERIAL**

Physical State:	Liquid	Odour/Appearance:	ether-like odour/ colorless liquid
Specific Gravity:	0.713	Odour Threshold(p.p.m.):	N/A
Boiling Point:	35.5°C	Evaporation Rate:	37.5 (Butyl-acetate=1)
Freezing Point:	N/E	Solubility in Water:	6.5%
% Volatile(by volume):	100	Vapour Pressure(mm)Hg:	537
Vapour Density(Air=1):	2.55	Coefficient of Water/Oil Distribut:	N/A
pH	N/A		

**SECTION IV-FIRE AND EXPLOSION HAZARD OF MATERIAL**

Flammability Yes/No:	Yes, extremely	If yes under which conditions?:	Excessive heat, open flame or sparks
Auto Ignition Temperature:	N/A	Means of Extinction:	carbon dioxide, dry chemical, foam
Flashpoint and Method:	-49°C	Hazardous Combustion Products:	N/A
	Tag C.C.		
Upper Flammable limit (% by volume):	48	Lower Flammable Limit(% by volume):	1.85
Explosion Data:	Sensitivity to Mechanical Impact: N.Ap	Sensitivity to Static Discharge:	N.Ap

**SECTION V-REACTIVITY DATA**




Chemical Stability Yes/No:	No	If NO under which conditions?	above 35.5°C
Incompatibility to Other Substances Yes/No:	Yes	If so which ones?	Inorganic acid conc., Peroxides, Caustics
Reactivity and under what conditions?	N/A		
Hazardous Decomposition Products:	Carbon monoxide & carbon dioxides.		
N/E: not established	N.Ap.: not applicable	N/A: not available	

Material Name/Identifier: Kleen-Start Starting Fluid		Stock No. 730	PAGE 2
<u>SECTION VI-TOXICOLOGICAL PROPERTIES OF PRODUCT</u>			
Route of Entry: ALL Routes	-SKIN CONTACT -SKIN ABSORPTION -EYE CONTACT -INHALATION -INGESTION		
Effects of Acute Exposure:	May cause defatting and drying of skin. May irritate mucous membranes of respiratory tract.		
	Overexposure may cause central nervous system depression. Headache or nausea.		
Effects of Chronic Exposure:	Continuous inhalation of spray may cause death (50 ml.)		
LD 50 of Product:	N/A	LC 50 of Product:	N/A
Irritancy of Product:	Skin & Eye Irritant	Exposure Limits of Product:	N/A
Sensitization of Product:	N/A	Toxicologically Synergistic Materials:	N/A
-CARCINOGENICITY -REPRODUCTIVE EFFECTS -TERATOGENICITY -MUTAGENICITY			None Known
<u>SECTION VII-PREVENTIVE MEASURES</u>			
Personal Protective Equipment to be used:			
Gloves(specify):	Rubber	Eye(specify):	Goggles
Respiratory(specify):	NIOSH organic vapor mask	Clothing:	Not required
Respiratory Protection:	If used indoors or on a continuous basis, use of cartridge type respirator is recommended		
Engineering Controls:	Local ventilation to keep exposure limit below 400 ppm (diethyl ether).		
Leak and Spill Procedure:	Absorb with paper towel which should then be taken away to a safe place for evaporation.		
Waste Disposal:	Defective cans with residual liquid should be disposed of in an approved hazardous waste site.		
	Empty cans can be disposed of at local recycling depots.		
Storage Requirements:	Storage at room temperature. Do not expose under direct sunlight for prolonged period.		
Handling Procedure & Equipment:	Keep away from open flame and spark. Do not store above 30°C for a long period of time.		
IATA (air transport)	Aerosol, flammable, n.o.s., (engine starting fluid), UN 1950, Class 2.1		
Marine (IMDG)	Aerosol, UN1950, Class 2, Marine Pollutant (Class 2.1 red label is required)		
TDG Classification:	Consumer Commodity		
WHMIS Classification:	Consumer Commodity - exempt from WHMIS labelling requirement.		
	If required: Class A,B5,D2B		
<u>SECTION VIII-FIRST AID MEASURES</u>			
Eye:	Flush with large amount of water for at least 15 minutes. If irritation persists, seek medical help.		
Skin:	Wash with soap and water.		
Inhalation:	Remove to open air. Maintain body warmth. Seek medical help.		
Ingestion:	Do not induce vomiting. Seek medical help.		
<u>SECTION IX-PREPARATION DATE OF M.S.D.S.</u>			
Additional Info/Comments:		Sources Used:	Handbook of Poisoning by R. Dreisbach
Phone Number:	(905) 793-4311	Prepared By:	Quality Control Laboratory
Date:	March 3rd 2003		Kleen-Flo Tumbler Industries Limited
<b>THIS SHEET SUPERSEDES ANY OTHER M.S.D.S. PREVIOUSLY PREPARED</b>			
N/A: not available		N/R: not established	





## Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

**Section 1. Chemical Product and Company Identification**

Product Name	CHAIN OIL (SUMMER, WINTER)	Code	CHAS, 490-431 CHAW, 490-430
Synonym	Not available	Validated on	5/5/2003.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-986-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	These products are designed for lubrication of chain saw chains in both high and low ambient temperatures.		

**Section 2. Composition and Information on Ingredients**

			Exposure Limits (ACGIH)		
Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
1) Mixture of severely hydrotreated and hydrocracked and/or solvent-refined base oil (petroleum) and other proprietary, non-hazardous additives.	Mixture	100	5 mg/m <sup>3</sup> (oil mist)	10 mg/m <sup>3</sup> (oil mist)	Not established
Manufacturer Recommendation	Not applicable				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

**Section 3. Hazards Identification.**

Potential Health Effects	Non irritating to slight transient irritation to skin and eyes, but no permanent damage. Relatively non-toxic via ingestion. This product has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions. Upon heating to high temperatures, or mechanical actions which may produce vapours or mists, inhalation of product may cause irritation of the breathing passages. For more information, refer to Section 11.
--------------------------	--

**Section 4. First Aid Measures**

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

**Section 5. Fire-fighting Measures**

Flammability	May be combustible at high temperature.	Flammable Limits	Not available
Flash Points	OPEN CUP: $\geq 166^{\circ}\text{C}$ (334.4°F) (Cleveland)	Auto-Ignition Temperature	Not available
Fire Hazards In Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), sulphur compounds (H <sub>2</sub> S), phosphorus compounds (PO <sub>x</sub> ), smoke and irritating vapours as products of incomplete combustion.		

**Fire Fighting  
Media and  
Instructions**

NAERG98, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO<sub>2</sub>. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

**Section 6. Accidental Release Measures****Material Release  
or Spill**

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

**Section 7. Handling and Storage****Handling**

Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.

**Storage**

Store in dry, cool, well-ventilated area. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).

**Section 8. Exposure Controls/Personal Protection****Engineering Controls**

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work station.

**Personal Protection**

*The selection of personal protective equipment varies, depending upon conditions of use.*

**Eyes**

Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

**Body**

Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

**Respiratory**

Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

**Hands**

Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

**Feet**

Wear appropriate footwear to prevent product from coming in contact with feet and skin.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Stringy liquid.	<b>Viscosity</b>	CHAS: 155 cSt @ 40°C (104°F), 16.2 cSt @ 100°C (212°F), VI=109 CHAW: 32 @ 40°C (104°F), 6.28 cSt @ 100°C (212°F), VI=151
<b>Colour</b>	Dark red.	<b>Pour Point</b>	CHAS: -21°C (-6°F) CHAW: -42°C (-44°F)
<b>Odour</b>	Slight petroleum oil like.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	Not available	<b>Penetration</b>	Not applicable.
<b>Density</b>	0.831 - 0.88 kg/L @ 15°C (59°F).	<b>Oil / Water Dist. Coefficient</b>	Not available
<b>Vapour Density</b>	Not available	<b>Ionicity (in water)</b>	Not available
<b>Vapour Pressure</b>	Negligible at ambient temperature and pressure.	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	Non-volatile.	<b>Solubility</b>	Insoluble in water.

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Copper corrosion, 3h, 100°C (ASTM D0130): 1a		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents, reducing agents and acids.	<b>Decomposition Products</b>	May release COx, NOx, SOx, H2S, POx, smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation and ingestion.		
<b>Acute Lethality</b>	Not available		
<b>Chronic or Other Toxic Effects</b>			
Dermal Route:	Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne.		
Inhalation Route:	Negligible breathing hazard at normal temperatures (up to 38°C) or recommended blending temperatures. Elevated temperatures or mechanical action may form vapours, mists or fumes. Inhalation of oil mists or vapours from hot oil may cause irritation of the upper respiratory tract.		
Oral Route:	Low toxicity; has laxative effect.		
Eye Irritation/Inflammation:	Repeated or prolonged contact may cause transient irritation, but no permanent damage.		
Immunotoxicity:	Not available		
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.		
Mutagenic:	This product is not expected to be a mutagen, based on the available data and the known hazards of the components.		
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.		
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.		
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as A1 or A2 carcinogens by ACGIH.		
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.		
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.		
Carcinogenicity (IRIS):	Not available		
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.		
<b>Other Considerations</b>	No additional remark		

**Section 12. Ecological Information**

<b>Environmental Fate</b>	Not available	<b>Persistence/Bioaccumulation Potential</b>	Not available
<b>BOD5 and COD</b>	Not available	<b>Products of Biodegradation</b>	Not available
<b>Additional Remarks</b>	No additional remark.		






**Section 13. Disposal Considerations**

<b>Waste Disposal</b>	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.
-----------------------	--

**Section 14. Transport Information**

<b>TDG Classification</b>	Not controlled under TDG (Canada).	<b>Special Provisions for Transport</b>	Not applicable.
---------------------------	------------------------------------	---	-----------------

**Section 15. Regulatory Information**

<b>Other Regulations</b>		This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).																									
		All components of this formulation are listed on the US EPA-TSCA inventory.																									
		All components of this formulation are listed on EINECS or are exempt.																									
		This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.																									
		Please contact Product Safety for more information.																									
<b>DSD/DPD (Europe)</b>		Not classified under the Dangerous Substances or Dangerous Preparations Directives.		<b>HCS (U.S.A.)</b>		Not controlled under the HCS (United States).																					
<b>ADR (Europe) (Pictograms)</b>				<b>DOT (U.S.A) (Pictograms)</b>																							
<b>HMIS (U.S.A.)</b>		<table><tr><td>Health Hazard</td><td>1</td></tr><tr><td>Fire Hazard</td><td>1</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>5</td></tr></table>		Health Hazard	1	Fire Hazard	1	Reactivity	0	Personal Protection	5	<b>NFPA (U.S.A.)</b>		<table><tr><td>Health</td><td></td><td>Fire Hazard</td><td>1</td></tr><tr><td></td><td></td><td>Reactivity</td><td>0</td></tr><tr><td></td><td></td><td>Specific hazard</td><td></td></tr></table>		Health		Fire Hazard	1			Reactivity	0			Specific hazard	
Health Hazard	1																										
Fire Hazard	1																										
Reactivity	0																										
Personal Protection	5																										
Health		Fire Hazard	1																								
		Reactivity	0																								
		Specific hazard																									
				Rating		<table><tr><td>0</td><td>Insignificant</td></tr><tr><td>1</td><td>Slight</td></tr><tr><td>2</td><td>Moderate</td></tr><tr><td>3</td><td>High</td></tr><tr><td>4</td><td>Extreme</td></tr></table>		0	Insignificant	1	Slight	2	Moderate	3	High	4	Extreme										
0	Insignificant																										
1	Slight																										
2	Moderate																										
3	High																										
4	Extreme																										

**Section 16. Other Information**

<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark
-------------------	---

**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists  
 ADR - Agreement on Dangerous goods by Road (Europe)  
 ASTM - American Society for Testing and Materials  
 BOD5 - Biological Oxygen Demand in 5 days  
 CAN/CGA B149.2 - Propane Installation Code  
 CAS - Chemical Abstract Services  
 CEPA - Canadian Environmental Protection Act  
 CERCLA - Comprehensive Environmental Response, Compensation and Liability Act  
 CFR - Code of Federal Regulations  
 CHIP - Chemicals Hazard Information and Packaging Approved Supply List  
 COD5 - Chemical Oxygen Demand in 5 days  
 CPR - Controlled Products Regulations  
 DOT - Department of Transport  
 DSEL - Dangerous Substances Classification and Labeling (Europe)  
 DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)  
 DSL - Domestic Substance List  
 EEC/EU - European Economic Community/European Union  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 EPCRA - Emergency Planning and Community Right to Know Act  
 FDA - Food and Drug Administration  
 FIFRA - Federal Insecticide, Fungicide and Rodenticide Act  
 HCS - Hazardous Communication System  
 HMIS - Hazardous Material Information System  
 IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System  
 LD50/LC50 - Lethal Dose/Concentration kill 50%  
 LDLo/LCLo - Lowest Published Lethal Dose/Concentration  
 NAERG'98 - North American Emergency Response Guide Book (1990)  
 NFPA - National Fire Protection Association  
 NIOSH - National Institute for Occupational Safety & Health  
 NPRI - National Pollutant Release Inventory  
 NSNR - New Substances Notification Regulations (Canada)  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety & Health Administration  
 PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 SARA - Superfund Amendments and Reorganization Act  
 SD - Single Dose  
 STEL - Short Term Exposure Limit (15 minutes)  
 TDG - Transportation Dangerous Goods (Canada)  
 TDLo/TCLo - Lowest Published Toxic Dose/Concentration  
 TLM - Median Tolerance Limit  
 TLV-TWA - Threshold Limit Value-Time Weighted Average  
 TSCA - Toxic Substances Control Act  
 USEPA - United States Environmental Protection Agency  
 USP - United States Pharmacopoeia  
 WHMIS - Workplace Hazardous Material Information System

For Copy of MSDS  
 Internet: [www.petro-canada.ca](http://www.petro-canada.ca)

Lubricants:  
 Western Canada, telephone: 1-800-861-1199; fax: (780) 484-9584  
 Ontario & Central Canada, telephone: 1-800-288-5850 and (905) 822-4222; fax: 1-800-201-6285  
 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 5/6/2003.

Data entry by Product Safety - JDW.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.





## Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

## Section 1. Chemical Product and Company Identification

Product Name	HYDREX <sup>®</sup> MV 22, 36, 60	Code	490-110-0, HDXMV22 490-111-0, HDXMV36 490-112-0, HDXMV60
Synonym	Not available.	Validated on	9/5/2001.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-298-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	These products are designed as heavy duty hydraulic power transmission fluids for use in equipment, which must operate over a wide range of temperatures. Typically, Hydrex <sup>®</sup> MV Oils are used in hydraulic systems, machine tools, hydraulic presses, rotary compressors, and centrifugal pumps.		

## Section 2. Composition and Information on Ingredients

			Exposure Limits (ACGIH)		
Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
1) Mixture of severely hydrotreated paraffinic oil and additives.	Mixture	100	5 mg/m <sup>3</sup> (oil mist)	10 mg/m <sup>3</sup> (oil mist)	Not established
Manufacturer Recommendation	Not applicable				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

## Section 3. Hazards Identification.

Potential Health Effects	Non irritating to slight transient irritation to skin and eyes, but no permanent damage. Relatively non-toxic via ingestion. This product has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions. Upon heating to high temperatures, or mechanical actions which may produce vapours or mists, inhalation of product may cause irritation of the breathing passages. For more information, refer to Section 11.
--------------------------	--

## Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

## Section 5. Fire-fighting Measures

Flammability	May be combustible at high temperature.	Flammable Limits	Not available.
Flash Points	OPEN CUP: ≥208°C (406.4°F) (Cleveland)	Auto-ignition Temperature	Not available.
Fire Hazards In Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards In Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), smoke and irritating vapours as products of incomplete combustion.		

HYDREX® MV 22, 36, 60

Page Number: 2

**Fire Fighting  
Media and  
Instructions**

NAERG98, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO<sub>2</sub>. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

**Section 6. Accidental Release Measures****Material Release  
or Spill**

NAERG98, GUIDE 171, Substances (low to moderate hazard). ELIMINATE ALL IGNITION SOURCES. Avoid contact. Stop leak if without risk. Contain spill. Absorb with inert absorbents, dry clay, or diatomaceous earth. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.

**Section 7. Handling and Storage****Handling**

Avoid inhalation and skin contact especially when handling used oil. Keep away from sources of ignition. DO NOT reuse empty containers without commercial cleaning or reconditioning. Practice good personal hygiene. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.

**Storage**

Store in tightly closed containers in cool, dry, isolated, well-ventilated area, and away from incompatibles.

**Section 8. Exposure Controls/Personal Protection****Engineering Controls**

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

**Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.****Eyes**

Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

**Body**

Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

**Respiratory**

Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

**Hands**

Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

**Feet**

Wear appropriate footwear to prevent product from coming in contact with feet and skin.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Viscous liquid.	<b>Viscosity</b>	22: 23.6 cSt @ 40°C (104°F), 5.01 cSt @ 100°C, VI=188 36: 32.25 cSt @ 40°C (104°F), 6.3 cSt @ 100°C, VI=148 60: 58.0 cSt @ 40°C (104°F), 8.95 cSt @ 100°C, VI=132
<b>Colour</b>	Pale, straw-yellow. 36: Under special circumstances this product may contain blue dye.	<b>Pour Point</b>	22: -61°C 36: -48°C 60: -42°C
<b>Odour</b>	Mild petroleum oil like.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available.	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	Not available.	<b>Penetration</b>	Not applicable.
<b>Density</b>	0.842 to 0.8623 kg/L @ 15°C (59°F).	<b>Oil / Water Dist. Coefficient</b>	Not available.
<b>Vapour Density</b>	Not available.	<b>Ioncity (in water)</b>	Not available.
<b>Vapour Pressure</b>	Negligible at ambient temperature and pressure.	<b>Dispersion Properties</b>	Not available.
<b>Volatility</b>	Non-volatile	<b>Solubility</b>	Insoluble in water.

HYDREX MV 22, 36, 60

Page Number: 3

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Copper corrosion, 3h, 100°C (ASTM D0130): 1a		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents and acids.	<b>Decomposition Products</b>	May release COx, SOx, H2S, POx, CaOx, ZnOx, methacrylate monomers, aldehydes, alkyl mercaptans, smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation, and ingestion.		
<b>Acute Lethality</b>	Based on toxicity of components. Acute oral toxicity (LD50): >5000 mg/kg (rat); Acute dermal toxicity (LD50): >2000 mg/kg (rabbit); Acute inhalation toxicity (LC50): >2500 mg/m³/4h (rat)		
<b>Chronic or Other Toxic Effects</b>			
Dermal Route:	Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne.		
Inhalation Route:	Negligible breathing hazard at normal temperatures (up to 38°C) or recommended blending temperatures. Elevated temperatures or mechanical action may form vapours, mists or fumes. Inhalation of oil mists or vapours from hot oil may cause irritation of the upper respiratory tract.		
Oral Route:	Low toxicity; has laxative effect.		
Eye Irritation/Inflammation:	Repeated or prolonged contact may cause transient irritation, but no permanent damage.		
Immunotoxicity:	Not available.		
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.		
Mutagenic:	Based on actual test results of base oils and results of similar products, severely hydrotreated base oils give negative results when tested for: (a) Salmonella Typhimurium TA98 using the Modified Ames Assay for Petroleum Product; (b) Salmonella-Escherichia coli/Mammalian-Microsome Reverse Mutation Assay (Ames test) with a Confirmatory Assay; (c) Structural Chromosomal Aberrations in Chinese Hamster Ovary (CHO) Cells.		
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.		
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.		
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as A1 or A2 carcinogens by ACGIH.		
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.		
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.		
Carcinogenicity (IRIS):	Not available.		
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.		
<b>Other Considerations</b>	No additional remark.		

**Section 12. Ecological Information**

<b>Environmental Fate</b>	Not available	<b>Persistence/Bioaccumulation Potential</b>	Not available
<b>BOD5 and COD</b>	Not available.	<b>Products of Biodegradation</b>	Not available.
<b>Additional Remarks</b>	No additional remark.		



HYDREX<sup>®</sup> MV 22, 38, 60

Page Number: 4






**Section 13. Disposal Considerations**

<b>Waste Disposal</b>	Spent/used/waste oil may meet the requirements of a hazardous waste. Consult your local or regional authorities. Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations.
-----------------------	---

**Section 14. Transport Information**

<b>TDG Classification</b>	Not controlled under TDG (Canada).	<b>Special Provisions for Transport</b>	Not applicable.
---------------------------	------------------------------------	---	-----------------

**Section 15. Regulatory Information**

<b>Other Regulations</b>		This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).																												
		All components of this formulation are listed on the US EPA-TSCA Inventory.																												
		All components of this formulation are listed on EINECS or exempt.																												
		This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.																												
		Please contact Product Safety for more information.																												
<b>DSD/DPD (Europe)</b>		Not classified under the Dangerous Substances or Dangerous Preparations Directives.		<b>HCS (U.S.A.)</b>		Not controlled under the HCS (United States).																								
<b>ADR (Europe) (Pictograms)</b>				<b>DOT (U.S.A.) (Pictograms)</b>																										
<b>WHMIS (U.S.A.)</b>		<table><tr><td>Health Hazard</td><td>(1)</td></tr><tr><td>Fire Hazard</td><td>(1)</td></tr><tr><td>Reactivity</td><td>(0)</td></tr><tr><td>Personal Protection</td><td>(b)</td></tr></table>		Health Hazard	(1)	Fire Hazard	(1)	Reactivity	(0)	Personal Protection	(b)	<b>NFPA (U.S.A.)</b>		<table><tr><td rowspan="3"></td><td>Fire Hazard</td><td>Rating</td><td>0 Insignificant</td></tr><tr><td>Health</td><td>Reactivity</td><td>1 Slight</td></tr><tr><td>Specific hazard</td><td>2 Moderate</td></tr><tr><td></td><td></td><td>3 High</td></tr><tr><td></td><td></td><td>4 Extreme</td></tr></table>			Fire Hazard	Rating	0 Insignificant	Health	Reactivity	1 Slight	Specific hazard	2 Moderate			3 High			4 Extreme
Health Hazard	(1)																													
Fire Hazard	(1)																													
Reactivity	(0)																													
Personal Protection	(b)																													
	Fire Hazard	Rating	0 Insignificant																											
	Health	Reactivity	1 Slight																											
	Specific hazard	2 Moderate																												
		3 High																												
		4 Extreme																												

**Section 16. Other Information**

<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark
-------------------	---

**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists  
 ADR - Agreement on Dangerous goods by Road (Europe)  
 ASTM - American Society for Testing and Materials  
 BOD5 - Biological Oxygen Demand in 5 days  
 CAN/CGA B149.2 Propane Installation Code  
 CAS - Chemical Abstract Services  
 CEPA - Canadian Environmental Protection Act  
 CERCLA - Comprehensive Environmental Response, Compensation and Liability Act  
 CFR - Code of Federal Regulations  
 CHIP - Chemicals Hazard Information and Packaging Approved Supply List  
 COD5 - Chemical Oxygen Demand in 5 days  
 CPR - Controlled Products Regulations  
 DOT - Department of Transport  
 DSEL - Dangerous Substances Classification and Labeling (Europe)  
 DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)  
 DSL - Domestic Substances List  
 EEC/EU - European Economic Community/European Union  
 EINECS - European Inventory of Existing Commercial Chemical Substances  
 EPCRA - Emergency Planning and Community Right to Know Act  
 FDA - Food and Drug Administration  
 FIFRA - Federal Insecticide, Fungicide and Rodenticide Act  
 HCS - Hazardous Communication System  
 HMIS - Hazardous Material Information System  
 IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System  
 LD50/LC50 - Lethal Dose/Concentration kill 50%  
 LDLo/LCLo - Lowest Published Lethal Dose/Concentration  
 NAERG'86 - North American Emergency Response Guide Book (1986)  
 NFPA - National Fire Protection Association  
 NIOSH - National Institute for Occupational Safety & Health  
 NPLI - National Pollutant Release Inventory  
 NSNR - New Substances Notification Regulations (Canada)  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety & Health Administration  
 PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 SARA - Superfund Amendments and Reorganization Act  
 SD - Single Dose  
 STEL - Short Term Exposure Limit (15 minutes)  
 TDG - Transportation Dangerous Goods (Canada)  
 TDLo/TCLo - Lowest Published Toxic Dose/Concentration  
 TLM - Median Tolerance Limit  
 TLV-TWA - Threshold Limit Value-Time Weighted Average  
 TSCA - Toxic Substances Control Act  
 USEPA - United States Environmental Protection Agency  
 USP - United States Pharmacopoeia  
 WHMIS - Workplace Hazardous Material Information System

**For Copy of MSDS**

**Lubricants:**  
 Western Canada, telephone: 1-800-661-1199; fax: (780) 484-9584  
 Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax: 1-800-201-6285  
 Quebec & Eastern Canada, telephone: 1-800-576-1886; fax: 800-201-6285

**For Product Safety Information: (905) 804-4752**

Prepared by Product Safety - TAR on 9/5/2001.

Data entry by Product Safety - JDW.

Continued on Next Page

Available in French

HYDREX<sup>®</sup> MV 22, 36, 60

Page Number: 8

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*



## Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

## Section 1. Chemical Product and Company Identification

Product Name	<b>DURON<sup>®</sup> MULTIGRADE ENGINE OIL SAE VISCOSITY GRADES 10W-30, 15W-40</b>	Code	420-051, DUR13 420-053, DUR15
Synonym	Not available	Validated on	11/1/2002.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-896-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	DURON <sup>®</sup> multigrade engine oils may be used in a wide range of compression and spark ignition engines in mobile and stationary equipment. They may also be used in many types of wet clutch transmissions and hydraulic systems.		

## Section 2. Composition and Information on Ingredients

			Exposure Limits (ACGIH)		
Name	CAS #	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
1) Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and other proprietary, non-hazardous additives.	Mixture	100	6 mg/m <sup>3</sup> (oil mist)	10 mg/m <sup>3</sup> (oil mist)	Not established
Manufacturer Recommendation	Not applicable				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

## Section 3. Hazards Identification.

Potential Health Effects	Non irritating to slight transient irritation to skin and eyes, but no permanent damage. Relatively non-toxic via ingestion. This product has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions. Upon heating to high temperatures, or mechanical actions which may produce vapours or mists, inhalation of product may cause irritation of the breathing passages. For more information, refer to Section 11.
--------------------------	--

## Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

## Section 5. Fire-fighting Measures

Flammability	May be combustible at high temperature.	Flammable Limits	Not available.
Flash Points	DUR13: OPEN CUP: 231°C (448°F) (Cleveland) DUR15: OPEN CUP: 225°C (437°F) (Cleveland)	Auto-ignition Temperature	Fire Point: DUR13: 257°C (495°F) DUR15: 255°C (491°F)
Fire Hazards In Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards In Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), CaO <sub>x</sub> , ZnO <sub>x</sub> , smoke and irritating vapours as products of incomplete combustion.		

DURON <sup>®</sup> MULTIGRADE ENGINE OIL, SAE VISCOSITY GRADES 10W-30, 15W-40		Page Number: 2
<b>Fire Fighting Media and Instructions</b>	NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO <sub>2</sub> . LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.	

### Section 6. Accidental Release Measures

<b>Material Release or Spill</b>	NAERG96, GUIDE 171, Substances (low to moderate hazard). ELIMINATE ALL IGNITION SOURCES. Avoid contact. Stop leak if without risk. Contain spill. Absorb with inert absorbents, dry clay, or diatomaceous earth. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.
----------------------------------	---

### Section 7. Handling and Storage

<b>Handling</b>	Avoid inhalation and skin contact especially when handling used oil. Keep away from sources of ignition. DO NOT return empty containers without commercial cleaning or reconditioning. Practice good personal hygiene. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.
<b>Storage</b>	Store in tightly closed containers in cool, dry, isolated, well-ventilated area, and away from incompatibles.

### Section 8. Exposure Controls/Personal Protection

<b>Engineering Controls</b>	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.
<b>Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.</b>	
<b>Eyes</b>	Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.
<b>Body</b>	Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.
<b>Respiratory</b>	Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.
<b>Hands</b>	Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.
<b>Feet</b>	Wear appropriate footwear to prevent product from coming in contact with feet and skin.

### Section 9. Physical and Chemical Properties

<b>Physical State and Appearance</b>	Viscous liquid.	<b>Viscosity</b>	DUR13: 74 cSt @ 40°C DUR15: 115 cSt @ 40°C
<b>Colour</b>	Light amber.	<b>Pour Point</b>	DUR13: -45°C DUR15: -39°C
<b>Odour</b>	Mild petroleum oil like.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available.	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	Not available.	<b>Penetration</b>	Not applicable.
<b>Density</b>	DUR13: 0.8604 kg/L @ 15°C (59°F) DUR15: 0.8720 kg/L @ 15°C (59°F)	<b>Oil / Water Dist. Coefficient</b>	Not available
<b>Vapour Density</b>	Not available.	<b>Ionicity (in water)</b>	Not available
<b>Vapour Pressure</b>	Negligible at ambient temperature and pressure.	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	Non-volatile	<b>Solubility</b>	Insoluble in water.

DURON<sup>®</sup> MULTIGRADE ENGINE OIL SAE VISCOSITY GRADES 10W-30,  
15W-40

Page Number: 3

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Copper corrosion, 3h, 100°C (ASTM D0130): 1b		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents, acids, halogens and halogen compounds.	<b>Decomposition Products</b>	May release COx, SOx, H2S, CaOx, alkyl mercaptans, sulfides, aldehydes, methacrylate monomers, smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation, and ingestion.		
<b>Acute Lethality</b>	Based on toxicity of components. acute oral toxicity (LD50): >5000 mg/kg (rat) acute dermal toxicity (LD50): >2000 mg/kg (rabbit) acute inhalation toxicity (LC50): >2500 mg/m <sup>3</sup> /4h (rat)		
<b>Chronic or Other Toxic Effects</b>			
Dermal Route:	Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne.		
Inhalation Route:	Negligible breathing hazard at normal temperatures (up to 38°C) or recommended blending temperatures. Elevated temperatures or mechanical action may form vapours, mists or fumes. Inhalation of oil mists or vapours from hot oil may cause irritation of the upper respiratory tract.		
Oral Route:	Low toxicity; has laxative effect.		
Eye Irritation/Inflammation:	Repeated or prolonged contact may cause transient irritation, but no permanent damage.		
Immunotoxicity:	Not available.		
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.		
Mutagenic:	Base oil exhibited negative mutagenic activity toward: (a) Salmonella Typhimurium TA98 using the Modified Ames Assay for Petroleum Product; (b) Salmonella-Escherichia coli/Mammalian-Microsome Reverse Mutation Assay (Ames test) with a Confirmatory Assay; (c) Structural Chromosomal Aberrations in Chinese Hamster Ovary (CHO) Cells.		
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.		
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.		
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as A1 or A2 carcinogens by ACGIH.		
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.		
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.		
Carcinogenicity (IRIS):	Not available.		
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.		
<b>Other Considerations</b>	No additional remark.		

**Section 12. Ecological Information**

<b>Environmental Fate</b>	Not available	<b>Persistence/Bioaccumulation Potential</b>	Not available
<b>BOD5 and COD</b>	Not available.	<b>Products of Biodegradation</b>	Not available.
<b>Additional Remarks</b>	No additional remark.		



DURON® MULTIGRADE ENGINE OIL 8AE VISCOSITY GRADES 10W-30,  
15W-40

Page Number: 4

**Section 13. Disposal Considerations**

**Waste Disposal** Spent/used/waste oil may meet the requirements of a hazardous waste. Consult your local or regional authorities. Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations.

**Section 14. Transport Information**

<b>TDG Classification</b>	Not controlled under TDG (Canada).	<b>Special Provisions for Transport</b>	Not applicable.
---------------------------	------------------------------------	---	-----------------





**Section 15. Regulatory Information**

**Other Regulations** This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

<b>DSD/DPD (Europe)</b>		Not classified under the Dangerous Substances or Dangerous Preparations Directives.		<b>HCS (U.S.A.)</b>		Not controlled under the HCS (United States).																										
<b>ADR (Europe) (Pictograms)</b>		NOT EVALUATED FOR EUROPEAN TRANSPORT  NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN		<b>DOT (U.S.A.) (Pictograms)</b>																												
<b>HMIS (U.S.A.)</b>		<table><tr><td>Health Hazard</td><td>(1)</td></tr><tr><td>Fire Hazard</td><td>(1)</td></tr><tr><td>Reactivity</td><td>(0)</td></tr><tr><td>Personal Protection</td><td>(0)</td></tr></table>		Health Hazard	(1)	Fire Hazard	(1)	Reactivity	(0)	Personal Protection	(0)	<b>NFPA (U.S.A.)</b>		<table><tr><td rowspan="3">Health</td><td rowspan="3"></td><td>Fire Hazard</td><td rowspan="3">Rating</td><td>0 Insignificant</td></tr><tr><td>Reactivity</td><td>1 Slight</td></tr><tr><td>Specific hazard</td><td>2 Moderate</td></tr><tr><td></td><td></td><td></td><td>3 High</td></tr><tr><td></td><td></td><td></td><td>4 Extreme</td></tr></table>		Health		Fire Hazard	Rating	0 Insignificant	Reactivity	1 Slight	Specific hazard	2 Moderate				3 High				4 Extreme
Health Hazard	(1)																															
Fire Hazard	(1)																															
Reactivity	(0)																															
Personal Protection	(0)																															
Health		Fire Hazard	Rating	0 Insignificant																												
		Reactivity		1 Slight																												
		Specific hazard		2 Moderate																												
			3 High																													
			4 Extreme																													

**Section 16. Other Information**

**References** Available upon request.  
\* Marque de commerce de Petro-Canada - Trademark

**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemicals Hazard Information and Packaging Approved Supply List COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSEL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substances List EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning and Community Right to Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer	IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NAERG'98 - North American Emergency Response Guide Book (1998) NFPA - National Fire Protection Association NIOSH - National Institute for Occupational Safety & Health NPLRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act SD - Single Dose STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration Tm - Median Tolerance Limit TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System
--	---

**For Copy of MSDS**  
Internet: [www.petro-canada.ca](http://www.petro-canada.ca)

**Lubricants:**  
 Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564  
 Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax: 1-800-201-6285  
 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

**For Product Safety Information: (905) 804-4752**

Prepared by Product Safety - JDW on 11/1/2002.

Data entry by Product Safety - JDW.

DURON® MULTIGRADE ENGINE OIL SAE VISCOSITY GRADES 10W-30,  
15W-40

Page Number: 5

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*