

Extreme Kwik-Set

Fast Setting, Oilwell Gyp Cement

Description

Extreme Kwik-Set is a special formula oilwell quality, gyp cement, which sets fast and is environment friendly.

Principle Use

Extreme Kwik-Set imparts tenacious bonding capabilities on loose and fractured formations to stabilize caving zones or lost circulation sections. Easy to use. Hardens quickly but remains easy to drill. Ideally suited for holes which must be redrilled, beyond the cemented section without deflecting off. Ensures re-entering existing borehole. Solidifies formation without becoming "Rock Hard" like portland cement.

Extreme Kwik-Set solidifies in approximately 1½ to 2½ hours depending on hole conditions and temperature.

Mixing

Mix contents of each pail with 2½ gallons of water. Stir only long enough to ensure all the cement product is wet. Then pour down drill rods and pump to bottom. For best results use wiper plugs or a "Burlap Spacer" in front of Extreme Kwik-Set in the drill rods and immediately behind it to eliminate dilution from water in the hole and drill rods.

Packaging

Extreme Kwik-Set comes in 5 gallon, 50 lb., high impact plastic pails with a snap-on lid. 32 pails per pallet.

MATERIAL SAFETY DATA SHEET



15640 Mountainview Dr., White Rock, BC V4P 2W9 • Tel: (604) 535-6699 Fax: (604) 535-5499

EMERGENCY PHONE NO. (604) 535-6699

PAGE 1 OF 4

WHMIS HAZARD INDEX:

DEGREE OF HAZARD:

HEALTH 0
FIRE 0
REACTIVITY 0
OTHER: B (GLASSES & GLOVES)

HAZARD RATING:

0 LEAST
1 SLIGHT
2 MODERATE
3 HIGH
4 EXTREME

SECTION 1

PRODUCT IDENTIFICATION

PRODUCT NAME:
CHEMICAL IDENTIFICATION:
MATERIAL USE:
WHMIS CLASSIFICATION:
WORK PLACE HAZARD:

EXTREME KWIK-SET
Calcium Sulphate
Oilwell Cement
Not Hazardous Material
Not Applicable

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION:
PACKAGE GROUP:
CAS NUMBER:
MSDS CODE:

Not Dangerous Goods
Not Applicable
Not Applicable
Not Applicable

SECTION 2

HAZARDOUS INGREDIENTS

INGREDIENT:
PERCENTAGE:
CAS NUMBER:
LD (50):
LC (50):

No Hazardous Ingredients

EXTREME KWIK-SET

MATERIAL SAFETY DATA SHEET

SECTION 3

PHYSICAL DATA

| | |
|-----------------------------|---|
| APPEARANCE AND ODOUR: | Greyish White to Buff Powder. Little odour. |
| DENSITY (SPECIFIC GRAVITY): | 2.7 |
| BOILING POINT: | N/A |
| MELTING POINT: | N/A |
| SOLUBILITY: | 2% @ 40°C |
| EVAPORATION RATE: (EE=1): | N/A |
| VAPOUR PRESSURE: (MM HG): | N/A |
| VAPOUR DENSITY: (AIR = 1): | N/A |
| pH: | 7-8 (Slurry) |

SECTION 4

FIRE AND EXPLOSION

| | |
|-------------------------------------|-------------------------|
| FLASHPOINT: | Not Combustible |
| FLAMMABLE LIMIT: | Not Combustible |
| AUTO IGNITION TEMP: | Not Combustible |
| EXTINGUISHING MEDIA: | Not Combustible |
| SPECIAL FIRE FIGHTING PROCEDURES: | No Special Requirements |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | None |

SECTION 5

REACTIVITY DATA

| | |
|--|----------------|
| STABILITY (THERMAL, LIGHT, ETC.): | Stable |
| INCOMPATIBILITY (CONDITIONS TO AVOID): | None Known |
| HAZARDOUS POLYMERIZATION: | Will Not Occur |
| HAZARDOUS DECOMPOSITION PRODUCTS: | None |

EXTREME KWIK-SE

MATERIAL SAFETY DATA SHEET

SECTION 6 HEALTH HAZARDS

ROUTE OF ENTRY:

☒ SKIN☒ EYE CONTACT☒ INHALATION☐ INGESTION

SKIN CONTACT:

May dry skin; may develop heat sufficient to cause burns if large mass is in contact with skin during hardening (hydration).

EYE CONTACT:

Particles may cause irritation.

INHALATION:

Nuisance dust may cause sneezing and nasal irritation. May contain trace amounts of crystalline silica, which is known to cause silicosis when exposed to greater amounts.

INGESTION:

Avoid ingestion; product may harden on contact with water. May cause obstruction.

SECTION 7 PREVENTATIVE MEASURES

SKIN PROTECTION:

Standard work clothes and gloves.

EYE PROTECTION:

Nuisance dust, suggest goggles.

VENTILATION:

No special requirements. 10 changes per hour suggested.

RESPIRATORY PROTECTION:

Nuisance dust, suggest NIOSH/MESA approved dust mask.

LEAK & SPILL PROCEDURE:

Vacuum or sweep-up.

WASTE DISPOSAL:

Dispose of in compliance with government regulations and local requirements.

STORAGE REQUIREMENTS:

Store in a cool, dry area.

EXTREME KWIK-SET

MATERIAL SAFETY DATA SHEET

SECTION 8

FIRST AID MEASURES

SKIN:

Wash promptly with water. If irritation develops consult a physician.

EYE:

Rinse eyes with plenty of running water for 10-15 minutes including under eyelids. If irritation persists, contact a physician.

INHALATION:

Remove to fresh air.

INGESTION:

Product may harden on contact with water. May result in obstruction if ingested. See physician.

SECTION 9

PREPARATION DATE

DATE ISSUED:

May 1, 1997

BY:

PRODUCT SAFETY COMMITTEE

THE DATA REPRESENTED HEREIN IS BELIEVED ACCURATE AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.

DATE REVISED: