

**SECTION 1 – PRODUCT INFORMATION**

**Product Name:** Propane  
**Trade Name:** LPG (Liquified Petroleum Gas), LP-Gas  
**Chemical Formula:** C<sub>3</sub>H<sub>8</sub>

**Supplier:** Superior Propane Inc.  
1111 - 49th Avenue N.E.  
Calgary, AB T2E 8V2

**WHMIS CLASSIFICATION**

Class A - Compressed Gas

Class B, Division 1 - Flammable Gas

**Business:** (403) 730-7500

**Local Branch**

**Emergency Number:** \_\_\_\_\_

(Non Medical)

**Application and Use:** Propane is commonly used as a fuel for heating, cooking, automobiles, forklift trucks, crop drying and welding and cutting operations. Propane is used in industry as a refrigerant, solvent and as a chemical feedstock.

**SECTION 2 – HAZARDOUS INGREDIENTS**

| COMPONENTS                       | CAS NO.   | % Volume (v/v) | LD50           |
|----------------------------------|-----------|----------------|----------------|
| Propane                          | 74 -98-6  | 90% - 99%      | Not Applicable |
| Propylene                        | 115 -07-1 | 0% - 5%        | Not Applicable |
| Ethane                           | 74 -84-0  | 0% - 5%        | Not Applicable |
| Butane and heavier hydro carbons | 106 -97-8 | 0% - 2.5%      | Not Applicable |

Occupational Exposure Limit:

Based upon animal test data, the acute toxicity of this product is expected to be inhalation: 4 hour LC50 = 280,000 ppm (Rat).

**Note:** Composition is typical for HD-5 Propane per The Canadian General Standard Board CGSB 3.14 National Standard of Canada. Exact composition will vary from shipment to shipment.

**SECTION 3 – CHEMICAL AND PHYSICAL DATA**

**Form:** Liquid and vapour while stored under pressure.

**Boiling Point:** -42°C @ 1 atm.

**Freezing Point:** -188°C

**Evaporation Rate:** Rapid (Gas at normal ambient conditions).

**Vapour Pressure:** 1435 kPa (maximum) @ 37.8°C

**Vapour Density:** 1.52 (Air = 1)

**Coefficient of Water/Oil Distribution:** Not available.

**pH:** Not available.

**Solubility in water:** Slight, 6.1% by volume @ 17.8°C

**Specific Gravity:** 0.51 (water = 1)

**Appearance/Odour:** Colourless liquid and vapour while stored under pressure. Colourless and odourless gas in natural state at any concentration. Commercial propane has an odourant added, ethyl mercaptan, which has an odour similar to boiling cabbage.\*

**Odour Threshold:** 4800 ppm

\* With proper handling, transportation and storage, adding a chemical odourant such as eth-merc has proven to be a very effective warning device, but all odourants have certain limitations. The effectiveness of the odourant may be diminished by a person's sense of smell, by competing odours and by oxidation which may cause a potentially dangerous situation.

**SECTION 4 – FIRE OR EXPLOSION HAZARD**

**Flash Point:** -103.4°C

**Method:** Closed cup.

**Flammable Limits:** Lower 2.4%, Upper 9.5%

**Auto Ignition Temperature:** 432°C

**Products Evolved Due To Heat Or Combustion:** Carbon monoxide can be produced when primary air and secondary air are deficient while combustion is taking place.

**Fire and Explosive Hazards:** Explosive air-vapour mixtures may form if allowed to leak to atmosphere.

**Sensitivity To Impact:** No.

**Sensitivity To Static Discharge:** Yes.

**Fire Extinguishing Precautions:** Use water spray to cool exposed cylinders or tanks. Do not extinguish fire unless the source of the escaping gas that is fueling the fire can be turned off. Fire can be extinguished with carbon dioxide and/or dry chemical (BC). Container metal shells require cooling with water to prevent flame impingement and the weakening of metal. If sufficient water is not available to protect the container shell from weakening, the area will be required to be evacuated. If gas has not ignited, liquid or vapour may be dispersed by water spray or flooding.

**Special Fire Fighting Equipment:** Protective clothing, hose monitors, fog nozzles, self-contained breathing apparatus.

**SECTION 5 – REACTIVITY DATA**

**Stability:** Stable.

**Conditions To Avoid:** Keep separate from oxidizing agents. Gas explodes spontaneously when mixed with chloride dioxide.

**Incompatibility:** Remove sources of ignition and observe distance requirements for storage tanks from combustible material, drains and openings to building.

**Hazardous Decomposition Products:** Deficient primary and secondary air can produce carbon monoxide.

**Hazardous Polymerization:** Will not occur.

## SECTION 6 – TOXICOLOGICAL PROPERTIES OF MATERIAL

### ROUTES OF ENTRY:

**Inhalation:** Simple asphyxiant. No effect at concentrations of 10,000 ppm (break exposures). Higher concentrations may cause central nervous system disorder and/or damage. Lack of oxygen may cause dizziness, loss of coordination, weakness, fatigue, euphoria, mental confusion, blurred vision, convulsions, breathing failure, coma and death. Breathing high vapour concentrations (saturated vapours) for a few minutes may be fatal. Saturated vapours may be encountered in confined spaces and/or under conditions of poor ventilation. Avoid breathing vapours or mist.

**Skin and Eye Contact:** Exposure to vapourizing liquid may cause frostbite (cold burns) and permanent eye damage.

**Ingestion:** Not considered to be a hazard.

**Acute Exposure:** The acute toxicity of this product is expected to be inhalation: 4 hour LC50=280,000ppm (Rat).

**Chronic Exposure:** There are no reported effects from long term low level exposure.

**Sensitization to Product:** Skin–unknown, Respiratory–unknown.

**Occupational Exposure Limits:** American Conference of Governmental Industrial Hygienists (ACGIH) lists as a simple asphyxiant. ACGIH TLV: 1000 ppm.

**Carcinogenicity, Reproductive Toxicity, Teratogenicity, Mutagenicity:** No effects reported.

## SECTION 7 – PREVENTIVE MEASURES

**Eyes:** Safety glasses, goggles or a face shield is recommended when transferring product.

**Skin:** Insulated gloves required if contact with liquid or liquid cooled equipment is expected. Wear gloves and long sleeves when transferring product.

**Inhalation:** Where concentration in air would reduce the oxygen level below 18% air or exceed occupational exposure limits in section 6, self-contained breathing apparatus is required.

**Ventilation:** Explosion proof ventilation equipment required in confined spaces.

## SECTION 8 – EMERGENCY AND FIRST AID PROCEDURES

### FIRST AID:

**Eyes:** Should eye contact with liquid occur, flush eyes with lukewarm water for 15 minutes. Obtain immediate medical care.

**Skin:** In case of "Cold Burn" from contact with liquid, immediately place affected area in lukewarm water and keep at this temperature until circulation returns. If fingers or hands are frostbitten, have the victim hold his hand next to his body such as under the armpit. Obtain immediate medical care.

**Ingestion:** None considered necessary.

**Inhalation:** Remove person to fresh air. If breathing is difficult or has stopped, administer artificial respiration. Obtain immediate medical care.

### SPILL OR LEAK:

Eliminate leak if possible.

Eliminate source of ignition.

Ensure cylinder is upright.

Disperse vapours with hose streams using fog nozzles. Monitor low areas as propane is heavier than air and can settle into low areas. Remain upwind of leak. Keep people away. Prevent vapour and/or liquid from entering into sewers, basements or confined areas.

## SECTION 9 – TRANSPORTATION, HANDLING AND STORAGE

- Transport and store cylinders and tanks secured in an upright position in a ventilated space away from ignition sources (so the pressure relief valve is in contact with the vapour space of the cylinder or tank).
- Cylinders that are not in use must have the valves in the closed position and be equipped with a protective cap or guard.
- Do not store with oxidizing agents, oxygen, or chlorine cylinders.

- Empty cylinders and tanks may contain product residue. Do not pressurize, cut, heat or weld empty containers.
- Transport, handle and store according to applicable federal and provincial regulations (CGA B149.2).

### Transportation of Dangerous Goods (TDG)

- TDG Classification: Flammable Gas 2.1
- TDG Shipping Name: Liquefied Petroleum Gas (Propane)
- TDG Special Provisions: 56, 90, 102
- PIN Number: UN1075

## SECTION 10 – PREPARATION

Superior Propane Inc., Regulations & Safety Department. (403) 730-7500 Date prepared: September 1999.  
Supersedes: November 1996.

The information contained herein is believed to be accurate. It is provided independently of any sale of the product. It is not intended to constitute performance information concerning the product. No express warranty, implied warranty of merchantability or fitness for a particular purpose is made with respect to the product information contained herein.

**IMPERIAL OIL  
MATERIAL SAFETY DATA SHEET****DIESEL, MINES SPECIAL-LS (DYED OR CLEAR)**

Date Prepared: October 18, 2000  
Supersedes: May 12, 1998  
MSDS Number: 05487

---

**1. PRODUCT INFORMATION**

Product Identifier: DIESEL, MINES SPECIAL-LS (DYED OR CLEAR)  
ESSO MINES DIESEL FUEL (DYED OR CLEAR)  
DIESEL MINES (DYED OR CLEAR)  
MINES DIESEL FUEL (DYED OR CLEAR)

Application and Use:  
Motor diesel fuel, for use in underground mining operations

Product Description:

A complex mixture of aliphatic, olefinic, naphthenic and aromatic hydrocarbons, and additives.

---

**REGULATORY CLASSIFICATION**

WHMIS:

Class B, Division 3: Combustible Liquids.  
Class D, Division 2, Subdivision B: Toxic Material

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT

All components of this product are either on the Domestic Substances List (DSL) or are exempt.

TDG INFORMATION (RAIL/ROAD):

Shipping Name: FUEL OIL  
Class: 3  
Packing Group: III  
PIN Number: UN1202

Please be aware that other regulations may apply.

---

**TELEPHONE NUMBERS**

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3183

**MANUFACTURER/SUPPLIER:**

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

---

**2. REGULATED COMPONENTS**

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

NAME

% CAS #

|                               |           |                                |
|-------------------------------|-----------|--------------------------------|
| Kerosene, straight run        | 0-100 V/V | 8008-20-6 LD50:>5g/kg,oral,rat |
| Light Atmospheric Gas Oil     | 0-100 V/V | 64741-44-2                     |
| Light Hydrocracked Distillate | 0-100 V/V | 64741-77-1                     |

---

### 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
Specific gravity: not available  
Viscosity: 1.95 cSt at 40 deg C  
Vapour Density: 4  
Boiling Point: 180 to 325 deg C  
Evaporation rate: <1 (1= n-butylacetate)  
Solubility in water: negligible  
Freezing/Pour Point: -39 deg C ASTM D97  
Odour Threshold: not available  
Vapour Pressure: 4 kPa at 38 deg C  
Density: 0.84 g/cc at 15 deg C  
Appearance/odour: White or pale yellow liquid, petroleum odour

---

### 4. HEALTH HAZARD INFORMATION

#### NATURE OF HAZARD

##### INHALATION:

Negligible hazard at normal temperatures (up to 38 deg C).  
High vapour concentrations are irritating to the eyes, nose, throat and lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.  
Avoid breathing vapours or mists.

##### EYE CONTACT:

Slightly irritating, but will not injure eye tissue.

##### SKIN CONTACT:

Low toxicity.  
Irritating.

##### INGESTION:

Low toxicity.  
Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

##### CHRONIC:

Lifetime skin painting tests indicate that materials of similar composition have produced skin cancer in experimental animals. The relationship of these results to humans has not been fully established.

##### ACUTE TOXICITY DATA:

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

|            |                     |          |
|------------|---------------------|----------|
| Oral       | : LD50 > 5000 mg/kg | (Rat)    |
| Dermal     | : LD50 > 2000 mg/kg | (Rabbit) |
| Inhalation | : LC50 > 2500 mg/m3 | (Rat)    |

##### OCCUPATIONAL EXPOSURE LIMIT:

Manufacturer recommends:  
100 ppm based on composition.

Local regulated limits may vary.

---

## 5. FIRST AID MEASURES

### INHALATION:

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

### EYE CONTACT:

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

### SKIN CONTACT:

Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention.

### INGESTION:

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

### PERSONAL PROTECTION:

The selection of personal protective equipment varies, depending upon conditions of use.  
In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves.  
Where only incidental contact is likely, wear safety goggles, long sleeves, and chemical-resistant gloves.  
Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

### ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces.

### HANDLING, STORAGE AND SHIPPING:

Keep containers closed. Handle and open containers with care.  
Store in a cool, well ventilated place away from incompatible materials.  
In keeping with good personal hygiene practices, wash hands thoroughly after handling the material.  
Do not handle or store near an open flame, sources of heat, or sources of ignition.  
Material will accumulate static charges which may cause a spark. Static charge build-up could become an ignition source. Use proper relaxation and grounding procedures.  
Empty containers may contain product residue. Do not pressurize cut, heat, or weld empty containers. Do not reuse empty containers

without commercial cleaning or reconditioning.

#### LAND SPILL:

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

#### WATER SPILL:

Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

## 7. FIRE AND EXPLOSION HAZARD

Flashpoint and method: >52 deg C PMCT ASTM D93

Autoignition: NA Flammable Limits: LEL: 0.7% UEL: 6.5%

#### GENERAL HAZARDS:

Combustible Liquid; may form combustible mixtures at or above the flash point.

Toxic gases will form upon combustion.

Static Discharge; material may accumulate static charges which may cause a fire.

#### FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire.

Use foam, dry chemical or water spray to extinguish fire.

Respiratory and eye protection required for fire fighting personnel.

Avoid spraying water directly into storage containers due to danger of boilover.

A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA may not be required.

#### HAZARDOUS COMBUSTION PRODUCTS:

Smoke, carbon monoxide, carbon dioxide, oxides of sulphur.

In addition, small amounts of nitrogen oxides will be formed.

---

## 8. REACTIVITY DATA

#### STABILITY:

This product is stable. Hazardous polymerization will not occur.

## INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents. Use product with caution around heat, sparks, pilot lights, static electricity and open flames.

## HAZARDOUS DECOMPOSITION:

none

---

9. NOTES

All components of this product are listed on the U.S. TSCA inventory.

NAME CHANGE.

---

10. PREPARATION

Date Prepared: October 18, 2000  
Prepared by: Lubricants & Specialties  
IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."

**IMPERIAL OIL  
MATERIAL SAFETY DATA SHEET**

**UNLEADED GASOLINE**

Date Prepared: January 12, 2001  
Supersedes: April 08, 2000  
MSDS Number: 08522

---

**1. PRODUCT INFORMATION**

Product Identifier: UNLEADED GASOLINE  
REGULAR UNLEADED  
MIDGRADE UNLEADED  
ESSO SUPER PREMIUM UNLEADED  
PREMIUM UNLEADED  
ESSO REGULAR UNLEADED  
ESSO MIDGRADE UNLEADED  
ESSO EXTRA MIDGRADE UNLEADED  
ESSO PREMIUM UNLEADED  
EXXON MIDGRADE UNLEADED  
EXXON PREMIUM UNLEADED  
INDOLINE GASOLINE  
EXXON REGULAR UNLEADED  
PREMIUM GASOLINE  
ESSO EXTRA MIDGRADE GASOLINE  
MIDGRADE GASOLINE  
GASOLINE REGULAR UNLEADED  
GASOLINE MIDGRADE UNLEADED MUL89 (DYED OR CLEAR)  
GASOLINE REGULAR UNLEADED RUL87 (DYED OR CLEAR)  
GASOLINE PREMIUM UNLEADED PUL91 (DYED OR CLEAR)  
GASOLINE PREMIUM UNLEADED PUL92 (DYED OR CLEAR)  
GASOLINE PREMIUM UNLEADED SUL94  
SUPERSUPREME 94 PREMIUM UNLEADED GASOLINE-MTBE  
GASOLINE MIDGRADE UNLEADED MUL89 <P91/R87>  
GASOLINE MIDGRADE UNLEADED MUL89 DCA <P92/R87>

Application and Use:  
Motor gasoline fuel, for use in internal combustion engines only

Product Description:  
A mixture of aliphatic and aromatic hydrocarbons and additives.

---

**REGULATORY CLASSIFICATION**

WHMIS:  
Class D, Division 2, Subdivision A: Very Toxic Material.  
Class B, Division 2: Flammable Liquids.

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT  
All components of this product are either on the Domestic Substances List (DSL), exempt, or have been notified under Section 26 of CEPA.

**TDG INFORMATION (RAIL/ROAD):**

Shipping Name: Gasoline  
Class: 3  
Packing Group: II  
PIN Number: UN1203

Please be aware that other regulations may apply.



## TELEPHONE NUMBERS

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3183

## MANUFACTURER/SUPPLIER:

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

## 2. REGULATED COMPONENTS

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

| NAME                 | %        | CAS #  |
|----------------------|----------|--|
| Gasoline             | >99 V/V  | 8006-61-9  |
|                      |          | LD50>18ml/kg, orl, rat<br>LD50> 5ml/kg, skn, rbt                           |
| Methyl T-Butyl Ether | 0-15 V/V | 1634-04-4  |
|                      |          | LD50:3.9g/Kg, ing, rat<br>LD50:>10g/Kg, skn, rbt<br>LC50:142Mg/L, inh, rat |

## 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
Specific gravity: not available  
Viscosity: 0.80 cSt at 20 deg C  
Vapour Density: 3.2  
Boiling Point: 25 to 210 deg C  
Evaporation rate: >10 (1= n-butylacetate)  
Solubility in water: negligible  
Freezing/Pour Point: -60 deg C less than  
Odour Threshold: not available  
Vapour Pressure: 76 kPa to 103 kPa at 38 deg C  
Density: 0.73 g/cc at 15 deg C  
Appearance/odour: Naturally occurring water white or pale yellow;  
may be dyed a variety of colours for tax or other  
purposes; petroleum odour.

## 4. HEALTH HAZARD INFORMATION

## NATURE OF HAZARD

## INHALATION:

High vapour concentrations are irritating to the eyes, nose, throat and lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.  
Avoid breathing vapours or mists.

## EYE CONTACT:

Slightly irritating, but will not injure eye tissue.

## SKIN CONTACT:

Low toxicity.  
Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

## INGESTION:

**Low toxicity.**

Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

**CHRONIC:**

The International Agency for Research on Cancer (IARC) has evaluated gasoline and found it to be a possible human carcinogen.

Contains benzene. Human health studies (epidemiology) indicate that prolonged and/or repeated overexposures to benzene may cause damage to the blood producing system and serious blood disorders, including leukemia.

Animal tests suggest that prolonged and/or repeated overexposures to benzene may damage the embryo/fetus. The relationship of these animal studies to humans has not been fully established.

Contains n-hexane. Prolonged and/or repeated exposures may cause damage to the peripheral nervous system (e.g. fingers, feet, arms etc.). Methyl Tertiary Butyl Ether (MTBE) was tested for carcinogenicity, neurotoxicity, chronic, reproductive and developmental toxicity. The NOEL for all endpoints evaluated in three animal species was 400 ppm or greater. An increase in kidney tumors/damage and liver tumors was observed in animals exposed to high concentrations of MTBE. Some embryo/fetal toxicity and birth defects were observed in the offspring of pregnant mice exposed to maternally toxic doses of MTBE, however the offspring of exposed pregnant rabbits were unaffected. The significance of the animal findings at high exposures are not believed to be directly related to potential human health hazards in the workplace.

**ACUTE TOXICITY DATA:**

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

Oral : LD50 > 18 ml/kg (Rat)  
Dermal : LD50 > 5 ml/kg (Rabbit)

**OCCUPATIONAL EXPOSURE LIMIT:**

Manufacturer recommends:

For Benzene (skin) 1 ppm TWA for 8 hour workday.

For gasoline, 300 mg/m3.

For Methyl-tert-Butyl Ether, 25 ppm (90 mg/m3) 8-hour TWA and 75 ppm (270 mg/m3) 15-minute STEL.

ACGIH recommends:

For Gasoline, ACGIH recommends a TWA of 300 ppm (890 mg/m3) and categorizes it as an animal carcinogen.

For n-Hexane (skin), 50 ppm (176 mg/m3).

For Benzene, ACGIH recommends a TWA of 0.5 ppm (1.6 mg/m3), (skin), and categorizes it as a confirmed human carcinogen.

For Methyl-tert-Butyl Ether, ACGIH recommends a TLV of 40 ppm (144 mg/m3) and categorizes it as an animal carcinogen.

Local regulated limits may vary.

---

**5. FIRST AID MEASURES****INHALATION:**

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

**EYE CONTACT:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:**

Flush with large amounts of water. Use soap if available. Remove severely contaminated clothing (including shoes) and launder before reuse. If irritation persists, seek medical attention.

**INGESTION:**

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

**PERSONAL PROTECTION:**

The selection of personal protective equipment varies, depending upon conditions of use. In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves. Where only incidental contact is likely, wear safety glasses with side shields. No other special precautions are necessary provided skin/eye contact is avoided. Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

**ENGINEERING CONTROLS:**

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

**HANDLING, STORAGE AND SHIPPING:**

Keep containers closed. Handle and open containers with care. In keeping with good personal hygiene practices, wash hands thoroughly after handling the material.

Store and load at normal (up to 38 deg C) temperature and at atmospheric pressure. Material will accumulate static charges which may cause a spark. Static charge build-up could become an ignition source. Use proper relaxation and grounding procedures. For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere. Empty containers may contain product residue. Do not pressurize cut, heat, or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.

**LAND SPILL:**

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Vapours or dust may be harmful or fatal. Warn occupants of downwind areas. Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust. Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent. Consult an expert on disposal of recovered material. Ensure disposal in

compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

#### WATER SPILL:

Eliminate all sources of ignition. Vapours or dust may be harmful or fatal. Warn occupants and shipping in downwind areas. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

## 7. FIRE AND EXPLOSION HAZARD

Flashpoint and method: -40 deg C COC D92 less than/moins de

Autoignition: NA Flammable Limits: LEL: 1.4% UEL: 7.6%

#### GENERAL HAZARDS:

Extremely flammable; material will readily ignite at normal temperatures. Flammable Liquid; may release vapours that form flammable mixtures at or above the flash point. Toxic gases will form upon combustion. Static Discharge; material may accumulate static charges which may cause a fire.

#### FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire if possible to do so without hazard. If a leak or spill has not ignited use water spray to disperse the vapours. Either allow fire to burn out under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Respiratory and eye protection required for fire fighting personnel. Avoid spraying water directly into storage containers due to danger of boilover. A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA may not be required.

#### HAZARDOUS COMBUSTION PRODUCTS:

Smoke, carbon monoxide, carbon dioxide under thermal decomposition.

---

## 8. REACTIVITY DATA

#### STABILITY:

This product is stable. Hazardous polymerization will not occur.

#### INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents

#### HAZARDOUS DECOMPOSITION:

none

## 9. NOTES

All components of this product are listed on the U.S. TSCA inventory.

OCCUPATIONAL EXPOSURE LIMIT CHANGE.

### REVISION SUMMARY:

Since 8 April 2000, this MSDS has been revised in Section(s):

4

---

## 10. PREPARATION

Date Prepared: January 12, 2001  
Prepared by: Lubricants & Specialties  
IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."

**IMPERIAL OIL  
MATERIAL SAFETY DATA SHEET****AVIATION GASOLINE 100LL**

Date Prepared: April 21, 1999  
Supersedes: May 22, 1998  
MSDS Number: 03834

---

**1. PRODUCT INFORMATION**

Product Identifier: AVIATION GASOLINE 100LL  
ESSO AVIATION GASOLINE 100LL

Application and Use:  
Aviation fuel.

Product Description:

A mixture of aliphatic and aromatic hydrocarbons and additives.

---

**REGULATORY CLASSIFICATION**

WHMIS:

Class B, Division 2: Flammable Liquids.

Class D, Division 2, Subdivision B: Toxic Material

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT

All components of this product are either on the Domestic Substances List (DSL) or are exempt.

TDG INFORMATION (RAIL/ROAD):

Shipping Name: Gasoline

Class: 3

Packing Group: II

PIN Number: UN1203

Please be aware that other regulations may apply.

---

**TELEPHONE NUMBERS**

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3183

**MANUFACTURER/SUPPLIER:**

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

---

**2. REGULATED COMPONENTS**

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

| NAME                                | %          | CAS #       |
|-------------------------------------|------------|-------------|
| Naphtha (petroleum), light alkylate | 70-100 V/V | 64741-66-8. |

Toluene

0-30 V/V

108-88-3 LD50:&gt;2g/kg, skn, rbt

LC50:8000ppm rat

---

### 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
Specific gravity: not available  
Viscosity: 0.60 cSt at 20 deg C  
Vapour Density: 4  
Boiling Point: 70 to 170 deg C  
Evaporation rate: >1 (1= n-butylacetate)  
Solubility in water: negligible  
Freezing/Pour Point: -58 deg C  
Odour Threshold: not available  
Vapour Pressure: 38 kPa to 48 kPa at 38 deg C  
Density: 0.71 g/cc at 15 deg C  
Appearance/odour: Clear blue liquid, pungent petroleum odour.

---

### 4. HEALTH HAZARD INFORMATION

#### NATURE OF HAZARD

##### INHALATION:

High vapour concentrations are irritating to the eyes, nose, throat and lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.  
Avoid breathing vapours or mists.

##### EYE CONTACT:

Slightly irritating, but will not injure eye tissue.

##### SKIN CONTACT:

Low toxicity.  
Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

##### INGESTION:

Low toxicity.  
Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

##### CHRONIC:

Contains n-hexane. Prolonged and/or repeated exposures may cause damage to the peripheral nervous system (e.g. fingers, feet, arms etc.).

##### ACUTE TOXICITY DATA:

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

Oral : LD50 > 18 ml/kg (Rat)  
Dermal : LD50 > 5 ml/kg (Rabbit)

##### OCCUPATIONAL EXPOSURE LIMIT:

Manufacturer recommends:  
For gasoline, 300 mg/m3.

ACGIH recommends:  
For n-Hexane (skin), 50 ppm (176 mg/m3).

For Toluene (skin), 50 ppm (188 mg/m<sup>3</sup>).

Local regulated limits may vary.

---

## 5. FIRST AID MEASURES

### INHALATION:

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

### EYE CONTACT:

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

### SKIN CONTACT:

Flush with large amounts of water. Use soap if available. Remove severely contaminated clothing (including shoes) and launder before reuse. If irritation persists, seek medical attention.

### INGESTION:

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

### PERSONAL PROTECTION:

The selection of personal protective equipment varies, depending upon conditions of use. In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves. Where only incidental contact is likely, wear safety glasses with side shields. No other special precautions are necessary provided skin/eye contact is avoided. Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

### ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

### HANDLING, STORAGE AND SHIPPING:

Store in a cool, well ventilated place away from incompatible materials. In keeping with good personal hygiene practices, wash hands thoroughly after handling the material. Material will accumulate static charges which may cause a spark. Static charge build-up could become an ignition source. Use proper relaxation and grounding procedures. Store and load at normal (up to 38 deg C) temperature and at atmospheric pressure. For personnel entry into confined spaces (i.e. bulk storage tanks) a proper



confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.

#### LAND SPILL:

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard.

Vapours or dust may be harmful or fatal. Warn occupants of downwind areas.

Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

#### WATER SPILL:

Eliminate all sources of ignition. Vapours or dust may be harmful or fatal. Warn occupants and shipping in downwind areas.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

## 7. FIRE AND EXPLOSION HAZARD

Flashpoint and method: -42 deg C TCC ASTM D56

Autoignition: 439 deg C Flammable Limits: LEL: 1.4% UEL: 7.6%

#### GENERAL HAZARDS:

Extremely flammable; material will readily ignite at normal temperatures. Flammable Liquid; may release vapours that form flammable mixtures at or above the flash point.

Decomposes; flammable/toxic gases will form at elevated temperatures (thermal decomposition).

Toxic gases will form upon combustion.

Static Discharge; material may accumulate static charges which may cause a fire.

#### FIRE FIGHTING:

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire if possible to do so without hazard. If a leak or spill has not ignited use water spray to disperse the vapours.

Either allow fire to burn out under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam.

Respiratory and eye protection required for fire fighting personnel.

Avoid spraying water directly into storage containers due to danger of boilover.

A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA may not be required.

#### HAZARDOUS COMBUSTION PRODUCTS:

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other

decomposition products, in the case of incomplete combustion.

---

## 8. REACTIVITY DATA

### STABILITY:

This product is stable. Hazardous polymerization will not occur.

### INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents. Use product with caution around heat, sparks, pilot lights, static electricity and open flames.

### HAZARDOUS DECOMPOSITION:

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

---

## 9. NOTES

All components of this product are listed on the U.S. TSCA inventory.

This MSDS has been revised in Section 4.  
Occupational Exposure Limit change.

---

## 10. PREPARATION

Date Prepared: April 21, 1999  
Prepared by: Lubricants & Specialties  
IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."

**IMPERIAL OIL  
MATERIAL SAFETY DATA SHEET****TURBINE FUEL TYPE AVIATION, WIDE CUT**

Date Prepared: June 15, 2000  
Supersedes: April 21, 1999  
MSDS Number: 08524

---

**1. PRODUCT INFORMATION**

Product Identifier: TURBINE FUEL AVIATION, WIDE CUT TYPE  
ESSO TURBO FUEL B  
ESSO JET B  
JET B  
TURBO FUEL B  
TURBO FUEL B F40  
TURBO FUEL B JP4  
ESSO TURBO FUEL B <FSII>  
JET B <FSII>  
AVIATION TURBINE FUEL <JP4>  
CAN/CGSB-3.22 GRADE F40  
ESSO JET B <FSII>

Application and Use:  
Aviation turbine fuel

Product Description:

A mixture of aliphatic and aromatic hydrocarbons and additives.

---

**REGULATORY CLASSIFICATION****WHMIS:**

Class B, Division 2: Flammable Liquids.  
Class D, Division 2, Subdivision A: Very Toxic Material.  
Class D, Division 2, Subdivision B: Toxic Material

**CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT**

All components of this product are either on the Domestic  
Substances List (DSL) or are exempt.

**TDG INFORMATION (RAIL/ROAD):**

Shipping Name: FUEL, AVIATION, TURBINE ENGINES  
Class: 3  
Packing Group: II  
PIN Number: UN1863

Please be aware that other regulations may apply.

---

**TELEPHONE NUMBERS**

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3183

**MANUFACTURER/SUPPLIER:**

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

## 2. REGULATED COMPONENTS

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

| NAME                               | %          | CAS #   |
|------------------------------------|------------|---|
| Kerosene, straight run             | 40-70 V/V  | 8008-20-6 LD50:>5g/kg,oral, rat                         |
| Naphtha, full range                | 30-60 V/V  | 64741-42-0  |
| Ethylene Glycol Monomethyl Ether   | 0-0.15 V/V | 109-86-4 LD50:2.4g/kg,orl, rat<br>LD50:0.8g/kg,orl, rab |
| Diethylene glycol monomethyl ether | 0-0.15 V/V | 111-77-3 LD50:9.2g/kg,orl, rat<br>LD50:6.6g/kg,skn.rbt  |

## 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
Specific gravity: not available  
Viscosity: 0.60 cSt at 40 deg C  
Vapour Density: 4  
Boiling Point: 40 to 270 deg C  
Evaporation rate: <1 (1= n-butylacetate)  
Solubility in water: negligible  
Freezing/Pour Point: -58 deg C ASTM D 2386  
Odour Threshold: not available  
Vapour Pressure: 21 kPa at 38 deg C  
Density: 0.78 g/cc at 15 deg C  
Appearance/odour: White or pale yellow liquid, petroleum odour

## 4. HEALTH HAZARD INFORMATION

### NATURE OF HAZARD

#### INHALATION:

Negligible hazard at normal temperatures (up to 38 deg C).  
High vapour concentrations are irritating to the eyes, nose, throat and lungs; may cause headaches and dizziness; may be anesthetic and may cause other central nervous system effects.  
Avoid breathing vapours or mists.

#### EYE CONTACT:

Slightly irritating, but will not injure eye tissue.

#### SKIN CONTACT:

Irritating.  
Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).  
Low toxicity.

#### INGESTION:

Low toxicity.  
Small amounts of this liquid drawn into the lungs from swallowing or vomiting may cause severe health effects (e.g. bronchopneumonia or pulmonary edema).

#### CHRONIC:

May contain ethylene glycol monomethyl ether (EGME). Prolonged and/or repeated exposure through inhalation or extensive skin contact with EGME may result in toxic effects on the blood, the blood producing system, the kidneys, the male reproductive system and the embryo/fetus. Contains benzene. Human health studies (epidemiology) indicate that prolonged and/or repeated overexposures to benzene may cause damage to the blood producing system and serious blood disorders, including leukemia.

Animal tests suggest that prolonged and/or repeated overexposures to benzene may damage the embryo/fetus. The relationship of these animal studies to humans has not been fully established.

Contains n-hexane. Prolonged and/or repeated exposures may cause damage to the peripheral nervous system (e.g. fingers, feet, arms etc.).

Contains diethylene glycol monomethyl ether (DIEGME). Prolonged and repeated exposure through inhalation or extensive skin contact with DIEGME may result in toxic effects on the kidneys, the reproductive system and/or the embryo/fetus.

#### ACUTE TOXICITY DATA:

Based on animal testing data from similar materials and products, the acute toxicity of this product is expected to be:

Oral : LD50 > 5000 mg/kg (Rat)  
Dermal : LD50 > 2000 mg/kg (Rabbit)  
Inhalation : LC50 > 2500 mg/m3 (Rat)

#### OCCUPATIONAL EXPOSURE LIMIT:

Manufacturer recommends:

100 ppm based on composition.

For Benzene (skin) 1 ppm TWA for 8 hour workday.

ACGIH recommends:

For n-Hexane (skin), 50 ppm (176 mg/m3).

For Benzene, ACGIH recommends a TWA of 0.5 ppm (1.6 mg/m3), (skin), and categorizes it as a confirmed human carcinogen.

For 2-Methoxyethanol, (skin) 5 ppm (16 mg/m3).

Local regulated limits may vary.

---

## 5. FIRST AID MEASURES

#### INHALATION:

In emergency situations use proper respiratory protection to immediately remove the affected victim from exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

#### EYE CONTACT:

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

#### SKIN CONTACT:

Immediately flush with large amounts of water. Use soap if available. Remove contaminated clothing, including shoes, after flushing has begun. If irritation persists, seek medical attention.

#### INGESTION:

DO NOT induce vomiting since it is important that no amount of the material should enter the lungs (aspiration). Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

### PERSONAL PROTECTION:

The selection of personal protective equipment varies, depending upon conditions of use.

In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves.

Where only incidental contact is likely, wear safety goggles, long sleeves, and chemical-resistant gloves.

Where concentrations in air may exceed the occupational exposure limits given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

### ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

### HANDLING, STORAGE AND SHIPPING:

Keep containers closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. In keeping with good personal hygiene practices, wash hands thoroughly after handling the material.

Store and load at normal (up to 38 deg C) temperature and at atmospheric pressure.

Material will accumulate static charges which may cause a spark. Static charge build-up could become an ignition source. Use proper relaxation and grounding procedures.

Empty containers may contain product residue. Do not pressurize cut, heat, or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.

### LAND SPILL:

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Vapours or dust may be harmful or fatal. Warn occupants of downwind areas.

Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Do not use combustible materials such as sawdust.

Recover by pumping (use an explosion proof motor or hand pump), or by using a suitable absorbent.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

### WATER SPILL:

Eliminate all sources of ignition. Vapours or dust may be harmful or fatal. Warn occupants and shipping in downwind areas.

Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

## 7. FIRE AND EXPLOSION HAZARD

Flashpoint and method: -18 deg C COC ASTM D92

Autoignition: NA    Flammable Limits: LEL: 0.6%    UEL: 8.0%

**GENERAL HAZARDS:**

Extremely flammable; material will readily ignite at normal temperatures.  
Flammable Liquid; may release vapours that form flammable mixtures at or above the flash point.  
Decomposes; flammable/toxic gases will form at elevated temperatures (thermal decomposition).  
Toxic gases will form upon combustion.  
Static Discharge; material may accumulate static charges which may cause a fire.

**FIRE FIGHTING:**

Use water spray to cool fire exposed surfaces and to protect personnel. Shut off fuel to fire if possible to do so without hazard. If a leak or spill has not ignited use water spray to disperse the vapours. Either allow fire to burn out under controlled conditions or extinguish with foam or dry chemical. Try to cover liquid spills with foam. Respiratory and eye protection required for fire fighting personnel. Avoid spraying water directly into storage containers due to danger of boilover. A self-contained breathing apparatus (SCBA) should be used for all indoor fires and any significant outdoor fires. For small outdoor fires, which may easily be extinguished with a portable fire extinguisher, use of an SCBA may not be required.

**HAZARDOUS COMBUSTION PRODUCTS:**

Smoke, carbon monoxide, carbon dioxide and traces of oxides of sulphur  
In addition, small amounts of nitrogen oxides will be formed.

---

**8. REACTIVITY DATA**

**STABILITY:**

This product is stable.    Hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:**

Strong oxidizing agents. Use product with caution around heat, sparks, pilot lights, static electricity and open flames.

**HAZARDOUS DECOMPOSITION:**

See: Hazardous Combustion Products

---

**9. NOTES**

All components of this product are listed on the U.S. TSCA inventory.

Boiling point change.

**REVISION SUMMARY:**

Since 21 April 1999, this MSDS has been revised in Section(s):  
2, 3

---

**10. PREPARATION**

Date Prepared: June 15, 2000  
Prepared by: Lubricants & Specialties

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."