

Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

Section 1. Chemical Product and Company Identification				
Product Name BARIMOL HEAVY GREASE		Code	650-119, BARH	
		DSL	See Section 15	
Synonym	Not available.	TSCA	See Section 15	
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult	
Material Uses	This product is a multi-purpose, barium soap based grease with a wide range of automotive and industrial lubricant applications.		local telephone directory for emergency number(s).	

Section 2. Composition and Information on Ingredients					
			E	xposure Limits (ACG	IH)
Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Mixture of severely hydrotreated and hydrocracked and/or solvent-refined base oil (petroleum) and other proprietary, non-hazardous additives.	Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established

Section 3. Hazards Identification.		
Potential Health Effects	Non irritating to slight transient irritation to skin and eyes, but no permanent damage. Relatively non-toxic via ingestion. This product has a low vapour pressure and is not expected to present an inhalation exposure at ambient conditions. Upon heating to high temperatures, or mechanical actions which may produce vapours or mists, inhalation of product may cause irritation of the breathing passages. For more information, refer to Section 11.	

Section 4. First Aid Measures		
Eye Contact	IMMEDIATELY flush eyes with running water for at lest 15 minutes, keeping eyelids open. Seek medical attention.	
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. High pressure grease gun is capable of injecting grease through the skin. Grease gun injuries require immediate physician assessment. Seek medical attention.	
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.	
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.	
Note to Physician	Not available	

Section 5. Fire-fighting Measures			
Flammability	May be combustible at high temperature.	Flammable Limits	Not available.
Flash Points	Mineral Oil Blend: OPEN CUP: 230°C (446°F) (Cleveland)	Auto-Ignition Temperature	Not available.
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion Carbon oxides (CO, CO2), sulphur oxides (SOx), smoke and irritating vapours as products of incomplete combustion.			
Fire Fighting Media and Instructions	NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. DO NOT extinguish a leaking gas flame unless leak can be stopped. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.		

Section 6. Accidental Release Measures

Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section 7. Handling and Storage		
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.	
Storage	Store in dry, cool, well-ventilated area. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).	

Section 8. Exposure Controls/Personal Protection			
Engineering Controls	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.		
Eyes	The selection of personal protective equipment varies, depending upon conditions of use. Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered. Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.		
	Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.		
	Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated. Wear appropriate footwear to prevent product from coming in contact with feet and skin.		
Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits. This product is not expected to form a mist		

Section 9. Phy	sical and Chemical Properties		
Physical State and Appearance	Paste of long fibred texture.	Viscosity	Mineral Oil Blend: 101.36 cSt @ 40°C (104°F), 10.71 cSt @ 100°C (212°F), VI=89
Colour	Dark grey.	Pour Point	Mineral Oil Blend: -18°C (0°F)
Odour	Mild grease like.	Softening Point	Not available.
Odour Threshold	Not available.	Dropping Point	239°C (462°F)
Boiling Point	Not available.	Penetration	299 (60 strokes)
Specific Gravity	Mineral Oil Blend: 0.8896 kg/L @ 15°C (59°F)	Oil / Water Dist. Coeff.	Not available
Vapor Density	Not available.	Ionicity (in water)	Not available
Vapor Pressure	Negligible at ambient temperature and pressure.	Dispersion Propertie	es Not available
Volatility	Non to semivolatile.	Solubility	Insoluble in water.

Section 10. Stability and Reactivity			
Corrosivity	Not corrosive to copper.		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances Reactive with oxidizing agents, acids, alkalis, / Conditions to Avoid metals and peroxides.		Decomposition Products	May release COx, NOx, SOx, diphenylamine, alkenes, smoke and irritating vapours when heated to decomposition.

BARIMOL HEAVY GREASE	BARIMOL	HEAVY GREASE	
----------------------	---------	--------------	--

Section 11. Toxicological Information		
Routes of Entry	Skin contact, eye contact, inhalation, ingestion.	
Acute Lethality	Based on toxicity of components. Acute oral toxicity (LD50): >5000 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >2500 mg/m³/4h (rat).	
Chronic or Other Toxic Effects Dermal Route:	Prolonged or repeated contact may cause skin irritation characterized by dermatitis or oil acne.	
Inhalation Route:	Negligible breathing hazard at normal temperatures (up to 38°C) or recommended blending temperatures. Elevated temperatures or mechanical action may form vapours, mists or fumes. Inhalation of oil mists or vapours from hot oil may cause irritation of the upper respiratory tract.	
Oral Route:	Low toxicity; has laxative effect.	
Eye Irritation/Inflammation:	Repeated or prolonged contact may cause transient irritation, but no permanent damage.	
Immunotoxicity:	Not available.	
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.	
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.	
Mutagenic:	Based on actual test results of base oils and results of similar products, severely hydrotreated base oils give negative results when tested for: (a) Salmonella Typhimurium TA98 using the Modified Ames Assay for Petroleum Product; (b) Salmonella-Escherichia coli/Mammalian-Microsome Reverse Mutation Assay (Ames test) with a Confirmatory Assay; (c) Structural Chromosomal Aberrations in Chinese Hamster Ovary (CHO) Cells.	
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.	
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.	
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as A1 or A2 carcinogens by ACGIH.	
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.	
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.	
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.	
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.	
Other Considerations	No additional remark.	

Page Number: 3

Section 12. Ecological Information					
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available		
BOD5 and COD	Not available.	Products of Biodegradation	Not available.		
Additional Remarks	No additional remark.				

Section 13. Disposal Considerations Waste Disposal Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.

Section 14. Transport Information				
TDG Classification	Not controlled under TDG (Canada).	Special Provisions for Transport	Not applicable.	

BARIMOL HEAVY GREASE

Section 15. Regulatory Information

Other Regulations

This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

All components of this product are on the European Inventory of Existing Commercial Chemical Substances.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (Europe)

Not classified under the Dangerous Substances or Dangerous Preparations Directives.

DSD/DPD (Europe) (Pictograms)



DOT (U.S.A) (Pictograms)



HMIS (U.S.A.)

	(1)
Health Hazard	
Fire Hazard	(1)
Reactivity	0
Personal Protection	(B)

NFPA (U.S.A.)

IRIS - Integrated Risk Information System

NFPA - National Fire Prevention Association

NPRI - National Pollutant Release Inventory

NTP - National Toxicology Program

PEL - Permissible Exposure Limit

TLm - Median Tolerance Limit

TSCA - Toxic Substances Control Act

USP - United States Pharmacopoeia

Data entry by Product Safety - JDW.

SD - Single Dose

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration NAERG'96 - North American Emergency Response Guide Book (1996)

NIOSH - National Institute for Occupational Safety & Health

NSNR - New Substances Notification Regulations (Canada)

SARA - Superfund Amendments and Reorganization Act

TLV-TWA - Threshold Limit Value-Time Weighted Average

USEPA - United States Environmental Protection Agency

WHMIS - Workplace Hazardous Material Information System

OSHA - Occupational Safety & Health Administration

RCRA - Resource Conservation and Recovery Act

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration



Page Number: 4

Section 16. Other Information

References

Available upon request

Marque de commerce de Petro-Canada - Trademark

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials (BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation and Liability

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply List

COD5 - Chemical Oxygen Demand in 5 days **CPR - Controlled Products Regulations**

DOT - Department of Transport DSCL - Dangerous Substances Classification and Labeling (Europe)

DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)

DSL - Domestic Substance List

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazardous Communication System HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

Information Contact Internet: www.petro-canada.ca

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Ouebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 5/2/2003.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.