

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled	₩	

Section 1. Cl	Section 1. Chemical Product and Company Identification				
Product Name	DEXRON® III/MERCON® AUTOMATIC TRANSMISSION FLUID	<b>Code</b> 460-601, DEXRON			
Synonym	Not available	Validated on 11/22/2005.			
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency 403-296-3000 Canutec Transportation: 613-996-6666			
Material Uses	Automatic transmission fluid for most North American automobiles and for off-highway torque converters requiring C-4 type transmission fluid. It is also suitable as a hydraulic fluid and as a top-up in power steering systems. Not to be used in conditions where aerosols could be generated.	directory for emergency number(s).			

Section 2. Com	position and Information o	n Ingredient	S			
				Expo	osure Limits (ACGIH)	
	Name	CAS#	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and other proprietary, non-hazardous additives.		Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established
Manufacturer Recommendation	Not applicable	•	•			
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Haza	rds Identification.
Potential Health Effects	Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.

Section 4. First	Aid Measures
Eye Contact	No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the chemical is removed. If irritation persists, obtain medical advice.
Skin Contact	Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with water and non-abrasive soap for 5 minutes or until chemical is removed. Remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). If irritation persists, repeat flushing. Obtain medical advice immediately. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, rinse mouth and repeat administration of water. Obtain medical attention.
Note to Physician	Not available

Section 5. Fire-fighting Measures				
Flammability	May be combustible at high temperature.	Flammable Lim	Flammable Limits Not available	
Flash Points	OPEN CUP: ≥180°C (356°F) (Cleveland)	Auto-Ignition Temperature	Fire Point: 205°C (401°F)	
Continued on Next	Page Internet: www.petro-car	nada.ca/msds		Available in French

DEXRON® III/MERCO	N® AUTOMATIC TRANSMISSION FLUID		Page Number: 2
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (combustion.	(NOx), smoke and	irritating vapours as products of incomplete
Fire Fighting Media and Instructions	NAERG96, GUIDE 171, Substances (low to rire, ISOLATE for 800 meters (0.5 mile) in all mile) in all directions. Shut off fuel to fire if it is from area and let fire burn out under controlled venting safety device or any discolouration of to prevent pressure build-up, autoignition or e or CO2. LARGE FIRE: use water spray, fogue used, and self contained breathing appar significant outdoor fires, SCBA is required.	I directions; also, cos s possible to do so vod d conditions. Withdank due to fire. Coo xplosion. SMALL F or foam. For small atus (SCBA) may r	onsider initial evacuation for 800 meters (0.5 without hazard. If this is impossible, withdraw fraw immediately in case of rising sound from ol containing vessels with water spray in order TRE: use DRY chemicals, foam, water spray outdoor fires, portable fire extinguishers may not be required. For all indoor fires and any

## Section 6. Accidental Release Measures

# **Material Release** or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section 7.	Handling and Storage
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid eye contact. Avoid skin contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area.

## Section 8. Exposure Controls/Personal Protection

# Engineering **Controls**

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes As a minimum, safety glasses with side shields should be worn when handling this material.

Body If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory A minimum of NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume of mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSH-approved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): Neoprene, Nitrile, Polyvinyl alcohol (PVA), Fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

**Feet** Wear appropriate footwear to prevent product from coming in contact with feet and skin.

DEXRON® III/MERCON® AUTOMATIC TRANSMISSION FLUID	Page Number: 3
--	----------------

Section 9. Phys	Section 9. Physical and Chemical Properties			
Physical State and Appearance	Viscous liquid.	Viscosity	34.26 cSt @ 40°C (104°F), 7.7 cSt @ 100°C (212°F), VI=210.	
Colour	Dark red.	Pour Point	-51°C (-59.8°F).	
Odour	Mild petroleum oil like.	Softening Point	Not applicable.	
Odour Threshold	Not available	<b>Dropping Point</b>	Not applicable.	
Boiling Point	Not available	Penetration	Not applicable.	
Density	0.855 kg/L @ 15°C(59°F) 7.14 lbs/US gal @ 15°C(59°F)	Oil / Water Dist. Coefficient	Not available	
Vapour Density	Not available	Ionicity (in water)	Not available	
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available	
Volatility	Non-volatile	Solubility	Insoluble in water.	

Section 10. St	ability and Reactivity		
Corrosivity	Copper corrosion, 3h, 149°C (ASTM D013	0): 1b.	
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avo	Reactive with oxidizing agents, reducing agents and acids.  pid	Decomposition Products	May release COx, NOx, metallic oxides, smoke and irritating vapours when heated to decomposition.

Routes of Entry	Skin contact, eye contact, inhalation, and ingestion.
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore, data for the base oils are provided below:  Acute oral toxicity (LD50): >5000 mg/kg (rat).  Acute dermal toxicity (LD50): >2000 mg/kg (rabbit).  Acute inhalation toxicity (LC50): >2500 mg/m³/4h (rat).
Chronic or Other Toxic Effect	is s
Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposure is expected to cause only slight irritation, if any.
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation.
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (ar accumulation of fluid in the lungs). May produce a laxative effect.
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization	:Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components this product is not expected to be a mutagen.
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.

Internet: www.petro-canada.ca/msds

Available in French

Continued on Next Page

DEXRON® III/MERCON® AUTOMATIC TRANSMISSION FLUID		Page Number: 4
Carcinogenicity (NTP):	This product is not known to contain any chemicals at repo carcinogens by NTP.	rtable quantities that are listed as
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at repo carcinogens by IRIS.	rtable quantities that are listed as
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at repo carcinogens by OSHA.	rtable quantities that are listed as
Other Considerations	No additional remark.	

Section 12. Ecological Information				
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available	
BOD5 and COD	Not available	Products of Biodegradation	Not available	
Additional Remarks No additional remark.				

Section 13. Disposal Considerations		
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.	

Section 14. Transport Information			
TDG Classification	Not a hazardous material for transport according to the TDG Regulations. (Canada)		Not applicable.

Section 15. Reg	Section 15. Regulatory Information			
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).			
	All components of this formulation are listed on the US EPA-TSCA Inventory.			
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).			
	German Water Hazard Classification (Verwaltungsvorschrift wassergefährdende Stoffe - VwVwS) WGK=2			
	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.			
	Please contact Product Safety for more inf	ormation.		
DSD/DPD (Europe)	Not classified under the Dangerous Substances or Dangerous Preparations Directives.	HCS (U.S.A.)	Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States)	
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT	DOT (U.S.A) (Pictograms)	Not evaluated for transport	
,	NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	, ,	Non évalué pour le transport	
HMIS (U.S.A.)	Health Hazard  Fire Hazard  Reactivity  Personal Protection  NFPA (U	Health 1 0 R	Rating 0 Insignificant eactivity 1 Slight ecific hazard 3 High Extreme	

Section 16. Other Information		
References	Available upon request.  * Marque de commerce de Petro-Canada - Trademark	
Glossary		
Continued on Ne	ext Page Internet: www.petro-canada.ca/msds	Available in French

### DEXRON® III/MERCON® AUTOMATIC TRANSMISSION FLUID

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe)

ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days

CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation and

Liability Act

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply List

CNS - Central Nervous System

COD5 - Chemical Oxygen Demand in 5 days **CPR - Controlled Products Regulations** 

DOT - Department of Transport

DSCL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives

(Europe)

DSL - Domestic Substance List

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

EPA - Environmental Protection Agency

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazard Communication Standard HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG'96 - North American Emergency Response Guide Book (1996)

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTECS - Registry of Toxic Effects of Chemical Substances SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLm - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

## For Copy of MSDS

The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: www.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 11/22/2005.

Page Number: 5

Data entry by Product Safety - JDW.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.