

# **Material Safety Data Sheet**

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
(M)	Not controlled	<b>₩</b>	

Section 1. Cl	hemical Product and Company Identification			
Product Name	DURON* SINGLE GRADE ENGINE OILS SAE VISCOSITY GRADES 10W, 20, 30, 40, 50		420-054, DUR1 420-055, DUR2 420-056, DUR3 420-057, DUR4 420-058, DUR5	
Synonym	Not available	Validated	on 10/7/2005.	
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergence	Canutec Transportation: 613-996-6666	
Material Uses	DURON* single grade oils are intended for use in diesel and spark ignition engines according to the specific viscosity grade and performance level for each grade of product. They may also be used for wet clutch and gear type transmissions and hydraulic systems in line with equipment builder specifications.		Poison Control Centrol Consult local telephor directory for emergence number(s).	

Section 2. Composition and Information on Ingredients							
				Expo	Exposure Limits (ACGIH)		
	Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING	
Mixture of severely hydrotreated and hydrocracked and/or solvent-refined base oil (petroleum) and other proprietary, non-hazardous additives.		Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established	
Manufacturer Recommendation	Not applicable						
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.						

Section 3. Haza	Section 3. Hazards Identification.				
Potential Health Effects	Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.				

Section 4. First	Aid Measures
Eye Contact	No effects expected. If irritation does occur, flush contaminated eye(s) with lukewarm, gently flowing water for 5 minutes or until the chemical is removed. If irritation persists, obtain medical advice.
Skin Contact	Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with water and non-abrasive soap for 5 minutes or until chemical is removed. Remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). If irritation persists, repeat flushing. Obtain medical advice immediately. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice.
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. DO NOT induce vomiting because of danger of aspirating liquid into lungs. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, rinse mouth and repeat administration of water. Obtain medical attention.
Note to Physician	Not available

DURON* SINGLE GRADE ENGINE OILS SAE VISCOSITY GRADES	Page Number: 2
10W. 20. 30. 40. 50	_

Section 5. Fire-	Section 5. Fire-fighting Measures					
Flammability	May be combustible at high temperature.	Flammable Limits	Not available.			
Flash Points	CLOSED CUP:≥194°C (381.2°F) (Pensky-Martens) OPEN CUP: ≥205°C (401°F) (Cleveland)	Auto-Ignition Temperature	Fire Point: ≥231°C (447.8°F)			
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.			
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), CaOx, ZnOx, POx, smoke and irritating vapours as products of incomplete combustion.					
Fire Fighting Media and Instructions	NAERG2004, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.					

## Section 6. Accidental Release Measures

# **Material Release** or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Ensure clean-up personnel wear appropriate personal protective equipment. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

Section 7. Ha	Section 7. Handling and Storage				
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Wear proper personal protective equipment (See Section 8). Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.				
Storage	Store in dry, cool, well-ventilated area. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).				

# Section 8. Exposure Controls/Personal Protection

## Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

# Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use. Eyes As a minimum, safety glasses with side shields should be worn when handling this material.

Body If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume of mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSHapproved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): neoprene, nitrile, polyvinyl alcohol (PVA), fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Available in French Continued on Next Page Internet: www.petro-canada.ca/msds

DURON* SINGLE GRADE ENGINE OILS SAE VISCOSITY GRADES	Page Number: 3
10W. 20. 30. 40. 50	

1011, 20, 00, 10, 00			
Section 9. Phy	sical and Chemical Properties		
Physical State and Appearance	Viscous liquid.	Viscosity	10W: 41.51 cSt @ 40°C (104°F) 20: 64.9 cSt @ 40°C (104°F) 30: 83.2 cSt @ 40°C (104°F) 40: 133.5 cSt @ 40°C (104°F) 50: 209 cSt @ 40°C (104°F)
Colour	Amber.	Pour Point	10W: -42°C (-43.6°F) 20: -39°C (-38.2°F) 30: -36°C (-32.8°F) 40: -30°C (-22°F) 50: -21°C (-5.8°F)
Odour	Mild petroleum oil like.	Softening Point	Not applicable.
Odour Threshold	Not available.	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	Not available.	Penetration	Not applicable.
Density	0.8667 to 0.8881 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not available
Vapour Density	Not available.	Ionicity (in water)	Not available
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available
Volatility	Not available	Solubility	Insoluble in water.

Section 10. S	Section 10. Stability and Reactivity					
Corrosivity	10W, 30, 40: Copper corrosion, 3h, 100°C 20, 50: Copper corrosion, 3h, 100°C (AST					
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.			
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents, acids, halogens and halogen compounds.	Decomposition Products	May release COx, NOx, SOx, POx, ZnOx, H2S, alkyl mercaptans, sulfides, aldehydes, methacrylate monomers, smoke and irritating vapours when heated to decomposition.			

Routes of Entry	Skin contact, eye contact, inhalation and ingestion.	
Acute Lethality	Acute toxicity information is not available for the product as a whole, there oils are provided below: Acute Oral toxicity (LD50): >5000 mg/kg (rat) Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit) Acute Inhalation toxicity (LC50): >2500 mg/m³/4h (rat)	iore, data for the base
Chronic or Other Toxic Effe	ects	
Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatities expected to cause only slight irritation, if any.	s. Short-term exposure
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhadurantity at ambient conditions. If heated to high temperatures or subjected which produce vapours or mists, inhalation may cause respiratory tract irritation	to mechanical actions
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vor result in chemical pneumonitis (inflammation of the lungs) and/or praccumulation of fluid in the lungs). May produce a laxative effect.	
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.	
Immunotoxicity:	Not available.	
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based used the known hazards of the components.	ipon the available data
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitiz available data and the known hazards of the components.	ation, based upon the
Mutagenic:	This product is not known to contain any components at >= 0.1% that have mutagenicity. Therefore, based upon the available data and the known components, this product is not expected to be a mutagen.	
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have reproductive toxicity. Therefore, based upon the available data and the components, this product is not expected to be a reproductive toxin.	
Continued on Next Page	Internet: www.petro-canada.ca/msds	Available in French

DURON* SINGLE GRADE ENGINE ( 10W, 20, 30, 40, 50	DILS SAE VISCOSITY GRADES	Page Number: 4
	This product is not known to contain any components at a teratogenicity and/or embryotoxicity. Therefore, based hazards of the components, this product is not expected to	upon the available data and the known
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at report A1 or A2 carcinogens by ACGIH.	ortable quantities that are listed as Group
Carcinogenicity (IARC):	This product is not known to contain any chemicals at report 1, 2A, or 2B carcinogens by IARC.	ortable quantities that are listed as Group
Carcinogenicity (NTP):	This product is not known to contain any chemicals at carcinogens by NTP.	reportable quantities that are listed as
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at carcinogens by IRIS.	reportable quantities that are listed as
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at carcinogens by OSHA.	reportable quantities that are listed as
Other Considerations	No additional remark.	

Section 12. Ec	ological Information		
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available
BOD5 and COD	Not available.	Products of Biodegradation	Not available
Additional Remarks	No additional remark.		

Section 13. Disposal Considerations		
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.	

Section 14. Transport Information			
TDG Classification Not a hazardous material for transport according to the TDG Regulations. (Canada)		Not applicable.	

Section 15. R	egulatory Information			
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).			
	All components of this formulation are listed on the US EPA-TSCA Inventory.			
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).			
	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.  Please contact Product Safety for more information.			
DSD/DPD (Europ	Not classified under the Dangerous Substances or Dangerous Preparations Directives.	HCS (U.S.A.)	Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States)	
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT	DOT (U.S.A)	Not evaluated for transport	
	NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	(Pictograms)	Non évalué pour le transport	
HMIS (U.S.A.)	Health Hazard  Fire Hazard  Reactivity  Personal Protection  NFPA (L	Health 1 0	Rating 0 Insignificant  Reactivity 1 Slight 2 Moderate  Specific hazard 3 High 4 Extreme	

### Section 16. Other Information

### References

Available upon request.

\* Marque de commerce de Petro-Canada - Trademark

### **Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials

BOD5 - Biological Oxygen Demand in 5 days CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply

CNS - Central Nervous System

COD5 - Chemical Oxygen Demand in 5 days **CPR - Controlled Products Regulations** 

DOT - Department of Transport

DSCL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations

Directives (Europe)

DSL - Domestic Substance List

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

EPA - Environmental Protection Agency

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazard Communication Standard HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG'96 - North American Emergency Response Guide Book (1996)

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health

NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act RTECS - Registry of Toxic Effects of Chemical Substances

SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLm - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

### For Copy of MSDS

The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: www.petro-canada.ca/msds

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax:

1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 10/7/2005.

Data entry by Product Safety - RS.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.