

Material Safety Data Sheet / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.
8069 Rivar Way, Delta, British Columbia,
Canada V4G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: PELADOW®
PRODUCT USE: Oil Well Fluid Additive
CHEMICAL FAMILY: Calcium Chloride (>90%)

WORK PLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Class D-2(B)
WORK PLACE HAZARD: Skin and Eye Irritant

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

SHIPPING NAME: Not Regulated Under TDG
TDG CLASSIFICATION: Not applicable
PACKAGE GROUP: Not applicable
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50 (oral rat)
Calcium Chloride	91 - 92%	10043-52-4	900-2100 mg / kg (100%)
Sodium Chloride	1 - 2%	7647-14-5	Not available
Potassium Chloride	2-3%	7447-40-7	Not available
Strontium Chloride	1%	10476-85-4	Not available

SECTION III: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:
[XX] Skin, [XX] Eye Contact, [XX] Inhalation, [XX] Ingestion

EYE CONTACT: Dusts may cause moderate to severe eye irritation, with corneal injury that may be slow to heal. When dissolving, the heat produced may cause more intense effects as well as thermal burns.

SKIN CONTACT: Short single exposure not likely to cause significant skin irritation. Prolonged or repeated exposure may cause skin irritation, even a burn. May cause more severe response if skin is damp and/or abraded, or if material is confined to skin. When dissolving, the heat produced may cause more intense effects as well as thermal burns. DOT classification: Noncorrosive.

SKIN ABSORPTION: A single prolonged exposure is not likely to result in the material being absorbed through the skin in harmful amounts. The LD₅₀ for skin absorption in rabbits is >5000 mg / kg.

INGESTION: Single dose oral toxicity is low. Swallowing solids may cause gastro-intestinal irritation or ulceration.

INHALATION: Vapours are unlikely due to physical properties. Dust may cause irritation of upper respiratory tract.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Immediately wash skin with lots of soap and water. Remove contaminated clothing and shoes; wash before reuses. Get medical attention if irritation persists after washing.

EYE CONTACT: *Get immediate medical attention.* Immediately flush eyes with lots of running water for 15 minutes, lifting the upper and lower eyelids occasionally.

**WESTCOAST DRILLING SUPPLIES LTD.**

8088 River Way, Delta, British Columbia, Canada V4C 1L3

Phone: (604) 940-8080 • Fax: (604) 940-6080

Toll Free: 1-800-882-0845

PELADOW®

Page 2 of 3

INGESTION: If conscious, immediately induce vomiting. *Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.*

INHALATION: remove to fresh air. Give artificial respiration if not breathing. *Get immediate medical attention.*

NOTE TO PHYSICIAN: If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Supportive care. Treatment based on judgement of the physician in response to reactions of patient.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR:	White to off-white powder; odorless.
DENSITY (SPECIFIC GRAVITY):	2.2 g/cc
BOILING POINT:	198° C
MELTING POINT:	Approximately 230° C
WATER SOLUBILITY:	Soluble pH 7-10
% VOLATILE BY VOLUME:	Not applicable
EVAPORATION RATE:	Not applicable
VAPOR PRESSURE: (mm Hg)	0.009 mm Hg 20° C
VAPOR DENSITY: (Air = 1)	Not applicable

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMIT:	Not applicable
EXTINGUISHING MEDIA:	This material is not combustible
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained respirators required for fire-fighting personnel
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []

INCOMPATIBILITY (CONDITIONS TO AVOID): (Specific Materials to Avoid) Calcium Chloride will: corrode most metals exposed to air, attack aluminium (and its alloys) and yellow brass; react with sulphuric acid to form hydrogen chloride which is corrosive, irritating, and reactive; give an exothermic reaction with water-reactive materials such as sodium; result in a runaway polymerization reaction with methyl vinyl ether (Brotherick, 1979); and, in solution form react with zinc (galvanizing) to yield hydrogen gas which is explosive (Ibid.). (Brotherick, L. 1979, Handbook of Reactive Chemical Hazards, 2nd Ed.)

HAZARDOUS DECOMPOSITION PRODUCTS: Not Applicable**HAZARDOUS POLYMERIZATION:** Will not occur [XX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION:	Approved dust respirator mask
VENTILATION:	Local mechanical exhaust
PROTECTIVE GLOVES:	Rubber gloves.
EYE PROTECTION:	Chemical goggles.
OTHER PROTECTIVE EQUIPMENT:	An eyewash and safety shower should be nearby and ready for use.

**WESTCOAST DRILLING SUPPLIES LTD.**

2800 River West Delta, British Columbia, Canada V8G 1L3

Phone: (604) 940-8080 - Fax: (604) 940-8080

Toll Free: 1-800-665-0645

PELADOW®

Page 3 of 3

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid eye and prolonged skin contact. Always use cool water (temperature less than 27° C). when dissolving calcium chloride. Heat developed by solutions is very high during dissolving and mixing. When exposed to atmosphere, calcium chloride will pick up water and form a solution. Leather clothing and shoes will be damaged by calcium chloride.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Losses incidental to correct applications of this product in its intended uses are not expected to be harmful to the environment. Wear appropriate safety apparel during clean-up. Avoid entry of large amount of product into sewers, natural waters, and drinking water sources. Due to possible harmful effects. Avoid contact with vegetation, animals and fish life. Recover quickly into suitable, dry sealable containers if reusing. Small quantities may be flushed away with plenty of water. Walking surfaces may remain wet longer due to moisture being held by spilled product - avoid by thoroughly water washing surfaces.

WASTE DISPOSAL METHOD:

Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate regulatory agencies to ascertain proper disposal procedures

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: December 15, 1994

DATE REVISED: April 1, 2000

BY: Product Safety Committee

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8089 River Way, Delta, British Columbia,
Canada V4C 1L3
Ph. (604) 940-8050 Fax (604) 940-6080

EMERGENCY 1-800-865-6845

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **W-OB POLYMER**
PRODUCT USE: Drilling Mud Additive
CHEMICAL FAMILY: Polysaccharide Polymer
WHMIS CLASSIFICATION: Class B-3 & D-2(B)
WORK PLACE HAZARD: Combustible and Skin and Eye Irritant

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not Dangerous Goods
PACKAGE GROUP: Not applicable
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50	LC50
Light mineral distillate	10 - 20%	64742-47-8	Not determined	

SECTION III: TOXICOLOGICAL PROPERTIES**ROUTE OF ENTRY:**

[XXX] Skin, [XXX] Eye Contact, [XXX] Inhalation, [XXX] Ingestion

THRESHOLD LIMIT VALUE:

5 mg/cu.M/8 hrs.

EFFECTS OF OVEREXPOSURE:

No significant signs or symptoms indicative of any adverse health effects are expected to occur upon short-term exposures.

SECTION IV: FIRST AID MEASURES**SKIN CONTACT:** Remove by wiping; then wash thoroughly with plenty of soap and water.**EYE CONTACT:** Flush eyes with clean, low pressure water for at least fifteen (15) minutes, occasionally lifting the eyelids. If pain or redness persists after flushing, obtain medical attention.**INHALATION:** Immediately remove personnel from contaminated area to fresh air. Obtain medical attention if there are signs of breathing difficulties.**INGESTION:** Do not induce vomiting, since aspiration into the lungs could cause lipid pneumonia. This material is not toxic and no significant signs or symptoms indicative of any adverse health effects are expected.**SECTION V: PHYSICAL DATA**

APPEARANCE AND ODOR: Opaque, blue liquid; Odorless,
DENSITY (SPECIFIC GRAVITY): 1.03
BOILING POINT: 200° C
MELTING POINT: Not applicable
WATER SOLUBILITY: Soluble
% VOLATILE BY VOLUME: Negligible
EVAPORATION RATE: Nil
VAPOR PRESSURE: (mm Hg) < 1.0
VAPOR DENSITY: (Air = 1) > 10.0
pH: 6 - 8

**WESTCOAST DRILLING SUPPLIES LTD.**

8088 River Way, Delta, British Columbia, Canada V4B 1L3

Phone: (604) 940-6080 Fax: (604) 940-6080

Toll Free: 1-800-666-0666

W-OB POLYMER

Page 2 of 2

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	62° C
FLAMMABLE LIMIT:	Auto-ignition Temp. 227° C
EXTINGUISHING MEDIA:	Dry chemical, CO ₂ , foam and water are effective but may cause frothing.
SPECIAL FIRE FIGHTING PROCEDURES:	Cool tanks and containers exposed to fire with water.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	To protect against hazardous effects of combustion products respiratory protective equipment when in confined spaces or down wind of fire.

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []	
INCOMPATIBILITY (CONDITIONS TO AVOID):	Extreme heat and open flame.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon dioxide; carbon monoxide.
HAZARDOUS POLYMERIZATION:	Will not occur [XXX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION:	
RESPIRATORY PROTECTION:	None required under normal conditions.
VENTILATION:	Adequate ventilation to minimize oil mists below acceptable standards.
PROTECTIVE GLOVES:	None required.
EYE PROTECTION:	Normal safety glasses suggested.
OTHER PROTECTIVE EQUIPMENT:	None required.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid ingestion. Practice reasonable caution and personal cleanliness. Avoid skin and eye contact.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

(Use appropriate safety equipment). Small spills, soak up with absorbent material. Large spills, dike to contain spill to prevent water pollution. Water will cause extreme slipperiness. Recover diked material; return recovered material to plant.

WASTE DISPOSAL METHOD:

Absorb spilled material with absorbent compound, incinerate/dispose to conform with local disposal regulations.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: October 29, 1993

DATE REVISED: April 1, 2000

BY: Product Safety Committee

MAR 14 2002 3:37PM

WESTCOAST#DRILLING

Material Safety Data / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.

8069 River Way, Delta, British Columbia,
Canada V4C 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-685-8845

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: DR-133 POLYMER
PRODUCT USE: Drilling Mud Additive
CHEMICAL FAMILY: Copolymer of Acrylamide with Sodium Acrylate
WHMIS CLASSIFICATION: B-3, D-2B
WORK PLACE HAZARD: Combustible liquid, Toxic material

(TDG TRANSPORTATION OF DANGEROUS GOODS)

TDG CLASSIFICATION: Not regulated by TDG

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	CAS NUMBER	LD ₅₀ (oral rat)	LD ₅₀ (Dermal rabbit)
Mineral Spirits	20-40	64742-47-8	>5 g/kg	>3 g/kg
Alkyl phenol ethoxylate	3-7	68412-54-4	3000 mg/kg	4400 mg/kg
Ethoxylated C12-15 Alcohol	1-5	68131-39-5	>3200 mg/kg	>2000 mg/kg

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: ☒ Skin ☒ Eye Contact ☐ Inhalation ☒ INGESTION

SKIN CONTACT: Contact can cause irritation, redness, swelling or dermatitis.
EYE CONTACT: Will cause painful burning or stinging of eyes and lids, watering of eyes, and inflammation of conjunctiva.
INHALATION: Not available.
INGESTION: May cause nausea, diarrhea, abdominal cramps and vomiting.
EFFECTS OF CHRONIC EXPOSURE: Skin irritation or dermatitis may occur upon frequent or prolonged exposure.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: In case of skin contact, immediately flush contacted area for at least 15 minutes with water. Remove contaminated clothing immediately and launder before reuse. If irritation develops consult a doctor.
EYE CONTACT: In case of contact with eyes, flush with water for at least 15 minutes. Seek immediate medical attention.
INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Seek medical attention.
INGESTION: If victim is conscious, give water. Do not induce vomiting. Seek immediate medical attention.

Material Safety Data / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V8G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-565-6646

DR-133 POLYMER

Page 2 of 3

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR	: Liquid emulsion
SPECIFIC GRAVITY	: Not available
BOILING POINT (°C)	: Not available
MELTING POINT (°C)	: Not available
SOLUBILITY IN WATER	: Soluble
pH	: 7.0 - 9.0 (0.6% in D.W.)
PERCENT VOLATILE BY VOLUME	: Not available
EVAPORATION RATE	: Not available
VAPOR PRESSURE (mm Hg)	: Not available
VAPOR DENSITY (Air = 1)	: Not available

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (°C):	: 70°C
FLAMMABLE LIMITS:	: Not available
EXTINGUISHING MEDIA	: Water, dry chemical, foam, carbon dioxide, Water will cause extreme slipperiness.
SPECIAL FIRE FIGHTING PROCEDURES	: Self-contained respirators required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	: sensitivity to static discharge.

SECTION VII: REACTIVITY DATA

STABILITY:	Stable [XXX]	Unstable []
INCOMPATIBILITY (MATERIALS TO AVOID):	Strong oxidizing agents and reducing agents.	
HAZARDOUS DECOMPOSITION PRODUCTS :	Not available	
HAZARDOUS POLYMERIZATION	Will not occur [XXX]	May occur []

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8088 River Way, Delta, British Columbia,
Canada V4G 1L5
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-8845

DR-133 POLYMER

Page 3 of 3

SECTION VIII: PREVENTIVE MEASURES**SPECIAL PROTECTION INFORMATION****RESPIRATORY PROTECTION:**

In absence of proper ventilation, recommend approved organic vapor-type respirator.

VENTILATION:

10 changes per hour suggested.

PROTECTIVE GLOVES:

Suggest plastic or rubber

EYE PROTECTION:

Goggles

OTHER PROTECTIVE EQUIPMENT

(Specify):

Suggest rubber apron

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Keep container closed when not in use.

Store in a cool and dry location away from oxidizing and reducing agents.

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED

Eliminate sources of ignition.

Collect into waste container.

Absorb remaining product with earth or sand and dispose of with solid waste.

Wash spill site after material pickup.

Do not breath vapours.

Water will cause extreme slipperiness.

Use NIOSH approved respirator if exposed to vapours.

WASTE DISPOSAL METHOD

Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

SUPERSEDES: October 29, 1993

DATE REVISED: June, 2000

DATE ISSUED: April 1, 2000

BY: Product Safety Committee

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8069 River Way, Delta, British Columbia,
Canada V4C 1L3
Ph. (604) 940-6060 Fax (604) 940-6080

EMERGENCY 1-800-665-0045

SECTION I: IDENTIFICATION OF PRODUCT**PRODUCT NAME:** 550X® POLYMER**CHEMICAL FAMILY:** Anionic water soluble polymer**PRODUCT USE:** Drilling mud additive**WHMIS CLASSIFICATION:** Not WHMIS regulated**TRANSPORTATION OF DANGEROUS GOODS (TDGR)****CLASSIFICATION:** Not applicable**PACKAGE GROUP:** Not applicable**UN NUMBER (PIN):** Not applicable**SECTION II: HAZARDOUS INGREDIENTS**

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50	LC50
Copolymer of Acrylamide and Sodium Acrylate		25085-02-3		
Acrylamide	0.1000	79-06-1		

SECTION III: HEALTH HAZARDS**ROUTES OF ENTRY**

[XXX] Skin [XXX] Eye Contact [XXX] Inhalation [XXX] Ingestion

THRESHOLD LIMIT VALUE:

Not determined

SKIN CONTACT:

No effects of exposure expected due to contact.
Prolonged contact may cause slight skin irritation or dermatitis in some individuals.

EYE CONTACT:

No effects of exposure expected with the exception of mechanical irritation.

INGESTION:

No adverse effects expected.
Product may swell in throat causing choking.

INHALATION:

May cause sneezing, slight irritation of nose and throat.

SECTION IV: FIRST AID MEASURES**SKIN CONTACT:**

Wash with soap and water as a precaution. In case of persistent skin irritation, consult a physician.

EYE CONTACT:

Rinse thoroughly with plenty of water, also under the eyelid. In case of persistent eye irritation, consult a physician.

INGESTION:

The product is not considered toxic based on studies on laboratory animals. Do not induce vomiting, give 2-3 glasses of water.

INHALATION:

Move to fresh air. If not breathing give artificial respiration. Seek medical attention.

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8089 River Way, Delta, British Columbia,
Canada V4C 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

550X® POLYMER

Page 2 of 4

SECTION V: PHYSICAL DATA

APPEARANCE	White granular solid
ODOR	None
SPECIFIC GRAVITY	0.8 at 25° C (77 F)
BOILING POINT (°C)	Not applicable
MELTING POINT (°C)	Not determined
SOLUBILITY IN WATER	Forms a gel
PERCENT VOLATILE BY VOLUME	Not determined
EVAPORATION RATE	Not determined
VAPOR PRESSURE (mm Hg)	Not determined
VAPOR DENSITY (Air=1)	Not determined
pH	4 - 9 @ 5g/L

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	93° C (200 F)
FLAMMABLE LIMITS	Not determined
EXTINGUISHING MEDIA	Dry Chemical, Carbon Dioxide
SPECIAL FIRE FIGHTING PROCEDURES	Aqueous solutions or powders that become wet render surfaces extremely slippery.
UNUSUAL FIRE AND EXPLOSION HAZARDS	No special equipment required.

SECTION VII: REACTIVITY DATA

STABILITY	[XXX] Stable [] Unstable
INCOMPATIBILITY (Conditions to avoid)	Oxidizing agents
CONDITIONS OF REACTIVITY	Not known
HAZARDOUS DECOMPOSITION PRODUCTS	NO _x , CO _x
HAZARDOUS POLYMERIZATION	[XXX] Will not occur [] May occur

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8088 River Way, Delta, British Columbia,
Canada V4C 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

550X® POLYMER

Page 3 of 4

SECTION VIII: PREVENTIVE MEASURES**SPECIAL PROTECTION INFORMATION****RESPIRATORY PROTECTION**

Dust masks are recommended where concentration of total dust is more than 10 mg/m³

VENTILATION

General mechanical

PROTECTIVE GLOVES

Chemically resistant

EYE PROTECTION

Safety glasses with side shields

OTHER PROTECTIVE EQUIPMENT (Specify)

Not known

ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED**

Do not flush with water. Clean up promptly by sweeping or vacuum.
Keep in suitable and closed containers for disposal.
After cleaning, flush away trace with water.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Wash hands before breaks and at the end of the day. Keep in a cool dry place (0 - 30 °C)

WASTE DISPOSAL METHOD

Can be land filled or incinerated, when in compliance with local, provincial and federal regulations.

SECTION IX: TOXICOLOGICAL INFORMATION**CARCINOGENICITY**

Not determined

REPRODUCTIVE TOXICITY

Not determined

TERATOGENICITY

Not determined

MUTAGENICITY

Not determined

DEVELOPMENTAL TOXICITY

Not determined

CHRONIC EFFECTS:

This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

Material Safety Data / Fiche signalétique**WESTCOAST DRILLING SUPPLIES LTD.**

8068 River Way, Delta, British Columbia,
Canada V8C 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-885-8848

550X POLYMER

Page 4 of 4

SECTION X: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: August, 2001

DATE REVISED: August, 1998

BY: Product Safety Committees

AMENDMENT
HAZARDOUS INGREDIENTS (550X)

Material or component	WT%	Hazard data
COPOLYACRYLAMIDE/SODIUM ACRYLATE		Not considered hazardous

ENVIRONMENTAL

DEGRADABILITY/AQUATIC TOXICITY:	Not determined	
OCTANOL/WATER PARTITION COEFFICIENT	Not determined	
WASTE DISPOSAL METHODS:	Incineration and/or disposal in Chemical Landfill. Disposer must comply with federal, provincial and local disposal or discharge laws.	
RCRA STATUS OF UNUSED MATERIAL IF DISCARDED:	Not a "Hazardous Waste"	
HAZARDOUS WASTE NUMBER:	Not available	
REPORTABLE QUANTITY:	EPA 40 CFR (CBRCLA 102):	Not applicable
THRESHOLD PLANNING QUANTITY:	EPA 40 CFR 355 (SERA 301-304):	Not applicable
TOXIC CHEMICAL RELEASE REPORTING:	EPA 40 CFR 372 (SERA 311-313):	Not applicable
EPA HAZARD CLASSIFICATION CODE:	ACUTE - Yes FIRE - No	CHRONIC - No PRESSURE - No REACTIVE - No
HMIS AND NFPA RATINGS:	HMIS	NFPA
HEALTH	1	1
FLAMMABILITY	0	0
REACTIVITY	1	1
SPECIAL	Not applicable	Not applicable

Superior
Propane Inc.

MATERIAL SAFETY DATA SHEET *Attn Rod.*

SECTION 1 - PRODUCT INFORMATION

Product Name: Propane
Trade Name: LPG (Liquified Petroleum Gas), LP-Gas
Chemical Formula: C₃H₈

Supplier: Superior Propane Inc.
1111 - 49th Avenue N.E.
Calgary, AB T2E 8V2

WHMIS CLASSIFICATION

Class A - Compressed Gas
Class B, Division 1 - Flammable Gas

Business: (403) 730-7500

Local Market

Emergency Number:

(Non Medical)

Application and Use: Propane is commonly used as a fuel for heating, cooking, automobiles, forklift trucks, crop drying and welding and cutting operations. Propane is used in industry as a refrigerant, solvent and as a chemical feedstock.

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENTS	CAS NO.	% Volume (v/v)	LD50
Propane	74-98-6	90% - 99%	Not Applicable
Propylene	115-07-1	0% - 5%	Not Applicable
Ethane	74-84-0	0% - 5%	Not Applicable
Butane and heavier hydro carbons	106-97-8	0% - 2.5%	Not Applicable

Occupational Exposure Limit:

Based upon animal test data, the acute toxicity of this product is expected to be inhalation: 4 hour LC50 = 280,000 ppm (Rat).

Note: Composition is typical for HD-5 Propane per The Canadian General Standard Board CGSB 3.14 National Standard of Canada. Exact composition will vary from shipment to shipment.

SECTION 3 - CHEMICAL AND PHYSICAL DATA

Form: Liquid and vapour while stored under pressure.
Boiling Point: -42°C @ 1 atm.
Freezing Point: -188°C
Evaporation Rate: Rapid (Gas at normal ambient conditions).
Vapour Pressure: 1435 kPa (maximum) @ 37.8°C
Vapour Density: 1.52 (Air = 1)
Coefficient of Water/Oil Distribution: Not available.
pH: Not available.

Solubility in water: Slight, 6.1% by volume @ 17.8°C

Specific Gravity: 0.51 (water = 1)

Appearance/Odour: Colourless liquid and vapour while stored under pressure. Colourless and odourless gas in natural state at any concentration. Commercial propane has an odourant added, ethyl mercaptan, which has an odour similar to boiling cabbage.

Odour Threshold: 4800 ppm

* With proper handling, transportation and storage, adding a chemical odourant such as eth-merc has proven to be a very effective warning device, but all odourants have certain limitations. The effectiveness of the odourant may be diminished by a person's sense of smell, by competing odours and by oxidation which may cause a potentially dangerous situation.

SECTION 4 - FIRE OR EXPLOSION HAZARD

Flash Point: -103.4°C
Method: Closed cup.
Flammable Limits: Lower 2.4%, Upper 9.5%
Auto Ignition Temperature: 432°C
Products Evolved Due To Heat Or Combustion: Carbon monoxide can be produced when primary air and secondary air are deficient while combustion is taking place.
Fire and Explosive Hazards: Explosive air-vapour mixtures may form if allowed to leak to atmosphere.
Sensitivity To Impact: No.
Sensitivity To Static Discharge: Yes.

Fire Extinguishing Precautions: Use water spray to cool exposed cylinders or tanks. Do not extinguish fire unless the source of the escaping gas that is fueling the fire can be turned off. Fire can be extinguished with carbon dioxide and/or dry chemical (BC). Container metal shells require cooling with water to prevent flame impingement and the weakening of metal. If sufficient water is not available to protect the container shell from weakening, the area will be required to be evacuated. If gas has not ignited, liquid or vapour may be dispersed by water spray or flooding.

Special Fire Fighting Equipment: Protective clothing, hose monitors, fog nozzles, self-contained breathing apparatus.

SECTION 5 - REACTIVITY DATA

Stability: Stable.
Conditions To Avoid: Keep separate from oxidizing agents. Gas explodes spontaneously when mixed with chloride dioxide.
Incompatibility: Remove sources of ignition and observe distance requirements for storage tanks from combustible material, drains and openings to building.

Hazardous Decomposition Products: Deficient primary and secondary air can produce carbon monoxide.

Hazardous Polymerization: Will not occur.

ATT: DOUG

SECTION 6 - TOXICOLOGICAL PROPERTIES OF MATERIAL

ROUTES OF ENTRY:

Inhalation: Simple asphyxiant. No effect at concentrations of 10,000 ppm (peak exposures). Higher concentrations may cause central nervous system disorder and/or damage. Lack of oxygen may cause dizziness, loss of coordination, weakness, fatigue, euphoria, mental confusion, blurred vision, convulsions, breathing failure, coma and death. Breathing high vapour concentrations (saturated vapours) for a few minutes may be fatal. Saturated vapours may be encountered in confined spaces and/or under conditions of poor ventilation. Avoid breathing vapours or mist.

Skin and Eye Contact: Exposure to vapourizing liquid may cause frostbite (cold burns) and permanent eye damage.

Ingestion: Not considered to be a hazard.

Acute Exposure: The acute toxicity of this product is expected to be inhalation: 4 hour LC50=280,000ppm (Rat).

Chronic Exposure: There are no reported effects from long term low level exposure.

Sensitization to Product: Skin-unknown, Respiratory-unknown.

Occupational Exposure Limits: American Conference of Governmental Industrial Hygienists (ACGIH) lists as a simple asphyxiant. ACGIH TLV: 1000 ppm.

Carcinogenicity, Reproductive Toxicity, Teratogenicity, Mutagenicity: No effects reported.

SECTION 7 - PREVENTIVE MEASURES

Eyes: Safety glasses, are recommended when transferring product.

Skin: Insulated gloves required if contact with liquid or liquid cooled equipment is expected. Wear gloves and long sleeves when transferring product.

Inhalation: Where concentration in air would reduce the oxygen level below 18% air or exceed occupational exposure limits in section 6, self-contained breathing apparatus is required.

Ventilation: Explosion proof ventilation equipment required in confined spaces.

SECTION 8 - EMERGENCY AND FIRST AID PROCEDURES

FIRST AID:

Eyes: Should eye contact with liquid occur, flush eyes with lukewarm water for 15 minutes. Obtain immediate medical care.

Skin: In case of "Cold Burn" from contact with liquid, immediately place affected area in lukewarm water and keep at this temperature until circulation returns. If fingers or hands are frostbitten, have the victim hold his hand next to his body such as under the armpit. Obtain immediate medical care.

Ingestion: None considered necessary.

Inhalation: Remove person to fresh air. If breathing is difficult or has stopped, administer artificial respiration. Obtain immediate medical care.

SPILL OR LEAK:

Eliminate leak if possible.

Eliminate source of ignition.

Ensure cylinder is upright.

Disperse vapours with hose streams using fog nozzles. Monitor low areas as propane is heavier than air and can settle into low areas. Remain upwind of leak. Keep people away. Prevent vapour and/or liquid from entering into sewers, basements or confined areas.

SECTION 9 - TRANSPORTATION, HANDLING AND STORAGE

- Transport and store cylinders and tanks secured in an upright position in a ventilated space away from ignition sources (so the pressure relief valve is in contact with the vapour space of the cylinder or tank).
- Cylinders that are not in use must have the valves in the closed position and be equipped with a protective cap or guard.
- Do not store with oxidizing agents, oxygen, or chlorine cylinders.

- Empty cylinders and tanks may contain product residue. Do not pressurize, cut, heat or weld empty containers.
- Transport, handle and store according to applicable federal and provincial codes and regulations.

Transportation of Dangerous Goods (TDG)

- TDG Classification: Flammable Gas 2.1
- TDG Shipping Name: Liquefied Petroleum Gas (Propane)
- TDG Special Provisions: 56, 90, 102
- PIN Number: UN1075

SECTION 10 - PREPARATION

Superior Propane Inc., Regulations & Safety Department. (403) 730-7500 Date prepared: November 2001.
Supersedes: September 1999.

The information contained herein is believed to be accurate. It is provided independently of any sale of the product. It is not intended to constitute performance information concerning the product. No express warranty, implied warranty of merchantability or fitness for a particular purpose is made with respect to the product information contained herein.

DIESEL FUEL		Page Number: 3	
Vapour Pressure	1.0 kPa @ 20°C (7.5 mmHg @ 68°F)	Dispersion Properties	Not available
Volatility	<0.1 (Butyl acetate = 1), less than gasoline.	Solubility	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

Section 10. Stability and Reactivity			
Corrosivity	Not available		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents and acids.	Decomposition Products	May release CO _x , NO _x , SO _x , H ₂ S, H ₂ O, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information	
Routes of Entry	Skin contact, eye contact, inhalation, and ingestion.
Acute Lethality	Acute oral toxicity (LD50): 7500 mg/kg (rat).
Chronic or Other Toxic Effects	
Dermal Route:	Skin contact may cause moderate to severe irritation. Repeated exposure would produce drying and cracking or defolting dermatitis.
Inhalation Route:	Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat.
Oral Route:	Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	Eye contact may cause mild irritation, but no permanent damage.
Immunotoxicity:	Not available
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.
Mutagenic:	This product is not expected to be a mutagen, based on the available data and the known hazards of the components.
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.
Carcinogenicity (ACGIH):	ACGIH Notice of Intended Change (2000): proposed A1: animal carcinogen. [Diesel oil]
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	Not available
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section 12. Ecological Information			
Environmental Fate	Not available	Persistence/Bioaccumulation Potential	Not available
BOD5 and COD	Not available	Products of Biodegradation	Not available
Additional Remarks	No additional remark.		

HAZARD FUEL

Page Number: 2

**Fire Fighting
Media and
Instructions**

NAERG96, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible).

CAUTION: This product has a moderate flash point above 40°C. Use of water spray when fighting fire may be inefficient.

If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

SMALL FIRES: Dry chemical, CO₂, water spray or regular foam.

LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk.

Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.

Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.

Section 6. Accidental Release Measures**Material Release
or Spill**

NAERG96, GUIDE 128, Flammable Liquids (Non-polar/ Water-immiscible).

ELIMINATE ALL IGNITION SOURCES. Avoid contact. Stop leak if without risk. Contain spill. Absorb with inert absorbents, dry clay, or diatomaceous earth. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.

Section 7. Handling and Storage**Handling**

Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. DO NOT reuse empty containers without commercial cleaning or reconditioning. Ground/bond line and equipment during pumping or transfer to avoid accumulation of static charge. DO NOT ingest. Do not breathe gas/vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately. Avoid contact with skin and eyes. Practice good personal hygiene. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.

Storage

Store in tightly closed containers in cool, dry, isolated, well-ventilated area, and away from incompatibles. Ground all equipment containing material.

Section 8. Exposure Controls/Personal Protection**Engineering Controls**

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work station.

Personal Protection

The selection of personal protective equipment varies, depending upon conditions of use.

Eyes

Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

Body

Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

Respiratory

Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

Hands

Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

Feet

Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Bright oily liquid.	Viscosity	1.3-4.1 cSt @ 40°C (104°F)
Colour	Clear to yellow / brown. Low sulphur diesel fuels (<0.05 wt % sulphur) are colourless to light yellow (and may be dyed red for taxation purposes). Regular sulphur diesel fuels (0.05-0.50 % sulphur) may be colourless to yellow / brown and are usually dyed red for taxation purposes.	Pour Point	Variable, 0°C to -50°C (32°F to -58°F)
Odour	Petroleum oil like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	150-371°C (302-700°F)	Penetration	Not applicable.
Density	0.85 kg/L @ 15°C (Water = 1).	Oil / Water Dist. Coefficient	Not available
Vapour Density	4.5 (Air = 1)	Ignicity (in water)	Not applicable.



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	B-3, D-2B		

Section 1. Chemical Product and Company Identification

Product Name	DIESEL FUEL	Code	W104 SAP: 120, 121, 122, 287
Synonym	Diesel 50, Diesel 50 LS, #1 Diesel, #1 Diesel LS, Diesel LC, Seasonal Diesel, Seasonal Diesel LS, Diesel AA, Domestic Marine Diesel, International marine Diesel, Seasonal Diesel Locomotive, Domestic Marine diesel LS, diesel -20°C (LS), LSD, Low Sulphur Diesel, dyed diesel, marked diesel, coloured diesel.	Validated on	3/2/2001.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-298-3000 Canutec Transportation: 613-896-6166 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type.		

Section 2. Composition and Information on Ingredients

Section 2. Composition and information on ingredients			Exposure Limits (ACGIH)		
Name	CAS #	% (V/V)	TLV-TWA (8 h)	STEL	CEILING
1) Diesel oil, 2) Proprietary additives, 3) Aromatic content is 50% maximum (benzene: nil), 4) * Notice of Intended Change (2000): 100 mg/m³, skin, A3.	68334-30-6 Not available	>89.9 <0.1	Not established* Not established	Not established Not established	Not established Not established
Manufacturer	Not applicable				
Recommendation					
Other Exposure Limits Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Hazards Identification

Potential Health Effects	Eye contact may cause mild eye irritation. Skin contact can cause moderate to severe irritation and produce drying, cracking, or defolating dermatitis. Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat. Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonia (fluid in the lungs), severe lung damage, or respiratory failure. For more information, refer to Section 11.
--------------------------	---

Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

Section 5. Fire-fighting Measures

Flammability	Class II - combustible liquid (NFPA).	Flammable Limits	LOWER: 0.7%, UPPER: 6%
Flash Points	Diesel Fuel: Closed Cup: >40°C (>104°F) Marine Diesel Fuel: Closed Cup: >60°C (>140°F)	Auto-ignition Temperature	225°C (437°F)
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks, or heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.	Explosion Hazards in Presence of Various Substances	Containers may explode in heat of fire. Do not cut, weld, heat, drill or pressurize empty container. Vapour explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.
Products of Combustion	Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), sulphur compounds (H ₂ S), water vapour (H ₂ O), smoke and irritating vapours as products of incomplete combustion.		

DIESEL FUEL Page Number: 4

Section 13. Disposal Considerations

Waste Disposal Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations. Consult your local or regional authorities.

Section 14. Transport Information

TDG Classification	Diesel Fuel UN1202 3 III	Special Provisions for Transport	Not applicable.
---------------------------	-----------------------------------	---	-----------------

Section 15. Regulatory Information

Other Regulations This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	CLASS: Irritating substance. CLASS: Target organ effects. CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 73.3°C (200°F).
-------------------------	----------------	---------------------	---

ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT NON EVALUÉ POUR LE TRANSPORT EUROPÉEN	DOT (U.S.A.) (Pictograms)	
----------------------------------	---	----------------------------------	---

HMIS (U.S.A.)	Health Hazard	2
	Fire Hazard	2
	Reactivity	0
	Personal Protection	0

NFPA (U.S.A.)	Health		Fire Hazard	2	Rating	0 Insignificant
			Reactivity	0		1 Slight
						2 Moderate
						3 High
						4 Extreme

--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

Section 16. Other Information

References Available upon request.
* Marque de commerce de Petro-Canada - Trademark

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous Goods by Road (Europe) ASTM - American Society for Testing and Materials BOD₅ - Biological Oxygen Demand in 5 days CAN/CEA 5149.2 - Propene Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemicals Hazard Information and Packaging Approved Supply List COD₅ - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSEL - Dangerous Substances Classification and Labelling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substances List EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning and Community Right-to-Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer	IRIS - Integrated Risk Information System LD₅₀/LC₅₀ - Lethal Dose/Concentration 50% LOEL/CLo - Lowest Published Lethal Dose/Concentration NAERG 98 - North American Emergency Response Guide Book (1998) NFPA - National Fire Protection Association NIOSH - National Institute for Occupational Safety & Health NPL - National Pollution Release Inventory NSMR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reauthorization Act SD - Single Dose STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TLCL - Lowest Published Toxic Dose/Concentration TLN - Marlin Tolerance Limit TLV-TWA - Threshold Limit Value-Time Weighted Average TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System
---	--

For Copy of MSDS

Fuels & Solvents:
Western Canada, telephone: 403-296-4158; fax: 403-296-8551
Ontario & Central Canada, telephone: 1-800-668-0220; fax: 1-800-837-1220
Quebec & Eastern Canada, telephone: 514-640-8308; fax: 514-640-8385

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - TAR on 3/2/2001.

Data entry by Product Safety - J.D.W.

03/14/02 THU 17:33 FAX

02/13/02 WED 11:14 FAX 867 873 8332

02/13/02 WED 09:40 FAX 8678739460

DISCOVERY MINING

MATONABEE PET.

020
005

DIESEL FUEL

Page 100 of 5

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

JET AVIATION TURBOFUEL

Page Number: 3

Section 9. Physical and Chemical Properties			
Physical State and Appearance	Clear liquid.	Viscosity	Not available.
Colour	Clear and colorless.	Pour Point	Freezing Point: <61°C (<60°F) for Jet B/Jet B D; <58°C (<72°F) for Jet Fuel F-40.
Odour	Gasoline like.	Softening Point	Not applicable.
Odour Threshold	Not available.	Dropping Point	Not applicable.
Boiling Point	50 to 270°C (122 to 518°F)	Penetration	Not applicable.
Density	0.78 to 0.80 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not measurable. The product is more soluble in oil.
Vapour Density	3.5 (Air = 1)	Ioninity (In water)	Insoluble in water.
Vapour Pressure	21 kPa (158 mmHg) @ 37.8°C (100°F).	Dispersion Properties	Not dispersed in cold water, or hot water.
Volatility	Volatile.	Solubility	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

Section 10. Stability and Reactivity			
Corrosivity	Non corrosive.		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Can react with strong organic oxidizing agents.	Decomposition Products	Releases of COx, NOx, SOx, H2S, smoke and irritating fumes when heated to decomposition.

Section 11. Toxicological Information	
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Based on toxicity of gasoline, acute oral toxicity (LD50): 18750 mg/kg (rat).
Chronic or Other Toxic Effects	
Dermal Route:	Prolonged or repeated contact can defat the skin, cause irritation, and lead to the development of dermatitis. Prolonged skin contact has same effects as inhalation. Injures blood-forming tissue on contact.
Inhalation Route:	Exposure to light hydrocarbons has been associated in animal studies with effects to the central nervous system, peripheral nervous system, liver, and kidneys. The significance of these animal models to predict similar human response is uncertain. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood forming system (particularly bone marrow), and serious blood disorders, such as aplastic anemia and leukemia.
Oral Route:	Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	May irritate the eyes.
Immunotoxicity:	Benzene-Hematologic and immunochemical investigations carried out in 270 workers with chronic exposure to benzene demonstrated changes of the nucleotogram and of the area of lymphocyte nuclei and disorders of the humoral immune response revealed by radial immunodiffusion.
Skin Sensitization:	No studies were found.
Respiratory Tract Sensitization:	No studies were found.
Mutagenic:	Benzene is tumorigenic by RTECS criteria.
Reproductive Toxicity:	Based on the available animal data for benzene, Dose: 150 ppm (rat/inhalation/24h/7-14 days of pregnancy) - abnormal development of the musculoskeletal system.
Teratogenicity/Embryotoxicity:	Based on the available animal data, benzene poses a developmental or teratogenicity risk to rats.
Carcinogenicity (ACGIH):	ACGIH A1: confirmed human carcinogen, based on toxicity of benzene.
Carcinogenicity (IARC):	IARC Group 1: carcinogenic to Humans, based on toxicity of benzene.
Carcinogenicity (NTP):	NTP Group 1: known to be a carcinogen, based on toxicity of benzene.
Carcinogenicity (IRIS):	No studies were found.
Carcinogenicity (OSHA):	OSHA Group X: carcinogen defined with no further categorization, based on toxicity of benzene.
Other Considerations	Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood forming system (particularly bone marrow), and serious blood disorders, such as aplastic anemia and leukemia. The epidemiologic literature on benzene and leukemia supports the inference that benzene causes acute myelocytic leukemia.

JET-B AVIATION TURBINE FUEL		Page Number: 4									
Section 12. Ecological Information											
Environmental Fate	Volatilizes and disperses rapidly. Volatilization is expected to be the dominant fate process. Biodegrade under both aerobic and anaerobic conditions.	Persistence/Bioaccumulation Potential	Floats on water. May be dangerous to aquatic life in high concentrations.								
BOD5 and COD	Not available.	Products of Biodegradation	Not available.								
Additional Remarks: If released to soil, fuel oil will strongly adsorb. It may biodegrade in water and soil or volatilize from water (half-life of 4.4 to 4.8 hrs from a model river) and moist soil surfaces, but adsorption may attenuate the rate of these processes.											
Section 13. Disposal Considerations											
Waste Disposal	Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations. Consult your local or regional authorities.										
Section 14. Transport Information											
TDG Classification	Shipping Name: Fuel, aviation, turbine engine; UN 1883; Class: 3; Packing Group: II; Label required: Flammable liquid.	Special Provisions for Transport	No additional remark.								
Section 15. Regulatory Information											
Other Regulations	CEPA: This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on DSL. This product may contain trace benzene, a carcinogen, which is listed on NPRI. USEPA: All components of this formulation are listed on TSCA Inventory. This product may contain trace benzene, a carcinogen, which is required to be listed under OSHA hazard communication standard, 29 CFR 1910.1200 (U.S.). Listed on New Jersey Environmental Hazardous Substances List. Benzene is listed on EPCRA or SARA Title III, Section 302/304/311/312 (40 CFR 355/370) for Extremely Hazardous Substances. Benzene is listed on EPCRA or SARA Title III, Section 313 (40 CFR 372) for Toxic Chemicals. Benzene is listed on CERCLA Hazardous Substances (RC Chemicals) (40 CFR 302.4). Benzene is listed on RCRA (40 CFR 261.33) for Hazardous Waste. Please note that the chemical identity of some or all of the ingredients that may be listed herein is confidential business information and is being withheld as permitted by 29 CFR 1910.1200 and various State Right to Know Laws.										
OSD/OPD (Europe)	5- Heating may cause an explosion. 12- Extremely flammable. 18- In use, may form flammable/explosive vapor-air mixture. 36/37/38- Irritating to eyes, respiratory system and skin. 40- Possible risks of irreversible effects.	HCS (U.S.A.)	HCS CLASS: Flammable liquid having a flash point lower than 37.8°C (100°F). HCS CLASS: Irritating substance. HCS CLASS: Toxic.								
ADR (Europe) (Pictograms)		DOT (U.S.A.) (Pictograms)									
HMIS (U.S.A.)	<table border="1"> <tr> <td>Health Hazard</td> <td>1</td> </tr> <tr> <td>Fire Hazard</td> <td>3</td> </tr> <tr> <td>Reactivity</td> <td>0</td> </tr> <tr> <td>Personal Protection</td> <td>2</td> </tr> </table>	Health Hazard	1	Fire Hazard	3	Reactivity	0	Personal Protection	2	NFPA (U.S.A.) Health:  1 Reactivity:  0 Specific Hazard:  2	Rating: 1 Slight 2 Moderate 3 High 4 Extreme
Health Hazard	1										
Fire Hazard	3										
Reactivity	0										
Personal Protection	2										
Section 16. Other Information											
References	Available upon request.										
Glossary	ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous Goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAN/CEA 8149.2 - Propane Installation Code CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemical Hazard Information and Packaging Approved Supply List COD5 - Chemical Oxygen Demand in 5 days CPR - Controlled Products Regulations DOT - Department of Transport DSL - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List EEC/EEU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning and Community Right to Know Act IRIIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration at 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NAERGSM - North American Emergency Response Guide Book (1998) NFPA - National Fire Protection Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollution Release Inventory NSNHL - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act SD - Single Dose STEL - Short Term Exposure Limit (15 Minutes) TDG - Transportation Dangerous Goods (Canada) TLV/TLCL - Lowest Published Toxic Dose/Concentration TLM - Median Tolerance Limit TLV/TWA - Threshold Limit Value-Time Weighted Average										

03/14/02 THU 17:35 FAX
02/13/02 WED 11:19 FAX 867 873 8332
02/13/02 WED 09:43 FAX 8678738460

DISCOVERY MINING
MATONABEE PET-

023
010

JET-B AVIATION TURBINE FUEL		Page Number 5
FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer		TCOA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Materials Information System
For Copy of MSDS Western Canada, telephone: 403-296-7694; fax: 403-296-3763 Ontario & Central Canada, telephone: 1-800-660-0220; fax: 1-800-837-1228 Quebec & Eastern Canada, telephone: 514-640-8398; fax: 514-640-8373		Prepared by Product Safety - TLR on 3/9/1999. Data entry by Product Safety - TLR.
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that those are the only hazards that exist.		

JET-B AVIATION TURBINE FUEL		Page Number: 2	
Fire Hazards in Presence of Various Substances	Easily ignites under almost all normal temperature conditions. Extremely flammable in presence of open flames, sparks, shocks, heat, oxidizing materials. Vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks), and may travel considerable distance to sources of ignition and flash back.	Explosion Hazards in Presence of Various Substances	Excessive heat. Do not cut, weld, heat, or drill empty container. Containers may explode in heat of fire. Runoff to sewer may create fire or explosion hazard.
Products of Combustion	Carbon oxides (CO, CO ₂), nitrogen oxides (NOx), sulphur oxides (SOx), sulphur compounds (H ₂ S), smoke and irritating fumes as products of incomplete combustion.		
Fire Fighting Media and Instructions	NAERG98, GUIDE 128. Flammable/combustible liquid (non-polar/water-immiscible). CAUTION: This product has a low flash point. Use of water spray when fighting fire may be inefficient. SMALL FIRE: Use DRY chemicals, CO ₂ , water spray or foam. LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions. DO NOT extinguish a leaking gas flame unless leak can be stopped. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid flushing spilled material into sewers, streams or other bodies of water. Self-contained breathing apparatus (SCBA) will be required if approaching the fire from downwind, or to enter enclosed areas or buildings.		

Section 6. Accidental Release Measures

Material Release or Spill	NAERG98, GUIDE 128. Flammable/combustible liquid (non-polar/water-immiscible). Evacuate in a downwind direction for at least 300 meters (1000 feet). ELIMINATE ALL IGNITION SOURCES. Ventilate closed spaces before entering. By forced ventilation, maintain concentration of vapour below the range of explosive mixture. Avoid contact, fully-encapsulating, vapour-protective clothing should be worn for spill and leaks with no fire. Stop leak if without risk. Remove the leaking container to an open area and allow it to bleed off into the atmosphere. Use vapour suppressing foam or water spray to reduce vapours. It may reduce vapour, but it may not prevent ignition in closed spaces; isolate area until vapour has dispersed. Contain spill. Absorb with inert absorbents such as dry clay, or diatomaceous earth, or recover using electrically grounded explosion-proof pumps. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.
---------------------------	---

Section 7. Handling and Storage

Handling	Keep away from sources of ignition. In case of insufficient ventilation, wear suitable respiratory equipment. HANDLE AS EXTREMELY FLAMMABLE LIQUID. Electrically ground/bond during the pumping or transfer to avoid static accumulation. DO NOT USE AS CLEANING FLUID OR SIPHON BY MOUTH. Precautions should be taken to minimize skin contact and inhalation. High standards of personal hygiene are necessary. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.
Storage	Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Store in tightly closed containers in cool, dry, isolated and well-ventilated area. Ground all equipments containing material.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	For normal outdoor application, special ventilation is not necessary. For indoor or confined spaces provide explosion-proof local exhaust ventilation, or other engineer controls, to keep airborne concentration below the allowable threshold limit value. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work station.
Personal Protection -	The selection of personal protective equipment varies, depending upon conditions of use.
Eyes	Face shield or chemical splash goggles in case of splashing.
Body	Wear long sleeved clothing to minimize skin contact.
Respiratory	When exposure is likely to exceed recommended exposure limit (see section 2), use NIOSH approved respiratory equipment. Respirator should be selected based on the form and concentration of contaminant in air (refer to NIOSH Pocket Guide for Chemical Hazard for respirator selection). In order to determine the concentration of the contaminant, air sampling is RECOMMENDED AND SHOULD BE PERFORMED BY A HEALTH & SAFETY SPECIALIST (AS PER THE NIOSH Manual of analytical Methods for method of measurement). If air sampling is not practical and concentration is unknown, use positive pressure self-contained breathing apparatus (SCBA). Contact appropriate HEALTH & SAFETY personnel or supplier for assistance.
Hands	For casual contact, polyvinyl alcohol (PVA) gloves are suitable. For direct contact for more than 2 hours, nitrile or vinyl gloves are recommended.
Feet	Safety boots or shoes.



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	LDG (pictograms)
	B-2, D-2A, D-2B		

Section 1. Chemical Product and Company Identification			
Product Name	JET B AVIATION TURBINE FUEL		Code File # W219
Synonym	Jet B, Jet B DI, International Jet B, International Jet B DI, Jet Fuel JP-4, Jet Fuel F-40, Turbine Fuel, Aviation, Wide Cut Type (CANCGSB-3.22).		Validated on 3/9/1999
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3		In case of Emergency: Petro-Canada: 403-295-3000 Canadian Transportation: 613-896-6868 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Used as aviation turbine fuel. May contain a fuel system icing inhibitor.		

Section 2. Composition and Information on Ingredients					
			Exposure Limits (ACGIH)		
Name	CAS #	% (v/v)	TLV-TWA(8 h)	STL	CEILING
1) Complex mixture of aliphatic and aromatic hydrocarbons (C6-C14).	64741-41-8	>99	300 ppm (gasoline)	500 ppm (gasoline)	Not established
2) Proprietary additives.	Not applicable	<0.2	Not established	Not established	Not established
Manufacturer Recommendation	Petro-Canada recommends a working guideline no greater than 1 ppm (3.2 mg/m ³) of benzene for 8 hours time weighted average when handling product which may contain benzene; 300 ppm for 8 hours time weighted average and 500 ppm for short term exposure limit when handling Jet B. Consult local authorities for acceptable exposure limits.				
Other Exposure Limits Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Hazards Identification	
Potential Health Effects	Inhalation of vapours or mist may cause irritation of nose and throat; headache, nausea, vomiting, dizziness, fatigue, light-headedness, reduced coordination and unconsciousness; central nervous system depression; kidney and liver damage from long-term exposure. May be narcotic in high concentrations. Skin contact may cause drying, cracking, defatting, or inflammation of skin. Prolonged or repeated contact with skin may cause dermatitis. Eye contact may cause irritation, but no permanent damage. Overexposure due to ingestion is unlikely for adults since taste and smell limit the amount swallowed. Harmful or fatal if swallowed. For more information, refer to Section 11.

Section 4. First Aid Measures	
Eye Contact	Check for and remove any contact lenses. IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. DO NOT use an eye ointment. Seek medical attention if irritation persists.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth-to-mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	Gastric decontamination to prevent absorption is important following a substantial recent ingestion. Is most effective if initiated within 30 minutes. DO NOT induce vomiting without supervision of medical personnel, because of danger of aspirating liquid into lungs. Seek immediate medical attention.
Note to Physician	Aspiration into lungs may cause chemical pneumonitis. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for respiratory tract irritation, bronchitis, or pneumonitis. Monitor blood gases to assure adequate ventilation. If vital signs become abnormal or symptoms develop obtain a chest x-ray. Prevent further absorption by administer charcoal slurry, aqueous or mixed with saline cathartic or sorbitol. The FOA suggested 2-10 ml of diluent/30 g of charcoal. Usual charcoal dose is 30 to 100 g in adults, 16 to 30 g in children and 1 to 2 g/kg in infants.

Section 5. Fire-fighting Measures			
Flammability	Flammable liquid (NFPA).	Flammable Limits	Lower: 1.3%; Upper: 7.6% (NFPA).
Flash Points	Closed Cup: -25°C (-13°F). Tag, ASTM D56.	Auto-ignition Temperature	240°C (464°F)