



Material Safety Data Sheet

Issue Date: 17-APR-2008
Supersedes: 17-APR-2008

POLYFLOC AP1138

1 Identification

Identification of substance or preparation

POLYFLOC AP1138

Product Application Area

Flocculant

Company/Undertaking Identification

GE Water & Process Technologies Canada
3239 Dundas Street West
Oakville, Ontario, L6M 4B2
T 905-465-3030

Emergency Telephone

(800) 877-1940

Prepared by Product Stewardship Group: T 215-355-3300 Prepared on: 17-APR-2008

2 Hazard(s) identification

EMERGENCY OVERVIEW

May cause slight irritation to the skin. May cause moderate irritation to the eyes. Dusts may cause irritation to the upper respiratory tract.

Odor: None; Appearance: White, Powder

Fire fighters should wear positive pressure self-contained breathing apparatus(full face-piece type). Proper fire-extinguishing media: dry chemical, carbon dioxide, foam or water

POTENTIAL HEALTH EFFECTS

ACUTE SKIN EFFECTS:

Primary route of exposure; May cause slight irritation to the skin.

ACUTE EYE EFFECTS:

May cause moderate irritation to the eyes.

ACUTE RESPIRATORY EFFECTS:

Dusts may cause irritation to the upper respiratory tract.

INGESTION EFFECTS:

May cause gastrointestinal irritation.

TARGET ORGANS:

No evidence of potential chronic effects.

MEDICAL CONDITIONS AGGRAVATED:

Not known.

SYMPTOMS OF EXPOSURE:

May cause redness or itching of skin.

3 Composition / information on ingredients

Information for specific product ingredients as required by the WHMIS Regulations is listed. Refer to additional sections of this MSDS for our assessment of the potential hazards of this formulation.

HAZARDOUS INGREDIENTS:

Product contains no hazardous ingredients reportable under WHMIS regulation

No component is considered to be a carcinogen by the U.S. National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC), the American Conference of Governmental Industrial Hygienists (ACGIH), or under WHMIS.

4 First-aid measures

SKIN CONTACT:

Wash thoroughly with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

EYE CONTACT:

Remove contact lenses. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get immediate medical attention.

INHALATION:

If nasal, throat or lung irritation develops - remove to fresh air and get medical attention.

INGESTION:

Do not feed anything by mouth to an unconscious or convulsive victim. Do not induce vomiting. Immediately contact physician. Dilute contents of stomach using 2-8 fluid ounces (60-240 mL) of milk or water.

NOTES TO PHYSICIANS:

No special instructions

5 Fire-fighting measures

FIRE FIGHTING INSTRUCTIONS:

Fire fighters should wear positive pressure self-contained breathing apparatus (full face-piece type).

EXTINGUISHING MEDIA:

dry chemical, carbon dioxide, foam or water

HAZARDOUS DECOMPOSITION PRODUCTS:

oxides of carbon

FLASH POINT:

> 200F > 93C P-M(CC)

6 Accidental release measures

PROTECTION AND SPILL CONTAINMENT:

Ventilate area. Use specified protective equipment. Sweep up and remove. Minimize dust generation.

DISPOSAL INSTRUCTIONS:

The waste characteristics of the absorbed material, or any contaminated soil, should be determined in accordance with provincial regulations. Water contaminated with this product may be sent to a sanitary sewer treatment facility, in accordance with any local agreement or discharged under provincial regulations. Incinerate or land dispose in an approved landfill.

7 Handling and storage

HANDLING:

This material may be combustible. As with all dry powders it is advisable to ground mechanical equipment in contact with dry material to dissipate the potential buildup of static electricity.

STORAGE:

Keep containers closed when not in use. Do not expose to moisture.

8 Exposure controls / personal protection

EXPOSURE LIMITS

Consult local authorities for acceptable provincial values.

Product contains no hazardous ingredients reportable under WHMIS regulation

ENGINEERING CONTROLS:

Adequate ventilation to maintain air contaminants below exposure limits.

RESPIRATORY PROTECTION:

If air-purifying respirator use is appropriate, use any of the following particulate respirators: N95, N99, N100, R95, R99, R100, P95, P99 or P100.

SKIN PROTECTION:

rubber, butyl, viton or neoprene gloves -- Wash off after each use. Replace as necessary.

EYE PROTECTION:

airtight chemical goggles

9 Physical and chemical properties

Density	43.120 lb/cu.	Vapor Pressure (mmHG)	< 0.1
Freeze Point (F)	NA	Vapor Density (air=1)	< 1.00
Freeze Point (C)	NA		
Viscosity(cps 70F,21C)	NA	% Solubility (water)	1.0
Odor	None		
Appearance	White		
Physical State	Powder		
Flash Point	P-M(CC)	> 200F	> 93C
pH 0.5% Sol. (approx.)	8.0		
Evaporation Rate (Ether=1)	< 1.00		
Percent VOC:	0.0		

NA = not applicable ND = not determined

10 Stability and reactivity

STABILITY:

Stable under normal storage conditions.

HAZARDOUS POLYMERIZATION:

Will not occur.

INCOMPATIBILITIES:

May react with strong oxidizers.

DECOMPOSITION PRODUCTS:

oxides of carbon

INTERNAL PUMPOUT/CLEANOUT CATEGORIES:

"B"

11 Toxicological information

Oral LD50 MOUSE:	>2,000 mg/kg
NOTE - Supplier estimate; Rat oral LD50: >5,000 mg/kg per alternate supplier	
Carcinogenicity RAT/DOG:	NEGATIVE
Dermal LD50 RABBIT:	>2,000 mg/kg
NOTE - Estimated value	
Skin Irritation Score RABBIT:	NONIRRITANT
Eye Irritation Score RABBIT:	SLIGHT
Skin Sensitization G.PIG:	NEGATIVE

12 Ecological information

AQUATIC TOXICOLOGY

Bluegill Sunfish 48 Hour Static Screen
 0% Mortality= 100 mg/L
 Daphnia magna 48 Hour Static Renewal Bioassay
 LC50= 470; No Effect Level= 178 mg/L
 Fathead Minnow 96 Hour Static Renewal Bioassay
 LC50= 239; No Effect Level= 45 mg/L

BIODEGRADATION

BOD-28 (mg/g): 0
 BOD-5 (mg/g): 0
 COD (mg/g): 775
 TOC (mg/g): 349

13 Disposal considerations

Incinerate or bury in approved landfill. Please be advised that there may be additional local or provincial requirements relating to the disposal of waste. Consult provincial and local regulations regarding the proper disposal of this material.

14 Transport information

Transportation of Dangerous Goods:

DOT EMERGENCY RESPONSE GUIDE #: Not applicable

15 Regulatory information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

CEPA:

All components of this product comply with substance notification requirements under CEPA.

WHMIS CLASSIFICATION:

NOT REGULATED

FOOD AND DRUG ADMINISTRATION:

The ingredients in this product are approved by FDA under 21 CFR 173.5 and 21 CFR 573.120

16 Other information

NFPA/HMIS

CODE TRANSLATION

Health	1	Slight Hazard
Fire	1	Slight Hazard
Reactivity	0	Minimal Hazard
Special	NONE	No special Hazard
(1) Protective Equipment	B	Goggles, Gloves

(1) refer to section 8 of MSDS for additional protective equipment recommendations.

CHANGE LOG

	EFFECTIVE DATE	REVISIONS TO SECTION:	SUPERCEDES
	-----	-----	-----
MSDS status:	07-MAY-1997		** NEW **
	01-MAY-1998	8;EDIT:9	07-MAY-1997
	01-JUN-1999	15	01-MAY-1998
	13-SEP-2000	4	01-JUN-1999
	11-DEC-2000	15	13-SEP-2000
	02-DEC-2003	16	11-DEC-2000
	03-NOV-2006	16	02-DEC-2003
	17-APR-2008	4, 5, 6, 7, 8, 10	03-NOV-2006



Shell Canada Limited Material Safety Data Sheet

Effective Date: 2008-08-01

Supersedes: 2005-08-15



Class B3 Combustible Liquid

Class D2A Embryo/Fetotoxicity
Class D2B Skin Irritation

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **SHELL* JET A-1**
SYNONYMS: Aviation Turbine Fuel (Kerosene Type)
May contain anti-icing additive (Diethylene Glycol Monomethyl Ether)
PRODUCT USE: Fuel Solvent
PRODUCT CODE: **142-011**

SUPPLIER

Shell Canada Limited (SCL)
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS

Shell Emergency Number
CANUTEC 24 HOUR EMERGENCY NUMBER
For general information:

1-800-661-7378
1-613-996-6666
1-800-661-1600
www.shell.ca

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Kerosene (Petroleum), Hydrodesulfurized	64742-81-0	60 - 100	Yes
Ethanol, 2-(2-methoxyethoxy)-	111-77-3	0 - 0.15	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Bright Clear Hydrocarbon Odour
Routes of Exposure: Exposure will most likely occur through skin contact or inhalation.
Hazards:

Vapour concentrations above the recommended exposure level are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.
Combustible Liquid.

Handling: Irritating to skin.
Ingestion may result in vomiting. Avoid aspiration of vomitus into lungs as small quantities may result in aspiration pneumonitis.
Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.
Avoid prolonged exposure to vapours.

For further information on health effects, see Section 11.

4. FIRST AID MEASURES

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for at least 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY.
Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Do not give anything by mouth to an unconscious person.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Carbon Dioxide
Foam
Dry Chemical
Water Fog

Firefighting Instructions: Caution - Combustible. Do not use a direct stream of water as it may spread fire. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Avoid inhalation of smoke. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Product will float and can be reignited on surface of water. Delayed lung damage can be experienced after exposure to combustion products, sometimes hours after the exposure.

Hazardous Combustion Products: A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Combustible". Eliminate all ignition sources. Isolate hazard area and restrict access. Wear appropriate breathing apparatus (if applicable) and protective clothing. Handling equipment must be grounded. Work upwind of spill if it is safe to do so. Avoid direct contact with material. Stop leak only if safe to do so. Dike and contain land spills; contain spills to water by booming. Use water fog to knock down vapours; contain runoff. Adsorb residue or small spills with adsorbent material and remove to non-leaking containers for disposal. Notify appropriate environmental agency(ies). After area has been cleaned up to the satisfaction of regulatory authorities, flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations.

7. HANDLING AND STORAGE

Handling: Combustible. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

Storage: Store in a cool, dry, well ventilated area, away from heat and ignition sources. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The following information, while appropriate for this product, are general in nature. The selection of personal protective equipment will vary depending on the conditions of use.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Kerosene/Jet fuels, as total hydrocarbon vapour (skin) : 200 mg/m³ (Application restricted to conditions in which there are negligible aerosol exposures.)

Skin Notation: Absorption through skin, eyes and mucous membranes may contribute significantly to the total exposure.

Mechanical Ventilation: Concentrations in air should be maintained below the occupational exposure limit if unprotected personnel are involved. Use explosion-proof ventilation as required to control vapour concentrations. Local ventilation recommended where mechanical ventilation is ineffective in controlling airborne concentrations below the recommended occupational exposure limit. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is

handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Appearance: Bright Clear
Odour: Hydrocarbon Odour
Odour Threshold: Not available
Freezing/Pour Point: < -47 °C
Boiling Point: 145 - 300 °C
Density: 775 - 840 kg/m³ @ 15 °C
Vapour Density (Air = 1): Not available
Vapour Pressure (absolute): 1 - 1.4 kPa @ 37.8 °C
pH: Not available
Flash Point: TCC > 43 °C
Lower Flammable Limit: 0.7 % (vol.)
Upper Flammable Limit: 5 % (vol.)
Autoignition Temperature: 210 °C
Viscosity: < 8 cSt @ -20 °C
Evaporation Rate (n-BuAc = 1): Not available
Partition Coefficient (log K_{OW}): 3.3 - 6
Water Solubility: Insoluble
Other Solvents: Hydrocarbon Solvents

10. STABILITY AND REACTIVITY

Chemically Stable: Yes
Hazardous Polymerization: No
Sensitive to Mechanical Impact: No
Sensitive to Static Discharge: Yes
Hazardous Decomposition Products: Thermal decomposition products are highly dependent on combustion conditions.
Incompatible Materials: Avoid strong oxidizing agents.
Conditions of Reactivity: Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Kerosene (Petroleum), Hydrodesulfurized	LD50 Oral Rat > 5000 mg/kg
	LD50 Dermal Rabbit > 2000 mg/kg

Ethanol, 2-(2-methoxyethoxy)-	LD50 Oral Rat 4140 - 5180 mg/kg LD50 Dermal Rabbit > 2000 mg/kg
-------------------------------	--

Routes of Exposure:	Exposure will most likely occur through skin contact or inhalation.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Acute Toxicity:	Vapour concentrations above the recommended exposure level are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anesthetic and may have other central nervous system effects.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression.
Feto/Teratogenicity:	A component of this product has shown adverse effects on the growth and development of the fetus in some animal studies.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
Carcinogenicity and Mutagenicity:	The International Agency for Research on Cancer (IARC) considers that this product is not classifiable as to its carcinogenicity to humans. Middle distillates have caused skin cancers in laboratory animals when applied repeatedly and left in place between applications. This effect is believed to be caused by the continuous irritation of the skin. Good personal hygiene should be maintained to avoid this risk. The American Conference of Governmental Industrial Hygienists (ACGIH) has classified this product as A3 - confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May cause physical fouling of aquatic organisms. The immediate effect of a release is the physical impairment of the environment from the coating of surfaces, resulting in the disruption of oxygen, water and light to flora and fauna. Prolonged exposure may result in the partitioning of light-end hydrocarbon fractions into the water and gas phases of the subsurface soil environment, adversely affecting the soil quality.

Biodegradability:	Not readily biodegradable.
Bioaccumulation:	Potential for bioaccumulation. Potential for bioconcentration.
Partition Coefficient (log K_{ow}):	3.3 - 6
Aquatic Toxicity:	Product is expected to be toxic to aquatic organisms.

Ingredient:	Toxicological Data
Kerosene (Petroleum), Hydrodesulfurized	LL50 (WAF method) Rainbow Trout (96hr) 1 - 10 mg/L. EL50 (WAF method) Daphnia Magna (48hr) 1 - 10 mg/L. EL50 - growth rate (WAF method) Algae (72hr) 1 - 10 mg/L.
Ethanol, 2-(2-methoxyethoxy)-	

Definition(s): LL and EL are the lethal loading concentration and effective loading concentration

respectively. The concentration represents the amount of substance added to the system to obtain a toxic concentration. They replace the traditional LC and EC for low solubility substances.

WAF is the water accommodated fraction. A slightly soluble hydrocarbon is stirred into water and the insoluble portions are removed. The remaining solution is the water accommodated fraction.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORT INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1863
Proper Shipping Name	FUEL, AVIATION, TURBINE ENGINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG III
Additional Information	Not Regulated in Containers Less Than or Equal to 450 Litres.
Shipping Description	FUEL, AVIATION, TURBINE ENGINE Class 3 UN1863 PG III Not Regulated in Containers Less Than or Equal to 450 Litres.

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations (CPR)* and the MSDS contains all the information required by the CPR.

WHMIS Class:	Class B3 Combustible Liquid Class D2A Embryo/Fetotoxicity Class D2B Skin Irritation
DSL/NDL Status:	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.
Other Regulatory Status:	No Canadian federal standards. Provincial criteria are likely and should be requested when notifying provincial authorities.

16. OTHER INFORMATION

LABEL STATEMENTS

Hazard Statement :	Combustible Liquid. Irritating to skin.
Handling Statement:	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Avoid prolonged exposure to vapours.
Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated. Changes have been made to: Section
2 Section 3 Section 6 Section 8 Section 11 Section 15

ADG Technology

PERTH

Tel (08) 9249 7599

Fax (08) 9249 7699

BRISBANE

Tel (07) 3271 5900

Fax (07) 3271 5907



Southern Exploration & Drilling Supplies

MELBOURNE

Tel (03) 9545 1277

Fax (03) 9545 1299

INTERNATIONAL

Tel +61 (8) 9249 7599

Fax +61 (8) 9249 7699

Material Safety Data Sheet

Lubtac Rod Grease

PO Box 148,

Kingsway WA 6065



Down hole hammers & bits
Top hole hammer equipment



Diamond drilling
Three cone rotary drill bits
(TCI or Mill Tooth)
Geological supplies
Radio communications
Drag & blade bits
Drilling fluids
Drilling rigs - all types
Elgi air compressors
Augers, teeth,
ground engaging tools
Drill pipe & subs
Geotechnical drilling supplies
International procurement
Machinery parts & equipment



A Smith/Schlumberger Company

M-I Australia Pty Ltd, 11/251 Adelaide Tce, Perth, WA, 6000
Tel: 08 9325 4822 Fax: 08 9325 1897



MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data is obtained from sources beyond our direct supervision. We cannot make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions in which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, neither warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.

For all drilling, mining, geological, geotechnical & radio communications equipment
Web: www.adgtech.com Email: info@adgtech.com



ENVIRONMENTAL AND SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

TRADE NAME: LUBTAC ROD GREASE

GENERIC DESCRIPTION: A MIXTURE OF INORGANIC INERT VISCOSIFIERS, TACKIFIERS, HYDROCARBON OILS AND VEGETABLE OILS.

2. HAZARDOUS INGREDIENTS

MATERIAL COMPONENT	OR	%	DATA
NONE			

3. PHYSICAL DATA

BOILING POINT : 120 °C

MELTING POINT : NA

FREEZING POINT : < 0 °C

pH : 7-8

SPECIFIC GRAVITY : 0.99

APPEARANCE AND : DARK BROWN STRINGY GREASE

4. FIRE AND EXPLOSION DATA

FLASH POINT °C: (AUTO IGNITION TEMPERATURE) > 200 °C

EXTINGUISHING MEDIA : USE EXTINGUISHER USED FOR EXTINGUISHING HYDROPHOBIC MATERIALS

5. HEALTH HAZARD INFORMATION

ROUTES OF EXPOSURE AND EFFECTS

EYES : MODERATE TO SEVERE IRRITATION

**INHALATION : NO IRRITATING FUMES ARE PRODUCED AT NORMAL
TEMPERTURES**

INGESTION : MAY CAUSE NAUSEA

**SKIN : MAY BE IRRITATING TO SENSITIVE SKINS ON
PROLONGED EXPOSURE**

6. EMERGENCY AND FIRST AID PROCEDURES

**EYES : WIPE OUT WITH DRY CLOTH. USE EYE DROPS IF NECESSARY.
OBTAIN MEDICAL ATTENTION IF NECESSARY**

**INHALATION : NO IRRITATING FUMES ARE PRODUCED AT NORMAL
TEMPERATURES**

**INGESTION : WASH MOUTH WITH WATER. INDUCE VOMITING. OBTAIN
MEDICAL ADVICE AS SOON AS POSSIBLE**

**SKIN : WASH WITH SOAPY WATER. IF DEGREASING OF SKIN HAS
OCCURED, APPLY MOISTURISING CREAM**

7. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: EXTREME HEAT

INCOMPATABILITY: NONE

**HAZARDOUS DECOMPOSITION PRODUCTS: CAN PRODUCE HYDROCARBON
DECOMPOSITION PRODUCT ON BURNING.**

**CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION: WILL NOT
OCCUR**

8. SPILL OR LEAK PROCEDURES

CONTAIN SPILL. SCRAPE UP EXCESS PRODUCTS WITH A SPADE. THROW SAND OR WOOD SHAVINGS OVER CONTAMINATED AREA AND SCRAPE UP WITH ASPADE. CONTAMINATED WOOD SHAVINGS OR SAND CAN BE DISCARDED IN ANY RUBBISH STORAGE AREA.

9. INDUSTRIAL HYGEINE CONTROL MEASURES

VENTILATION: **NORMAL**

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY:	NONE
EYES :	NONE
GLOVES :	YES
OTHER :	CLOTHING PROTECTOR AS REQUIRED TO PROTECT CLOTHES FROM GREASE WHICH IS DIFFICULT TO REMOVE.

10. SPECIAL PRECAUTIONS

NONE

11. OTHER HANDLING AND STORAGE REQUIREMENTS

NONE

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300

Salt Lake City, Utah 84119

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dnna.hse@am.dynonobel.com**FOR 24 HOUR EMERGENCY, CALL** CHEMTREC (USA) 800-424-9300
CANUTEC (CANADA) 613-996-6666**MSDS # 1122****Date 01/22/09**

Supersedes

MSDS # 1122 08/13/08

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): NONEL[®] MS
NONEL[®] MS ARCTIC
NONEL[®] LP
NONEL[®] SL
NONEL[®] TD
NONEL[®] MS CONNECTOR
NONEL[®] TWINPLEX[™]
NONEL[®] STARTER

NONEL[®] EZ DET[®]
NONEL[®] EZTL[™]
NONEL[®] EZ DRIFTER[®]

Product Class: NONEL[®] Non-electric Delay Detonators**Product Appearance & Odor:** Aluminum cylindrical shell with varying length and diameter of attached colored plastic tubing. The detonator may be enclosed in a plastic housing, and an assembly may contain two detonators. Odorless.

DOT Hazard Shipping Description: UN0029 Detonators, non-electric 1.1B II
-or- UN0360 Detonator assemblies, non-electric 1.1B II
-or- UN0361 Detonator assemblies, non-electric 1.4B II

NFPA Hazard Classification: Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

Occupational Exposure Limits

Ingredients	CAS#	OSHA PEL-TWA	ACGIH TLV-TWA
Pentaerythritol Tetranitrate (PETN)	78-11-5	None ¹	None ²
Lead Azide	13424-46-9	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Lead	7439-92-1	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Silicon	7440-21-3	15 mg / m ³ (total dust) 5 mg / m ³ (respirable fraction)	10 mg / m ³
Selenium	7782-49-2	0.2 mg/m ³	0.2 mg/m ³
Red Lead (Lead tetroxide)	1314-41-6	0.05 mg (Pb)/m ³	0.05 mg (Pb)/m ³
Titanium dioxide	13463-67-7	15 mg/m ³	10 mg/m ³
Barium Chromate	10294-40-3	1 mg (CrO ₃)/10m ³ (ceiling)	0.01 mg (Cr)/m ³
Lead Chromate	7758-97-6	0.5 mg (Ba)/m ³ 0.05 mg (Pb)/m ³ 1 mg (CrO ₃)/10m ³ (ceiling)	0.5 mg (Ba)/m ³ 0.15 mg (Pb)/m ³ 0.012 mg (Cr)/m ³
Barium Sulfate	7727-43-7	0.5 mg (Ba)/m ³	10 mg/m ³
Potassium Perchlorate ³	7778-74-7	None ¹	None ²
Silica (crystalline)	61790-53-2	See Note Below	0.05 mg/m ³ (resp frac)

Material Safety Data Sheet

Molybdenum	7439-98-7	None ¹	None ²
Tungsten	7440-33-7	None ¹	5 mg/m ³ (TWA) 10 mg/m ³ (STEL)
Aluminum	7429-90-5	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	5 mg/m ³
Antimony	7440-36-0	0.5 mg/m ³	0.5 mg/m ³
Cyclotetramethylene Tetranitramine (HMX)	2691-41-0	None ¹	None ²

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.

² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

Note: The OSHA PEL for crystalline silica is calculated as follows:

Quartz, respirable: $10 \text{ mg/m}^3 \times \% \text{ SiO}_2 + 2$ Quartz, total dust: $30 \text{ mg/m}^3 / \% \text{ SiO}_2 + 2$

³ Not all delay periods contain perchlorate. Those that do contain between from about 4 to a maximum of about 60 mg perchlorate per detonator.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable

Vapor Density: Not Applicable

Percent Volatile by Volume: Not Applicable

Evaporation Rate (Butyl Acetate = 1): Not Applicable

Vapor Pressure: Not Applicable

Density: Not Applicable

Solubility in Water: Not Applicable

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flammable Limits: Not Applicable

Extinguishing Media: (See Special Fire Fighting Procedures section.)

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe, distant location. Allow fire to burn unless it can be fought remotely or with fixed extinguishing systems (sprinklers).

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

This is a packaged product that will not result in exposure to the explosive material under normal conditions of use. Exposure concerns are primarily with post-detonation reaction products, particularly heavy metal compounds.

Eyes: No exposure to chemical hazards anticipated with normal handling procedures. Particulates in the eye may cause irritation, redness, swelling, itching, pain and tearing.

Skin: No exposure to chemical hazards anticipated with normal handling procedures. Exposure to post-detonation reaction products may cause irritation.

Ingestion: No exposure to chemical hazards anticipated with normal handling procedures. Post-detonation reaction product residue is toxic by ingestion. Symptoms may include gastroenteritis with abdominal pain, nausea, vomiting and diarrhea. See systemic effects below.

Material Safety Data Sheet

Inhalation: Not a likely route of exposure. See systemic effects below.

Systemic or Other Effects: None anticipated with normal handling procedures. Repeated inhalation or ingestion of post-detonation reaction products may lead to systemic effects such as respiratory tract irritation, ringing of the ears, dizziness, elevated blood pressure, blurred vision and tremors. Heavy metal (lead) poisoning can occur.

Carcinogenicity: ACGIH classifies Lead as a "Suspected Human Carcinogen" and insoluble Chromium VI as "Confirmed Human Carcinogen". NTP, OSHA, and IARC consider components contained in this detonator carcinogenic.

Perchlorate: Perchlorate can potentially inhibit iodide uptake by the thyroid and result in a decrease in thyroid hormone. The National Academy of Sciences (NAS) has reviewed the toxicity of perchlorate and has concluded that even the most sensitive populations could ingest up to 0.7 microgram perchlorate per kilogram of body weight per day without adversely affecting health. The USEPA must establish a maximum contaminant level (MCL) for perchlorate in drinking water by 2007, and this study by NAS may result in a recommendation of about 20 ppb for the MCL.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: Not applicable.

Special Considerations: None

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions, may explode when subjected to fire, supersonic shock or high-energy projectile impact.

Conditions to Avoid: Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock. Do not attempt to disassemble.

Materials to Avoid (Incompatibility): Corrosives (acids and bases or alkalis).

Hazardous Decomposition Products: Carbon Monoxide (CO), Nitrous Oxides (NO_x), Sulfides, Chromates, Lead (Pb), Antimony (Sb) and various oxides and complex oxides of metals.

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate all personnel to a safe distant area and allow to burn or fight fire remotely. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repack product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. If loose explosive powder is spilled, such as from a broken detonator, only properly qualified and authorized personnel should be involved with handling and clean-up activities. Spilled explosive powder is extremely sensitive to initiation and may detonate. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

Material Safety Data Sheet

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: None required for normal handling. Provide enhanced ventilation after use if in underground mines or other enclosed areas.

Respiratory Protection: None required for normal handling.

Protective Clothing: Cotton gloves are recommended.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State, and local regulations. Only properly qualified and authorized personnel should handle and use explosives. Keep away from heat, flame, ignition sources, impact, friction, electrostatic discharge and strong shock.

Precautions to be taken during use: Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death. Avoid breathing the fumes or gases from detonation of explosives. Detonation in confined or unventilated areas may result in exposure to hazardous fumes or oxygen deficiency.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

Material Safety Data Sheet

SECTION X - SPECIAL INFORMATION

These products contain the following substances that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Max. lbs/1000 units</u>
Lead	7439-92-1	39.4
(Use Toxic Chemical Category Code)		
Lead Compounds	N420	2.0
Barium Compounds	N040	1.8
Chromium Compounds	N090	1.9

Range* of Section 313 Chemicals in each product

Product	lb Pb per 1000 detonators	lb Pb compounds per 1000 detonators	lb Ba compounds per 1000 detonators	lb Cr compounds per 1000 detonators
NONEL [®] MS	0 - 27	0.3 - 1.5	0 - 0.9	0 - 0.9
NONEL [®] LP	0 - 30	0.3 - 2.0	0 - 1.8	0 - 1.9
NONEL [®] SL	7 - 27	0.3 - 1.5	0	0
NONEL [®] TD	0 - 18	0.3 - 0.7	0	0
NONEL [®] MS Connector	5 - 16	0.3 - 0.4	0	0
NONEL [®] TWINPLEX [™]	5 - 15	0.3 - 0.7	0	0
NONEL [®] STARTER	0	0.3	0	0
NONEL [®] EZ DET [®]	22 - 36	2.0	0	0
NONEL [®] EZTL [™]	5 - 15	0.5 - 0.7	0	0
NONEL [®] EZ DRIFTER	39.4	1.3	1.2	1.3

* The exact quantity and weight percent of Section 313 Chemicals in each delay period and tubing length for each product is available upon request.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300

Salt Lake City, Utah 84119

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dnna.hse@am.dynonobel.com**FOR 24 HOUR EMERGENCY, CALL** CHEMTREC (USA) 800-424-9300
CANUTEC (CANADA) 613-996-6666**MSDS # 1063****Date 10/30/08**

Supersedes

MSDS # 1063 07/02/07

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s):

BLASTEX [®]	DYNO [®] 1.5 SB
BLASTEX [®] PLUS	DYNO [®] 1.5 SBC
BLASTEX [®] PLUS HD	DYNO [®] 1.5 SB30
BLASTEX [®] TX	DYNO [®] 900
BLASTEX [®] TX PLUS	DYNO [®] 1300
BLASTGEL [®] 1000	DYNO [®] 1500
BLASTGEL [®] 1070	DYNO [®] 1520
SUPER BLASTEX [®]	DYNO [®] 1540
SUPER BLASTEX [®] TX	DYNOTEX
SUPER BLASTEX [®] TX	DX-2011
	DX-2012

Product Class: Emulsion Explosives, Packaged**Product Appearance & Odor:** White or pink opaque semi-solid, which will appear gray if product contains aluminum.
Little or no odor. Packaged in cylindrical cartridges of paper or plastic film.**DOT Hazard Shipping Description:** UN0332 Explosive, blasting, type E 1.5D II**NFPA Hazard Classification:** Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients:</u>	<u>CAS#</u>	<u>% (Range)</u>	<u>Occupational Exposure Limits</u>	
			<u>ACGIH TLV-TWA</u>	<u>OSHA PEL-TWA</u>
Ammonium Nitrate	6484-52-2	60-85	None	None
Sodium Nitrate	7631-99-4	0-12	None	None
Methylamine Nitrate*	22133-87-7	0-3	None	None
Aluminum	7429-90-5	0-10	10 mg/m ³ (dust)	15 mg/m ³ (total)
Mineral Oil	64742-35-4	0-6	5 mg/m ³ (mist)	None
Kerosene	8008-20-6	0-6	None	None

* This ingredient may be used only in products produced at the Paige Plant.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

Material Safety Data Sheet

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable

Vapor Density: (Air = 1) Not Applicable

Percent Volatile by Volume: <20 (water)

Evaporation Rate (Butyl Acetate = 1): <1

Vapor Pressure: Not Applicable

Density: 1.15-1.35 g/cc

Solubility in Water: Product partially dissolves very slowly in water.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: >100°C

Flammable Limits: Not Applicable

Extinguishing Media: (See Special Fire Fighting Procedures section.)

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

Eyes: May cause irritation, redness and tearing.

Skin: Prolonged contact may cause irritation.

Ingestion: Large amounts may be harmful if swallowed.

Inhalation: Not a likely route of exposure.

Systemic or Other Effects: None known.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least 15 minutes. If irritation persists seek medical attention.

Skin: Remove contaminated clothing. Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: If irritation occurs, remove to fresh air.

Special Considerations: None.

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions, may explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.

Conditions to Avoid: Keep away from heat, flame, ignition sources and strong shock.

Materials to Avoid (Incompatibility): Corrosives (strong acids and strong bases or alkalis).

Hazardous Decomposition Products: Nitrogen Oxides (NO_x), Carbon Monoxide (CO)

Hazardous Polymerization: Will not occur

Material Safety Data Sheet

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate area not less than 2,500 feet in all directions. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Not required for normal handling.

Respiratory Protection: None normally required.

Protective Clothing: Gloves and work clothing that reduce skin contact are suggested.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State and local regulations. Keep away from heat, flame, ignition sources and strong shock.

Precautions to be taken during use: Avoid breathing the fumes or gases from detonation of explosives. Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

SECTION X - SPECIAL INFORMATION

The reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372 may become applicable if the physical state of this product is changed to an aqueous solution. If an aqueous solution of this product is manufactured, processed, or otherwise used, the nitrate compounds category and ammonia listing of the previously referenced regulation should be reviewed.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300

Salt Lake City, Utah 84119

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dnna.hse@am.dynonobel.com**FOR 24 HOUR EMERGENCY, CALL** CHEMTREC (USA) 800-424-9300
CANUTEC (CANADA) 613-996-6666**MSDS # 1019****Date 03/27/07**

Supersedes

MSDS # 1019 01/24/05

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): D-GEL™ 1000
DYNOSPLIT®: D1, D 3/4, D 7/8
EXTRA GELATIN: 40%, 75%
GELAPRIME® F
UNIGEL®
UNIMAX®
VIBROGEL®: 1,3
Z POWDER™
DYNOMAX PRO™

Oil Well Explosive 80%
Oil Well Explosive 100%
STONECUTTER™
REDH® A
RED H® B
POWERGEL D
60% Hi-Pressure Gelatin
IRESPLIT® D
IP: 724, 738

Product Class: Dynamites and Blasting Gelatins**Product Appearance & Odor:** Powdery to gelatinous solid, light tan to dark brown color. Faint, waxy odor.**DOT Hazard Shipping Description:** Explosive, blasting, type A 1.1D UN0081 II**NFPA Hazard Classification:** Not Available (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

<u>Ingredients:</u>	<u>CAS#</u>	<u>% (Range)</u>	<u>Occupational Exposure Limits</u>	
			<u>ACGIH TLV-TWA</u>	<u>OSHA PEL-TWA</u>
Nitroglycerin (NG)	55-63-0	1-20	0.05 ppm	0.05 ppm
Ethylene Glycol Dinitrate (EGDN)	628-96-6	8-76	0.05 ppm	0.05 ppm
Nitrocellulose	9004-70-0	0-6	None	None
Ammonium Nitrate	6484-52-2	0-75	None	None
Sodium Nitrate	7631-99-4	0-50	None	None
Sulfur ¹	7704-34-9	0-4	None	None

¹ This ingredient is not found in most of the products listed above.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable**Vapor Density:** Not Applicable**Percent Volatile by Volume:** Not Applicable**Evaporation Rate (Butyl Acetate = 1):** Not Applicable**Vapor Pressure:** Not Applicable**Density:** 0.8-1.48 g/cc**Solubility in Water:** Ammonium and sodium nitrates are completely soluble. NG and EGDN are very slightly soluble.

Material Safety Data Sheet

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flammable Limits: Not Applicable

Extinguishing Media: (See Special Fire Fighting Procedures section.)

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

Eyes: May cause irritation, redness and tearing.

Skin: Contact may result in headache, nausea and blood vessel dilation.

Ingestion: May result in headache, nausea, intestinal upset and blood vessel dilation.

Inhalation: May result in headache, nausea and blood vessel dilation.

Systemic or Other Effects: None known.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Remove contaminated clothing. Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: Remove to fresh air. If irritation persists, seek medical attention.

Special Considerations: None.

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions. May explode when subjected to fire, supersonic shock, or high-energy projectile impact, especially when confined or in large quantities.

Conditions to Avoid: Keep away from heat, flame, ignition sources and strong shock.

Materials to Avoid (Incompatibility): Corrosives (mineral acids, bases, strong acids).

Hazardous Decomposition Products: Carbon Monoxide (CO), Hydrogen Sulfide (H₂S), Nitrous Oxides (NO_x), and Sulfur Oxides (SO_x).

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate area not less than 2,500 feet in all directions. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. Follow applicable Federal, State, and local spill reporting requirements. Contact of this product with water may result in a reportable release.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

Material Safety Data Sheet

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Forced ventilation may be necessary where natural ventilation is limited. Magazines containing NG and/or EGDN based explosives must be ventilated before entry.

Respiratory Protection: None normally required.

Protective Clothing: Chemical resistant (nitrile) gloves are suggested.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: Inhalation and skin contact should be minimized to avoid headaches, nausea, and blood vessel dilation. Protective clothing should be changed daily, more often if contaminated.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State, and local regulations. Keep away from heat, flame, ignition sources, and strong shock.

Precautions to be taken during use: Avoid breathing the fumes or gases from detonation of explosives. Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

SECTION X - SPECIAL INFORMATION

Chemical Name

Nitroglycerin

CAS Number

55-63-0

% By Weight

1-20

The reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR 372 may become applicable if the physical state of this product is changed to an aqueous solution. If an aqueous solution of this product is manufactured, processed, or otherwise used, the nitrate compounds category and ammonia listing of the previously referenced regulation should be reviewed.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: February 15, 2007
8750 – 53rd Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **POTASSIUM CHLORIDE (POTASH)**

PRODUCT USE: Oil well drilling fluid and cement additive.
CHEMICAL FAMILY: Inorganic salt CAS#: 7447-40-7

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not WHMIS controlled.
WORKPLACE HAZARD: Treat as nuisance dust.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀ Oral-Rat</u>	<u>LC₅₀ Inhal-Rat</u>	<u>ACGIH-TLV</u>
Contains no WHMIS controlled ingredients.					

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [XX]EYE CONTACT []SKIN []INHALATION []INGESTION
EYE CONTACT: May cause mild irritation, including stinging, watering and redness.
SKIN CONTACT: May cause mild irritation including redness and a burning sensation.
Prolonged or repeated contact may cause dry skin. No information available on skin absorption.
INGESTION: Low to moderate degree of toxicity. LD₅₀ (oral-rat) = 2.6 g/kg.
INHALATION: High dust levels may cause upper respiratory tract irritation.
CARCINOGENICITY: No information available.
TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.
MUTAGENICITY: No information available.
SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Flush with water. Dry area thoroughly and apply skin cream or moisturizing cream. If irritation persists, obtain medical attention.
EYE CONTACT: Flush with gently flowing warm water for 15 minutes, or until irritation ceases. Hold eyelids open to ensure thorough flushing. If irritation persists, obtain medical attention.
INGESTION: Do not induce vomiting unless directed to do so by medical personnel. If large amount swallowed, obtain medical attention.
INHALATION: Move to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties, or distress, continue obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR: White to reddish-brown crystals; odourless
SPECIFIC GRAVITY: 2.0
BOILING POINT (°C): 1500 (sublimes)
MELTING POINT (°C): 773
SOLUBILITY IN WATER: 342 g/L @ 20°C pH: 8-9 (5% sol'n)
PERCENT VOLATILE BY VOLUME: 0
EVAPORATION RATE: Not applicable
VAPOUR PRESSURE (mmHg): ~0
VAPOUR DENSITY (air = 1): 2.57
BULK DENSITY: Loose; 1025 – 1200 kg/m³

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not flammable
FLAMMABLE LIMITS: Not applicable
EXTINGUISHING MEDIA: Use media suitable for surrounding materials and packaging.
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with hot nitric acid; may cause evolution of toxic nitrosyl chloride. Contact with other strong acids may produce hydrogen chloride gas. May react violently with bromine trifluoride and may explode if mixed with potassium permanganate and sulfuric acid.	
CONDITIONS OF REACTIVITY:	Contact with incompatible materials.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Hydrogen chloride and fumes of Na ₂ O.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	Use NIOSH approved dust mask, or respirator with dust/mist filters, if TLV is exceeded. 8 hour OEL Nuisance Dust Total Mass = 10mg/m ³ .
VENTILATION:	Suggest local exhaust ventilation, if TLV's are exceeded.
PROTECTIVE GLOVES:	Suggest cloth or leather work gloves be worn to prevent skin contact.
EYE PROTECTION:	Safety glasses with side shields or goggles recommended.
OTHER PROTECTIVE EQUIPMENT (Specify):	Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Store in a cool, dry well-ventilated place away from incompatibles. Keep bags or fibre drums dry at all times. Product is hygroscopic (may absorb moisture from the air when relative humidity >72%).

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Collect by sweeping and scoop up or shovel. Collect uncontaminated material for repackaging. Collect contaminated material in an approved container for disposal. Keep out of sewers, storm drains, surface waters and soils.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. This product may be suitable for disposal in landfills; check with local operator. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Dispose of all packaging in accordance with local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: February 15, 2007
SUPERSEDES: April 27, 2004

BY: Product safety committee
PHONE: 780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**



MATERIAL SAFETY DATA SHEET

MSDS No. 10068

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: POLY-PLUS* RD

Chemical Family: Acrylamide polymer.
Product Use: Drilling fluid additive.

Supplied by: M-I L.L.C.
P.O. Box 42842
Houston, TX 77242
www.miswaco.com

Telephone Number: 281-561-1511
Emergency Telephone (24 hr.): 281-561-1600
Prepared by: Product Safety Group

Revision No. 5

HMIS Rating

Health: 1 **Flammability:** 1 **Physical Hazard:** 0 **PPE:** E

4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal Hazard. *Chronic effects - See Section 11. See Section 8 for Personal Protective Equipment recommendations.

2. HAZARDS IDENTIFICATION

Emergency Overview: Caution! May cause mechanical irritation of eyes, skin and respiratory tract. Long term inhalation of particulates may cause lung damage.

Canadian Classification:

UN PIN No: Not regulated.

WHMIS Class: Not a controlled product.

Physical State: Powder.

Color: White

Odor: Odorless

Potential Health Effects:

Acute Effects

Eye Contact: May cause mechanical irritation
Skin Contact: May cause mechanical irritation.
Inhalation: May cause mechanical irritation.
Ingestion: May cause gastric distress, nausea and vomiting if ingested.

Acute Effects Note:

This product may release ammonia or amines when heated or exposed to high pH. Ammonia is a severe eye, skin and respiratory irritant. Ammonia has a very strong odor and can be detected at levels as low as 5 ppm. Many amines are also eye, skin and respiratory irritants.

Carcinogenicity & Chronic Effects: See Section 11 - Toxicological Information.

Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.

MATERIAL SAFETY DATA SHEET

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

MSDS No. 10068

Page 2/6

Target Organs/Medical Conditions Aggravated by Overexposure: Eyes. Skin. Respiratory System.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Wt. %	Comments:
Anionic acrylamide copolymer		90 - 100	No comments.

4. FIRST AID MEASURES

Eye Contact: Promptly wash eyes with lots of water while lifting eye lids. Look for and remove contact lenses. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact: Wash skin thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if any discomfort continues.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Dilute with 2 - 3 glasses of water or milk, if conscious. Never give anything by mouth to an unconscious person. If signs of irritation or toxicity occur seek medical attention.

General notes: Persons seeking medical attention should carry a copy of this MSDS with them.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: F (C): NA

Flammable Limits in Air - Lower (%): ND

Flammable Limits in Air - Upper (%): ND

Autoignition Temperature: F (C): ND

Flammability Class: NA

Other Flammable Properties: Particulate may accumulate static electricity. Dusts at sufficient concentrations can form explosive mixtures with air.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Do not enter fire area without proper personal protective equipment, including NIOSH/MSHA approved self-contained breathing apparatus. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and waterways.

Hazardous Combustion Products: Ammonia or amines. Oxides of: Carbon. Nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment identified in Section 8.

MATERIAL SAFETY DATA SHEET

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

MSDS No. 10068

Page 3/6

Spill Procedures: Evacuate the spill area with the exception of the spill response team. Wet product may create a slipping hazard. Contain spilled material. Do not allow spilled material to enter sewers, storm drains or surface waters. Avoid the generation of dust. Sweep, vacuum, or shovel and place into closable container for disposal.

Environmental Precautions: Waste must be disposed of in accordance with federal, state and local laws.

7. HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid generating or breathing dust. Product is slippery if wet. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Store in dry, well-ventilated area. Keep container closed. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits (TLV & PEL - 8H TWA):

Ingredient	CAS No.	Wt. %	ACGIH TLV	OSHA PEL	Other	Notes
Anionic acrylamide copolymer		90 - 100	NA	NA	NA	(1) (6)

Notes

(1) Control as an ACGIH particulate not otherwise specified (PNOS): 10 mg/m³ (Inhalable); 3 mg/m³ (Respirable) and an OSHA particulate not otherwise regulated (PNOR): 15 mg/m³ (Total); 5 mg/m³ (Respirable).

(6) Ammonia or amines may be released when this component is heated or exposed to high pH. The recommended exposure limits for ammonia are ACGIH TLV 25 ppm and OSHA PEL 50 ppm. No general recommended exposure limit is available for amines. A NIOSH/MSHA approved respirator with ammonia/methylamine cartridges should be used to protect against ammonia or amine inhalation exposure.

Engineering Controls: Use appropriate engineering controls such as, exhaust ventilation and process enclosure, to ensure air contamination and keep workers exposure below the applicable limits.

Personal Protection Equipment

All chemical Personal Protective Equipment (PPE) should be selected based on an assessment of both the chemical hazards present and the risk of exposure to those hazards. The PPE recommendations below are based on our assessment of the chemical hazards associated with this product. The risk of exposure and need for respiratory protection will vary from workplace to workplace and should be assessed by the user.

Eye/Face Protection: Dust resistant safety goggles.

Skin Protection: Not normally necessary. If needed to minimize irritation: Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear chemical resistant gloves such as: Nitrile. Neoprene.

MATERIAL SAFETY DATA SHEET

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

MSDS No. 10068

Page 4/6

Respiratory Protection:

All respiratory protection equipment should be used within a comprehensive respiratory protection program that meets the requirements of 29 CFR 1910.134 (U.S. OSHA Respiratory Protection Standard) or local equivalent.

If exposed to airborne particles of this product use at least a NIOSH-approved N95 half-mask disposable or re-useable particulate respirator. In work environments containing oil mist/aerosol use at least a NIOSH-approved P95 half-mask disposable or re-useable particulate respirator.

General Hygiene Considerations: Work clothes should be washed separately at the end of each work day. Disposable clothing should be discarded, if contaminated with product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	White
Odor:	Odorless
Physical State:	Powder.
pH:	7.7 (1% solution)
Specific Gravity (H ₂ O = 1):	1.25 - 1.40 at 68F (20C)
Solubility (Water):	Soluble
Melting/Freezing Point:	ND
Boiling Point:	ND
Vapor Pressure:	NA
Vapor Density (Air=1):	NA
Evaporation Rate:	NA
Odor Threshold(s):	ND

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions to Avoid:	Heat. Moisture.
Materials to Avoid:	Oxidizers.
Hazardous Decomposition Products:	For thermal decomposition products, see Section 5.
Hazardous Polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

Component Toxicological Data: Any adverse component toxicological effects are listed below. If no effects are listed, no such data were found.

Ingredient	CAS No.	Acute Data
Anionic acrylamide copolymer		Oral LD50: Estimated >2000 mg/kg (rat)

Product Toxicological Information:

Long term inhalation of particulate can cause irritation, inflammation and/or permanent injury to the lungs. Illnesses such as pneumoconiosis ("dusty lung"), pulmonary fibrosis, chronic bronchitis, emphysema and bronchial asthma may develop.

This product may contain trace amounts of acrylamide (< 0.1%). Acrylamide (CAS 79-06-1) has been classified by the International Agency for Research on Cancer (IARC) as a Group 2A carcinogen (probably carcinogenic to humans) and a suspect carcinogen by the National Toxicology Program (NTP). (LOLI)

MATERIAL SAFETY DATA SHEET

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

MSDS No. 10068

Page 5/6

12. ECOLOGICAL INFORMATION

Component Ecotoxicity Data: Component ecotoxicity data are listed below. If no data are listed, none was found in the component review.

Product Ecotoxicity Data: Contact M-I Environmental Affairs Department for available product ecotoxicity data.

Biodegradation: ND

Bioaccumulation: ND

Octanol/Water Partition Coefficient: ND

13. DISPOSAL CONSIDERATIONS

Waste Classification: ND

Waste Management: Under U.S. Environmental Protection Agency (EPA) Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user to determine at the time of disposal, whether the product meets RCRA criteria for the hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting materials hazardous. Empty containers retain residues. All labeled precautions must be observed.

Disposal Method: Recover and reclaim or recycle, if practical. Should this product become a waste, dispose of in a permitted industrial landfill. Ensure that the containers are empty by the RCRA criteria prior to disposal in a permitted industrial landfill.

14. TRANSPORT INFORMATION

U.S. DOT Shipping Description:	Not regulated for transportation by DOT, TDG, IMDG, ICAO/IATA.
Canada TDG Shipping Description:	Not regulated.
UN PIN No:	Not regulated.
IMDG Shipping Description:	Not regulated.
ICAO/IATA Shipping Description:	Not regulated.

15. REGULATORY INFORMATION

U.S. Federal and State Regulations

SARA 311/312 Hazard Categories: Not a SARA 311/312 hazard.

SARA 302/304, 313; CERCLA RQ, California Proposition 65: Note: If no components are listed below, this product is not subject to the referenced SARA and CERCLA regulations and is not known to contain a Proposition 65 listed chemical at a level that is expected to pose a significant risk under anticipated use conditions.

International Chemical Inventories

MATERIAL SAFETY DATA SHEET

Trade Name: POLY-PLUS* RD

Revision Date: 06/03/2009

MSDS No. 10068

Page 6/6

Australia AICS - Components are listed or exempt from listing.
Canada DSL - Components are listed or exempt from listing.
China Inventory - Components are listed or exempt from listing.
European Union EINECS/ELINCS - Components are listed or exempt from listing.
Japan METI ENCS - Components are listed or exempt from listing.
Korea TCCL ECL - Components are listed or exempt from listing.
New Zealand - Components are listed or exempt from listing.
Philippine PICCS - Components are listed or exempt from listing.
U.S. TSCA - Components are listed or exempt from listing.
U.S. TSCA - No components are subject to TSCA 12(b) export notification requirements.

Canadian Classification:

Controlled Products Regulations Statement: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Class: Not a controlled product.

16. OTHER INFORMATION

The following sections have been revised: 1, 4, 6, 15, 16

NA - Not Applicable, ND - Not Determined.

*A mark of M-I L.L.C.

Disclaimer:

MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data are obtained from sources beyond our direct supervision. We can not make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions under which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, no warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.



MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE

Revision Date: 07/21/2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: ROD EASE

Chemical Family: Mixture

Product Use: Drilling fluid additive. Lubricant.

Supplied by: M-I L.L.C.
P.O. Box 42842
Houston, TX 77242
www.miswaco.com

Telephone Number: 281-561-1511

Emergency Telephone (24 hr.): 281-561-1600

Prepared by: Product Safety Group

Revision No. 6

HMIS Rating

Health: 1

Flammability: 1

Physical Hazard: 0

PPE: J

4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal Hazard. *Chronic effects - See Section 11. See Section 8 for Personal Protective Equipment recommendations.

2. HAZARDS IDENTIFICATION

Emergency Overview: Occupational exposure not expected to present a health or physical hazard. Prolonged exposure, however, may cause eye, skin and respiratory irritation.

Canadian Classification:

UN PIN No: Not regulated.

WHMIS Class: Not a controlled product.

Physical State: Thick Liquid

Color: Dark brown.

Odor: Distinctive

Potential Health Effects:

Acute Effects

Eye Contact: Not expected to irritate eyes. Prolonged contact, however, may cause irritation.

Skin Contact: Not expected to irritate skin. Prolonged contact, however, may cause irritation.

Inhalation: Not expected to be an inhalation hazard. Prolonged inhalation of vapors or mists, however, may cause irritation.

Ingestion: May cause gastric distress, nausea and vomiting if ingested.

Carcinogenicity & Chronic Effects: See Section 11 for additional information.

Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.

Target Organs/Medical Conditions Aggravated by Overexposure: None expected from occupational exposure.

MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE
Revision Date: 07/21/2009

Page 2/6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Wt. %	Comments:
Vegetable oil		60 - 100	No comments.
Additives		10 - 30	No comments.

4. FIRST AID MEASURES

Eye Contact: Promptly wash eyes with lots of water while lifting eye lids. Look for and remove contact lenses. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact: Wash skin thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if any discomfort continues.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Dilute with 2 - 3 glasses of water or milk, if conscious. Never give anything by mouth to an unconscious person. Get medical attention.

General notes: Persons seeking medical attention should carry a copy of this MSDS with them.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: F (C): 734F (390C)
Flash Point Method: COC
Flammable Limits in Air - Lower (%): ND
Flammable Limits in Air - Upper (%): ND
Autoignition Temperature: F (C): ND
Flammability Class: IIIB
Other Flammable Properties: ND
Extinguishing Media: Carbon dioxide. Dry chemical. Foam. Water mist.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Do not enter fire area without proper personal protective equipment, including NIOSH/MSHA approved self-contained breathing apparatus. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and waterways.

Hazardous Combustion Products: Oxides of Carbon. Sulfur.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment identified in Section 8.

Spill Procedures: Evacuate the spill area with the exception of the spill response team. Keep personnel removed and upwind of spill. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Shut off leak if it can be done safely. Contain spilled material. Do not allow spilled material to enter sewers, storm drains or surface waters. Absorb in vermiculite, dry sand or earth. Place into containers for disposal.

MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE
Revision Date: 07/21/2009

Page 3/6

Environmental Precautions: Waste must be disposed of in accordance with federal, state and local laws. In the U.S., for products with reportable quantity (RQ) components - if the RQ is exceeded, report to National Spill Response Office at 1 800 424 8802.

7. HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid breathing vapors or spray mists. Use only in a well ventilated area. Wash thoroughly after handling.

Storage: Store in dry, well-ventilated area. Keep container closed. Keep away from heat, sparks and flames. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits (TLV & PEL - 8H TWA):

Ingredient	CAS No.	Wt. %	ACGIH TLV	OSHA PEL	Other	Notes
Vegetable oil		60 - 100	NA	NA	NA	(1)
Additives		10 - 30	NA	NA	NA	None

Notes

(1) Control as an ACGIH particulate not otherwise specified (PNOS): 10 mg/m³ (Inhalable); 3 mg/m³ (Respirable) and an OSHA particulate not otherwise regulated (PNOR): 15 mg/m³ (Total); 5 mg/m³ (Respirable).

Engineering Controls: Local exhaust ventilation as necessary to maintain exposures to within applicable limits.

Personal Protection Equipment

All chemical Personal Protective Equipment (PPE) should be selected based on an assessment of both the chemical hazards present and the risk of exposure to those hazards. The PPE recommendations below are based on our assessment of the chemical hazards associated with this product. The risk of exposure and need for respiratory protection will vary from workplace to workplace and should be assessed by the user.

Eye/Face Protection: Wear chemical safety goggles.

Skin Protection: Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear chemical resistant gloves such as nitrile or neoprene.

Respiratory Protection: All respiratory protection equipment should be used within a comprehensive respiratory protection program that meets the requirements of 29 CFR 1910.134 (U.S. OSHA Respiratory Protection Standard) or local equivalent. If exposed to airborne mist/aerosol of this product, use at least a NIOSH-approved N95 half-mask disposable or re-usable particulate respirator. In work environments containing oil mist/aerosol, use at least a NIOSH-approved P95 half-mask disposable or reuseable particulate respirator.

General Hygiene Considerations: Wash promptly with soap and water if skin becomes contaminated. Change work clothing daily if there is any possibility of contamination.

9. PHYSICAL AND CHEMICAL PROPERTIES

MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE
Revision Date: 07/21/2009

Page 4/6

Color:	Dark brown.
Odor:	Distinctive
Physical State:	Thick Liquid
pH:	7 - 7.5
Specific Gravity (H ₂ O = 1):	0.887
Solubility (Water):	ND
Flash Point: F (C):	734F (390C)
Melting/Freezing Point:	-13F (-25C)
Boiling Point:	>572F (>300C)
Vapor Pressure:	ND
Vapor Density (Air=1):	ND
Evaporation Rate:	ND
Odor Threshold(s):	ND

10. STABILITY AND REACTIVITY

Chemical Stability:	Stable
Conditions to Avoid:	Keep away from heat, sparks and flame.
Materials to Avoid:	Oxidizers.
Hazardous Decomposition Products:	For thermal decomposition products, see Section 5.
Hazardous Polymerization	Will not occur

11. TOXICOLOGICAL INFORMATION

Component Toxicological Data: Any adverse component toxicological effects are listed below. If no effects are listed, no such data were found.

Product Toxicological Information:

Oral LD50: >5000 mg/kg (rat).

12. ECOLOGICAL INFORMATION

Component Ecotoxicity Data: Component ecotoxicity data are listed below. If no data are listed, none was found in the component review.

Product Ecotoxicity Data: Contact M-I Environmental Affairs Department for available product ecotoxicity data.

Biodegradation:	ND
Bioaccumulation:	ND
Octanol/Water Partition Coefficient:	ND

13. DISPOSAL CONSIDERATIONS

Waste Classification: This product does not meet the criteria of a hazardous waste if discarded in its purchased form.

MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE

Revision Date: 07/21/2009

Page 5/6

Waste Management: Under U.S. Environmental Protection Agency (EPA) Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user to determine at the time of disposal, whether the product meets RCRA criteria for the hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting materials hazardous. Empty containers retain residues. All labeled precautions must be observed.

Disposal Method: Recover and reclaim or recycle, if practical. Should this product become a waste, dispose of in a permitted industrial landfill. Ensure that the containers are empty by the RCRA criteria prior to disposal in a permitted industrial landfill.

14. TRANSPORT INFORMATION

U.S. DOT

Shipping Description:

Not regulated for transportation by DOT, TDG, IMDG, ICAO/IATA.

Canada TDG Shipping Description:

Not regulated.

UN PIN No:

Not regulated.

IMDG Shipping Description:

Not regulated.

ICAO/IATA Shipping Description:

Not regulated.

15. REGULATORY INFORMATION

U.S. Federal and State Regulations

SARA 311/312 Hazard Categories: Immediate (acute) health hazard.

SARA 302/304, 313; CERCLA RQ, California Proposition 65: Note: If no components are listed below, this product is not subject to the referenced SARA and CERCLA regulations and is not known to contain a Proposition 65 listed chemical at a level that is expected to pose a significant risk under anticipated use conditions.

International Chemical Inventories

Australia AICS - Components are listed or exempt from listing.
Canada DSL - Components are listed or exempt from listing.
China Inventory - Components are listed or exempt from listing.
European Union EINECS/ELINCS - Components are listed or exempt from listing.
Japan METI ENCS - Components are listed or exempt from listing.
Korea TCCL ECL - Components are listed or exempt from listing.
New Zealand - Components are listed or exempt from listing.
Philippine PICCS - Components are listed or exempt from listing.
U.S. TSCA - Contains a component(s) that is not listed.
U.S. TSCA - No components are subject to TSCA 12(b) export notification requirements.

Canadian Classification:

Controlled Products Regulations Statement: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Class: Not a controlled product.

16. OTHER INFORMATION

The following sections have been revised: 1, 4, 6, 15, 16

MATERIAL SAFETY DATA SHEET

MSDS No. 12011

Trade Name: ROD EASE

Revision Date: 07/21/2009

Page 6/6

NA - Not Applicable, ND - Not Determined.

Disclaimer:

MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data are obtained from sources beyond our direct supervision. We can not make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions under which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, no warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.

Material Safety Data Sheet

Dyno Nobel Inc.

2650 Decker Lake Boulevard, Suite 300

Salt Lake City, Utah 84119

Phone: 801-364-4800 Fax: 801-321-6703

E-Mail: dnna.hse@am.dynonobel.com**FOR 24 HOUR EMERGENCY, CALL** CHEMTREC (USA) 800-424-9300

CANUTEC (CANADA) 613-996-6666

MSDS # 1124**Date 08/13/08**

Supersedes

MSDS # 1124 01/24/05

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): NONEL[®] LEAD LINE**Product Class:** Shock Tube**Product Appearance & Odor:** Hollow plastic tubing (normally yellow) with dusty inner coating of HMX and aluminum. No detectable odor.**DOT Hazard Shipping Description:****UN0349** Articles, explosive, n.o.s. (HMX) 1.4S II.

For 10,000 ft spools with Wire Lock Terminations only:

Not regulated as an explosive, 0000

NFPA Hazard Classification: Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

Ingredients:	CAS#	% (Range)	<u>Occupational Exposure Limits</u>	
			OSHA PEL-TWA	ACGIH TLV-TWA
Cyclotetramethylene	2691-41-0	0.35	None ¹	None ²
Tetranitramine (HMX)				
Aluminum (dust)	7429-90-5	0.04	15 mg/m ³ (total) 5 mg/m ³ (respirable)	10 mg/m ³

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

Note: The above hazardous dust mixture is present at approximately 15 mg per meter of tubing.

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable**Vapor Density:** Not Applicable**Melting Point:** HMX decomposes violently at melting pt., about 278°C**Evaporation Rate (Butyl Acetate = 1):** Not Applicable**Vapor Pressure:** Not Applicable**Density:** Not Applicable**Solubility in Water:** Not Soluble**Percent Volatile by Volume:** Not Applicable

Material Safety Data Sheet

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable

Flammable Limits: Not Applicable

Extinguishing Media: Water, inert powder, CO₂

Special Fire Fighting Procedures: For shock tube only, consider initial isolation of at least 15 meters (50 feet) in all directions. Fight fire with normal precautions and methods used for plastic fires from a reasonable distance. IF DETONATORS OR OTHER EXPLOSIVES ARE PRESENT, DO NOT FIGHT FIRE.

Unusual Fire and Explosion Hazards: May burn vigorously with localized detonations and projection of fragments, with effects usually confined to the immediate vicinity of packages. Toxic smoke from combustion of the plastic material may be emitted. If product functions, high heat and pressure are released from the end of the tube if not covered or enclosed, typically by a metal device.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

This is a packaged product that will not result in exposure to hazardous ingredients (inner coating materials) under normal conditions of use.

Eyes: Not a likely route of exposure. Dust particles may be irritating.

Skin: Not a likely route of exposure. Dust particles may cause skin irritation.

Ingestion: Not a likely route of exposure. Ingestion of large amounts of the reactive powder (HMX) is poisonous and may cause cardiovascular collapse.

Inhalation: Not a likely route of exposure. Breathing dust can cause respiratory irritation. During manufacture and at processing temperatures, irritating fumes may evolve.

Systemic or Other Effects: None known.

Carcinogenicity: No constituents are listed by NTP, IARC or OSHA.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Ingestion: Not Applicable

Inhalation: Not Applicable

Special Considerations: None.

SECTION VI - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Keep away from heat, flame, impact, friction, ignition sources and strong shocks. Also avoid stretching to failure.

Materials to Avoid (Incompatibility): Incompatible with strong oxidizers and acids.

Hazardous Decomposition or Combustion Products: Hazardous carbon monoxide (CO), nitrogen oxide (NO_x) gases and products of plastic decomposition produced.

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate area not less than 50 feet in all directions. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, repackage undamaged devices in original packaging, accounting for every device. If the ends or tube wall have been opened such that powder may have

Material Safety Data Sheet

been released from the tube, isolate the spill area. Contamination of the HMX/Aluminum powder with sand, grit or dirt will render the material more sensitive to detonation. Carefully wet down and clean "loose" powder spills using a damp sponge or rag, avoid applying friction or pressure to the explosive, and place in a (Velostat) electrically conductive bag. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: None normally required. Provide enhanced ventilation if used in underground mines, indoors or other enclosed areas.

Respiratory Protection: None normally required. Extended testing of the product indoors or in enclosed areas may necessitate respiratory protection.

Protective Clothing: None normally required. Wear chemical-resistant gloves during post-detonation cleanup or spill cleanup operations.

Eye Protection: Safety glasses or goggles are recommended for handling, testing or cleanup.

Other Precautions Required: None

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State, and local regulations. Keep away from heat, flame, ignition sources and strong shock. Only properly qualified and authorized personnel should handle and use Shock Tube.

Precautions to be taken during use: Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death. Avoid breathing the fumes or gases from detonation of explosives. Detonation in confined or unventilated areas may result in exposure to hazardous fumes or oxygen deficiency.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

SECTION X - SPECIAL INFORMATION

This product contains the following substances that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

<u>Chemical Name</u>	<u>CAS Number</u>	<u>% By Weight</u>
None		

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.

MATERIAL SAFETY DATA SHEET

Soda Ash

Date: November 4, 2005

I Company Identification

Company Name: BHS Marketing / Western Briquette
Mailing Address: P.O. Box 27955 SLC, UT 84127-0955
Physical Address: 2320 West Indiana Ave. SLC, UT 84104
Telephone: (801) 973-8232
Fax: (801) 973-8838
Emergency Number: PERS (800) 633-8253

II Product Identification

Product Name: Soda Ash
Product Class: 55
Chemical Description: Sodium Carbonate, anhydrous, is a white odorless, granular material, free of contamination. Meets federal specification O-S-571 G, Type II. Meets AWWA Std.
Cas Number: 497-19-8

III Typical Physical Properties

Physical Appearance: White granules solid
Odor: Odorless
Molecular Weight: 105.99
pH: 11.3 at 1wt/wt%
Boiling Point: Decomposes at 1800 F
Melting Point: 851 Deg C (1564 F)
Specific Gravity: 2.53 at (68F)
Solubility in Water: Soluble 7wt/wt% at (77 F)

IV Reactivity Data

Chemical Stability:	This material is stable under normal handling and storage conditions
Conditions to Avoid:	Extreme Heat
Materials to Avoid:	Aluminum, Fluorine, Humid Air, Moisture, Sulfuric Acid, Acids, Magnesium, Phosphorus Pentoxide
Hazardous Decomposition Products:	Carbon Dioxide
Hazardous Polymerization:	Will not occur
Decomposition Temperature Range:	400 Deg. C (752 Deg F)

V Toxicological Information and Interpretation

Acute	
Eye irritation:	Eye-Eye irritation, 50 mg Rabbit. Severely irritating
Skin Irritation:	Skin-Skin irritation, Rabbit. Mildly irritating
Dermal Toxicity:	No test data found for Product
Respiratory Irritation:	No test data found for Product.
Acute Inhalation Toxicity:	LC50-Lethal concentration. 50% of Test Species, 2300 mg/cu m/2hrs, rat
Acute Oral Toxicity:	LD50-Lethal Dose. 50% of Test Species, 4090 mg/kg, rat
Chronic Toxicity:	This product does not contain any substances that are considered by OSHA, NTP, IARC or ACGIH to be "probable" or "suspected" human carcinogens

VII Fire and Explosion Hazard Data

Effects of Overexposure:

Acute

Eye Contact:	Causes Irritation.
Skin Contact:	May cause redness, swelling
Ingestion:	Low acute oral toxicity. May cause nausea, vomiting, diarrhea, irritation, corrosion.
Inhalation:	May cause upper respiratory tract irritation, lung irritation
Chronic Effects:	This product does not contain any ingredient designated by IARC, NTP, ACGIH, OSHA as probable or suspected human carcinogens.

VIII Recommended First Aid Measures

Eye Exposure:	Hold eyelids open and flush with a steady, gentle stream of water for at least 15 mins. Seek immediate medical attention.
Skin Exposure:	In case of contact, immediately wash with plenty of soap and water for at least 5 mins. Seek medical attention if irritation develops or persists. Remove contaminated clothing and shoes. Clean contaminated clothing and shoes before re-use.
Inhalation Exposure	Remove and assure that the victim is breathing. If breathing is difficult, administer oxygen, if available. If victim is not breathing, administer CPR (cardio-pulmonary resuscitation). Seek immediate medical attention.
Ingestion Exposure:	If victim is conscious and alert, give 1-2 glasses of water to drink. Do not give anything by mouth to an unconscious person. Seek immediate medical attention. Do not leave victim unattended. To prevent aspiration of swallowed product, lay victim on side with head lower than waist. Vomiting may occur spontaneously. If vomiting occurs and the victim is conscious, give water to further dilute the chemical.
Medical conditions possible aggravated by exposure:	Inhalation of product may aggravate existing chronic respiratory problems such as asthma emphysema or bronchitis. Skin contact may aggravate existing skin disease.
Notes to Physician:	All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

IX Fire Fighting Measures

Extinguishing Media:	Not combustible. Use extinguishing methods suitable for surrounding fire.
Special Fire Fighting Procedures:	Firefighters should wear NIOSH/MSHA approved self-contained breathing apparatus and full protective clothing. Dike area top prevent runoff and contamination of water sources. Dispose of fire control water later.
Unusual Fire and Explosion Hazard:	Not combustible

X Accidental Release Measures

Evacuation Procedure & Safety:	Ventilate closed spaces before entering. Wear appropriate protective gear for situation. See personal information.
Containment of Spills:	Follow Procedure described below under Cleanup and Disposal of spill
Environmental & Regulatory Reporting:	Do not flush to drain. If spilled on the ground, the affected area should be scraped clean placed in an appropriate container for disposal. Prevent material from entering public sewer system or any waterway. Large spills should be handled according to a predetermined plan. For assistance in developing a plan contact with the Technical Service Department using the Product Information phone number.

XI Handling & Storage

Handling:	Do not get in eyes. Do not breath dusts. Avoid direct or prolonged contact with skin.
Storage:	Store in area that is cool, dry, well-ventilated.

XII Exposure Controls/ Personal Protection

Appropriate

Hygienic Practices:
procedure,
prompt

As part of good industrial, personal hygiene and safety avoid all unnecessary exposure to the product and ensure removal from eyes, skin and clothing. Maintain good housekeeping to control dust accumulations.

Personal Protection Equipment

Eye Protection:

Eye and face protection requirements will vary dependent upon work environment conditions and material handling practices. Appropriate ANSI Z87 approved equipment should be selected for the particular use intended for this material.

Skin Protection:

Skin contact should be minimized through use of gloves and suitable long-sleeved clothing (i.e. shirts and pants.) Consideration must be give both to durability as well as permeation resistance.

XIII Ecological Information

Acute Ecotoxicity:

Crustaceans, Daphnia magna, EC₅₀, 48 hours, 265 mg/l
Fishes, Lepomis macrochirus, LC₅₀ 96 hours, 300 mg/l
Algae, Nitzscheria linearis, EC₅₀, 5 day(s), 242 mg/l

Chronic Ecotoxicity:

Phytoplankton, EC biomass, 7 day(s), 14 mg/l

Mobility:

Considerable solubility and mobility

Degradation

Abiotic:

Water, hydrolysis. Degradation products: carbonate (pH. 10/bicarbonate (pH 6-10)/carbonic acid/carbon dioxide (ph<6))

Soil-result: N/A

Biotic:

N/A

Potential for

Bioaccumulation:

Log Po/w: Result- N/A

Other Adverse

Effects/ Comments:

Observed effects are related to alkaline properties of product. Product is not significantly hazardous for the environment.

XIV Disposal Consideration

Waste Treatment: Sodium Carbonate is not a listed hazardous waste under 40 CFR 261. However, state and local regulations for waste disposal may be more restrictive. Spilled product should be disposed of in an EPA-approved disposal facility in accordance with applicable national, state and local environmental laws and regulations.

Packing Treatment: Use dedicated containers where possible
Rinse the empty containers and treat the effluent in the same way as waste
Consult current federal, state and local regulations regarding the proper disposal of emptied containers.

RCRA Hazardous Waste: Not listed

XV Transport Information

Mode	DOT	IMDG	IATA
UN Number	Not a regulated hazardous material	Not a regulated hazardous material	Not a regulated hazardous material
Other	It is not recommended that ERG guide #111 be used for all non-DOT-regulated material		
STCC#	28-123-22		

XVI Regulatory Information

National Regulations (US)

TSCA Inventory 8(b): Yes

SARA Title III
Sec. 302/303
Extremely Hazardous
Substances (40 CFR 355): No

SARA Title III Sec 311/312
(40 CFR 370): Hazard Category: Acute health hazard; Chronic health hazard. Threshold planning quantity: 10,000 lbs

SARA Title III Sec 313
Toxic Chemical
Emissions Reporting
(40 CFR 372): No

CERCLA Hazardous
Substance (40 CFR Part 302) Listed: No
Unlisted Substance: No
Characteristic: N/A

State Component Listing: None identified

National Regulations (Canada)
Canadian DSL Registration: DSL

WHMIS Classifications: D2B—Material causing other toxic effects
 This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations, and the SDS contains all the information required by the Controlled Products Regulations.

EEC Labeling: Name of dangerous product- sodium carbonate

Symbols	Xi	Irritant
Phrases R	36	Irritating to eyes
Phrases S	(2)	Keep out of reach of children
	22	Do not breath dust.
	26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

Labeling “Dangerous for the environment.” Not dangerous.
 Provisions classification of WG from EU-DGXI-1/3-04-98

XVII Other Information

Ratings:

NFPA (National Fire Protection Association)

Health = 2 Flammability = 0 Instability = 0 Special = None

HMIS (Hazardous Material Information system)

Health = 2 Fire = 0 Reactivity = 0 PPE = Supplied by User; dependent on local conditions

XVIII Additional Information

The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, expressed or implied, regarding its correctness.

The conditions or methods of handling, storage, use and disposal are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage, or expense arising out of or in any way connected with handling, storage, use or disposal of the product.

*n/a= Not Applicable

MSDS Number: **S4040** * * * * *Effective Date: 11/21/08* * * * * *Supersedes: 01/25/06*

MSDS**Material Safety Data Sheet**

From: Mallinckrodt Baker, Inc.
222 Red School Lane
Phillipsburg, NJ 08865



Mallinckrodt
CHEMICALS



24 Hour Emergency Telephone: 908-859-2151
CHEMTREC: 1-800-424-9300

National Response in Canada
CANUTEC: 613-996-6666

Outside U.S. and Canada
Chemtec: 703-527-3887

NOTE: CHEMTREC, CANUTEC and National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

All non-emergency questions should be directed to Customer Service (1-800-582-2537) for assistance.

SODIUM HYDROXIDE SOLUTIONS AND CONCENTRATES

1. Product Identification

Synonyms: Sodium hydroxide, 0.2 to 2.0 normal volumetric solutions; DILUT-IT® analytical concentrates; Sodium Hydroxide Concentrate Solution StandARd®

CAS No.: 1310-73-2

Molecular Weight: 40.00

Chemical Formula: NaOH in water

Product Codes:

J.T. Baker: 0328, 0329, 0387, 0388, 0389, 0390, 3726, 4687, 4691, 4715, 5633, 5634, 5635, 5636, 5638, 5665, 5667

Mallinckrodt: 4693, H361, H380

2. Composition/Information on Ingredients

Ingredient	CAS No	Percent	Hazardous
Sodium Hydroxide	1310-73-2	0.8 - 8%	Yes
Water	7732-18-5	92 - 99%	No

3. Hazards Identification

Emergency Overview

DANGER! CORROSIVE. HARMFUL IF SWALLOWED OR INHALED. CAUSES BURNS TO ANY AREA OF CONTACT. REACTS WITH WATER, ACIDS AND OTHER MATERIALS.

SAF-T-DATA^(tm) Ratings (Provided here for your convenience)

Health Rating: 3 - Severe

Flammability Rating: 0 - None

Reactivity Rating: 2 - Moderate

Contact Rating: 4 - Extreme (Corrosive)

Lab Protective Equip: GOGGLES & SHIELD; LAB COAT & APRON; VENT HOOD; PROPER GLOVES

Storage Color Code: White Stripe (Store Separately)

Potential Health Effects

The health effects from exposure to diluted forms of this chemical are not well documented. They are expected to be less severe than those for concentrated forms which are referenced in the descriptions below.

Inhalation:

Severe irritant. Effects from inhalation of mist vary from mild irritation to serious damage of the upper respiratory tract, depending on severity of exposure. Symptoms may include sneezing, sore throat or runny nose. Severe pneumonitis may occur.

Ingestion:

Corrosive! Swallowing may cause severe burns of mouth, throat, and stomach. Severe scarring of tissue and death may result. Symptoms may include bleeding, vomiting, diarrhea, fall in blood pressure. Damage may appear days after exposure.

Skin Contact:

Corrosive! Contact with skin can cause irritation or severe burns and scarring with greater exposures.

Eye Contact:

Corrosive! Causes irritation of eyes, and with greater exposures it can cause burns that may result in permanent impairment of vision, even blindness.

Chronic Exposure:

Prolonged contact with dilute solutions or dust has a destructive effect upon tissue.

Aggravation of Pre-existing Conditions:

Persons with pre-existing skin disorders or eye problems or impaired respiratory function may be more susceptible to the effects of the substance.

4. First Aid Measures

Inhalation:

Remove to fresh air. Get medical attention for any breathing difficulty.

Ingestion:

If swallowed, DO NOT INDUCE VOMITING. Give large quantities of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Skin Contact:

Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse.

Eye Contact:

Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Note to Physician:

Perform endoscopy in all cases of suspected sodium hydroxide ingestion. In cases of severe esophageal corrosion, the use of therapeutic doses of steroids should be considered. General supportive measures with continual monitoring of gas exchange, acid-base balance, electrolytes, and fluid intake are also required.

5. Fire Fighting Measures

Fire:

Not considered to be a fire hazard.

Explosion:

Not considered to be an explosion hazard.

Fire Extinguishing Media:

Use any means suitable for extinguishing surrounding fire. Adding water to caustic solution generates large amounts of heat.

Special Information:

Use protective clothing and breathing equipment appropriate for the surrounding fire.

6. Accidental Release Measures

Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Contain and recover liquid when possible. Do not flush caustic residues to the sewer. Residues from spills can be diluted with water, neutralized with dilute acid such as acetic, hydrochloric or sulfuric. Absorb neutralized caustic residue on clay, vermiculite or other inert substance and package in a suitable container for disposal.

US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

J. T. Baker NEUTRACIT®-2 or BuCAIM® caustic neutralizers are recommended for spills of this product.

7. Handling and Storage

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Protect from freezing. Always add the caustic to water while stirring; never the reverse. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Do not store with aluminum or magnesium. Do not mix with acids or organic materials.

8. Exposure Controls/Personal Protection

Airborne Exposure Limits:

Sodium hydroxide:

-OSHA Permissible Exposure Limit (PEL):

2 mg/m³ Ceiling

-ACGIH Threshold Limit Value (TLV):

2 mg/m³ Ceiling

Ventilation System:

A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, *Industrial Ventilation, A Manual of Recommended Practices*, most recent edition, for details.

Personal Respirators (NIOSH Approved):

If the exposure limit is exceeded and engineering controls are not feasible, a half facepiece particulate respirator (NIOSH type N95 or better filters) may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest.. A full-face piece particulate respirator (NIOSH type N100 filters) may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. If oil particles (e.g. lubricants, cutting fluids, glycerine, etc.) are present, use a NIOSH type R or P filter. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator. WARNING: Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Eye Protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and Chemical Properties

Physical data is displayed for a 5% solution of sodium hydroxide.

Appearance:

Clear, colorless solution.

Odor:

Odorless.

Solubility:

Miscible in water.

Density:

5% solution: 1.05

pH:

14.0

% Volatiles by volume @ 21C (70F):

No information found.

Boiling Point:

102C (216F) (5% solution)

Melting Point:

-4C (25F) (5% solution)

Vapor Density (Air=1):

No information found.

Vapor Pressure (mm Hg):

No information found.

Evaporation Rate (BuAc=1):

No information found.

10. Stability and Reactivity

Stability:

Stable under ordinary conditions of use and storage.

Hazardous Decomposition Products:

No hazardous decomposition products.

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Sodium hydroxide in contact with acids and organic halogen compounds, especially trichloroethylene, may causes violent reactions. Contact with nitromethane and other similar nitro compounds causes formation of shock-sensitive salts. Contact with metals such as aluminum, magnesium, tin, and zinc cause formation of flammable hydrogen gas. Sodium hydroxide, even in fairly dilute solution, reacts readily with various sugars to produce carbon monoxide. Precautions should be taken including monitoring the tank atmosphere for carbon monoxide to ensure safety of personnel before vessel entry.

Conditions to Avoid:

Heat, moisture, incompatibles.

11. Toxicological Information

Sodium hydroxide: irritation data: skin, rabbit: 500 mg/24H severe; eye rabbit: 50 ug/24H severe. Investigated as

a mutagen.

-----\Cancer Lists\-----			
Ingredient	---NTP Carcinogen---		IARC Category
	Known	Anticipated	
Sodium Hydroxide (1310-73-2)	No	No	None
Water (7732-18-5)	No	No	None

12. Ecological Information

Environmental Fate:

No information found.

Environmental Toxicity:

No information found.

13. Disposal Considerations

Whatever cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Although not a listed RCRA hazardous waste, this material may exhibit one or more characteristics of a hazardous waste and require appropriate analysis to determine specific disposal requirements. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. Transport Information

Domestic (Land, D.O.T.)

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Hazard Class: 8

UN/NA: UN1824

Packing Group: II

Information reported for product/size: 460LB

International (Water, I.M.O.)

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Hazard Class: 8

UN/NA: UN1824

Packing Group: II

Information reported for product/size: 460LB

15. Regulatory Information

-----\Chemical Inventory Status - Part 1\-----				
Ingredient	TSCA	EC	Japan	Australia
Sodium Hydroxide (1310-73-2)	Yes	Yes	Yes	Yes
Water (7732-18-5)	Yes	Yes	Yes	Yes

-----\Chemical Inventory Status - Part 2\-----				
Ingredient	--Canada--			
	Korea	DSL	NDSL	Phil.

Sodium Hydroxide (1310-73-2)	Yes	Yes	No	Yes
Water (7732-18-5)	Yes	Yes	No	Yes
-----\Federal, State & International Regulations - Part 1\-----				
	-SARA 302-		-----SARA 313-----	
Ingredient	RQ	TPQ	List	Chemical Catg.
Sodium Hydroxide (1310-73-2)	No	No	No	No
Water (7732-18-5)	No	No	No	No
-----\Federal, State & International Regulations - Part 2\-----				
	-RCRA-		-TSCA-	
Ingredient	CERCLA	261.33	8(d)	
Sodium Hydroxide (1310-73-2)	1000	No	No	
Water (7732-18-5)	No	No	No	

Chemical Weapons Convention: No TSCA 12(b): No CDTA: No
SARA 311/312: Acute: Yes Chronic: No Fire: No Pressure: No
Reactivity: No (Pure / Liquid)

Australian Hazchem Code: 2R**Poison Schedule: S5****WHMIS:**

This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

16. Other Information

NFPA Ratings: Health: **3** Flammability: **0** Reactivity: **0**

Label Hazard Warning:

DANGER! CORROSIVE. HARMFUL IF SWALLOWED OR INHALED. CAUSES BURNS TO ANY AREA OF CONTACT. REACTS WITH WATER, ACIDS AND OTHER MATERIALS.

Label Precautions:

Do not get in eyes, on skin, or on clothing.

Do not breathe mist.

Keep container closed.

Use only with adequate ventilation.

Wash thoroughly after handling.

Label First Aid:

If swallowed, give several glasses of water or milk to drink. Vomiting may occur spontaneously, but DO NOT INDUCE! Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. In all cases get medical attention immediately.

Product Use:

Laboratory Reagent.

Revision Information:

No Changes.

Disclaimer:

Mallinckrodt Baker, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. MALLINCKRODT BAKER, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR

PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, MALLINCKRODT BAKER, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.

Prepared by: Environmental Health & Safety

Phone Number: (314) 654-1600 (U.S.A.)



MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: SUPER-VIS*

Revision Date: 07/21/2009

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: SUPER-VIS*

Chemical Family: Polysaccharide gum Biopolymer.
Product Use: Drilling fluid additive.

Supplied by: M-I L.L.C.
P.O. Box 42842
Houston, TX 77242
www.miswaco.com

Telephone Number: 281-561-1511
Emergency Telephone (24 hr.): 281-561-1600
Prepared by: Product Safety Group

Revision No. 4

HMIS Rating

Health: 1 **Flammability:** 1 **Physical Hazard:** 0 **PPE:** E

4=Severe, 3=Serious, 2=Moderate, 1=Slight, 0=Minimal Hazard. *Chronic effects - See Section 11. See Section 8 for Personal Protective Equipment recommendations.

2. HAZARDS IDENTIFICATION

Emergency Overview: Caution! May cause mechanical irritation of eyes, skin and respiratory tract. Long term inhalation of particulates may cause lung damage.

Canadian Classification:

UN PIN No: Not regulated.

WHMIS Class: Not a controlled product.

Physical State: Powder, dust. **Color:** White to tan **Odor:** Slight

Potential Health Effects:

Acute Effects

Eye Contact: May cause mechanical irritation
Skin Contact: May cause mechanical irritation.
Inhalation: May cause mechanical irritation.
Ingestion: May cause gastric distress, nausea and vomiting if ingested.

Carcinogenicity & Chronic Effects: See Section 11 - Toxicological Information.

Routes of Exposure: Eyes. Dermal (skin) contact. Inhalation.
Target Organs/Medical Conditions Aggravated by Overexposure: Eyes. Skin. Respiratory System.

MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: **SUPER-VIS***
Revision Date: 07/21/2009

Page 2/6

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	Wt. %	Comments:
Xanthan gum	11138-66-2	100	No comments.

4. FIRST AID MEASURES

Eye Contact: Promptly wash eyes with lots of water while lifting eye lids. Look for and remove contact lenses. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

Skin Contact: Wash skin thoroughly with soap and water. Remove contaminated clothing and launder before reuse. Get medical attention if any discomfort continues.

Inhalation: Move person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Dilute with 2 - 3 glasses of water or milk, if conscious. Never give anything by mouth to an unconscious person. If signs of irritation or toxicity occur seek medical attention.

General notes: Persons seeking medical attention should carry a copy of this MSDS with them.

5. FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: F (C): NA

Flammable Limits in Air - Lower (%): ND

Flammable Limits in Air - Upper (%): ND

Autoignition Temperature: F (C): >392 (F)

Flammability Class: NA

Other Flammable Properties: Particulate may accumulate static electricity. Dusts at sufficient concentrations can form explosive mixtures with air.

Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Protection Of Fire-Fighters:

Special Fire-Fighting Procedures: Do not enter fire area without proper personal protective equipment, including NIOSH/MSHA approved self-contained breathing apparatus. Evacuate area and fight fire from a safe distance. Water spray may be used to keep fire-exposed containers cool. Keep water run off out of sewers and waterways.

Hazardous Combustion Products: Oxides of: Carbon.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protective equipment identified in Section 8.

Spill Procedures: Evacuate the spill area with the exception of the spill response team. Wet product may create a slipping hazard. Contain spilled material. Do not allow spilled material to enter sewers, storm drains or surface waters. Avoid the generation of dust. Sweep, vacuum, or shovel and place into closable container for disposal.

Environmental Precautions: Waste must be disposed of in accordance with federal, state and local laws.

MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: **SUPER-VIS***
Revision Date: 07/21/2009

Page 3/6

7. HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment. Avoid contact with skin and eyes. Avoid generating or breathing dust. Product is slippery if wet. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Store in dry, well-ventilated area. Keep container closed. Store away from incompatibles. Follow safe warehousing practices regarding palletizing, banding, shrink-wrapping and/or stacking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits (TLV & PEL - 8H TWA):

Ingredient	CAS No.	Wt. %	ACGIH TLV	OSHA PEL	Other	Notes
Xanthan gum	11138-66-2	100	NA	NA	NA	(1)

Notes

(1) Control as an ACGIH particulate not otherwise specified (PNOS): 10 mg/m³ (Inhalable); 3 mg/m³ (Respirable) and an OSHA particulate not otherwise regulated (PNOR): 15 mg/m³ (Total); 5 mg/m³ (Respirable).

Engineering Controls: Use appropriate engineering controls such as, exhaust ventilation and process enclosure, to ensure air contamination and keep workers exposure below the applicable limits.

Personal Protection Equipment

All chemical Personal Protective Equipment (PPE) should be selected based on an assessment of both the chemical hazards present and the risk of exposure to those hazards. The PPE recommendations below are based on our assessment of the chemical hazards associated with this product. The risk of exposure and need for respiratory protection will vary from workplace to workplace and should be assessed by the user.

Eye/Face Protection: Dust resistant safety goggles.

Skin Protection: Not normally necessary. If needed to minimize irritation: Wear appropriate clothing to prevent repeated or prolonged skin contact. Wear chemical resistant gloves such as: Nitrile. Neoprene.

Respiratory Protection: All respiratory protection equipment should be used within a comprehensive respiratory protection program that meets the requirements of 29 CFR 1910.134 (U.S. OSHA Respiratory Protection Standard) or local equivalent.

If exposed to airborne particles of this product use at least a NIOSH-approved N95 half-mask disposable or re-useable particulate respirator. In work environments containing oil mist/aerosol use at least a NIOSH-approved P95 half-mask disposable or re-useable particulate respirator.

General Hygiene Considerations: Work clothes should be washed separately at the end of each work day. Disposable clothing should be discarded, if contaminated with product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: White to tan
Odor: Slight
Physical State: Powder, dust.

MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: **SUPER-VIS***
Revision Date: 07/21/2009

Page 4/6

pH: 5.4 - 8.6 (1% solution)
Specific Gravity (H₂O = 1): ND
Solubility (Water): Soluble
Melting/Freezing Point: ND
Boiling Point: ND
Vapor Pressure: NA
Vapor Density (Air=1): NA
Evaporation Rate: ND
Odor Threshold(s): ND

10. STABILITY AND REACTIVITY

Chemical Stability: Stable
Conditions to Avoid: ND
Materials to Avoid: Oxidizers.
Hazardous Decomposition Products: For thermal decomposition products, see Section 5.
Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

Component Toxicological Data: Any adverse component toxicological effects are listed below. If no effects are listed, no such data were found.

Ingredient	CAS No.	Acute Data
Xanthan gum	11138-66-2	Oral LD50: > 5,000 mg/kg (rat)

Product Toxicological Information:

Long term inhalation of particulate can cause irritation, inflammation and/or permanent injury to the lungs. Illnesses such as pneumoconiosis ("dusty lung"), pulmonary fibrosis, chronic bronchitis, emphysema and bronchial asthma may develop.

12. ECOLOGICAL INFORMATION

Component Ecotoxicity Data: Component ecotoxicity data are listed below. If no data are listed, none was found in the component review.

Ingredient	CAS No.	Data
Xanthan gum	11138-66-2	LC50 96H: 490 mg/l (rainbow trout); LC50 48H: 980 mg/l (Daphnia magna)

Product Ecotoxicity Data: Contact M-I Environmental Affairs Department for available product ecotoxicity data.

Biodegradation: ND
Bioaccumulation: ND
Octanol/Water Partition Coefficient: ND

13. DISPOSAL CONSIDERATIONS

MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: **SUPER-VIS***
Revision Date: 07/21/2009

Page 5/6

Waste Classification: ND

Waste Management: Under U.S. Environmental Protection Agency (EPA) Resource Conservation and Recovery Act (RCRA), it is the responsibility of the user to determine at the time of disposal, whether the product meets RCRA criteria for the hazardous waste. This is because product uses, transformations, mixtures, processes, etc., may render the resulting materials hazardous. Empty containers retain residues. All labeled precautions must be observed.

Disposal Method: Recover and reclaim or recycle, if practical. Should this product become a waste, dispose of in a permitted industrial landfill. Ensure that the containers are empty by the RCRA criteria prior to disposal in a permitted industrial landfill.

14. TRANSPORT INFORMATION

U.S. DOT

Shipping Description:

Not regulated for transportation by DOT, TDG, IMDG, ICAO/IATA.

Canada TDG Shipping Description:

Not regulated.

UN PIN No:

Not regulated.

IMDG Shipping Description:

Not regulated.

ICAO/IATA Shipping Description:

Not regulated.

15. REGULATORY INFORMATION

U.S. Federal and State Regulations

SARA 311/312 Hazard Categories:Not a SARA 311/312 hazard.

SARA 302/304, 313; CERCLA RQ, California Proposition 65: Note: If no components are listed below, this product is not subject to the referenced SARA and CERCLA regulations and is not known to contain a Proposition 65 listed chemical at a level that is expected to pose a significant risk under anticipated use conditions.

State Comments: Proposition 65: This product is not known to contain chemicals considered by the State of California's Safe Drinking Water and Toxic Enforcement Act of 1986 as causing cancer and/or reproductive toxicity at levels that are expected to pose a significant risk under anticipated use conditions.

International Chemical Inventories

Australia AICS - Components are listed or exempt from listing.
Canada DSL - Components are listed or exempt from listing.
China Inventory - Components are listed or exempt from listing.
European Union EINECS/ELINCS - Components are listed or exempt from listing.
Japan METI ENCS - Components are listed or exempt from listing.
Korea TCCL ECL - Components are listed or exempt from listing.
New Zealand - Components are listed or exempt from listing.
Philippine PICCS - Components are listed or exempt from listing.
U.S. TSCA - Components are listed or exempt from listing.
U.S. TSCA - No components are subject to TSCA 12(b) export notification requirements.

Canadian Classification:

MATERIAL SAFETY DATA SHEET

MSDS No. 10374

Trade Name: **SUPER-VIS***

Revision Date: 07/21/2009

Page 6/6

Controlled Products Regulations Statement: This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Class: Not a controlled product.

16. OTHER INFORMATION

The following sections have been revised: 1, 4, 6, 15, 16

NA - Not Applicable, ND - Not Determined.

*A mark of M-I L.L.C.

Disclaimer:

MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data are obtained from sources beyond our direct supervision. We can not make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions under which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, no warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.



Shell Canada Limited Material Safety Data Sheet

Effective Date: 2006-06-05

Supersedes: 2003-06-05

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **TELLUS* T 32**
SYNONYMS: LOW TEMPERATURE HYDRAULIC OIL
PRODUCT USE: Hydraulic Fluid
PRODUCT CODE: **407-159**

SUPPLIER

Shell Canada Limited (SCL)
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS

Shell Emergency Number
CANUTEC 24 HOUR EMERGENCY NUMBER
For general information:

1-800-661-7378
1-613-996-6666
1-800-661-1600
www.shell.ca

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION / INFORMATION ON INGREDIENTS

THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE.

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Lightly Coloured Hydrocarbon Odour
Routes of Exposure: Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mists.

Hazards:

This product is not expected to be irritating and has a low level of toxicity under normal use.

Inhalation of oil mist or vapours from hot oil may cause irritation of the upper respiratory tract.

For further information on health effects, see Section 11.

4. FIRST AID MEASURES

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wipe excess from skin. Wash contaminated skin with mild soap and water for at least 15 minutes. If irritation occurs and persists, obtain medical attention. If material is injected under the skin, get medical attention promptly to prevent serious damage; do not wait for symptoms to develop.

Ingestion: Not normally required; obtain medical attention if large amounts have been ingested. Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent

- Inhalation:** aspiration of liquid into the lungs. Remove victim from further exposure. Additional first aid treatment is not ordinarily required.
- Notes to Physician:** In general, lubricating oils have low oral toxicity. High pressure injection under the skin may have serious consequences and may require urgent treatment.

5. FIRE FIGHTING MEASURES

- Extinguishing Media:** Dry Chemical
Carbon Dioxide
Foam
Water Fog
- Firefighting Instructions:** Material will not burn unless preheated. Product will float and can be reignited on surface of water. Do not use a direct stream of water as it may spread fire. Use water to cool fire exposed containers. Water may be used to flush spills away from exposure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.
- Hazardous Combustion Products:** Carbon monoxide, carbon dioxide and dense smoke are produced on combustion.

6. ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources. Isolate hazard area and restrict access. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Spilled material is slippery. Dike and contain land spills; contain spills to water by booming. For large spills remove by mechanical means and place in containers. Adsorb residue or small spills with adsorbent material and remove to non-leaking containers for disposal. Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

- Handling:** Avoid excessive heat, formation of oil mist, breathing of vapours and mist of hot oil and prolonged or repeated contact with skin. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.
- Storage:** Store in a cool, dry, well ventilated area, away from heat and ignition sources.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The following information, while appropriate for this product, is general in nature. The selection of personal protective equipment will vary depending on the conditions of use.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Oil mist (mineral): 5 mg/m³ (STEL: 10 mg/m³)

- Mechanical Ventilation:** Not normally required. Local ventilation is recommended if oil mist is present or if exposure limit is exceeded. Make up air should always be supplied to balance air exhausted (either generally or locally).

PERSONAL PROTECTIVE EQUIPMENT:

- Eye Protection:** No special eye protection is routinely necessary. Wear safety glasses as appropriate.
- Skin Protection:** Not normally needed. Chemically-resistant gloves should be worn for frequent or

Respiratory Protection: prolonged contact with this product.
Not normally required under intended conditions of use. If airborne concentration is high (e.g. when product is heated), use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges in combination with a P95 particulate filter.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid	Odour:	Hydrocarbon Odour
Appearance:	Lightly Coloured	Odour Threshold:	Not available
Pour Point	Pour Point < -39 °C	Boiling Point	
Vapour Pressure (absolute):		Vapour Density (air = 1):	Not available
Density:	approximately 869 kg/m ³ @ 15 °C	Flash Point	COC > 160 °C
Specific Gravity (Water = 1):		Lower Flammable Limit:	Not available
pH:	Not applicable	Upper Flammable Limit:	Not available
Viscosity:	28.8 - 35.2 cSt @ 40 °C	Auto-ignition Temperature:	Not available
Evaporation Rate (n-BuAc = 1):	Not available	Partition Coefficient (log K_{ow}):	Not available
Water Solubility:	Insoluble	Molecular Weight:	
Other Solvents:	Hydrocarbon Solvents	Formula:	

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes	Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No	Sensitive to Static Discharge:	No
Incompatible Materials:	Avoid strong oxidizing agents.		
Conditions of Reactivity:	Avoid excessive heat, formation of vapours or mists.		

11. TOXICOLOGICAL INFORMATION

Routes of Exposure:	Exposure will most likely occur through skin contact or from inhalation of mechanically or thermally generated oil mists.
Irritancy:	This product is not a primary skin irritant after exposure of short duration, is not a skin sensitizer and is not irritating to the eyes.
Acute Toxicity:	This product is not expected to be irritating and has a low level of toxicity under normal use.
Chronic Effects:	Prolonged or repeated contact may cause various forms of dermatitis including folliculitis and oil acne. Long term intensive exposure to oil mist may cause benign lung fibrosis.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.
Biodegradability:	Not readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site.

14. TRANSPORT INFORMATION**Canadian Road and Rail Shipping Classification:**

This product is not regulated under the Canadian Transportation of Dangerous Goods Regulations for transport by road and rail.

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

DSL/NDSL Status:	THIS PRODUCT IS NOT A WHMIS CONTROLLED SUBSTANCE. One or more of the components of this product are listed on the NDSL. All other components are on the DSL. This product and/or all components are listed on the U.S. EPA TSCA Inventory.
Other Regulatory Status:	No Canadian federal standard; however, for general discharge guidance, federal installations limited to 15 mg/L for total oil and grease. Provincial criteria are likely and should be requested when notifying provincial authorities.

16. OTHER INFORMATION

Revisions:	This MSDS has been reviewed and updated. Changes have been made to: Section 5 Section 8 Section 15
-------------------	---

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: Dec. 23, 2008
8750-53 Ave. PHONE: 780-468-4064
Edmonton, AB T6E 5G2 FAX: 780-469-1899

PRODUCT NAME: **W-OB POLYMER**

PRODUCT USE: Drilling mud additive
CHEMICAL FAMILY: Polysaccharide suspension CAS #: Mixture

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D2B
WORKPLACE HAZARD: Skin and eye irritant

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (v/v)</u>	<u>CAS NUMBER</u>	<u>LD₅₀ Oral-Rat</u>	<u>LC₅₀ Inhal-Rat</u>	<u>ACGIH-TLV</u>
Ethoxylated nonylphenol	1-5	9016-45-9	5100 mg/kg	Not determined	Not available

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [XX] EYE CONTACT [XX] SKIN [XX] INHALATION [XX] INGESTION
EYE CONTACT: Irritant. Can cause redness, tearing and inflammation.
SKIN CONTACT: Irritant. Can cause redness, irritation and inflammation.
INGESTION: Low oral toxicity. May cause nausea, abdominal cramps and diarrhea.
INHALATION: High concentrations of vapour and mist can cause irritation of the nose and throat
CARCINOGENICITY: No information available.
TERATOGENICITY: No information available.
REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: No information available.
SYNERGISTIC
PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing. Immediately wash exposed area with water and soap for 5 minutes. If irritation persists, obtain medical attention.

EYE CONTACT: Immediately flush with gently flowing warm water for 15 minutes, or until irritation ceases. When flushing period is completed, obtain medical attention.

INGESTION: Rinse mouth and give 1 - 2 glasses of water to dilute. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs keep head below hips to prevent aspiration. Even small amounts of liquid drawn into the lungs from swallowing, or vomiting may cause severe health effects. Obtain medical attention. Never give anything by mouth if patient is unconscious, rapidly losing consciousness or convulsing.

INHALATION: Move patient to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties or distress continues obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Opaque dark yellow to beige liquid; little odour	
SPECIFIC GRAVITY:	1.078	
BOILING POINT (°C):	Not determined	
MELTING POINT (°C):	Not determined	
SOLUBILITY IN WATER:	Dispersible	pH: Not determined
PERCENT VOLATILE BY VOLUME:	Not determined	
EVAPORATION RATE:	Not determined	
VAPOUR PRESSURE (mmHg):	Not determined	
VAPOUR DENSITY (air = 1):	Not determined	
BULK DENSITY:	Not applicable	

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not flammable
FLAMMABLE LIMITS:	Not determined
EXTINGUISHING MEDIA:	CO ₂ , water, mist, foam
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel.

**UNUSUAL FIRE AND
EXPLOSION HAZARDS:**

None known.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Strong oxidizers and acids.	
CONDITIONS OF REACTIVITY:	Not applicable.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon on combustion.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES**SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION:	An approved respirator with organic vapour cartridge if TLV is exceeded.
VENTILATION:	Use local exhaust ventilation, process enclosure or other engineering control to prevent exposure.
PROTECTIVE GLOVES:	Rubber or viton gloves recommended.
EYE PROTECTION:	Chemical goggles and/or face shield required. Do not wear contact lenses.
OTHER PROTECTIVE EQUIPMENT (Specify):	It is recommended that chemical resistant protective clothing be worn at all times when handling this product. Make eye bath and emergency shower available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid ingestion. Practice reasonable caution and personal cleanliness. Avoid skin and eye contact. Avoid inhalation of vapours or mists. Wear suitable protection for eyes and skin when handling. Launder contaminated clothing before reuse. Avoid contact with incompatible materials. Store in cool, well-ventilated area away from sources of ignition. Keep container tightly closed when not in use. Store unused material in original container. Handle and store empty containers as if full.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment including respiratory protection. Eliminate ignition sources. Ventilate area. Stop leak if possible to do so without risk. Soak up small spills with absorbent material. Contain large spills using absorbent materials. Collect spilled material and absorbents in approved containers for disposal. Prevent entry into bodies of water or sewer systems.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine at the time of disposal whether the product meets criteria for hazardous waste. Empty containers, which have not been cleaned and purged, contain residual hazardous material and must be disposed of, or recycled, according to local regulations.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED:	December 23, 2008	BY:	Product safety committee
SUPERSEDES:	January 18, 2006	PHONE:	780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies.**

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00486

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: COD TNTPlus™, LR (3-150 MG/L)
Catalog Number: TNT821

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00486
Chemical Name: Not applicable
CAS No.: Not applicable
Chemical Formula: Not applicable
Chemical Family: Not applicable
PIN: 1830
Intended Use: Determination of Chemical Oxygen Demand
Date of MSDS Preparation:
Day: 22
Month: February
Year: 2010
MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Mercuric Sulfate

Percent Range: 0.1 - 1.0
Percent Range Units: weight / weight
CAS No.: 7783-35-9 Contains Mercury. Dispose Per Local, State or Federal Laws.
LD50: Oral rat LD₅₀ = 57 mg/kg; Oral mouse LD₅₀ = 25 mg/kg.
LC50: None reported
TLV: 0.05 mg/m³ (Hg)
PEL: 0.1 mg/m³ (Hg)
Ingredient WHMIS Symbol: Acute Poison

Demineralized Water

Percent Range: 15.0 - 25.0
Percent Range Units: weight / weight
CAS No.: 7732-18-5
LD50: None reported
LC50: None reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Chromic Acid

Percent Range: 0.01 - 0.1
Percent Range Units: weight / weight
CAS No.: 13530-68-2
LD50: None reported
LC50: Inhalation human TCLo = 110 µg/m³

TLV: 0,05 mg/m³ (0.0235 ppm) as Cr⁺⁶
PEL: 5 µg/m³ (0.00235 ppm Cr⁺⁶), 8 Hr TWA; Action Level is 2.5 µg/m³ (0.00117 ppm), 8 Hr TWA
Ingredient WHMIS Symbol: Not applicable

Silver Sulfate

Percent Range: 0.5 - 3.0
Percent Range Units: weight / weight
CAS No.: 10294-26-5
LD50: None reported
LC50: None reported
TLV: 0.01 mg/m³ (Ag)
PEL: 0.01 mg/m³ (Ag)
Ingredient WHMIS Symbol: Not applicable

Sulfuric Acid

Percent Range: 80.0 - 90.0
Percent Range Units: weight / weight
CAS No.: 7664-93-9
LD50: Oral rat LD50 = 2140 mg/kg.
LC50: Inhalation rat LC50 = 87 ppm/4 hr
TLV: 1 mg/m³ (TWA); 3 mg/m³ (STEL)
PEL: 1 mg/m³
Ingredient WHMIS Symbol: Acute Poison Corrosive

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: Turbid, light orange liquid
Physical State: Liquid
Odor: Not determined
MAY BE FATAL IF SWALLOWED CAUSES SEVERE BURNS HARMFUL IF INHALED OR ABSORBED THROUGH SKIN
CANCER HAZARD CONTAINS MATERIAL WHICH CAN CAUSE CANCER CAN CAUSE KIDNEY AND CENTRAL NERVOUS SYSTEM EFFECTS

HMIS:

Health: 3*
Flammability: 0
Reactivity: 2
Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes severe burns
Skin Contact: Causes severe burns
Skin Absorption: Will be absorbed through the skin. Effects similar to those of ingestion
Target Organs: Central nervous system Kidneys
Ingestion: Causes: severe burns May cause: abdominal pain circulatory disturbances diarrhea loosening of the teeth nausea vomiting rapid pulse and respirations toxic nephritis (inflammation of the kidneys) shock collapse kidney damage death
Target Organs: Central nervous system Kidneys
Inhalation: Toxic. Causes: severe burns May cause: difficult breathing mouth soreness teeth erosion Effects similar to those of ingestion. Inhalation of mists / sprays: Causes asthma Causes damage to the nasal epithelia Causes lung cancer
Target Organs: Central nervous system Kidneys Lungs Teeth Nasal cavity
Medical Conditions Aggravated: Pre-existing: Eye conditions Skin conditions Respiratory conditions Allergies or sensitivity to chromates or chromic acid. Allergies or sensitivity to mercury.
Chronic Effects: Chronic overexposure may cause destruction of any tissue contacted erosion of the teeth mouth soreness chronic irritation or inflammation of the lungs accumulation of silver in body tissues which causes a slate-gray

to bluish discoloration. Chromate and dichromate salts may cause ulceration and perforation of the nasal septum, severe liver damage, central nervous system effects, and lung cancer. Mercury is a general protoplasmic poison; it circulates in the blood and is stored in the liver, kidneys, spleen and bones. Main symptoms are sore mouth, tremors and psychic disturbances.

Cancer / Reproductive Toxicity Information:

An ingredient of this mixture is: IARC Group 1: Recognized Carcinogen

Hexavalent Chromium Compounds Sulfuric Acid - The IARC evaluation was based on exposure to the mist or vapor of concentrated sulfuric acid generated during chemical processes.

An ingredient of this mixture is: NTP Listed Group 1: Recognized Carcinogen

Hexavalent Chromium Compounds

Additional Cancer / Reproductive Toxicity Information: Contains: an experimental teratogen.

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class D, Division 1, Subdivision A - Very toxic materials (immediate effects) Class D, Division 2, Subdivision A - Very toxic materials (other toxic effects) Class E - Corrosive material

WHMIS Symbols: Acute Poison Corrosive

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water for 15 minutes. Remove contaminated clothing. Call physician immediately.

Ingestion (First Aid): Do not induce vomiting. Give large quantities of water. Never give anything by mouth to an unconscious person. Call physician immediately.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: Not Flammable, but reacts with most metals to form flammable hydrogen gas. During a fire, corrosive and toxic gases may be generated by thermal decomposition.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not applicable

Hazardous Combustion Products: This material will not burn.

Fire / Explosion Hazards: Contact with metals gives off hydrogen gas which is flammable. May react violently with: strong bases water

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Use media appropriate to surrounding fire conditions

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear. Evacuate area and fight fire from a safe distance. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Releases of this material may contaminate the environment. Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment. Dike the spill to contain material for later disposal.

Clean-up Technique: Mercury and its compounds are extremely toxic! Be extremely careful not to contact the spill or breathe any vapors. Absorb spilled liquid with non-reactive sorbent material. Dispose of all mercury contaminated material at an E.P.A. hazardous waste facility. Dispose of material in an E.P.A. approved hazardous waste facility. Decontaminate area with commercially available mercury absorbing compounds.

Evacuation Procedure: Evacuate general area (50 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. Deny access to unnecessary and unprotected personnel. Remain up-wind from spilled material. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: 137

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe mist or vapors. Use with adequate ventilation. Maintain general industrial hygiene practices when using this product.

Storage: Protect from: light contamination by organic materials (will affect product stability) heat

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Have a safety shower nearby. Use a fume hood to avoid exposure to dust, mist or vapor. Maintain general industrial hygiene practices when using this product. Refer to the OSHA Standard at 29CFR1910.1026 for Cr (VI) (See Federal Register 28 February 2006 Page 10100.)

Personal Protective Equipment:

Eye Protection: chemical splash goggles

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: laboratory fume hood

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: mist/vapor Wash thoroughly after handling. Use with adequate ventilation. Protect from: light organic materials heat Keep away from: alkalies metals other combustible materials oxidizers reducers

TLV: Not established. 0.05 mg/m³ (0.0235 ppm as Cr⁺⁶).

PEL: Not established. 5 µg/m³ (0,00235 ppm Cr⁺⁶), 8 Hr TWA; Action Level is 2,5 µg/m³ (0,00117 ppm), 8 Hr TWA

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Turbid, light orange liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: Not determined

pH: < 0.5

Vapor Pressure: Not determined

Vapor Density (air = 1): Not determined

Boiling Point: ~ 105°C (~ 221°F)

Melting Point: Not applicable

Specific Gravity (water = 1): ~ 1.78

Evaporation Rate (water = 1): Not determined

Volatile Organic Compounds Content: Not applicable

Coefficient of Water / Oil: Not applicable

Solubility:

Water: Miscible

Acid: Not determined

Other: Not determined

Metal Corrosivity:

Steel: Corrosive

Aluminum: Corrosive

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Exposure to light or contamination by organic materials will affect this product's stability.

Reactivity / Incompatibility: May react violently in contact with: caustics

Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: mercury compounds sulfur oxides

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: Oral rat (male) LD₅₀ = 428 mg/kg; Oral rat (female) LD₅₀ = 360 mg/kg.

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: None reported

Mutation Data: None reported

Reproductive Effects Data: None reported

--

Ingredient Toxicological Data: Sulfuric Acid: Oral rat LD₅₀ = 2140 mg/kg; Mercuric Sulfate: Oral rat LD₅₀ = 57 mg/kg, Oral mouse LD₅₀ = 25 mg/kg.

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product.

Ingredient Ecological Information: --

No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Dispose of all mercury contaminated material at an E.P.A. hazardous waste facility. Dispose of material in an E.P.A. approved hazardous waste facility.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash. Rinsate from empty containers may contain sufficient product to require disposal as hazardous waste.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Sulphuric Acid Solution

--

Hazard Class: 8

PIN: 1830

Group: II

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor). Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. Cassaret and Doull's Toxicology, 3rd Ed. New York: Macmillan Publishing Co., Inc., 1986. CCINFO RTECS. Canadian Centre for Occupational Health and Safety. Hamilton, Ontario Canada: 30 June 1993. Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Association, 1991. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987. List of Dangerous Substances Classified in Annex I of the EEC Directive (67/548) - Classification, Packaging and Labeling of Dangerous Substances, Amended July 1992. Outside Testing. Sixth Annual Report on Carcinogens, 1991. U.S. Department of Health and Human Services. Rockville, MD: Technical Resources, Inc. 1991. Technical Judgment. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. Verschueren, Karel. Handbook of Environmental Data on Organic Chemicals. New York: Van Nostrand Reinhold Co., 1977.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

**THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE.
HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA
OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.**

HACH COMPANY ©2010

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00035

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: PhosVer ® 3 Phosphate Reagent
Catalog Number: 2106046

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00035

Chemical Name: Not applicable

CAS No.: Not applicable

Chemical Formula: Not applicable

Chemical Family: Not applicable

PIN: NA

Intended Use: Phosphate determination

Date of MSDS Preparation:

Day: 15

Month: October

Year: 2009

MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Potassium Pyrosulfate

Percent Range: 75.0 - 85.0

Percent Range Units: weight / weight

CAS No.: 7790-62-7

LD50: Oral rat LD50 = 2340 mg/kg

LC50: None reported

TLV: Not established

PEL: Not established

Ingredient WHMIS Symbol: Other Toxic Effects

Ascorbic Acid

Percent Range: 15.0 - 25.0

Percent Range Units: weight / weight

CAS No.: 50-81-7

LD50: Oral rat LD50 = 11900 mg/kg

LC50: None reported

TLV: Not established

PEL: Not established

Ingredient WHMIS Symbol: Not applicable

Sodium Molybdate

Percent Range: 1.0 - 10.0

Percent Range Units: weight / weight

CAS No.: 10102-40-6

LD50: Oral rat LD₅₀ = 4000 mg/kg.

LC50: Inhalation rat LC50 = > 2080 mg/m³/4 hrs
TLV: 5 mg/m³ (as Mo)
PEL: 5 mg/m³ (as Mo)
Ingredient WHMIS Symbol: Not applicable

Other components, each

Percent Range: 0.1 - 1.0
Percent Range Units: weight / weight
CAS No.: Not applicable
LD50: Not applicable
LC50: Not applicable
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: White to off-white powder

Physical State: Solid

Odor: None

CAUSES EYE BURNS MAY CAUSE RESPIRATORY TRACT IRRITATION

HMIS:

Health: 3

Flammability: 1

Reactivity: 0

Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes eye burns.

Skin Contact: No effects are anticipated

Skin Absorption: None Reported

Target Organs: None Reported

Ingestion: May cause: copper deficiency anemia gout loss of appetite loss of coordination listlessness diarrhea liver damage May effect enzyme activity.

Target Organs: Blood Liver

Inhalation: May cause: respiratory tract irritation Effects similar to those of ingestion.

Target Organs: Blood Liver

Medical Conditions Aggravated: Pre-existing: Eye conditions Respiratory conditions Gout

Chronic Effects: Chronic overexposure may cause copper deficiency enzyme activity effects liver damage Molybdenum poisoning signs include loss of appetite, listlessness and reduced growth rate. Excessive exposure to molybdenum compounds may cause gout and anemia.

Cancer / Reproductive Toxicity Information:

This product does NOT contain any IARC listed chemicals.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: Contains: an experimental mutagen.

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class D, Division 2, Subdivision B - Toxic material (other toxic effects)

WHMIS Symbols: Other Toxic Effects

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: Can burn in fire, releasing toxic vapors.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not determined

Hazardous Combustion Products: Toxic fumes of: sulfur oxides. carbon monoxide, carbon dioxide. sodium monoxide

Fire / Explosion Hazards: None reported

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Use media appropriate to surrounding fire conditions

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Stop spilled material from being released to the environment.

Clean-up Technique: Scoop up spilled material into a large beaker and dissolve with water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled.

D.O.T. Emergency Response Guide Number: NONE

7. HANDLING / STORAGE

Handling: Avoid contact with eyes Do not breathe dust. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Store between 10° and 25°C.

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes Do not breathe: dust Wash thoroughly after handling.

TLV: Not established

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: White to off-white powder

Physical State: Solid

Molecular Weight: Not applicable

Odor: None

pH: of a 5% solution = 1.5

Vapor Pressure: Not applicable

Vapor Density (air = 1): Not applicable
Boiling Point: Not applicable
Melting Point: 105 °C (221 °F)
Specific Gravity (water = 1): 2.22
Evaporation Rate (water = 1): Not applicable
Volatile Organic Compounds Content: Not applicable
Coefficient of Water / Oil: Not applicable
Solubility:
 Water: Soluble
 Acid: Soluble
 Other: Not determined
Metal Corrosivity:
 Steel: Not Applicable
 Aluminum: Not Applicable

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.
Conditions to Avoid: Extreme temperatures
Reactivity / Incompatibility: Incompatible with: oxidizers dyes alkalies iron copper
Hazardous Decomposition: Heating to decomposition releases: carbon dioxide carbon monoxide sulfur oxides
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: None reported

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: Not corrosive to skin, no erythema

Mutation Data: None reported

Reproductive Effects Data: None reported

--

Ingredient Toxicological Data: Potassium Pyrosulfate Oral rat LD50 = 2340 mg/kg; Sodium Molybdate Oral rat LD50 = 4000 mg/kg, Inhalation rat LC50 > 2080mg/m³/4 hr; Ascorbic Acid Oral rat LD50 = 11.9 g/kg

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product.

Ingredient Ecological Information: --

No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Work in an approved fume hood. Dilute material with excess water making a weaker than 5% solution. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Not Currently Regulated

--

Hazard Class: NA

PIN: NA

Group: NA

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. In-house information. Technical Judgment. Outside Testing. NIOSH/OSHA Occupational Health Guidelines for Chemical Hazards. Cincinnati: Department of Health and Human Services, 1981. Sax, N. Irving. Dangerous Properties of Industrial Materials, 7th Ed. New York: Van Nostrand Reinhold Co., 1989. Gosselin, R. E. et al. Clinical Toxicology of Commercial Products, 5th Ed. Baltimore: The Williams and Wilkins Co., 1984. Vendor Information. Patty, Frank A. Industrial Hygiene and Toxicology, 3rd Revised Edition. Volume 2. New York: A Wiley-Interscience Publication, 1981.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2009

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00039

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Potassium Persulfate
Catalog Number: 2084766

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00039
Chemical Name: Peroxydisulfuric Acid, Dipotassium Salt
CAS No.: 7727-21-1
Chemical Formula: K₂S₂O₈
Chemical Family: Oxidizing Agents
PIN: 1492
Intended Use: Laboratory Reagent
Date of MSDS Preparation:
Day: 15
Month: October
Year: 2009
MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Potassium Persulfate
Percent Range: 100.0
Percent Range Units: weight / weight
CAS No.: 7727-21-1
LD50: Oral Rat LD50 = 802 mg/kg
LC50: None reported
TLV: 5 mg/m³
PEL: Not established
Ingredient WHMIS Symbol: Oxidizing Other Toxic Effects

3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance: White to light yellow crystals
Physical State: Solid
Odor: None
CAUSES EYE AND RESPIRATORY TRACT IRRITATION
MAY CAUSE ALLERGIC SKIN AND RESPIRATORY REACTIONS
STRONG OXIDIZER: CONTACT WITH OTHER MATERIAL MAY CAUSE FIRE

HMIS:
Health: 2
Flammability: 0
Reactivity: 0
Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes severe irritation

Skin Contact: May cause irritation May cause allergic reaction

Skin Absorption: None Reported

Target Organs: None Reported

Ingestion: May cause: gastrointestinal irritation

Target Organs: None reported

Inhalation: Causes: irritation of nose and throat May cause: allergic respiratory reaction

Target Organs: None reported

Medical Conditions Aggravated: Pre-existing: Allergies or sensitivity to potassium persulfate.

Chronic Effects: Chronic overexposure may cause allergic skin reactions allergic respiratory reactions

Cancer / Reproductive Toxicity Information:

IARC Listed: No

NTP Listed: No

Additional Cancer / Reproductive Toxicity Information: None reported

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class D, Division 2, Subdivision B - Toxic material (other toxic effects) Class C - Oxidizing materials

WHMIS Symbols: Oxidizing Other Toxic Effects

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water. Call physician if irritation develops.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: Strong oxidizer. Contact with combustible materials may cause a fire. During a fire, this product decomposes to form toxic gases.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not determined

Hazardous Combustion Products: Toxic fumes of: sulfur oxides.

Fire / Explosion Hazards: May react violently with: strong reducers combustible materials

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Water.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear. Evacuate area and fight fire from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Stop spilled material from being released to the environment. Cover spilled solid material with sand or other inert material.

Clean-up Technique: Remove all combustible materials from the spill area. Cover with an inert material, such as sand. Sweep up material. Incinerate material at an E.P.A. approved hazardous waste facility. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: a pound or more of loose powder is spilled. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: 140

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin Do not breathe dust. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Keep away from: reducers oxidizable materials Protect from: moisture heat

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Use a fume hood to avoid exposure to dust, mist or vapor.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: lab coat disposable latex gloves

Inhalation Protection: laboratory fume hood

Precautionary Measures: Avoid contact with: eyes skin Do not breathe: dust Wash thoroughly after handling. Keep away from: oxidizable materials reducers

TLV: 5 mg/m³

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: White to light yellow crystals

Physical State: Solid

Molecular Weight: 270.32

Odor: None

pH: of 5% solution = 4.1

Vapor Pressure: Not applicable

Vapor Density (air = 1): Not applicable

Boiling Point: Not applicable

Melting Point: Decomposes at >100°C or 212°F

Specific Gravity (water = 1): 2.477

Evaporation Rate (water = 1): Not applicable

Volatile Organic Compounds Content: 0.0%

Coefficient of Water / Oil: Not determined

Solubility:

Water: Soluble

Acid: Not determined

Other: Not determined

Metal Corrosivity:

Steel: 0.704 in/yr

Aluminum: 0.137 in/yr

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Excess moisture Exposure to air. Heating to decomposition.

Reactivity / Incompatibility: May react violently in contact with: oxidizable material reducers

Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: sulfur oxides

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: Oral Rat LD50 = 802 mg/kg

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: Testing showed only slight erythema to rabbit skin.

Mutation Data: None reported

Reproductive Effects Data: None reported

--

Ingredient Toxicological Data: --
Not applicable

12. ECOLOGICAL INFORMATION

Product Ecological Information: --
No ecological data available for this product.
Ingredient Ecological Information: --
Not applicable

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Incinerate material at an E.P.A. approved hazardous waste facility.
Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash. Rinsate from empty containers may contain sufficient product to require disposal as hazardous waste.
NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:
Proper Shipping Name: Potassium Persulphate
--
Hazard Class: 5.1
PIN: 1492
Group: III
Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:
Canadian Inventory Status: DSL Listed: Yes
This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. The Merck Index, 11th Ed. Rahway, New Jersey: Merck and Co., Inc., 1989. Technical Judgment. Sax, N. Irving. Dangerous Properties of Industrial Materials, 7th Ed. New York: Van Nostrand Reinhold Co., 1989. List of Dangerous Substances Classified in Annex I of the EEC Directive (67/548) - Classification, Packaging and Labeling of Dangerous Substances, Amended July 1992. In-house information. Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Association, 1991. CCINFO RTECS. Canadian Centre for Occupational Health and Safety. Hamilton, Ontario Canada: 30 June 1993. CCINFO MSDS/FTSS. Canadian Centre for Occupational Health and Safety. Hamilton, Ontario Canada: 30 June 1993. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor).

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

**THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE.
HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA
OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.**

HACH COMPANY ©2009

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M01622

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Sodium Hydroxide Solution, 1.54N
Catalog Number: 2743042

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M01622
Chemical Name: Not applicable
CAS No.: Not applicable
Chemical Formula: Not applicable
Chemical Family: Not applicable
PIN: 1824
Intended Use: Standard solution
Date of MSDS Preparation:
Day: 22
Month: February
Year: 2010
MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Sodium Hydroxide

Percent Range: 5.0 - 15.0
Percent Range Units: weight / volume
CAS No.: 1310-73-2
LD50: Oral rat LDLo = 500 mg/kg.
LC50: None reported
TLV: 2 mg/m³ Ceiling/STEL
PEL: 2 mg/m³
Ingredient WHMIS Symbol: Corrosive

Demineralized Water

Percent Range: > 90.0
Percent Range Units: volume / volume
CAS No.: 7732-18-5
LD50: None reported
LC50: None reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance: Clear, colorless liquid

Physical State: Liquid
Odor: None
CAUSES SEVERE BURNS

HMIS:

Health: 3

Flammability: 0

Reactivity: 0

Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes severe burns

Skin Contact: Causes severe burns

Skin Absorption: None Reported

Target Organs: None Reported

Ingestion: Causes: severe burns vomiting rapid pulse and respirations shock collapse death

Target Organs: None reported

Inhalation: Causes: severe burns

Target Organs: None reported

Medical Conditions Aggravated: Pre-existing: Eye conditions Skin conditions Respiratory conditions

Chronic Effects: None reported

Cancer / Reproductive Toxicity Information:

This product does NOT contain any IARC listed chemicals.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: None reported

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class E - Corrosive material

WHMIS Symbols: Corrosive

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water for 15 minutes. Remove contaminated clothing. Call physician immediately.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air.

5. FIRE FIGHTING MEASURES

Flammable Properties: Material will not burn.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not applicable

Hazardous Combustion Products: This material will not burn.

Fire / Explosion Hazards: None reported

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Use media appropriate to surrounding fire conditions

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment.

Clean-up Technique: Cover spilled material with a dry acid, such as citric or boric. Scoop up slurry into a large beaker. Dilute with a large excess of water. Adjust to a pH between 6 and 9 with an acid, such as sulfuric or citric. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a weak acid solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: 154

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe mist or vapors. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Protect from: heat Keep away from: acids

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have a safety shower nearby. Have an eyewash station nearby. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: chemical splash goggles

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: mist/vapor Wash thoroughly after handling. Protect from: heat Keep away from: acids/acid fumes

TLV: Not established

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Clear, colorless liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: None

pH: >13

Vapor Pressure: Not determined

Vapor Density (air = 1): Not determined

Boiling Point: Not determined

Melting Point: Not applicable

Specific Gravity (water = 1): Not determined

Evaporation Rate (water = 1): Not determined

Volatile Organic Compounds Content: Not applicable

Coefficient of Water / Oil: Not applicable

Solubility:

Water: Miscible

Acid: Reacts with acid

Other: Not determined

Metal Corrosivity:

Steel: Not determined

Aluminum: Not determined

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Heat Evaporation Exposure to air.

Reactivity / Incompatibility: May react violently in contact with: strong acids Incompatible with: halogenated organic compounds tin aluminum zinc nitro compounds

Hazardous Decomposition: No hazardous decomposition products known.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: None reported

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: None reported

Mutation Data: None reported

Reproductive Effects Data: None reported

--

Ingredient Toxicological Data: Sodium hydroxide: oral rat LDLo = 500 mg/kg

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product.

Ingredient Ecological Information: --

No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an acid, such as sulfuric or citric. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash. Rinsate from empty containers may contain sufficient product to require disposal as hazardous waste.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Sodium Hydroxide Solution

--

Hazard Class: 8

PIN: 1824

Group: II

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor). Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. Technical Judgment. In-house information. Fire Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Fire

Protection Guide on Hazardous Materials, 10th Ed. Quincy, MA: National Fire Protection Association, 1991. List of Dangerous Substances Classified in Annex I of the EEC Directive (67/548) - Classification, Packaging and Labeling of Dangerous Substances, Amended July 1992.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2010

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M01616

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Phosphate Acid Reagent Vials
Catalog Number: 2742900

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M01616
Chemical Name: Not applicable
CAS No.: Not applicable
Chemical Formula: Not applicable
Chemical Family: Not applicable
PIN: 3264
Intended Use: Standard solution
Date of MSDS Preparation:
Day: 18
Month: February
Year: 2010
MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Demineralized Water

Percent Range: 90.0 - 100.0
Percent Range Units: volume / volume
CAS No.: 7732-18-5
LD50: None reported
LC50: None reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Sulfuric Acid

Percent Range: 1 - 9
Percent Range Units: weight / weight
CAS No.: 7664-93-9
LD50: Oral rat LD50 = 2140 mg/kg.
LC50: Inhalation rat LC50 = 87 ppm/4 hr
TLV: 1 mg/m³ (TWA); 3 mg/m³ (STEL)
PEL: 1 mg/m³
Ingredient WHMIS Symbol: Corrosive Other Toxic Effects

3. HAZARDS IDENTIFICATION

Emergency Overview:
Appearance: Clear, colorless liquid

Physical State: Liquid

Odor: None

CAUSES EYE BURNS MAY CAUSE RESPIRATORY TRACT IRRITATION

CANCER HAZARD CONTAINS SULFURIC ACID WHICH CAN CAUSE CANCER

HMIS:

Health: 4

Flammability: 0

Reactivity: 0

Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes eye burns.

Skin Contact: No effects are anticipated

Skin Absorption: None Reported

Target Organs: None Reported

Ingestion: Causes: irritation of the mouth and esophagus May cause: vomiting diarrhea

Target Organs: None reported

Inhalation: May cause: respiratory tract irritation teeth erosion mouth soreness difficult breathing

Target Organs: Lungs

Medical Conditions Aggravated: Pre-existing: Eye conditions Respiratory conditions

Chronic Effects: Chronic overexposure may cause erosion of the teeth chronic irritation or inflammation of the lungs cancer

Cancer / Reproductive Toxicity Information:

An ingredient of this mixture is: IARC Group 1: Recognized Carcinogen

Sulfuric Acid - The IARC evaluation was based on exposure to the mist or vapor of concentrated sulfuric acid generated during chemical processes.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: None reported

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class E - Corrosive material Class D, Division 2, Subdivision A - Very toxic materials (other toxic effects)

WHMIS Symbols: Corrosive Other Toxic Effects

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with plenty of water.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air.

5. FIRE FIGHTING MEASURES

Flammable Properties: Material will not burn. During a fire, irritating and highly toxic gases may be generated by thermal decomposition.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not determined

Hazardous Combustion Products: This material will not burn.

Fire / Explosion Hazards: This product will not burn or explode.

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Use media appropriate to surrounding fire conditions

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Absorb spilled liquid with non-reactive sorbent material. Stop spilled material from being released to the environment.

Clean-up Technique: Cover spilled material with an alkali, such as soda ash or sodium bicarbonate. Scoop up slurry into a large beaker. Dilute with a large excess of water. Adjust to a pH between 6 and 9. Use sulfuric or citric acid to lower pH. Use soda ash or sodium bicarbonate to increase pH. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: 154

7. HANDLING / STORAGE

Handling: Avoid contact with eyes. Do not breathe mist or vapors. Use with adequate ventilation. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Store between 10° and 25°C.

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Use general ventilation to minimize exposure to mist, vapor or dust. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: chemical splash goggles

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin. Do not breathe: mist/vapor. Use with adequate ventilation. Protect from: heat

TLV: Not established

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Clear, colorless liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: None

pH: Not determined

Vapor Pressure: Not determined

Vapor Density (air = 1): Not determined

Boiling Point: Not determined

Melting Point: Not applicable

Specific Gravity (water = 1): Not determined

Evaporation Rate (water = 1): Not determined

Volatile Organic Compounds Content: Not applicable

Coefficient of Water / Oil: Not applicable

Solubility:

Water: Soluble

Acid: Not determined

Other: Not determined

Metal Corrosivity:

Steel: Not determined

Aluminum: Not determined

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Extreme temperatures Heating to decomposition.
Reactivity / Incompatibility: Incompatible with: alkalies oxidizers reducers
Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: sulfur oxides
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: None reported

LC50: None reported

Dermal Toxicity Data: None reported

Skin and Eye Irritation Data: Skin irritation testing performed on 10% sulfuric acid showed SLIGHT to NO IRRITATION effects

Mutation Data: None reported

Reproductive Effects Data: None reported

--

Ingredient Toxicological Data: Sulfuric acid: oral rat LD50 = 2140 mg/kg; inhalation rat LC50 = 87 ppm/4h

12. ECOLOGICAL INFORMATION

Product Ecological Information: --

No ecological data available for this product.

Ingredient Ecological Information: --

No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Work in an approved fume hood. Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash. Rinsate from empty containers may contain sufficient product to require disposal as hazardous waste.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Corrosive Liquid, Acidic, Inorganic, N.O.S.

(< 10 % Sulphuric Acid Solution)

Hazard Class: 8

PIN: 3264

Group: III

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. In-house information. Technical Judgment. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. Vendor Information. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2010

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00127

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ammonia Salicylate Reagent
Catalog Number: 2395266

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00127

Chemical Name: Not applicable

CAS No.: Not applicable

Chemical Formula: Not applicable

Chemical Family: Not applicable

PIN: NA

Intended Use: Reagent for ammonia test

Date of MSDS Preparation:

Day: 15

Month: October

Year: 2009

MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Sodium Salicylate

Percent Range: 40.0 - 50.0

Percent Range Units: weight / weight

CAS No.: 54-21-7

LD50: Oral rat LD₅₀ = 1200 mg/kg; Oral mouse LD₅₀ = 540 mg/kg; Oral rabbit LD₅₀ = 1700 mg/kg.

LC50: None reported.

TLV: Respirable particles: 3 mg/m³; Inhalable particles: 10 mg/m³

PEL: Total dust: 15 mg/m³; Respirable fraction: 5 mg/m³

Ingredient WHMIS Symbol: Other Toxic Effects

Sodium Nitroferriocyanide

Percent Range: < 1.0

Percent Range Units: weight / weight

CAS No.: 14402-89-2

LD50: Oral rat LD₅₀ = 99 mg/kg (anhydrous).

LC50: None reported.

TLV: 5 mg/m³ as CN⁻

PEL: 5 mg/m³ as CN⁻

Ingredient WHMIS Symbol: Other Toxic Effects

Other components, each

Percent Range: 0.1 - 1.0

Percent Range Units: weight / weight

CAS No.: Not applicable

LD50: Not applicable

LC50: Not applicable
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Sodium Citrate

Percent Range: 40.0 - 50.0
Percent Range Units: weight / weight
CAS No.: 68-04-2
LD50: Oral rat LD50 >8 g/Kg
LC50: None Reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Sodium Tartrate

Percent Range: 10.0 - 20.0
Percent Range Units: weight / weight
CAS No.: 6106-24-7
LD50: Oral rabbit LD50 = 5290 mg/kg
LC50: None Reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: Tan powder

Physical State: Solid

Odor: None

HARMFUL IF SWALLOWED, INHALED OR ABSORBED THROUGH SKIN MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION

CONTACT WITH ACIDS FORMS TOXIC FUMES

HMIS:

Health: 3

Flammability: 1

Reactivity: 0

Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: May cause irritation

Skin Contact: May cause irritation

Skin Absorption: Harmful if absorbed through the skin Effects similar to those of ingestion Sodium nitroferrocyanide produces a delayed cyanide poisoning reaction.

Target Organs: Central nervous system Blood

Ingestion: Sodium nitroferrocyanide produces a delayed cyanide poisoning reaction. May cause: headache nausea vomiting central nervous system effects

Target Organs: Central nervous system Blood

Inhalation: Sodium nitroferrocyanide produces a delayed cyanide poisoning reaction. May cause: headache nausea, vomiting central nervous system effects

Target Organs: Central nervous system Blood

Medical Conditions Aggravated: Allergies or sensitivity to aspirin or salicylates.

Chronic Effects: Chronic overexposure may cause confusion diarrhea fatigue weakness death Salicylates may cause ringing in the ears (tinnitus), abnormal bleeding, gastric ulceration, mental deterioration, skin eruption, temporary vision loss, and other optical effects.

Cancer / Reproductive Toxicity Information:

This product does NOT contain any IARC listed chemicals.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: Contains: an experimental mutagen. an experimental teratogen.

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class D, Division 2, Subdivision A - Very toxic materials (other toxic effects)

WHMIS Symbols: Other Toxic Effects

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with soap and plenty of water. Remove contaminated clothing. Call physician immediately.

Ingestion (First Aid): Never give anything by mouth to an unconscious person. Call physician immediately.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: During a fire, this product decomposes to form toxic gases.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not determined.

Hazardous Combustion Products: May emit acrid smoke and fumes.

Fire / Explosion Hazards: This product will not burn or explode.

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Dry chemical. Carbon dioxide. Alcohol foam.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear. Evacuate area and fight fire from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Releases of this material may contaminate the environment. Stop spilled material from being released to the environment.

Clean-up Technique: Avoid contact with spilled material. Sweep up material. Dilute with a large excess of water. Flush the spilled material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: a pound or more of loose powder is spilled. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: None

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe dust. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Store between 10° and 25°C. Keep away from: acids / acid fumes. oxidizers

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Use a fume hood to avoid exposure to dust, mist or vapor.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: lab coat disposable latex gloves

Inhalation Protection: laboratory fume hood
Precautionary Measures: eyes skin clothing Do not breathe: dust Wash thoroughly after handling. Use with adequate ventilation. Keep away from: acids/acid fumes oxidizers
TLV: Not established.
PEL: Not established.

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Tan powder
Physical State: Solid
Molecular Weight: Not applicable
Odor: None
pH: 7.84 (5% solution)
Vapor Pressure: Not applicable
Vapor Density (air = 1): Not applicable
Boiling Point: Not applicable
Melting Point: 97°C (206.6°F)
Specific Gravity (water = 1): 1.689
Evaporation Rate (water = 1): Not applicable
Volatile Organic Compounds Content: None.
Coefficient of Water / Oil: Not applicable
Solubility:
 Water: Soluble.
 Acid: Soluble.
 Other: Not determined.
Metal Corrosivity:
 Steel: Not applicable
 Aluminum: Not applicable

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.
Conditions to Avoid: Heating to decomposition. Extreme temperatures
Reactivity / Incompatibility: Incompatible with: acids iodine iron salts lead acetate organic materials oxidizers silver nitrate sodium phosphate
Hazardous Decomposition: Heating to decomposition releases toxic and/or corrosive fumes of: cyanide nitrogen oxides sodium oxides
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:
 LD50: None reported.
 LC50: None reported.
 Dermal Toxicity Data: None reported.
 Skin and Eye Irritation Data: None reported.
 Mutation Data: None reported.
 Reproductive Effects Data: None reported.
 --
Ingredient Toxicological Data: Sodium Salicylate: Oral rat LD₅₀ = 1200 mg/kg; Sodium Citrate: Oral rat LD₅₀ > 8 g/kg; Sodium Tartrate: Oral rabbit LD₅₀ = 5290 mg/kg; Sodium Nitroferricyanide: Oral rat LD₅₀ = 99 mg/kg.

12. ECOLOGICAL INFORMATION

Product Ecological Information: --
No ecological data available for this product.
Ingredient Ecological Information: --
No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Dilute to 3 to 5 times the volume with cold water. Flush system with plenty of water.

Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Not Currently Regulated

--

Hazard Class: NA

PIN: NA

Group: NA

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL/NDSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992. Technical Judgment. Sixth Annual Report on Carcinogens, 1991. U.S. Department of Health and Human Services. Rockville, MD: Technical Resources, Inc. 1991. Sax, N. Irving. Dangerous Properties of Industrial Materials, 7th Ed. New York: Van Nostrand Reinhold Co., 1989. List of Dangerous Substances Classified in Annex I of the EEC Directive (67/548) - Classification, Packaging and Labeling of Dangerous Substances, Amended July 1992. In-house information. IARC Monographs on the Evaluation of the Carcinogenic Risks to Humans. World Health Organization (Volumes 1-42) Supplement 7. France: 1987. Gosselin, R. E. et al. Clinical Toxicology of Commercial Products, 5th Ed. Baltimore: The Williams and Wilkins Co., 1984. Cassaret and Doull's Toxicology, 3rd Ed. New York: Macmillan Publishing Co., Inc., 1986. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor).

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2009

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M00128

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Ammonia Cyanurate Reagent
Catalog Number: 2395466

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M00128
Chemical Name: Not Applicable
CAS No.: Not Applicable
Chemical Formula: Not Applicable
Chemical Family: Not applicable
PIN: 1759
Intended Use: Reagent for ammonia test
Date of MSDS Preparation:
Day: 15
Month: October
Year: 2009
MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Sodium Dichloroisocyanurate

Percent Range: 1.0 - 5.0
Percent Range Units: weight / weight
CAS No.: 2893-78-9
LD50: Oral rat LD50 = 1400 mg/kg; Oral human LDLo = 3570 mg/kg
LC50: None reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Lithium Hydroxide, Anhydrous

Percent Range: 1.0 - 5.0
Percent Range Units: weight / weight
CAS No.: 1310-65-2
LD50: Oral rat LD50 = 225 mg/kg
LC50: Inhalation rat LC50 = 980 mg/m³/4H
TLV: 3mg/m³ Respirable Particles; 10 mg/m³ Inhalable particles
PEL: 5 mg/m³ Respirable Fraction; 15 mg/m³ Total Dust
Ingredient WHMIS Symbol: Corrosive

Sodium Citrate

Percent Range: 80.0 - 90.0
Percent Range Units: weight / weight
CAS No.: 68-04-2
LD50: Oral rat LD50 >8 g/Kg

LC50: None Reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

Sodium Tartrate

Percent Range: 5.0 - 15.0
Percent Range Units: weight / weight
CAS No.: 6106-24-7
LD50: Oral rabbit LD50 = 5290 mg/kg
LC50: None Reported
TLV: Not established
PEL: Not established
Ingredient WHMIS Symbol: Not applicable

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: White powder
Physical State: Solid
Odor: Chlorine
CAUSES BURNS HARMFUL IF SWALLOWED
MAY CAUSE KIDNEY OR LIVER DAMAGE BASED ON ANIMAL DATA

HMIS:

Health: 3
Flammability: 1
Reactivity: 1
Protective Equipment: X - See protective equipment, Section 8.

Potential Health Effects:

Eye Contact: Causes eye burns.
Skin Contact: Causes burns.
Skin Absorption: None Reported
Target Organs: None Reported
Ingestion: Causes: burns May cause: dizziness nausea kidney damage liver damage
Target Organs: Liver Kidneys Central nervous system Bone marrow
Inhalation: Causes: burns May cause: shortness of breath coughing
Target Organs: None reported
Medical Conditions Aggravated: Pre-existing: Eye conditions Skin conditions Respiratory conditions
Chronic Effects: Lithium compounds have been implicated in development of aplastic anemia. Signs of lithium poisoning include dehydration, extreme weight loss, fine tremor of hands, nausea, vomiting and diarrhea, Chronic overexposure may cause central nervous system effects kidney damage liver damage
Cancer / Reproductive Toxicity Information:
This product does NOT contain any IARC listed chemicals.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: None reported

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Class E - Corrosive material Class D, Division 2, Subdivision B - Toxic material (other toxic effects)

WHMIS Symbols: Corrosive Other Toxic Effects

4. FIRST AID

Eye Contact: Immediately flush eyes with water for 15 minutes. Call physician.

Skin Contact (First Aid): Wash skin with soap and plenty of water for 15 minutes. Remove contaminated clothing. Call physician immediately.

Ingestion (First Aid): Do not induce vomiting. Give 1-2 glasses of water. Call physician immediately. Never give anything by mouth to an unconscious person.

Inhalation: Remove to fresh air. Give artificial respiration if necessary. Call physician.

5. FIRE FIGHTING MEASURES

Flammable Properties: During a fire, irritating and highly toxic gases may be generated by thermal decomposition.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not determined

Hazardous Combustion Products: May emit toxic and corrosive fumes.

Fire / Explosion Hazards: Not combustible.

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Dry chemical. Carbon dioxide. Water.

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Cover spilled solid material with sand or other inert material. Stop spilled material from being released to the environment.

Clean-up Technique: Scoop up spilled material into a large beaker and dissolve with water. Adjust to a pH between 6 and 9 with an acid, such as sulfuric or citric. Flush reacted material to the drain with a large excess of water. Decontaminate the area of the spill with a soap solution.

Evacuation Procedure: Evacuate local area (15 foot radius or as directed by your facility's emergency response plan) when: any quantity is spilled. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: 154

7. HANDLING / STORAGE

Handling: Avoid contact with eyes skin clothing Do not breathe dust. Wash thoroughly after handling. Maintain general industrial hygiene practices when using this product.

Storage: Protect from: heat moisture Store away from: acids / acid fumes.

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Have an eyewash station nearby. Have a safety shower nearby. Use a fume hood to avoid exposure to dust, mist or vapor. Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: disposable latex gloves lab coat

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes skin clothing Do not breathe: dust Wash thoroughly after handling. Keep away from: acids/acid fumes metals

TLV: 3mg/m³ Respirable Particles; 10 mg/m³ Inhalable particles

PEL: 5 mg/m³ Respirable Fraction; 15 mg/m³ Total Dust

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: White powder

Physical State: Solid

Molecular Weight: Not applicable
Odor: Chlorine
pH: of a 5% solution = 12.33
Vapor Pressure: Not applicable
Vapor Density (air = 1): Not applicable
Boiling Point: Not applicable
Melting Point: >240 °C, >464 °F
Specific Gravity (water = 1): 1.783
Evaporation Rate (water = 1): Not applicable
Volatile Organic Compounds Content: None reported
Coefficient of Water / Oil: Not applicable
Solubility:
 Water: Soluble
 Acid: Soluble
 Other: Not determined
Metal Corrosivity:
 Steel: 0.00 in/yr
 Aluminum: 0.803 in/yr

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.
Conditions to Avoid: Heating to decomposition. Extreme temperatures Excess moisture
Reactivity / Incompatibility: Incompatible with: acids
Hazardous Decomposition: Contact with acids releases toxic and/or corrosive fumes of: chlorides nitrogen oxides
Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:
 LD50: None Reported
 LC50: None Reported
 Dermal Toxicity Data: None Reported
 Skin and Eye Irritation Data: None Reported
 Mutation Data: None Reported
 Reproductive Effects Data: None Reported

--

Ingredient Toxicological Data: Sodium Citrate Oral rat LD50 > 8 g/kg; Sodium Tartrate Oral rabbit LD50 = 5290 mg/kg;
Lithium Hydroxide Oral rat LD50 = 225 mg/kg; Sodium Dichloroisocyanurate Oral rat LD50 = 1400 mg/kg

12. ECOLOGICAL INFORMATION

Product Ecological Information: --
No ecological data available for this product.
Ingredient Ecological Information: --
No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an acid, such as sulfuric or citric. Open cold water tap completely, slowly pour the reacted material to the drain. Flush system with plenty of water.
Empty Containers: Rinse three times with an appropriate solvent. Dispose of empty container as normal trash.
NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Corrosive Solid, N.O.S.

(Lithium Hydroxide Mixture)

Hazard Class: 8

PIN: 1759

Group: II

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: NIOSH Registry of Toxic Effects of Chemical Substances, 1985-86. Cincinnati: U.S. Department of Health and Human Services, April, 1987. Patty, Frank A. Industrial Hygiene and Toxicology, 3rd Revised Edition. Volume 2. New York: A Wiley-Interscience Publication, 1981. Gosselin, R. E. et al. Clinical Toxicology of Commercial Products, 5th Ed. Baltimore: The Williams and Wilkins Co., 1984. Technical Judgment. In-house information. Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. TLV's Threshold Limit Values and Biological Exposure Indices for 1992-1993. American Conference of Governmental Industrial Hygienists, 1992.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

HACH COMPANY ©2009

World Headquarters
Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

MSDS No: M01553

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: AmVer™ High Range Ammonia Test 'N Tube™ Reagent
Catalog Number: 2607000

Hach Company
P.O.Box 389
Loveland, CO USA 80539
(970) 669-3050

Emergency Telephone Numbers:
(Medical and Transportation)
(303) 623-5716 24 Hour Service
(515)232-2533 8am - 4pm CST

MSDS Number: M01553

Chemical Name: Not applicable

CAS No.: Not applicable

Chemical Formula: Not applicable

Chemical Family: Not applicable

PIN: NA

Intended Use: Determination of ammonium nitrogen

Date of MSDS Preparation:

Day: 10

Month: March

Year: 2010

MSDS Prepared: MSDS prepared by Product Compliance Department extension 3350

2. COMPOSITION / INFORMATION ON INGREDIENTS

Demineralized Water

Percent Range: > 99.0

Percent Range Units: volume / volume

CAS No.: 7732-18-5

LD50: None reported

LC50: None reported

TLV: Not established

PEL: Not established

Ingredient WHMIS Symbol: Not applicable

Other components, each

Percent Range: < 1.0

Percent Range Units: weight / volume

CAS No.: Not applicable

LD50: Not applicable

LC50: Not applicable

TLV: Not established

PEL: Not established

Ingredient WHMIS Symbol: Not applicable

3. HAZARDS IDENTIFICATION

Emergency Overview:

Appearance: Colorless liquid

Physical State: Liquid
Odor: None

HMIS:

Health: 0

Flammability: 0

Reactivity: 0

Protective Equipment: Not applicable

Potential Health Effects:

Eye Contact: No effects are anticipated

Skin Contact: No effects are anticipated

Skin Absorption: No effects anticipated

Target Organs: Not applicable

Ingestion: No Effects Anticipated

Target Organs: Not applicable

Inhalation: No effects anticipated

Target Organs: Not applicable

Medical Conditions Aggravated: None reported

Chronic Effects: No effects anticipated

Cancer / Reproductive Toxicity Information:

This product does NOT contain any IARC listed chemicals.

This product does NOT contain any NTP listed chemicals.

Additional Cancer / Reproductive Toxicity Information: None reported

Toxicologically Synergistic Products: None reported

WHMIS Hazard Classification: Not applicable

WHMIS Symbols: Not applicable

4. FIRST AID

Eye Contact: Flush eyes with water. Call physician if irritation develops.

Skin Contact (First Aid): Wash skin with plenty of water.

Ingestion (First Aid): Give large quantities of water. Call physician immediately.

Inhalation: None required.

5. FIRE FIGHTING MEASURES

Flammable Properties: Material will not burn.

Flash Point: Not applicable

Method: Not applicable

Flammability Limits:

Lower Explosion Limits: Not applicable

Upper Explosion Limits: Not applicable

Autoignition Temperature: Not applicable

Hazardous Combustion Products: This material will not burn.

Fire / Explosion Hazards: None reported

Static Discharge: None reported.

Mechanical Impact: None reported

Extinguishing Media: Use media appropriate to surrounding fire conditions

Fire Fighting Instruction: As in any fire, wear self-contained breathing apparatus pressure-demand and full protective gear. Evacuate area and fight fire from a safe distance.

6. ACCIDENTAL RELEASE MEASURES

Spill Response Notice:

Only persons properly qualified to respond to an emergency involving hazardous substances should respond to a spill involving chemicals. See Section 13, Special Instructions for disposal assistance.

Containment Technique: Stop spilled material from being released to the environment.

Clean-up Technique: Cover spilled material with a dry acid, such as citric or boric. Scoop up slurry into a large beaker. Adjust to a pH between 6 and 9 with an acid, such as sulfuric or citric. Flush reacted material to the drain with a large excess of water.

Evacuation Procedure: Evacuate as needed to perform spill clean-up. If conditions warrant, increase the size of the evacuation.

D.O.T. Emergency Response Guide Number: None

7. HANDLING / STORAGE

Handling: Maintain general industrial hygiene practices when using this product.

Storage: Keep container tightly closed when not in use.

8. EXPOSURE CONTROLS / PROTECTIVE EQUIPMENT

Engineering Controls: Maintain general industrial hygiene practices when using this product.

Personal Protective Equipment:

Eye Protection: safety glasses with top and side shields

Skin Protection: disposable latex gloves

Inhalation Protection: adequate ventilation

Precautionary Measures: Avoid contact with: eyes

TLV: Not established

PEL: Not established

9. PHYSICAL / CHEMICAL PROPERTIES

Appearance: Colorless liquid

Physical State: Liquid

Molecular Weight: Not applicable

Odor: None

pH: 11

Vapor Pressure: Not determined

Vapor Density (air = 1): Not determined

Boiling Point: ~ 100° C (~212° F)

Melting Point: Not determined

Specific Gravity (water = 1): ~1.00

Evaporation Rate (water = 1): Not determined

Volatile Organic Compounds Content: Not applicable

Coefficient of Water / Oil: Not applicable

Solubility:

Water: Miscible

Acid: Miscible

Other: Not determined

Metal Corrosivity:

Steel: Not determined

Aluminum: Not determined

10. STABILITY / REACTIVITY

Chemical Stability: Stable when stored under proper conditions.

Conditions to Avoid: Extreme temperatures

Reactivity / Incompatibility: None reported

Hazardous Decomposition: None reported

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Product Toxicological Data:

LD50: None reported

LC50: None reported

Dermal Toxicity Data: None reported
Skin and Eye Irritation Data: None reported
Mutation Data: None reported
Reproductive Effects Data: None reported

--
Ingredient Toxicological Data: --
No toxicological data available for the ingredients of this product.

12. ECOLOGICAL INFORMATION

Product Ecological Information: --
No ecological data available for this product.
Ingredient Ecological Information: --
No ecological data available for the ingredients of this product.

13. DISPOSAL CONSIDERATIONS

Special Instructions (Disposal): Dilute to 3 to 5 times the volume with cold water. Adjust to a pH between 6 and 9 with an alkali, such as soda ash or sodium bicarbonate. Open cold water tap completely, slowly pour the reacted material to the drain. Allow cold water to run for 5 minutes to completely flush the system.

Empty Containers: Dispose of empty container as normal trash.

NOTICE (Disposal): These disposal guidelines are based on federal regulations and may be superseded by more stringent state or local requirements. Please consult your local environmental regulators for more information.

14. TRANSPORT INFORMATION

T.D.G.:

Proper Shipping Name: Not Currently Regulated

--

Hazard Class: NA

PIN: NA

Group: NA

Subsidiary Risk: NA

Additional Information: There is a possibility that this product could be contained in a reagent set or kit composed of various compatible dangerous goods. If the item is NOT in a set or kit, the classification given above applies. If the item IS part of a set or kit, the classification would change to the following: UN3316 Chemical Kit, Class 9, PG II or III. If the item is not regulated, the Chemical Kit classification does not apply.

15. REGULATORY INFORMATION

National Inventories:

Canadian Inventory Status: All ingredients of this product are DSL Listed.

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

16. OTHER INFORMATION

References: 29 CFR 1900 - 1910 (Code of Federal Regulations - Labor). Air Contaminants, Federal Register, Vol. 54, No. 12. Thursday, January 19, 1989. pp. 2332-2983. Technical Judgment.

Legend:

NA - Not Applicable	w/w - weight/weight
ND - Not Determined	w/v - weight/volume
NV - Not Available	v/v - volume/volume

USER RESPONSIBILITY: Each user should read and understand this information and incorporate it in individual site safety programs in accordance with applicable hazard communication standards and regulations.

**THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE.
HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THESE DATA
OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.**

HACH COMPANY ©2010

Appendix G

Relevant Spill Contingency and Reporting Regulations

CONSOLIDATION OF REGULATION R -068-93 *SPILL CONTINGENCY PLANNING AND REPORTING REGULATIONS* (Dated 22 July, 1993)

AS AMENDED BY:

USE OF CONSOLIDATION

This Consolidation is provided for use by the Department of Resources, Wildlife and Economic Development staff only. It is not provided to the public. The public may purchase Gazette copies of Legislation or subscriptions to receive Legislation from the company contracted by the Government of the Northwest Territories for that purpose.

This Consolidation is not an Official (Gazette) copy of the Law.
It is prepared by Manager, Enforcement and Legislative Services,
Department of Resources, Wildlife and Economic Development
Government of the Northwest Territories
for use by:
Department of Resources, Wildlife and Economic Development staff only.

SPILL CONTINGENCY PLANNING AND REPORTING REGULATIONS

TABLE OF CONTENTS

	<u>SECTION</u>
Definitions Regulations	1
Exemption Motor Vehicle/Sewage/Sludge	2 (1)
Exemption Domestic Contaminants	(2)
Explanation Schedule A	(3)
Explanation Schedule B	(4)

SPILL CONTINGENCY PLAN

No Storage Contaminants in Excess of Schedule A	3 (1)
- No Contingency Plan	
Special Requirement Contingency Plan	(2)
Exemption Filing Contingency Plan	(3)
Onus to Prepare Spill Contingency Plan	4 (1)
Information Requirement Spill Contingency Plan	(2)
File Plan Chief EPO	5 (1)
One Year Exemption to File Plan	(2)
Chief EPO Review Plan	6 (1)
Requirement for Change to Plan	(2)
Time to Make Changes	(3)
Obligation to Complete Plan	(4)
Annual Review Plan	7 (1)
Filing Revised Plan	(2)
Implementation of Plan	8

SPILLS

Requirement to Report Spill	9	(1)
Requirement to Report Potential Spill		(2)
24 Hour Spill Line Number	10	
Information Requirement Spill Report	11	(1)
No Delay Reporting for Lack of Complete Information		(2)
False Report of Spill	12	
Requirement Owner to Provide Report on Spill	13	(1)
Information in Report to Chief EPO		(2)

Schedule A - Facilities

Schedule B - Spill Report Minimum

ENVIRONMENTAL PROTECTION ACT

SPILL CONTINGENCY PLANNING AND REPORTING REGULATIONS

The Commission, on the recommendation of the Minister, under section 34 of the *Environmental Protection Act* and every enabling power, makes the *Spill Contingency Planning and Reporting Regulations*.

1. In this regulations,

Aabove ground facility \equiv means a facility that is stationary for a period of 30 days or more and is not an underground facility;

AAct \equiv means the *Environmental Protection Act*;

Afacility \equiv means any thing capable of storing or containing contaminants and includes any thing used in the transfer of contaminants to and from the facility;

APCB \equiv means the chlorobiphenyls that have the molecular formula $C_{12}H_{10-N}Cl_N$ in which N is great than 2;

Aspill \equiv means a discharge of a contaminant in contravention of the Act or regulations made under the Act or a permit or license issued under the Act or regulations made under the Act;

Astorage capacity \equiv means the aggregate capacity of all facilities placed together in one location;

ATDGA Class \equiv means a class of dangerous goods set out in the Schedule to the *Transportation of Dangerous Goods Act, 1992* (Canada), and any division of a class established in regulations made or continued under that Act;

Aunderground facility \equiv means a facility having more than 10% of its structure beneath ground level.

2. (1) Sections 3 to 8 of these regulations to not apply to the following:

- (a) a motor vehicle, as defined in the *Motor Vehicles Act*, unless that motor vehicle is an above ground facility;
- (b) sewage and sewage sludge.

- (2) Contaminants used solely for domestic purposes and discharged from within a dwelling-house are exempt from the requirements of these regulations.
- (3) In Schedule A, the amounts set out in column 3 under the heading AStorage Capacity \equiv refer to liquids, where the amount is expressed in liters, and to solids, where the amount is expressed in kilograms.
- (4) In Schedule B, the amounts set out in column 4 under the heading AAmount Spilled \equiv refer to liquids, where the amount is expressed in liters, and to solids, where the amount is expressed in kilograms.

SPILL CONTINGENCY PLAN

- 3. (1) No person shall store contaminants in a facility where the storage capacity of the facility equals or exceeds the storage capacity shown in Schedule A unless a spill contingency plan has been prepared and filed in accordance with these regulations.
- (2) Where the storage capacity of a facility is less than the storage capacity shown in Schedule A and where, in the opinion of the Chief Environmental Protection Officer a spill contingency plan is necessary for the protection of the environment, the Chief Environmental Protection Officer may require the owner or person in charge, management or control of a facility to prepare a spill contingency plan.
- (3) Where the Chief Environmental Protection Officer is satisfied, on reasonable grounds, that a person uses a means of storing contaminants and a method of dealing with the spill of contaminants, that provide a level of environmental protection at least equivalent to that which would be provided by compliance with these regulations, the Chief Environmental Protection Officer may, in writing, subject to such conditions as the Chief Environmental Protection Officer considers necessary,
 - (a) exempt a person from the requirement to file a spill contingency plan under subsection (1); or
 - (b) exempt a person from the requirement to include in a spill contingency plan information required in one or more of paragraphs 4(2)(a) to (j).
- 4. (1) The owner or person in charge, management or control of a facility shall ensure that a spill contingency plan is prepared.

- (2) A spill contingency plan for a facility must contain the following information:
- (a) the name, address and job title of the owner or person in charge, management or control;
 - (b) the name, job title and 24-hour telephone number for the persons responsible for activating the spill contingency plan;
 - (c) a description of the facility including the location, size and storage capacity;
 - (d) a description of the type and amount of contaminants normally stored at the location described in paragraph (c);
 - (e) a site map of the location described in paragraph (c);
 - (f) the steps to be taken to report, contain, clean up and dispose of contaminants in the case of a spill;
 - (g) the means by which the spill contingency plan is activated;
 - (h) a description of the training provided to employees to respond to a spill;
 - (i) an inventory of and the location of response and clean-up equipment available to implement the spill contingency plan;
 - (j) the date the contingency plan was prepared.
5. (1) Subject to subsection (2), the person responsible for preparing a spill contingency plan shall file the plan with the Chief Environmental Protection Officer before making use of a facility.
- (2) Where a facility is already in use on the day these regulations come into force, the person responsible for preparing a spill contingency plan shall file the plan with the Chief Environmental Protection Officer within one year after that day.
6. (1) The Chief Environmental Protection Officer shall review each spill contingency plan after it is filed.
- (2) The Chief Environmental Protection Officer may require the person who filed the spill contingency plan to make changes to it.
- (3) Where the Chief Environmental Protection Officer requires changes under subsection (2), he or she may indicate a reasonable period of time within which the changes must be filed.
- (4) The person who filed a spill contingency plan shall make and file any changes required under subsection (2).
7. (1) The person responsible for preparing a spill contingency plan shall review the plan annually.
- (2) The person responsible for preparing a spill contingency plan shall, in writing,

notify the Chief Environmental Protection Officer when a review under subsection (1) has been completed and shall immediately file with the Chief Environmental Protection Officer any changes made to the plan.

8. Once a spill contingency plan has been filed, the person responsible for preparing the plan shall implement the plan.

SPILLS

9.
 - (1) The owner or person in charge, management or control of contaminants at the time a spill occurs shall immediately report the spill where the spill is of an amount equal to or greater than the amount set out in Schedule B.
 - (2) Where there is a reasonable likelihood of a spill in an amount equal to or greater than the amount set out in Schedule B, the owner or person in charge, management or control of the contaminants shall immediately report the potential spill.
10. A person reporting a spill shall contact the 24 Hour Spill Report Line by calling **(403) 920-8130**.
11.
 - (1) A person reporting a spill shall give as much of the following information as possible:
 - (a) date and time of spill;
 - (b) location of spill;
 - (c) direction spill is moving;
 - (d) name and phone number of a contact person close to the location of spill;
 - (e) type of contaminant spilled and quantity spilled;
 - (f) cause of spill;
 - (g) whether spill is continuing or has stopped;
 - (h) description of existing contaminant;
 - (i) action taken to contain, recover, clean-up and dispose of spilled contaminant;
 - (j) name, address and phone number of person reporting spill;
 - (k) name of owner or person in charge, management or control of contaminants at time of spill.
 - (2) No person shall delay reporting a spill because of lack of knowledge of any of the factors listed in subsection (1).
12. No person shall knowingly make a false report of a spill or a potential spill.

- 13. (1)** For the purposes of evaluating the effectiveness of the spill contingency plan, the Chief Environmental Protection Officer may require, in writing, the owner or person in charge, management or control of a facility at the time a spill occurred to prepare and file a written report concerning the spill.
- (2)** The person required to prepare the report described in subsection (1) shall provide all information required by the Chief Environmental Protection Officer.

Dated at Yellowknife July 22, 1993.

Original signed by
D.L. Norris
Commissioner of the Northwest Territories

SCHEDULE A

(Section 3)

<i>Item No.</i>	<i>Type of Facility</i>	<i>Storage Capacity</i>
1.	Above-ground facility	20,000 l or 20,000 kg
2.	Under-ground facility	4,000 l or 4,000 kg

SCHEDULE B

(Section 9)

<i>Item No.</i>	<i>TDGA Class</i>	<i>Description of Contaminant</i>	<i>Amount Spoiled</i>
1.	1	Explosives	Any amount
2.	2.1	Compressed gas (flammable)	Any amount of gas from containers with a capacity greater than 100 l.
3.	2.2	Compressed gas (non-corrosive, non flammable)	Any amount of gas from containers with a capacity greater than 100 l.
4.	2.3	Compressed gas (toxic)	Any amount
5.	2.4	Compressed gas (corrosive)	Any amount
6.	3.1, 3.2, 3.3	Flammable liquid	100 l
7.	4.1	Flammable solid	25 kg
8.	4.2	Spontaneously combustible solids	25 kg
9.	4.3	Water reactant solids	25 kg
10.	5.1	Oxidizing substances	50 l or 50 kg
11.	5.2	Organic Peroxides	1 l or 1 kg
12.	6.1	Poisonous substances	5 l or 5 kg
13.	6.2	Infectious substances	Any amount
14.	7	Radioactive	Any amount
15.	8	Corrosive substances	5 l or 5 kg
16.	9.1 (in part)	Miscellaneous products or substances, excluding PCB mixtures	50 l or 50 kg
17.	9.2	Environmentally hazardous	1 l or 1 kg
18.	9.3	Dangerous wastes	5 l or 5 kg
19.	9.1 (in part)	PCB mixtures of 5 or more parts per million	0.5 l or 0.5 kg
20.	None	Other contaminants	100 l or 100 kg

