

PHASE 2 OF THE HOPE BAY PROJECT
DRAFT ENVIRONMENTAL IMPACT STATEMENT

Appendix V5-1J


Doris North Project: 2013 Hydrology Compliance
Monitoring Report



TMAC Resources Inc.

DORIS NORTH PROJECT

2013 Hydrology Compliance Monitoring Report



ERM Rescan
Suite 908-5201 50th Avenue
Yellowknife, NT Canada X1A 3S9
Tel: (867) 920-2090 Fax: (867) 920-2015

February 2014

DORIS NORTH PROJECT

2013 HYDROLOGY COMPLIANCE

MONITORING REPORT

February 2014
Project #0194098-0004

Citation:


ERM Rescan. 2014. *Doris North Project: 2013 Hydrology Compliance Monitoring Report*. Prepared for TMAC Resources Inc. by ERM Rescan: Yellowknife, Northwest Territories.

Prepared for:



TMAC Resources Inc.

Prepared by:



ERM Rescan
Yellowknife, Northwest Territories

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Executive Summary



Executive Summary

The Doris North Project (the Project) is located within the Hope Bay Belt, an 80 by 20 kilometer property located along the south shore of Melville Sound in Nunavut. The property consists of a greenstone belt (the Hope Bay Belt) that contains three main gold deposits. The Doris and Madrid deposits are located in the northern portion of the belt, and the Boston deposit is at the southern end. The Project is located approximately 125 km southwest of Cambridge Bay on the southern shore of Melville Sound. The nearest communities are Umingmaktok (75 km to the southwest of the property), Cambridge Bay, and Kingaok (Bathurst Inlet; 160 km to the southwest of the property).

TMAC Resources Inc. (TMAC) acquired the Hope Bay Belt Project from Newmont Corporation in March 2013. The acquisition included exploration and mineral rights over the Hope Bay Belt, including the Doris North Gold Mine and its permits, licences and authorizations for development received by previous owners. In late 2012, prior to the sale, the Hope Bay Belt Project was placed into care and maintenance, and the project was seasonally closed during the winter of 2012/2013. TMAC re-opened the Doris North Camp in March of 2013 for the purposes of conducting site water management, environmental compliance programs and to support exploration activities. The Doris North Project remains in care and maintenance although it will not be seasonally closed for the winter of 2013/2014.

The compliance requirements for hydrometric monitoring applicable to the Doris North Project Certificate (Nunavut Impact Review Board (NIRB) No. 003, issued September 15, 2006; NIRB 2006) and Type A Water Licence (Nunavut Water Board (NWB) Licence No. 2AM-DOH0713 Type A, issued September 19, 2007; NWB 2007) are as follows:

- Doris North Project Certificate
 - [The Proponent] will monitor stage and discharge in Doris Outflow both upstream and downstream of the decant discharge point to provide information that can be used in assessing the accuracy of the impact predictions relating to fish habitat downstream.
- Doris North Project Type A Water Licence
 - Part G, Item 30. The Licensee shall ensure that flow from the [Tail Lake] Tailings Impoundment Area into Doris Creek at monitoring station TL-4 does not exceed 10% of the background flow in Doris Creek as measured at monitoring station TL-2 at the time of discharge.
 - Part J, Item 2. The Licensee shall install appropriate instrumentation in Doris Creek at monitoring station TL-2, to monitor flow when ice conditions allow for such measurements to be taken, on a real time and continuous basis.
 - Part J, Item 3. The Licensee shall undertake the Water Monitoring Program detailed in the Tables of Schedule J.

The 2013 hydrology monitoring program also supported work required by the Tail Lake Outflow Fisheries Authorization (NU-02-0117.3), the No Net Loss Plan (Golder 2007) and No Net Loss Plan Updates (Rescan 2010a, Rescan 2010b), and portions of the water quantity monitoring schedule detailed in the *Doris North Project Interim Water Management Plan* (SRK 2012).

To comply with these requirements, TMAC contracted ERM Consultants Canada Inc. (ERM Rescan) to undertake monitoring activities at the site and report on its findings. This report presents the methodology and results of the 2013 hydrology compliance monitoring program. The goals of the 2013

program were to support the regulatory compliance requirements described above and to add to data records at existing sites within the Doris North area.

A network of six automated hydrometric monitoring stations was operated within the Doris North Project area as part of the 2013 hydrology compliance monitoring program. Lake and stream water levels were monitored at stations Doris TL-2 (Doris Creek upstream), Doris TL-3 (Doris Creek downstream), Windy Hydro (Windy Lake outflow), Roberts Hydro (Roberts Lake outflow), Doris Lake, and Tail Lake. The 2013 program commenced in early June and continued until early September, when stations Doris TL-2, Doris TL-3, Windy Hydro, and Roberts Hydro were demobilized for the winter. The hydrometric stations at Doris and Tail lakes remain in operation and will continue recording data through the 2013/2014 winter season.

During the automated monitoring period, continuous time series stage data were collected at each station. In 2013 a total of 30 manual discharge measurements were completed with a minimum of five measurements conducted at each stream monitoring station. The stage and discharge data were used to develop stage-discharge rating equations and generate hydrographs.

Changes in the channel geometry at the Doris TL-2 monitoring station altered the channel hydraulics compared to previous years. Therefore, a new rating curve was generated based on 2013 manual flow measurements. It is expected that this rating curve, and its resulting hydrograph and hydrologic indices, will be modified and improved when more rating points are available based on future manual flow measurements.

In the 2013 open water season, runoff in the monitored watersheds ranged between 40 mm and 56 mm. Mean discharge for the open water season ranged from 0.07 m³/s at station Windy Hydro (drainage area 14.1 km²) to 0.67 m³/s at station Roberts Hydro (drainage area 97.9 km²). Peak flows for 2013 occurred in mid-June for stations Doris TL-2, Doris TL-3, and Roberts Hydro, and in early July for station Windy Hydro. Daily peak flows ranged from 0.12 m³/s at station Windy Hydro to 1.97 m³/s at station Roberts Hydro. Low flows for the open water season occurred in late August at station Doris TL-3 and early September at stations Doris TL-2, Roberts Hydro, and Windy Hydro. Low flows ranged from 0.02 m³/s at station Windy Hydro to 0.11 m³/s at station Roberts Hydro.

To comply with the requirements of Part G, Item 30 and Part J, Item 2 of the Type A Water Licence, the Doris Creek flow prediction program conducted in 2011-2012 was continued in 2013. Doris Creek water levels were recorded on a continuous basis. A satellite telemetry station provided remote access to real-time data, allowing daily flow volume predictions. The results indicate that there was not an overall prediction exceedance relative to the recorded background flow volume in Doris Creek.

Water level fluctuation was similar at Doris and Tail lakes in 2013, varying by approximately 0.3 m at each lake. Water levels at both Doris and Tail lakes peaked in mid-June as a result of snow and ice melt during freshet, then declined throughout July and August. At Windy Lake, water level variation over the open water season was 0.10 m, less than that observed at Doris and Tail lakes. Windy Lake water level increased rapidly in early to mid-June, then remained fairly consistent throughout most of June and July, reaching an annual peak in early July before declining until late August. A series of precipitation events from late August to early September slowed the rate of water level decrease at all three lakes, resulting in stabilization of water levels at Doris Lake and slight recharge of Tail and Windy lakes in early September.

Compared to previous monitoring years (2009-2012), 2013 was a drier year in terms of runoff and discharge. For all stream monitoring stations the 2013 open water season runoff was 52-72% less than the average open water season runoff for 2009 to 2012.

Atanguyan Naetomik Okaohen

Doris North-mi Havaak (Havaak) inikaktok Kapihilitumi, 80-kilamitamik avatiknun 20-kilamitamiklo avatiknun nunagiyaoyok hinaani hivogaata Melville Sound, Nunavumi. Nanminigyaoyok oyagaktagakhaktok (Kapihilitumi Oyagaktaakhan) pikatok pigahunik kulmik oyagaktavikhanik. Doris-mi Madrid-milo oyagaktaakhan tununganetun oyagaktavikham, Boston-milo oyagaktaakhan hivugaanetun. Havaak inikaktok 125-nik kilamitamik ugahiknikaktomik hivugaata oalikheani Ikaloktuteam hivugaata hinaani Melville sound-goyum. Kaninikhak nunangiyaoyun uko Umikmuktuk (75-nik kilamitamik ugahiknikaktok hivugaata oalikheani oyagaktavikham), Ikaloktuteak, Kigaoklo (Kigaok 160-nik kilamitamik ugahiknikaktok hivugaata oalikheani oyagakteavikham).

TMAC-kon neovikhimaya Kapihilitumi Oyagaktavikham Newmont-konin March-mi 2013-mi. Neovikniga ilakaktok nälvakheoknikun oyagaktaakhaniklo ihomakhutinik Kipihilitumi, unalo Doris North-mi Kulmik Oyagaktavik piyonaoetaelo, laesigyaelo agigutilo oyagaktavigyaagani pihimayun nanminikaktugaluyonin. Nuguliktilogo 2012 ukeok, neoviktaotinagu, Kapihilitumi Oyagaktavikham monagyaolikhimayok, havaaklo ilagani ukeom umikhimayok ukeogani 2012, 2013-lo. TMAC-kon akmavaaktaan Doris North-mi Iglukpakavik March-mi, 2013-mi talvani imavaloen monagyaagani, avatilikeyotilo atogeakmagaa havaan ikayoktoklogilo nälvakheoktun hulilogaagutaen. Doris North-mi Havaak aolagitok monagyaoginakniganik ilagani umikhimalimaetugaloak ukeomi 2013-min 2014-mun.

Atoteageagani piyageakaktun imavaloen amiginigagun atolaaktok Doris North-mi Havaagenagealigeagani (Nunavumi Avatilikeyin Katimayin (NIRB-kon) Napaa 003, toniyaohimayok September 15-mi 2006-mi) Kanoginigalo A Imaknik Atogeagani Laeseoyok (Nunavumi Imalikiyin Katimayin (NWB-kon) Laeseoyum Napaa 2AM-DOH0713 Kanoginiga A, tuniyaohimayok September 19-mi 2007-mi; NWB-kon 2007-mi) ukoaguyun:

- Doris North-mi Havaagiyaolikniga
 - [Havaakagumayok] amigineakok kanogiliniga kuktitaoyoklo Doris-min Kukniginik kulvani atpanilo kukmun ilaleotiyum piyaagani hivonikhuyotikanik atoktaolaktonik ilitokhaknigagun nalaomaniganik aktokniginik nalaotaktaoyun piyotikaktun ikaloen nunagiyaenik atpani kum.
- o Doris North-mi Havaam Kanoginiga A Imaknik Atogeagani Laeseoyok
 - Ilaga G, Okaohik 30. Laesikaktok una kuhniga [Tail-min Tahikmin] Atagukvikmin uvuga Doris Kuganun amikhivikmi TL-4-mi avatkoyotigitaagani 10%-mik avataoyomin kuhniga Doris Kugani naonaeyakniganin TL-2-mi kuktitaolikniganin.
 - Ilaga J, Okaohik 2. Tigumeaktok Laesimik ileogaeneakok ihoaktonik naonaeyaotinik Doris-mi Kukmi amikhuyotimi TL-2-mi, amigyaagani kuknigin hikokateagoekan naonaeyageagani, piyageakalikan penaklonilo.
 - Ilaga J, Okaohik 3. Laesikaktum havaagineakaen Imaknik Amikhiyaagani Havaak okakhimayok Naonaepkotini Aolanikun J-mi.

2013-mi imavaloknik amigiyotinun havaak ikayutaoyoklo havaagiyaoyageakaktok uvuna Atakukmikmin Kuknigagun Ikalolikinikun Ataniktutaoyok (NU-02-0117.3-mi), Aheoyokagitaagani Opologaeyaon (Golder 2007-mi) Aheoyokagitaaganilo Oplaogaeyaon Kanoginigagun (Rescan 2010a-mi, Rescan 2010b-mi), ilagilo imagikniginik amikhuyotinun atoktukhan okaotaoyun Doris North-mi Havaak Tayaenak Imaknik Monakhuyotinun Opologaeyaon (SRK 2012-mi).

Maligeami ukua atogeakaktun, TMAC-kon havaktitiyun katraktigun ERM-konik Kanatami (ERM Rescan-kon) amikhiyaagani iglukpakkavikmi okaohigilogilo nalohoektatik. Una unipkaak kanogileoguhenik nalohoektaeniklo 2013-mi imalikinikun atogeagani amigiyotin havaami. Iniktigakhan 2013-mi havaani ikayutaoyukhan maligoagakhan atogeagaktun okaotaoyun kuleoyoni ilageaklogilo naonaepkotin atoktaoyoni iglukpakkavikni Doris North-mi nunami.

Siksin ilikun aolayun imavaloknik amikhiyotin atoktaoyun Doris North-mi Havaami ilagani 2013-mi imakakniginik maligoamaga amigiyotinun havaami. Tatini kuvaloknilo imakaknigin amigiyahimayun naonaeyaevikni Doris TL-2-mi (Doris-mi Kukmi kulgani), Doris-mi TL-3-mi (Doris-mi Kukmi Atpani), Windy-mi Imakakniga (Windy-mi Tatimin Kuknigin), Roberts-mi Imakakniga (Roberts-mi Tatimi Kukniga), Doris Tahik, Atagukviklo Tahik. 2013-mi havaak atulikhimayok atulihaliktilogo June atokhimaginakhonilo September-mun, ilitohakveoyun Doris TL-2-mi, Doris TL-3, Windy-mi Imakakniga, Roberts-milo Imakakniga agiptiktaohimayun tutkuktaohimayun ukeokneaknigan. Imavaloknik ilitokhaeven Doris-mi Atagukvikmilo atokhimaginaktuk titigakhimadinakneaktuklo naonaepkotikhanik ukeogani 2013-min 2014-mun.

Inmigun aolayotikaktok amikhiyotin atoktilogin, kagugugaagan naonaepkotin katitaovaktun atuni naonaeyaeviknin. 2013-mi ataotimun 30-guyun kuktitaohimayun naonaeyagaoyun inikhimayun ikinikhani talimanik naonaeyaotinik atuni kukmi amikhiyotinun ihoakunmi. Kanogiligaagan kuktitaonigagulo naonaepkotin atoktaohimayun ihoakhageagani kuktitaokataknikaenik hatkigeaganilo imavaloknik naonaepkotinik.

Aalaguknigin kum kuhniga Doris TL-2-mi amikhiyotinun ihoakunmi aheagugutaoyok kuhnigin aepaaganin. Talvuna, nutaak ilitokhaeyun pihimayok atokhigin 2013-mi inum kuktiniganik naonaeyaotinik. Nahogiyaoyok una naonaeyakniga, kigoagulo imavaloen aolaniginik kuktovaloelo ilitokhaknigin ihoakhaktaoneakun ihoakhivaaliklotiklo amigaenikhan naonaeyakven kahakhikpata hivunikhami kuktitaokataknigin ilitokhaktaokatakata.

2013-mi imaktilogo, kuhnigin amigiyaoyonim imakaknivaloknia akungani 40-milametamin 56-milametamiklo. Tamaenin kuhnigin imakaktilogo aoyami kanitoani $0.07 \text{ m}^3/\text{s}$ -goyok naonaeyaevikmi Windy-mi Imakakniganik (kukveoyok 14.1 km^2 -goyok nunan) uvuga $0.67 \text{ m}^3/\text{s}$ -goyok Roberts-mi Imakakniganik (kukveoyok 97.9 km^2 -goyok nunan). Kugiknigin 2013-mi June-mi pihimayun naonaeyaevikni Doris TL-2-mi, Doris TL-3-mi, Roberts-milo Imakakniga. Imakakpalaaginigin kuvaloen aoyami pihimayun nuguliktilogo August naonaeyaevikni Doris TL-3-mi atulihaliktilogolo September naonaeyaevikni Doris TL-2-mi, Roberts-mi Imakakniga, Windy-milo Imakakniga. Imakakpalaaginigin kuvaloen $0.02 \text{ m}^3/\text{s}$ -min naonaeyaevikni Windy-mi Imakaknigan 0.11 m^3/s -mun naonaeyaevikni Roberts-mi Imakaknigan.

Maligeagani atogeakaktunn Ilagani G, Ilaga 30 Ilaganilo J, Ilaga 2 Kanoginigan A Imaknik Atogeagani Laeseoyok, Doris-mi Kukmi kuhniganun nalaotaktaoyok 2011-min 2012-mun atoktaohimaktok 2013-mi. Doris-mi Kukmi imakakniga naonaeyaktoahimadinaktok. Kilaenaguktomik naonaeyaonmik ugahiktoani naonaeyaotinik pihimadinaktok, uplotoagaagan kuhniginik nalaotaktaovakhotik. Kigoani naonaektaoyok tamaeni nalaotaagaoyun kuhniginik aalagukpalagidok aginikhaanik kuhniganik Doris-mi Kugani.

Imakaknigin aalaguknigin ayikotaen Doris-mi Atagukvikmilo tatini 2013-mi, kanitoaneginakhotik 0.3-milametamik atuni tahikmi. Imakaknigin tamakni Doris-mi Atagukvikmilo tahikni aginihaoyun kitigukman June aputin hikulo aoktukniganin, imayeyakpaleavlotik July-mi August-milo. Windy-mi tahikmi, imakaknigin aalaganigin aoyaotilogo 0.10-milametoyomik, mikinikhak Doris-mi Atagukvikmilo tahikni. Windy-mi imakakniga imayeyakpaleayok kilamik atulihalikman kitigakniganun June, aalagukpalagidok June-mi July-milo, kugikhivloni atulihalikman July imakakpalaaginiganun nugulikman August. Nipaliknigin nugulikman August atulihalikniganun September kayumegutaoyok imayeyaknigin

tamaeni pigahun tatin, imakateagutaovlotik Doris-mi tahikmi imaokakyakniganiklo Atagukvikmi Windymilo tahikni atulihalikman September.

Naonaeyagaokpan hivulikni amikhiyotini ukeoni (2009-min 2012-mun), 2013-mi imakakpalaagitok aoktukniganin aputin hikuvaloelo kukniganun. Tamaeni kuvaloen amikhiyotaeni 2013-mi aoyaotilogo kuknigin 52-min 72%-mun mikinikhaoyok tamaeni aoyaotilogo kukniginin 2009-min 2012-mun.

ՀԱՄԵԿ ԱԴՃՎԵԼՎԵԿ

Résumé analytique

Le projet Doris North (le « projet ») est situé dans la ceinture Hope Bay, une propriété de 80 par 20 kilomètres longeant la rive sud du détroit de Melville au Nunavut. La propriété est constituée d'une ceinture de roches vertes (la « ceinture Hope Bay ») qui contient trois gisements d'or majeurs. Les gisements Doris et Madrid sont situés dans la partie nord de la ceinture, et le gisement Boston est à l'extrémité sud. Le projet se trouve approximativement à 125 km au sud-ouest de Cambridge Bay sur la rive sud du détroit de Melville. Les localités les plus proches sont Umingmaktok (à 75 km au sud-ouest de la propriété), Cambridge Bay et Kingaok (Bathurst Inlet; à 160 km au sud-ouest de la propriété).

TMAC Resources Inc. (« TMAC ») a acheté le projet de la ceinture Hope Bay à Newmont Corporation en mars 2013. L'acquisition incluait les droits d'exploration et d'exploitation minière dans la ceinture Hope Bay, y compris la mine d'or Doris North et les permis, licences et autorisations de développement reçus par les précédents propriétaires. À la fin 2012, avant la vente, le projet de la ceinture Hope Bay a été mis en état d'entretien et de maintenance, et a été fermé de façon saisonnière durant l'hiver 2012/2013. TMAC a rouvert le camp Doris North en mars 2013 afin de vérifier les systèmes de gestion de l'eau du site, les programmes de conformité environnementale, et de soutenir les activités d'exploration. Le projet Doris North reste en état d'entretien et de maintenance, même s'il ne sera pas fermé saisonnièrement pour l'hiver 2013/2014.

Les exigences de conformité pour la surveillance hydrométrique applicables au certificat N° 003 (délivré par la Commission du Nunavut chargée de l'examen des répercussions (CNCER) le 15 septembre 2006; NIRB 2006) et au permis d'utilisation des eaux de type A N° 2AM-DOH0713 (délivré par l'Office des eaux du Nunavut (OEN) le 19 septembre 2007; NWB 2007) pour le projet Doris North sont les suivantes:

- Certificat pour le projet Doris North:
 - *[Le promoteur] surveillera le niveau et le débit du déversement Doris à la fois en amont et en aval du point de déversement des eaux décantées afin de fournir des données qui pourront être utilisées pour évaluer la précision des prédictions relatives aux effets concernant l'habitat du poisson en aval.*
- Permis d'utilisation des eaux de type A pour le projet Doris North:
 - Partie G, article 30. *Le titulaire du permis devra s'assurer que le débit de la zone de retenue des résidus [du lac Tail] dans le ruisseau Doris à la station de surveillance TL-4 ne dépasse pas 10 % du débit de base du ruisseau Doris tel que mesuré à la station de surveillance TL-2 au moment du déversement.*
 - Partie J, article 2. *Le titulaire du permis devra installer des instruments de mesure adéquats dans le ruisseau Doris à la station de surveillance TL-2, afin de mesurer le débit quand l'état de la glace le permet, et ce de manière continue et en temps réel.*
 - Partie J, article 3. *Le titulaire du permis devra mettre en place le programme de surveillance des eaux détaillé dans les tableaux de l'annexe J.*

Le programme de surveillance hydrométrique 2013 a aussi permis de soutenir le travail requis par l'autorisation liée aux pêches pour le déversement du lac Tail (NU-02-0117.3), le Plan Aucune Perte Nette (Golder 2007) et les mises à jour du Plan Aucune Perte Nette (Rescan 2010a, 2010b), ainsi que

certaines parties du plan de surveillance de la quantité d'eau détaillé dans le *Plan provisoire de gestion de l'eau du projet Doris North* (SRK 2012).

Pour se conformer à ces exigences, TMAC a retenu les services d'ERM Consultants Canada Inc. (ERM Rescan) pour mettre en œuvre les activités de surveillance du site et fournir un rapport sur ses conclusions. Ce rapport présente les méthodes et les résultats du programme de surveillance de la conformité hydrométrique pour 2013. Le programme 2013 avait pour objectifs de soutenir les exigences réglementaires en matière de conformité décrites ci-dessus et d'ajouter des enregistrements de données pour les sites existants dans la zone Doris North.

Un réseau de six stations de surveillance hydrométrique automatisées a opéré dans la zone du projet Doris North dans le cadre du programme de surveillance de la conformité hydrométrique pour 2013. Les niveaux d'eau des lacs et cours d'eau ont été mesurés aux stations Doris TL-2 (en amont du ruisseau Doris), Doris TL-3 (en aval du ruisseau Doris), Windy Hydro (exutoire du lac Windy), Roberts Hydro (exutoire du lac Roberts), lac Doris et lac Tail. Le programme 2013 a commencé début juin et s'est poursuivi jusqu'à début septembre, quand les stations Doris TL-2, Doris TL-3, Windy Hydro et Roberts Hydro ont été désactivées pour l'hiver. Les stations hydrométriques des lacs Doris et Tail sont toujours opérationnelles et continueront à enregistrer les données pendant la saison hivernale 2013-2014.

Durant la période de surveillance automatisée, des séries chronologiques continues de données de niveau ont été enregistrées à chaque station. En 2013, un total de 30 mesures manuelles de débit a été réalisé, à raison de cinq mesures au minimum pour chaque station de surveillance des cours d'eau. Les données de niveau et de débit ont servi à développer des équations pour calculer les taux de tarage et à générer des hydrogrammes.

Des changements dans la géométrie du canal à la station de surveillance Doris TL-2 ont altéré l'hydraulique du canal comparativement aux années précédentes. De ce fait, une nouvelle courbe de tarage a été créée à partir des mesures manuelles de débit de 2013. Il faut s'attendre à ce que cette courbe de tarage – ainsi que l'hydrogramme et les indices hydrologiques en résultant – soit modifiée et améliorée dans l'avenir quand de nouvelles mesures manuelles de débit apporteront des points d'évaluation supplémentaires.

Durant la saison des eaux libres 2013, le ruissellement dans les bassins hydrographiques surveillés s'est échelonné de 40 à 56 mm. Le débit moyen pendant la saison des eaux libres 2013 s'est échelonné de 0,07 m³/s à la station Windy Hydro (bassin versant 14,1 km²) à 0,67 m³/s à la station Roberts Hydro (bassin versant 97,9 km²). Les débits de pointe de 2013 ont été atteints mi-juin pour les stations Doris TL-2, Doris TL-3 et Roberts Hydro, et début juillet pour la station Windy Hydro. Les débits de pointe quotidiens s'échelonnaient de 0,12 m³/s à la station Windy Hydro à 1,97 m³/s à la station Roberts Hydro. Les plus faibles débits de la saison des eaux libres ont eu lieu fin août à la station Doris TL-3 et début septembre aux stations Doris TL-2, Roberts Hydro et Windy Hydro. Les débits faibles s'échelonnaient de 0,02 m³/s à la station Windy Hydro à 0,11 m³/s à la station Roberts Hydro.

Pour se conformer aux exigences de la Partie G, article 30, et de la Partie J, article 2 du permis d'utilisation des eaux de type A, le programme de prévision du débit du ruisseau Doris mené en 2011-2012 a été poursuivi en 2013. Les niveaux d'eau du ruisseau Doris ont été enregistrés en continu. Une station télémétrique par satellite donnait accès aux données en temps réel à distance, et permettait de prévoir le débit volumétrique quotidien. Les résultats indiquent qu'il n'y a pas eu de dépassement des prévisions globales concernant le débit volumétrique de base enregistré dans le ruisseau Doris.

Les variations du niveau d'eau dans les lacs Doris et Tail ont été similaires en 2013, soit approximativement 0,3 m pour chaque lac. Les niveaux d'eau ont atteint leur plus haut point mi-juin en

raison de la fonte de la neige et de la glace durant la crue nivale, puis ont diminué au cours des mois de juillet et août. Dans le lac Windy, le niveau d'eau a varié de 0.10 m pendant la saison des eaux libres, soit moins que la variation observée aux lacs Doris et Tail. Le niveau d'eau du lac Windy a augmenté rapidement de début à mi-juin, puis est resté plutôt constant en juin et juillet, atteignant son plus haut point annuel début juillet avant de diminuer jusqu'à fin août. Une série de précipitations entre fin août et début septembre a freiné la baisse du niveau d'eau dans les trois lacs, permettant de stabiliser le niveau d'eau du lac Doris et de recharger légèrement les lacs Tail et Windy début septembre.

Par rapport aux années précédentes du programme de surveillance (2009-2012), 2013 était une année plus sèche en termes de ruissellement et de déversement. Pour toutes les stations de surveillance des cours d'eau, le ruissellement pendant la saison des eaux libres 2013 était de 56 à 68% inférieur au ruissellement moyen pendant la saison des eaux libres des années 2009 à 2012.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Acknowledgements

Acknowledgements

This report was prepared for TMAC Resources Inc. by ERM Rescan. Hydrometric data collection was conducted by Natasha Cowie (M.Sc.) and Emerson Belland (B.Sc.). Field assistance was provided by Leonard Wingnek and Cathy Anablak. The report was prepared and written by Natasha Cowie and technically reviewed by Ted Lewis (Ph.D.) and Ali Naghibi (Ph.D., P. Eng.). The compliance program was coordinated by Cassie Chow (B. Eng., E.I.T.) and managed by Marc Wen (M.Sc., R.P.Bio.).

Field-related logistics support was provided by TMAC, Great Slave Helicopters, Braden Burry Expediting, and Nuna Logistics.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Table of Contents



DORIS NORTH PROJECT

2013 HYDROLOGY COMPLIANCE

MONITORING REPORT

Table of Contents

Executive Summary	i
Acknowledgements.....	iii
Table of Contents	v
List of Figures	vi
List of Tables.....	vi
List of Plates	vii
List of Appendices.....	vii
Glossary and Abbreviations	ix
1. Introduction	1-1
1.1 Project Background	1-1
1.2 Objectives	1-3
2. Methods	2-1
2.1 Hydrometric Monitoring Station Network	2-1
2.2 Hydrometric Station Setups	2-3
2.3 Discharge Measurements	2-3
2.4 Hydrometric Station Surveys	2-5
2.4.1 Levelling Surveys	2-5
2.4.2 Channel Geometry Surveys	2-5
2.5 Rating Curve Development	2-5
2.6 Hydrograph Generation.....	2-6
2.7 Hydrologic Indices.....	2-6
2.8 Quality Assurance and Quality Control	2-7
3. Results and Observations.....	3-1
3.1 Discharge Measurements	3-1
3.2 Hydrometric Surveys	3-2
3.2.1 Levelling Surveys	3-2
3.2.2 Channel Geometry Surveys	3-2
3.3 Stage-Discharge Rating Curves	3-2
3.4 Discharge Hydrographs	3-4

3.5	Hydrologic Indices	3-4
3.5.1	Runoff and Discharge	3-4
3.5.2	Peak and Low Flows.....	3-9
3.6	Lake Water Levels.....	3-11
4.	Summary	4-1
	References.....	R-1

List of Figures

FIGURE	PAGE
Figure 1.1-1. Doris North Project Location	1-2
Figure 2.1-1. 2013 Doris North Project Compliance Hydrometric Monitoring Stations	2-2
Figure 3.4-1. Daily Discharge Hydrograph for Hydrometric Station Doris TL-2 in 2013	3-5
Figure 3.4-2. Daily Discharge Hydrograph for Hydrometric Station Doris TL-3 in 2013	3-6
Figure 3.4-3. Daily Discharge Hydrograph for Hydrometric Station Roberts Hydro in 2013	3-7
Figure 3.4-4. Daily Discharge Hydrograph for Hydrometric Station Windy Hydro in 2013	3-8
Figure 3.6-1. Doris Lake Water Levels, May to September 2013	3-12
Figure 3.6-2. Tail Lake Water Levels, May to September 2013.....	3-13
Figure 3.6-3. Windy Lake Water Levels, June to September.....	3-14

List of Tables

TABLE	PAGE
Table 2.1-1. 2013 Compliance Hydrometric Monitoring Stations in the Doris North Project Area	2-1
Table 3.1-1. Summary of 2013 Manual Flow Discharge Measurements.....	3-1
Table 3.3-1. 2013 Stage-Discharge Rating Equations.....	3-3
Table 3.5-1. Observed and Annual Runoff	3-9
Table 3.5-2. Observed and Annual Mean Discharge	3-9
Table 3.5-3. Peak Flow	3-10
Table 3.5-4. Peak Unit Yield.....	3-10
Table 3.5-5. Observed Low Flows	3-11
Table 3.6-1. Lake Water Level Variations.....	3-11
Table 3.6-2. Regression Analysis Summary for Doris Lake Water Level Estimation.....	3-11

Table 4-1. Summary of Hydrologic Indices for Compliance Monitoring Stations in the Doris North Project Area, 2013 Open Water Season	4-1
Table 4-2. Summary of Lake Water Level Variations for Compliance Monitoring Stations in the Doris North Project Area, 2013 Open Water Season	4-2

List of Plates

PLATE	PAGE
Plate 2.2-1. View downstream (northwest) along Doris Creek showing the satellite telemetry instrumentation used at hydrometric station Doris TL-2. June 6, 2013.	2-4
Plate 3.3-1. Streambank slumping along Doris Creek at hydrometric monitoring station Doris TL-2. View is downstream (north). June 10, 2013.....	3-3

List of Appendices

Appendix A. Hydrometric Monitoring Station Information Sheets
Appendix B. Manual Stage and Discharge Measurements
Appendix C. Channel Geometry Surveys
Appendix D. Rating Curves
Appendix E. Mean Daily Discharge Tables
Appendix F. Memorandum: Estimation of Maximum Allowable Water Discharges from the Tail Lake Tailings Impoundment Area into Doris Creek
Appendix G. Lake Water Level Tables

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Glossary and Abbreviations



Glossary and Abbreviations

Terminology used in this document is defined where it is first used. The following list will assist readers who may choose to review only portions of the document.

Datum	A reference system for computing or correlating the results of a survey
Freshet	In channels, the relatively high annual peak water discharge period resulting from spring/summer meltwater runoff of the winter snowpack
Hydrograph	A graphical plot of water discharge versus time
ISO	International Organization for Standardization
NAD83	North American Datum 1983, based on the spheroid (GRS80)
NIRB	Nunavut Impact Review Board
NWB	Nunavut Water Board
RMS	Root Mean Square, a statistical measure of the differences between modelled and observed values
Runoff	The part of precipitation that appears in surface streams and is a measure of hydrologic response of a watershed, commonly presented as a depth of water over an entire watershed in mm
Stage	The depth of water in a water course or channel
Stage-Discharge Curve (Rating Curve)	A curve derived from concurrently measured stage and discharge data that is used to estimate the discharge for any given observed stage at a hydrometric station (often referred to as a rating curve)
TMAC	TMAC Resources Inc.
Unit Yield	A ratio of water discharges normalized to the drainage area for a basin
USGS	United States Geological Survey
UTM	Universal Transverse Mercator
Watershed	The entire geographical area drained by a river and its tributaries; an area characterized by all runoff being conveyed to the same outlet
WSC	Water Survey of Canada

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

1. Introduction



1. Introduction

1.1 PROJECT BACKGROUND

The Doris North Project (the Project) is located within the Hope Bay Belt, an 80 by 20 kilometer property located along the south shore of Melville Sound in Nunavut (Figure 1.1-1). The property consists of a greenstone belt (the Hope Bay Belt) that contains three main gold deposits. The Doris and Madrid deposits are located in the northern portion of the belt, and the Boston deposit is at the southern end. The Project is located approximately 125 km southwest of Cambridge Bay on the southern shore of Melville Sound. The nearest communities are Umingmaktok (75 km to the southwest of the property), Cambridge Bay, and Kingaok (Bathurst Inlet; 160 km to the southwest of the property).

TMAC Resources Inc. (TMAC) acquired the Hope Bay Belt Project from Newmont Corporation in March 2013. The acquisition included exploration and mineral rights over the Hope Bay Belt, including the Doris North Gold Mine and its permits, licences and authorizations for development received by previous owners. In late 2012, prior to the sale, the Hope Bay Belt Project was placed into care and maintenance, and the project was seasonally closed during the winter of 2012/2013. TMAC re-opened the Doris North Camp in March of 2013 for the purposes of conducting site water management, environmental compliance programs and to support exploration activities. The Doris North Project remains in care and maintenance although it will not be seasonally closed for the winter of 2013/2014.

The compliance requirements for hydrometric monitoring applicable to the Doris North Project Certificate (Nunavut Impact Review Board (NIRB) No. 003, issued September 15, 2006; NIRB 2006) and Type A Water Licence (Nunavut Water Board (NWB) Licence No. 2AM-DOH0713 Type A, issued September 19, 2007; NWB 2007) are as follows:

- Doris North Project Certificate
 - [The Proponent] will monitor stage and discharge in Doris Outflow both upstream and downstream of the decant discharge point to provide information that can be used in assessing the accuracy of the impact predictions relating to fish habitat downstream.
- Doris North Project Type A Water Licence
 - Part G, Item 30. The Licensee shall ensure that flow from the [Tail Lake] Tailings Impoundment Area into Doris Creek at monitoring station TL-4 does not exceed 10% of the background flow in Doris Creek as measured at monitoring station TL-2 at the time of discharge.
 - Part J, Item 2. The Licensee shall install appropriate instrumentation in Doris Creek at monitoring station TL-2, to monitor flow when ice conditions allow for such measurements to be taken, on a real time and continuous basis.
 - Part J, Item 3. The Licensee shall undertake the Water Monitoring Program detailed in the Tables of Schedule J.

The 2013 hydrology monitoring program also supported work required by the Tail Lake Outflow Fisheries Authorization (NU-02-0117.3), the No Net Loss Plan (Golder 2007) and No Net Loss Plan Updates (Rescan 2010a, Rescan 2010b), and portions of the water quantity monitoring schedule detailed in the *Doris North Project Interim Water Management Plan* (SRK 2012). To comply with these requirements, TMAC contracted ERM Consultants Canada Inc. (ERM Rescan) to undertake monitoring activities at the site and report on its findings.



1.2 OBJECTIVES

ERM Rescan (formerly Rescan Environmental Services Ltd.) has conducted hydrometric monitoring in the project area continuously since 2009. The hydrology compliance monitoring program began in 2011 and has continued to the present. The 2013 program included four stream monitoring stations and two lake monitoring stations. The goals of the 2013 program were to support the regulatory compliance requirements described above and to add to data records at existing sites within the Doris North area. The objectives of the program were to:

- continue automated water level monitoring at existing stream and lake sites;
- conduct manual flow measurements over a range of flow conditions during the open water season;
- update established rating curves at each site or generate new rating curves where required;
- generate annual hydrographs for each monitoring site;
- calculate hydrological indices including runoff, mean discharge, and annual peak and low flow; and
- provide streamflow predictions for Doris Creek at monitoring station TL-2 on a real-time continuous basis.

This report describes the methods employed and results obtained during the 2013 hydrology compliance monitoring program.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

2. Methods

2. Methods

The following section describes the monitoring stations and methodology used in the 2013 hydrology compliance monitoring program.

2.1 HYDROMETRIC MONITORING STATION NETWORK

In 2013 the hydrology compliance monitoring network consisted of six hydrometric stations in the Doris North Mine area. Table 2.1-1 provides an overview of the stations, and station locations are shown in Figure 2.1-1. Detailed station information sheets are provided in Appendix A.


Table 2.1-1. 2013 Compliance Hydrometric Monitoring Stations in the Doris North Project Area

Hydrometric Station	Location	UTM Coordinates (Zone 13W, NAD83)		Drainage Area (km ²)	Lake Coverage (%)	Monitoring Period	Period of Operation in 2013	Purpose
		Easting	Northing					
Stream Monitoring Stations								
Doris TL-2	Doris Lake outflow	434,059	7,559,504	94.6	20	1996-1998, 2000, 2003-2013	June 6 - September 9	Monitoring required for Project Certificate and Type A Water Licence
Doris TL-3	Doris Creek, downstream of Doris Falls	434,204	7,559,985	95.3	20	2011-2013	June 9 - September 7	Monitoring required for Project Certificate and Type A Water Licence
Roberts Hydro	Roberts Lake outflow	435,325	7,562,815	97.9	17	2003-2013	June 7 - September 8	Supports requirements for Fisheries Authorization and No Net Loss Plan
Windy Hydro ^a	Northwest shore of Windy Lake	431,481	7,555,089	14.1	39	2006-2013	June 5 - September 8	Supports requirements for Fisheries Authorization and No Net Loss Plan
Lake Monitoring Stations								
Doris Lake	Northwest shore of Doris Lake	433,512	7,558,452	n/a	n/a	2004-2013	January 1 - December 31	Monitoring required for Type A Water Licence
Tail Lake	Northwest shore of Tail Lake	434,832	7,558,560	n/a	n/a	2004-2013	January 1 - December 31	Monitoring required for Type A Water Licence

n/a - not applicable

^a Windy Hydro serves as a monitoring station for both stream and lake levels.

The stream monitoring stations Doris TL-2, Doris TL-3, Roberts Hydro, and Windy Hydro were remobilized at the onset of freshet between June 5 and June 9, 2013. To prevent ice damage, these stations were demobilized in early September 2013.



The lake monitoring stations located at Doris and Tail lakes have been in continuous operation since 2004. These stations are installed approximately 5 m below the surface of the lakes to prevent ice damage. Both the Doris and Tail lake stations operated through the 2012/2013 winter season and remained in operation as of the last site visit in September 2013. The Windy Hydro station serves as both a lake and stream monitoring station.

2.2 HYDROMETRIC STATION SETUPS

Across the monitoring network, each station consisted of a pressure transducer paired with a data logger. Pressure transducers were installed as deep in the channel or lake as possible. The transducers continuously sampled water levels. These data were recorded by the data loggers at 10 minute intervals.

At the stream monitoring stations, pressure transducers and cabling were inserted into flexible aluminium conduit with one end of the conduit attached to a 1.5 m piece of angle iron. The angle iron was placed flat on the stream or lake bed and stabilized with rebar. In fine-grained substrates the angle iron was attached to a wooden frame to distribute weight and prevent the assembly from sinking.

The instrumentation package at the stream monitoring station Doris TL-2 consisted of a 0-55 psi vented PS-9800® pressure transducer (Instrumentation Northwest Inc.) paired with an HOBO® Energy Pro Datalogger (Onset Computer Corp.). It also included a Solarstream™ solar-powered Iridium® satellite transceiver (Upward Innovations Inc.). Every two hours the system automatically sent the recorded water level data to a secure Internet server. Data were then available for viewing or downloading over a secure 256-bit encrypted connection. The sensor, datalogger, and satellite transceiver were housed in a polycarbonate waterproof enclosure. Power to the station was supplied by a 12 volt battery connected to a backup solar panel. All the instrumentation was mounted to a 3.0 m-tall galvanized steel tripod located along the adjacent channel bank above the high water mark (Plate 2.2-1).

Instrumentation at stream monitoring stations Doris TL-3, Roberts Hydro, and Windy Hydro consisted of a 0-5 psi vented Aquistar PT-2X Smart Sensor® (Instrumentation Northwest Inc.). This sensor combines the pressure transducer and data logger in a small diameter unit.

The setup and instrumentation of the Doris and Tail lake monitoring stations consisted of a 10 psi vented KPSI 730-series solid-state pressure transducer (Measurement Specialties Inc.) paired with a DD-320 data logger (Optimum Instruments Inc.). The pressure transducers and cabling were inserted through a 10 cm diameter steel pipe anchored to an on-shore bedrock outcrop. The pipes were set in the lakes to a depth below 5 m to prevent freezing during the winter months. The data loggers were housed in steel enclosures located along the lake shorelines above the high water mark.

2.3 DISCHARGE MEASUREMENTS

At each hydrometric stream monitoring station current velocity measurements were conducted in order to calculate the volumetric flow, or discharge, of the stream. Measurements were taken throughout the open water season (June to September) to obtain a range of discharges. The location of the metered section at each site was determined based on channel geometry and flow conditions at the time of measurement. Generally, the stream was measured along a straight reach where the bed was relatively uniform. Areas with turbulent flow and/or immovable rocks were avoided where feasible. At stations Doris TL-2 and Doris TL-3, current velocity measurements were taken in close proximity to the respective pressure transducers in Doris Creek. At stations Roberts Hydro and Windy Hydro, pressure transducers were located in lakes and current velocity measurements were taken in the lake outlet streams.




Plate 2.2-1. View downstream (northwest) along Doris Creek showing the satellite telemetry instrumentation used at hydrometric station Doris TL-2. June 6, 2013.

Current velocities were measured using a portable electromagnetic current meter (Marsh-McBirney Flo-Mate™ 2000 or Hach FH950™). A fixed sampling interval of 40 seconds was used for each velocity measurement, during which an average velocity was determined.

During each station visit, measurements of water current velocity, depth of flow, and distance across the channel were obtained. Typically, a minimum of 20 current velocity measurements were taken across the width of a channel, with the aim of having each vertical or observation interval accounting for less than 10% of the total discharge. This method assumes that the velocity measured at each vertical represents the mean velocity in a segment. At each observation point across the channel, if the measured water depth was less than 0.75 m, current velocities were measured at 60% of the depth from the water surface. The measurement at 60% of the flow depth is generally accepted as representing the mean velocity of the vertical water section (Herschy 2009). When water depths were greater than 0.75 m, current velocities were measured at 20% and 80% of water depth, with the average of the two readings taken to represent the mean velocity for the vertical. In all cases, methods followed the *British Columbia Manual of Standard Operating Procedures for Hydrometric Surveys* (RISC 2009) and Water Survey of Canada (WSC) standard operating procedures (Terzi 1981).

Water discharges were computed from the current velocity measurements using the mid-section method. The partial discharges measured at verticals across the channel were summed to obtain the total estimated discharge for the gauged section. Measurement uncertainty, expressed as a percentage, was calculated for each discharge measurement according to methods described in Herschy (2009).

2.4 HYDROMETRIC STATION SURVEYS

2.4.1 Levelling Surveys

To establish and maintain vertical elevation control at stations where water surface elevation (stage) is measured it is common practice to determine the stage above a specified reference surface or gauge datum. In order to check the accuracy and consistency of the recorded data, it is necessary to periodically verify the elevation of the gauge in relation to the established station datum.

Local benchmarks established at each station were used as survey control points. Benchmarks consisted of 76 mm concrete expansion bolts secured in bedrock or large stable boulders found in the vicinity of the stations. One benchmark at each station was designated as the primary reference point, and assigned an arbitrary local elevation of 100.000 m. All recorded water levels were then referenced to this primary benchmark.

To allow for continuity in the elevation of the recorded water levels at existing hydrometric stations, benchmarks installed in previous years were used in 2013 as survey control points for each station. Throughout the 2013 monitoring period, hydrometric levelling surveys were conducted during all site visits at each station to check and verify pressure transducer readings, as well as to determine the reliability of the water level data that were recorded between site visits.

2.4.2 Channel Geometry Surveys

Surveys were completed at hydrometric monitoring stations to define channel geometry of the gauged stream sections. Cross-sections perpendicular to the direction of flow in the channel reach were surveyed using an engineer's level and stadia rod. Surveyed cross-sections were referenced to the established arbitrary local datum. Channel geometry surveys were conducted using procedures consistent with the practices of the United States Geological Survey (USGS; Wharton 1994).

At stations Doris TL-2 and Doris TL-3, a suitable channel reach was selected using the pressure transducer as the relative midpoint of the survey. Along the reach, three cross-sections were surveyed. Each survey transverse extended across the channel and beyond it to full bankfull width (level of the active floodplain). At stations Roberts Hydro and Windy Hydro, cross-section surveys were conducted at the pressure transducer locations along the lake shore, at the lake outlets, and at the flow gauging sections in the lake outlet streams.

2.5 RATING CURVE DEVELOPMENT

Unlike water level (stage), discharge is not typically monitored on a continuous basis at hydrometric stations. To produce a continuous record of the discharge at a monitoring site, a relationship between recorded stages and associated measured discharges is developed. This empirical relationship is referred to as a rating curve (ISO 2010). Once the rating curve is established for a monitoring site, water level data can be converted into a continuous discharge time series, or hydrograph.

Rating curves are hydraulic functions expressed as a parabolic equation of the form:

$$Q = C (h - a)^b \quad (1)$$

where Q is the discharge (m^3/s), C and b are regression coefficients, h is the stage (water level; m), and a is the stage at zero flow (datum correction; m).

The quality of a rating curve depends on the number and accuracy of the individual data points used to generate the curve as well as the hydraulic characteristics of the monitoring location. Each additional stage-discharge measurement at varying flow conditions increases the range and robustness of the rating curve. The stage-discharge rating relation may change from low to high flow periods if the channel geometry changes at higher stages, in which case separate rating curves are produced for each period. The stage that separates the curves is known as a breakpoint (Hershey 2009).

In the absence of a stage-discharge measurement corresponding to high flow conditions, rating curves may be extrapolated to a high flow value that is beyond the range of the observed data used to generate the curve. Discharge extrapolation beyond 1.5 times (ISO 2010) or two times (Rantz et al. 1982) the greatest manually measured discharge is not recommended as the resulting value has a high associated uncertainty. Due to relatively low flows in 2013, it was not necessary to calculate discharges from curves extrapolated above the recommended limit.

When developing 2013 rating curves, manual flow measurements collected in previous years were included as rating points to increase the accuracy of the curve. However, significant alterations in channel morphology can render historic flow measurements inapplicable for rating curve development and require a new rating relation. At station Doris TL-2, a new rating curve was developed for 2013 to reflect altered channel geometry as a result of gradual slumping of the right bank (described in Section 3.3).

Rating curves were developed using Aquarius™ Time Series Hydrologic Software (Aquatics Informatics Inc.). The software uses standard methods outlined by the United States Geological Survey and the International Organization for Standardization (Kennedy 1984, ISO 2010).

2.6 HYDROGRAPH GENERATION

Annual hydrographs, presented as mean daily discharge, were generated for each of the hydrometric monitoring stations operated in 2013. For the operational period at each hydrometric station, water discharges were calculated at 10 minute intervals by applying the developed rating curve to the recorded stage data. The 10 minute discharge data were averaged over a 24 hour period to calculate mean daily discharge. Standard logarithmic growth and linear decay functions were used to estimate daily discharge values beyond the period of record for all stations.

The hydrograph for station Doris TL-2 was updated on a daily basis with the most recent data downloaded via satellite transmissions. Daily discharge data were sent via email to TMAC personnel to support water transfer activities from Tail Lake to Doris Creek.

2.7 HYDROLOGIC INDICES

Calculated and estimated discharge values were used to determine a series of hydrologic indices including runoff, mean discharge, and annual peak and low flows.

Runoff (expressed as water depth, in mm) represents the hydrologic difference between all inputs and outputs for a watershed on an annual basis. Runoff is valuable for obtaining gross estimates of the water available in a basin. Because it is standardized by drainage area, it can be used to compare the hydrological response of drainage basins of different sizes. Two runoff metrics were used: 1) runoff for the period of record (also referred to as observed runoff) and 2) total annual runoff (including estimated values for periods when stations were demobilized).

Mean discharge (expressed as a volumetric flow rate, in m^3/s) gives an indication of the potential amount of water a basin can provide as a function of drainage area, geology, and climate. Mean discharge was calculated for both the period of record and the calendar year.

Peak flows, determined from hydrographs, represent the maximum water discharge (m^3/s) that is produced by a drainage catchment during a year. Conversely, low flows (m^3/s) provide an estimate of baseflow conditions, which are important for the sustained health of aquatic communities. The streams at the compliance monitoring stations freeze solid in winter; therefore, the reported low flow values correspond to the period of record during the open water season between June and September 2013.

2.8 QUALITY ASSURANCE AND QUALITY CONTROL

The hydrotechnical standards and methods used in the study are based on standards published by the British Columbia Ministry of Environment (RISC 2009). These standards complement the national standards developed by the Water Survey of Canada (WSC 1999). Methods used in rating curve development follow those outlined by both the RISC manual and the International Organization for Standardization (ISO 2010).

The RISC manual outlines four criteria for both water level data and discharge data that are used to assess and grade (i.e., A, B, C, E - estimated and U - unknown) the overall quality of hydrometric data. The criteria are: instrumentation, stream channel condition, field procedures, and data calculation and assessment. The list provided below details the quality assurance/quality control (QA/QC) criteria and methods used in the monitoring program, with the aim to achieve high quality data based on the standards in each of the four criteria.

1. Instrumentation

All instrumentation used and calibration/verification procedures comply with the highest quality standard outlined by RISC (i.e., Grade A). Data loggers and pressure transducers are checked, calibrated, and if necessary serviced by the manufacturer prior to each field season.

2. Stream Channel Condition

The channel conditions affecting control of water level and discharge measurements meet the high to mid range of quality standards outlined by RISC (i.e., Grade A/B). Channels are generally stable, with minimal aggradation/degradation due to the low-energy nature of the streams.

3. Field Procedures

The field procedures follow the highest standards outlined by RISC (i.e., Grade A). These include the use of a minimum of three benchmarks at each station, more than two level checks per year, 20 or more verticals in manual flow measurements, and five or more manual flow measurements per year. Because the stream monitoring stations are deactivated during winter, the annual data are graded as E, a similar approach to that used for seasonal WSC stations.

4. Data Calculation and Assessment

For this criterion, standards are followed to the greatest extent possible given channel characteristics and seasonal constraints on site access. Results are compared to other stations and years and reviewed for anomalies. The methods used to develop rating curves are based on those outlined by RISC (RISC 2009) and the International Standards Organization (ISO 2010). One area where standards have not been met for all stations is in the number of rating measurements recommended to develop a robust relation. Ten (RISC 2009) to fifteen (ISO 2010) measurements are required to develop quality rating relations and in the case of

station Doris TL-2 these minimums are not met due to changes in channel geometry, which rendered the historic rating points inapplicable and made a new rating curve necessary for 2013 (described in Section 3.3). In this criterion the overall data quality varies between sites (i.e., A/B).

For quality assurance purposes, data checks are conducted in the field during the hydrometric monitoring process. In the office, the following 3-step data quality procedure is performed:

1. Data reduction and analysis are carried out by the project hydrologist or technician. The data are then imported into Aquarius™ software.
2. Within the Aquarius™ software the data are examined by the project hydrologist and ERM Rescan's Water Resources Discipline Coordinator for data integrity and consistency with provincial and federal standards.
3. After the review is completed, a final assessment is conducted and, if necessary, rationalization of data anomalies or shortcomings is discussed and documented with ERM Rescan's Water Resources Discipline Lead.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

3. Results and Observations

3. Results and Observations

Results from the 2013 hydrology compliance monitoring program are presented as follows: 1) discharge measurements; 2) hydrometric surveys; 3) stage-discharge rating curves; 4) daily discharge hydrographs; 5) hydrologic indices; and 6) lake water levels.

Results of the 2013 monitoring program were compared to historic data from 2009-2012. Details of the 2009-2012 monitoring programs are presented in previously published hydrology baseline and compliance reports (Rescan 2009, 2011a, 2011b, 2012a, 2012b).

3.1 DISCHARGE MEASUREMENTS

A total of 30 manual water discharge measurements were taken in 2013 (Table 3.1-1; Appendix B). The measurements were collected throughout the open water season.

Table 3.1-1. Summary of 2013 Manual Flow Discharge Measurements

Hydrometric Station and Drainage Area	Date	Stage (m) ^a	Discharge (m ³ /s)	Discharge Measurement Error (%) ^b	Equipment Used
Doris TL-2 (94.6 km ²)	June 5	n/a ^c	0.005	18.52	FH950
	June 6	98.782 ^d	0.16	7.57	FH950
	June 9	98.882 ^d	0.54	5.97	FH950
	June 10	98.903	0.52	6.40	FH950
	June 11	98.917	0.57	5.69	FH950
	June 12	98.943	0.70	5.79	FH950
	June 13	98.955	0.74	5.28	FH950
	July 6	98.927	0.78	5.39	Flo-Mate 2000
	July 8	98.916	0.71	4.83	Flo-Mate 2000
	August 14	98.712	0.19	5.82	Flo-Mate 2000
	September 7	98.647	0.10	6.71	Flo-Mate 2000
Doris TL-3 (95.3 km ²)	June 9	97.240	0.49	6.25	FH950
	June 10	97.251	0.60	6.84	FH950
	June 12	97.289	0.72	6.55	FH950
	June 13	97.325	0.80	6.15	FH950
	July 6	97.324	0.83	5.31	Flo-Mate 2000
	July 8	97.303	0.79	5.46	Flo-Mate 2000
	August 15	97.074	0.19	6.68	Flo-Mate 2000
	September 7	97.018	0.10	7.84	Flo-Mate 2000
Roberts Hydro (97.9 km ²)	June 7	99.246 ^d	0.62	6.06	FH950
	June 11	99.344	1.57	5.25	FH950
	July 7	99.218	0.81	5.62	Flo-Mate 2000
	August 16	99.052	0.20	6.10	Flo-Mate 2000
	September 8	99.018	0.11	6.48	Flo-Mate 2000

(continued)

Table 3.1-1. Summary of 2013 Manual Flow Discharge Measurements (completed)

Hydrometric Station and Drainage Area	Date	Stage (m) ^a	Discharge (m ³ /s)	Discharge Measurement Error (%) ^b	Equipment Used
Windy Hydro (14.1 km ²)	June 7	94.970	0.08	11.56	FH950
	June 12	94.983	0.12	6.76	FH950
	July 7	95.008	0.10	6.79	Flo-Mate 2000
	August 17	94.946	0.04	7.21	Flo-Mate 2000
	August 18	94.937	0.03	7.57	Flo-Mate 2000
	September 8	94.918	0.02	8.03	Flo-Mate 2000

^a Surveyed water levels referenced to site-specific arbitrary datum. Values are raw data; measurements may be adjusted for rating curve development.

^b 95% level of confidence

^c data not available; stream frozen at station

^d ice in channel affected stage; measurement not used in development of rating curve

3.2 HYDROMETRIC SURVEYS

3.2.1 Levelling Surveys

Levelling surveys were completed in conjunction with flow measurements for the four stream stations (Doris TL-2, Doris TL-3, Roberts Hydro, and Windy Hydro) and at each station visit for the two lake stations (Doris Lake and Tail Lake). Summaries of the survey control points at each station are provided in the station information sheets in Appendix A. Survey data are provided in Appendix B.

3.2.2 Channel Geometry Surveys

Channel geometry surveys were conducted at all four of the stream monitoring stations (Appendix C). Shoreline profile surveys were not conducted at the two lake level monitoring stations, as the shorelines at both stations are bedrock and are not expected to have changed since the initial shoreline surveys conducted in 2011.

Surveys of the monitored reaches provide a physical representation of the channel geometry. These data were used in rating curve development to help define the point of zero flow, and the elevation of any transitions between high flow and low flow rating curves. Cross-sections of the channels at the installed pressure transducers also show the water levels associated with minimum, mean, and maximum daily discharges measured in 2013.

3.3 STAGE-DISCHARGE RATING CURVES

Stage-discharge rating curves were developed for all hydrometric stations in the network. Rating equations are summarized in Table 3.3-1 and rating curves are provided in Appendix D. Root Mean Square (RMS) is used by the Aquarius™ software as an overall measure of error of the stage-discharge rating relation. RMS is a statistical parameter that describes how well the values predicted by the stage-discharge relation fit or represent the observed data. The lower the RMS at each station, the better the estimated values provided by the rating relation, given that rating points are precise.

For hydrometric stations Doris TL-3, Roberts Hydro, and Windy Hydro, the majority of the 2013 stage-discharge measurements plotted along previously established rating curves. This indicated that the stream channel at the monitoring locations remained relatively stable and that no substantial changes in the stage-discharge relations occurred between the previous rating period and the 2013 rating period. However, the curves for these three locations were refined on the basis of the 2013

measurements. The breakpoints in the 2012 Doris TL-3 and Windy Hydro rating curves were removed, as it was determined that a single rating equation sufficiently described the stage-discharge relation at these stations. Conversely, the Roberts Hydro rating curve was updated with the addition of a breakpoint to express the effects of channel geometry at high stage.

Table 3.3-1. 2013 Stage-Discharge Rating Equations

Hydrometric Station	Rating Equation $Q = C (h - a)^b$	Number of Flow Measurements Used in Curve	Root Mean Square	Monitoring Period Used to Develop Curve (Years) ^a
Doris TL-2	$Q = 3.84 (h - 95.85)^{2.10}$	8	2.8	2013
Doris TL-3	$Q = 4.12 (h - 96.84)^{2.15}$	16	7.5	2011-2013
Roberts Hydro	$Q = 7.00 (h - 98.89)^{1.93}$ ($h \leq 99.26$) $Q = 15.33 (h - 99.00)^{2.01}$ ($h > 99.26$)	16	8.3	2009-2013
Windy Hydro	$Q = 4.71 (h - 94.85)^{2.04}$	15	15.6	2010-2013

^a In some cases not all of the data collected during the year(s) listed were used in the development of the rating curve (e.g., stage measurements affected by ice were excluded).

Changes in the channel geometry at station Doris TL-2, induced by gradual slumping of the right bank that initiated prior to the 2013 field season, altered the hydraulics at the site (Plate 3.3-1). As a result, the existing rating curve could not be used in conjunction with data collected in 2013, so a new rating curve was generated.




Plate 3.3-1. Streambank slumping along Doris Creek at hydrometric monitoring station Doris TL-2. View is downstream (north). June 10, 2013.

At stations Doris TL-2 and Roberts Hydro, ice within the channel affected three of the June 2013 measurements (June 6 and 9 at Doris TL-2; June 7 at Roberts Hydro) and they were deemed unreliable for use in rating curve development.

3.4 DISCHARGE HYDROGRAPHS

Annual mean daily discharge hydrographs are presented in Figures 3.4-1 to 3.4-4, and in tabular form in Appendix E. Data were estimated for periods of station demobilization and periods when ice in the channel affected the stage. Estimated periods are indicated by dashed lines in the hydrographs. Daily precipitation data recorded at the Doris meteorological station are included on the hydrographs. Precipitation values and details of the meteorological compliance program are provided in the 2013 Meteorology Compliance Report (ERM Rescan 2014).

The onset of freshet occurred in early June. Discharge at stations Doris TL-2, Doris TL-3, and Roberts Hydro reached an annual peak in mid- to late June as a result of melting of ice and snow. Discharge at these three stations declined steadily after freshet, with the exception of a few minor, short-term increases in response to precipitation events in early and mid-July. The decreasing trend continued at all three stations until late August, when several days of rainfall generated a gradual increase in discharge that continued until station demobilization in early September.

Pumping from the Tail Lake Tailings Impoundment Area (TIA) commenced for the 2013 season on June 21 and continued until September 6. The pumped water was discharged into Doris Creek at the end-of-pipe discharge point TL-4, located approximately halfway between monitoring stations TL-2 and TL-3. The pumped discharge from Tail Lake amplified flows at station TL-3, an effect that is most clearly visible at the hydrograph peak (Figure 3.4-2). To ensure that pumping from the TIA could be measured and tracked against requirements of the Type A Water Licence, the Doris TL-2 satellite telemetry station provided remote access to real-time water level data, which were used to calculate Doris Creek flow volumes on a continuous basis. The Doris Creek flow volume prediction program is described in detail in Appendix F. The results of the prediction program indicate that there was not an overall prediction exceedance relative to the recorded background flow volume in Doris Creek.


Discharge trends at Windy Hydro were distinct from the Doris Creek and Roberts Hydro stations. The discharge peak at Windy Hydro was prolonged, spanning a period from mid-June to late July. Discharge initially peaked in mid-June, then declined slightly before rapidly increasing to the annual peak in early July, following two large precipitation events. A third peak occurred in mid-July in response to precipitation. From late July to station demobilization in early September, the discharge trend at Windy Hydro was similar to that of the other three stations: a steady decline until late August, followed by a slight increase as a result of precipitation.

3.5 HYDROLOGIC INDICES

3.5.1 Runoff and Discharge

Runoff amounts are normalized values of discharge, allowing direct comparison between watersheds normalized to drainage area. Runoff and discharge values for 2013 are presented in Tables 3.5-1 and 3.5-2, respectively. Data from 2009-2012 are provided for comparison.

In 2013, observed runoff for the gauged basins ranged from 40-56 mm, and annual runoff ranged from 41-61 mm (Table 3.5-1). Comparatively, 2013 was a substantially drier year than 2009-2012. Environment Canada ranked winter 2012/2013 the 54th driest winter out of 66 years of record (-23% below normal) for the Arctic Tundra climatic region (EC 2014). Runoff for the monitored watersheds during the 2013 open water season was 52-72% lower than the 2009-2012 average.



Note: Precipitation data from January 1 to September 29, 2013.

Due to closure of Doris Camp during winter 2012/2013, it was not possible to complete necessary winter maintenance on the precipitation adapter. Therefore, winter precipitation values may be missing or unreliable.


Daily Discharge Hydrograph for Hydrometric Station Doris TL-2 in 2013

Figure 3.4-1



Figure 3.4-1






Note: Precipitation data from January 1 to September 29, 2013.

Due to closure of Doris Camp during winter 2012/2013, it was not possible to complete necessary winter maintenance on the precipitation adapter. Therefore, winter precipitation values may be missing or unreliable.

Daily Discharge Hydrograph for Hydrometric Station Doris TL-3 in 2013


Figure 3.4-2



Note: Precipitation data from January 1 to September 29, 2013.

Due to closure of Doris Camp during winter 2012/2013, it was not possible to complete necessary winter maintenance on the precipitation adapter. Therefore, winter precipitation values may be missing or unreliable.

Daily Discharge Hydrograph for Hydrometric Station Roberts Hydro in 2013



Note: Precipitation data from January 1 to September 29, 2013.

Due to closure of Doris Camp during winter 2012/2013, it was not possible to complete necessary winter maintenance on the precipitation adapter. Therefore, winter precipitation values may be missing or unreliable.

Daily Discharge Hydrograph for Hydrometric Station Windy Hydro in 2013

Figure 3.4-4

Table 3.5-1. Observed and Annual Runoff

Hydrometric Station	Total Runoff (mm)								
	2009 to 2012 Observed ^a				Min	Mean	Max	2013 Observed ^a	2013 Annual ^b
	2009	2010	2011	2012					
Doris TL-2	87	121	184	104	87	124	184	40	41
Doris TL-3 ^c	n/a	n/a	183	105	n/a	144	n/a	44	47
Roberts Hydro ^d	87	137	144	98	87	117	144	56	61
Windy Hydro	141	197	143	112	112	148	197	42	43

Note: Italics denote estimated values.

^a Calculated from recorded values during the open water season. Site-specific periods of record for historic data are presented in published baseline and compliance reports (Rescan 2009, 2011a, 2011b, 2012a, and 2012b), and site-specific periods of record for 2013 data are provided in Table 2.1-1.

^b Annual values include estimated data for periods when stations were demobilized.

^c Station established in July 2011; values were estimated for June 2011 and historical minimum and maximum values are not available.

^d Roberts Hydro values from 2009 include estimated values for period when station was damaged.

Table 3.5-2. Observed and Annual Mean Discharge

Hydrometric Station	Mean Discharge (m ³ /s)								
	2009 to 2012 Observed ^a				Min	Mean	Max	2013 Observed ^a	2013 Annual ^b
	2009	2010	2011	2012					
Doris TL-2	1.00	1.15	1.58	1.16	1.00	1.22	1.58	0.46	0.12
Doris TL-3 ^c	n/a	n/a	1.58	1.23	n/a	1.41	n/a	0.53	0.14
Roberts Hydro ^d	1.02	1.40	1.68	1.16	1.02	1.32	1.68	0.67	0.19
Windy Hydro	0.23	0.30	0.26	0.22	0.22	0.25	0.30	0.07	0.02

Note: Italics denote estimated values.

^a Calculated from recorded values during the open water season. Site-specific periods of record for historic data are presented in published baseline and compliance reports (Rescan 2009, 2011a, 2011b, 2012a, and 2012b), and site-specific periods of record for 2013 data are provided in Table 2.1-1.

^b Annual values include estimated data for periods when stations were demobilized.

^c Station established in July 2011; values were estimated for June 2011 and historical minimum and maximum values are not available.

^d Roberts Hydro values from 2009 include estimated values for period when station was damaged.

Mean observed discharge for 2013 ranged from 0.07 m³/s at station Windy Hydro, with drainage area of 14.1 km², to 0.67 m³/s at station Roberts Hydro, with drainage area of 97.9 km² (Table 3.5-2). Mean annual discharge for 2013 ranged from 0.02 m³/s at Windy Hydro to 0.19 m³/s at Roberts Hydro. The substantial difference between observed (open water season) and annual mean discharge for all stations is due to the inclusion of the October-May period in the annual mean. The monitored streams freeze to the bed in winter, so discharge between October and May is minimal.

3.5.2 Peak and Low Flows

Annual peak flow and peak unit yield for 2013 are respectively presented in Tables 3.5-3 and 3.5-4. Data from 2009-2012 are provided for comparison. Daily peak flows (i.e., the average flow rate during the highest runoff day in the year) ranged from 0.12 m³/s at station Windy Hydro to 1.97 m³/s at station Roberts Hydro (Table 3.5-3). Instantaneous peak flows (i.e., the highest flow for a 10-minute interval) were slightly higher, ranging from 0.13 m³/s at Windy Hydro to 2.01 m³/s at Roberts Hydro.

2013 HYDROLOGY COMPLIANCE MONITORING REPORT

Relative to the historic averages, peak flows in all drainages were lower in 2013. Peak flows in 2013 were 59-76% below the mean and 21-65% below the minimum for the 2009-2012 period of record.

Table 3.5-3. Peak Flow

Hydrometric Station	Peak Flow (m ³ /s)							
	2009 to 2012					Min	Mean	Max
	2009	2010	2011	2012				
<i>Doris TL-2</i>								
Instantaneous	2.39	4.61	5.88	3.62	2.39	4.13	5.88	1.00 (June 21)
Daily	2.29	4.44	5.77	3.56	2.29	4.02	5.77	0.98 (June 22)
<i>Doris TL-3^a</i>								
Instantaneous	n/a	n/a	5.96	3.83	n/a	4.90	n/a	1.29 (June 22)
Daily	n/a	n/a	5.86	3.78	n/a	4.82	n/a	1.25 (June 23)
<i>Roberts Hydro</i>								
Instantaneous	2.55	5.84	7.47	3.63	2.55	4.87	7.47	2.01 (June 17)
Daily	2.49	5.78	7.34	3.60	2.49	4.80	7.34	1.97 (June 17)
<i>Windy Hydro</i>								
Instantaneous	0.36	0.49	0.66	0.37	0.36	0.47	0.66	0.13 (July 3)
Daily	0.34	0.46	0.64	0.36	0.34	0.45	0.64	0.12 (July 4)

Note: Italics denote estimated values.

^a Station established in July 2011; historical minimum and maximum values are not available. Peak flow values for 2011 were estimated from modelled data.

Daily peak unit yield (an expression of discharge normalized to drainage area) ranged from 8.25 L/s/km² at Windy Hydro to 20.10 L/s/km² at Roberts Hydro, and instantaneous peak unit yield ranged from 9.21 L/s/km² at Windy Hydro to 20.58 L/s/km² at Roberts Hydro (Table 3.5-4). Peak unit yields in 2013 followed the same trend relative to the historic data as the peak flows.

Table 3.5-4. Peak Unit Yield

Hydrometric Station	Peak Unit Yield (L/s/km ²)							
	2009 to 2012					Min	Mean	Max
	2009	2010	2011	2012				
<i>Doris TL-2</i>								
Instantaneous	25.24	48.57	62.19	38.29	25.24	43.57	62.19	10.55 (June 21)
Daily	24.17	46.73	60.97	37.65	24.17	42.38	60.97	10.37 (June 22)
<i>Doris TL-3^a</i>								
Instantaneous	n/a	n/a	62.51	40.14	n/a	51.33	n/a	13.50 (June 22)
Daily	n/a	n/a	61.50	39.66	n/a	50.58	n/a	13.15 (June 23)
<i>Roberts Hydro</i>								
Instantaneous	26.03	59.59	76.35	37.09	26.03	49.77	76.35	20.58 (June 17)
Daily	25.47	58.97	75.00	36.82	25.47	49.07	75.00	20.10 (June 17)
<i>Windy Hydro</i>								
Instantaneous	25.76	34.95	46.62	25.93	25.76	33.32	46.62	9.21 (July 3)
Daily	23.91	32.55	45.47	25.49	23.91	31.86	45.47	8.25 (July 4)

Note: Italics denote estimated values.

^a Station established in July 2011; historical minimum and maximum values are not available. Peak unit yield values for 2011 were estimated from modelled data.

The observed low flows for the 2013 period of record occurred in late August at station Doris TL-3 and early September at the other three stations (Table 3.5-5). Low flows in 2013 were 58-87% below the mean for the 2009-2012 period of record.

Table 3.5-5. Observed Low Flows

Hydrometric Station	Daily Low Flow (m ³ /s)							
	2009 to 2012				2013 (Date)			
	2009	2010	2011	2012	Min	Mean	Max	
Doris TL-2	0.43	0.45	0.40	0.14	0.14	0.35	0.45	0.09 (September 6)
Doris TL-3 ^a	n/a	n/a	0.37	0.17	n/a	0.27	n/a	0.09 (August 25)
Roberts Hydro ^b	0.52	0.33	0.12	0.11	0.11	0.27	0.52	0.11 (September 1)
Windy Hydro	0.15	0.16	0.11	0.06	0.06	0.12	0.16	0.02 (September 1)

Note: Italics denote estimated values.

^aStation established in July 2011; historical minimum and maximum values are not available.

^bRoberts Hydro station was damaged in 2009; observed low flow value for 2009 was estimated from modelled data.

3.6 LAKE WATER LEVELS

Minimum and maximum recorded water levels for Doris, Tail, and Windy lakes are provided in Table 3.6-1 and Appendix G. Water levels are presented graphically in Figures 3.6-1 to 3.6-3. Water levels are for the open water season (May/June to September). At Doris and Tail lakes, water levels are recorded by transducers on a continuous basis; however, the water level records were affected by ice prior to late May. At Windy Lake, the transducer was in operation from station installation in early June to station demobilization in early September.

Table 3.6-1. Lake Water Level Variations




Lake	Lake Area (km ²)	Drainage Area at Lake Outlet (km ²)	Min Water Level (m) (Date)	Max Water Level (m) (Date)	Mean Water Level ± Standard Deviation (m)	Water Level Change (m)
Doris	3.4	94.6	97.799 (May 22)	98.144 (June 19)	97.952 ± 0.113	0.346
Tail	0.8	4.2	93.869 (September 1)	94.204 (June 22)	94.026 ± 0.108	0.335
Windy	5.3	14.1	94.913 (September 1)	95.017 (July 4)	94.978 ± 0.033	0.104

Notes: Water levels are referenced to a site-specific arbitrary datum. Water levels are for the period of record during the open water season (May-September for Doris and Tail lakes, June-September for Windy Lake). Periods when water levels were affected by ice are excluded. Italics denote estimated values.

A gap exists in the time series for Doris Lake due to a data logger malfunction. Daily water levels for the missing period of data were estimated by means of ranked correlation analysis (i.e., frequency-paired regression). Table 3.6-2 presents a summary of the analysis.




Table 3.6-2. Regression Analysis Summary for Doris Lake Water Level Estimation

Station	Reference Station	Concurrent Period	Correlation Equation	R ²	Estimated Period
Doris Lake	Doris TL-2	June 7 to July 10 and August 20 to September 10	y = 0.89x + 12.10	0.99	July 11 to August 19



Notes: Water levels are referenced to a site specific non-geodetic datum
Minimum and maximum water levels are for the 2013 period of record
(May 22-Sept 10; data prior to May 22 affected by ice)
Shoreline profile surveyed August 16, 2011; shoreline is bedrock

Figure 3.6-1



Notes: Water levels are referenced to a site specific non-geodetic datum
 Minimum and maximum water levels are for the 2013 period of record
 (May 22-Sept 9; data prior to May 22 affected by ice)
 Shoreline profile surveyed August 19, 2011; shoreline is bedrock

Tail Lake Water Levels, May to September 2013

Figure 3.6-2




Figure 3.6-3

Water level fluctuation was similar at Doris and Tail lakes in 2013, varying by approximately 0.3 m at each lake (Table 3.6-1). Water levels at both Doris and Tail lakes peaked in mid-June as a result of snow and ice melt during freshet (Figures 3.6-1 and 3.6-2). After the peak, water levels at both lakes declined steadily except for several brief, minor increases in response to precipitation events. Runoff contributions from multiple days of rain in late August and early September recharged the lakes, interrupting the declining trend. Water levels at Doris Lake remained fairly consistent from late August to the last station visit in early September, while water levels at Tail Lake increased slightly during the same time period.

At Windy Lake, water level variation over the observed period was 0.1 m, less than that observed at Doris and Tail lakes (Table 3.6-1). Water level increased rapidly from station mobilization on June 6 to June 18, then remained fairly consistent throughout most of June and July, reaching an annual peak on July 4 (Figure 3.6-3). Water levels declined steadily beginning in late July until the end of August, when Windy Lake underwent recharge in response to several precipitation events. Water levels increased slightly from late August to early September, when the station was demobilized for the season.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

4. Summary

4. Summary

A network of six hydrometric monitoring stations was operated within the Doris North Project area as part of the 2013 hydrology compliance monitoring program. The 2013 program commenced in early June and continued until early September, when the stream monitoring stations Doris TL-2, Doris TL-3, Roberts Hydro, and Windy Hydro were demobilized for the winter. The lake monitoring stations at Doris and Tail lakes remain in operation and will continue recording data through the 2013/2014 winter season.

The four stream monitoring stations (including Windy Hydro, which serves as both a stream and lake monitoring station) were operated from June to September, 2013. For all stream stations, daily discharge was estimated beyond the period of record using standard logarithmic growth and linear decay functions. For the two lake stations that remain in continuous operation (Doris Lake and Tail Lake), the 2013 period of record extended from the beginning of the year until the last station visit in early September. However, water level data at both lake stations were affected by ice prior to late May.

Changes in the channel geometry at the Doris TL-2 monitoring station altered the channel hydraulics compared to previous years. Therefore, a new rating curve was generated based on the 2013 manual flow measurements. Rating curves for Doris TL-3, Roberts Hydro, and Windy Hydro were refined using the 2013 measurements. It is expected that the rating curves, and their resulting hydrographs and hydrologic indices, will continue to be modified and improved with information provided by future manual flow measurements.

Hydrologic indices are summarized in Table 4-1. In 2013, observed runoff for the gauged basins averaged approximately 46 mm, ranging from 40-56 mm. Mean open water season discharge ranged from 0.07 m³/s at station Windy Hydro to 0.67 m³/s at station Roberts Hydro. Peak flows were recorded in mid-June at stations Doris TL-2, Doris TL-3, and Roberts Hydro, and in early July at station Windy Hydro. Daily peak flows ranged from 0.12 m³/s at station Windy Hydro to 1.97 m³/s at station Roberts Hydro. Open water season low flows occurred in late August at station Doris TL-3, and early September at the other three stations. Low flows ranged from 0.02 m³/s at station Windy Hydro to 0.11 m³/s at station Roberts Hydro.

Table 4-1. Summary of Hydrologic Indices for Compliance Monitoring Stations in the Doris North Project Area, 2013 Open Water Season

Hydrometric Station	Drainage Area (km ²)	Observed Runoff (mm)	Mean Discharge (m ³ /s)	Daily Peak Flow (m ³ /s) (Date)	Daily Low Flow (m ³ /s) (Date)
Doris TL-2	94.6	40	0.46	0.98 (June 22)	0.09 (September 6)
Doris TL-3	95.3	44	0.53	1.25 (June 23)	0.09 (August 25)
Roberts Hydro	97.9	56	0.67	1.97 (June 17)	0.11 (September 1)
Windy Hydro	14.1	42	0.07	0.12 (July 4)	0.02 (September 1)

Note: Hydrologic indices are calculated from recorded values during the open water season. Site-specific periods of record are provided in Table 2.1-1.

To comply with the requirements of Part G, Item 30 and Part J, Item 2 of the Type A Water Licence, the Doris Creek flow prediction program conducted in 2011-2012 was continued in 2013. Doris Creek water levels were recorded on a continuous basis. A satellite telemetry station provided remote access to real-time data, allowing daily flow volume predictions. The results indicate that there was not an overall prediction exceedance relative to the recorded background flow volume in Doris Creek.

Lake water levels for the 2013 open water season are summarized in Table 4-2. During the 2013 monitoring period, water levels at Doris and Tail lakes varied by approximately 0.3 m. Water levels at both Doris and Tail lakes peaked in mid-June as a result of snow and ice melt during freshet, then declined steadily throughout July and August. At Windy Lake, water level variation over the open water season was approximately 0.1 m, less than that observed at Doris and Tail lakes. Windy Lake water level increased rapidly in early to mid-June, then remained fairly consistent throughout most of June and July, reaching an annual peak in early July before declining until late August. A series of precipitation events from late August to early September slowed the rate of water level decrease at all three lakes, resulting in stabilization of water levels at Doris Lake and slight recharge of Tail and Windy lakes in early September.

Table 4-2. Summary of Lake Water Level Variations for Compliance Monitoring Stations in the Doris North Project Area, 2013 Open Water Season

Lake	Lake Area (km ²)	Drainage Area at Lake Outlet (km ²)	Min Water Level (m) (Date)	Max Water Level (m) (Date)	Water Level Change (m)
Doris	3.4	94.6	97.799 (May 22)	98.144 (June 19)	0.346
Tail	0.8	4.2	93.869 (September 1)	94.204 (June 22)	0.335
Windy	5.3	14.1	94.913 (September 1)	95.017 (July 4)	0.104

Notes: Water levels are referenced to a site-specific arbitrary datum. Water levels are for the period of record during the open water season (May-September for Doris and Tail lakes, June-September for Windy Lake). Periods when water levels were affected by ice are excluded.

Compared to previous monitoring years (2009-2012), 2013 was a drier year in terms of runoff and discharge. For all stream monitoring stations the 2013 open water season runoff was 52-72% less than the average open water season runoff for 2009 to 2012.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

References

References

Environment Canada (EC). 2014. *Climate Trends and Variations Bulletins*. <http://www.ec.gc.ca/adsc-cmda/default.asp?lang=En&n=8C03D32A-1>. Accessed February 2014.

ERM Rescan. 2014. *Doris North Project: 2013 Compliance Monitoring Program - Meteorology*. Prepared for TMAC Resources Inc. by ERM Rescan: Vancouver, BC.

Golder. 2007. *Doris North Project “No Net Loss” Plan*. Prepared for Miramar Hope Bay Ltd. by Golder Associates Ltd.: Edmonton, AB.

Herschy, R.W. 2009. *Streamflow Measurement*. 3rd ed. New York, NY: Taylor & Francis.

International Organization for Standardization (ISO). 2010. *ISO 1100-2: 2010. Hydrometry - Measurement of liquid flow in open channels - Part 2: Determination of the stage discharge relationship*. 3rd ed. ISO, Switzerland.

Kennedy, E.J. 1984. *Discharge ratings at gauging stations*. United States Geological Survey Techniques of Water Resources Investigations. Book 3. United States Geological Survey: n.p.

Nunavut Impact Review Board (NIRB). 2006. *Project Certificate NIRB No. 003*, issued September 15, 2006, Cambridge Bay, NU.

Nunavut Water Board (NWB). 2007. Nunavut Water Board Licence No. 2AM-DOH0713 Type A, issued September 19, 2007, Gjoa Haven, NU.

Rantz, S. E. et al. 1982. *Measurement and Computation of Streamflow*. Geological Survey Water-Supply Paper 2175. 1st ed. USGS, United States Government Printing Office: Washington, DC.

Rescan. 2009. *2009 Hydrology Baseline Report, Hope Bay Belt Project*. Prepared for Newmont Mining Corporation by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2010a. *Hope Bay Belt Project: Updates to the Doris North No Net Loss Plan for Tail Lake*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2010b. *Hope Bay Belt Project: Updates to the Doris North No Net Loss Plan for Tail Outflow*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2011a. *Hope Bay Belt Project: 2010 Hydrology Baseline Report*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2011b. *Doris North Project: Hydrology Compliance Report 2011*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2012a. *Hope Bay Belt Project: 2011 Hydrology Baseline Report*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Rescan. 2012b. *Doris North Project: Hydrology Compliance Report 2012*. Prepared for Hope Bay Mining Ltd. by Rescan Environmental Services Ltd.: Vancouver, BC.

Resources Information Standards Committee, Ministry of Environment (RISC). 2009. *Manual of British Columbia Hydrometric Standards*.

SRK Consulting Inc. (SRK). 2012. *Doris North Project Interim Water Management Plan*. Revision 5. Prepared for Hope Bay Mining Ltd. by SRK Consulting Inc.: Vancouver, BC.

2013 HYDROLOGY COMPLIANCE MONITORING REPORT

Terzi, R.A. 1981. *Hydrometric Field Manual - Measurement of Streamflow*. Environment Canada, Inland Waters Directorate. Ottawa, ON.

Water Survey of Canada (WSC). 1999. *National Hydrometric Training Development Manual*. Volumes 1 to 5. Environment Canada. Ottawa, ON.

Wharton, G. 1994. *The Channel Geometry Method: Guidelines and Applications*. Earth Surface Processes and Landforms. Vol. 20, 649-660.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix A


Hydrometric Monitoring Station Information Sheets



General Site Information


Site ID:	Doris TL-2	Drainage Area (km ²):	94.6
Site Location:	Doris Creek at Doris Lake outflow		
UTM:	NAD 83, Zone 13 W	434,059 E	7,559,504 N
Benchmarks	Elevation	Description	
BM59	100.000	Bolt in boulder	
BM58	100.593	Bolt in boulder	
BM57	102.608	Underside of bridge (right bank)	
Transducer:	PS9800	Data Logger:	HOBO Energy Pro
Operating Period:	1996-1998, 2000, 2003-2013		
2013	June 6-September 9		
General Comments:	<ul style="list-style-type: none"> Access by Tail Lake road Transducer is paired with satellite telemetry station for real-time data monitoring during open water season Wadeable under all flow conditions Flow gauging section is approximately 60 m downstream from station 		

Plan View of Hydrometric Station Doris TL-2




DL: data logger, PT: pressure transducer, BM: benchmark

Site Map



Site Photo




Doris TL-2. View is downstream (north). September 6, 2013.

General Site Information


Site ID:	Doris TL-3	Drainage Area (km ²):	95.3		
Site Location:	Doris Creek downstream from waterfall				
UTM:	NAD 83, Zone 13 W	434,204 E	7,559,985 N		
Benchmarks	Elevation	Description			
BM87	100.000	Bolt in boulder			
BM88	99.945	Bolt in boulder			
BM89	100.277	Bolt in boulder			
Transducer and Data Logger:	PT2x				
Operating Period:	2011-2013				
2013	June 9-September 7				
General Comments:	<ul style="list-style-type: none"> Access by foot from Tail Lake road (approximately 500 m downstream from Doris Creek bridge and station Doris TL-2) or by helicopter Wadeable under most flow conditions Flow gauging section is approximately 20 m upstream from station 				

Plan View of Hydrometric Station Doris TL-3




DL: data logger, PT: pressure transducer, BM: benchmark

Site Map



Site Photo




Doris TL-3. View is downstream (north). August 15, 2013.

General Site Information


Site ID:	Roberts Hydro	Drainage Area (km ²):	97.9		
Site Location:	Roberts Lake outflow				
UTM:	NAD 83, Zone 13 W	435,325 E	7,562,815 N		
Benchmarks	Elevation	Description			
BM49	100.000	Bolt in bedrock			
BM50	100.077	Bolt in boulder			
BM64	99.813	Bolt in boulder			
BM12	100.059	Bolt in bedrock			
Transducer and Data Logger:	PT2x				
Operating Period:	2003-2013				
2013	June 7-September 8				
General Comments:	<ul style="list-style-type: none"> Access by helicopter Wadeable under most flow conditions Flow gauging section is approximately 80 m downstream from lake outlet 				

Plan View of Hydrometric Station Roberts Hydro




DL: data logger, PT: pressure transducer, BM: benchmark

Site Map



Site Photo




Roberts Hydro (station demobilized for winter). View is northwest towards lake outlet. September 8, 2013.

General Site Information


Site ID:	Windy Hydro	Drainage Area (km ²):	14.1
Site Location:	Windy Lake outflow		
UTM:	NAD 83, Zone 13 W	431,481 E	7,555,089 N
Benchmarks	Elevation		Description
BM24	100.000		Bolt in bedrock
BM23	99.656		Bolt in bedrock
BM45	95.617		Bolt in boulder
Transducer and Data Logger:	PT2x		
Operating Period:	2006-2013		
2013	June 5-September 8		
General Comments:	<ul style="list-style-type: none"> Access by helicopter Wadeable under all flow conditions Flow gauging section is approximately 500 m downstream from lake outlet 		

Plan View of Hydrometric Station Windy Hydro




DL: data logger, PT: pressure transducer, BM: benchmark

Site Map



Site Photo




Windy Hydro. View is northwest. July 7, 2013.

General Site Information


Site ID:	Doris Lake	Drainage Area (km ²):	n/a
Site Location:	Northwest shore of Doris Lake near Doris Camp		
UTM:	NAD 83, Zone 13 W	433,512 E	7,558,452 N
Benchmarks	Elevation	Description	
BM70	100.000	Bolt in bedrock	
BM71	99.243	Bolt in bedrock	
BM72	98.550	Bolt in bedrock	
Transducer:	KPSI 730-series	Data Logger:	DD-320
Operating Period:	2004-2013		
2013	Continuous operation		
General Comments:	<ul style="list-style-type: none"> Access by foot from Doris Lake boat ramp Station monitors lake levels only; no flow measurements are taken at this location Station operates continuously; transducer is installed approximately 5 m deep to prevent ice damage 		

Plan View of Hydrometric Station Doris Lake



DL: data logger, PT: pressure transducer, BM: benchmark

Site Map



Site Photo




General Site Information

Site ID:	Tail Lake	Drainage Area (km ²):	n/a
Site Location:	Northwest shore of Tail Lake near North Dam		
UTM:	NAD 83, Zone 13 W	434,832 E	7,558,560 N
Benchmarks	Elevation	Description	
BM80	100.000	Bolt in bedrock	
BM81	97.480	Bolt in bedrock	
BM82	98.173	Bolt in bedrock	
Transducer:	KPSI 730-series	Data Logger:	DD-320
Operating Period:	2004-2013		
2013	Continuous operation		
General Comments:	<ul style="list-style-type: none"> Access by foot from North Dam (station is approximately 800 m south of dam), or by helicopter Station monitors lake levels only; no flow measurements are taken at this location Station operates continuously; transducer is installed approximately 5 m deep to prevent ice damage 		


Plan View of Hydrometric Station Tail Lake



Site Map



Site Photo



DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix B

Manual Stage and Discharge Measurements



Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method									
Project Name	Hope Bay					Time (24 hr PST)	Start	12:44	End	13:05	Location	Approximately 50 m DS of station			
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)		Instrument Model	FH950					
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic flow meter		Instrument Serial #	130861001498					
Date Monitored	5-Jun-13					Stage (m)	Start	Reading	n/a	Time	n/a				
Time at Site (24 hr PST)	Start Time:	10:00	End Time:	13:45			End	Reading	n/a	Time	n/a				
Personnel	Natasha Cowie, Emerson Belland						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q	
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	
	434059	7559504				RB	1.00	0.00	0.0	0.01	0		0.000	0.0	
Weather Conditions	Warm, sunny, calm						1.10	0.10	0.1	0.01	0.01		0.000	1.8	
Transducer Information							1.20	0.10	0.1	0.01	0.03		0.000	5.5	
PT Model	PS9800	Serial #	21041003				1.30	0.13	0.1	0.01	0.04		0.001	9.6	
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				1.40	0.13	0.1	0.02	0.01		0.000	3.6	
Status	Inactive	Battery	100%				1.60	0.14	0.2	0.02	0.04		0.001	15.5	
# of Records	None	Memory Free	wrap				1.70	0.16	0.1	0.02	0.03		0.000	8.8	
Date Serviced	Unknown	Crest Gauges	No				1.80	0.16	0.1	0.02	0.03		0.000	8.8	
Hydrometric Leveling Survey							1.90	0.16	0.1	0.02	0.03		0.000	8.8	
Stn	BS	HI	FS	Elevation	Notes		2.00	0.15	0.1	0.02	0.02		0.000	5.5	
BM 59	1.758	101.758		100.000			2.10	0.16	0.1	0.02	0.04		0.001	11.8	
BM 58			1.166	100.592			2.20	0.14	0.1	0.01	0.05		0.001	12.9	
BM 57			-0.844	102.602	inverted BM		2.30	0.14	0.1	0.01	0.02		0.000	5.2	
TBM	1.718	101.784	1.692	100.066			2.40	0.12	0.1	0.01	0.01		0.000	2.2	
BM 57			-0.820	102.604	inverted BM	LB	2.50	0.00	0.1	0.01	0		0.000	0.0	
BM 58			1.191	100.593											
BM 59			1.785	99.999											
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes										
BM 59		100.000													
BM 58		100.593													
BM 57		102.603			New	Total Q						0.005	100.0		
Summary							General Notes								
Stage (m)	-						Satellite telemetry station and PT set up, but were not launched because stream was still frozen to bed at station. Water level was not surveyed due to ice at station. Established new benchmark (BM 57) on the underside of the bridge and surveyed it into the network as an inverted benchmark. At flow measurement, only half of channel was open and flowing; the other half was frozen solid to the bed. Flow measurement was taken from RB to rock near midchannel that marked the edge of the ice. Velocity measurements recorded in field notes have been checked against FH950 file.								
Discharge (m ³ /s)	0.005														
Pressure Transducer Reading (m)	-														
Pressure Transducer Elevation (m)	-														

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method															
Project Name	Hope Bay					Time (24 hr PST)	Start	11:35	End	12:00	Location	Approximately 60 m DS of station									
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950										
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498										
Date Monitored	6-Jun-13					Stage (m)	Start	Reading	0.7346	Time	11:13										
Time at Site (24 hr PST)	Start Time:	10:00	End Time:	12:15			End	Reading	n/a	Time											
Personnel	Natasha Cowie, Emerson Belland					Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q								
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%							
	434059	7559504				RB	0.32	0.00	0.0	0.02	0		0.000	0.0							
Weather Conditions	Cloudy, cold, windy, light rain						0.45	0.30	0.1	0.04	0.06		0.003	1.6							
Transducer Information							0.60	0.30	0.2	0.05	0.2		0.009	5.7							
PT Model	PS9800	Serial #		2104003			0.75	0.32	0.2	0.05	0.28		0.013	8.5							
Gain	Low: 4mA = 0.0m H2O			Offset	High: 20mA = 3.515 m H2O			0.90	0.35	0.2	0.06	0.26		0.016	10.1						
Status	Active	Battery		100%			1.10	0.32	0.2	0.06	0.27		0.015	9.6							
# of Records	None	Memory Free		wrap			1.25	0.32	0.2	0.05	0.33		0.016	10.1							
Date Serviced	Unknown	Crest Gauges		None			1.40	0.32	0.2	0.05	0.31		0.015	9.4							
Hydrometric Leveling Survey							1.55	0.28	0.2	0.04	0.22		0.009	5.9							
Stn	BS	HI	FS	Elevation	Notes		1.70	0.30	0.2	0.05	0.2		0.009	5.7							
BM 59	1.838	101.838		100.000			1.85	0.30	0.2	0.05	0.22		0.010	6.3							
BM 58			1.245	100.593			2.00	0.27	0.2	0.04	0.24		0.010	6.2							
BM 57			-0.764	102.602	inverted BM		2.15	0.29	0.2	0.04	0.21		0.009	5.8							
PT			3.596	98.242	PT end of pipe		2.30	0.23	0.2	0.03	0.16		0.006	3.5							
WL			3.048	98.790	surveyed at 10:52		2.45	0.24	0.2	0.04	0.11		0.004	2.5							
TBM	3.055	101.732	3.161	98.677		behind rock	2.60	0.22	0.2	0.04	-0.01		0.000	-0.2							
WL			2.958	98.774	surveyed at 11:02		2.80	0.26	0.2	0.05	0.05		0.002	1.4							
PT			3.491	98.241			2.95	0.28	0.2	0.05	0.18		0.009	5.6							
BM 57			-0.870	102.602	inverted BM		3.15	0.08	0.2	0.02	0.15		0.004	2.3							
BM 58			1.139	100.593		LB	3.55	0.00	0.4	0.02	0		0.000	0.0							
BM 59			1.732	100.000																	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																	
BM 59		100.000																			
BM 58		100.593																			
BM 57		102.602				Total Q					0.16	100.0									
Summary						General Notes															
Stage (m)	98.782					Doris TL-2 station launched at 10:30 PST. Water depth above transducer (measured from end of PVC) was 0.555 m at 10:52 PST. Fluctuating water level was observed during the survey. Velocity measurements recorded in field notes have been checked against FH950 file.															
Discharge (m ³ /s)	0.16																				
Pressure Transducer Reading (m)	0.735																				
Pressure Transducer Elevation (m)	98.047																				

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method								
Project Name	Hope Bay					Time (24 hr PST)	Start	13:38	End	14:06	Location	Approximately 60 m DS of station		
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950			
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498			
Date Monitored	9-Jun-13					Stage (m)	Start	Reading	0.849	Time	13:31			
Time at Site (24 hr PST)	Start Time:	12:45	End Time:	14:15			End	Reading	0.851	Time	14:01			
Personnel	Natasha Cowie, Emerson Belland					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%
	434059	7559504				LB	1.95	0.00	0.0	0.00	0		0.000	0.0
Weather Conditions	Cloudy, cold, windy, some sleet, air temp +1°C, water temp +3°C						2.00	0.16	0.1	0.01	0.07		0.001	0.2
Transducer Information							2.10	0.17	0.1	0.02	0.6		0.010	1.9
PT Model	PS9800	Serial #	2104003				2.20	0.15	0.1	0.02	0.56		0.013	2.4
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				2.40	0.16	0.2	0.03	0.36		0.012	2.1
Status	Active	Battery	100%				2.60	0.18	0.2	0.04	0.69		0.025	4.6
# of Records	Must download	Memory Free	wrap				2.80	0.18	0.2	0.04	0.7		0.025	4.7
Date Serviced	Unknown	Crest Gauges	None				3.00	0.19	0.2	0.04	0.58		0.022	4.1
Hydrometric Leveling Survey							3.20	0.21	0.2	0.04	0.59		0.025	4.6
Stn	BS	HI	FS	Elevation	Notes		3.40	0.20	0.2	0.04	0.57		0.023	4.3
BM 59	1.762	101.762		100.000			3.60	0.20	0.2	0.05	0.6		0.027	5.0
BM 58			1.168	100.594			3.85	0.22	0.3	0.05	0.56		0.028	5.2
BM 57			-0.836	102.598	inverted BM		4.05	0.24	0.2	0.04	0.77		0.032	6.0
WL			2.881	98.881	surveyed at 13:04		4.20	0.24	0.2	0.04	0.85		0.036	6.7
PT			3.533	98.229	PT end of pipe		4.40	0.24	0.2	0.05	0.93		0.045	8.3
TBM	3.254	101.799	3.217	98.545	BS corrected (see notes)		4.60	0.25	0.2	0.05	0.85		0.042	7.9
PT			3.570	98.229			4.80	0.25	0.2	0.05	0.73		0.037	6.8
WL			2.917	98.882	surveyed at 13:13		5.00	0.26	0.2	0.05	0.72		0.037	7.0
BM 57			-0.800	102.599			5.20	0.24	0.2	0.05	0.87		0.042	7.8
BM 58			1.205	100.594			5.40	0.24	0.2	0.04	0.69		0.025	4.6
BM 59			1.799	100.000			5.50	0.24	0.1	0.04	0.52		0.019	3.5
							5.70	0.18	0.2	0.07	0.18		0.012	2.3
							RB	6.25	0.00	0.6	0.05	0	0.000	0.0
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes										
BM 59		100.000												
BM 58		100.594												
BM 57		102.599					Total Q						0.54	100.0
Summary							General Notes							
Stage (m)	98.882						Rod holder (E. Belland) noticed that the temporary benchmark shifted slightly while the level was being moved. All shots after the TBM were either 3 or 4 mm off, so the TBM BS was corrected from 3.257 to 3.254. Velocity measurements recorded in field notes have been checked against FH950 file.							
Discharge (m ³ /s)	0.54													
Pressure Transducer Reading (m)	0.847													
Pressure Transducer Elevation (m)	98.034													

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method								
Project Name	Hope Bay					Time (24 hr PST)	Start	14:30	End	14:55	Location	Approximately 40 m US of station		
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950			
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498			
Date Monitored	10-Jun-13					Stage (m)	Start	Reading	0.873	Time	14:31			
Time at Site (24 hr PST)	Start Time:	12:00	End Time:	16:30			End	Reading	0.876	Time	14:51			
Personnel	Natasha Cowie, Emerson Belland					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%
	434059	7559504				LB	10.00	0.00	0.0	0.16	0		0.000	0.0
Weather Conditions	Sunny, warm, light wind, air temp 13°C, water temp 5°C						8.40	0.20	-1.6	0.17	0.05		0.009	1.6
Transducer Information							8.30	0.37	-0.1	0.07	0.21		0.016	3.0
PT Model	PS9800	Serial #	2104003				8.00	0.42	-0.3	0.13	0.26		0.033	6.2
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				7.70	0.41	-0.3	0.12	0.23		0.028	5.4
Status	Active	Battery	100%				7.40	0.42	-0.3	0.13	0.29		0.037	7.0
# of Records	Must download	Memory Free	wrap				7.10	0.44	-0.3	0.13	0.28		0.037	7.0
Date Serviced	Unknown	Crest Gauges	None				6.80	0.48	-0.3	0.14	0.26		0.037	7.1
Hydrometric Leveling Survey							6.50	0.50	-0.3	0.15	0.19		0.029	5.4
Stn	BS	HI	FS	Elevation	Notes		6.20	0.51	-0.3	0.15	0.16		0.024	4.7
BM 59	1.768	101.768		100.000			5.90	0.50	-0.3	0.15	0.15		0.023	4.3
BM 58			1.173	100.595			5.60	0.51	-0.3	0.15	0.15		0.023	4.4
BM 57			-0.834	102.602			5.30	0.49	-0.3	0.15	0.14		0.021	3.9
WL			2.867	98.901	surveyed at 16:06		5.00	0.44	-0.3	0.13	0.16		0.021	4.0
PT			3.542	98.226	PT end of pipe		4.70	0.39	-0.3	0.12	0.19		0.022	4.2
TBM	3.405	101.755	3.418	98.350			4.40	0.38	-0.3	0.11	0.2		0.023	4.3
PT			3.529	98.226			4.10	0.40	-0.3	0.12	0.24		0.029	5.5
WL			2.851	98.904	surveyed at 16:16		3.80	0.33	-0.3	0.10	0.25		0.025	4.7
BM 57			-0.848	102.603			3.50	0.28	-0.3	0.08	0.23		0.019	3.7
BM 58			1.159	100.596			3.20	0.25	-0.3	0.08	0.26		0.020	3.7
BM 59			1.755	100.000			2.90	0.22	-0.3	0.09	0.24		0.021	4.0
							2.40	0.18	-0.5	0.09	0.21		0.019	3.6
							1.90	0.14	-0.5	0.06	0.15		0.009	1.8
							1.50	0.06	-0.4	0.02	0.06		0.001	0.2
						RB	1.20	0.00	0.0	0.01	0		0.000	0.0
BM# Established Elevation (m) Mean Elevation (this date) (m) Difference (m) Notes						Total Q							0.52	100.0
Summary						General Notes								
Stage (m)	98.903					Flow measurement was recorded on FH950 only, no field notes taken.								
Discharge (m ³ /s)	0.52													
Pressure Transducer Reading (m)	0.875													
Pressure Transducer Elevation (m)	98.028													

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name	Hope Bay					Time (24 hr PST)	Start	9:32	End	10:31	Location	Approximately 40 m US of station											
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950												
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498												
Date Monitored	11-Jun-13					Stage (m)	Start	0.891	Time	9:31													
Time at Site (24 hr PST)	Start Time: 7:45	End Time: 10:50					End	0.894	Time	10:31													
Personnel	Natasha Cowie, Emerson Belland (survey), Cathy Anablak (flow measurement)					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q									
Station Coordinates	Easting 434059	Northing 7559504	Elevation			Notes RB	(m) 0.40	(m) 0.00	(m ²) 0.01	60% 0	20% 0.000	80% 0.000	(m ³ /s)	% 0.0									
Weather Conditions	Sunny, warm, light wind, air temp 13°C, water temp 4°C						0.80	0.06	0.4	0.02	0.04		0.001	0.1									
Transducer Information							1.00	0.11	0.2	0.02	0.14		0.003	0.5									
PT Model	PS9800	Serial #	2104003				1.20	0.14	0.2	0.03	0.17		0.005	0.8									
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				1.40	0.15	0.2	0.03	0.19		0.006	1.0									
Status	Active	Battery	100%				1.60	0.18	0.2	0.04	0.18		0.006	1.1									
# of Records	Must download	Memory Free	wrap				1.80	0.21	0.2	0.05	0.22		0.012	2.0									
Date Serviced	Unknown	Crest Gauges	None				2.10	0.24	0.3	0.07	0.2		0.014	2.5									
Hydrometric Leveling Survey							2.40	0.29	0.3	0.09	0.23		0.020	3.5									
Stn	BS	HI	FS	Elevation	Notes		2.70	0.31	0.3	0.09	0.22		0.020	3.6									
BM 59	1.992	101.992		100.000	primary		3.00	0.32	0.3	0.10	0.23		0.022	3.8									
BM 58			1.397	100.595			3.30	0.34	0.3	0.10	0.24		0.024	4.3									
BM 57			-0.611	102.603	inverted on bridge		3.60	0.36	0.3	0.11	0.23		0.025	4.3									
WL			3.075	98.917	on conduit		3.90	0.38	0.3	0.11	0.2		0.023	4.0									
PT			3.771	98.221	PT end of pipe		4.20	0.39	0.3	0.12	0.16		0.019	3.3									
TBM	3.048	101.718	3.322	98.670			4.50	0.43	0.3	0.15	0.12		0.018	3.1									
PT			3.499	98.219			4.90	0.45	0.4	0.16	0.1		0.016	2.7									
WL			2.802	98.916			5.20	0.47	0.3	0.14	0.09		0.013	2.2									
BM 57			-0.882	102.600			5.50	0.48	0.3	0.17	0.11		0.018	3.2									
BM 58			1.125	100.593			5.90	0.50	0.4	0.20	0.12		0.024	4.2									
BM 59			1.721	99.997			6.30	0.50	0.4	0.20	0.14		0.028	4.9									
							6.70	0.50	0.4	0.18	0.23		0.040	7.0									
							7.00	0.52	0.3	0.16	0.28		0.044	7.6									
							7.30	0.49	0.3	0.15	0.28		0.041	7.2									
							7.60	0.44	0.3	0.13	0.28		0.037	6.4									
							7.90	0.44	0.3	0.13	0.27		0.036	6.2									
							8.20	0.41	0.3	0.12	0.29		0.036	6.2									
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			8.50	0.34	0.3	0.10	0.22		0.022	3.9									
BM 59	100.000	99.999	0.001				8.80	0.12	0.3	0.04	0.03		0.001	0.2									
BM 58		100.594					9.20	0.09	0.4	0.05	0		0.000	0.0									
BM 57		102.602				LB	10.00	0.00	0.8	0.04	0		0.000	0.0									
Summary						Total Q							0.57	100.0									
Stage (m)	98.917					General Notes																	
Discharge (m ³ /s)	0.57					Velocity measurements recorded in field notes have been checked against FH950 file.																	
Pressure Transducer Reading (m)	0.892																						
Pressure Transducer Elevation (m)	98.025																						

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method														
Project Name	Hope Bay					Time (24 hr PST)	Start	16:50	End	17:20	Location	Approximately 60 m DS of station								
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950									
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498									
Date Monitored	12-Jun-13					Stage (m)	Start	Reading	0.921	Time	16:51									
Time at Site (24 hr PST)	Start Time:	15:45	End Time:	17:30			End	Reading	0.923	Time	17:21									
Personnel	Natasha Cowie, Cathy Anabla					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q						
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%						
	434059	7559504				RB	2.10	0.00	0.0	0.01	0		0.000	0.0						
Weather Conditions	Warm, cloudy, light breeze, air temp 13°C, water temp 6°C					grass	2.20	0.13	0.1	0.01	0.31		0.004	0.6						
Transducer Information							2.30	0.24	0.1	0.03	0.46		0.014	2.0						
PT Model	PS9800	Serial #	2104003				2.45	0.24	0.2	0.04	0.56		0.020	2.9						
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O			on rock	2.60	0.22	0.2	0.04	0.65		0.025	3.6						
Status	Active	Battery	100%				2.80	0.32	0.2	0.06	0.73		0.041	5.8						
# of Records	Must download	Memory Free	wrap				2.95	0.33	0.2	0.06	0.74		0.043	6.1						
Date Serviced	Unknown	Crest Gauges	None				3.15	0.28	0.2	0.06	0.74		0.041	5.9						
Hydrometric Leveling Survey							3.35	0.32	0.2	0.06	0.71		0.045	6.5						
Stn	BS	HI	FS	Elevation	Notes		3.55	0.32	0.2	0.06	0.79		0.051	7.2						
BM 59	1.679	101.679		100.000	primary		3.75	0.31	0.2	0.06	0.8		0.050	7.1						
BM 58			1.083	100.596			3.95	0.30	0.2	0.06	0.71		0.043	6.1						
BM 57			-0.925	102.604	inverted BM		4.15	0.32	0.2	0.06	0.65		0.036	5.2						
WL			2.737	98.942	surveyed at 16:07		4.30	0.32	0.1	0.06	0.59		0.033	4.7						
PT			3.465	98.214	PT end of pipe		4.50	0.26	0.2	0.06	0.55		0.032	4.6						
TBM	1.882	101.649	1.912	99.767			4.75	0.28	0.3	0.06	0.64		0.040	5.7						
WL			2.705	98.944	surveyed at 16:16		4.95	0.28	0.2	0.06	0.63		0.040	5.7						
PT			3.435	98.214			5.20	0.25	0.3	0.06	0.76		0.043	6.1						
BM 57			-0.952	102.601			5.40	0.18	0.2	0.04	0.74		0.027	3.8						
BM 58			1.053	100.596			5.60	0.22	0.2	0.04	0.57		0.025	3.6						
BM 59			1.648	100.001			5.80	0.20	0.2	0.04	0.51		0.020	2.9						
							6.00	0.22	0.2	0.04	0.42		0.018	2.6						
							6.20	0.20	0.2	0.04	0.28		0.011	1.6						
						LB	6.40	0.00	0.2	0.02	0		0.000	0.0						
BM# Established Elevation (m) Mean Elevation (this date) (m) Difference (m) Notes							Total Q			0.70			100.0							
BM 59	100.000	100.001	-0.001				General Notes													
Discharge (m ³ /s)	98.943						Assistant (C. Anabla) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.727 m at 16:07 PST. Velocity measurements recorded in field notes have been checked against FH950 file.													
Pressure Transducer Reading (m)	0.70																			
Pressure Transducer Elevation (m)	0.922																			
	98.021																			
Summary							Total Q			0.70			100.0							
Stage (m)	98.943						General Notes													
Discharge (m ³ /s)	0.70																			
Pressure Transducer Reading (m)	0.922																			
Pressure Transducer Elevation (m)	98.021																			

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method									
Project Name	Hope Bay					Time (24 hr PST)	Start	9:05	End		9:52	Location	Approximately 60 m DS of station		
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	FH950				
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498				
Date Monitored	13-Jun-13					Stage (m)	Start	Reading	0.935	Time	9:01				
Time at Site (24 hr PST)	Start Time: 7:30	End Time: 11:36					End	Reading	0.935	Time	9:51				
Personnel	Natasha Cowie, Cathy Anabla					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q	
Station Coordinates	Easting 434059	Northing 7559504	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%	
Weather Conditions	Partly cloudy, warm, calm, air temp 22°C falling to 15°C, water temp 5°C					RB side channel	8.40	0.00	0.0	0.05	0		0.000	0.0	
						grass	7.90	0.18	-0.5	0.07	0.01		0.001	0.1	
						grass	7.60	0.14	-0.3	0.04	0.03		0.001	0.1	
						grass	7.40	0.10	-0.2	0.05	0.01		0.000	0.1	
PT Model	PS9800	Serial #	2104003			LB side channel	6.70	0.00	-0.7	0.04	0		0.000	0.0	
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O			RB main channel	6.70	0.00	0.0	0.02	0		0.000	0.0	
Status	Active	Battery	100%										0.000	0.0	
# of Records	Must download	Memory Free	wrap										0.010	1.3	
Date Serviced	Unknown	Crest Gauges	None										0.023	3.1	
Hydrometric Leveling Survey							6.10	0.32	-0.2	0.06	0.49		0.027	3.7	
Stn	BS	HI	FS	Elevation	Notes		5.95	0.35	-0.1	0.05	0.62		0.033	4.4	
BM 59	1.663	101.663		100.000	primary		5.80	0.34	-0.2	0.05	0.75		0.038	5.2	
BM 58			1.068	100.595			5.65	0.36	-0.1	0.06	0.61		0.038	5.2	
BM 57			-0.938	102.601	inverted on bridge		5.45	0.35	-0.2	0.06	0.72		0.044	6.0	
WL			2.710	98.953	surveyed at 8:00		5.30	0.35	-0.2	0.06	0.72		0.044	6.0	
PT			3.453	98.210	PT end of pipe		5.10	0.32	-0.2	0.06	0.75		0.048	6.5	
TBM	1.843	101.607	1.899	99.764			4.90	0.36	-0.2	0.07	0.68		0.049	6.6	
WL			2.651	98.956	surveyed at 8:12		4.70	0.35	-0.2	0.07	0.67		0.047	6.3	
PT			3.395	98.212			4.50	0.34	-0.2	0.07	0.6		0.041	5.5	
BM 57			-0.996	102.603			4.30	0.32	-0.2	0.06	0.48		0.031	4.2	
BM 58			1.012	100.595			4.10	0.31	-0.2	0.06	0.54		0.033	4.5	
BM 59			1.605	100.002			3.90	0.30	-0.2	0.06	0.58		0.035	4.7	
							3.70	0.31	-0.2	0.06	0.6		0.037	5.0	
							3.50	0.32	-0.2	0.06	0.68		0.044	5.9	
							3.30	0.28	-0.2	0.04	0.72		0.030	4.1	
					on rock		3.20	0.20	-0.1	0.04	0.67		0.027	3.6	
							2.90	0.24	-0.3	0.06	0.48		0.029	3.9	
							2.70	0.24	-0.2	0.05	0.4		0.019	2.6	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			2.50	0.18	-0.2	0.04	0.28		0.010	1.4	
BM 59		100.001					grass	2.30	0.11	-0.2	0.02	0.02		0.000	0.1
BM 58		100.595					LB main channel	2.10	0.00	-0.2	0.01	0		0.000	0.0
BM 57		102.602													
Summary						Total Q							0.74	100.0	
Stage (m)	98.955					General Notes									
Discharge (m ³ /s)	0.74					Assistant (C. Anabla) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.750 m at 11:10 PST. Velocity measurements recorded in field notes have been checked against FH950 file.									
Pressure Transducer Reading (m)	0.935														
Pressure Transducer Elevation (m)	98.020														

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method								
Project Name	Hope Bay					Time (24 hr PST)	Start	9:54	End	10:30	Location	Approximately 60 m DS of station		
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000			
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614			
Date Monitored	6-Jul-13					Stage (m)	Start	Reading	0.949	Time	9:51			
Time at Site (24 hr PST)	Start Time: 8:20	End Time: 11:00					End	Reading	0.947	Time	10:31			
Personnel	Natasha Cowie, Leonard Wingnek					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	60%	20%	80%	(m³/s)	%
	434059	7559504				RB side channel	8.10	0.00	0.0	0.04	0		0.000	0.0
Weather Conditions	Warm, sunny, light wind, 24°C					grass	7.60	0.14	-0.5	0.06	0		0.000	0.0
Transducer Information						grass	7.30	0.13	-0.3	0.05	0.01		0.001	0.1
PT Model	PS9800	Serial #	2104003			LB side channel	6.80	0.00	-0.5	0.00	0		0.000	0.0
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O			RB main channel	6.30	0.00	-0.5	0.01	0		0.000	0.0
Status	Active	Battery	100%				6.20	0.20	-0.1	0.03	0.19		0.006	0.7
# of Records	4287	Memory Free	wrap				6.00	0.33	-0.2	0.07	0.41		0.027	3.5
Date Serviced	Unknown	Crest Gauges	None				5.80	0.34	-0.2	0.07	0.51		0.035	4.5
Hydrometric Leveling Survey							5.60	0.36	-0.2	0.06	0.71		0.045	5.8
Stn	BS	HI	FS	Elevation	Notes		5.45	0.35	-0.1	0.05	0.72		0.038	4.9
BM 59	1.713	101.713		100.000	P		5.30	0.35	-0.2	0.06	0.65		0.040	5.1
BM 58			1.116	100.597			5.10	0.36	-0.2	0.07	0.74		0.053	6.9
BM 57			-0.902	102.615	inverted on bridge		4.90	0.36	-0.2	0.06	0.70		0.044	5.7
WL			2.786	98.927	surveyed at 8:48 PST		4.75	0.32	-0.2	0.05	0.74		0.036	4.6
PT			3.506	98.207	hose clamp bolt on end		4.60	0.36	-0.2	0.06	0.70		0.044	5.7
TBM	1.991	101.751	1.953	99.760			4.40	0.34	-0.2	0.07	0.68		0.046	6.0
WL			2.825	98.926	surveyed at 9:06 PST		4.20	0.33	-0.2	0.07	0.65		0.043	5.5
PT			3.544	98.207			4.00	0.32	-0.2	0.06	0.58		0.037	4.8
BM 57			-0.865	102.616			3.80	0.33	-0.2	0.07	0.49		0.032	4.2
BM 58			1.154	100.597			3.60	0.31	-0.2	0.06	0.57		0.035	4.6
BM 59			1.751	100.000			3.40	0.30	-0.2	0.06	0.63		0.038	4.9
							3.20	0.30	-0.2	0.06	0.68		0.041	5.3
							3.00	0.26	-0.2	0.06	0.69		0.040	5.2
							2.75	0.25	-0.3	0.06	0.62		0.039	5.0
							2.50	0.21	-0.3	0.05	0.55		0.026	3.4
							2.30	0.23	-0.2	0.04	0.48		0.019	2.5
							2.15	0.20	-0.2	0.03	0.35		0.011	1.4
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	grass		2.00	0.14	-0.2	0.02	0.02		0.000	0.1
BM 59		100.000			LB main channel		1.80	0.00	-0.2	0.01	0		0.000	0.0
BM 58		100.597												
BM 57		102.616												
Summary						Total Q							0.78	100.0
Stage (m)	98.927					General Notes								
Discharge (m³/s)	0.78					Water depth above end of PVC containing transducer approx. 0.753 m.								
Pressure Transducer Reading (m)	0.945													
Pressure Transducer Elevation (m)	97.982													

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method								
Project Name	Hope Bay					Time (24 hr PST)	Start	11:40	End	12:17	Location	Approximately 60 m DS of station		
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000			
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614			
Date Monitored	8-Jul-13					Stage (m)	Start	Reading	0.924	Time	11:41			
Time at Site (24 hr PST)	Start Time:	9:20	End Time:	11:30			End	Reading	0.930	Time	12:21			
Personnel	Natasha Cowie, Jem Morrison						Station	Depth	Distance	Area	Velocity (m/s)			Q
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)
	434059	7559504				RB side channel	0.50	0.00	0.0	0.03	0			0.000
Weather Conditions	Warm, sunny, light wind, air 24°C, water 9°C					grass	1.00	0.13	0.5	0.06	0			0.000
						grass	1.40	0.12	0.4	0.05	0			0.000
Transducer Information														
PT Model	PS9800	Serial #	2104003			LB side channel	1.75	0.00	0.4	0.00	0			0.000
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O			RB main channel	2.35	0.00	0.6	0.01	0			0.000
Status	Active	Battery	100%				2.45	0.24	0.1	0.03	0.26			0.008
# of Records	4585	Memory Free	wrap				2.60	0.32	0.2	0.05	0.38			0.018
Date Serviced	Unknown	Crest Gauges	None				2.75	0.33	0.2	0.05	0.48			0.024
Hydrometric Leveling Survey							2.90	0.35	0.2	0.05	0.55			0.029
Stn	BS	HI	FS	Elevation	Notes		3.05	0.35	0.2	0.05	0.72			0.038
BM 59	1.714	101.714		100.000	P		3.20	0.31	0.2	0.05	0.72			0.033
BM 58			1.116	100.598			3.35	0.29	0.2	0.04	0.70			0.030
BM 57			-0.901	102.615	inverted		3.50	0.32	0.2	0.05	0.72			0.035
SG			2.468	99.246	top of vertical rebar		3.65	0.31	0.2	0.05	0.71			0.033
WL			2.797	98.917	surveyed at 11:08 PST		3.80	0.34	0.2	0.05	0.70			0.036
PT			3.532	98.182	end of PVC		3.95	0.36	0.2	0.05	0.66			0.036
TBM	1.858	101.773	1.799	99.915			4.10	0.36	0.1	0.05	0.61			0.033
PT			3.590	98.183			4.25	0.35	0.2	0.05	0.63			0.033
WL			2.858	98.915	surveyed at 11:16 PST		4.40	0.34	0.2	0.05	0.57			0.029
SG			2.527	99.246			4.55	0.33	0.1	0.05	0.52			0.026
BM 57			-0.843	102.616			4.70	0.32	0.2	0.05	0.46			0.022
BM 58			1.175	100.598			4.85	0.32	0.1	0.05	0.46			0.022
BM 59			1.773	100.000			5.00	0.30	0.2	0.05	0.51			0.023
							5.15	0.31	0.2	0.05	0.54			0.025
							5.30	0.29	0.1	0.04	0.56			0.024
							5.45	0.30	0.2	0.05	0.60			0.027
							5.60	0.31	0.1	0.05	0.63			0.029
							5.75	0.30	0.2	0.05	0.56			0.025
							5.90	0.27	0.2	0.04	0.49			0.020
							6.05	0.27	0.1	0.04	0.42			0.017
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			6.20	0.26	0.2	0.04	0.36			0.014
BM 59		100.000					6.35	0.24	0.1	0.04	0.33			0.012
BM 58		100.598				grass	6.50	0.22	0.2	0.04	0.16			0.006
BM 57		102.616				LB main channel	6.70	0.00	0.2	0.02	0			0.000
Summary						Total Q						0.71	100.0	
Stage (m)	98.916					General Notes								
Discharge (m ³ /s)	0.71					Water depth above end of PVC containing transducer approx. 0.737 m at 11:30 PST. Staff gauge installed at 9:20 PST and surveyed relative to benchmarks.								
Pressure Transducer Reading (m)	0.928													
Pressure Transducer Elevation (m)	97.988													

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name	Hope Bay					Time (24 hr PST)	Start	12:22	End	12:54	Location	Approximately 60 m DS of station											
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000												
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614												
Date Monitored	14-Aug-13					Stage (m)	Start	Reading	0.732	Time	12:21												
Time at Site (24 hr PST)	Start Time:	10:30	End Time:	16:00			End	Reading	0.732	Time	12:51												
Personnel	Natasha Cowie, Leonard Wingnek					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q									
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	60%	20%	80%	(m³/s)	%									
	434059	7559504				RB	0.55	0.00	0.0	0.01	0		0.000	0.0									
Weather Conditions	Warm, sunny, light wind, air 25°C rising to 33°C, water 17°C					grass	0.65	0.15	0.1	0.02	0.05		0.001	0.4									
Transducer Information							0.75	0.18	0.1	0.03	0.11		0.003	1.6									
PT Model	PS9800	Serial #	2104003				0.95	0.18	0.2	0.04	0.22		0.008	4.2									
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				1.15	0.21	0.2	0.04	0.29		0.012	6.4									
Status	Active	Battery	100%				1.35	0.21	0.2	0.04	0.20		0.009	4.4									
# of Records	Must download	Memory Free	wrap				1.55	0.18	0.2	0.04	0.39		0.014	7.4									
Date Serviced	Unknown	Crest Gauges	None				1.75	0.20	0.2	0.03	0.38		0.013	6.8									
Hydrometric Leveling Survey							1.90	0.21	0.2	0.03	0.39		0.012	6.5									
Stn	BS	HI	FS	Elevation	Notes		2.05	0.21	0.2	0.03	0.42		0.013	6.9									
BM 59	1.788	101.788		100.000	primary		2.20	0.21	0.2	0.03	0.42		0.013	6.9									
BM 58			1.202	100.586			2.35	0.21	0.2	0.03	0.38		0.012	6.3									
BM 57		-0.835	102.623	inverted on bridge			2.50	0.21	0.2	0.04	0.35		0.013	6.8									
SG 1		2.634	99.154	angled rebar			2.70	0.20	0.2	0.03	0.23		0.008	4.1									
SG 2		2.54	99.248	straight rebar			2.85	0.18	0.2	0.03	0.23		0.006	3.3									
WL		3.078	98.710	11:06 PST			3.00	0.17	0.2	0.03	0.22		0.006	2.9									
PT		3.611	98.177	end of PVC			3.15	0.17	0.2	0.03	0.21		0.005	2.7									
TBM	1.828	101.589	2.027	99.761			3.30	0.15	0.2	0.02	0.22		0.005	2.6									
PT		3.413	98.176				3.45	0.17	0.2	0.03	0.24		0.006	3.1									
WL		2.876	98.713	11:21 PST			3.60	0.17	0.2	0.03	0.29		0.007	3.8									
SG 1		2.436	99.153				3.75	0.18	0.2	0.03	0.26		0.007	3.7									
SG 2		2.344	99.245				3.90	0.15	0.2	0.02	0.22		0.005	2.6									
BM 57		-1.034	102.623				4.05	0.12	0.2	0.02	0.22		0.004	2.1									
BM 58		1.004	100.585	on rock			4.20	0.06	0.2	0.01	0.2		0.002	1.1									
BM 59		1.589	100.000				4.40	0.12	0.2	0.02	0.21		0.004	2.3									
							4.55	0.09	0.1	0.02	0.15		0.002	1.2									
					LB		4.75	0.00	0.2	0.01	0		0.000	0.0									
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																			
BM 59		100.000																					
BM 58		100.586																					
BM 57		102.623																					
Summary						Total Q							0.19	100.0									
Stage (m)	98.712					General Notes																	
Discharge (m³/s)	0.19					Imperial rod, measurements have been converted																	
Pressure Transducer Reading (m)	0.733																						
Pressure Transducer Elevation (m)	97.979																						

Appendix B-1. Stage and Discharge Measurements at Station Doris TL-2 in 2013

Site Information						Discharge Measurement - Mid-Section Method														
Project Name	Hope Bay					Time (24 hr PST)	Start	9:15	End	9:40	Location	Approximately 60 m DS of station								
Station Identification	Doris TL-2					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000									
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614									
Date Monitored	7-Sep-13					Stage (m)	Start	0.663	Time	9:11										
Time at Site (24 hr PST)	Start Time: 8:00	End Time: 10:00					End	0.658	Time	9:41										
Personnel	Natasha Cowie, Cathy Anablk					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q						
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%						
	434059	7559504				RB	6.80	0.00	0.0	0.01	0.00		0.000	0.0						
Weather Conditions	Cloudy, calm, air 2°C, water 5°C					grass	6.70	0.14	-0.1	0.02	0.00		0.000	0.0						
Transducer Information							6.50	0.15	-0.2	0.03	0.10		0.003	2.7						
PT Model	PS9800	Serial #	2104003				6.35	0.18	-0.2	0.03	0.22		0.006	6.1						
Gain	Low: 4mA = 0.0m H2O	Offset	High: 20mA = 3.515 m H2O				6.20	0.18	-0.1	0.03	0.24		0.007	6.7						
Status	Active	Battery	100%			behind rock	6.05	0.17	-0.2	0.03	0.08		0.002	2.0						
# of Records	Must download	Memory Free	wrap				5.90	0.14	-0.1	0.02	0.22		0.005	5.3						
Date Serviced	Unknown	Crest Gauges	None				5.70	0.15	-0.2	0.03	0.26		0.007	7.0						
Hydrometric Leveling Survey							5.55	0.17	-0.2	0.03	0.25		0.006	6.4						
Stn	BS	HI	FS	Elevation	Notes		5.40	0.17	-0.1	0.03	0.28		0.008	8.3						
BM 59	1.728	101.728		100.000	primary		5.20	0.18	-0.2	0.03	0.22		0.007	7.1						
BM 58			1.146	100.582			5.05	0.18	-0.2	0.03	0.21		0.006	5.8						
BM 57			-0.895	102.623	inverted on bridge		4.90	0.17	-0.1	0.03	0.22		0.006	5.6						
SG 1			2.576	99.152	angled rebar		4.75	0.17	-0.2	0.03	0.19		0.005	4.8						
SG 2			2.480	99.248	straight rebar		4.60	0.17	-0.2	0.03	0.17		0.005	5.0						
WL			3.081	98.647	8:36 PST		4.40	0.15	-0.2	0.03	0.16		0.005	4.9						
PT			3.543	98.185			4.20	0.12	-0.2	0.02	0.15		0.004	3.7						
TBM	3.317	101.977	3.068	98.660			4.00	0.12	-0.2	0.02	0.13		0.003	3.2						
PT			3.797	98.180			3.80	0.15	-0.2	0.03	0.18		0.005	5.5						
WL			3.330	98.647	8:45 PST		3.60	0.12	-0.2	0.02	0.14		0.003	3.5						
SG 2			2.729	99.248			3.40	0.14	-0.2	0.03	0.11		0.003	3.0						
SG 1			2.825	99.152			3.20	0.09	-0.2	0.02	0.10		0.002	1.8						
BM 57			-0.646	102.623			3.00	0.09	-0.2	0.02	0.08		0.001	1.3						
BM 58			1.395	100.582		grass	2.85	0.08	-0.2	0.01	0.01		0.000	0.1						
BM 59			1.978	99.999		LB	2.75	0.00	-0.1	0.00	0		0.000	0.0						
BM# Established Elevation (m) Mean Elevation (this date) (m) Difference (m) Notes						Total Q	0.10			0.10	100.0									
BM 59 100.000						General Notes														
BM 58 100.582						Imperial rod, measurements have been converted														
BM 57 102.623																				
Summary																				
Stage (m)	98.647																			
Discharge (m ³ /s)	0.10																			
Pressure Transducer Reading (m)	0.663																			
Pressure Transducer Elevation (m)	97.984																			

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method										
Project Name	Hope Bay					Time (24 hr PST)	Start	11:45	End	12:13	Location	Approximately 10 m US of station				
Station Identification	Doris TL-3					Method	Velocity-area (Mid-section)			Instrument Model	Hach FH950					
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498					
Date Monitored	9-Jun-13					Stage (m)	Start	Reading	0.6793	Time	11:51					
Time at Site (24 hr PST)	Start Time:	10:15	End Time:	12:30	End	Reading	0.6813	Time	12:11							
Personnel	Natasha Cowie, Emerson Belland					Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q		
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%	
	434204	7559985				RB	3.35	0.00	0.0	0.01	0			0.000	0.0	
Weather Conditions	Cold, cloudy, icy, moderate wind, air 0°C, water +3°C					grass US	3.30	0.46	0.1	0.05	0.16			0.007	1.5	
Transducer Information							3.15	0.46	0.2	0.07	0.33			0.023	4.6	
PT Model	PT2x	Serial #		2922015			3.00	0.45	0.2	0.06	0.36			0.020	4.1	
Gain	0.995	Offset	-0.346			on rock	2.90	0.46	0.1	0.05	0.37			0.017	3.5	
Status	Active	Battery		3.0 v (full)			2.80	0.41	0.1	0.05	0.42			0.022	4.4	
# of Records	0	Memory Free			130,705		2.65	0.48	0.2	0.07	0.45			0.032	6.6	
Date Serviced	Spring 2012	Crest Gauges		No			2.50	0.49	0.2	0.06	0.47			0.029	5.8	
Hydrometric Leveling Survey							2.40	0.50	0.1	0.05	0.45			0.023	4.6	
Stn	BS	HI	FS	Elevation	Notes		2.30	0.50	0.1	0.06	0.45			0.028	5.7	
BM 87	0.362	100.362		100.000			2.15	0.52	0.2	0.08	0.43			0.034	6.8	
BM 88			0.417	99.945			2.00	0.53	0.2	0.08	0.43			0.034	6.9	
BM 89			0.085	100.277			1.85	0.54	0.2	0.08	0.42			0.034	6.9	
WL			3.120	97.242	surveyed at 11:17		1.70	0.55	0.2	0.07	0.42			0.029	5.9	
PT			3.765	96.597	end of PVC		1.60	0.56	0.3	0.07	0.4			0.028	5.7	
TBM	3.628	100.298	3.692	96.670			1.45	0.58	0.2	0.09	0.33			0.029	5.8	
PT			3.701	96.597			1.30	0.58	0.2	0.09	0.28			0.024	4.9	
WL			3.060	97.238	surveyed at 11:26		1.15	0.59	0.2	0.09	0.23			0.020	4.1	
BM 89					could not read		1.00	0.59	0.3	0.09	0.23			0.020	4.1	
BM 88			0.352	99.946			0.85	0.57	0.2	0.09	0.22			0.019	3.8	
BM 87			0.299	99.999	brush blocking view		0.70	0.54	0.2	0.08	0.22			0.018	3.6	
							0.55	0.50	0.2	0.05	0.06			0.003	0.6	
						LB	0.50	0.00	0.1	0.05	0			0.000	0.0	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	Total Q										0.49	100.0
Summary						General Notes										
Stage (m)		97.240				Second shot on BM 89 was not taken because the bottom of the wooden rod was chipped and numbers could not be read. Velocity measurements in field notes have been checked against velocity measurements recorded by the FH950.										
Discharge (m ³ /s)		0.49														
Pressure Transducer Reading (m)		0.679														
Pressure Transducer Elevation (m)		96.561														

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method																													
Project Name	Hope Bay					Time (24 hr PST)	Start	17:00	End	17:33	Location	Approximately 10 m US of station																							
Station Identification	Doris TL-3					Method	Velocity-area (Mid-section)		Instrument Model	Hach FH950																									
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter		Instrument Serial #	130861001498																									
Date Monitored	10-Jun-13					Stage (m)	Start	Reading	0.6985	Time	17:01																								
Time at Site (24 hr PST)	Start Time:	16:40	End Time:	17:40			End	Reading	0.6978	Time	17:31																								
Personnel	Natasha Cowie, Emerson Belland						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q																					
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)																					
	434204	7559985				LB	5.00	0.00	0.0	0.03	0			0.000																					
Weather Conditions	Sunny, warm, light wind, air +16°C, water +5°C						4.90	0.58	0.1	0.07	0.15			0.011																					
Transducer Information							4.75	0.60	0.2	0.09	0.23			0.021																					
PT Model	PT2zx	Serial #	2922015				4.60	0.60	0.2	0.11	0.26			0.027																					
Gain	0.995	Offset	-0.346				4.40	0.61	0.2	0.12	0.29			0.035																					
Status	Active	Battery	3.0 v (full)				4.20	0.60	0.2	0.12	0.34			0.041																					
# of Records	182	Memory Free	130,523				4.00	0.60	0.2	0.12	0.41			0.049																					
Date Serviced	Spring 2012	Crest Gauges	No				3.80	0.59	0.2	0.12	0.46			0.054																					
Hydrometric Leveling Survey							3.60	0.56	0.2	0.08	0.5			0.042																					
Stn	BS	HI	FS	Elevation	Notes		3.50	0.54	0.1	0.05	0.49			0.026																					
BM 87	0.226	100.226		100.000			3.40	0.53	0.1	0.08	0.49			0.039																					
BM 88			0.278	99.948			3.20	0.53	0.2	0.11	0.51			0.054																					
WL			2.978	97.248	surveyed at 16:55		3.00	0.51	0.2	0.08	0.48			0.037																					
PT			3.626	96.600	end of PVC		2.90	0.52	0.1	0.05	0.52			0.027																					
TBM	3.295	100.206	3.315	96.911			2.80	0.51	0.2	0.05	0.47			0.024																					
PT			3.603	96.603			2.70	0.50	0.1	0.08	0.44			0.033																					
WL			2.953	97.253	surveyed at 17:02		2.50	0.49	0.2	0.10	0.41			0.040																					
BM 88			0.255	99.951			2.30	0.49	0.2	0.09	0.33			0.028																					
BM 87			0.201	100.005			2.15	0.49	0.4	0.04	0.17			0.007																					
						RB	2.14	0.00	0.0	0.01	0			0.000																					
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																															
BM 87		100.003																																	
BM 88		99.950																																	
						Total Q						0.60	100.0																						
Summary						General Notes																													
Stage (m)	97.251		Did not survey BM 89, level had been set up so that BM 89 was not visible and due to time constraints on site the survey was continued rather than restarted. Flow measurement was recorded on FH950 only, no field notes taken.																																
Discharge (m ³ /s)	0.60																																		
Pressure Transducer Reading (m)	0.699																																		
Pressure Transducer Elevation (m)	96.551																																		

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method																		
Project Name	Hope Bay					Time (24 hr PST)	Start	14:00	End	14:35	Location	Approximately 10 m US of station												
Station Identification	Doris TL-3					Method	Velocity-area (Mid-section)			Instrument Model	Hach FH950													
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498													
Date Monitored	12-Jun-13					Stage (m)	Start	Reading	0.7358	Time	14:01													
Time at Site (24 hr PST)	Start Time:	12:30	End Time:	15:26			End	Reading	0.7359	Time	14:31													
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)			Q										
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)										
	434204	7559985				LB	4.10	0.00	0.0	0.07	0			0.000										
Weather Conditions	Sunny, warm, calm, air 22°C, water 6°C						4.30	0.66	0.2	0.13	0.23			0.030										
Transducer Information							4.50	0.66	0.2	0.13	0.28			0.037										
PT Model	PT2x	Serial #	2922015				4.70	0.69	0.2	0.14	0.3			0.041										
Gain	0.995	Offset	-0.346				4.90	0.64	0.2	0.13	0.35			0.045										
Status	Active	Battery	3.0 v (full)				5.10	0.62	0.2	0.11	0.43			0.047										
# of Records	459	Memory Free	130,246				5.25	0.62	0.2	0.09	0.46			0.043										
Date Serviced	Spring 2012	Crest Gauges	No				5.40	0.61	0.2	0.09	0.51			0.047										
Hydrometric Leveling Survey						snow bank collapsed app	5.55	0.61	0.1	0.09	0.55			0.050										
Stn	BS	HI	FS	Elevation	Notes		5.70	0.61	0.2	0.09	0.52			0.048										
BM 87	0.588	100.588		100.000			5.85	0.60	0.1	0.09	0.54			0.049										
BM 88			0.643	99.945			6.00	0.59	0.2	0.09	0.55			0.049										
BM 89			0.311	100.277			6.15	0.58	0.2	0.09	0.56			0.049										
WL			3.301	97.287	surveyed at 13:05		6.30	0.55	0.1	0.08	0.56			0.046										
PT			3.930	96.658	end of PVC		6.45	0.54	0.3	0.08	0.52			0.042										
TBM	3.098	100.560	3.126	97.462			6.60	0.53	0.1	0.08	0.47			0.037										
PT			3.970	96.590			6.75	0.54	0.2	0.08	0.42			0.034										
WL			3.270	97.290	surveyed at 13:25		6.90	0.53	0.2	0.07	0.36			0.024										
BM 89			0.286	100.274			7.00	0.50	0.3	0.10	0.03			0.003										
BM 88			0.617	99.943			7.30	0.12	0.4	0.07	0			0.000										
BM 87			0.564	99.996		RB	8.10	0.00	0.8	0.19	0			0.000										
Summary						Total Q						0.72		100.0										
General Notes																								
Stage (m)	97.289				Assistant (C. Anablak) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.715 m at 13:25 PST. During flow measurement, a snow bank approximately 10 m US collapsed into the water, sending a wave downstream.																			
Discharge (m ³ /s)	0.72																							
Pressure Transducer Reading (m)	0.734																							
Pressure Transducer Elevation (m)	96.554																							

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method										
Project Name	Hope Bay					Time (24 hr PST)	Start	13:50	End	14:27	Location	Approximately 10 m US of station				
Station Identification	Doris TL-3					Method	Velocity-area (Mid-section)		Instrument Model	Hach FH950						
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter		Instrument Serial #	130861001498						
Date Monitored	13-Jun-13					Stage (m)	Start	Reading	0.7606	Time	13:51					
Time at Site (24 hr PST)	Start Time: 12:16	End Time: 14:53					End	Reading	0.7618	Time	14:31					
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q		
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)		
	434204	7559985				LB	3.60	0.00	0.0	0.04	0			0.000		
Weather Conditions	Sunny, warm, light wind, air 26°C, water 7°C					grass	4.15	0.16	0.6	0.06	-0.01			-0.001		
							4.30	0.68	0.1	0.12	0.17			0.020		
Transducer Information														2.5		
PT Model	PT2zx	Serial #	2922015					4.50	0.70	0.2	0.12	0.29		0.036	4.5	
Gain	0.995	Offset	-0.346					4.65	0.70	0.2	0.12	0.33		0.040	5.1	
Status	Active	Battery	3.0 v (full)					4.85	0.67	0.2	0.12	0.36		0.042	5.3	
# of Records	600	Memory Free		130,105				5.00	0.66	0.2	0.10	0.41		0.041	5.1	
Date Serviced	Spring 2012	Crest Gauges	No					5.15	0.64	0.2	0.10	0.5		0.048	6.0	
Hydrometric Leveling Survey								5.30	0.64	0.1	0.10	0.54		0.052	6.5	
Stn	BS	HI	FS	Elevation	Notes			5.45	0.63	0.2	0.09	0.54		0.051	6.4	
BM 87	0.548	100.548		100.000				5.60	0.62	0.1	0.09	0.51		0.047	5.9	
BM 88			0.602	99.946				5.75	0.62	0.2	0.09	0.53		0.049	6.2	
BM 89			0.271	100.277				5.90	0.61	0.2	0.09	0.54		0.049	6.2	
WL			3.224	97.324	surveyed at 13:02			6.05	0.60	0.1	0.09	0.59		0.053	6.7	
PT			3.960	96.588	end of PVC			6.20	0.59	0.3	0.09	0.59		0.052	6.5	
TBM	2.446	100.581	2.413	98.135				6.35	0.57	0.1	0.09	0.61		0.052	6.5	
PT			3.990	96.591				6.50	0.55	0.2	0.08	0.55		0.045	5.7	
WL			3.256	97.325	surveyed at 13:20			6.65	0.54	0.2	0.08	0.51		0.041	5.2	
BM 89			0.303	100.278				6.80	0.58	0.3	0.10	0.47		0.048	6.0	
BM 88			0.635	99.946				7.00	0.56	0.4	0.11	0.27		0.030	3.8	
BM 87			0.581	100.000				grass	7.20	0.15	0.2	0.05	0.01		0.001	0.1
								grass	7.70	0.11	0.5	0.06	0		0.000	0.0
								RB	8.30	0.00	0.6	0.13	0		0.000	0.0
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes											
BM 87		100.000														
BM 88		99.946														
BM 89		100.278					Total Q						0.80	100.0		
Summary							General Notes									
Stage (m)	97.325						Assistant (C. Anablak) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.735 m at 13:20 PST.									
Discharge (m ³ /s)	0.80															
Pressure Transducer Reading (m)	0.759															
Pressure Transducer Elevation (m)	96.566															

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method																													
Project Name		Hope Bay						Time (24 hr PST)	Start	13:00	End	13:34	Location	Approximately 10 m US of station																					
Station Identification		Doris TL-3						Method	Velocity-area (Mid-section)		Instrument Model	Marsh Mc Birney Flo-Mate 2000																							
Stream Name		Doris Creek						Flow Meter Type	Electromagnetic current meter		Instrument Serial #	14614																							
Date Monitored		6-Jul-13						Stage (m)	Start	Reading	0.7538	Time	13:01																						
Time at Site (24 hr PST)		Start Time:	11:30	End Time:	14:25				End	Reading	0.7547	Time	13:31																						
Personnel		Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q																				
Station Coordinates		Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%																			
		434204	7559985				LB	8.45	0.00	0.0	0.03	0			0.000	0.0																			
Weather Conditions		Sunny, warm, light wind, air 32°C, water 11°C						grass	7.90	0.10	0.5	0.04	-0.01		0.000	0.0																			
Transducer Information															0.023	2.8																			
PT Model	PT2x	Serial #	2922015					7.55	0.71	0.2	0.12	0.31			0.039	4.6																			
Gain	0.995	Offset	-0.346					7.35	0.72	0.2	0.13	0.35			0.044	5.3																			
Status	Active	Battery	2.9 v					7.20	0.72	0.1	0.11	0.33			0.036	4.3																			
# of Records	3907	Memory Free	126,798					7.05	0.69	0.2	0.10	0.39			0.040	4.9																			
Date Serviced	Spring 2012	Crest Gauges	No					6.90	0.68	0.1	0.10	0.43			0.044	5.3																			
Hydrometric Leveling Survey															0.046	5.5																			
Stn	BS	HI	FS	Elevation	Notes			6.65	0.66	0.1	0.07	0.58			0.038	4.6																			
BM 87	0.427	100.427		100.000	P			6.55	0.65	0.1	0.07	0.57			0.037	4.5																			
BM 88			0.483	99.944				6.45	0.65	0.1	0.08	0.6			0.049	5.9																			
BM 89		0.150	100.277					6.30	0.65	0.2	0.08	0.59			0.048	5.8																			
WL			3.102	97.325	surveyed at 12:10 PST			6.20	0.64	0.1	0.06	0.56			0.036	4.3																			
PT			3.823	96.604	end of PVC			6.10	0.65	0.2	0.07	0.54			0.035	4.2																			
TBM	2.277	100.412	2.292	98.135				6.00	0.62	0.1	0.06	0.54			0.033	4.0																			
PT			3.808	96.604				5.90	0.62	0.1	0.06	0.55			0.034	4.1																			
WL			3.090	97.322	surveyed at 12:27 PST			5.80	0.61	0.1	0.06	0.54			0.033	4.0																			
BM 89			0.136	100.276				5.70	0.60	0.2	0.06	0.56			0.034	4.0																			
BM 88			0.468	99.944				5.60	0.59	0.2	0.06	0.57			0.034	4.0																			
BM 87			0.415	99.997				5.50	0.58	0.1	0.06	0.56			0.032	3.9																			
								5.40	0.58	0.1	0.06	0.54			0.031	3.8																			
								5.30	0.58	0.1	0.06	0.52			0.030	3.6																			
								5.20	0.57	0.1	0.06	0.46			0.026	3.2																			
								5.10	0.57	0.1	0.07	0.39			0.028	3.3																			
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	grass	4.95	0.25	0.1	0.08	0.01				0.001	0.1																				
BM 87		99.999			grass	4.50	0.15	0.5	0.10	0				0.000	0.0																				
BM 88		99.944			RB	3.60	0.00	0.9	0.27	0				0.000	0.0																				
BM 89		100.277			Total Q									0.83	100.0																				
Summary						General Notes																													
Stage (m)	97.324			Water depth above PT (measured from end of PVC) was approx. 0.732 m at 14:21 PST. Water pumped from Tail Lake was being discharged into Doris Creek at discharge point TL-4 (above waterfall) during the station visit.																															
Discharge (m ³ /s)	0.83																																		
Pressure Transducer Reading (m)	0.754																																		
Pressure Transducer Elevation (m)	96.569																																		

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name						Time (24 hr PST)	Start	14:15	End	14:47	Location	Approximately 10 m US of station											
Station Identification						Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000												
Stream Name						Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614												
Date Monitored						Stage (m)	Start	Reading	0.7344	Time	14:11												
Time at Site (24 hr PST)							End	Reading	0.736	Time	14:51												
Personnel						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q									
Station Coordinates						Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)									
						LB	3.50	0.00	0.0	0.02	0			0.000									
Weather Conditions						grass	4.00	0.07	0.5	0.03	-0.01			0.000									
							4.30	0.68	0.3	0.15	0.07			0.011									
														1.4									
Transducer Information														0.033									
PT Model							4.45	0.70	0.2	0.11	0.31			4.1									
Gain							4.60	0.70	0.1	0.11	0.31			0.033									
Status							4.75	0.69	0.2	0.10	0.35			0.036									
# of Records							4.90	0.69	0.2	0.10	0.34			0.035									
Date Serviced							5.05	0.67	0.1	0.10	0.45			0.045									
							5.20	0.66	0.2	0.10	0.49			0.049									
Hydrometric Leveling Survey														6.2									
Stn	BS	HI	FS	Elevation	Notes		5.35	0.65	0.1	0.10	0.58			0.057									
BM 87	0.487	100.487		100.000	P		5.50	0.64	0.2	0.10	0.56			0.054									
BM 88			0.543	99.944			5.65	0.64	0.2	0.08	0.58			0.046									
BM 89			0.210	100.277			5.75	0.62	0.1	0.06	0.56			0.035									
SG			2.766	97.721	top of vertical rebar		5.85	0.62	0.1	0.06	0.56			0.035									
WL			3.184	97.303	surveyed at 13:40 PST		5.95	0.60	0.2	0.06	0.52			0.031									
PT			3.883	96.604	end of PVC		6.05	0.60	0.1	0.06	0.53			0.032									
TBM	2.277	100.414	2.350	98.137			6.15	0.60	0.1	0.06	0.51			0.031									
PT			3.811	96.603			6.25	0.59	0.1	0.06	0.55			0.032									
WL			3.112	97.302	surveyed at 13:55 PST		6.35	0.57	0.2	0.06	0.55			0.031									
SG			2.693	97.721		on rock	6.45	0.50	0.2	0.06	0.54			0.034									
BM 89			0.137	100.277			6.60	0.55	0.1	0.07	0.52			0.036									
BM 88			0.468	99.946			6.70	0.56	0.1	0.06	0.46			0.026									
BM 87			0.415	99.999			6.80	0.58	0.1	0.07	0.45			0.033									
							6.95	0.58	0.2	0.06	0.35			0.020									
							7.00	0.56	0.0	0.06	0.27			0.015									
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	grass		7.15	0.18	0.2	0.11	0			0.000									
BM 87		100.000			RB		8.20	0.00	1.1	0.09	0			0.000									
BM 88		99.945																					
BM 89		100.277			Total Q								0.79	100.0									
Summary						General Notes																	
Stage (m)						Staff gauge installed. Water depth above PT (measured from end of PVC) was approx. 0.715 m at 14:05 PST. Water pumped from Tail Lake was being discharged into Doris Creek at discharge point TL-4 (above waterfall) during the station visit.																	
Discharge (m ³ /s)																							
Pressure Transducer Reading (m)																							
Pressure Transducer Elevation (m)																							

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method																					
Project Name		Hope Bay						Time (24 hr PST)	Start	9:38	End	10:05	Location	Approximately 10 m US of station													
Station Identification		Doris TL-3						Method	Velocity-area (Mid-section)		Instrument Model	Marsh Mc Birney Flo-Mate 2000															
Stream Name		Doris Creek						Flow Meter Type	Electromagnetic current meter		Instrument Serial #	14614															
Date Monitored		15-Aug-13						Stage (m)	Start	Reading	0.4852	Time	9:41														
Time at Site (24 hr PST)		Start Time:	8:00	End Time:	14:40				End	Reading	0.4842	Time	10:01														
Personnel		Natasha Cowie, Leonard Wingnek							Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q											
Station Coordinates		Easting	Northing	Elevation				Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%										
		434204	7559985					RB	3.50	0.00	0.0	0.01	0			0.000	0.0										
Weather Conditions		Cloudy, cool, light wind, air 12°C, water 13°C						grass	3.45	0.30	0.0	0.03	0.02			0.001	0.3										
Transducer Information																											
PT Model	PT2x	Serial #	2922015						3.15	0.32	0.2	0.05	0.15			0.007	3.9										
Gain	0.995	Offset	-0.346						3.00	0.32	0.2	0.05	0.2			0.010	5.2										
Status	Active	Battery	2.9 v						2.85	0.34	0.2	0.05	0.23			0.012	6.2										
# of Records	9645	Memory Free	121,060						2.70	0.34	0.2	0.05	0.25			0.013	6.8										
Date Serviced	Spring 2012	Crest Gauges	No						2.55	0.35	0.2	0.05	0.26			0.014	7.4										
Hydrometric Leveling Survey																											
Stn	BS	HI	FS	Elevation	Notes				2.30	0.35	0.1	0.04	0.26			0.011	6.1										
BM 87	0.416	100.416		100.000	P				2.15	0.37	0.2	0.05	0.29			0.013	7.1										
BM 88			0.473	99.943					2.05	0.37	0.1	0.04	0.31			0.011	6.1										
BM 89			0.178	100.238					1.95	0.37	0.1	0.05	0.29			0.013	7.1										
SG 1			2.907	97.509	top of angled rebar				1.80	0.38	0.2	0.05	0.28			0.013	7.2										
SG 2			2.687	97.729	top of vertical rebar				1.70	0.38	0.3	0.04	0.24			0.009	4.9										
WL			3.343	97.073	8:33 PST				1.60	0.38	0.1	0.04	0.18			0.007	3.7										
PT			3.809	96.607	end of PVC				1.50	0.40	0.1	0.04	0.12			0.005	2.6										
TBM	3.285	100.374	3.327	97.089					1.40	0.40	0.1	0.05	0.09			0.004	2.4										
PT			3.767	96.607					1.25	0.41	0.3	0.06	0.08			0.005	2.7										
WL			3.300	97.074	8:50 PST				1.10	0.43	0.3	0.05	0.11			0.006	3.2										
SG 2			2.648	97.726					1.00	0.43	0.1	0.05	0.1			0.005	2.9										
SG 1			2.866	97.508					0.85	0.43	0.2	0.05	0.1			0.005	2.9										
BM 89			0.138	100.236					0.75	0.44	0.1	0.04	0.04			0.002	1.0										
BM 88			0.433	99.941				LB	0.65	0.00	0.1	0.02	0			0.000	0.0										
BM 87			0.376	99.998																							
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																							
BM 87		99.999																									
BM 88		99.942																									
BM 89		100.237													0.19	100.0											
Summary															General Notes												
Stage (m)	97.074			Water depth above PT (measured from end of PVC) was approx. 0.467 m at 12:00 PST. Water pumped from Tail Lake was being discharged into Doris Creek at discharge point TL-4 (above waterfall) during the station visit. Used imperial rod, measurements have been converted.																							
Discharge (m ³ /s)	0.19																										
Pressure Transducer Reading (m)	0.484																										
Pressure Transducer Elevation (m)	96.589																										

Appendix B-2. Stage and Discharge Measurements at Station Doris TL-3 in 2013

Site Information						Discharge Measurement - Mid-Section Method											
Project Name	Hope Bay					Time (24 hr PST)	Start	12:00	End	12:25	Location	Approximately 10 m US of station					
Station Identification	Doris TL-3					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000						
Stream Name	Doris Creek					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614						
Date Monitored	7-Sep-13					Stage (m)	Start	Reading	0.4257	Time	12:01						
Time at Site (24 hr PST)	Start Time: 10:15	End Time: 13:00					End	Reading	0.4249	Time	12:21						
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)			Q			
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%		
	434204	7559985				RB	7.00	0.00	0.0	0.01	0			0.000	0.0		
Weather Conditions	Cloudy, calm, air 4°C, water 6°C					grass	6.95	0.24	0.0	0.02	0.09			0.002	2.2		
							6.80	0.24	0.2	0.04	0.16			0.006	5.8		
Transducer Information																	
PT Model	PT2x	Serial #	2922015											0.006	6.1		
Gain	0.995	Offset	-0.346			on rock	6.50	0.18	0.2	0.03	0.19			0.005	5.1		
Status	Active	Battery	2.9 v											0.007	7.2		
# of Records	12,971	Memory Free	117,734											0.008	7.9		
Date Serviced	Spring 2012	Crest Gauges	No											0.009	8.4		
Hydrometric Leveling Survey							5.90	0.27	0.1	0.04	0.23			0.009	9.3		
Stn	BS	HI	FS	Elevation	Notes		5.75	0.27	0.2	0.04	0.25			0.010	10.1		
BM 87	0.474	100.474		100.000	P		5.60	0.30	0.2	0.04	0.25			0.010	9.4		
BM 88			0.531	99.943			5.50	0.30	0.1	0.04	0.24			0.009	9.0		
BM 89			0.243	100.231			5.35	0.32	0.2	0.05	0.22			0.011	10.4		
SG 1			2.963	97.511	top of angled rebar		5.20	0.34	0.1	0.05	0.08			0.004	4.0		
SG 2			2.743	97.731	top of vertical rebar		5.05	0.34	0.3	0.05	0.01			0.001	0.5		
WL			3.456	97.018	10:45 PST		4.90	0.35	0.1	0.05	0.01			0.001	0.5		
PT			3.863	96.611			4.75	0.37	0.2	0.05	0.01			0.001	0.5		
TBM	3.488	100.452	3.510	96.964			4.60	0.38	0.2	0.06	0			0.000	0.0		
PT			3.836	96.616		grass US	4.45	0.37	0.3	0.05	0.05			0.003	2.7		
WL			3.434	97.018	10:54 PST		4.30	0.34	0.3	0.04	0.02			0.001	0.8		
SG 2			2.721	97.731		LB	4.20	0.00	0.1	0.02	0			0.000	0.0		
SG 1			2.942	97.510													
BM 89			0.221	100.231													
BM 88			0.507	99.945													
BM 87			0.451	100.001													
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes													
BM 87		100.001															
BM 88		99.944															
BM 89		100.231					Total Q							0.10	100.0		
Summary							General Notes										
Stage (m)	97.018						Water pumped from Tail Lake was being discharged into Doris Creek at discharge point TL-4 (above waterfall) during the station visit. Used imperial rod, measurements have been converted.										
Discharge (m ³ /s)	0.10																
Pressure Transducer Reading (m)	0.427																
Pressure Transducer Elevation (m)	96.591																

Appendix B-3. Stage and Discharge Measurements at Station Roberts Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																										
Project Name	Hope Bay					Time (24 hr PST)	Start	13:00	End	13:35	Location	Approximately 80 m DS of outflow																				
Station Identification	Roberts Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Hach FH950																					
Stream Name	Roberts Lake Outflow					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498																					
Date Monitored	7-Jun-13					Stage (m)	Start	Reading	0.6263	Time	13:00																					
Time at Site (24 hr PST)	Start Time:	8:45	End Time:	13:45			End	Reading	0.6285	Time	13:30																					
Personnel	Natasha Cowie, Emerson Belland						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q																	
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%																	
	435310	7562560				RB	0.60	0.00	0.0	0.03	0			0.000	0.0																	
Weather Conditions	Cold, light rain, air temp 4°C, water temp 2°C					grass	1.30	0.08	0.7	0.03	0.01			0.000	0.1																	
Transducer Information							1.45	0.25	0.2	0.06	0.15			0.008	1.4																	
PT Model	PT2x	Serial #	2922019				1.75	0.24	0.3	0.07	0.36			0.024	3.8																	
Gain	1.002	Offset	0.007				2.00	0.24	0.3	0.07	0.29			0.019	3.1																	
Status	Active	Battery	3.1v (full)				2.30	0.21	0.3	0.06	0.24			0.015	2.4																	
# of Records	0	Memory Free	130,705				2.60	0.19	0.3	0.06	0.2			0.011	1.8																	
Date Serviced	Winter 2011?		Crest Gauges		No		2.90	0.24	0.3	0.06	0.34			0.020	3.3																	
Hydrometric Leveling Survey							3.10	0.26	0.2	0.05	0.39			0.020	3.3																	
Stn	BS	HI	FS	Elevation	Notes		3.30	0.28	0.2	0.06	0.42			0.024	3.8																	
BM 49	1.252	101.252		100.000		on rock	3.50	0.26	0.2	0.07	0.42			0.027	4.4																	
BM 12			1.190	100.062			3.80	0.40	0.3	0.10	0.33			0.033	5.3																	
BM 64			1.415	99.837			4.00	0.44	0.2	0.09	0.4			0.035	5.7																	
BM 50			1.154	100.098			4.20	0.43	0.2	0.09	0.48			0.041	6.6																	
PT		2.596	98.656	end of PVC			4.40	0.45	0.2	0.09	0.53			0.048	7.7																	
WL		2.006	99.246				4.60	0.45	0.2	0.09	0.37			0.033	5.4																	
TBM	2.042	101.314	1.980	99.272			4.80	0.50	0.2	0.10	0.36			0.036	5.8																	
WL		2.068	99.246	surveyed at 12:26 PST			5.00	0.50	0.2	0.10	0.38			0.038	6.1																	
PT		2.655	98.659				5.20	0.52	0.2	0.10	0.36			0.037	6.0																	
BM 50		1.213	100.101				5.40	0.52	0.2	0.10	0.44			0.046	7.4																	
BM 64		1.475	99.839				5.60	0.52	0.2	0.10	0.44			0.046	7.4																	
BM 49		1.313	100.001				5.80	0.48	0.2	0.10	0.46			0.044	7.1																	
BM 12		1.250	100.064				6.00	0.40	0.2	0.10	0.14			0.014	2.3																	
						LB	6.30	0.00	0.3	0.06	0			0.000	0.0																	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes																											
BM 49		100.001																														
BM 50		100.100																														
BM 64		99.838																														
BM 12		100.063				Total Q						0.62	100.0																			
Summary						General Notes																										
Stage (m)	99.246					Installed station in same location as 2010-2012. Had to break surface ice in order to place PT, and part of conduit resting on solid ice (frozen to lake bottom) near the shore. BM 65 was removed (loose bolt in bedrock).																										
Discharge (m ³ /s)	0.62																															
Pressure Transducer Reading (m)	0.626																															
Pressure Transducer Elevation (m)	98.620																															

Appendix B-3. Stage and Discharge Measurements at Station Roberts Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																		
Project Name	Hope Bay					Time (24 hr PST)	Start	15:15	End	16:00	Location	Approximately 80 m DS of outflow												
Station Identification	Roberts Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Hach FH950													
Stream Name	Roberts Lake Outflow					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	130861001498													
Date Monitored	11-Jun-13					Stage (m)	Start	Reading	0.7331	Time	15:20													
Time at Site (24 hr PST)	Start Time:	12:40	End Time:	16:08			End	Reading	0.733	Time	16:00													
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q									
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%									
	435310	7562560				RB	0.50	0.00	0.0	0.03	0			0.000	0.0									
Weather Conditions	Sunny, warm, light wind, air temp 16°C, water temp 3°C					grass	1.10	0.10	0.6	0.05	0.02			0.001	0.1									
	Transducer Information					grass	1.40	0.16	0.3	0.05	0.05			0.002	0.2									
PT Model	PT2x	Serial #	2922019			grass	1.70	0.23	0.3	0.09	0.08			0.007	0.5									
Gain	1.002	Offset	0.007				2.20	0.37	0.5	0.13	0.45			0.058	3.7									
Status	Active	Battery	3.1v (full)				2.40	0.39	0.2	0.08	0.51			0.040	2.5									
# of Records	593	Memory Free	130,112				2.60	0.40	0.2	0.09	0.45			0.041	2.6									
Date Serviced	Winter 2011?	Crest Gauges	No				2.85	0.38	0.3	0.10	0.3			0.029	1.8									
Hydrometric Leveling Survey							3.10	0.37	0.3	0.09	0.4			0.037	2.4									
Stn	BS	HI	FS	Elevation	Notes		3.35	0.40	0.3	0.10	0.29			0.029	1.8									
BM 49	1.199	101.199		100.000			3.60	0.44	0.3	0.12	0.38			0.046	2.9									
BM 12			1.146	100.053			3.90	0.49	0.3	0.15	0.53			0.078	5.0									
BM 64			1.361	99.838			4.20	0.54	0.3	0.14	0.57			0.077	4.9									
BM 50			1.100	100.099			4.40	0.55	0.2	0.11	0.67			0.074	4.7									
WL			1.855	99.344	surveyed at 14:00		4.60	0.62	0.2	0.12	0.73			0.091	5.8									
PT			2.500	98.699	end of PVC		4.80	0.62	0.2	0.12	0.85			0.105	6.7									
TBM	1.377	101.265	1.311	99.888			5.00	0.60	0.2	0.12	0.87			0.104	6.6									
WL			1.922	99.343	surveyed at 14:15		5.20	0.65	0.2	0.13	0.86			0.112	7.1									
PT			2.610	98.655			5.40	0.64	0.2	0.13	0.9			0.115	7.3									
BM 50			1.165	100.100			5.60	0.69	0.2	0.14	0.66			0.091	5.8									
BM 64			1.426	99.839			5.80	0.70	0.2	0.14	0.78			0.109	6.9									
BM 49			1.265	100.000			6.00	0.70	0.2	0.14	0.8			0.112	7.1									
BM 12			1.208	100.057			6.20	0.69	0.2	0.14	0.76			0.105	6.7									
							6.40	0.66	0.2	0.13	0.67			0.088	5.6									
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	grass		6.60	0.64	0.2	0.16	0.08			0.013	0.8									
BM 49		100.000					6.90	0.23	0.3	0.07	0.1			0.007	0.4									
BM 50		100.100					7.20	0.14	0.3	0.04	0.04			0.001	0.1									
BM 64		99.839				LB	7.40	0.00	0.2	0.01	0			0.000	0.0									
BM 12		100.055				Total Q								1.57	100.0									
Summary						General Notes																		
Stage (m)	99.344					Assistant (C. Anablak) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.700 m at 14:15 PST. Ice frozen to bed near shore had melted enough to be broken and pushed out from under conduit. The PT did not appear to have been disturbed by ice movement. Discharge measurements in field notes do not match FH950 file. The first six measurements appear to have been inadvertently deleted from the FH950 file.																		
Discharge (m ³ /s)	1.57																							
Pressure Transducer Reading (m)	0.732																							
Pressure Transducer Elevation (m)	98.611																							

Appendix B-3. Stage and Discharge Measurements at Station Roberts Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name	Hope Bay					Time (24 hr PST)	Start	11:33	End	12:00	Location	Approximately 80 m DS of outflow											
Station Identification	Roberts Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000												
Stream Name	Roberts Lake Outflow					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614												
Date Monitored	7-Jul-13					Stage (m)	Start	Reading	0.6567	Time	11:30												
Time at Site (24 hr PST)	Start Time:	8:50	End Time:	12:30			End	Reading	0.6528	Time	12:00												
Personnel	Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q								
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%								
	435310	7562560				RB	6.40	0.00	0.0	0.03	0			0.000	0.0								
Weather Conditions	Cloudy, warm, calm, air temp 12°C, water temp 6°C					grass	6.00	0.14	-0.4	0.05	0.01			0.000	0.1								
	Transducer Information					grass	5.70	0.24	-0.3	0.07	0.04			0.003	0.3								
PT Model	PT2x	Serial #	2922019				5.45	0.24	-0.3	0.06	0.35			0.021	2.6								
Gain	1.002	Offset	0.007				5.20	0.25	-0.3	0.06	0.37			0.023	2.8								
Status	Active	Battery	3.0 v				4.95	0.24	-0.3	0.06	0.3			0.018	2.2								
# of Records	4322	Memory Free	126,383				4.70	0.21	-0.3	0.05	0.31			0.016	2.0								
Date Serviced	Winter 2011?	Crest Gauges	No				4.45	0.23	-0.3	0.06	0.25			0.014	1.8								
Hydrometric Leveling Survey							4.20	0.30	-0.3	0.08	0.3			0.023	2.8								
Stn	BS	HI	FS	Elevation	Notes		3.95	0.32	-0.3	0.08	0.37			0.030	3.6								
BM 49	1.193	101.193		100.000	P		3.70	0.33	-0.3	0.07	0.37			0.027	3.4								
BM 12			1.135	100.058			3.50	0.35	-0.2	0.07	0.41			0.029	3.5								
BM 64			1.376	99.817			3.30	0.38	-0.2	0.08	0.57			0.043	5.3								
BM 50			1.117	100.076			3.10	0.40	-0.2	0.08	0.59			0.047	5.8								
WL			1.975	99.218	surveyed at 9:15 PST		2.90	0.42	-0.2	0.08	0.62			0.052	6.4								
PT			2.600	98.593	end of PVC		2.70	0.46	-0.2	0.09	0.69			0.063	7.8								
TBM	1.964	101.222	1.935	99.258			2.50	0.48	-0.2	0.10	0.66			0.063	7.8								
WL			2.005	99.217	surveyed at 9:40 PST		2.30	0.48	-0.2	0.10	0.61			0.059	7.2								
PT			2.628	98.594			2.10	0.49	-0.2	0.10	0.45			0.044	5.4								
BM 50			1.147	100.075			1.90	0.51	-0.2	0.10	0.62			0.063	7.8								
BM 64			1.405	99.817			1.70	0.52	-0.2	0.10	0.58			0.060	7.4								
BM 12			1.164	100.058			1.50	0.51	-0.2	0.10	0.48			0.049	6.0								
BM 49			1.223	99.999			1.30	0.50	-0.2	0.10	0.48			0.048	5.9								
						grass	1.10	0.30	-0.2	0.06	0.26			0.016	1.9								
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			0.90	0.08	-0.2	0.01	-0.01			0.000	0.0								
BM 49		100.000				LB	0.75	0.00	-0.2	0.01	0			0.000	0.0								
BM 50		100.076																					
BM 64		99.817																					
BM 12		100.058				Total Q								0.81	100.0								
Summary						General Notes																	
Stage (m)	99.218																						
Discharge (m ³ /s)	0.81																						
Pressure Transducer Reading (m)	0.656																						
Pressure Transducer Elevation (m)	98.562																						

Appendix B-3. Stage and Discharge Measurements at Station Roberts Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name	Hope Bay					Time (24 hr PST)	Start	15:38	End	16:14	Location	Approximately 80 m DS of outflow											
Station Identification	Roberts Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000												
Stream Name	Roberts Lake Outflow					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614												
Date Monitored	16-Aug-13					Stage (m)	Start	Reading	0.5491	Time	15:40												
Time at Site (24 hr PST)	Start Time:	13:40	End Time:	17:00			End	Reading	0.5511	Time	16:10												
Personnel	Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)			Q									
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)									
	435310	7562560				RB	1.20	0.00	0.0	0.01	0			0.000									
Weather Conditions	Cloudy, cool, light wind, air 12°C, water 12°C					grass	1.40	0.12	0.2	0.03	0.1			0.003									
							1.65	0.14	0.3	0.03	0.25			0.008									
														3.9									
Transducer Information														0.005									
PT Model	PT2x	Serial #	2922019											2.7									
Gain	1.002	Offset	0.007											0.004									
Status	Active	Battery	2.9 v											1.9									
# of Records	10,108	Memory Free	120,597											0.003									
Date Serviced	Winter 2011?	Crest Gauges	No											0.004									
Hydrometric Leveling Survey							2.90	0.14	0.2	0.03	0.18			0.005									
Stn	BS	HI	FS	Elevation	Notes		3.10	0.15	0.2	0.03	0.17			0.005									
BM 49	1.189	101.189		100.000	P		3.30	0.17	0.2	0.03	0.18			0.006									
BM 64			1.400	99.789			3.50	0.20	0.2	0.04	0.17			0.007									
BM 50			1.132	100.057			3.70	0.21	0.2	0.04	0.19			0.008									
BM 12			1.130	100.059			3.90	0.23	0.2	0.05	0.21			0.010									
WL			2.137	99.052	14:36 PST		4.10	0.26	0.2	0.05	0.22			0.011									
PT			2.655	98.534	end of PVC		4.30	0.27	0.2	0.05	0.25			0.014									
TBM	1.148	101.120	1.217	99.972			4.50	0.30	0.2	0.06	0.13			0.008									
PT			2.587	98.533			4.70	0.30	0.2	0.06	0.16			0.010									
WL			2.069	99.051	14:54 PST		4.90	0.32	0.2	0.06	0.19			0.012									
BM 12			1.062	100.058			5.10	0.34	0.2	0.07	0.26			0.017									
BM 50			1.064	100.056			5.30	0.34	0.2	0.06	0.22			0.013									
BM 64			1.332	99.788			5.45	0.35	0.2	0.04	0.25			0.011									
BM 49			1.121	99.999			5.55	0.35	0.1	0.04	0.28			0.010									
							5.65	0.35	0.1	0.04	0.3			0.011									
														5.3									
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			5.75	0.34	0.1	0.03	0.25			0.008									
BM 49		100.000				grass	5.85	0.34	0.1	0.04	0.06			0.003									
BM 50		100.057				LB	6.00	0	0.2	0.03	0			0.000									
BM 64		99.789																					
BM 12		100.059				Total Q								0.20									
Summary						General Notes																	
Stage (m)	99.052					Used imperial rod, measurements have been converted.																	
Discharge (m ³ /s)	0.20																						
Pressure Transducer Reading (m)	0.551																						
Pressure Transducer Elevation (m)	98.500																						

Appendix B-3. Stage and Discharge Measurements at Station Roberts Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																			
Project Name	Hope Bay					Time (24 hr PST)	Start	12:22	End	13:00	Location	Approximately 80 m DS of outflow													
Station Identification	Roberts Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000														
Stream Name	Roberts Lake Outflow					Flow Meter Type	Electromagnetic current meter			Instrument Serial #	14614														
Date Monitored	8-Sep-13					Stage (m)	Start	Reading	0.5353	Time	12:20														
Time at Site (24 hr PST)	Start Time:	11:00	End Time:	14:20			End	Reading	0.5272	Time	13:00														
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q										
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%										
	435310	7562560				RB	5.50	0.00	0.0	0.02	0			0.000	0.0										
Weather Conditions	Cloudy, cold, light wind					grass	5.10	0.09	-0.4	0.03	0			0.000	0.0										
Transducer Information							4.90	0.09	-0.2	0.02	0.13			0.002	2.2										
PT Model	PT2x	Serial #	2922019				4.70	0.09	-0.2	0.02	0.18			0.003	3.0										
Gain	1.002	Offset	0.007				4.50	0.08	-0.2	0.02	0.15			0.002	2.1										
Status	Active	Battery	2.9 v				4.30	0.08	-0.2	0.02	0.12			0.002	1.7										
# of Records	13,402	Memory Free	117,303				4.10	0.06	-0.2	0.01	-0.03			0.000	-0.3										
Date Serviced	Winter 2011?	Crest Gauges	No				3.90	0.06	-0.2	0.01	0.07			0.001	0.8										
Hydrometric Leveling Survey							3.70	0.09	-0.2	0.02	0.07			0.001	1.2										
Stn	BS	HI	FS	Elevation	Notes		3.50	0.11	-0.2	0.02	0.09			0.002	1.8										
BM 49	1.175	101.175		100.000	P		3.30	0.12	-0.2	0.02	0.1			0.002	2.2										
BM 12			1.115	100.060			3.10	0.15	-0.2	0.03	0.11			0.003	3.1										
BM 64			1.392	99.783			2.90	0.17	-0.2	0.03	0.1			0.003	3.1										
BM 50			1.120	100.055			2.70	0.20	-0.2	0.04	0.13			0.005	4.7										
WL			2.157	99.018	11:43 PST		2.50	0.20	-0.2	0.04	0.13			0.005	4.7										
PT			2.662	98.513			2.30	0.23	-0.2	0.05	0.16			0.007	6.7										
TBM	2.167	101.216	2.126	99.049			2.10	0.26	-0.2	0.05	0.17			0.009	8.1										
PT			2.703	98.513			1.90	0.27	-0.2	0.05	0.09			0.005	4.5										
WL			2.199	99.017	12:00 PST		1.70	0.27	-0.2	0.05	0.08			0.004	4.0										
BM 50			1.162	100.054			1.50	0.29	-0.2	0.06	0.11			0.006	5.8										
BM 64			1.434	99.782			1.30	0.29	-0.2	0.04	0.19			0.008	7.6										
BM 12			1.157	100.059			1.20	0.30	-0.1	0.03	0.17			0.005	4.7										
BM 49			1.216	100.000			1.10	0.30	-0.1	0.03	0.15			0.005	4.2										
							1.00	0.30	-0.1	0.03	0.17			0.005	4.7										
							0.90	0.32	-0.1	0.03	0.19			0.006	5.6										
							0.80	0.30	-0.1	0.03	0.21			0.006	5.9										
							0.70	0.30	-0.1	0.03	0.23			0.007	6.4										
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes	grass	0.60	0.30	-0.1	0.03	0.03			0.001	0.8										
BM 49		100.000				grass	0.50	0.27	-0.1	0.03	0.03			0.001	0.8										
BM 50		100.055				LB	0.40	0	-0.1	0.01	0			0.000	0.0										
BM 64		99.783																							
BM 12		100.060				Total Q								0.11	100.0										
Summary						General Notes																			
Stage (m)	99.018					Used imperial rod, measurements have been converted.																			
Discharge (m ³ /s)	0.11																								
Pressure Transducer Reading (m)	0.534																								
Pressure Transducer Elevation (m)	98.483																								

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method												
Project Name	Hope Bay					Time (24 hr PST)	Start	15:55	End	16:08	Location	Approximately 500 m DS of station						
Station Identification	Windy Hydro					Method	Velocity-area (Mid-section)			Instrument Model	FH950							
Stream Name	Windy Lake Outflow					Flow Meter Type	Electromagnetic flow meter			Instrument Serial #	130861001498							
Date Monitored	7-Jun-13					Stage (m)	Start	Reading	0.4131	Time	15:55							
Time at Site (24 hr PST)	Start Time:	14:00	End Time:	16:30			End	Reading	0.4156	Time	16:05							
Personnel	Natasha Cowie, Emerson Belland						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q				
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)				
	431479	7555091				LB	0.55	0.00	0.0	0.01	0			0.000				
Weather Conditions	Cloudy, cool, windy, 4°C							0.60	0.22	0.0	0.02	0.09		0.001				
Transducer Information								0.70	0.22	0.1	0.02	0.29		0.006				
PT Model	PT2x	Serial #	2922016					0.80	0.21	0.1	0.02	0.42		0.009				
Gain	1.01	Offset	-0.017					0.90	0.21	0.1	0.02	0.50		0.011				
Status	Active	Battery	3.1 v (full)					1.00	0.22	0.1	0.02	0.61		0.013				
# of Records	279	Memory Free	130,426					1.10	0.22	0.1	0.02	0.67		0.015				
Date Serviced	Spring 2012	Crest Gauges	No					1.20	0.19	0.1	0.02	0.53		0.010				
Hydrometric Leveling Survey								1.30	0.14	0.1	0.02	0.45		0.008				
Stn	BS	HI	FS	Elevation	Notes			1.45	0.09	0.2	0.01	0.14		0.001				
BM 24	0.527	100.527		100.000		RB		1.50	0.00	0.1	0.00	0		0.000				
BM 23			0.872	99.655														
TP 1	1.223	98.355	3.395	97.132	turning point													
WL			3.385	94.970														
BM 45			2.669	95.686														
PT			3.761	94.594	end of PVC													
TBM	3.842	98.507	3.690	94.665														
PT			3.915	94.592														
BM 45			2.820	95.687														
WL			3.538	94.969	surveyed at 15:05													
TP 2	3.390	100.525	1.372	97.135	turning point													
BM 24			0.522	100.003														
BM 23			0.868	99.657														
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes													
BM 24		100.002																
BM 23		99.656																
BM 45		95.687				Total Q						0.080	100.0					
Summary							General Notes											
Stage (m)	94.970						Station installed on June 6 2013 in same location as 2010-2012. Water level survey was not completed on June 6 due to approaching thunderstorm. Ice on lake, although some melt around shorelines and outlet is clear. BM 44 was permanently removed because it was located on a slumping section of shoreline. BM 23 and BM 24 (primary) are in bedrock, across the field (approx. 200 m) from the station. BM 45 is less reliable because it is in a boulder along the lakeshore.											
Discharge (m ³ /s)	0.08																	
Pressure Transducer Reading (m)	0.407																	
Pressure Transducer Elevation (m)	94.562																	

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																	
Project Name	Hope Bay					Time (24 hr PST)	Start	10:10	End	10:40	Location	Approximately 500 m DS of station											
Station Identification	Windy Hydro					Method	Velocity-area (Mid-section)			Instrument Model	FH950												
Stream Name	Windy Lake Outflow					Flow Meter Type	Electromagnetic flow meter			Instrument Serial #	130861001498												
Date Monitored	12-Jun-13					Stage (m)	Start	Reading	0.4356	Time	10:05												
Time at Site (24 hr PST)	Start Time:	7:20	End Time:	12:04			End	Reading	0.4359	Time	10:45												
Personnel	Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)			Q									
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)									
	431481	7555089				RB	1.30	0.00	0.0	0.00	0			0.000									
Weather Conditions	Sunny, clear, air temp 18°C, water temp 5°C					grass	1.25	0.15	-0.1	0.01	0.25			0.003									
						grass	1.15	0.16	-0.1	0.01	0.48			0.006									
Transducer Information														4.7									
PT Model	PT2x	Serial #	2922016			grass	1.10	0.25	-0.05	0.01	0.39			0.005									
Gain	1.01	Offset	-0.017				1.05	0.28	-0.1	0.01	0.45			0.006									
Status	Active	Battery	3.0 v				1.00	0.29	-0.1	0.01	0.59			7.0									
# of Records	973	Memory Free	129,732				0.95	0.31	-0.1	0.02	0.64			0.009									
Date Serviced	Spring 2012	Crest Gauges	No				0.90	0.32	-0.05	0.02	0.67			0.010									
Hydrometric Leveling Survey							0.85	0.32	-0.1	0.02	0.67			0.011									
Stn	BS	HI	FS	Elevation	Notes		0.80	0.32	0.0	0.02	0.64			0.010									
BM 24	0.563	100.563		100.000			0.75	0.30	-0.1	0.02	0.57			0.009									
BM 23			0.907	99.656			0.70	0.28	-0.1	0.01	0.53			0.007									
TP 1	1.161	98.274	3.450	97.113	turning point		0.65	0.29	0.0	0.01	0.52			0.008									
WL			3.290	94.984	surveyed at 8:13		0.60	0.29	-0.1	0.01	0.49			0.007									
BM 45			2.601	95.673			0.55	0.29	0.0	0.01	0.44			0.006									
PT			3.700	94.574	end of PVC		0.50	0.28	-0.1	0.01	0.34			0.005									
TBM	1.875	98.234	1.915	96.359			0.45	0.28	-0.1	0.01	0.32			0.004									
PT			3.660	94.574			0.40	0.28	-0.1	0.01	0.29			0.004									
BM 45			2.562	95.672			0.35	0.27	-0.1	0.01	0.15			0.002									
WL			3.252	94.982	surveyed at 8:28	LB	0.30	0.00	-0.1	0.01	0			0.000									
TP 2	1.681	98.796	1.119	97.115	turning point																		
TP 3	2.647	100.518	0.925	97.871	turning point																		
BM 23			0.862	99.656																			
BM 24			0.520	99.998																			
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																			
BM 24		99.999																					
BM 23		99.656																					
BM 45		95.673				Total Q						0.12		100.0									
Summary						General Notes																	
Stage (m)	94.983					Assistant (C. Anablak) took shots on PT because she did not have waders and could not enter the water. Water depth above PT (measured from end of PVC) was 0.412 m at 8:30 PST. Level was difficult to focus on long shots due to damage sustained by a fall onto bedrock on June 8, so a third turning point was added to the survey to reduce the distance of the shots.																	
Discharge (m ³ /s)	0.12																						
Pressure Transducer Reading (m)	0.435																						
Pressure Transducer Elevation (m)	94.548																						

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																						
Project Name		Hope Bay						Time (24 hr PST)	Start	15:19	End	15:42	Location	Approximately 500 m DS of station														
Station Identification		Windy Hydro						Method	Velocity-area (Mid-section)		Instrument Model	Marsh Mc Birney Flo-Mate 2000																
Stream Name		Windy Lake Outflow						Flow Meter Type	Electromagnetic flow meter		Instrument Serial #	14614																
Date Monitored		7-Jul-13						Stage (m)	Start	Reading	0.4638	Time	14:05															
Time at Site (24 hr PST)		Start Time:	13:00	End Time:	15:50				End	Reading	0.4588	Time	14:25															
Personnel		Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q													
Station Coordinates		Easting	Northing	Elevation				Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%											
		431481	7555089					RB	0.65	0.00	0.0	0.01	0			0.000	0.0											
Weather Conditions		Partly cloudy, light wind, warm, air 17°C, water 8°C							0.70	0.27	0.0	0.01	0.27			0.004	3.5											
Transducer Information																0.005	4.6											
PT Model	PT2x	Serial #	2922016						0.80	0.27	0.1	0.01	0.50			0.007	6.5											
Gain	1.01	Offset	-0.017						0.85	0.27	0.0	0.01	0.58			0.008	7.6											
Status	Active	Battery	3.0 v						0.90	0.27	0.1	0.01	0.62			0.008	8.1											
# of Records	4593	Memory Free	126,112						0.95	0.27	0.0	0.01	0.60			0.008	7.9											
Date Serviced	Spring 2012	Crest Gauges	No						1.00	0.27	0.1	0.01	0.59			0.008	7.7											
Hydrometric Leveling Survey																0.007	7.1											
Stn	BS	HI	FS	Elevation	Notes				1.10	0.26	0.1	0.01	0.53			0.007	6.7											
BM 24	0.756	100.756		100.000					1.15	0.26	0.0	0.01	0.53			0.007	6.7											
BM 23			1.099	99.657					1.20	0.24	0.1	0.01	0.49			0.006	5.7											
TP 1	1.142	98.211	3.687	97.069	turning point				1.25	0.25	0.1	0.01	0.44			0.006	5.3											
WL			3.203	95.008	surveyed at 13:52 PST				1.30	0.25	0.1	0.01	0.40			0.005	4.9											
BM 45			2.571	95.640					1.35	0.25	0.1	0.01	0.42			0.005	5.1											
PT			3.637	94.574	end of PVC				1.40	0.23	0.0	0.01	0.38			0.004	4.2											
TBM	1.314	98.179	1.346	96.865					1.45	0.23	0.1	0.01	0.31			0.004	3.5											
PT			3.603	94.576					1.50	0.22	0.1	0.01	0.27			0.003	2.9											
BM 45			2.539	95.640					1.55	0.21	0.1	0.01	0.20			0.002	2.0											
WL			3.171	95.008	surveyed at 14:04 PST	LB			1.60	0.00	0.1	0.01	0			0.000	0.0											
TP 2	3.510	100.579	1.110	97.069	turning point																							
BM 23			0.923	99.656																								
BM 24			0.577	100.002																								
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes																								
BM 24		100.001																										
BM 23		99.657																										
BM 45		95.640						Total Q							0.10	100.0												
Summary															General Notes													
Stage (m)	95.008				Data download was completed prior to discharge measurement due to the distance between station and flow measurement location, so stage readings are not from the same time period as the measurement.																							
Discharge (m ³ /s)	0.10																											
Pressure Transducer Reading (m)	0.462																											
Pressure Transducer Elevation (m)	94.546																											

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method											
Project Name	Hope Bay					Time (24 hr PST)	Start	10:50	End	11:10	Location	Approximately 500 m DS of station					
Station Identification	Windy Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000						
Stream Name	Windy Lake Outflow					Flow Meter Type	Electromagnetic flow meter			Instrument Serial #	14614						
Date Monitored	17-Aug-13					Stage (m)	Start	Reading	0.4126	Time	10:45						
Time at Site (24 hr PST)	Start Time:	8:30	End Time:	12:45			End	Reading	0.4226	Time	11:05						
Personnel	Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)			Q	% of Total Q		
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%		
	431481	7555089				RB	0.50	0.00	0.0	0.00	0			0.000	0.0		
Weather Conditions	Cool, cloudy, windy, air 10°C						0.55	0.18	0.1	0.01	0.11			0.001	2.6		
Transducer Information							0.60	0.18	0.0	0.01	0.28			0.003	6.5		
PT Model	PT2x	Serial #	2922016				0.65	0.18	0.1	0.01	0.36			0.003	8.4		
Gain	1.01	Offset	-0.017				0.70	0.18	0.0	0.01	0.38			0.003	8.9		
Status	Active	Battery					0.75	0.18	0.1	0.01	0.36			0.003	8.4		
# of Records	Memory Free						0.80	0.18	0.1	0.01	0.35			0.003	8.2		
Date Serviced	Spring 2012	Crest Gauges	No				0.85	0.18	0.0	0.01	0.33			0.003	7.7		
Hydrometric Leveling Survey							0.90	0.17	0.1	0.01	0.32			0.003	6.8		
Stn	BS	HI	FS	Elevation	Notes		0.95	0.17	0.0	0.01	0.3			0.003	6.4		
BM 24	0.549	100.549		100.000	P		1.00	0.17	0.1	0.01	0.31			0.003	6.6		
BM 23			0.895	99.654			1.05	0.17	0.1	0.01	0.28			0.002	6.0		
TP 1	1.205	98.251	3.503	97.046	turning point		1.10	0.15	0.1	0.01	0.24			0.002	4.7		
WL			3.305	94.946	9:24 PST		1.15	0.15	0.0	0.01	0.23			0.002	4.5		
BM 45			2.677	95.574			1.20	0.15	0.1	0.01	0.22			0.002	4.3		
PT			3.690	94.561	end of PVC		1.25	0.15	0.1	0.01	0.21			0.002	4.1		
TBM	2.148	98.238	2.161	96.090			1.30	0.15	0.1	0.01	0.18			0.001	3.5		
BM 45			2.665	95.573			1.35	0.12	0.1	0.01	0.11			0.001	1.7		
PT			3.669	94.569			1.40	0.12	0.0	0.01	0.06			0.000	0.9		
WL			3.293	94.945	9:50 PST	LB	1.45	0.00	0.1	0.00	0			0.000	0.0		
TP 2	3.447	100.497	1.188	97.050	turning point												
BM 23			0.836	99.661													
BM 24			0.493	100.004													
BM#		Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes											
BM 24			100.002														
BM 23			99.658														
BM 45			95.574				Total Q						0.04	100.0			
Summary							General Notes										
Stage (m)	94.946						Strong wind, choppy waves, water level fluctuating 8-10 cms during survey. Used imperial rod, measurements have been converted. Data download not completed on this site visit because site was departed quickly; field crew had been trying to access Roberts Hydro earlier but were unable to due to bear presence in the area. Field crew was also trying to coordinate work at Roberts with aquatics in order to increase the human presence in the area for safety concerns. When bears left Roberts and opportunity arose to work at the site, field crew quickly departed Windy for Roberts.										
Discharge (m ³ /s)	0.04																
Pressure Transducer Reading (m)	0.409																
Pressure Transducer Elevation (m)	94.536																

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																										
Project Name	Hope Bay					Time (24 hr PST)	Start	10:14	End	10:37	Location	Approximately 500 m DS of station																				
Station Identification	Windy Hydro					Method	Velocity-area (Mid-section)			Instrument Model	Marsh Mc Birney Flo-Mate 2000																					
Stream Name	Windy Lake Outflow					Flow Meter Type	Electromagnetic flow meter			Instrument Serial #	14614																					
Date Monitored	18-Aug-13					Stage (m)	Start	Reading	0.4045	Time	10:15																					
Time at Site (24 hr PST)	Start Time:	7:45	End Time:	14:45			End	Reading	0.4145	Time	10:35																					
Personnel	Natasha Cowie, Leonard Wingnek						Station	Depth	Distance	Area	Velocity (m/s)			Q																		
Station Coordinates	Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)																		
	431481	7555089				RB	0.70	0.00	0.0	0.00	0			0.000																		
Weather Conditions	Cool, cloudy, windy, air 12°C, water 12°C					grass	0.75	0.17	0.1	0.01	0.02			0.000																		
							0.80	0.17	0.1	0.01	0.16			0.001																		
Transducer Information														3.9																		
PT Model	PT2x	Serial #	2922016											0.003																		
Gain	1.01	Offset	-0.017											8.1																		
Status	Active	Battery	2.9 v											9.9																		
# of Records	10,622	Memory Free	120,083											9.1																		
Date Serviced	Spring 2012	Crest Gauges	No											7.6																		
Hydrometric Leveling Survey							1.10	0.17	0.1	0.01	0.31			0.003																		
Stn	BS	HI	FS	Elevation	Notes		1.15	0.17	0.0	0.01	0.30			0.003																		
BM 24	0.637	100.637		100.000	P		1.20	0.17	0.1	0.01	0.29			0.002																		
BM 23			0.981	99.656			1.25	0.15	0.1	0.01	0.24			5.4																		
TP 1	1.265	98.311	3.591	97.046	turning point		1.30	0.15	0.1	0.01	0.24			0.002																		
BM 45			2.742	95.569			1.35	0.15	0.1	0.01	0.24			5.4																		
WL			3.371	94.940	8:21 PST		1.40	0.15	0.0	0.01	0.22			0.002																		
PT			3.746	94.565	end of PVC		1.45	0.15	0.1	0.01	0.18			4.0																		
TBM	1.705	98.194	1.822	96.489			1.50	0.14	0.1	0.01	0.15			0.001																		
PT			3.627	94.567			1.55	0.12	0.1	0.01	0.08			0.000																		
WL			3.260	94.934	8:38 PST	LB	1.60	0.00	0.1	0.00	0			0.000																		
BM 45			2.624	95.570																												
TP 2	3.690	100.736	1.148	97.046	turning point																											
BM 23			1.080	99.656																												
BM 24			0.736	100.000																												
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes																											
BM 24		100.000																														
BM 23		99.656																														
BM 45		95.570				Total Q						0.03	100.0																			
Summary						General Notes																										
Stage (m)	94.937					Water surface calm, but water level slowly rising and falling by about 25 mm during the survey. Possible seiche effect following strong winds the previous day. Used imperial rod, measurements have been converted.																										
Discharge (m ³ /s)	0.03																															
Pressure Transducer Reading (m)	0.411																															
Pressure Transducer Elevation (m)	94.526																															

Appendix B-4. Stage and Discharge Measurements at Station Windy Hydro in 2013

Site Information						Discharge Measurement - Mid-Section Method																										
Project Name		Hope Bay						Time (24 hr PST)	Start	8:10	End	8:36	Location	Approximately 500 m DS of station																		
Station Identification		Windy Hydro						Method	Velocity-area (Mid-section)		Instrument Model	Marsh Mc Birney Flo-Mate 2000																				
Stream Name		Windy Lake Outflow						Flow Meter Type	Electromagnetic flow meter		Instrument Serial #	14614																				
Date Monitored		8-Sep-13						Stage (m)	Start	Reading	0.3858	Time	8:05																			
Time at Site (24 hr PST)		Start Time:	7:35	End Time:	9:45				End	Reading	0.3804	Time	8:35																			
Personnel		Natasha Cowie, Cathy Anablak						Station	Depth	Distance	Area	Velocity (m/s)		Q	% of Total Q																	
Station Coordinates		Easting	Northing	Elevation			Notes	(m)	(m)	(m)	(m ²)	60%	20%	80%	(m ³ /s)	%																
		431481	7555089				RB	1.60	0.00	0.0	0.00	0			0.000	0.0																
Weather Conditions		Cloudy, calm, air 3°C, water 6°C							1.55	0.12	-0.1	0.01	0.05		0.000	1.8																
		Transducer Information							1.50	0.12	-0.1	0.01	0.19		0.001	6.8																
PT Model		PT2x	Serial #	2922016					1.45	0.12	-0.1	0.01	0.23		0.001	8.2																
Gain		1.01	Offset	-0.017					1.40	0.12	-0.1	0.01	0.29		0.002	10.4																
Status		Active	Battery	2.9 v					1.35	0.12	0.0	0.01	0.23		0.001	8.2																
# of Records		13,637	Memory Free	117,068					1.30	0.12	-0.1	0.01	0.22		0.001	7.9																
Date Serviced		Spring 2012	Crest Gauges	No					1.25	0.12	-0.1	0.01	0.24		0.001	8.6																
Hydrometric Leveling Survey																																
Stn	BS	HI	FS	Elevation	Notes			1.15	0.12	-0.1	0.01	0.20		0.001	7.1																	
BM 24	0.799	100.799		100.000	P			1.10	0.12	0.0	0.01	0.19		0.001	6.8																	
BM 23			1.142	99.657				1.05	0.12	-0.1	0.01	0.17		0.001	6.1																	
TP 1	1.276	98.320	3.755	97.044	turning point			1.00	0.11	-0.1	0.01	0.20		0.001	6.3																	
BM 45			2.761	95.559				0.95	0.11	-0.1	0.01	0.16		0.001	5.0																	
WL			3.402	94.918	9:29 PST			0.90	0.11	0.0	0.01	0.11		0.001	3.4																	
PT			3.767	94.553	end of PVC			0.85	0.11	-0.1	0.01	0.15		0.001	4.7																	
TBM	1.769	98.283	1.806	96.514				0.80	0.08	0.0	0.00	0.06		0.000	1.3																	
PT			3.732	94.551				0.75	0.08	-0.1	0.00	0.00		0.000	0.0																	
WL			3.366	94.917	9:34 PST		LB	0.70	0.00	-0.1	0.00	0		0.000	0.0																	
BM 45			2.724	95.559																												
TP 2	3.655	100.698	1.240	97.043	turning point																											
BM 23			1.047	99.651																												
BM 24			0.701	99.997																												
BM#		Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes																										
BM 24			99.999																													
BM 23			99.654																													
BM 45			95.559					Total Q					0.02	100.0																		
Summary															General Notes																	
Stage (m)		94.918		Used imperial rod, measurements have been converted.																												
Discharge (m ³ /s)		0.02																														
Pressure Transducer Reading (m)		0.381																														
Pressure Transducer Elevation (m)		94.536																														

Appendix B-5. Water Level Surveys at Doris Lake in 2013

Site Information					General Notes
Project Name					On June 8, two new benchmarks (BM S and BM N) were installed (BM W was originally installed by Golder in 2008 and was previously the only benchmark at the site), data download was completed, and memory was cleared (contained records from 2010 to the present). Benchmarks were temporarily assigned IDs according to their compass orientations. BMs will be tagged and numbered on a subsequent trip.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model		KPSI 730-series	Serial #		
Gain			Offset		
Status		Active	Battery		3.24
# of Records			Memory Free		
Date Serviced			Crest Gauges		No
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM W	1.500	101.500		100.000	primary, existing BM
BM S			2.258	99.242	new BM
BM N			2.950	98.550	new BM
WL			3.433	98.067	surveyed at 17:28
TBM	3.298	101.461	3.337	98.163	
WL			3.395	98.066	surveyed at 17:34
BM N			2.913	98.548	
BM S			2.219	99.242	
BM W			1.458	100.003	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes
BM W		100.002			
BM S		99.242			
BM N		98.549			
Summary					
Stage (m)		98.067			
Pressure Transducer Reading (m)		5.756			
Pressure Transducer Elevation (m)		92.310			

Appendix B-5. Water Level Surveys at Doris Lake in 2013

Site Information					General Notes
Project Name					
Station Identification					Doris Lake
Stream Name					Doris Lake northwest shore
Date Monitored					6-Jul-13
Time at Site (24 hr PST)					Start Time: 16:00 End Time: 16:40
Personnel					Natasha Cowie, Leonard Wingnek
Station Coordinates					Easting Northing Elevation
					433512 7558452
Weather Conditions					Warm, sunny, calm
Transducer Information					
PT Model					KPSI 730-series
Gain					Offset
Status					Active Battery 3.47
# of Records					Memory Free
Date Serviced					Crest Gauges No
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM W	0.825	100.825		100.000	P
BM S			1.581	99.244	
BM N			2.274	98.551	
WL			2.753	98.072	surveyed at 16:18 PST
TBM	2.654	100.833	2.646	98.179	
WL			2.762	98.071	surveyed at 16:22 PST
BM N			2.283	98.550	
BM S			1.588	99.245	
BM W			0.833	100.000	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	
BM W		100.000			
BM S		99.245			
BM N		98.551			
Summary					
Stage (m)		98.072			
Pressure Transducer Reading (m)		5.750			
Pressure Transducer Elevation (m)		92.321			

Appendix B-5. Water Level Surveys at Doris Lake in 2013

Site Information					General Notes
Project Name					BM W (original BM installed by Golder) was tagged as BM 70, BM S was tagged as BM 71, and BM N was tagged as BM 72. Data download was completed.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model					
Gain					
Status					
# of Records					
Date Serviced					
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 70	0.857	100.857		100.000	P, formerly BM W
			1.615	99.242	formerly BM S
BM 72			2.307	98.550	formerly BM N
WL			2.812	98.045	surveyed at 9:03 PST
TBM	2.707	100.849	2.715	98.142	
WL			2.804	98.045	surveyed at 9:06 PST
BM 72			2.300	98.549	
BM 71			1.607	99.242	
BM 70			0.850	99.999	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	
BM 70		100.000			
BM 71		99.242			
BM 72		98.550			
Summary					
Stage (m)		98.045			
Pressure Transducer Reading (m)		5.729			
Pressure Transducer Elevation (m)		92.316			

Appendix B-5. Water Level Surveys at Doris Lake in 2013

Site Information					General Notes
Project Name					BM W (original BM installed by Golder) is BM 70, BM S is BM 71, and BM N is BM 72. Data download was completed. Strong wind during survey. Station status check (of original station) showed a reasonable PT reading (5.532 m) but data download gave erroneous (negative) stage level values since the last data download on July 9. New station installed (PT2x, serial number 2922013, gain 1.007, offset -0.062) to check quality of data recorded by existing station.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model		KPSI 730-series	Serial #		
Gain		Offset			
Status		Active	Battery	3.39 v	
# of Records			Memory Free		
Date Serviced			Crest Gauges	No	
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 70	0.347	100.347		100.000	P, formerly BM W
BM 71			1.103	99.244	formerly BM S
BM 72			1.795	98.552	formerly BM N
WL			2.515	97.832	15:42 PST
PT (new stn)			2.846	97.501	
TBM	2.422	100.412	2.357	97.990	
WL			2.576	97.836	15:51 PST
PT (new stn)			2.914	97.498	
BM 72			1.856	98.556	
BM 71			1.164	99.248	
BM 70			0.407	100.005	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	
BM 70		100.003			
BM 71		99.246			
BM 72		98.554			
Summary					
Stage (m)		97.834			
Pressure Transducer Reading (m)		5.532 (original station), 0.375 (new station)			
Pressure Transducer Elevation (m)		92.302 (original station), 97.459 (new station)			

Appendix B-5. Water Level Surveys at Doris Lake in 2013

Site Information					General Notes
Project Name					Hope Bay
Station Identification					Doris Lake
Stream Name					Doris Lake northwest shore
Date Monitored					9-Sep-13
Time at Site (24 hr PST)					Start Time: 7:20 End Time: 8:20
Personnel					Natasha Cowie, Cathy Anablak
Station Coordinates					Easting Northing Elevation
					433512 7558452
Weather Conditions					Cloudy, windy
Transducer Information					
PT Model					KPSI 730-series
Gain					Serial # Offset
Status					Active Battery 3.3 v
# of Records					149,137 Memory Free wrap
Date Serviced					unknown Crest Gauges No
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 70	0.989	100.989		100.000	P, formerly BM W
BM 71			1.747	99.242	formerly BM S
BM 72			2.441	98.548	formerly BM N
WL			3.172	97.817	7:33 PST
TBM	3.045	100.917	3.117	97.872	
WL			3.097	97.820	7:38 PST
BM 72			2.367	98.550	
BM 71			1.675	99.242	
BM 70			0.917	100.000	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	
BM 70		100.000			
BM 71		99.242			
BM 72		98.549			
Summary					
Stage (m)		97.819			
Pressure Transducer Reading (m)		5.510 (original station), 0.334 (new station)			
Pressure Transducer Elevation (m)		92.309 (original station), 97.485 (new station)			

Appendix B-6. Water Level Surveys at Tail Lake in 2013

Site Information					General Notes		
Project Name					Hope Bay		
Station Identification					Tail Lake		
Stream Name					Tail Lake northwest shore		
Date Monitored					10-Jun-13		
Time at Site (24 hr PST)					Start Time: 10:20 End Time: 11:00		
Personnel					Natasha Cowie, Emerson Belland		
Station Coordinates					Easting Northing Elevation		
					434832 7558560		
Weather Conditions					Warm, sunny, calm		
Transducer Information							
PT Model					KPSI 730-series		
Gain					Serial # Offset		
Status					Battery		
# of Records					Memory Free		
Date Serviced					Crest Gauges No		
Hydrometric Leveling Survey							
Stn	BS	HI	FS	Elevation	Notes		
BM W	1.148	101.148		100.000	primary, existing BM		
BM N			2.977	98.171	new BM		
BM S			3.671	97.477	new BM		
TP 1	0.115	97.618	3.645	97.503			
WL			3.472	94.146	10:42 PST		
TBM	2.169	98.099	1.688	95.930			
WL			3.953	94.146	10:53 PST		
TP 2	3.444	101.330	0.213	97.886			
BM N			3.160	98.170			
BM S			3.853	97.477			
BM W			1.330	100.000			
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes			
BM W		100.000					
BM S		97.477					
BM N		98.171					
Summary							
Stage (m)							
94.146							
Pressure Transducer Reading (m)							
5.523							
Pressure Transducer Elevation (m)							
88.623							

Appendix B-6. Water Level Surveys at Tail Lake in 2013

Site Information					General Notes
Project Name					BM W (original BM installed by Golder) was tagged as BM 80, BM S was tagged as BM 81, and BM N was tagged as BM 82. Data download was completed.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model					
Gain					
Status					
# of Records					
Date Serviced					
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 80	0.977	100.977		100.000	P
			3.497	97.480	
BM 82			2.802	98.175	
TP 1	0.854	97.854	3.977	97.000	
WL			3.748	94.106	16:48 PST
TBM	2.704	97.749	2.809	95.045	
WL			3.642	94.107	16:54 PST
TP 2	3.834	100.974	0.609	97.140	
BM 82			2.796	98.178	
BM 81			3.490	97.484	
BM 80			0.970	100.004	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)	Notes	
BM 80		100.002			
BM 81		97.482			
BM 82		98.177			
Summary					
Stage (m)		94.107			
Pressure Transducer Reading (m)		5.455			
Pressure Transducer Elevation (m)		88.651			

Appendix B-6. Water Level Surveys at Tail Lake in 2013

Site Information					General Notes
Project Name					BM W (original BM installed by Golder) was tagged as BM 80, BM S was tagged as BM 81, and BM N was tagged as BM 82. Data download was completed. Strong wind during survey. High degree of uncertainty on second shot on BM 82 (2.081) due to chipped paint on rod. New station installed (PT2x, serial number 2922011, gain 0.998, offset 0.009) to check quality of data recorded by existing station.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model	KPSI 730-series	Serial #			
Gain	unknown	Offset			unknown
Status	active	Battery			3.35 v
# of Records		Memory Free			wrap
Date Serviced	unknown	Crest Gauges			No
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 80	0.479	100.479		100.000	P
BM 81			2.999	97.480	
BM 82			2.304	98.175	
TP 1	0.073	99.275	1.277	99.202	
TP 2	0.489	97.557	2.207	97.068	
TP 3	0.448	95.623	2.382	95.175	
WL			1.705	93.918	10:30 PST
PT (new stn)			2.482	93.141	
TBM	1.434	95.592	1.465	94.158	
WL			1.668	93.924	10:47 PST
PT (new stn)			2.449	93.143	
TP 4	2.622	97.804	0.410	95.182	
TP 5	2.383	99.459	0.728	97.076	
TP 6	1.058	100.271	0.246	99.213	
BM 82			2.081	98.190	
BM 81			2.777	97.494	
BM 80			0.259	100.012	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)	Difference (m)		Notes
BM 80		100.006			
BM 81		97.487			
BM 82		98.183			
Summary					
Stage (m)		93.921			
Pressure Transducer Reading (m)		5.260 (original station), 0.781 (new station)			
Pressure Transducer Elevation (m)		88.661 (original station), 93.140 (new station)			

Appendix B-6. Water Level Surveys at Tail Lake in 2013


Site Information					General Notes
Project Name					BM W (original BM installed by Golder) was tagged as BM 80, BM S was tagged as BM 81, and BM N was tagged as BM 82. Data download was completed. PT is secondary station installed in August 2013 (primary station installed by Golder is 5 m deep and cannot be surveyed). Water depth above PT (new station) at 15:55 PST averaged 0.740 m (min 0.735 m, max 0.750 m). New station was demobilized for the winter; original station remained in continuous operation.
Station Identification					
Stream Name					
Date Monitored					
Time at Site (24 hr PST)					
Personnel					
Station Coordinates					
Weather Conditions					
Transducer Information					
PT Model		PT2x	Serial #	2922011	
Gain		0.998	Offset	0.009	
Status		active	Battery	3.0 v	
# of Records		3,018	Memory Free	127,687	
Date Serviced		Summer 2013	Crest Gauges	No	
Hydrometric Leveling Survey					
Stn	BS	HI	FS	Elevation	Notes
BM 80	0.555	100.555		100.000	P
BM 81			3.072	97.483	
BM 82			2.381	98.174	
TP 1	0.164	97.019	3.700	96.855	
WL			3.136	93.883	15:15 PST
PT (new stn)			3.882	93.137	
TBM	2.838	97.042	2.815	94.204	
WL			3.161	93.881	15:26 PST
PT (new stn)			3.903	93.139	
TP 4	3.600	100.454	0.188	96.854	
BM 82			2.282	98.172	
BM 81			2.975	97.479	
BM 80			0.455	99.999	
BM#	Established Elevation (m)	Mean Elevation (this date) (m)		Difference (m)	Notes
BM 80		100.000			
BM 81		97.481			
BM 82		98.173			
Summary					
Stage (m)		93.882			
Pressure Transducer Reading (m)		5.242 (original station), 0.764 (new station)			
Pressure Transducer Elevation (m)		88.640 (original station), 93.118 (new station)			

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix C


Channel Geometry Surveys






Notes: Elevations and water levels are referenced to a site specific non-geodetic datum.
Minimum, mean, and maximum discharge values are calculated from recorded
water level data for the 2013 period of record (June 6-September 9).
cms = cubic meters per second (m^3/s)

- - - 2013 Maximum Daily Discharge = 0.98 cms (June 22)
- - - 2013 Mean Daily Discharge = 0.46 cms
- - - 2013 Minimum Daily Discharge = 0.09 cms (September 6)
- Stream Bed
- Pressure Transducer




Upstream view of station Doris TL-2 and the surveyed channel reach – cross-sections A (21 m upstream of station), B (at station), and C (11 m downstream of station). June 11, 2013.



Downstream view of station Doris TL-2 and the surveyed channel reach – cross-sections B (at station) and C (11 m downstream of station). August 14, 2013.


Figure C-1

Doris TL-2




Notes: Elevations and water levels are referenced to a site specific non-geodetic datum.
Minimum, mean, and maximum discharge values are calculated from recorded
water level data for the 2013 period of record (June 9-September 7).
cms = cubic meters per second (m^3/s)

- - - 2013 Maximum Daily Discharge = 1.25 cms (June 23)
- - - 2013 Mean Daily Discharge = 0.53 cms
- - - 2013 Minimum Daily Discharge = 0.09 cms (August 25)
- Stream Bed
- Pressure Transducer






Upstream view of station Doris TL-3 and the surveyed channel reach – cross-sections A (15 m upstream of station) and B (at station). August 15, 2013.





Downstream view of station Doris TL-3 and the surveyed channel reach – cross-sections B (at station) and C (7 m downstream of station). August 15, 2013.


Figure C-2

Doris TL-3




- 2013 Maximum Daily Discharge = 1.97 cms (June 17)
- 2013 Mean Daily Discharge = 0.67 cms
- 2013 Minimum Daily Discharge = 0.11 cms (Sept 1)
- Stream Bed
- Pressure Transducer






Notes: Elevations and water levels are referenced to a site specific non-geodetic datum.
Minimum, mean, and maximum discharge values are calculated from recorded
water level data for the 2013 period of record (June 5-September 8).
cms = cubic meters per second (m^3/s)

- - - 2013 Maximum Daily Discharge = 0.12 cms (July 4)
- - - 2013 Mean Daily Discharge = 0.07 cms
- - - 2013 Minimum Daily Discharge = 0.02 cms (Sept 1)
- Stream Bed
- Pressure Transducer



High angle view of station Windy Hydro and the surveyed channel reach – cross-sections A (shoreline profile at station) and B (lake outlet 150 m northeast of station). August 17, 2013.




Downstream view of the surveyed channel reach – cross-section C (flow gauging section 500 m downstream of lake outlet). August 17, 2013.

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report


Appendix D

Rating Curves






Doris TL-2, looking downstream (north) toward the station. June 10, 2013.




Notes: Rating period from June 10, 2013 to September 7, 2013.
Pressure transducer stage readings are referenced to local (non geodetic) datum.

Figure D-1




Doris TL-3, looking downstream (north) toward the station. September 7, 2013.






Roberts Hydro, looking upstream (east) toward the gauged section. August 16, 2013.




Notes: Rating period from June 22, 2009 to September 8, 2013.
 Pressure transducer stage readings are referenced to local (non geodetic) datum.

Figure D-3



Windy Hydro, looking downstream (north) toward the gauged section. September 8, 2013.



Notes: Rating period from June 16, 2011 to September 8, 2013.
Pressure transducer stage readings are referenced to local (non geodetic) datum.

Figure D-4

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix E

Mean Daily Discharge Tables

Appendix E-1. Mean Daily Discharge (Q, m³/s) at Hydrometric Station Doris TL-2 in 2013

Drainage Area 94.6 km²

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.000	0.000	0.000	0.000	0.000	0.003	0.831	0.326	0.093	0.021	0.000	0.000
2	0.000	0.000	0.000	0.000	0.000	0.003	0.837	0.325	0.097	0.018	0.000	0.000
3	0.000	0.000	0.000	0.000	0.000	0.004	0.820	0.307	0.093	0.014	0.000	0.000
4	0.000	0.000	0.000	0.000	0.000	0.004	0.827	0.299	0.092	0.011	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.005	0.810	0.290	0.096	0.007	0.000	0.000
6	0.000	0.000	0.000	0.000	0.000	0.160	0.784	0.275	0.090	0.003	0.000	0.000
7	0.000	0.000	0.000	0.000	0.000	0.273	0.760	0.269	0.093	0.000	0.000	0.000
8	0.000	0.000	0.000	0.000	0.000	0.331	0.733	0.253	0.093	0.000	0.000	0.000
9	0.000	0.000	0.000	0.000	0.000	0.405	0.704	0.246	0.093	0.000	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.476	0.671	0.238	0.092	0.000	0.000	0.000
11	0.000	0.000	0.000	0.000	0.000	0.544	0.643	0.230	0.091	0.000	0.000	0.000
12	0.000	0.000	0.000	0.000	0.000	0.615	0.621	0.220	0.087	0.000	0.000	0.000
13	0.000	0.000	0.000	0.000	0.000	0.682	0.591	0.213	0.084	0.000	0.000	0.000
14	0.000	0.000	0.000	0.000	0.000	0.747	0.565	0.203	0.081	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.810	0.552	0.196	0.077	0.000	0.000	0.000
16	0.000	0.000	0.000	0.000	0.000	0.867	0.540	0.180	0.074	0.000	0.000	0.000
17	0.000	0.000	0.000	0.000	0.000	0.914	0.531	0.176	0.070	0.000	0.000	0.000
18	0.000	0.000	0.000	0.000	0.000	0.948	0.515	0.168	0.067	0.000	0.000	0.000
19	0.000	0.000	0.000	0.000	0.001	0.967	0.507	0.162	0.063	0.000	0.000	0.000
20	0.000	0.000	0.000	0.001	0.000	0.973	0.500	0.150	0.060	0.000	0.000	0.000
21	0.000	0.000	0.000	0.000	0.001	0.971	0.477	0.147	0.056	0.000	0.000	0.000
22	0.000	0.000	0.000	0.000	0.001	0.981	0.457	0.138	0.053	0.000	0.000	0.000
23	0.000	0.000	0.000	0.000	0.001	0.977	0.441	0.135	0.049	0.000	0.000	0.000
24	0.000	0.000	0.000	0.001	0.000	0.973	0.434	0.125	0.046	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.001	0.963	0.428	0.103	0.042	0.000	0.000	0.000
26	0.000	0.000	0.000	0.000	0.001	0.943	0.413	0.100	0.039	0.000	0.000	0.000
27	0.000	0.000	0.000	0.000	0.002	0.923	0.396	0.099	0.035	0.000	0.000	0.000
28	0.000	0.000	0.000	0.000	0.002	0.907	0.384	0.097	0.032	0.000	0.000	0.000
29	0.000	0.000	0.000	0.000	0.002	0.877	0.362	0.099	0.028	0.000	0.000	0.000
30	0.000	0.000	0.000	0.000	0.002	0.865	0.357	0.096	0.025	0.000	0.000	0.000
31	0.000	0.000	0.000	0.003		0.348	0.094		0.000			
Mean	0.000	0.000	0.000	0.000	0.001	0.637	0.575	0.192	0.070	0.002	0.000	0.000
Max	0.000	0.000	0.000	0.000	0.003	0.981	0.837	0.326	0.097	0.021	0.000	0.000
Min	0.000	0.000	0.000	0.000	0.000	0.003	0.348	0.094	0.025	0.000	0.000	0.000

Notes: Period of operation for 2013 was June 6-September 9. Water levels were potentially affected by ice prior to June 9. Estimated values are italicized.

Appendix E-2. Mean Daily Discharge (Q, m³/s) at Hydrometric Station Doris TL-3 in 2013

Drainage Area 95.3 km²

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.000	0.000	0.000	0.000	0.000	0.028	1.030	0.342	0.096	0.031	0.000	0.000
2	0.000	0.000	0.000	0.000	0.000	0.040	0.950	0.358	0.105	0.028	0.000	0.000
3	0.000	0.000	0.000	0.000	0.000	0.057	0.892	0.327	0.102	0.024	0.000	0.000
4	0.000	0.000	0.000	0.000	0.000	0.082	0.910	0.315	0.100	0.021	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.117	0.899	0.304	0.110	0.017	0.000	0.000
6	0.000	0.000	0.000	0.000	0.000	0.168	0.865	0.289	0.102	0.014	0.000	0.000
7	0.000	0.000	0.000	0.000	0.000	0.240	0.839	0.282	0.107	0.010	0.000	0.000
8	0.000	0.000	0.000	0.000	0.000	0.343	0.813	0.261	0.108	0.007	0.000	0.000
9	0.000	0.000	0.000	0.000	0.000	0.490	0.777	0.253	0.106	0.004	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.602	0.740	0.246	0.103	0.000	0.000	0.000
11	0.000	0.000	0.000	0.000	0.000	0.646	0.708	0.235	0.100	0.000	0.000	0.000
12	0.000	0.000	0.000	0.000	0.000	0.691	0.680	0.224	0.096	0.000	0.000	0.000
13	0.000	0.000	0.000	0.000	0.000	0.766	0.644	0.214	0.093	0.000	0.000	0.000
14	0.000	0.000	0.000	0.000	0.000	0.855	0.633	0.205	0.089	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.941	0.603	0.197	0.086	0.000	0.000	0.000
16	0.000	0.000	0.000	0.000	0.000	1.023	0.589	0.179	0.082	0.000	0.000	0.000
17	0.000	0.000	0.000	0.000	0.000	1.086	0.582	0.175	0.079	0.000	0.000	0.000
18	0.000	0.000	0.000	0.000	0.000	1.131	0.579	0.167	0.076	0.000	0.000	0.000
19	0.000	0.000	0.000	0.000	0.000	1.148	0.564	0.162	0.072	0.000	0.000	0.000
20	0.000	0.000	0.000	0.000	0.000	1.148	0.560	0.151	0.069	0.000	0.000	0.000
21	0.000	0.000	0.000	0.000	0.001	1.138	0.534	0.146	0.065	0.000	0.000	0.000
22	0.000	0.000	0.000	0.000	0.001	1.187	0.507	0.137	0.062	0.000	0.000	0.000
23	0.000	0.000	0.000	0.000	0.001	1.253	0.489	0.136	0.058	0.000	0.000	0.000
24	0.000	0.000	0.000	0.002	0.000	1.235	0.481	0.126	0.055	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.002	1.229	0.478	0.091	0.052	0.000	0.000	0.000
26	0.000	0.000	0.000	0.000	0.003	1.193	0.453	0.094	0.048	0.000	0.000	0.000
27	0.000	0.000	0.000	0.000	0.005	1.156	0.432	0.092	0.045	0.000	0.000	0.000
28	0.000	0.000	0.000	0.000	0.007	1.137	0.420	0.093	0.041	0.000	0.000	0.000
29	0.000	0.000	0.000	0.010	0.000	1.101	0.393	0.099	0.038	0.000	0.000	0.000
30	0.000	0.000	0.000	0.014	0.000	1.080	0.383	0.095	0.034	0.000	0.000	0.000
31	0.000	0.000	0.020	0.000	0.000	0.376	0.096	0.000	0.000	0.000	0.000	0.000
Mean	0.000	0.000	0.000	0.000	0.002	0.777	0.639	0.197	0.079	0.005	0.000	0.000
Max	0.000	0.000	0.000	0.000	0.020	1.253	1.030	0.358	0.110	0.031	0.000	0.000
Min	0.000	0.000	0.000	0.000	0.000	0.028	0.376	0.091	0.034	0.000	0.000	0.000

Notes: Period of operation for 2013 was June 9-September 7. Estimated values are italicized.

Appendix E-3. Mean Daily Discharge (Q, m³/s) at Hydrometric Station Roberts Hydro in 2013

Drainage Area 97.9 km²

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.000	0.000	0.000	0.000	0.000	0.154	0.970	0.406	0.112	0.056	0.000	0.000
2	0.000	0.000	0.000	0.000	0.000	0.195	0.982	0.391	0.118	0.053	0.000	0.000
3	0.000	0.000	0.000	0.000	0.000	0.245	0.978	0.381	0.116	0.050	0.000	0.000
4	0.000	0.000	0.000	0.000	0.000	0.309	0.951	0.371	0.114	0.047	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.390	0.894	0.359	0.117	0.044	0.000	0.000
6	0.000	0.000	0.000	0.000	0.000	0.492	0.855	0.342	0.115	0.041	0.000	0.000
7	0.000	0.000	0.000	0.000	0.000	0.620	0.820	0.326	0.120	0.038	0.000	0.000
8	0.000	0.000	0.000	0.000	0.001	0.860	0.791	0.313	0.121	0.035	0.000	0.000
9	0.000	0.000	0.000	0.000	0.001	1.001	0.767	0.311	0.119	0.032	0.000	0.000
10	0.000	0.000	0.000	0.000	0.001	1.225	0.735	0.300	0.119	0.029	0.000	0.000
11	0.000	0.000	0.000	0.000	0.001	1.406	0.694	0.288	0.116	0.026	0.000	0.000
12	0.000	0.000	0.000	0.000	0.002	1.566	0.663	0.275	0.113	0.023	0.000	0.000
13	0.000	0.000	0.000	0.000	0.002	1.705	0.626	0.265	0.110	0.020	0.000	0.000
14	0.000	0.000	0.000	0.000	0.002	1.809	0.595	0.260	0.107	0.017	0.000	0.000
15	0.000	0.000	0.000	0.000	0.003	1.892	0.588	0.246	0.104	0.014	0.000	0.000
16	0.000	0.000	0.000	0.000	0.004	1.928	0.589	0.236	0.101	0.011	0.000	0.000
17	0.000	0.000	0.000	0.000	0.005	1.967	0.585	0.229	0.098	0.008	0.000	0.000
18	0.000	0.000	0.000	0.000	0.006	1.966	0.583	0.218	0.095	0.005	0.000	0.000
19	0.000	0.000	0.000	0.000	0.008	1.923	0.572	0.207	0.092	0.002	0.000	0.000
20	0.000	0.000	0.000	0.000	0.010	1.835	0.559	0.197	0.089	0.000	0.000	0.000
21	0.000	0.000	0.000	0.000	0.012	1.733	0.542	0.184	0.086	0.000	0.000	0.000
22	0.000	0.000	0.000	0.000	0.015	1.653	0.522	0.173	0.083	0.000	0.000	0.000
23	0.000	0.000	0.000	0.000	0.019	1.579	0.504	0.169	0.080	0.000	0.000	0.000
24	0.000	0.000	0.000	0.000	0.024	1.484	0.488	0.138	0.077	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.031	1.402	0.483	0.124	0.074	0.000	0.000	0.000
26	0.000	0.000	0.000	0.000	0.038	1.327	0.477	0.122	0.071	0.000	0.000	0.000
27	0.000	0.000	0.000	0.000	0.049	1.238	0.458	0.121	0.068	0.000	0.000	0.000
28	0.000	0.000	0.000	0.000	0.061	1.153	0.445	0.122	0.065	0.000	0.000	0.000
29	0.000	0.000	0.000	0.000	0.077	1.070	0.433	0.122	0.062	0.000	0.000	0.000
30	0.000	0.000	0.000	0.000	0.097	1.015	0.421	0.118	0.059	0.000	0.000	0.000
31	0.000	0.000	0.000	0.123		0.411	0.115		0.000			
Mean	0.000	0.000	0.000	0.000	0.019	1.238	0.644	0.240	0.097	0.018	0.000	0.000
Max	0.000	0.000	0.000	0.000	0.123	1.967	0.982	0.406	0.121	0.056	0.000	0.000
Min	0.000	0.000	0.000	0.000	0.000	0.154	0.411	0.115	0.059	0.000	0.000	0.000

Notes: Period of operation for 2013 was June 7-September 8. Water levels were potentially affected by ice prior to June 11. Estimated values are italicized

Appendix E-4. Mean Daily Discharge (Q, m³/s) at Hydrometric Station Windy Hydro in 2013

Drainage Area 14.1 km²

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	0.000	0.000	0.000	0.000	0.000	0.002	0.089	0.084	0.015	0.002	0.000	0.000
2	0.000	0.000	0.000	0.000	0.000	0.004	0.100	0.083	0.017	0.002	0.000	0.000
3	0.000	0.000	0.000	0.000	0.000	0.007	0.100	0.079	0.017	0.001	0.000	0.000
4	0.000	0.000	0.000	0.000	0.000	0.014	0.116	0.077	0.017	0.001	0.000	0.000
5	0.000	0.000	0.000	0.000	0.000	0.026	0.112	0.074	0.017	0.000	0.000	0.000
6	0.000	0.000	0.000	0.000	0.000	0.050	0.110	0.071	0.017	0.000	0.000	0.000
7	0.000	0.000	0.000	0.000	0.000	0.053	0.108	0.067	0.017	0.000	0.000	0.000
8	0.000	0.000	0.000	0.000	0.000	0.059	0.105	0.063	0.015	0.000	0.000	0.000
9	0.000	0.000	0.000	0.000	0.000	0.070	0.103	0.062	0.015	0.000	0.000	0.000
10	0.000	0.000	0.000	0.000	0.000	0.079	0.101	0.061	0.014	0.000	0.000	0.000
11	0.000	0.000	0.000	0.000	0.000	0.081	0.099	0.059	0.013	0.000	0.000	0.000
12	0.000	0.000	0.000	0.000	0.000	0.085	0.098	0.056	0.013	0.000	0.000	0.000
13	0.000	0.000	0.000	0.000	0.000	0.089	0.096	0.055	0.012	0.000	0.000	0.000
14	0.000	0.000	0.000	0.000	0.000	0.091	0.093	0.053	0.012	0.000	0.000	0.000
15	0.000	0.000	0.000	0.000	0.000	0.093	0.094	0.052	0.011	0.000	0.000	0.000
16	0.000	0.000	0.000	0.000	0.000	0.095	0.095	0.048	0.011	0.000	0.000	0.000
17	0.000	0.000	0.000	0.000	0.000	0.098	0.100	0.045	0.010	0.000	0.000	0.000
18	0.000	0.000	0.000	0.000	0.000	0.099	0.103	0.042	0.010	0.000	0.000	0.000
19	0.000	0.000	0.000	0.000	0.000	0.098	0.103	0.041	0.009	0.000	0.000	0.000
20	0.000	0.000	0.000	0.000	0.000	0.095	0.101	0.038	0.008	0.000	0.000	0.000
21	0.000	0.000	0.000	0.000	0.000	0.094	0.100	0.036	0.008	0.000	0.000	0.000
22	0.000	0.000	0.000	0.000	0.000	0.093	0.097	0.032	0.007	0.000	0.000	0.000
23	0.000	0.000	0.000	0.000	0.000	0.095	0.095	0.031	0.007	0.000	0.000	0.000
24	0.000	0.000	0.000	0.000	0.000	0.095	0.095	0.028	0.006	0.000	0.000	0.000
25	0.000	0.000	0.000	0.000	0.000	0.094	0.098	0.018	0.006	0.000	0.000	0.000
26	0.000	0.000	0.000	0.000	0.000	0.094	0.098	0.017	0.005	0.000	0.000	0.000
27	0.000	0.000	0.000	0.000	0.000	0.092	0.095	0.016	0.005	0.000	0.000	0.000
28	0.000	0.000	0.000	0.000	0.000	0.089	0.092	0.017	0.004	0.000	0.000	0.000
29	0.000	0.000	0.000	0.000	0.000	0.087	0.090	0.017	0.004	0.000	0.000	0.000
30	0.000	0.000	0.000	0.001	0.001	0.088	0.091	0.015	0.003	0.000	0.000	0.000
31	0.000	0.000	0.001			0.088	0.015			0.000		
Mean	0.000	0.000	0.000	0.000	0.000	0.074	0.099	0.047	0.011	0.000	0.000	0.000
Max	0.000	0.000	0.000	0.000	0.001	0.099	0.116	0.084	0.017	0.002	0.000	0.000
Min	0.000	0.000	0.000	0.000	0.000	0.002	0.088	0.015	0.003	0.000	0.000	0.000

Notes: Period of operation for 2013 was June 5-September 8. Water levels were potentially affected by ice prior to June 7. Estimated values are italicized

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix F

Memorandum: Estimation of Maximum Allowable Water Discharges from the Tail Lake Tailings Impoundment Area into Doris Creek





Memorandum

Date: November 15, 2013

Refer to File No.: A.1_Doris TL-2 Memo.docx

To: Katsky Venter, Lea-Marie Bowes-Lyon

From: Natasha Cowie

CC: David Luzi, Marc Wen

Subject: Estimation of Maximum Allowable Water Discharges from the Tail Lake Tailings Impoundment Area into Doris Creek

1. INTRODUCTION

Any discharge of water from the Tail Lake Tailings Impoundment Area (TIA) into Doris Creek must comply with the regulatory requirements of the Doris North Project Type A Water License (2AM-DOH1323, issued August 16, 2013). The license states in Part G, Item 30 that:

"The Licensee shall ensure that the flow from the Tailings Impoundment Area into Doris Creek at monitoring station TL-4 does not exceed 10% of the background flow in Doris Creek as measured at monitoring station TL-2 at the time of discharge."

In 2011, Rescan Environmental Services Ltd. (now ERM Rescan) initiated a program to determine allowable maximum daily discharge from Tail Lake TIA into Doris Creek, using a satellite telemetry station to provide remote access to real-time water level data recorded at the hydrometric monitoring station TL-2. The program continued in 2012 and 2013. This memorandum describes the methods and results of the 2013 program.

2. METHODOLOGY

2.1 Station Instrumentation and Field Measurements

The hydrometric station Doris TL-2 was remobilized for the open water season (June-September) on June 6, 2013 (Plate 2-1). The instrumentation package consisted of a 0-5 psi vented PS-9800® pressure transducer (Instrumentation Northwest Inc.) paired with an HOBO® Energy Pro Datalogger (Onset Computer Corp). It also included a Solarstream™ solar-powered Iridium® satellite transceiver (Upward Innovations Inc.). The station was powered by a 12 volt battery connected to a backup solar panel. Water level (stage) data were recorded every 10 minutes at the station. Every two hours the system automatically transmitted the recorded water level data to a secure Internet server. Data were then available for viewing or downloading over a secure 256-bit encrypted connection. The station was demobilized for the season on September 9, 2013.

Between June and September, a total of 11 manual current velocity measurements were taken at station TL-2 in order to calculate the volumetric flow (discharge) of Doris Creek. Velocity measurements were taken with a portable electromagnetic current meter (Marsh-McBirney Flo-Mate 2000™ or Hach FH950™). Water discharges were calculated from the velocity measurements using the velocity-area

method, in accordance with methods and standards described by the Water Survey of Canada (Lane 1999) and the British Columbia Resources Information Standards Committee (RISC 2009).




Plate 2-1. Doris TL-2 hydrometric monitoring station on Doris Creek. View is downstream (north). September 9, 2013.

During 10 of the 11 station visits, water level (stage) was surveyed prior to current velocity measurements. The exception was June 5, 2013, prior to station mobilization, when a substantial amount of ice in the channel prevented an accurate measurement of water level. Surveys were conducted using an engineer's rod and level. Water levels were referenced to an established local datum. Manual measurements of water level and volumetric flow for the 2013 season are provided in Table 2-1.

2.2 Rating Curve Development

To provide a time series of the flow volumes at TL-2, a relationship between recorded stage and associated measured stream discharge was developed. This empirical relation is referred to as a rating curve (ISO 2010). Once a rating curve is established for a monitoring site, water level data can be converted into a discharge time series, or hydrograph. However, the rating curve may change over time due to changes in channel geometry (e.g., bank collapse, scouring, aggradation, vegetation growth). Using measurements taken in June 2013, a new rating curve was developed for TL-2 to reflect altered channel geometry as a result of slumping of the right bank (Plate 2-2). The updated rating curve was applied to convert the recorded water level data to flow volumes.

At the end of the field season, the rating curve was updated with the addition of data collected in July, August, and September 2013 (i.e., the last four manual measurements in Table 2-1). The hydrograph generated by the updated rating curve allows a retrospective evaluation of the performance of the rating curve established in June 2013.




Plate 2-2. Streambank slumping along Doris Creek at hydrometric monitoring station Doris TL-2. View is downstream (north). June 10, 2013.

Table 2-1. 2013 Manual Flow Discharge Measurements at Hydrometric Station Doris TL-2

Date	Discharge (m ³ /s)	Stage (m) ^a
June 5	0.005	n/a ^b
June 6	0.16	96.180 ^c
June 9	0.54	96.222 ^c
June 10	0.52	96.244
June 11	0.57	96.263
June 12	0.70	96.293
June 13	0.74	96.304
July 6	0.78	96.312
July 8	0.71	96.301
August 14	0.19	96.089
September 7	0.10	96.024

Note: Data have been reviewed and corrected according to quality assurance/quality control (QA/QC) standard procedures.

^aWater levels are referenced to a site specific non-geodetic datum.

^bStage not measured on June 5 because a substantial amount of ice in the channel prevented an accurate measurement of water level.

^cIce encroachment in channel affected water level; measurement not used in development of rating curve.

2.3 Regression Models

Under the regulatory requirements of the Doris North Project Type A Water License, the water discharged from the Tail Lake TIA into Doris Creek should not exceed the maximum allowance of 10% of the stream's background flow volume. Therefore, daily predictions of Doris Creek flow volumes were

necessary in order to ensure that pumped volumes were in compliance. A regression procedure was developed to forecast the mean daily flows for Doris Creek at TL-2.

Every three days, a regression model was fit to the daily mean flow values (m^3/s) for the previous three to five days. Both polynomial and power models were evaluated, and the model with the best visual fit was used to predict flow volumes for the next three days. Although predictions were provided for three days at a time, the regression models were generally checked against the data on a daily basis and updated on a more frequent basis if necessary. An example of the procedure is provided in Figure 2-1 and Table 2-2. In this example, a model fit to recorded flow volumes for July 6-10 is used to predict volumes for July 11-13. The independent variable (x) of the regression model is the daily record number (e.g., 1 for June 6, and 2 for June 7) and the dependent variable (y) is the corresponding daily flow.




Figure 2-1. Example of Regression Model Development for Prediction of Mean Daily Discharge (m^3/s) at Hydrometric Station Doris TL-2

Table 2-2. Example of Regression Model Used to Predict Mean Daily Discharge at Hydrometric Station Doris TL-2

Period of Recorded Data Used to Build Model	Period of Predicted Data Derived from Model	Model Equation	R ²
July 6-10	July 11-13	$y = 114.01x^{-1.435}$	0.99

Total daily volumes (m^3/day) were calculated from the mean daily discharge values (m^3/s). The maximum allowable discharge from the Tail Lake TIA on a given day was calculated as 10% of the predicted total daily volume for that day, in accordance with water license requirements.

3. RESULTS

During the 2013 monitoring season, Doris Creek flow volumes were recorded for 96 days. Predicted and recorded flow volumes at TL-2 for the 2013 monitoring period are summarized in Table 3-1 and provided in graphical form in Figure 3-1. Daily mean (m^3/s) and total (m^3/day) flow volumes are provided in Appendix A, as well as daily allowable total discharge volumes (10% of background flow volume of Doris Creek at TL-2, m^3/day) from the Tail Lake TIA.

In comparison to the recorded flow volumes calculated from the June 2013 rating curve, the forecasted values overpredicted flows on 55 days. On days when forecasted volumes were greater than recorded volumes, predicted flows were 4% above the recorded daily flows on average (range: 0.04% to 24%). Over the entire 2013 monitoring period (June 6 to September 9), the total predicted flow volume exceeded the total recorded flow volume by 1,050 m^3 , an error of 0.29% (Table 3-1).

Table 3-1. Summary of Predicted and Recorded Discharge Volumes for 2013 at Hydrometric Station Doris TL-2

Period of Record	Rating Curve	Number of Days Overpredicted ^a	Predicted Total Allowable Volume (m^3) ^b	Recorded Total Allowable Volume (m^3) ^b	Difference between Total Allowable Volume based on Predicted and Recorded Flow (m^3)	Prediction Error ^c
June 6-Sept 9 (96 days)	June 2013	55	367,634	366,584	1,050	0.29%
	October 2013	20	367,634	377,200	-9,566	-2.54%

^aPredicted total daily flow greater than recorded total daily flow

^bAllowable volume defined as 10% of total flow volumes at TL-2

^cPercent difference between predicted and recorded total flow volumes

The revised rating curve developed in October 2013 indicates that flow volumes were slightly higher than those calculated from the June 2013 rating curve (Figure 3-1). The October 2013 rating curve is based on eight manual measurements and therefore may be considered more reliable than the June 2013 rating curve, which was based on four manual measurements in 2013. Forecasted values overpredicted flows on 20 days in comparison to recorded volumes calculated from the October 2013 rating curve. On days when forecasted volumes were greater than recorded volumes, predicted flows were 2% above the recorded daily flows on average (range: 0.07% to 9%). The total predicted flow volume for the monitoring period was 9,566 m^3 less than the total recorded flow volume based on the October 2013 rating curve, an error of -2.54% (Table 3-1).

In summary, the results indicate that the estimated maximum allowable discharge predictions did not result in an overall prediction exceedance relative to the recorded background flow volume in Doris Creek.





Figure 3-1. Comparison of Predicted and Recorded Total Daily Discharge (m³/day) for 2013 at Hydrometric Station Doris TL-2

Prepared By:



Natasha Cowie, M.Sc.
ERM Rescan, Hydrology

Reviewed By:



Ali Naghibi, Ph.D., P.Eng., Senior Consultant
ERM Rescan, Hydrology

REFERENCES

ISO. 2010. *ISO 1100-2: 2010. Hydrometry: measurement of liquid flow in open channels. Part 2: determination of the stage discharge relationship*. 3rd ed. ISO, Switzerland.

Lane, R. J. 1999. *Principles of Discharge Measurement: Hydrometric Technician Career Development Program. Lesson Package No. 10.1*. Environment Canada, Water Survey of Canada: Fredericton, NB.

Resources Information Standards Committee (RISC). 2009. *Manual of British Columbia Hydrometric Standards*. British Columbia Ministry of Environment, Science and Information Branch. March 2009.

- APPENDIX A -

2013 Predicted and Recorded Flow Volumes for Doris Creek Hydrometric Monitoring Station Doris
TL-2

Table A.1. Predicted (Regression Model) and Recorded (June 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
6-Jun	0.22	18,870	1,887	0.23	20,062	2,006	-6%	predicted volume under 10%
7-Jun	0.30	25,730	2,573	0.30	25,890	2,589	-1%	predicted volume under 10%
8-Jun	0.37	32,383	3,238	0.38	32,425	3,242	0%	predicted volume under 10%
9-Jun	0.45	38,828	3,883	0.45	38,690	3,869	0%	predicted volume over 10%
10-Jun	0.52	45,066	4,507	0.52	44,684	4,468	1%	predicted volume over 10%
11-Jun	0.59	51,097	5,110	0.59	50,858	5,086	0%	predicted volume over 10%
12-Jun	0.66	56,920	5,692	0.66	56,816	5,682	0%	predicted volume over 10%
13-Jun	0.72	62,536	6,254	0.72	62,593	6,259	0%	predicted volume under 10%
14-Jun	0.79	67,945	6,794	0.79	68,223	6,822	0%	predicted volume under 10%
15-Jun	0.85	73,146	7,315	0.85	73,271	7,327	0%	predicted volume under 10%
16-Jun	0.90	78,140	7,814	0.90	77,470	7,747	1%	predicted volume over 10%
17-Jun	0.96	82,927	8,293	0.93	80,580	8,058	3%	predicted volume over 10%
18-Jun	1.01	87,506	8,751	0.95	82,382	8,238	6%	predicted volume over 10%
19-Jun	1.06	91,878	9,188	0.96	82,916	8,292	11%	predicted volume over 10%
20-Jun	0.95	82,469	8,247	0.96	82,814	8,281	0%	predicted volume under 10%
21-Jun	0.93	80,551	8,055	0.97	83,682	8,368	-4%	predicted volume under 10%
22-Jun	0.90	77,388	7,739	0.97	83,444	8,344	-7%	predicted volume under 10%
23-Jun	0.96	82,771	8,277	0.96	83,104	8,310	0%	predicted volume under 10%
24-Jun	0.95	81,994	8,199	0.95	82,312	8,231	0%	predicted volume under 10%
25-Jun	0.94	80,784	8,078	0.93	80,651	8,065	0%	predicted volume over 10%
26-Jun	0.93	80,145	8,014	0.91	78,931	7,893	2%	predicted volume over 10%
27-Jun	0.88	76,326	7,633	0.90	77,452	7,745	-1%	predicted volume under 10%
28-Jun	0.86	74,503	7,450	0.87	74,758	7,476	0%	predicted volume under 10%
29-Jun	0.84	72,636	7,264	0.85	73,795	7,380	-2%	predicted volume under 10%
30-Jun	0.82	70,667	7,067	0.82	71,099	7,110	-1%	predicted volume under 10%
1-Jul	0.77	66,830	6,683	0.83	71,587	7,159	-7%	predicted volume under 10%
2-Jul	0.75	64,990	6,499	0.81	69,911	6,991	-7%	predicted volume under 10%
3-Jul	0.80	69,503	6,950	0.82	70,503	7,050	-1%	predicted volume under 10%
4-Jul	0.79	68,629	6,863	0.80	69,285	6,929	-1%	predicted volume under 10%
5-Jul	0.78	67,793	6,779	0.78	67,040	6,704	1%	predicted volume over 10%
6-Jul	0.76	65,396	6,540	0.75	64,988	6,499	1%	predicted volume over 10%
7-Jul	0.74	63,513	6,351	0.72	62,590	6,259	1%	predicted volume over 10%
8-Jul	0.71	61,335	6,134	0.70	60,154	6,015	2%	predicted volume over 10%
9-Jul	0.69	59,262	5,926	0.66	57,266	5,727	3%	predicted volume over 10%
10-Jul	0.67	57,582	5,758	0.63	54,776	5,478	5%	predicted volume over 10%
11-Jul	0.62	53,268	5,327	0.61	52,839	5,284	1%	predicted volume over 10%
12-Jul	0.59	51,319	5,132	0.58	50,185	5,019	2%	predicted volume over 10%
13-Jul	0.57	49,488	4,949	0.55	47,939	4,794	3%	predicted volume over 10%
14-Jul	0.54	46,648	4,665	0.54	46,697	4,670	0%	predicted volume under 10%
15-Jul	0.52	44,891	4,489	0.53	45,725	4,572	-2%	predicted volume under 10%
16-Jul	0.51	44,115	4,411	0.52	44,930	4,493	-2%	predicted volume under 10%
17-Jul	0.49	42,745	4,275	0.50	43,626	4,363	-2%	predicted volume under 10%
18-Jul	0.48	41,447	4,145	0.50	42,827	4,283	-3%	predicted volume under 10%

Table A.1. Predicted (Regression Model) and Recorded (June 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
19-Jul	0.48	41,889	4,189	0.49	42,316	4,232	-1%	predicted volume under 10%
20-Jul	0.48	41,041	4,104	0.47	40,354	4,035	2%	predicted volume over 10%
21-Jul	0.47	40,227	4,023	0.45	38,549	3,855	4%	predicted volume over 10%
22-Jul	0.44	38,295	3,829	0.43	37,199	3,720	3%	predicted volume over 10%
23-Jul	0.43	37,315	3,731	0.42	36,551	3,655	2%	predicted volume over 10%
24-Jul	0.42	36,379	3,638	0.42	36,018	3,602	1%	predicted volume over 10%
25-Jul	0.40	34,555	3,456	0.40	34,828	3,483	-1%	predicted volume under 10%
26-Jul	0.39	33,631	3,363	0.38	33,252	3,325	1%	predicted volume over 10%
27-Jul	0.38	32,748	3,275	0.37	32,210	3,221	2%	predicted volume over 10%
28-Jul	0.36	31,443	3,144	0.35	30,331	3,033	4%	predicted volume over 10%
29-Jul	0.35	30,506	3,051	0.35	29,868	2,987	2%	predicted volume over 10%
30-Jul	0.34	29,612	2,961	0.34	29,051	2,905	2%	predicted volume over 10%
31-Jul	0.33	28,171	2,817	0.31	27,152	2,715	4%	predicted volume over 10%
1-Aug	0.32	27,329	2,733	0.31	27,089	2,709	1%	predicted volume over 10%
2-Aug	0.31	26,525	2,652	0.30	25,511	2,551	4%	predicted volume over 10%
3-Aug	0.29	24,783	2,478	0.29	24,797	2,480	0%	predicted volume under 10%
4-Aug	0.28	23,918	2,392	0.28	24,026	2,403	0%	predicted volume under 10%
5-Aug	0.27	23,096	2,310	0.26	22,845	2,285	1%	predicted volume over 10%
6-Aug	0.26	22,255	2,225	0.26	22,246	2,225	0%	predicted volume over 10%
7-Aug	0.25	21,474	2,147	0.24	20,848	2,085	3%	predicted volume over 10%
8-Aug	0.24	20,732	2,073	0.23	20,106	2,011	3%	predicted volume over 10%
9-Aug	0.22	19,371	1,937	0.23	19,564	1,956	-1%	predicted volume under 10%
10-Aug	0.22	18,593	1,859	0.22	18,786	1,879	-1%	predicted volume under 10%
11-Aug	0.21	17,857	1,786	0.21	17,986	1,799	-1%	predicted volume under 10%
12-Aug	0.20	17,601	1,760	0.20	17,368	1,737	1%	predicted volume over 10%
13-Aug	0.20	17,040	1,704	0.19	16,517	1,652	3%	predicted volume over 10%
14-Aug	0.19	16,505	1,650	0.18	15,903	1,590	4%	predicted volume over 10%
15-Aug	0.18	15,587	1,559	0.17	14,565	1,457	7%	predicted volume over 10%
16-Aug	0.17	15,049	1,505	0.16	14,105	1,411	7%	predicted volume over 10%
17-Aug	0.17	14,535	1,454	0.16	13,427	1,343	8%	predicted volume over 10%
18-Aug	0.15	12,951	1,295	0.15	12,871	1,287	1%	predicted volume over 10%
19-Aug	0.14	12,311	1,231	0.14	11,923	1,192	3%	predicted volume over 10%
20-Aug	0.14	11,709	1,171	0.13	11,637	1,164	1%	predicted volume over 10%
21-Aug	0.13	11,144	1,114	0.13	10,848	1,085	3%	predicted volume over 10%
22-Aug	0.12	10,613	1,061	0.12	10,567	1,057	0%	predicted volume over 10%
23-Aug	0.12	10,113	1,011	0.11	9,909	991	2%	predicted volume over 10%
24-Aug	0.11	9,643	964	0.09	7,756	776	24%	predicted volume over 10%
25-Aug	0.11	9,200	920	0.09	7,558	756	22%	predicted volume over 10%
26-Aug	0.10	8,782	878	0.09	7,472	747	18%	predicted volume over 10%
27-Aug	0.10	8,387	839	0.08	7,319	732	15%	predicted volume over 10%
28-Aug	0.09	8,015	802	0.09	7,486	749	7%	predicted volume over 10%
29-Aug	0.09	7,663	766	0.08	7,234	723	6%	predicted volume over 10%
30-Aug	0.08	7,331	733	0.08	7,063	706	4%	predicted volume over 10%

Table A.1. Predicted (Regression Model) and Recorded (June 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
31-Aug	0.08	7,016	702	0.08	7,075	707	-1%	predicted volume under 10%
1-Sep	0.08	6,718	672	0.09	7,372	737	-9%	predicted volume under 10%
2-Sep	0.07	6,436	644	0.08	7,145	715	-10%	predicted volume under 10%
3-Sep	0.07	6,169	617	0.08	6,923	692	-11%	predicted volume under 10%
4-Sep	0.07	5,915	592	0.09	7,345	735	-19%	predicted volume under 10%
5-Sep	0.07	5,675	567	0.08	6,797	680	-17%	predicted volume under 10%
6-Sep	0.06	5,446	545	0.08	7,096	710	-23%	predicted volume under 10%
7-Sep	0.06	5,229	523	0.08	7,127	713	-27%	predicted volume under 10%
8-Sep	0.06	5,023	502	0.08	7,142	714	-30%	predicted volume under 10%
9-Sep	0.06	4,827	483	0.08	7,030	703	-31%	predicted volume under 10%

^a Predicted from regression model

^b Calculated from stage-discharge rating equation established in June 2013

Table A.2. Predicted (Regression Model) and Recorded (October 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
6-Jun	0.22	18,870	1,887	0.27	23,575	2,357	-20%	predicted volume under 10%
7-Jun	0.30	25,730	2,573	0.33	28,565	2,857	-10%	predicted volume under 10%
8-Jun	0.37	32,383	3,238	0.41	35,026	3,503	-8%	predicted volume under 10%
9-Jun	0.45	38,828	3,883	0.48	41,143	4,114	-6%	predicted volume under 10%
10-Jun	0.52	45,066	4,507	0.54	47,029	4,703	-4%	predicted volume under 10%
11-Jun	0.59	51,097	5,110	0.61	53,096	5,310	-4%	predicted volume under 10%
12-Jun	0.66	56,920	5,692	0.68	58,906	5,891	-3%	predicted volume under 10%
13-Jun	0.72	62,536	6,254	0.75	64,584	6,458	-3%	predicted volume under 10%
14-Jun	0.79	67,945	6,794	0.81	69,986	6,999	-3%	predicted volume under 10%
15-Jun	0.85	73,146	7,315	0.87	74,899	7,490	-2%	predicted volume under 10%
16-Jun	0.90	78,140	7,814	0.91	78,926	7,893	-1%	predicted volume under 10%
17-Jun	0.96	82,927	8,293	0.95	81,938	8,194	1%	predicted volume over 10%
18-Jun	1.01	87,506	8,751	0.97	83,560	8,356	5%	predicted volume over 10%
19-Jun	1.06	91,878	9,188	0.97	84,045	8,405	9%	predicted volume over 10%
20-Jun	0.95	82,469	8,247	0.97	83,910	8,391	-2%	predicted volume under 10%
21-Jun	0.93	80,551	8,055	0.98	84,748	8,475	-5%	predicted volume under 10%
22-Jun	0.90	77,388	7,739	0.98	84,405	8,441	-8%	predicted volume under 10%
23-Jun	0.96	82,771	8,277	0.97	84,105	8,410	-2%	predicted volume under 10%
24-Jun	0.95	81,994	8,199	0.96	83,188	8,319	-1%	predicted volume under 10%
25-Jun	0.94	80,784	8,078	0.94	81,436	8,144	-1%	predicted volume under 10%
26-Jun	0.93	80,145	8,014	0.92	79,711	7,971	1%	predicted volume over 10%
27-Jun	0.88	76,326	7,633	0.91	78,389	7,839	-3%	predicted volume under 10%
28-Jun	0.86	74,503	7,450	0.88	75,746	7,575	-2%	predicted volume under 10%
29-Jun	0.84	72,636	7,264	0.86	74,703	7,470	-3%	predicted volume under 10%
30-Jun	0.82	70,667	7,067	0.83	71,758	7,176	-2%	predicted volume under 10%
1-Jul	0.77	66,830	6,683	0.84	72,341	7,234	-8%	predicted volume under 10%
2-Jul	0.75	64,990	6,499	0.82	70,857	7,086	-8%	predicted volume under 10%
3-Jul	0.80	69,503	6,950	0.83	71,468	7,147	-3%	predicted volume under 10%
4-Jul	0.79	68,629	6,863	0.81	69,969	6,997	-2%	predicted volume under 10%
5-Jul	0.78	67,793	6,779	0.78	67,716	6,772	0%	predicted volume over 10%
6-Jul	0.76	65,396	6,540	0.76	65,680	6,568	0%	predicted volume under 10%
7-Jul	0.74	63,513	6,351	0.73	63,291	6,329	0%	predicted volume over 10%
8-Jul	0.71	61,335	6,134	0.70	60,851	6,085	1%	predicted volume over 10%
9-Jul	0.69	59,262	5,926	0.67	57,984	5,798	2%	predicted volume over 10%
10-Jul	0.67	57,582	5,758	0.64	55,574	5,557	4%	predicted volume over 10%
11-Jul	0.62	53,268	5,327	0.62	53,636	5,364	-1%	predicted volume under 10%
12-Jul	0.59	51,319	5,132	0.59	51,022	5,102	1%	predicted volume over 10%
13-Jul	0.57	49,488	4,949	0.56	48,805	4,881	1%	predicted volume over 10%
14-Jul	0.54	46,648	4,665	0.55	47,661	4,766	-2%	predicted volume under 10%
15-Jul	0.52	44,891	4,489	0.54	46,677	4,668	-4%	predicted volume under 10%
16-Jul	0.51	44,115	4,411	0.53	45,854	4,585	-4%	predicted volume under 10%
17-Jul	0.49	42,745	4,275	0.51	44,482	4,448	-4%	predicted volume under 10%
18-Jul	0.48	41,447	4,145	0.51	43,785	4,379	-5%	predicted volume under 10%

Table A.2. Predicted (Regression Model) and Recorded (October 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
19-Jul	0.48	41,889	4,189	0.50	43,176	4,318	-3%	predicted volume under 10%
20-Jul	0.48	41,041	4,104	0.48	41,223	4,122	0%	predicted volume under 10%
21-Jul	0.47	40,227	4,023	0.46	39,456	3,946	2%	predicted volume over 10%
22-Jul	0.44	38,295	3,829	0.44	38,130	3,813	0%	predicted volume over 10%
23-Jul	0.43	37,315	3,731	0.43	37,489	3,749	0%	predicted volume under 10%
24-Jul	0.42	36,379	3,638	0.43	37,001	3,700	-2%	predicted volume under 10%
25-Jul	0.40	34,555	3,456	0.41	35,700	3,570	-3%	predicted volume under 10%
26-Jul	0.39	33,631	3,363	0.40	34,173	3,417	-2%	predicted volume under 10%
27-Jul	0.38	32,748	3,275	0.38	33,143	3,314	-1%	predicted volume under 10%
28-Jul	0.36	31,443	3,144	0.36	31,312	3,131	0%	predicted volume over 10%
29-Jul	0.35	30,506	3,051	0.36	30,850	3,085	-1%	predicted volume under 10%
30-Jul	0.34	29,612	2,961	0.35	30,044	3,004	-1%	predicted volume under 10%
31-Jul	0.33	28,171	2,817	0.33	28,152	2,815	0%	predicted volume over 10%
1-Aug	0.32	27,329	2,733	0.32	28,051	2,805	-3%	predicted volume under 10%
2-Aug	0.31	26,525	2,652	0.31	26,535	2,653	0%	predicted volume under 10%
3-Aug	0.29	24,783	2,478	0.30	25,822	2,582	-4%	predicted volume under 10%
4-Aug	0.28	23,918	2,392	0.29	25,030	2,503	-4%	predicted volume under 10%
5-Aug	0.27	23,096	2,310	0.28	23,762	2,376	-3%	predicted volume under 10%
6-Aug	0.26	22,255	2,225	0.27	23,208	2,321	-4%	predicted volume under 10%
7-Aug	0.25	21,474	2,147	0.25	21,889	2,189	-2%	predicted volume under 10%
8-Aug	0.24	20,732	2,073	0.25	21,251	2,125	-2%	predicted volume under 10%
9-Aug	0.22	19,371	1,937	0.24	20,585	2,058	-6%	predicted volume under 10%
10-Aug	0.22	18,593	1,859	0.23	19,856	1,986	-6%	predicted volume under 10%
11-Aug	0.21	17,857	1,786	0.22	19,044	1,904	-6%	predicted volume under 10%
12-Aug	0.20	17,601	1,760	0.21	18,412	1,841	-4%	predicted volume under 10%
13-Aug	0.20	17,040	1,704	0.20	17,578	1,758	-3%	predicted volume under 10%
14-Aug	0.19	16,505	1,650	0.20	16,915	1,691	-2%	predicted volume under 10%
15-Aug	0.18	15,587	1,559	0.18	15,553	1,555	0%	predicted volume over 10%
16-Aug	0.17	15,049	1,505	0.18	15,177	1,518	-1%	predicted volume under 10%
17-Aug	0.17	14,535	1,454	0.17	14,498	1,450	0%	predicted volume over 10%
18-Aug	0.15	12,951	1,295	0.16	13,978	1,398	-7%	predicted volume under 10%
19-Aug	0.14	12,311	1,231	0.15	12,984	1,298	-5%	predicted volume under 10%
20-Aug	0.14	11,709	1,171	0.15	12,730	1,273	-8%	predicted volume under 10%
21-Aug	0.13	11,144	1,114	0.14	11,910	1,191	-6%	predicted volume under 10%
22-Aug	0.12	10,613	1,061	0.14	11,698	1,170	-9%	predicted volume under 10%
23-Aug	0.12	10,113	1,011	0.13	10,804	1,080	-6%	predicted volume under 10%
24-Aug	0.11	9,643	964	0.10	8,886	889	9%	predicted volume over 10%
25-Aug	0.11	9,200	920	0.10	8,624	862	7%	predicted volume over 10%
26-Aug	0.10	8,782	878	0.10	8,560	856	3%	predicted volume over 10%
27-Aug	0.10	8,387	839	0.10	8,390	839	0%	predicted volume under 10%
28-Aug	0.09	8,015	802	0.10	8,536	854	-6%	predicted volume under 10%
29-Aug	0.09	7,663	766	0.10	8,263	826	-7%	predicted volume under 10%
30-Aug	0.08	7,331	733	0.09	8,081	808	-9%	predicted volume under 10%

Table A.2. Predicted (Regression Model) and Recorded (October 2013 Rating Curve) Total Daily Flow Volumes for Doris TL-2, June 6-September 9, 2013

Date	Predicted Mean Daily Flow (m ³ /s) ^a	Predicted Total Daily Flow (m ³ /day)	10% Allowable from Predicted Flow (m ³ /day)	Recorded Mean Daily Flow (m ³ /s) ^b	Recorded Total Daily Flow (m ³ /day)	10% Allowable from Recorded Flow (m ³ /day)	Prediction Error (% Difference Between Predicted and Recorded Daily Flow)	Notes
31-Aug	0.08	7,016	702	0.09	8,066	807	-13%	predicted volume under 10%
1-Sep	0.08	6,718	672	0.10	8,372	837	-20%	predicted volume under 10%
2-Sep	0.07	6,436	644	0.09	8,043	804	-20%	predicted volume under 10%
3-Sep	0.07	6,169	617	0.09	7,915	792	-22%	predicted volume under 10%
4-Sep	0.07	5,915	592	0.10	8,288	829	-29%	predicted volume under 10%
5-Sep	0.07	5,675	567	0.09	7,789	779	-27%	predicted volume under 10%
6-Sep	0.06	5,446	545	0.09	8,032	803	-32%	predicted volume under 10%
7-Sep	0.06	5,229	523	0.09	8,047	805	-35%	predicted volume under 10%
8-Sep	0.06	5,023	502	0.09	8,047	805	-38%	predicted volume under 10%
9-Sep	0.06	4,827	483	0.09	7,916	792	-39%	predicted volume under 10%

^a Predicted from regression model

^b Calculated from stage-discharge rating equation established in October 2013

DORIS NORTH PROJECT
2013 Hydrology Compliance Monitoring Report

Appendix G

Lake Water Level Tables



Appendix G-1. Mean Daily Water Levels (m) at Doris Lake in 2013

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	97.791	97.793	97.795	97.800	97.801	97.823	98.092	97.945	97.821			
2	97.791	97.792	97.794	97.800	97.801	97.837	98.095	97.944	97.824			
3	97.790	97.792	97.794	97.801	97.801	97.855	98.087	97.937	97.821			
4	97.790	97.792	97.795	97.801	97.801	97.865	98.091	97.934	97.820			
5	97.792	97.792	97.795	97.801	97.801	97.883	98.082	97.930	97.819			
6	97.792	97.792	97.795	97.802	97.801	97.912	98.074	97.923	97.820			
7	97.791	97.792	97.797	97.802	97.801	97.942	98.065	97.921	97.823			
8	97.791	97.792	97.798	97.799	97.802	97.970	98.056	97.914	97.824			
9	97.791	97.793	97.798	97.799	97.801	98.000	98.047	97.910	97.822			
10	97.792	97.793	97.798	97.798	97.800	98.025	98.042	97.907	97.819			
11	97.792	97.792	97.797	97.797	97.800	98.043	98.041	97.903				
12	97.792	97.791	97.799	97.799	97.800	98.062	98.034	97.898				
13	97.792	97.792	97.801	97.799	97.799	98.080	98.035	97.894				
14	97.793	97.794	97.801	97.800	97.798	98.096	98.028	97.889				
15	97.793	97.794	97.801	97.800	97.798	98.111	98.023	97.885				
16	97.794	97.794	97.801	97.800	97.798	98.123	98.020	97.877				
17	97.793	97.794	97.800	97.799	97.797	98.133	98.017	97.875				
18	97.792	97.794	97.799	97.799	97.799	98.139	98.012	97.870				
19	97.793	97.794	97.800	97.800	97.800	98.144	98.009	97.866				
20	97.792	97.793	97.801	97.800	97.800	98.143	98.007	97.860				
21	97.792	97.794	97.801	97.800	97.799	98.140	98.000	97.861				
22	97.790	97.795	97.799	97.799	97.799	98.139	97.993	97.855				
23	97.792	97.794	97.798	97.799	97.799	98.137	97.988	97.852				
24	97.793	97.794	97.799	97.799	97.799	98.133	97.985	97.844				
25	97.792	97.794	97.799	97.799	97.799	98.130	97.983	97.832				
26	97.792	97.795	97.798	97.799	97.803	98.126	97.978	97.826				
27	97.792	97.795	97.798	97.801	97.806	98.120	97.971	97.823				
28	97.792	97.796	97.798	97.801	97.808	98.112	97.967	97.824				
29	97.793		97.799	97.801	97.809	98.104	97.959	97.824				
30	97.793		97.800	97.801	97.812	98.098	97.957	97.822				
31	97.793		97.800		97.818		97.953	97.821				
Mean	97.792	97.793	97.798	97.800	97.802	98.047	98.022	97.880	97.821			
Max	97.794	97.796	97.801	97.802	97.818	98.144	98.095	97.945	97.824			
Min	97.790	97.791	97.794	97.797	97.797	97.823	97.953	97.821	97.819			

Note: Lake water levels affected by ice are italicized. Red text denotes estimated values.

Appendix G-2. Mean Daily Water Levels (m) at Tail Lake in 2013

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1	94.015	94.010	94.012	94.010	94.001	94.040	94.144	93.978	93.869			
2	94.015	94.007	94.009	94.010	94.006	94.052	94.147	93.974	93.875			
3	94.015	94.004	94.008	94.011	94.006	94.069	94.139	93.968	93.876			
4	94.013	94.004	94.010	94.011	94.006	94.077	94.140	93.964	93.875			
5	94.013	94.004	94.010	94.011	94.006	94.083	94.132	93.958	93.876			
6	94.009	94.003	94.010	94.011	94.006	94.099	94.124	93.952	93.875			
7	94.008	94.003	94.011	94.010	94.006	94.116	94.115	93.947	93.881			
8	94.009	94.004	94.012	94.008	94.006	94.128	94.107	93.942	93.882			
9	94.009	94.004	94.012	94.007	94.004	94.145	94.098	93.938	93.882			
10	94.009	94.005	94.011	94.006	94.004	94.157	94.089	93.933				
11	94.008	94.004	94.011	94.006	94.003	94.164	94.080	93.929				
12	94.008	94.003	94.011	94.005	94.003	94.171	94.072	93.926				
13	94.008	94.004	94.012	94.007	94.000	94.175	94.062	93.923				
14	94.008	94.005	94.013	94.008	93.996	94.180	94.056	93.920				
15	94.009	94.005	94.013	94.008	93.997	94.186	94.051	93.920				
16	94.009	94.003	94.014	94.009	93.997	94.192	94.049	93.915				
17	94.008	94.010	94.011	94.009	93.997	94.197	94.047	93.912				
18	94.007	94.010	94.009	94.009	93.997	94.201	94.045	93.906				
19	94.006	94.010	94.009	94.009	93.998	94.203	94.040	93.903				
20	94.005	94.010	94.010	94.008	93.998	94.202	94.035	93.900				
21	94.009	94.009	94.012	94.007	93.998	94.203	94.029	93.896				
22	94.005	94.009	94.010	94.005	94.002	94.204	94.022	93.893				
23	94.011	94.009	94.009	94.005	94.003	94.196	94.016	93.893				
24	94.012	94.009	94.008	94.006	94.004	94.189	94.012	93.890				
25	94.011	94.009	94.008	94.002	94.004	94.183	94.010	93.880				
26	94.005	94.009	94.008	94.002	94.006	94.179	94.006	93.878				
27	94.004	94.010	94.008	94.002	94.008	94.172	94.002	93.875				
28	94.004	94.012	94.008	94.002	94.012	94.164	93.996	93.877				
29	94.008		94.008	94.002	94.019	94.157	93.989	93.879				
30	94.010		94.009	94.002	94.026	94.151	93.984	93.874				
31	94.011		94.010		94.033		93.982	93.870				
Mean	94.009	94.007	94.010	94.007	94.005	94.155	94.059	93.917	93.877			
Max	94.015	94.012	94.014	94.011	94.033	94.204	94.147	93.978	93.882			
Min	94.004	94.003	94.008	94.002	93.996	94.040	93.982	93.870	93.869			

Note: Lake water levels affected by ice are italicized.

Appendix G-3. Mean Daily Water Levels (m) at Windy Lake in 2013

2013	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
1							94.997	94.993	94.913			
2							95.005	94.992	94.917			
3							95.005	94.989	94.918			
4							95.017	94.987	94.918			
5							95.014	94.984	94.917			
6						94.962	95.012	94.982	94.917			
7						94.965	95.011	94.978	94.918			
8						94.971	95.009	94.975	94.918			
9						94.981	95.008	94.974	94.916			
10						94.989	95.007	94.972				
11						94.990	95.005	94.971				
12						94.994	95.004	94.968				
13						94.997	95.002	94.967				
14						94.999	95.000	94.965				
15						95.000	95.001	94.963				
16						95.002	95.001	94.959				
17						95.004	95.005	94.957				
18						95.005	95.008	94.953				
19						95.004	95.008	94.951				
20						95.002	95.006	94.948				
21						95.001	95.005	94.945				
22						95.000	95.003	94.941				
23						95.002	95.002	94.940				
24						95.001	95.002	94.935				
25						95.001	95.004	94.919				
26						95.001	95.004	94.918				
27						94.999	95.001	94.916				
28						94.997	95.000	94.917				
29						94.996	94.998	94.917				
30						94.996	94.999	94.914				
31						94.996	94.996	94.914				
Mean						94.994	95.004	94.955	94.917			
Max						95.005	95.017	94.993	94.918			
Min						94.962	94.996	94.914	94.913			