Engineering Drawings for the Doris Connector Vent Raise Access Road, Doris North Project, Nunavut, Canada


ACTIVE DRAWING STATUS


DWG NUMBER	DRAWING TITLE	REVISION	DATE	STATUS
DCVR-00	Engineering Drawings for the Doris Connector Vent Raise Access Road, Doris North Project, Nunavut, Canada	0	Aug 08, 2018	Issued For Construction
DCVR-01	General Arrangement	0	Aug 08, 2018	Issued For Construction
DCVR-02	Doris Connector Vent Raise Access Road Plan and Profile	0	Aug 08, 2018	Issued For Construction
DCVR-03	Culvert Design	0	Aug 08, 2018	Issued For Construction
DCVR-04	Typical Sections and Details	0	Aug 08, 2018	Issued For Construction
DCVR-05	Material List and Quantity Estimates	0	Aug 08, 2018	Issued For Construction







PROJECT NO: 1CT022.030 Revision 0 August 8, 2018 Drawing DCVR-00








REFERENCE DRAWINGS



DETAIL 1 TYPICAL CROSS SECTION OF CULVERT CROSSING



TYPICAL CROSS SECTION OF CULVERT INLET/OUTLET

NOT TO SCALE

srk consulting

STAMP FILE NAME 1CT022 030 Doris Vent Raise_Rev0.dwg

August 8, 2018

SRK JOB NO

LICENSE

0 Issued for Construction
NO DESCRIPTION

10/24/18

Installation of the corrugated steel culvert will follow the manufacturers assembly and installation guide. Total depth of cover above culvert, including hedding manufacturers.

Surfacing Material

Bedding Material

Run of Quarry Material

Rip Rap, $D_{50} = 0.15$ m

Non-woven Geotextile Road Centerline Major Contour

Approx, High Water Mark
Approx, Unnamed Stream Alignment

Original Ground

Minor Contour

LEGEND

NOTES

- Total depth of cover above culvert, including bedding material, surfacing material and ROQ, will be 1,0 m minimum.

 The second of the factor of the factor
- Topographic contour data for the terrain model were provided by Hope Bay Mining Ltd, and is based on 2007 Aerial Photography, Contour intervals are 0,5 m.

1. All dimensions are in metric units, unless otherwise noted.

- 5. Coordinate system is UTM Zone 13, datum NAD83,
- 6. Culvert alignment will be field fit to match stream alignment.

Doris Connector Vent Raise Access Road

Culvert Design

SHEET


4 OF 6

0

DRAWING TITLE:


DCVR-03

7. Additional notes located on DCVR-05



HOPE BAY PROJECT

1CT022 030



Materials List and Quantity Estimates

Item	Quantity / Area / Volume		Description
1. Run of Quarry Material	Doris Connector Vent Raise Access Road Total	ROQ (cu.m.) 4,420 4,420	Approximate In-Place Neat-line Volume (3D volume based on Civil 3D surfaces - no allowance has been made for losses and/or tundra embedment)
2. Surface Material	Doris Connector Vent Raise Access Road Total	Surfacing Material (cu.m.) 330	Approximate In-Place Neat-line Volume
Bedding Material	Culvert Crossing	Bedding Material (cu.m.) 34	Approximate In-Place Neat-line Volume
4. Rip Rap	Culvert Crossing	Bedding Material (cu.m.)	Approximate In-Place Neat-line Volume D ₅₀ = 0.15m
5. Culvert	Culvert Crossing	Steal Pipe Culvert (each)	AIL Corrugated Steel Pipe 68x13 corrugated profile 500mm diameter Length = 22000mm

Tolerances on Road Material Placement:

Location	Fill (mm)	Excavation (mm)	
Vertical Tolerance on Roads	0 to +75	n/a	
Horizontal Tolerance on Roads	-150 to +150		

Note: Grade shall not be uniformly high or low.

NOTES - GENERAL


- 1. The Engineer will provide the Construction Manager and Contractor with digital design files for setting out the works. The Engineer will instruct the Contractor to survey random spot checks to confirm whether the works have been set out
- 2. Construction shall be in accordance with the following; Technical Specifications: Earthworks and Geotechnical Engineering, Hope Bay project, Nunavut, Canada, Revision H - Issued for Construction.
- 3. A temporary free-span crossing (design by others) may be constructed to reach the opposite stream bank to allow construction to advance prior to installing the culvert.
- 4. Construction can be completed during the summer or winter in accordance with the normal construction procedures used on site for roads and rockfill pads.
- Construction must be in accordance with appropriate DFO guidelines for self-assessment,
- 6. Notes in this drawing apply to all other active drawings.

NOTES - CULVERT

- 1. Culvert installation should be carried out from the edge of the road, with no need for temporary access to the tundra or streambed by equipment.
- 2. All fuels, lubricants and other potentially hazardous materials must be stored outside the riparian management area of the stream, in locations designated for such storage on site.
- 3. A non-woven geotextile must be placed along the surface of natural ground in the culvert's footprint, to prevent loss of fines and gravels through seepage along the culvert.
- 4. Once the culvert is in place, backfill lifts of 0.3m must be placed on either side using bedding material, and are compacted to 85% Standard Proctor Density.

NOTES - SEDIMENT AND EROSION CONTROL

- 1. If required, sandbags are to be placed by hand to create a small coffer dam approximately 5m upstream of the proposed culvert installation location.
- 2. Ponded water (maximum head of about 0.5m) which accumulates behind the sand bags must be pumped around the construction area and discharged back into the stream about 10m downstream of the culvert.
- 3. A flow energy dissipation blanket (likely old conveyor belt, or something equivalent) must be used to ensure erosion is minimized from pump outlet
- 4, A silt fence must be installed approximately 5m downstream of the construction area to contain any sediment that may become mobile should a rainfall event occur during construction.





*	srk cor	consulting	
DESIGN	DRAWN DP	REVIEWED:	

APPROVED: EMR HOPE BAY PROJECT August 8, 2018



Doris Connector Vent Raise Access Road

Material List and Quantity Estimates

DCVR-05

SHEET 6 OF 6

0