

Project #: 09-1428-5007  
 Short Title: Meadowbank Gold Project  
 Client: AEM  
 Location: Nunavut  
 Lab ID: 41

Field Label	SWD110609-1		SWD110609-2			
Sample Number	194		195			
Sample Location	Sta. 10+565		Sta. 10+440			
Depth (m)						
Mass of Dry Soil (g)	4101.5		4229.3			
Water Content W (%)	1.5		1.2			

Field Label						
Sample Number						
Sample Location						
Depth (m)						
Mass of Dry Soil (g)						
Water Content W (%)						

Field Label						
Sample Number						
Sample Location						
Depth (m)						
Mass of Dry Soil (g)						
Water Content W (%)						

Field Label						
Sample Number						
Sample Location						
Depth (m)						
Mass of Dry Soil (g)						
Water Content W (%)						

PC  
TESTED BY

Mar 12-10  
DATE TESTED

LP  
CHECKED BY

March 15,2010  
DATE CHECKED



**Golder Associates Ltd.**  
 500 - 4260 Still Creek Drive, Burnaby, British  
 Columbia, Canada V5C 6C6  
 Tel: +1 (604) 296 4200 Fax: +1 (604) 298 5253 www.golder.com



---

Project #: 08-1429-0029  
Short Title: Meadowbank Gold Mine  
Client: AEM  
Location: Nunavut  
Lab ID: Sheet No. 1

---

Field Label	SWD091909-1	SWD091909-2	SWD091909-4			
Sample Number	71	72	74			
Sample Location	SWD Sta. 10+380	SWD Sta. 10+360	SWD Sta. 10+430			
Material Spec.	Fine filter	Fine filter	Fine filter			
Depth (m)	-	-	-			
Mass of Dry Soil (g)	2984.6	2527.6	2312.9			
Water Content W (%)	<b>5.6</b>	<b>5.9</b>	<b>6.9</b>			

RB

September 22, 2009

TESTED BY

DATE TESTED

CHECKED BY

DATE CHECKED



**Golder Associates Ltd.**  
500 - 4260 Still Creek Drive, Burnaby, British  
Columbia, Canada V5C 6C6  
Tel: +1 (604) 296 4200 Fax: +1 (604) 298 5253 [www.golder.com](http://www.golder.com)



## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **28**
**Field Label:** TSF090409-01

**Depth (m):** NA

**Lab ID No:** SA28

**Remarks:** Water content = 1.3%

**Sa. Location:** SWD Sta. 10+460 Bedding layer in place


**Date Sampled:** September 4, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 5, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	96.7
1/2"	12.5	85.6
3/8"	9.5	73.2
#4	4.8	53.4
#10	2.0	34.6
#20	0.9	23.9
#40	0.4	18.8
#60	0.3	16.1
#100	0.2	14.3
#200	0.1	12.8



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

DE

September 5, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **38**
**Field Label:** TSF090609-05

**Depth (m):** NA

**Lab ID No:** SA38

**Remarks:** Water content= 1.4%

**Sa. Location:** SWD Sta. 10+470 Bedding layer in place


**Date Sampled:** September 6, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 8, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	100.0
1/2"	12.5	90.5
3/8"	9.5	78.4
#4	4.8	57.3
#10	2.0	39.6
#20	0.9	28.5
#40	0.4	22.6
#60	0.3	19.2
#100	0.2	16.8
#200	0.1	14.4



BOULDER	COBBLE	GRAVEL		SAND			FINES (Silt, Clay)
		Coarse	Fine	Coarse	Medium	Fine	

\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

DE

September 8, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **71**
**Field Label:** SWD 091909-03

**Depth (m):** NA

**Lab ID No:** SA71

**Remarks:** Water content=5.5%

**Sa. Location:** SWD Sta. 10+380 Bedding layer in place


**Date Sampled:** September 19, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	99.3
1/2"	12.5	90.2
3/8"	9.5	76.9
#4	4.8	54.1
#10	2.0	36.0
#20	0.9	25.8
#40	0.4	20.6
#60	0.3	17.8
#100	0.2	15.8
#200	0.1	14.0



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **72**
**Field Label:** SWD 091909-04

**Depth (m):** NA

**Lab ID No:** SA72

**Remarks:** Water content=2.0%

**Sa. Location:** SWD Sta. 10+360 Bedding layer in place


**Date Sampled:** September 19, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	90.6
1/2"	12.5	77.5
3/8"	9.5	69.5
#4	4.8	52.4
#10	2.0	35.0
#20	0.9	23.5
#40	0.4	17.7
#60	0.3	14.5
#100	0.2	12.2
#200	0.1	10.1



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

DE	September 23, 2009		
TESTED BY	DATE	CHECKED BY	DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **73**
**Field Label:** SWD 091909-05

**Depth (m):** NA

**Lab ID No:** SA73

**Remarks:** Water content=3.1%

**Sa. Location:** SWD Sta. 10+310 Bedding layer in place


**Date Sampled:** September 19, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	95.7
1/2"	12.5	75.7
3/8"	9.5	66.4
#4	4.8	48.1
#10	2.0	34.0
#20	0.9	24.2
#40	0.4	19.2
#60	0.3	16.5
#100	0.2	14.5
#200	0.1	12.7



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **74**
**Field Label:** SWD 091909-06

**Depth (m):** NA

**Lab ID No:** SA74

**Remarks:** Water content=5.3%

**Sa. Location:** SWD Sta. 10+430 Bedding layer in place


**Date Sampled:** September 19, 2009

**Material Specification:** Fine filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	98.9
1/2"	12.5	89.2
3/8"	9.5	78.8
#4	4.8	59.4
#10	2.0	42.1
#20	0.9	30.5
#40	0.4	24.5
#60	0.3	21.3
#100	0.2	19.0
#200	0.1	16.7



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE



## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **75**
**Field Label:** SWD 091909-07

**Depth (m):** NA

**Lab ID No:** SA75

**Remarks:** Water content= 1.6%

**Sa. Location:** SWD Sta. 10+270 Bedding layer in place


**Date Sampled:** September 19, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	90.1
1/2"	12.5	73.5
3/8"	9.5	65.3
#4	4.8	48.7
#10	2.0	32.1
#20	0.9	22.0
#40	0.4	17.0
#60	0.3	14.3
#100	0.2	12.4
#200	0.1	10.5



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **76**
**Field Label:** SWD-091909-0

**Depth (m):** N/A

**Lab ID No:** SA-76

**Remarks:** Water content = 5,3%

**Sa. Location:** SWD Sta. 10+430 Bedding layer in place


**Sampling Date:** September 19, 2009

**Material Specification:** Fine Filter

**Method:** SPLIT, WASHED

**Date Tested:** September 20, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	97.8
1/2"	12.5	85.6
3/8"	9.5	69.0
#4	4.8	50.7
#10	2.0	37.0
#20	0.9	27.4
#40	0.4	21.9
#60	0.3	18.8
#100	0.2	16.5
#200	0.1	15.2



*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

OM	September 20, 2009		
TESTED BY	DATE	CHECKED BY	DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **80**
**Field Label:** SWD 092109-01

**Depth (m):** NA

**Lab ID No:** SA80

**Remarks:** Water content=5.8%

**Sa. Location:** SWD Sta. 10+810 Bedding layer in place


**Date Sampled:** September 21, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	100.0
1/2"	12.5	90.1
3/8"	9.5	74.6
#4	4.8	51.9
#10	2.0	32.7
#20	0.9	22.9
#40	0.4	18.3
#60	0.3	15.7
#100	0.2	13.8
#200	0.1	11.8



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 08-1428-0029 (5000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **81**
**Field Label:** SWD 092109-02

**Depth (m):** NA

**Lab ID No:** SA81

**Remarks:** Water content=5.7%

**Sa. Location:** SWD Sta. 10+835 Bedding layer in place


**Date Sampled:** September 21, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** September 23, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	100.0
1/2"	12.5	90.6
3/8"	9.5	80.8
#4	4.8	59.1
#10	2.0	40.6
#20	0.9	28.2
#40	0.4	22.2
#60	0.3	19.0
#100	0.2	16.7
#200	0.1	14.4



\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

DE

September 23, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007 (2000)

**Sample No.:** **179**
**Client:** AEM

**Field Label:** SWD 102409-02

**Project:** Meadowbank Gold Project

**Depth (m):** NA

**Location:** Nunavut

**Lab ID No:** SA179

**Remarks:** Water content=0.8%

**Date Sampled:** October 24, 2009


**Sa. Location:** SWD Sta. 10+640 Bedding layer in place El. 135.5m

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** October 31, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	87.3
1/2"	12.5	55.0
3/8"	9.5	38.2
#4	4.8	14.7
#10	2.0	6.6
#20	0.9	4.5
#40	0.4	3.7
#60	0.3	3.3
#100	0.2	3.0
#200	0.1	2.5



\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

Damian Edwards

October 31, 2009

Glen Rutherford

November 9, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007 (2000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **180**
**Field Label:** SWD 102409-02

**Depth (m):** NA

**Lab ID No:** SA180

**Remarks:** Water content= 1.6%

**Date Sampled:** October 24, 2009


**Sa. Location:** SWD Sta. 10+640 Bedding layer in place El. 133.5m

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** October 31, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	83.8
1/2"	12.5	62.6
3/8"	9.5	49.6
#4	4.8	31.0
#10	2.0	18.4
#20	0.9	12.4
#40	0.4	9.5
#60	0.3	7.9
#100	0.2	6.6
#200	0.1	5.3



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

Damian Edwards

October 31, 2009

Glen Rutherford

November 9, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007 (2000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **190**
**Field Label:** SWD 110309-01

**Depth (m):** NA

**Lab ID No:** SA190

**Remarks:** Water content= 1.5%

**Date Sampled:** November 3, 2009


**Sa. Location:** SWD Sta. 10+810 Bedding layer in place El. 138 m

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** November 4, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	98.2
3/4"	19.0	89.0
1/2"	12.5	67.5
3/8"	9.5	56.7
#4	4.8	34.4
#10	2.0	19.8
#20	0.9	12.8
#40	0.4	9.8
#60	0.3	8.3
#100	0.2	7.1
#200	0.1	6.1



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

*\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.*

Damian Edwards

November 4, 2009

Glen Rutherford

November 9, 2009

TESTED BY

DATE

CHECKED BY

DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007 (2000)

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **191**
**Field Label:** SWD 110309-02

**Depth (m):** NA

**Lab ID No:** SA191

**Remarks:** Water content=0.7%

**Sa. Location:** SWD Sta. 10+770 Bedding layer in place El 137 m


**Date Sampled:** November 3, 2009

**Material Specification:** Fine Filter

**Method:** COMBINED, WASHED

**Date Tested:** November 4, 2009

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	98.0
3/4"	19.0	85.3
1/2"	12.5	53.3
3/8"	9.5	41.4
#4	4.8	23.5
#10	2.0	14.3
#20	0.9	10.1
#40	0.4	7.9
#60	0.3	6.6
#100	0.2	5.6
#200	0.1	4.7



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only. Interpretation of the data can be provided upon request.

Damian Edwards

November 4, 2009

Glen Rutherford

November 9, 2009

TESTED BY

DATE

CHECKED BY

DATE



## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **194**
**Field Label** SWD110609-1

**Depth (m):** NA

**Lab ID No:** 41

**Remarks:**
**Sa. Location:** SWD Sta. 10+565 Bedding layer in place El. 139 m


**Date Sampled:** November 6, 2009

**Material Specification:** Fine Filter

**Method:** SPLIT, WASHED

**Date Tested:** March 12, 2010

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	87.9
1/2"	12.5	68.0
3/8"	9.5	54.5
#4	4.8	34.7
#10	2.0	21.8
#20	0.9	15.0
#40	0.4	11.5
#60	0.3	9.7
#100	0.2	8.4
#200	0.1	7.0



BOULDER	COBBLE	GRAVEL	SAND	FINES (Silt, Clay)
---------	--------	--------	------	--------------------

\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only.  
 Interpretation of the data can be provided upon request.

PC	March 12, 2010	LP	March 15, 2010
TESTED BY	DATE	CHECKED BY	DATE

## PARTICLE SIZE ANALYSIS OF SOILS

**Reference**

ASTM C136-06 &amp; C117-04

**Project No.:** 09-1428-5007

**Client:** AEM

**Project:** Meadowbank Gold Project

**Location:** Nunavut

**Sample No.:** **195**
**Field Label:** SWD110609-2

**Depth (m):** NA

**Lab ID No:** 41

**Remarks:**
**Sa. Location:** SWD Sta. 10+440 Bedding layer in place El. 138 m


**Date Sampled:** November 6, 2009

**Material Specification:** Fine Filter

**Method:** SPLIT, WASHED

**Date Tested:** March 12, 2010

Sieve Size (USS)	(mm)	Passing %
3.5"	87.5	100.0
3"	75.0	100.0
2"	50.0	100.0
1.5"	37.5	100.0
1"	25.0	100.0
3/4"	19.0	82.0
1/2"	12.5	51.2
3/8"	9.5	37.7
#4	4.8	20.5
#10	2.0	12.1
#20	0.9	8.4
#40	0.4	6.5
#60	0.3	5.5
#100	0.2	4.9
#200	0.1	4.1



\* The test data given herein pertain to the sample provided only. This report constitutes a testing service only.  
 Interpretation of the data can be provided upon request.

PC

March 12, 2010

LP

March 15, 2010

TESTED BY

DATE

CHECKED BY

DATE



**ANALYSIS REPORT**  
**SCC Accreditation No.: 40**

Mrs Fiona Esford  
**Golder Associates Ltd**

Date: December 14, 2009  
 Report: S785-003-39772A

**IDENTIFICATION:** Bituminous membrane: Roll AA9XR Panel 273  
 Project name: Meadowbank Gold  
 Project #: 09-1428-5007  
 Received: December 7, 2009

**STANDARD:**

**TEST:** Nominal Thickness of Geosynthetics ASTM D5199-01 (2006)

**TEST CONDITIONS:** Conditioned sample(s) (21 °C, 65 % R.H.);  
 Dimension of the test specimens: minimum diameter of 75 mm;  
 Apparatus: Mitutoyo - measuring unit: inch (has precedence on the values in mm) ;  
 Diameter of the presser foot: 6.35 mm ;  
 Pressure applied: 20 kPa; Loading time interval: 5 sec. ;  
 Tested December 11, 2009

RESULTS:	Individual Data					Avg.	S.D.	% CV
Thickness (mils):	187	193	180	180	179	<b>180</b>	7	<b>4.1</b>
	187	173	174	175	170			
Thickness (mm):	4.75	4.89	4.56	4.56	4.55	<b>4.56</b>	0.19	<b>4.1</b>
	4.75	4.38	4.42	4.43	4.31			

Prepared by:

*Nancy Fontaine*  
 Nancy Fontaine, Tech.  
 Technician

Approved by:

*Eric Blond*  
 Eric Blond, Eng., M.Sc.A.  
 Vice-President

Date: December 14, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.



# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: December 14, 2009  
Report: S785-003-39772A

IDENTIFICATION: Bituminous membrane: Roll AA9XR Panel 273  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: December 7, 2009

### STANDARD:

TEST: Density and Specific Gravity (Relative Density) of Plastics by Displacement ASTM D792 - 08 Method A

TEST CONDITIONS: Conditioned sample(s) (21°C, 65% R.H.);  
Test method A;  
Temperature of water (°C): 21.1  
Tested December 11 and 14, 2009

RESULTS:	Individual Data		Avg.	S.D.	% CV
Density (g/cm³):	1.268	1.271	<b>1.270</b>	0.002	<b>0.2</b>

Prepared by:

*Nancy Fontaine*  
Nancy Fontaine, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: December 14, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.

**ANALYSIS REPORT**  
**SCC Accreditation No.: 40**

Mrs Fiona Esford  
**Golder Associates Ltd**

Date: December 11, 2009  
 Report: S785-003-39773A

**IDENTIFICATION:** Bituminous membrane seam: DT Panel 217/218, DT Panel 224/225, DT Panel 238/239, DT Panel 241/242, DT Panel 253/254, DT Panel 284/285  
 Project name: Meadowbank Gold  
 Project #: 09-1428-5007  
 Received: December 7, 2009

**STANDARD:**

**TEST:** Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

**TEST CONDITIONS:** Apparatus used: Dynamometer with a Constant Rate of Extension (CRE);  
 Speed: 50 mm/min.;  
 5 test specimens per product;  
 Conditioned sample(s) 24 hours at 21 ± 2°C, 30 à 50% R.H.);  
 Tested December 9, 2009

RESULTS:	Individual Data					Avg.	S.D.	% CV
DT Panel 217/218								
Width of seam, in the direction of the test (mm):	95.0	92.0	118.0	100.0	114.0			
Width of specimen, perpendicular to the direction of the test (mm):	50.5	50.5	50.5	50.5	50.5			
Maximum load value (N):	61.5	77.6	150.6	696.9	1214.1	440.1	505.9	114.9
Seam strength (kN/m):	1.23	1.55	3.01	13.94	24.28	8.80	10.12	114.9
DT Panel 224/225								
Width of seam, in the direction of the test (mm):	120.0	123.0	121.0					
Width of specimen, perpendicular to the direction of the test (mm):	49.5	50.5	50.5					
Maximum load value (N):	1133	1126	1137			1 132	6	0.5
Seam strength (kN/m):	22.7	22.5	22.7			22.6	0.1	0.5

Prepared by:

*Catherine Groleau Rivard*  
 Catherine Groleau Rivard, Tech.  
 Technician

Approved by:

*Eric Blond*  
 Eric Blond, Eng., M.Sc.A.  
 Vice-President

Date: December 11, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.



# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: December 11, 2009  
Report: S785-003-39773A

**IDENTIFICATION:** Bituminous membrane seam: DT Panel 217/218, DT Panel 224/225, DT Panel 238/239, DT Panel 241/242, DT Panel 253/254, DT Panel 284/285  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: December 7, 2009

### STANDARD:

**TEST:** Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

**RESULTS (CONT):** Individual Data Avg. S.D. % CV

#### DT Panel 238/239

Width of seam, in the direction of the test (mm):	110.0	97.0	110.0	113.0			
Width of specimen, perpendicular to the direction of the test (mm):	49.5	50.5	50.5	50.5			
Maximum load value (N):	1042	1139	1058	1059	<b>1 075</b>	44	<b>4.1</b>
Seam strength (kN/m):	20.9	22.8	21.2	21.2	<b>21.5</b>	0.9	<b>4.0</b>

#### DT Panel 241/242

Width of seam, in the direction of the test (mm):	107.0	117.0	113.0	108.0	109.0		
Width of specimen, perpendicular to the direction of the test (mm):	50.5	50.5	50.0	50.0	50.5		
Maximum load value (N):	1227	1237	1312	1205	1236	<b>1 243</b>	40 <b>3.3</b>
Seam strength (kN/m):	24.5	24.7	26.2	24.1	24.7	<b>24.8</b>	0.8 <b>3.2</b>

#### DT Panel 253/254

Width of seam, in the direction of the test (mm):	136.0	131.0	128.0	141.0	130.0		
Width of specimen, perpendicular to the direction of the test (mm):	50.5	50.5	50.5	50.5	50.0		
Maximum load value (N):	1291	1173	970	1188	1174	<b>1 159</b>	117 <b>10.1</b>
Seam strength (kN/m):	25.8	23.5	19.4	23.8	23.5	<b>23.2</b>	2.3 <b>10.0</b>

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: December 11, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.





# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: December 11, 2009  
Report: S785-003-39773A

**IDENTIFICATION:** Bituminous membrane seam: DT Panel 217/218, DT Panel 224/225, DT Panel 238/239, DT Panel 241/242, DT Panel 253/254, DT Panel 284/285  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: December 7, 2009

### STANDARD:

**TEST:** Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

**RESULTS (CONT):** Individual Data Avg. S.D. % CV

### DT Panel 284/285

Width of seam, in the direction of the test (mm): 117.0 121.0 125.0 110.0 115.0

Width of specimen, perpendicular to the direction of the test (mm): 50.5 50.0 50.5 50.5 50.5

Maximum load value (N): 1125 1111 1234 1105 1150 **1 145** 53 **4.6**

Seam strength (kN/m): 22.5 22.2 24.7 22.1 23.0 **22.9** 1.1 **4.7**

**REMARKS:** DT Panel 224/225 and DT Panel 238/239: The size of the samples received was not sufficient to conduct the number of specimens required by the test method.

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: December 11, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.



# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: December 11, 2009  
Report: S785-003-39819A

**IDENTIFICATION:** Bituminous membrane seam: DT Panel 270/271, DT Panel 275/276, DT Panel 279/280, DT Panel 296/297  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: December 9, 2009

### STANDARD:

**TEST:** Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

**TEST CONDITIONS:** Apparatus used: Dynamometer with a Constant Rate of Extension (CRE);  
Speed: 50 mm/min.;  
5 test specimens per product;  
Conditioned sample(s) 24 hours at  $21 \pm 2^{\circ}\text{C}$ , 30 à 50% R.H.);  
Tested December 11, 2009

**RESULTS:** Individual Data Avg. S.D. % CV

#### DT Panel 270/271

Width of seam, in the direction of the test (mm): 91.0 78.0 80.0 78.0 84.0

Width of specimen, perpendicular to the direction of the test (mm): 50.5 50.5 50.5 50.5 50.5

Maximum load value (N): 1088 908 1012 1013 1192 **1 043** 105 **10.1**

Seam strength (kN/m): 21.8 18.2 20.2 20.3 23.8 **20.9** 2.1 **10.0**

#### DT Panel 275/276

Width of seam, in the direction of the test (mm): 68.0 70.0 90.0 98.0 114.0

Width of specimen, perpendicular to the direction of the test (mm): 50.5 50.5 50.5 50.5 50.5

Maximum load value (N): 1226 1139 1061 1175 1186 **1 157** 62 **5.4**

Seam strength (kN/m): 24.5 22.8 21.2 23.5 23.7 **23.1** 1.2 **5.4**

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: December 11, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.





# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: December 11, 2009  
Report: S785-003-39819A

IDENTIFICATION: Bituminous membrane seam: DT Panel 270/271, DT Panel 275/276, DT Panel 279/280, DT Panel 296/297  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: December 9, 2009

### STANDARD:

TEST: Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

RESULTS (CONT): Individual Data Avg. S.D. % CV

#### DT Panel 279/280

Width of seam, in the direction of the test (mm): 94.0 93.0 98.0 100.0 90.0

Width of specimen, perpendicular to the direction of the test (mm): 50.5 50.5 50.5 50.5 50.5

Maximum load value (N): 1225 1175 1142 1201 1066 **1 162** 62 **5.3**

Seam strength (kN/m): 24.5 23.5 22.8 24.0 21.3 **23.2** 1.2 **5.4**

#### DT Panel 296/297

Width of seam, in the direction of the test (mm): 170.0 168.0 171.0 173.0 165.0

Width of specimen, perpendicular to the direction of the test (mm): 50.5 50.5 50.5 50.5 50.5

Maximum load value (N): 1152 1288 1115 1250 1224 **1 206** 71 **5.9**

Seam strength (kN/m): 23.1 25.8 22.3 25.0 24.5 **24.1** 1.4 **5.9**

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: December 11, 2009

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.



# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: January 25, 2010  
Report: S785-003-40733A

**IDENTIFICATION:** Bituminous membrane seam: DT Panel 228/229, DT Panel 246/247, DT Panel 258/259, DT Panel 267/268  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: January 21, 2010

### STANDARD:

**TEST:** Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

**TEST CONDITIONS:** Apparatus used: Dynamometer with a Constant Rate of Extension (CRE);  
Speed: 50 mm/min.;  
5 test specimens per product;  
Conditioned sample(s) 48 hours at  $21 \pm 2^{\circ}\text{C}$ , 55 à 70% R.H.) ;  
Tested January 25, 2010

RESULTS:	Individual Data			Avg.	S.D.	% CV
DT Panel 228/229						
Width of seam, in the direction of the test (mm):	85.0	88.0	90.0			
Width of specimen, perpendicular to the direction of the test (mm):	50.5	50.5	50.5			
Maximum load value (N):	1155	1140	1226	1 174	46	3.9
Seam strength (kN/m):	23.1	22.8	24.5	23.5	0.9	3.9

### DT Panel 246/247

Width of seam, in the direction of the test (mm):	106.0	112.0	113.0	112.0	109.0			
Width of specimen, perpendicular to the direction of the test (mm):	49.5	50.5	50.5	50.5	50.0			
Maximum load value (N):	1258	1162	1241	1235	1180	<b>1 215</b>	42	<b>3.4</b>
Seam strength (kN/m):	25.2	23.2	24.8	24.7	23.6	<b>24.3</b>	0.9	<b>3.5</b>

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: January 25, 2010

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.



# ANALYSIS REPORT

## SCC Accreditation No.: 40

Mrs Fiona Esford  
Golder Associates Ltd

Date: January 25, 2010  
Report: S785-003-40733A

IDENTIFICATION: Bituminous membrane seam: DT Panel 228/229, DT Panel 246/247, DT Panel 258/259, DT Panel 267/268  
Project name: Meadowbank Gold  
Project #: 09-1428-5007  
Received: January 21, 2010

### STANDARD:

TEST: Determining the Tensile Shear Strength of Pre-Fabricated Bituminous Geomembrane Seams ASTM D7056 - 07

RESULTS (CONT):	Individual Data					Avg.	S.D.	% CV
DT Panel 258/259								
Width of seam, in the direction of the test (mm):	147.0	147.0	105.0	125.0	148.0			
Width of specimen, perpendicular to the direction of the test (mm):	49.5	50.5	50.0	50.0	50.0			
Maximum load value (N):	1092	1078	975	1101	1182	1 086	74	6.8
Seam strength (kN/m):	21.8	21.6	19.5	22.0	23.6	21.7	1.5	6.7

### DT Panel 267/268

Width of seam, in the direction of the test (mm):	70.0	75.0	91.0	100.0				
Width of specimen, perpendicular to the direction of the test (mm):	50.5	50.0	50.5	50.5				
Maximum load value (N):	594	488	1148	1192		<b>856</b>	366	<b>42.8</b>
Seam strength (kN/m):	11.9	9.8	23.0	23.8		<b>17.1</b>	7.3	<b>42.6</b>

REMARKS: DT Panel 228/229 and DT Panel 267/268: The size of the samples received was not sufficient to conduct the number of specimens required by the test method.

Prepared by:

*Catherine Groleau Rivard*  
Catherine Groleau Rivard, Tech.  
Technician

Approved by:

*Eric Blond*  
Eric Blond, Eng., M.Sc.A.  
Vice-President

Date: January 25, 2010

**\*\*For any information concerning this report, please contact Eric Blond\*\***

The reports are identified by an alphanumeric code, the last character refers to the number of revision(s), this is emitted in ascending order. The samples in relation to this test are retained for a period of 30 days following the expedition day of the written report, unless other instructions are received. The fees for all services after the tests are 125.00 \$ per hour and for appraisal in Court, 195.00\$ per hour. The above reported results refer exclusively to the samples submitted for evaluation. This analysis report cannot be partly used or reproduced, unless in whole, without CTT Group prior written consent.