

MEADOWBANK GOLD PROJECT

Monitoring Program Summary Report

March 2009

Type A Water License 2AM-MEA0815

TABLE OF CONTENTS

SECTION	ON 1 •	BACKGROUND	1
SECTION	ON 2 •	WATER QUALITY MONITORING	2
2.1	Dewaterin	ng of Second Portage Lake	2
SECTION	ON 3 •	WATER MANAGEMENT	4
3.1	Water Us	age	4
3.2		Treatment Plant Monitoring	
SECTIO	ON 4 •	SPILL MANAGEMENT SUMMARY	5
		LIST OF TABLES	
Table 3	B.1: March : B.2: March :	ring Results March 14 – 31 2009 2009 Water Consumption 2009 STP Seprotech L333 effluent results ary of March 2009 AEM Internal Spill Reports	4 4

SECTION 1 • BACKGROUND

As required under Part I, Item 25 of Type A Water License 2AM-MEA0815, this report documents the water management, monitoring activity and analytical monitoring along the All Weather Private Access Road (AWPAR) and mine site for the month of March 2009.

It should be noted that the Meadowbank Project is just entering the construction phase and is not scheduled to commence operations until early 2010. Consequently many of the license specified reporting locations or requirements are associated with facilities that are not yet constructed and thus reporting cannot be fully initiated until these facilities are constructed and commissioned. The dewatering of the northwest arm of Second Portage Lake began March 17. During this phase of construction no other water has been pumped, discharged or transferred, rather all site contact runoff are contained and directed to the Stormwater Management Pond (Tear Drop Attenuation Pond). The monitoring points covered by this monthly report will expand as the facilities are constructed.

Additionally, for the NWB to review, Section 4 summarizes the AEM internal spill reporting for March.

SECTION 2 • WATER QUALITY MONITORING

In March, no monitoring or sampling was completed along the AWPAR or at the mine site due to ice conditions. No water was discharged around the mine site, rather all the water (ie Sewage Treatment Plant, construction pumping) was directed to the Storm Water Management Pond.

2.1 DEWATERING OF SECOND PORTAGE LAKE

Dewatering of the northwest arm of Second Portage Lake started March 17th, 2009 with one pump in operation. The second and the third pumps were in service on the 20th and the 23rd of March respectively. To date, the amount of water pumped to Third Portage Lake is estimated at 719,712 m³.

Total Suspended Solids (TSS) and turbidity are monitored daily at the intake pump (ST-DD-1) and once per week at Third Portage Lake near the outlet. The results respect the maximum monthly mean effluent quality limits (15 mg/L for TSS and 15 NTU for turbidity). Table 2.1 lists the monitoring results through the end of March.

	ı	l	Turbidity	TSS	1	
Sample ID	Date	Time	result	result	pН	Al
	jj/mm/aaaa	hh:mm	NTU	mg/L	0.70	mg/L
Pre-dewatering 2nd Portage intake Pre-dewatering 2nd Portage intake	3/14/2009 3/14/2009	9:55 9:55	4.65 2.56	4	6.78	< 0.002
Pre-dewatering 3rd Portage Outlet	3/15/2009	14:00	2.50	6	6.72	< 0.002
Pre-dewatering 3rd Portage Outlet	3/15/2009	14:00	4.30	6		
Intake Unit 3	3/17/2009	15:00	2.43			
Outlet 3rd Portage on ice Intake Unit 3	3/17/2009 3/18/2009	11:00 9:00	0.43 2.61	. 1	_	
Intake Unit 3	3/18/2009	16:00	2.45	< 1		
Intake Unit 3	3/19/2009	9:45	2.43	< 1		
Intake Unit 3	3/19/2009	16:30	2.28			
Intake Unit 3	3/20/2009	9:00	2.26	< 1		
Intake Unit 2 Intake Unit 3	3/20/2009 3/20/2009	16:30 16:30	2.30			
Intake Unit 2	3/21/2009	10:00	2.43	< 1		
Intake Unit 3	3/21/2009	10:00	2.28	< 1		
Intake Unit 2	3/21/2009	17:00	2.16			
Intake Unit 3	3/21/2009	17:00	2.37			
Intake Unit 2 Intake Unit 3	3/22/2009 3/22/2009				_	
Intake Unit 2	3/23/2009	10:00	2.21	< 1		
Intake Unit 3	3/23/2009	10:00	2.32	< 1		
Outlet 3rd Portage on ice	3/23/2009	10:00	0.36			
Intake Unit 1 Intake Unit 2	3/24/2009 3/24/2009	10:00 10:00	3.61 2.60	< 1		
Intake Unit 3	3/24/2009	10:00	2.34	< 1		
Outlet 3rd Portage on ice Dewatering outlet	3/24/2009	14:00	-0.99	< 1		
Intake Unit 1	3/24/2009	17:30	2.34			
Intake Unit 2	3/24/2009	17:30	2.98			
Intake Unit 3 Intake Unit 1	3/24/2009 3/25/2009	17:30 10:15	2.74 3.18	< 1	_	
Intake Unit 2	3/25/2009	10:15	3.54	< 1		
Intake Unit 3	3/25/2009	10:15	3.45	< 1		
Intake Unit 1	3/25/2009	16:30	3.14			
Intake Unit 2 Intake Unit 3	3/25/2009 3/25/2009	16:30 16:30	3.59			
Intake Unit 1	3/27/2009	12:00	3.04	< 1		
Intake Unit 2	3/27/2009	12:00	3.50	< 1		
Intake Unit 3	3/27/2009	12:00	3.45	< 1		
Intake Unit 1	3/27/2009	18:00	3.18			
Intake Unit 2 Intake Unit 3	3/27/2009 3/27/2009	18:00 18:00	3.53 3.18			
Intake Unit 1	3/28/2009	9:30	3.25	< 1		
Intake Unit 2	3/28/2009	9:30	3.51	< 1		
Intake Unit 3	3/28/2009	9:30	3.24	< 1		
Intake Unit 1 Intake Unit 2	3/28/2009 3/28/2009	17:15 17:15	2.48			
Intake Unit 3	3/28/2009	17:15	3.01			
Intake Unit 1	3/29/2009	10:00	5.16	< 1		
Intake Unit 2	3/29/2009	10:00	5.48	< 1		
Intake Unit 3 Intake Unit 1	3/29/2009	10:00 18:30	5.12 5.34	< 1		
Intake Unit 1 Nalgene bottle	3/29/2009	18:30	4.41		_	
Intake Unit 2	3/29/2009	18:30	5.57			
Intake Unit 2 Nalgene bottle	3/29/2009	18:30	4.33			
Intake Unit 3	3/29/2009	18:30	5.10			
Intake Unit 3 Nalgene bottle Outlet 3rd Portage on ice	3/29/2009 3/29/2009	18:30 17:00	4.34 2.09	5		
Intake Unit 1	3/30/2009	17:00	4.23	< 1		
Intake Unit 2	3/30/2009	17:00	3.79	< 1		
Intake Unit 3	3/30/2009	17:00	4.05	< 1		
Intake Unit 1 Intake Unit 1	3/31/2009 3/31/2009	10:30 10:30	5.81 4.42	3		
Intake Unit 2	3/31/2009	10:30	5.32	2		
Intake Unit 2	3/31/2009	10:30	4.35			
Intake Unit 3	3/31/2009	10:30	5.20	2		
Intake Unit 3 Intake Unit 1	3/31/2009	10:30	4.34			
Intake Unit 1 Intake Unit 1	3/31/2009 3/31/2009	17:30 17:30	5.27 4.48			
Intake Unit 2	3/31/2009	17:30	5.52			
Intake Unit 2	3/31/2009	17:30	4.46			
Intake Unit 3 Intake Unit 3	3/31/2009	17:30	5.41			
IIIIANG UIIII 3	3/31/2009	17:30	4.06			

Table 2.1: Monitoring Results March 14 – 31 2009

SECTION 3 • WATER MANAGEMENT

3.1 WATER USAGE

Under Water License 2AM-MEA0815, the total water consumption limit for the Meadowbank Project is 700,000 m³/year or 58,333 m³/month for batch plant, domestic and milling water use. During March, the average number of people on site by day was 321. The total consumption of water for the batch plant and the mine site was 2,593 m³ for the month, an average of 84 m³ /day.

Table 3.1: March 2009 Water Consumption

	Water Usage (m ³)
Batch Plant	845
Water Treatment Plant	1,748
Total for the Site	2,593

3.2 SEWAGE TREATMENT PLANT MONITORING

At the sewage treatment plant (STP), five samples were taken in March only for the Seprotech L333. The two Little John LJ100s are in recirculation mode. No sludge was removed from the STP.

Table 3.2: March 2009 STP Seprotech L333 effluent results

Parameter	3/2/2009	3/9/2009	3/16/2009	3/23/2009	3/30/2009
NH3-NH4(mg/L)	10.5	12.8	11.8	11.1	16
DBO-5 (mg/L)	5	5	9	7	3
COD (mg/L)	111	101	77	97	69
TSS (mg/L)	23	14	24	21	4
NO2-NO3 (mg N/L)	31.4		33.5	32.5	37.3
pH (mg/L)	4.9	4.6	3.94	4.64	4.39
P tot (mg P/L)	9.9	12.1	12.9	13.2	15.2
Fecal Coliform (UFC/ 100mL)	<2	0	0	0	0
Total Coliform (UFC /100mL)	160	60	50	20	100
Atypical Colony (UFC /100mL)	1620	1640	440	930	1 800

Not sampled

Requested but not been analysed by lab

SECTION 4 • SPILL MANAGEMENT SUMMARY

During the construction phase as part of the global Environmental Management System, AEM is developing a system of tracking spills on-site. Table 4.1 summarizes the AEM Internal spill reports for March.

Table 4.1: Summary of March 2009 AEM Internal Spill Reports

AEM Internal #	Date of Spill	Hazardous Material (Fuel, Oil, etc.)	Quantity	Location	Cause of Spill	Clean-up Action Taken	Reported to GN Spill HotLine
03-2009-01	3/3/2009	Hydraulic oil	10 L	East Dike	Hose burst on a drill	Drilling ceased and the spill was contained.	No
03-2009-02	3/11/2009	Hydraulic oil	8 L	Entrance of the Tarmak	Hose burst	Contaminated snow was taken to the contaminated snow cell.	No
03-2009-03	3/14/2009	Oil	10 L	Waste management area	Engine connecting rod went through engine block	Absorbent sheets were applied. Contaminated snow was taken to the contaminated snow cell.	No
03-2009-04	03/16/2009	Prestone	8 L	AWPAR km 100	Incorrect Prestone product in the radiator caused crack and leakage	Absorbent sheets were applied. Contaminated snow was taken to the contaminated snow cell.	No
03-2009-05	03/23/2009	Oil	4 L	Container by new drill & Toromont Coverall	Oil drum was punctured drum while moving it to Coverall	The remainder of oil in the drum was drained into an empty drum using the crane on the service truck. Used spill pads to soak up spilled oil.	No
03-2009-06	03/13/2009	Oil	60 L	Blue coverall laydown	Fire in the engine compartment melted hoses	Spill contained with spill kit materials. Top soil was cleaned up immediately and sent to Quarry 22 with other contaminated soil. Further excavation was completed on April 13, with 48 m ³ contaminated soil sent to Quarry 22.	No
03-2009-07	03/19/2009	Hydraulic oil	20 L	Front of cold storage	Leak from the rotation motor for the drill	Contaminated material was taken to the hazardous materials storage area.	No