



LINE	BEARING	DISTANCE
A4-B4	\$56°46'05"E	810.96m
B4-C4	N77°09'08"E	1709.40m
C4-D4	S26°19'05"E	606.73m
D4-E4	S80°14'19"W	551.83m
E4-F4	S47°58'54"W	1589.98m
F4-G4	S81°41'25"W	525.97m
G4-H4	N33°15'36"W	1727.33m
H4-A4	N55°30'57"E	702.34m

LINE	BEARING	DISTANCE
A5-B5	\$88°25'34"E	1064.68m
B5-C5	S39°36'37"E	220.13m
C5-D5	S74'34'42"W	703.67m
D5-E5	S42°27'17"W	372.51m
E5-F5	S5°26'25"E	370.07m
F5-G5	\$67°17'07"W	272.59m
G5-H5	N15°38'30"E	455.45m
H5-A5	N14°36'04"W	719.10m

LINE	BEARING	DISTANCE
A6-B6	\$66'44'30"E	965.47m
B6-C6	\$59°59'27"W	256.64m
C6-D6	N68°45'22"W	877.68m
D6-E6	N38'39'36"E	245.34m

POINT	NORTHING	EASTING
A4	7915269.73	552920.6
B4	7914825.30	553598.9
C4	7915205.40	555265.5
D4	7914661.56	555534.5
E4	7914568.00	554990.7
F4	7913503.72	553809.4
G4	7913427.70	553289.0
H4	7914872.08	552341.6

POINT	NORTHING	EASTING	
A5	7915345.75	555821.08	
B5	7915316.51	556885.36	
C5	7915146.92	557025.70	
D5	7914959.80	556347.37	
E5	7914684.96	556095.92	
F5	7914316.55	556131.00	
G 5	7914211.30	555879.56	
H5	7914649.88	556002.35	

POINT	NORTHING	EASTING
A6	7913262.24	562167.04
В6	7912881.00	563054.05
C6	7912752.64	562831.82
D6	7913070.66	562013.78

LEGEND:

Maximum Extent of Rock Quarrying

Maximum Extent of Identified Borrow Sources

--- Existing Tote Road

- 1. Airphotos provided by Eagle Mapping (2005).
- 2. Coordinate grid is shown in UTM (NAD 83) and is in metres.

300 150 0 300 600 900 1200 1500 Metres

Knight Piésold

Baffinland

MARY RIVER PROJECT — BULK SAMPLING PROGRAM

MARY RIVER BORROW AREA PLAN

NB102-00181/10

0 13JUL07 ISSUED IN FINAL MD KH DRG. NO. DESIGN DRAWN CHK'D APP'D DESIGN DRAWN CHK'D APP'D REFERENCE DRAWINGS REVISIONS REVISIONS

202

0











