

4-E: Addendum Noise and Vibration Impact Assessment Parameters



Appendix 4-E - Noise and Vibration Impact Assessment Addendum

Whale Tail Pit - Expansion Project

Submitted to:

Nunavut Impact Review Board

Submitted by:

Agnico Eagle Mines Limited – Meadowbank Division

Prepared by:

Golder Associates Ltd.

Appendix 4-E - Addendum NIA

1896037

December 2018



Table of Contents

4.E-1 INTRODUCTION	1
4.E-2 EXPANSION PROJECT DESCRIPTION AND EMISSIONS SOURCES.....	1
4.E-2.1 Haul Road Widening	1
4.E-2.1.1 Conventional Noise Sources.....	2
4.E-2.1.2 Blasting Noise and Vibration Sources	4
4.E-2.2 Pit and Underground Operations	4
4.E-2.2.1 Conventional Noise Sources.....	4
4.E-2.2.2 Blasting Noise and Vibration Sources	10
4.E-2.3 Haul Road Operations.....	10
4.E-2.3.1 Conventional Noise Sources.....	10
4.E-3 ASSESSMENT APPROACH	12
4.E-3.1 Regulatory Guidance	12
4.E-3.1.1 Conventional Noise	12
4.E-3.1.2 Blasting Noise and Vibration.....	12
4.E-3.2 Study Areas.....	12
4.E-3.3 Assessment Criteria	13
4.E-3.3.1 Conventional Noise: Broadband	13
4.E-3.3.2 Conventional Noise: Low Frequency	13
4.E-3.3.3 Blasting Noise and Vibration.....	14
4.E-3.4 Prediction Methodology.....	14
4.E-3.4.1 Conventional Noise	14
4.E-3.4.2 Blasting Noise and Vibration.....	16
4.E-4 REFERENCES	18

TABLES

Table 4-E-1: Haul Road Widening - Noise Source Emissions	3
Table 4-E-2: Expansion Project Operations - Noise Emissions for Surface Mining Sources	6
Table 4-E-3: Expansion Project Operations - Noise Emissions for Sources on Pit-to-Waste Pile Road	7
Table 4-E-4: Expansion Project Operations - Noise Emissions for Underground Mining Ventilation Fans	7
Table 4-E-5: Expansion Project Operations - Noise Emissions for Power Plant Sources	8
Table 4-E-6: Expansion Project Operations - Noise Emissions for Ore Crushing Sources	8
Table 4-E-7: Expansion Project Operations - Noise Emissions for Water Treatment Plant Sources	9
Table 4-E-8: Expansion Project Operations - Noise Emissions for Building Heaters and Incinerator	9
Table 4-E-9: Haul Road Operations - Noise Emissions	11
Table 4-E-10: Applicable Permissible Sound Level Values	13
Table 4-E-11: Applicable Blasting Limits	14
Table 4-E-12: Expansion Project Noise Model Input Parameters	15

4.E-1 INTRODUCTION

The Expansion Project has the potential to affect both ambient noise levels and vibration levels in the environment. Therefore, the noise and vibration impact assessment completed for the Approved Project has been updated to reflect the Expansion Project. Supporting information for the Expansion Project noise and vibration assessment is presented in this technical appendix. The results of the Expansion Project noise and vibration impact assessment are presented in Volume 4, Section 4.4 of the FEIS Addendum.

4.E-2 EXPANSION PROJECT DESCRIPTION AND EMISSIONS SOURCES

The Expansion Project will consist of a larger Whale Tail open pit, development of the IVR Pit, and Underground operations, power generation, ore crushing, a water treatment plant, building heaters, incinerator, and miscellaneous support equipment. All ore extracted from Whale Tail and IVR pits will be hauled to Meadowbank Mine for processing and so the Expansion Project includes a 62 km haul road connecting Whale Tail Pit to existing processing and tailings infrastructure at Meadowbank Mine.

As described in the effects pathways table (Volume 3, Appendix 3-C, Table 3-C-1), the Expansion Project noise and vibration assessment was focused on the three Expansion Project activities for which primary effects pathways were identified:

- haul road widening from 9.5 to 15 m;
- pit and underground operations; and
- haul road operations.

Expansion Project activities for which secondary effects pathways were identified (i.e., Whale Tail Pit construction, Whale Tail Pit decommissioning, and haul road decommissioning) were not assessed in the Expansion Project noise and vibration assessment, since noise and vibration emissions associated with these activities are expected to be comparable or less than Expansion Project noise and vibration emissions during activities with primary effects pathways. The additional years of processing and use of supporting infrastructure at the Meadowbank Mine that will result from the Expansion Project were not assessed in the noise and vibration assessment, as they were assessed as a secondary effects pathway. Noise emissions from the Meadowbank Mine have already been characterized as part of an earlier regulatory process (Cumberland 2005a,b), will not change as a result of the Expansion Project and are currently monitored. The Expansion Project noise and vibration assessment was focussed on those activities for which effects are expected to be highest.

4.E-2.1 Haul Road Widening

The 62 km haul road will be improved by expanding the existing road to a 15 m width. Haul road widening will require use of mobile heavy machinery (i.e., conventional noise sources, like loaders, excavators, and dozers). Use of conventional noise sources during haul road widening is not expected to result in any vibration effects in the environment and so the Expansion Project noise and vibration assessment only assessed the potential for these sources to affect ambient noise levels.

Haul road widening will involve explosive blasting. As such, potential noise and vibration effects associated with blasting as part of haul road widening were considered in the Expansion Project noise and vibration assessment.

4.E-2.1.1 Conventional Noise Sources

Estimated noise emissions from conventional noise sources associated with haul road widening used a combination of:

- vendor noise specifications for comparable equipment;
- empirical formulae from acoustics handbooks (Crocker 2007; Bies and Hansen 2003; DEFRA 2005); and
- professional experience assessing noise from similar facilities.

Table 4-E-1 presents noise emissions used to represent haul road widening activities. Noise emissions are presented in the form of octave-band sound power levels per unit. For mobile equipment, the noise emission values include the contribution from a back-up alarm, with a suitable penalty applied to account for the tonal nature of this source (ISO 2003). For each source, Table 4-E-1 also presents the quantity and usage factor assumed in the Expansion Project noise and vibration assessment. The quantity and usage factor for each source were calculated using information provided by Agnico Eagle.

Table 4-E-1: Haul Road Widening - Noise Source Emissions

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Loader	1	40	102.0	104.0	118.0	116.0	107.0	115.5	105.0	98.0	90.0	117.0
Dozer	2	40	92.8	97.8	113.8	110.8	106.8	115.6	102.8	97.8	89.8	116.5
Excavator	2	40	104.0	103.0	116.0	106.0	108.0	113.2	105.0	99.0	94.0	114.9
Roller / Compactor	1	20	118.4	118.2	113.1	105.6	109.2	102.0	96.8	94.0	90.1	108.9
Pickup Truck	2	40	68.0	79.4	98.6	85.9	84.0	82.2	77.8	70.3	63.1	87.9

^a Sound power levels are presented per unit and, where appropriate, include the contribution of a tonal back-up alarm.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

4.E-2.1.2 Blasting Noise and Vibration Sources

The Expansion Project noise and vibration assessment assumed that blasting for haul road widening will be similar to the blasting associated with construction of the Whale Tail Pit haul road, as described in the Approved Project FEIS (Agnico Eagle 2016). In particular, the Expansion Project noise and vibration assessment assumed that each blasting event for haul road widening will require detonation of a single 45 kg explosive charge.

Because of the high-energy and short-duration nature of explosive blasting, the Expansion Project noise and vibration assessment characterized potential noise and vibration effects associated with Expansion Project blasting using widely-accepted empirical formulae (ISEE 1998; DFO 1998). A detailed explanation of the empirical formulae used to characterize Expansion Project blasting is provided in Section 4.E-3.4.2.

4.E-2.2 Pit and Underground Operations

Whale Tail and IVR pits and Underground operations will require the use of mobile and stationary heavy machinery (e.g., excavators, loaders, trucks, electrical generators, and ventilation fans for underground mining), which will emit noise continuously 24 hours per day. Use of these conventional noise sources during pit and underground operations is not expected to result in any vibration effects in the environment and so the Expansion Project noise and vibration assessment only assessed the potential for these sources to affect ambient noise levels.

Pit and underground operations will also involve explosive blasting. In contrast to conventional noise sources, which operate continuously 24 hours per day, blasting is an extremely short-duration activity that will occur periodically. In particular, information provided by Agnico Eagle indicates a maximum of two blasting events per day, each of which will last only a few seconds. Blasting activities associated with pit operations have the potential to affect both ambient noise levels and vibration levels in the environment, and so both blasting noise and blasting vibration were assessed in the Expansion Project noise and vibration assessment.

4.E-2.2.1 Conventional Noise Sources

Noise emissions were estimated from conventional noise sources associated with pit operations using a combination of:

- vendor noise specification sheets and calculation tools for comparable equipment (CAT 2013);
- empirical formulae from acoustics handbooks (Crocker 2007; Bies and Hansen 2003); and
- professional experience assessing noise from similar facilities.

The noise and vibration assessment for the Expansion Project is focused on pit and underground operations during the year 2022, which is the year of highest production for the Expansion Project. Table 4-E-2 through Table 4-E-8 present noise emissions used to represent pit and underground operations. In particular:

- Table 4-E-2 presents noise emissions for surface mining sources that will operate within the Whale Tail and IVR open pits;
- Table 4-E-3 presents noise emissions for sources that will operate on the short access road between the Whale Tail and IVR pits and adjacent waste piles;
- Table 4-E-4 presents noise emissions for ventilation fans required to support underground mining;

- Table 4-E-5 presents noise emissions for sources associated with the power generation at the ramp portal and worker camp;
- Table 4-E-6 presents noise emissions for sources associated with the ore crushing facility;
- Table 4-E-7 presents noise emissions for sources associated with the water treatment plant; and
- Table 4-E-8 presents noise emissions for miscellaneous building heaters and for an incinerator unit.

In all cases, noise emissions are presented in the form of octave-band sound power levels per unit. For mobile equipment, the noise emission values include the contribution from a back-up alarm, with a suitable penalty applied to account for the tonal nature of this source (ISO 2003). For each source, Table 4-E-2 through Table 4-E-8 also present the quantity and usage factor (i.e., the percentage of time that a given source will operate) assumed in the Expansion Project noise and vibration assessment. The quantity and usage factor for each source were calculated using information provided by Agnico Eagle.

Table 4-E-2: Expansion Project Operations - Noise Emissions for Surface Mining Sources

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^(a) [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Excavator - Terex Rh120	3	83	121.8	122.7	124.5	120.1	118.1	117.0	112.9	106.9	100.9	121.3
Track Dozer - CAT D9T	4	83	101.2	104.2	122.2	112.2	110.2	115.8	106.2	100.2	91.2	117.5
Wheel Loader - CAT 992G	2	83	102.0	104.0	118.0	116.0	107.0	115.5	105.0	98.0	90.0	117.0
Wheel Dozer - CAR 834H	1	83	92.8	97.8	113.8	110.8	106.8	115.6	102.8	97.8	89.8	116.5
Mining Truck – CAT 785C/D	14	42	106.0	108.0	115.0	111.0	112.0	112.0	110.0	104.0	96.0	116.3
Water Truck - CAT 773D	1	17	118.8	119.8	123.8	116.8	109.8	112.0	106.8	100.8	99.8	116.2
Motor Grader – CAT 16M	3	83	101.0	103.0	116.0	112.0	110.0	112.8	105.0	100.0	95.0	115.1
Excavator – CAT 390DL	1	83	104.0	103.0	116.0	106.0	108.0	113.2	105.0	99.0	94.0	114.9
Production Drill - Atlas DM45	7	83	103.9	111.9	119.9	104.9	105.9	106.9	105.9	102.9	100.9	112.6
Excavator – CAT 345D	2	83	114.3	112.4	113.0	106.9	100.5	112.1	91.1	83.0	85.1	112.6
Mining Truck – CAT 777F	10	42	113.0	118.0	120.0	111.0	106.0	106.0	104.0	99.0	88.0	111.6
Dewatering Pump	2	100	99.3	100.7	102.0	103.3	103.3	105.7	103.3	99.7	93.3	109.7

^a Sound power levels are presented per unit and, where appropriate, include the contribution of a tonal back-up alarm.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-3: Expansion Project Operations - Noise Emissions for Sources on Pit-to-Waste Pile Road

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Mining Truck – CAT 785C/D	14	42	106.0	108.0	115.0	111.0	112.0	112.0	110.0	104.0	96.0	116.3
Water Truck - CAT 773D	1	17	118.8	119.8	123.8	116.8	109.8	112.0	106.8	100.8	99.8	116.2
Mining Truck - CAT 777F	10	21	113.0	118.0	120.0	111.0	106.0	106.0	104.0	99.0	88.0	111.6

^a Sound power levels are presented per unit and, where appropriate, include the contribution of a tonal back-up alarm.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-4: Expansion Project Operations - Noise Emissions for Underground Mining Ventilation Fans

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level [dBZ]									Overall Sound Power Levela [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Whale Tail 1 Intake Fan	1	100	129.0	126.0	124.2	123.2	122.5	120.4	118.3	112.3	110.2	125.4
Ramp Portal Exhaust Fan	1	100	127.7	124.7	122.9	121.9	121.2	119.1	117.0	111.0	108.9	124.1
Whale Tail 2 Exhaust Fan	1	100	126.0	123.0	121.2	120.2	119.5	117.4	115.3	109.3	107.2	122.4
IVR Raise Intake Fan	1	100	122.3	119.3	117.5	116.5	115.8	113.7	111.6	105.6	103.5	118.7

^a Sound power levels are presented per unit.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-5: Expansion Project Operations - Noise Emissions for Power Plant Sources

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Ramp Portal Power Plant (all sources)	1	100	121.1	121.8	130.9	122.6	122.3	122.0	124.9	126.8	123.5	131.7
Work Camp Power Plant (all sources)	1	100	81.7	84.4	88.9	85.6	87.6	90.8	99.0	103.3	102.2	107.1

^a Sound power levels are presented per unit.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-6: Expansion Project Operations - Noise Emissions for Ore Crushing Sources

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Jaw Crusher	2	83	117.2	119.5	121.8	119.9	113.5	113.8	111.7	111.0	105.3	119.5
Wheel Loader - CAT 992G	2	83	102.0	104.0	118.0	116.0	107.0	115.5	105.0	98.0	90.0	117.0

^a Sound power levels are presented per unit and, where appropriate, include the contribution of a tonal back-up alarm.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-7: Expansion Project Operations - Noise Emissions for Water Treatment Plant Sources

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Open Bay Door - Large	1	100	99.5	97.2	98.0	99.0	100.0	102.6	101.2	98.3	94.3	107.2
Open Bay Door - Small	1	100	96.4	94.1	94.9	95.9	96.9	99.5	98.1	95.2	91.2	104.1
Air Handling Unit	1	100	97.3	96.9	96.5	93.0	93.8	93.4	89.1	83.7	73.5	97.1
Open Man Door	2	100	88.9	86.6	87.4	88.4	89.4	92.0	90.6	87.7	83.7	96.6
Building Roof	1	100	114.0	105.7	100.5	97.5	96.5	86.1	83.7	73.8	69.8	96.1
Ventilation Louver	2	100	88.7	85.4	86.2	86.2	87.2	88.8	87.4	83.5	78.5	93.3
Building Wall - Large	2	100	108.0	99.7	94.5	91.5	90.5	80.1	77.7	67.8	63.8	90.1
Building Wall - Small	2	100	106.0	97.7	92.5	89.5	88.5	78.1	75.7	65.8	61.8	88.1

^a Sound power levels are presented per unit.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

Table 4-E-8: Expansion Project Operations - Noise Emissions for Building Heaters and Incinerator

Source	Quantity	Usage Factor [%]	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
			31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Incinerator	1	100	84.1	87.8	91.3	93.6	98.4	92.3	86.3	80.4	74.9	97.8
Truck Shop Heaters	4	100	82.5	86.3	89.8	92.1	96.9	90.8	84.8	78.9	73.4	96.3

^a Sound power levels are presented per unit.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

4.E-2.2.2 Blasting Noise and Vibration Sources

Based on information provided by Agnico Eagle, the Expansion Project noise and vibration assessment assumed that each blasting event during pit operations will consist of simultaneous detonation of up to 2,120 kg of explosives (i.e., simultaneous detonation of 20 blast holes each containing 106 kg of explosives).

Because of the high-energy and short-duration nature of explosive blasting, the Expansion Project noise and vibration assessment characterized potential noise and vibration effects associated with Expansion Project blasting using empirical formulae (ISEE 1998; DFO 1998). A detailed explanation of the empirical formulae used to characterize Project blasting is provided in Section 4.E-3.4.2.

4.E-2.3 Haul Road Operations

A 62 km road connects the Expansion Project to existing ore processing infrastructure at Meadowbank Mine. This road is primarily used to haul ore from the Expansion Project to Meadowbank Mine, but it is also used to transport workers, explosives, and other supplies from Meadowbank Mine to the Expansion Project.

Haul road operations will require the use of conventional noise sources, which have the potential to affect ambient noise levels but are not expected to affect vibration levels. Haul road operations will not involve any blasting or other activities that might result in vibration effects. As such, the Expansion Project noise and vibration assessment only assessed the potential effects of haul road operations on ambient noise levels.

4.E-2.3.1 Conventional Noise Sources

Estimated noise emissions from conventional noise sources associated with haul road operations used a combination of:

- vendor noise specifications for comparable equipment;
- empirical formulae from acoustics handbooks (Crocker 2007; Bies and Hansen 2003); and
- professional experience assessing noise from similar facilities.

Table 4-E-9 presents noise emissions used in the Expansion Project noise and vibration assessment to represent haul road operations. Noise emissions are presented in the form of octave-band sound power levels per unit. For each source, Table 4-E-9 also presents the expected number of trips per day assumed in the Expansion Project noise and vibration assessment. Information about the number of trips per day was provided by Agnico Eagle.

Table 4-E-9: Haul Road Operations - Noise Emissions

Source	Trips Per Day	Octave-Band Sound Power Level ^a [dBZ]									Overall Sound Power Level ^a [dBA]
		31.5 Hz	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	
Haul Truck - CAT 785D	173	121.9	126.9	128.9	119.9	114.9	114.9	112.9	107.9	96.9	120.5
Oversize Cargo Truck - Western Star 6900XD	4	124.0	124.0	117.0	107.0	107.0	104.0	103.0	95.0	90.0	110.2
Explosives Truck - Western Star 4800SB	5	121.0	121.0	114.0	104.0	104.0	101.0	100.0	92.0	87.0	107.2
Fuel Truck - Kenworth T800	4	121.0	121.0	114.0	104.0	104.0	101.0	100.0	92.0	87.0	107.2
Cargo Truck - Kenworth C500B	10	121.0	121.0	114.0	104.0	104.0	101.0	100.0	92.0	87.0	107.2
Crew Bus - Blue Bird Vision SL	4	121.0	121.0	114.0	104.0	104.0	101.0	100.0	92.0	87.0	107.2
Pickup Truck - Ford F250	26	68.0	79.4	98.6	85.9	84.0	82.2	77.8	70.3	63.1	87.9

^a Sound power levels are presented per unit and, where appropriate, include the contribution of a tonal back-up alarm.

dBA = A-weighted decibel; dBZ = unweighted or linear decibels; Hz = hertz; % = percent.

4.E-3 ASSESSMENT APPROACH

4.E-3.1 Regulatory Guidance

4.E-3.1.1 Conventional Noise

Nunavut does not have any environmental noise regulations or guidelines and the Nunavut Impact Review Board (NIRB) does not endorse or recommend any specific noise regulation or guideline as being appropriate for assessing potential noise effects from the Expansion Project. Alberta Energy Regulator (AER) *Directive 038: Noise Control* (AER 2007) is the environmental noise regulation applicable to oil sands and coal mines in Alberta, and it is common practice to use AER Directive 038 to assess potential noise effects from existing and proposed mines in Canadian provinces and territories that lack specific noise regulations. For example, AER Directive 038 was used in the Approved Project FEIS (Agnico Eagle 2016), and was also used recently to assess potential noise effects from the Yancoals Southey Potash Mine in Saskatchewan (Yancoals 2015) and from the Dominion Diamond Jay Project in the Northwest Territories (Dominion Diamond 2014). Furthermore, an earlier version of AER Directive 038 was used to assess potential noise effects from the Meadowbank Mine (Cumberland 2005a, b) as part of the original regulatory process for this facility. In addition, AER Directive 038 has been explicitly identified by the Environmental Impact Review Board for the Inuvialuit Settlement Region as containing useful guidance for assessing potential noise effects (EIRB 2007).

Because AER Directive 038 is considered to represent best practices for environmental noise assessment and because this regulation was used to assess noise from the Approved Project, AER Directive 038 assessment methodologies and criteria were used in the Expansion Project noise and vibration assessment.

4.E-3.1.2 Blasting Noise and Vibration

Nunavut does not have any regulations or guidelines related to potential environmental noise and vibration effects from blasting and the NIRB does not endorse or recommend any specific regulation or guideline as being appropriate for assessing potential environmental effects from blasting. Ontario Ministry of Environment, Conservation and Parks (MECP) *Noise Pollution Control (NPC) Publication 119* (MECP 1978) represents best practices with respect to the assessment of potential noise and vibration effects from blasting. As such, NPC-119 assessment methodologies and criteria were used in the Expansion Project noise and vibration impact assessment.

4.E-3.2 Study Areas

AER Directive 038 indicates that noise effects from new facilities should be assessed at receptors corresponding to the nearest occupied dwellings. In the absence of occupied dwellings within 1.5 km, noise effects should be assessed at 1.5 km from the facility fence line.

The Expansion Project is located in a very remote area far from any occupied dwellings and, because of its remote location, the Expansion Project will not include a formal fence line. As such, the Expansion Project noise and vibration assessment assessed potential noise and vibration effects across a Local Study Area (LSA) established as a buffer surrounding the Expansion Project footprint at a distance of 5 km and a Regional Study Area (RSA) established as a buffer surrounding the Expansion Project footprint at a distance of 7 km. The Expansion Project footprint was taken to include the Whale Tail and IVR pits and underground activities, associated waste piles, power plants, ore crushing facility, water treatment plant, building heaters, incinerator, and haul road. Expansion Project noise levels were predicted for a grid of receptors covering the LSA and RSA and for a discrete receptor corresponding to the most impacted location on the LSA boundary. These study areas are consistent with the LSA

and RSA used in the noise assessments for the Approved Project FEIS (Agnico Eagle 2016) and for the Meadowbank Mine (Cumberland 2005a, b).

4.E-3.3 Assessment Criteria

4.E-3.3.1 Conventional Noise: Broadband

AER Directive 038 indicates that broadband noise should be assessed by comparing cumulative noise levels, expressed in A-weighted decibels (dBA), with a mandated Permissible Sound Level (PSL). In the case of the Expansion Project noise and vibration assessment, cumulative noise levels consist of existing ambient noise levels added to the predicted noise contribution from the Expansion Project.

Table 4-E-10 presents the PSL values applicable to the Expansion Project LSA and RSA. The summertime PSL is applicable during periods when the temperature is above 0 degrees Celsius or when the ground is free of snow or ice cover. The wintertime PSL is applicable during periods when temperature is below 0 degrees Celsius and the ground is covered by snow or ice. The daytime PSL is applicable during the period 7 am to 10 pm (i.e., daytime) and the nighttime PSL is applicable during the period 10 pm to 7 am (i.e., nighttime); daytime and nighttime periods are defined by AER Directive 038 and are not adjusted to reflect actual daylight hours.

Table 4-E-10: Applicable Permissible Sound Level Values

Area of Applicability	Permissible Sound Level [dBA]			
	Summertime		Wintertime	
	Daytime: 7 am to 10 pm	Nighttime: 10 pm to 7 am	Daytime: 7 am to 10 pm	Nighttime: 10 pm to 7 am
LSA and RSA	50	40	55	45

LSA = local study area; RSA = regional study area; dBA = A-weighted decibels.

4.E-3.3.2 Conventional Noise: Low Frequency

AER Directive 038 indicates that a separate assessment of potential Low Frequency Noise (LFN) effects should be conducted where suitable information is available because LFN can be an issue even when broadband noise levels are otherwise acceptable. AER Directive 038 indicates that a LFN effect may exist when the following occur:

- the value of the predicted noise level, expressed in C-weighted decibels (dBC), minus the value of the predicted noise level, expressed in dBA, is greater than or equal to 20; and
- a clear tonal component exists at a frequency below 20 Hz.

Noise levels expressed in dBC have been scaled to emphasize low frequency content - as opposed to noise levels expressed in dBA, which have been scaled to reflect the frequency sensitivity of the human auditory system.

The first LFN condition can be assessed using model predictions but the second LFN condition requires high-resolution spectral data, which are not available from model predictions and can only be obtained from field measurements once Expansion Project operations have commenced. As such, the Expansion Project noise and vibration assessment was able to provide an assessment of potential LFN effects based on the first condition.

Tonal components are sometimes observed in noise emissions from equipment that operates in a highly periodic manner (e.g., cooling fans). It is very unusual to observe tonal components in noise emissions from mining equipment, and even more unusual to observe tonal components in cumulative noise levels resulting from the

combined contribution of multiple pieces of mining equipment. As such, it is very unlikely that noise levels from Expansion Project will satisfy the second LFN condition from AER Directive 038, and equally unlikely that an LFN effect will exist for the Expansion Project.

4.E-3.3.3 Blasting Noise and Vibration

NPC-119 establishes blasting limits for Peak Particle Velocity (PPV) associated with ground vibration and for Peak Pressure Level (PPL) associated with airborne noise. When assessing potential blasting effects, the Expansion Project noise and vibration assessment considered both the PPV and PPL limits from NPC-119. The Expansion Project noise and vibration assessment also considered blasting limits set by the Fisheries and Oceans (DFO) to protect general fish habitat and fish spawning beds during the period of egg incubation (DFO 1998). The specific blasting limits considered in the Expansion Project noise and vibration assessment are presented in Table 4-E-11.

Table 4-E-11: Applicable Blasting Limits

Area of Applicability	Peak Particle Velocity Limits - Ground Vibration		Peak Pressure Level - Airborne Noise	
	NPC-119 ^a	Fish Spawning Beds During the Period of Egg Incubation ^b	NPC-119 ^a	Fish Habitat ^b
LSA and RSA	10 mm/s	13 mm/s	120 dBZ	100 kPa

^a OMOE (1978).

^b DFO (1998).

LSA = local study area; RSA = regional study area; mm/s = millimetres per second; dBZ = unweighted or linear decibels; kPa = Kilo-Pascal.

4.E-3.4 Prediction Methodology

4.E-3.4.1 Conventional Noise

Computer noise models used in the noise and vibration assessment were developed using the CadnaA Version 4.5.151 software package. In accordance with AER Directive 038, CadnaA implements the noise propagation algorithm described in the ISO 9613-2 technical standard (ISO 1996).

The computer models were used to predict Expansion Project noise levels for a grid or receptors covering the LSA and RSA. Inputs to the computer models consisted of source emissions in the form of octave-band sound power levels (see Section 4.E-2 of this technical appendix) and environmental conditions – like ground cover, temperature, humidity, and wind conditions – that are known to affect noise propagation. A summary of model input parameters is provided in Table 4-E-12.

Table 4-E-12: Expansion Project Noise Model Input Parameters

Parameter	Model Setting	Description/Comments
Standard	ISO 9613-2 (ISO 1996)	models treated noise sources, noise attenuation, and noise propagation in accordance with this standard
Ground absorption	<u>Summertime</u> : 0.5 <u>Wintertime</u> : 0.0	a value of 0.5 is consistent with mixed ground (e.g., a mixture of porous/absorptive tundra and hard/reflective lakes) a value of 0.0 is consistent with hard ground (e.g., frozen lakes and ice-covered snow)
Temperature / humidity	<u>Summertime</u> : 10 degrees Celsius / 70% relative humidity <u>Wintertime</u> : -26 degrees Celsius / 69% relative humidity	summertime values are typical defaults for ISO 9613-2 intended to represent nighttime summertime conditions wintertime values are intended to represent nighttime wintertime conditions in the area
Wind conditions	1 m/s to 5 m/s downwind	wind conditions selected as per ISO 9613-2 requirements - moderate temperature inversion with all receptors downwind from all sources 100% of the time
Terrain	ground elevation contours at 10 m intervals	terrain was not considered in the noise modelling for the Approved Project but was added to the noise modelling for the Expansion Project to address a Health Canada information request from the Approved Project FEIS (see information request "HC_4")

LSA = local study area; RSA = regional study area; m/s = metre per second.

When calculating noise levels, the ISO 9613-2 algorithm used the environmental inputs listed in Table 4-E-12 to account for four noise attenuation mechanisms:

- geometric divergence;
- atmospheric absorption;
- ground absorption; and
- screening by barriers.

Geometric divergence accounts for the fact that a given noise source radiates a finite amount of acoustic energy, and as this finite amount of energy propagates into the environment it is spread out over a larger and larger area (i.e., the surface of an ever expanding sphere). This geometric spreading means that the farther away a receptor is located from a source, the less energy will be received (i.e., the lower the observed noise level).

Atmospheric absorption accounts for the fact that acoustic energy associated with a given noise source is absorbed via interaction with molecules in the air through which it propagates. Attenuation effects associated with atmospheric absorption are most substantial at high frequencies, but can be important at lower frequencies for very large propagation distances.

Ground absorption accounts for the fact that each time the acoustic energy emitted by a noise source interacts with the ground, some of it is absorbed. The amount of energy absorbed depends on the type of ground surface – during interactions with hard ground (e.g., frozen lakes) very little energy is absorbed but during interactions with soft

ground (e.g., tundra) a substantial amount of energy is absorbed. As a result, if all other factors are held constant, observed noise levels associated with sources operating in an area of hard ground will be higher than observed noise levels associated with sources operating in an area of soft ground.

Screening by barriers accounts for the fact that a physical object (either terrain-based or man-made) placed between a noise source and receptor will tend to block some of the acoustic energy and so serve to reduce observed noise levels.

4.E-3.4.2 Blasting Noise and Vibration

The noise and vibration assessment characterized potential noise and vibration effects associated with Expansion Project blasting using empirical formulae (ISEE 1998; DFO 1998). In particular, the Expansion Project noise and vibration assessment used empirical formulae to predict PPV and PPL values across the LSA and RSA.

The empirical formulae used to assess Expansion Project blasting have only one input, charge mass, and they do not account for specific ground conditions or atmospheric conditions in the LSA/RSA. Therefore, there is substantial uncertainty associated with the specific PPV and PPL predictions obtained using these formulae. However, the empirical formulae are useful for gauging the likely magnitude of noise and vibration effects associated with blasting activities (i.e., they provide useful information about approximate setbacks required to achieve compliance with PPV and PPL limits). As such, use of empirical formulae to assess blasting is appropriate in the context of a FEIS - particularly, in the case of the Expansion Project since there are no dwellings or other sensitive receptors at which specific PPV or PPL values must be predicted.

When assessing blasting-induced ground vibration in the context of NPC-119 limits, the Expansion Project noise and vibration assessment used the following empirical formula to calculate PPV in mm/s (ISEE 1998):

$$PPV = 1725 \left(\frac{D}{\sqrt{M}} \right)^{-1.6}$$

where D is the distance from the explosive charge (expressed in m) and M is the mass of the explosive charge (expressed in kg).

When assessing blasting-induced airborne noise in the context of NPC-119 limits, the Expansion Project noise and vibration assessment used the following empirical formula to calculate PPL in dBZ (ISEE 1998):

$$PPL = 20 \log_{10} \left[\left(\frac{3.28D}{\sqrt[3]{2.2M}} \right)^{-1.1} \right] + 170.75$$

where D is the distance from the explosive charge (expressed in m) and M is the mass of the explosive charge (expressed in kg).

When calculating the setback distance, D (expressed in m), required to achieve compliance with the PPV limit of 13 mm/s set by the DFO for protection of spawning fish, the Expansion Project noise and vibration assessment used the following empirical formula (DFO 1998):

$$D = 15.09\sqrt{M}$$

where M is the mass of the explosive charge (expressed in kg).

When calculating the setback distance, D (expressed in m), required to achieve compliance with the PPL limit of 100 kPa set by the DFO for protection of fish habitat, the Expansion Project noise and vibration assessment used the following empirical formula (DFO 1998):

$$D = 3.2\sqrt{M}$$

where M is the mass of the explosive charge (expressed in kg).

4.E-4 REFERENCES

- Agnico Eagle (Agnico Eagle Mines Limited). 2011. Phase 1 - Meliadine All-Weather Access Road Project Description and Environmental Assessment.
- Agnico Eagle. 2016. Whale Tail Pit Project - Meadowbank Mine Final Environmental Impact Statement and Type A Water Licence Amendments. Amendment/Reconsideration of the Project Certificate (No. 004/ File No. 03MN107) and Amendment to the Type A Water Licence (No. 2AM-MEA1525). Submitted to the Nunavut Impact Review Board. June 2016.
- AER (Alberta Energy Regulator). 2007. Directive 038: Noise Control.
- Bies, D.A, and Hansen, C.H. 2003. Engineering Noise Control Theory and Practice - Third Edition.
- CAT (Caterpillar Inc.) 2013. Computer Software: Gas Engine Rating Pro Version 4.05.
- Crocker, M.J. 2007. Handbook of Noise and Vibration Control.
- Cumberland (Cumberland Resources Ltd.). 2005a. Meadowbank Gold Project - Environmental Impact Statement.
- Cumberland. 2005b. Meadowbank Gold Project - Noise Impact Assessment.
- DEFRA (United Kingdom Department for Environment, Food, and Rural Affairs). 2005. Update of Noise Database for Prediction of Noise on Construction and Open Sites.
- DFO (Department of Fisheries and Oceans). 1998. Guidance for the Use of Explosives In or Near Canadian Fisheries Waters.
- Dominion Diamond. 2014. Developer's Assessment Report - Jay Project. Appendix 13B, Noise.
- EIRB (Environmental Impact Review Board for the Inuvialuit Settlement Region). 2007. Environmental Impact Review Guidelines.
- ISEE (International Society of Explosives Engineers). 1998. Blaster's Handbook of International Society of Explosives Engineers.
- ISO (International Organization for Standardization). 1996. ISO 9613-2 Acoustics - Attenuation of sound during propagation outdoors - Part 2: General method of calculation.
- ISO. 2003. ISO 1996-1 Acoustics - Description, measurement and assessment of environmental noise - Part 1: Basic quantities and assessment procedures.
- MECP (Ontario Ministry of Environment, Conservation and Parks). 1978. Model Municipal Noise Control By-Law - Final Report. Noise Pollution Control Publication 119.
- Yancoal (Yancoal Canada Resources Company Ltd.). 2015. Yancoal Southey Project - Environmental Impact Statement. Appendix 14-B, Acoustic Environment.