

Material Safety Data Sheet

Dyno Nobel Inc.
2650 Decker Lake Boulevard, Suite 300
Salt Lake City, Utah 84119
Phone: 801-364-4800 Fax: 801-321-6703
E-Mail: dnnn.hse@am.dynonobel.com
FOR 24 HOUR EMERGENCY, CALL CHEMTREC (USA) 800-424-9300
CANUTEC (CANADA) 613-996-6666

MSDS # 1076
Date 01/24/05

Supersedes
MSDS # 1076 01/22/03

SECTION I - PRODUCT IDENTIFICATION

Trade Name(s): ELECTRIC SUPER™ COAL
ELECTRIC SUPER™ LP
ELECTRIC SUPER™ SP
ELECTRIC SUPER™ SEISMIC
ELECTRIC SUPER™ INSTANT

Product Class: Commercial Electric Detonators and Accessory Products

Product Appearance & Odor: Metal cylinder with varying length of attached plastic coated wires.

DOT Hazard Shipping Description: Detonators, Electric 1.1B UN0030 II

Or
Detonators, Electric 1.4B UN0255 II

Or
Detonators, Electric 1.4S UN0456 II

NFPA Hazard Classification: Not Applicable (See Section IV - Special Fire Fighting Procedures)

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS#	<u>EXPOSURE LIMITS</u>	
		OSHA PEL-TWA	ACGIH TLV-TWA
Tungsten	7440-33-7	None ¹	5 mg/m ³ (TWA) 10 mg/m ³ (STEL)
Barium Chromate	10294-40-3	1 mg (CrO ₃)/10m ³ (ceiling)	0.01 mg (Cr)/m ³
Lead Compounds	-----	0.5 mg (Ba)/m ³ 0.5 mg (Pb)/m ³	0.5 mg (Ba)/m ³ 0.5 mg (Pb)/m ³
Pentaerythritol Tetranitrate (PETN)	78-11-5	None ¹	None ²
Boron	7440-42-8	No Value Established	No Value Established
Potassium Perchlorate ³	7778-74-7	None ¹	None ²
Diazodinitrophenol (DDNP)	4682-03-5	No Value Established	No Value Established
Nitrocellulose	9004-70-0	No Value Established	No Value Established

¹ Use limit for particulates not otherwise regulated (PNOR): Total dust, 15 mg/m³; respirable fraction, 5 mg/m³.

² Use limit for particulates not otherwise classified (PNOC): Inhalable particulate, 10 mg/m³; respirable part., 3 mg/m³.

³ Not all delay periods contain perchlorate. Those that do contain between from about 4 to a maximum of about 25 mg perchlorate per detonator.

Material Safety Data Sheet

Ingredients, other than those mentioned above, as used in this product are not hazardous as defined under current Department of Labor regulations, or are present in de minimus concentrations (less than 0.1% for carcinogens, less than 1.0% for other hazardous materials).

SECTION III - PHYSICAL DATA

Boiling Point: Not Applicable
Vapor Density: Not Applicable
Percent Volatile by Volume: Not Applicable

Vapor Pressure: Not Applicable
Density: Not Applicable
Solubility in Water: Not Applicable

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not Applicable
Extinguishing Media: None

Flammable Limits: Not Applicable

Special Fire Fighting Procedures: Do not attempt to fight fires involving explosive materials. Evacuate all personnel to a predetermined safe location, no less than 2,500 feet in all directions.

Unusual Fire and Explosion Hazards: Can explode or detonate under fire conditions. Burning material may produce toxic vapors.

SECTION V - HEALTH HAZARD DATA

Effects of Overexposure

This is a packaged product that will not result in exposure to the explosive material under normal conditions of use. Exposure concerns are primarily with post-detonation reaction products, particularly heavy metal compounds.

Eyes: No exposure to chemical hazards anticipated with normal handling procedures. Particulates in the eye may cause irritation, redness and tearing.

Skin: No exposure to chemical hazards anticipated with normal handling procedures.

Ingestion: No exposure to chemical hazards anticipated with normal handling procedures.

Inhalation: Not a likely route of exposure.

Systemic or Other Effects: None anticipated with normal handling procedures. Repeated inhalation or ingestion of post-detonation reaction products may lead to systemic effects such as respiratory tract irritation, ringing of the ears, dizziness, elevated blood pressure, blurred vision and tremors. Heavy metal (lead) poisoning can occur.

Carcinogenicity: ACGIH classifies Lead as a "Suspected Human Carcinogen" and insoluble Chromium VI as "Confirmed Human Carcinogen". NTP, OSHA, and IARC consider components contained in this detonator carcinogenic.

Perchlorate: Perchlorate can potentially inhibit iodide uptake by the thyroid and result in a decrease in thyroid hormone. The National Academy of Sciences (NAS) has reviewed the toxicity of perchlorate and has concluded that even the most sensitive populations could ingest up to 0.7 microgram perchlorate per kilogram of body weight per day without adversely affecting health. The USEPA must establish a maximum contaminant level (MCL) for perchlorate in drinking water by 2007, and this study by NAS may result in a recommendation of about 20 ppb for the MCL.

Emergency and First Aid Procedures

Eyes: Irrigate with running water for at least fifteen minutes. If irritation persists, seek medical attention.

Skin: Wash with soap and water.

Ingestion: Seek medical attention.

Inhalation: Not applicable.

Special Considerations: None

Material Safety Data Sheet

SECTION VI - REACTIVITY DATA

Stability: Stable under normal conditions, may explode when subjected to fire, supersonic shock or high-energy projectile impact, especially when confined or in large quantities.

Conditions to Avoid: Keep away from heat, flame, ignition sources, strong shock and electrical impulse. Do not attempt to disassemble.

Materials to Avoid (Incompatibility): Corrosives (acids and bases)

Hazardous Decomposition Products: Carbon Monoxide (CO), Nitrous Oxides (NO_x), Lead (Pb) and various oxides and complex oxides of metals.

Hazardous Polymerization: Will not occur.

SECTION VII - SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Protect from all ignition sources. In case of fire evacuate area not less than 2,500 feet in all directions. Notify authorities in accordance with emergency response procedures. Only personnel trained in emergency response should respond. If no fire danger is present, and product is undamaged and/or uncontaminated, repackage product in original packaging or other clean DOT approved container. Ensure that a complete account of product has been made and is verified. Follow applicable Federal, State, and local spill reporting requirements.

Waste Disposal Method: Disposal must comply with Federal, State and local regulations. If product becomes a waste, it is potentially regulated as a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR, part 261. Review disposal requirements with a person knowledgeable with applicable environmental law (RCRA) before disposing of any explosive material.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Ventilation: Not required for normal handling.

Respiratory Protection: None normally required.

Protective Clothing: Cotton clothing is suggested.

Eye Protection: Safety glasses are recommended.

Other Precautions Required: None.

SECTION IX - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storage: Store in cool, dry, well-ventilated location. Store in compliance with Federal, State, and local regulations. Keep away from heat, flame, ignition sources, strong shock, and electrical impulses.

Precautions to be taken during use: Avoid breathing the fumes or gases from detonation of explosives. Use accepted safe industry practices when using explosive materials. Unintended detonation of explosives or explosive devices can cause serious injury or death.

Other Precautions: It is recommended that users of explosive materials be familiar with the Institute of Makers of Explosives Safety Library Publications.

Material Safety Data Sheet

SECTION X - SPECIAL INFORMATION

This product contains the following substances that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

<u>Chemical Name</u>	<u>CAS Number</u> (Use Toxic Chemical Category Code)	<u>% By Weight</u>
Barium Compounds	N040	1.2
Lead Compounds	N420	0 – 0.59
Chromium Compounds	N090	1.2

Amount of Lead in Detonator Product Line *				
Product	Pb compounds in detonator [grams]	Pb compounds in detonator [Wt.%]	Pb in detonator [grams]	Pb in detonator [Wt. %]
Electric Super SP	0.0412	0.588%	0.0357	0.5093%
Electric Super LP	0.0412	0.588%	0.0357	0.5093%
Electric Super Coal	0.0412	0.588%	0.0357	0.5093%
Electric Super Seismic	0.0000	0.0000%	0.0000	0.0000%
Electric Super Instant	0.0000	0.0000%	0.0000	0.0000%

*Applies to only the detonator (source of lead). Do not use case weight or weight of any other component.

Disclaimer

Dyno Nobel Inc. and its subsidiaries disclaim any warranties with respect to this product, the safety or suitability thereof, the information contained herein, or the results to be obtained, whether express or implied, INCLUDING WITHOUT LIMITATION, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND/OR OTHER WARRANTY. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever from any and all injuries (including death), losses, or damages to persons or property arising from the use of this product or information. Under no circumstances shall either Dyno Nobel Inc. or any of its subsidiaries be liable for special, consequential or incidental damages or for anticipated loss of profits.