



# MSDS

Revised February 15, 2005

## Material Safety Data Sheet

### PRODUCT NAME: PORTLAND CEMENT

#### 1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

##### Supplier

Name: Lafarge North America Inc.  
Address: 12950 Worldgate Drive, Suite 500  
Herndon, VA 20170  
Telephone: 703-480-3600

##### Product Identifier

Hydraulic Cement, Oil Well Cement, White Cement, Portland Cement  
Type I, IA, II, IIA, III, IIIA, IV, IVA, V, VA, 10, 20, 30, 40, 50,  
OWH, OWG Cement, OW Class G HSR

Note: This MSDS covers many products. Individual composition of hazardous constituents will vary.

WHMIS Classification: D2A, E

##### Emergency Telephone Numbers

Health & Transportation: CHEMTREC 1-800-424-9300 or 703-527-3887

#### 2. INFORMATION ON COMPONENTS

Component Name	%	CAS No.
Tri-Calcium Silicate	20 - 70	12168-85-3
Di-Calcium Silicate	10 - 60	10034-77-2
Tetra-Calcium- Alumino-Ferrite	5 - 15	12068-35-8
Calcium Sulfate	2 - 10	Various
Tri-Calcium Aluminate	1 - 15	12042-78-3
Calcium Carbonate	0 - 5	1317-65-3
Magnesium Oxide	0 - 4	1309-48-4
Calcium Oxide	0 - 0.2	1305-78-8
Crystalline Silica	0 - 0.2	14808-60-7
Chromates	0 - 0.005	Various

Component Name	EXPOSURE LIMITS	
	OSHA PEL TWA	ACGIH TLV TWA
Portland Cement (CAS 65997-15-1)*		
(Respirable Dust)	5 mg/m <sup>3</sup>	
(Total Dust)	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Calcium Sulfate		
(Respirable Dust)	5 mg/m <sup>3</sup>	
(Total Dust)	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Calcium Carbonate		
(Respirable dust)	5 mg/m <sup>3</sup>	
(Total Dust)	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Magnesium Oxide	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>
Calcium Oxide	5 mg/m <sup>3</sup>	2 mg/m <sup>3</sup>
Crystalline Silica Quartz		0.05 mg/m <sup>3</sup>
Quartz (Respirable)	10 mg/m <sup>3</sup> (%SiO <sub>2</sub> +2)	
Quartz (Total Dust)	30 mg/m <sup>3</sup> (%SiO <sub>2</sub> +2)	
Chromates	0.1 mg(CrO <sub>3</sub> )/m <sup>3</sup>	0.05 mg(Cr)/m <sup>3</sup>
Nuisance Dust		
(Respirable)	5 mg/m <sup>3</sup>	3 mg/m <sup>3</sup>
(Total / Inhalable)	15 mg/m <sup>3</sup>	10 mg/m <sup>3</sup>

\*This value is for particulate matter containing no asbestos and < 1% crystalline silica.

#### 3. HAZARD IDENTIFICATION

##### Emergency Overview

Solid; grey powder; odorless.

##### Potential Health Effects

**INHALATION (acute):** Breathing dust may cause nose, throat or lung irritation and choking. The described effect depends on the degree of exposure.

**INHALATION (chronic):** Prolonged or repeated exposure may cause lung injury including silicosis. This product may contain crystalline silica. Crystalline silica has been classified by IARC as a known human carcinogen. Some human studies indicate potential for lung cancer from crystalline silica exposure. Risk of injury depends on duration and level of exposure. Long term exposures which result in silicosis may result in additional health effects.

**EYE CONTACT (acute/chronic):** May cause eye irritation, severe burns and damage to cornea.

**SKIN CONTACT (acute/chronic):** May cause dry skin, redness, discomfort, irritation or severe burns. May produce allergic reaction potentially associated with hexavalent chromium. Thickening of the skin (scleroderma) may be associated with exposure to high levels of crystalline silica.

**INGESTION (acute/chronic):** Ingestion of large amounts may cause intestinal distress.

#### 4. FIRST AID MEASURES

**INHALATION:** Move person to fresh air. Seek medical attention for discomfort.

**EYE CONTACT:** Rinse thoroughly with water. Seek medical attention for abrasions.

**SKIN CONTACT:** Wash with soap and water. Use moisturizing creams for irritated skin. Seek medical attention for burns.

**INGESTION:** Do not induce vomiting, but drink plenty of water. Seek medical attention for discomfort.

#### 5. FIREFIGHTING MEASURES

**Flashpoint and Method:** None.

**Flammable Limits:** Not combustible.

**Autoignition Temperature:** None.

**General Hazard:** Avoid breathing dust.

**Firefighting Instructions:** Treat adjacent material.

**Firefighting Equipment:** This product is not a fire hazard. Self contained breathing apparatus is recommended to limit exposures to smoke from any combustion source.

**Hazardous Combustion Products:** None.

#### 6. ACCIDENTAL RELEASE MEASURES



## Material Safety Data Sheet , Portland Cement

Page 2 of 2

**General:** Wind blown dust may cause the hazards identified in Section 3. Remove spilled material to limit potential harm.

**Land Spill:** Clean up spilled material.

**Water Spill:** Clean up spilled material.

### 7. HANDLING AND STORAGE

**General:** Avoid accidental release. Store dry and away from water.

**Storage Temperature:** Unlimited.

**Storage Pressure:** Unlimited.

**Empty Containers:** Dispose of containers in an approved landfill or incinerator.

### 8. EXPOSURE CONTROL & PERSONAL PROTECTION

#### Engineering Controls

Use exhaust ventilation to maintain dust levels below exposure limits in workplaces with poor ventilation and dusty conditions.

#### Personal Protection

**RESPIRATORY PROTECTION:** Under ordinary conditions no respiratory protection is required. Wear a NIOSH approved respirator when exposed to dust above exposure limits.

**EYE PROTECTION:** Wear glasses or safety goggles to prevent contact with eyes. Wearing contact lenses when using this product under dusty conditions is not recommended.

**SKIN PROTECTION:** Wear impervious gloves, shoes and protective clothing to prevent skin contact.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure:	Not measurable
Vapor Density:	Not measurable
Specific Gravity:	3.2
Solubility in Water:	Slight (0.1 - 1.0%)
Evaporation Rate:	Not measurable
pH (in water):	12 - 13
Boiling Point:	>1000° C
Freezing Point:	None, solid
Viscosity:	None, solid

### 10. STABILITY AND REACTIVITY

**General:** Product is stable but must be kept dry. Reacts with water forming polymerized silicates and calcium oxide.

**Incompatible Materials and Conditions to Avoid:** Must be kept dry. Dissolves in hydrofluoric acid producing corrosive silicon tetrafluoride gas. Silicates react with powerful oxidizers such as fluorine, chlorine trifluoride and oxygen difluoride.

**Hazardous Decomposition:** None, powdered solid.

### 11. MSDS PREPARATION AND TOXICOLOGICAL INFORMATION

For detailed toxicological information contact:

Environment, Health & Safety and Public Affairs  
Lafarge North America  
12950 Worldgate Drive, Suite 500  
Herndon, VA 20170  
(703) 480-3600

### 12. ECOLOGICAL INFORMATION

For detailed ecological information: See Section 11 above.

### 13. DISPOSAL CONSIDERATIONS

Dispose in landfill in accordance with all applicable regulations. Any disposal practice must be in compliance with local, provincial, state and federal laws and regulations. Contact local environmental agency for specific rules.

### 14. REQUIRED TRANSPORT INFORMATION

Not a hazardous material for DOT or TDG shipping.

### 15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### OSHA Hazard Communication Rule, 29 CFR 1910.1200:

This product is considered by OSHA to be a hazardous chemical and should be included in the employer's hazard communication program.

**CERCLA/SUPERFUND, 40 CFR 117.302:** Not listed.

#### SARA TITLE III, Sections 311-312 Hazard Category:

This product has been reviewed according to the EPA Hazard Categories promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 and is considered a hazardous chemical and a delayed health hazard.

#### SARA Section 313 Information:

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### Toxic Substance Control Act (TSCA):

Some constituents identified in this product are listed on the TSCA Inventory.

#### California Proposition 65:

CHRYSTALLINE SILICA (CAS - 14808-60-7) is considered to be a carcinogen by the state of California.

#### WHMIS Information

This product contains substances considered to be hazardous by Health Canada and is a controlled product. Consult local authorities for acceptable exposure limits. WHMIS Information - 613-957-2342

### 16. OTHER INFORMATION

#### Abbreviations:

CAS No	Chemical Abstract Service number
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
ACGIH	American Conference of Governmental Industrial Hygienists
TLV	Threshold Limit Value
TWA	Time Weighted Average (8 hour)
CL	Ceiling Limit
mg/m <sup>3</sup>	milligrams per cubic meter
IARC	International Agency for Research on Cancer
NIOSH	National Institute for Occupational Safety and Health
pH	negative log of hydrogen ion
>	greater than
DOT	U.S. Department of Transportation
TDG	Transportation of Dangerous Goods
CFR	Code for Federal Regulations
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
SARA	Superfund Amendments and Reauthorization Act
WHMIS	Workplace Hazardous Materials Information System

Information in this MSDS is believed to be current and accurate at the time provided. It is the user's obligation to determine the conditions of safe use of this product.