

MATERIAL SAFETY DATA SHEET
Revision Date: 06/08/2004

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: DARINA® Grease AX 2

MSDS NUMBER: 56260E - 9

PRODUCT CODE(S): 70330

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4427, Houston, TX. 77210-4427

TELEPHONE NUMBERS

Spill Information: (877) 242-7400

Health Information: (877) 504-9351

MSDS Assistance Number: (877) 276-7285

SECTION 2 PRODUCT/INGREDIENTS

CAS#	CONCENTRATION	INGREDIENTS
		Multipurpose Grease
Mixture	85 - 94.99 %weight	Highly refined petroleum oils
Mixture	1 - 2.99 %weight	Additives

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance & Odor: Brown, smooth grease. Mild Hydrocarbon Odor.

Health Hazards: No known immediate health hazards. High-pressure injection under the skin may cause serious damage.

Physical Hazards: No known physical hazards.

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3

Extreme - 4

Inhalation:

Inhalation of vapors (generated at high temperatures only) or oil mist may cause mild irritation of the nose, throat, and respiratory tract.

Eye Irritation:

May cause slight irritation of the eyes. If irritation occurs, a temporary burning sensation, minor redness, swelling, and/or blurred vision may result.

Skin Contact:

May cause slight irritation of the skin. If irritation occurs, a temporary burning sensation and minor redness and/or swelling may result. Release of the material during high-pressure applications may result in injection under the skin causing possible extensive tissue damage which is difficult to heal.

Other adverse effects not expected from brief skin contact.

Ingestion:

Generally considered to have a low order of acute oral toxicity.

Signs and Symptoms:

Irritation as noted above. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

Aggravated Medical Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

SECTION 4 FIRST AID MEASURES

Inhalation:

If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin:

Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye:

Flush eyes with plenty of water while holding eyelids open. Rest eyes for 30

minutes. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment.

Ingestion:

Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Note to Physician:

In general, emesis induction is unnecessary in high viscosity, low volatility products such as oils and greases.

SECTION 5 FIRE FIGHTING MEASURES

Flash Point [Method]: >430 °F/>221.11 °C [Pensky-Martens Closed Cup]

Extinguishing Media:

Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures:

May burn although not readily ignitable.

Spill Management:

Scoop up excess grease. Clean area with appropriate cleaner.

Reporting:

CERCLA: Product is covered by EPA's Comprehensive Environmental Response,

Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures:

Avoid heat, open flames, including pilot lights, and strong oxidizing agents.

Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Handling:

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Contaminated leather articles including shoes cannot be decontaminated and should be destroyed to prevent reuse.

Storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Container Warnings:

Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or perform similar operations on or near containers.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Oil mist, mineral ACGIH TLV TWA: 5 mg/m3 STEL: 10 mg/m3
Oil mist, mineral OSHA PEL TWA: 5 mg/m3

EXPOSURE CONTROLS

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

PERSONAL PROTECTION

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation.

Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

Eye Protection:

Chemical Goggles, or Safety glasses with side shields

Skin Protection:

Use protective clothing which is chemically resistant to this material.

Selection of protective clothing depends on potential exposure conditions and

may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by:

Neoprene, or Nitrile Rubber

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with

the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus for use in environments with unknown concentrations or emergency situations.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance & Odor: Brown, smooth grease. Mild Hydrocarbon Odor.

Appearance: Brown, smooth grease.

Drop Point: > 500 °F

Flash Point: > 430 °F [Pensky-Martens Closed Cup]

Solubility (in Water): Insoluble

Specific Gravity: 0.9

Stability: Stable

SECTION 10 REACTIVITY AND STABILITY

Stability:
Material is stable under normal conditions.

Conditions to Avoid:
Avoid heat and open flames.

Materials to Avoid:
Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:
Thermal decomposition products are highly dependent on combustion conditions.
A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Carbon Monoxide, Carbon Dioxide and other unidentified organic compounds may be formed upon combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Toxicity
Dermal LD50 >5.0 g/kg(Rabbit) OSHA: Non-Toxic Based on components(s)
Oral LD50 >5.0 g/kg(Rat) OSHA: Non-Toxic Based on components(s)
Carcinogenicity Classification
Multipurpose Grease
NTP: No IARC: No ACGIH: No OSHA: No

SECTION 12 ECOLOGICAL INFORMATION

Environmental Impact Summary:
There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

SECTION 13 DISPOSAL CONSIDERATIONS

RCRA Information:

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

SECTION 14 TRANSPORT INFORMATION

US Department of Transportation Classification
This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

International Air Transport Association
Not regulated under IATA rules.

International Maritime Organization Classification
Not regulated under International Maritime Organization rules.

SECTION 15 REGULATORY INFORMATION

FEDERAL REGULATORY STATUS

OSHA Classification:

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Ozone Depleting Substances (40 CFR 82 Clean Air Act):

This material does not contain nor was it directly manufactured with any Class

I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III:

There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312):

Immediate Health:NO Delayed Health:NO Fire:NO Pressure:NO
Reactivity:NO

SARA Toxic Release Inventory (TRI) (313):

There are no components in this product on the SARA 313 list.

Toxic Substances Control Act (TSCA) Status:

All component(s) of this material is(are) listed on the EPA/TSCA Inventory of

Chemical Substances.

Other Chemical Inventories:

Component(s) of this material is (are) listed on the Australian AICS,
Canadian DSL, European EINECS,

State Regulation

This material is not regulated by California Prop 65, New Jersey Right-to-Know

Chemical List or Pennsylvania Right-To-Know Chemical List. However for details on your regulation requirements you should contact the appropriate agency in your state.

SECTION 16 OTHER INFORMATION

Revision#: 9

Revision Date: 06/08/2004

Revisions since last change (discussion): This Material Safety Data Sheet (MSDS) has been reviewed to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-1998). We encourage you to take the opportunity to read the MSDS and review the information contained therein.

SECTION 17 LABEL INFORMATION

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODE(S): 70330

DARINA® Grease AX 2

ATTENTION!

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL ACNE OR DERMATITIS.
HIGH-PRESSURE INJECTION UNDER SKIN MAY CAUSE SERIOUS DAMAGE.

Precautionary Measures:

Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid breathing of vapors, fumes, or mist. Use only with adequate ventilation. Wash thoroughly after handling.

FIRST AID

Inhalation: Remove victim to fresh air and provide oxygen if breathing is difficult. Get medical attention.

Skin Contact: Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility

for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye Contact: Flush eyes with plenty of water while holding eyelids open. Rest eyes for 30 minutes. If redness, burning, blurred vision or swelling occur, transport to nearest medical facility for additional treatment.

Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. If vomiting occurs spontaneously, keep head below hips to prevent

aspiration. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water. Material will float and can be re-ignited on surface of water.

SPILL OR LEAK

Scoop up excess grease. Clean area with appropriate cleaner.

CONTAINS: Highly refined petroleum oils, Mixture; Additives, Mixture

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

TRANSPORTATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address

SOPUS Products
P.O. Box 4427
Houston, TX 77210-4427

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4427, Houston, TX.
77210-4427

Company Product Stewardship & Regulatory Compliance Contact: Timothy W Childs

Phone Number: (713) 241-1524

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE TO

US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT : IT IS PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN. YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE OR DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT

TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE APPROPRIATE

GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE

UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT
DATA,
IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR
EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

30865-11231-100R-06/08/2004

**PERTH**

Tel (08) 9249 7599

Fax (08) 9249 7699

BRISBANE

Tel (07) 3271 5900

Fax (07) 3271 5907

**MELBOURNE**

Tel (03) 9545 1277

Fax (03) 9545 1299

INTERNATIONAL

Tel +61 (8) 9249 7599

Fax +61 (8) 9249 7699

PO Box 148,

Kingsway WA 6065

Material Safety Data Sheet

Lubtac Rod Grease

Down hole hammers & bits
Top hole hammer equipmentDiamond drilling
Three cone rotary drill bits
(TCI or Mill Tooth)
Geological supplies
Radio communications
Drag & blade bits
Drilling fluids
Drilling rigs - all types
Elgi air compressors
Augers, teeth,
ground engaging tools
Drill pipe & subs
Geotechnical drilling supplies
International procurement
Machinery parts & equipment

A Smith/Schlumberger Company

M-I Australia Pty Ltd, 11/251 Adelaide Tce, Perth, WA, 6000
Tel: 08 9325 4822 Fax: 08 9325 1897

MSDS furnished independent of product sale. While every effort has been made to accurately describe this product, some of the data is obtained from sources beyond our direct supervision. We cannot make any assertions as to its reliability or completeness; therefore, user may rely on it only at user's risk. We have made no effort to censor or conceal deleterious aspects of this product. Since we cannot anticipate or control the conditions in which this information and product may be used, we make no guarantee that the precautions we have suggested will be adequate for all individuals and/or situations. It is the obligation of each user of this product to comply with the requirements of all applicable laws regarding use and disposal of this product. Additional information will be furnished upon request to assist the user; however, neither warranty, either expressed or implied, nor liability of any nature with respect to this product or to the data herein is made or incurred hereunder.

For all drilling, mining, geological, geotechnical & radio communications equipment
Web: www.adgtech.com Email: info@adgtech.com

ENVIRONMENTAL AND SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

TRADE NAME: LUBTAC ROD GREASE

GENERIC DESCRIPTION: A MIXTURE OF INORGANIC INERT VISCOSIFIERS, TACKIFIERS, HYDROCARBON OILS AND VEGETABLE OILS.

2. HAZARDOUS INGREDIENTS

MATERIAL COMPONENT	OR	%	DATA
NONE			

3. PHYSICAL DATA

BOILING POINT : 120 °C

MELTING POINT : NA

FREEZING POINT : < 0 °C

pH : 7-8

SPECIFIC GRAVITY : 0.99

APPEARANCE AND : DARK BROWN STRINGY GREASE

4. FIRE AND EXPLOSION DATA

FLASH POINT °C: (AUTO IGNITION TEMPERATURE) > 200 °C

EXTINGUISHING MEDIA : USE EXTINGUISHER USED FOR EXTINGUISHING HYDROPHOBIC MATERIALS

5. HEALTH HAZARD INFORMATION

ROUTES OF EXPOSURE AND EFFECTS

EYES : MODERATE TO SEVERE IRRITATION

INHALATION : NO IRRITATING FUMES ARE PRODUCED AT NORMAL
TEMPERTURES

INGESTION : MAY CAUSE NAUSEA

SKIN : MAY BE IRRITATING TO SENSITIVE SKINS ON
PROLONGED EXPOSURE

6. EMERGENCY AND FIRST AID PROCEDURES

EYES : WIPE OUT WITH DRY CLOTH. USE EYE DROPS IF NECESSARY.
OBTAIN MEDICAL ATTENTION IF NECESSARY

INHALATION : NO IRRITATING FUMES ARE PRODUCED AT NORMAL
TEMPERATURES

INGESTION : WASH MOUTH WITH WATER. INDUCE VOMITING. OBTAIN
MEDICAL ADVICE AS SOON AS POSSIBLE

SKIN : WASH WITH SOAPY WATER. IF DEGREASING OF SKIN HAS
OCCURED, APPLY MOISTURISING CREAM

7. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: **EXTREME HEAT**

INCOMPATABILITY: **NONE**

HAZARDOUS DECOMPOSITION PRODUCTS: **CAN PRODUCE HYDROCARBON
DECOMPOSITION PRODUCT ON BURNING.**

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERISATION: **WILL NOT
OCCUR**

8. SPILL OR LEAK PROCEDURES

CONTAIN SPILL. SCRAPE UP EXCESS PRODUCTS WITH A SPADE. THROW SAND OR WOOD SHAVINGS OVER CONTAMINATED AREA AND SCRAPE UP WITH ASPADE. CONTAMINATED WOOD SHAVINGS OR SAND CAN BE DISCARDED IN ANY RUBBISH STORAGE AREA.

9. INDUSTRIAL HYGEINE CONTROL MEASURES

VENTILATION: NORMAL

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY:	NONE
EYES :	NONE
GLOVES :	YES
OTHER :	CLOTHING PROTECTOR AS REQUIRED TO PROTECT CLOTHES FROM GREASE WHICH IS DIFFICULT TO REMOVE.

10. SPECIAL PRECAUTIONS

NONE

11. OTHER HANDLING AND STORAGE REQUIREMENTS

NONE



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-01-08

Class B2 Flammable
LiquidClass D2B Other Toxic
Effects - Skin IrritantClass D2A Other Toxic
Effects - Carcinogen

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **SHELL JET B WITH ANTI-ICING ADDITIVE**
SYNONYMS: WIDE BOILING RANGE AVIATION TURBINE FUEL
PLUS ANTI ICING ADDITIVE
PRODUCT USE: Fuel
MSDS Number: 141-020

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Naphtha (Petroleum), Full-range Reformed	68919-37-9	>95	Yes
Benzene	71-43-2	0.5 - 1.5	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Bright Clear Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Flammable Liquid.
Irritating to skin.
Contains Benzene.
May cause cancer.
Vapours are moderately irritating to the eyes.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Excessive exposure to benzene may cause leukemia in man.

Handling:

Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

- Firefighting Instructions:** Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Flashback may occur along vapour trail. Do not use water except as a fog. Use water to cool fire exposed containers. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Always stay away from ends of containers due to explosive potential. Fight fire from maximum distance.
- Hazardous Combustion Products:** A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Handling equipment must be grounded. Isolate hazard area and restrict access. Try to work upwind of spill. Avoid direct contact with material. Saturated clothing should be immediately removed to avoid flammability hazard. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand . Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

- Handling:** Extremely flammable. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Never siphon by mouth. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.
- Storage:** Use explosion-proof ventilation to prevent vapour accumulation. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON

THE CONDITIONS OF USE.**OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):**

North American exposure limits have not been established for the product. Consult local authorities for acceptable provincial values.

Recommend SHELL guideline of 125 mg/m³ for vapours (8 hour shift).

Gasoline: 300 ppm (STEL: 500 ppm)

Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Bright Clear
Odour:	Typical Gasoline Odour
Odour Threshold:	Not available
Freezing/Pour Point:	<-51 degrees C
Boiling Point:	60 - 260 degrees C
Density:	750 - 801 kg/m ³ @ 15 degrees C
Vapour Density (Air = 1):	Not available
Vapour Pressure (absolute):	>42 mm Hg @ 38 degrees C
pH:	Not applicable
Flash Point:	Method Tag Closed Cup <1 degrees C
Lower Explosion Limit:	1 % (vol.)
Upper Explosion Limit:	7 % (vol.)
Autoignition Temperature:	Not available
Viscosity:	Not available
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{ow}):	Not available
Water Solubility:	Insoluble

Other Solvents: Hydrocarbon Solvents

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Hazardous Decomposition Products:	Thermal decomposition products are highly dependent on combustion conditions.
Incompatible Materials:	Avoid contact with strong oxidizing agents and acids.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Naphtha (Petroleum), Full-range Reformed	LD50 Oral Rat >28 mL/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
Carcinogenicity and Mutagenicity:	This product contains benzene. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes. Carcinogenic hazard.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. May cause physical fouling of aquatic organisms.
Biodegradability:	Not readily biodegradable. Potential for bioaccumulation.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1863
Proper Shipping Name	FUEL, AVIATION, TURBINE ENGINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Shipping Description	FUEL, AVIATION, TURBINE ENGINE Class 3 UN1863 PG II

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class:	Class B2 Flammable Liquid Class D2B Other Toxic Effects - Skin Irritant Class D2A Other Toxic Effects - Carcinogen
DSL/NDL Status:	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.
Other Regulatory Status:	No Canadian federal standards.

16. ADDITIONAL INFORMATION

LABEL STATEMENTS

Hazard Statement :	Flammable Liquid. Irritating to skin. Contains Benzene. May cause cancer.
Handling Statement:	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.
First Aid Statement :	Wash contaminated skin with soap and water. Flush eyes with water. If overcome by vapours remove to fresh air. Do not induce vomiting. Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 14



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-01-08

Class B2 Flammable
LiquidClass D2B Other Toxic
Effects - Skin IrritantClass D2A Other Toxic
Effects - Carcinogen

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **SHELL JET B WITH ANTI-ICING ADDITIVE**
SYNONYMS: WIDE BOILING RANGE AVIATION TURBINE FUEL
PLUS ANTI ICING ADDITIVE
PRODUCT USE: Fuel
MSDS Number: 141-020

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Naphtha (Petroleum), Full-range Reformed	68919-37-9	>95	Yes
Benzene	71-43-2	0.5 - 1.5	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Bright Clear Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Flammable Liquid.
Irritating to skin.
Contains Benzene.
May cause cancer.
Vapours are moderately irritating to the eyes.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Excessive exposure to benzene may cause leukemia in man.

Handling:

Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

- Firefighting Instructions:** Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Flashback may occur along vapour trail. Do not use water except as a fog. Use water to cool fire exposed containers. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Always stay away from ends of containers due to explosive potential. Fight fire from maximum distance.
- Hazardous Combustion Products:** A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Handling equipment must be grounded. Isolate hazard area and restrict access. Try to work upwind of spill. Avoid direct contact with material. Saturated clothing should be immediately removed to avoid flammability hazard. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. For large spills remove by mechanical means and place in containers. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand . Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

- Handling:** Extremely flammable. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Never siphon by mouth. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.
- Storage:** Use explosion-proof ventilation to prevent vapour accumulation. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON

THE CONDITIONS OF USE.**OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):**

North American exposure limits have not been established for the product. Consult local authorities for acceptable provincial values.

Recommend SHELL guideline of 125 mg/m³ for vapours (8 hour shift).

Gasoline: 300 ppm (STEL: 500 ppm)

Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Bright Clear
Odour:	Typical Gasoline Odour
Odour Threshold:	Not available
Freezing/Pour Point:	<-51 degrees C
Boiling Point:	60 - 260 degrees C
Density:	750 - 801 kg/m ³ @ 15 degrees C
Vapour Density (Air = 1):	Not available
Vapour Pressure (absolute):	>42 mm Hg @ 38 degrees C
pH:	Not applicable
Flash Point:	Method Tag Closed Cup <1 degrees C
Lower Explosion Limit:	1 % (vol.)
Upper Explosion Limit:	7 % (vol.)
Autoignition Temperature:	Not available
Viscosity:	Not available
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{ow}):	Not available
Water Solubility:	Insoluble

Other Solvents: Hydrocarbon Solvents

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Hazardous Decomposition Products:	Thermal decomposition products are highly dependent on combustion conditions.
Incompatible Materials:	Avoid contact with strong oxidizing agents and acids.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Naphtha (Petroleum), Full-range Reformed	LD50 Oral Rat >28 mL/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
Carcinogenicity and Mutagenicity:	This product contains benzene. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes. Carcinogenic hazard.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. May cause physical fouling of aquatic organisms.
Biodegradability:	Not readily biodegradable. Potential for bioaccumulation.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1863
Proper Shipping Name	FUEL, AVIATION, TURBINE ENGINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Shipping Description	FUEL, AVIATION, TURBINE ENGINE Class 3 UN1863 PG II

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class:	Class B2 Flammable Liquid Class D2B Other Toxic Effects - Skin Irritant Class D2A Other Toxic Effects - Carcinogen
DSL/NDSL Status:	This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.
Other Regulatory Status:	No Canadian federal standards.

16. ADDITIONAL INFORMATION

LABEL STATEMENTS

Hazard Statement :	Flammable Liquid. Irritating to skin. Contains Benzene. May cause cancer.
Handling Statement:	Eliminate all ignition sources. Wear suitable gloves and eye protection. Bond and ground transfer containers and equipment to avoid static accumulation. Avoid prolonged exposure to vapours. Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.
First Aid Statement :	Wash contaminated skin with soap and water. Flush eyes with water. If overcome by vapours remove to fresh air. Do not induce vomiting. Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 14



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-01-08

Class B2 Flammable
LiquidClass D2A Other Toxic
Effects - Carcinogen

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **REGULAR UNLEADED GASOLINE MARKED**
SYNONYMS: Automotive Fuel
Petrol
PRODUCT USE: Fuel
MSDS Number: 215-002

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Gasoline, Natural	8006-61-9	80 - 100	Yes
Benzene	71-43-2	<1.5	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Dyed for tax purposes Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Flammable Liquid.
May cause cancer.
Vapours are moderately irritating to the eyes.
Ingestion may result in vomiting. Avoid aspiration of vomitus into lungs as small quantities may result in aspiration pneumonitis.
May be absorbed by skin contact. Prolonged immersion in liquid may lead to chemical burns.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Excessive exposure to benzene may cause leukemia in man.

Handling:

Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

- Firefighting Instructions:** Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Do not use water except as a fog. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.
- Hazardous Combustion Products:** Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations.

7. HANDLING AND STORAGE

- Handling:** Extremely flammable. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Avoid all direct contact with this material. Avoid prolonged or repeated inhalation of vapours. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Never siphon by mouth. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Launder contaminated clothing prior to reuse. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities.
- Storage:** Store in a cool, dry, well ventilated area, away from heat and ignition sources. Protect against physical damage to containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Gasoline: 300 ppm (STEL: 500 ppm)

Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)

Skin Notation: The occupational exposure limit is based on the fact that skin and/or eye is a major route of exposure through absorption.

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves should be worn at all times when handling this product. PVC or nitrile rubber gloves are recommended. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Dyed for tax purposes
Odour:	Typical Gasoline Odour
Odour Threshold:	>0.25 ppm
Freezing/Pour Point:	Not available
Boiling Point:	35 - 220 degrees C
Density:	750 - 850 kg/m ³ @ 15 degrees C
Vapour Density (Air = 1):	3.5
Vapour Pressure (absolute):	Not available
pH:	Not applicable
Flash Point:	Method Tag Closed Cup = -30 degrees C
Lower Explosion Limit:	1.4 % (vol.)
Upper Explosion Limit:	7.6 % (vol.)
Autoignition Temperature:	280 degrees C
Viscosity:	<1 cSt @ 38 degrees C
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{OW}):	200
Water Solubility:	Insoluble

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Incompatible Materials:	Avoid strong oxidizing agents.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Gasoline, Natural	LD50 Oral Rat = 18800 mg/kg LD50 Dermal Rabbit >8000 mg/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Irritancy:	Based on testing with similar materials, this product is not expected to be a primary skin irritant after exposure of short duration, would not be a skin sensitizer and would not be irritating to the eye.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
Carcinogenicity and Mutagenicity:	This product contains benzene. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. Fish Toxicity: 5 to 40 ppm 96 hr TLm Rainbow Trout Freshwater
Biodegradability:	Not readily biodegradable. Potential for bioaccumulation. Rapid volatilization.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION**Canadian Road and Rail Shipping Classification:**

UN Number	UN1203
Proper Shipping Name	GASOLINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II

Additional Information
Shipping Description

Marine Pollutant
GASOLINE Class 3 UN1203 PG II
Marine Pollutant

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B2 Flammable Liquid
Class D2A Other Toxic Effects - Carcinogen
DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.
Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION

LABEL STATEMENTS

Hazard Statement : Flammable Liquid.
May cause cancer.

Handling Statement: Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 1
Section 2
Section 14



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-01-08

Class B2 Flammable
LiquidClass D2A Other Toxic
Effects - Carcinogen

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **REGULAR UNLEADED GASOLINE MARKED**
SYNONYMS: Automotive Fuel
Petrol
PRODUCT USE: Fuel
MSDS Number: 215-002

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Gasoline, Natural	8006-61-9	80 - 100	Yes
Benzene	71-43-2	<1.5	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Dyed for tax purposes Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Flammable Liquid.
May cause cancer.
Vapours are moderately irritating to the eyes.
Ingestion may result in vomiting. Avoid aspiration of vomitus into lungs as small quantities may result in aspiration pneumonitis.
May be absorbed by skin contact. Prolonged immersion in liquid may lead to chemical burns.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Excessive exposure to benzene may cause leukemia in man.

Handling:

Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

- Firefighting Instructions:** Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Do not use water except as a fog. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.
- Hazardous Combustion Products:** Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations.

7. HANDLING AND STORAGE

- Handling:** Extremely flammable. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Avoid all direct contact with this material. Avoid prolonged or repeated inhalation of vapours. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Never siphon by mouth. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Launder contaminated clothing prior to reuse. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities.
- Storage:** Store in a cool, dry, well ventilated area, away from heat and ignition sources. Protect against physical damage to containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Gasoline: 300 ppm (STEL: 500 ppm)

Benzene (skin) : 0.5 ppm (STEL: 2.5 ppm)

Skin Notation: The occupational exposure limit is based on the fact that skin and/or eye is a major route of exposure through absorption.

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves should be worn at all times when handling this product. PVC or nitrile rubber gloves are recommended. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Dyed for tax purposes
Odour:	Typical Gasoline Odour
Odour Threshold:	>0.25 ppm
Freezing/Pour Point:	Not available
Boiling Point:	35 - 220 degrees C
Density:	750 - 850 kg/m ³ @ 15 degrees C
Vapour Density (Air = 1):	3.5
Vapour Pressure (absolute):	Not available
pH:	Not applicable
Flash Point:	Method Tag Closed Cup = -30 degrees C
Lower Explosion Limit:	1.4 % (vol.)
Upper Explosion Limit:	7.6 % (vol.)
Autoignition Temperature:	280 degrees C
Viscosity:	<1 cSt @ 38 degrees C
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{OW}):	200
Water Solubility:	Insoluble

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Incompatible Materials:	Avoid strong oxidizing agents.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Gasoline, Natural	LD50 Oral Rat = 18800 mg/kg LD50 Dermal Rabbit >8000 mg/kg
Benzene	LD50 Oral Rat = 930 - 5600 mg/kg LC50 Inhalation Rat = 13700 ppm for 4 hours
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Irritancy:	Based on testing with similar materials, this product is not expected to be a primary skin irritant after exposure of short duration, would not be a skin sensitizer and would not be irritating to the eye.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression. Prolonged and repeated exposure may cause serious injury to blood forming organs, resulting in anemia and similar conditions.
Carcinogenicity and Mutagenicity:	This product contains benzene. Epidemiological studies indicate that long term inhalation of benzene vapour can cause leukaemia in man. Benzene has also produced chromosomal aberrations in peripheral blood lymphocytes.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. Fish Toxicity: 5 to 40 ppm 96 hr TLm Rainbow Trout Freshwater
Biodegradability:	Not readily biodegradable. Potential for bioaccumulation. Rapid volatilization.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION**Canadian Road and Rail Shipping Classification:**

UN Number	UN1203
Proper Shipping Name	GASOLINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II

Additional Information
Shipping Description

Marine Pollutant
GASOLINE Class 3 UN1203 PG II
Marine Pollutant

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B2 Flammable Liquid
Class D2A Other Toxic Effects - Carcinogen
DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.
Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION

LABEL STATEMENTS

Hazard Statement : Flammable Liquid.
May cause cancer.

Handling Statement: Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 1
Section 2
Section 14

MATERIAL SAFETY DATA SHEET

Product Trade Name: EZ-MUD®

Revision Date: 16-Feb-2004

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: EZ-MUD®

Synonyms: None

Chemical Family: Blend

Application: Shale Inhibitor

Manufacturer/Supplier Baroid Drilling Fluids
a Product Service Line of Halliburton Energy Services, Inc.
P.O. Box 1675
Houston, TX 77251
Telephone: (281) 871-4000
Emergency Telephone: (800) 666-9260 or (713) 753-3000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335

2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Hydrotreated light petroleum distillate	64742-47-8	10 - 30%	200 mg/m ³	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists. Remove contaminated shoes and discard.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Ingestion Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	> 200
Flash Point/Range (C):	Min: > 200
Flash Point Method:	Not Determined
Autoignition Temperature (F):	PMCC
Autoignition Temperature (C):	> 392
Flammability Limits in Air - Lower (%):	> 200
Flammability Limits in Air - Upper (%):	Not Determined
	Not Determined

Fire Extinguishing Media	Water fog, carbon dioxide, foam, dry chemical.
Special Exposure Hazards	Decomposition in fire may produce toxic gases. Use water spray to cool fire exposed surfaces.
Special Protective Equipment for Fire-Fighters	Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.
NFPA Ratings:	Health 2, Flammability 1, Reactivity 0
HMIS Ratings:	Flammability 1, Reactivity 0, Health 2

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures	Use appropriate protective equipment.
Environmental Precautionary Measures	Prevent from entering sewers, waterways, or low areas.
Procedure for Cleaning / Absorption	Isolate spill and stop leak where safe. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions	Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse.
Storage Information	Store away from oxidizers. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls	A well ventilated area to control dust levels. Local exhaust ventilation should be used in areas without good cross ventilation.
Respiratory Protection	Organic vapor respirator with a dust/mist filter. In high concentrations, supplied air respirator or a self-contained breathing apparatus.
Hand Protection	Impervious rubber gloves.
Skin Protection	Rubber apron.
Eye Protection	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	White to gray
Odor:	Mild hydrocarbon
pH:	6-8

Specific Gravity @ 20 C (Water=1):	1.0
Density @ 20 C (lbs./gallon):	8.3
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	347
Boiling Point/Range (C):	175
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	0.002
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	70
Evaporation Rate (Butyl Acetate=1):	< 1
Solubility in Water (g/100ml):	Partially soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistrokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers.
Hazardous Decomposition Products	Ammonia. Oxides of nitrogen. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.
Skin Contact	May cause skin irritation.
Eye Contact	May cause severe eye irritation.
Ingestion	Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions.
Aggravated Medical Conditions	Lung disorders.
Chronic Effects/Carcinogenicity	No data available to indicate product or components present at greater than 1% are chronic health hazards.
Other Information	None known.
Toxicity Tests	

Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined
Carcinogenicity	Not determined
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined
Persistence/Degradability	BOD(28 Day): 40% of COD
Bio-accumulation	Not Determined

Ecotoxicological Information

Acute Fish Toxicity:	TLM96: >1000 mg/l (Pimephales promelas)
Acute Crustaceans Toxicity:	TLM48: 98 mg/l (Acartia tonsa)
Acute Algae Toxicity:	EC50: 16.70 mg/l (Skeletonema costatum)

Chemical Fate Information	Not determined
Other Information	Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	If empty container retains product residues, all label precautions must be observed. Store away from ignition sources. Transport with all closures in place. Return for reuse or disposal according to national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT
Not restricted

Canadian TDG
Not restricted

ADR Not restricted

Air Transportation

ICAO/IATA
Not restricted

Sea Transportation

IMDG
Not restricted

Other Shipping Information

Labels: None

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity For This Product Not applicable.

EPA RCRA Hazardous Waste Classification If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law Does not apply.

NJ Right-to-Know Law Does not apply.

PA Right-to-Know Law Does not apply.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory.

WHMIS Hazard Class D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-11-06

Supersedes: 2002-08-14



Class B3 Combustible Class D2B Other Toxic
Liquid Effects - Skin Irritant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **LOW SUL. DIESEL FUEL MARKED CP -43 - GEN. ELECTRICITY**
SYNONYMS: Diesel
Automotive Gas Oil
PRODUCT USE: Fuel Solvent
MSDS Number: 329-143

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Fuels, Diesel, No. 2	68476-34-6	>99	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Red Colour Hydrocarbon Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Handling: Combustible Liquid.
Irritating to skin.
Vapours are moderately irritating to the eyes.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Eliminate all ignition sources.
Avoid prolonged exposure to vapours.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: DO NOT INDUCE VOMITING! OBTAIN MEDICAL ATTENTION IMMEDIATELY.
Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Do not give anything by mouth to an unconscious person.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

Firefighting Instructions: Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Caution - Combustible. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Do not use water except as a fog. Product will float and can be reignited on surface of water. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus.

Hazardous Combustion Products: A complex mixture of airborne solid, liquid, particulates and gases will evolve when this material undergoes pyrolysis or combustion. Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Combustible". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Flush area with water to remove trace residue. Dispose of recovered material as noted under Disposal Considerations. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

Handling: Combustible. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Do not pressurize drum containers to empty them. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

Storage: Store in a cool, dry, well ventilated area, away from heat and ignition sources. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

North American exposure limits have not been established for the product. Consult local authorities for acceptable provincial values.

Diesel fuel, as total hydrocarbons: 100 mg/m³

Mechanical Ventilation: Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

- Eye Protection:** Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.
- Skin Protection:** Impervious gloves (viton, nitrile) should be worn at all times when handling this material. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.
- Respiratory Protection:** If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Red Colour
Odour:	Hydrocarbon Odour
Odour Threshold:	Not available
Freezing/Pour Point:	Varies with region and season
Boiling Point:	150 - 380 degrees C
Density:	<876 kg/m ³ @ 15 degrees C
Vapour Density (Air = 1):	Not available
Vapour Pressure (absolute):	Not available
pH:	Not available
Flash Point:	Method Pensky-Martens CC >40 degrees C
Lower Explosion Limit:	1 % (vol.)
Upper Explosion Limit:	6 % (vol.)
Autoignition Temperature:	250 degrees C
Viscosity:	1.4 - 4.1 cSt @ 40 degrees C
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{OW}):	Not available
Water Solubility:	Insoluble

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Hazardous Decomposition Products:	Thermal decomposition products are highly dependent on combustion conditions.
Incompatible Materials:	Avoid strong oxidizing agents.
Conditions of Reactivity:	Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified) Toxicological Data

Fuels, Diesel, No. 2

LD50 Oral Rat >5000 mg/kg

LD50 Dermal Rabbit >2000 mg/kg

Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged exposure to high vapour concentration can cause headache, dizziness, nausea, blurred vision and central nervous system depression.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.
Carcinogenicity and Mutagenicity:	The International Agency for Research on Cancer (IARC) considers that this product is not classifiable as to its carcinogenicity to humans. Middle distillates have caused skin cancers in laboratory animals when applied repeatedly and left in place between applications. This effect is believed to be caused by the continuous irritation of the skin. Good personal hygiene should be maintained to avoid this risk. The American Conference of Governmental Industrial Hygienists (ACGIH) has classified this product as A3 - confirmed animal carcinogen with unknown relevance to humans.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May cause physical fouling of aquatic organisms.
Biodegradability:	Not readily biodegradable. Potential for bioaccumulation.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1202
Proper Shipping Name	DIESEL FUEL
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG III
Shipping Description	DIESEL FUEL Class 3 UN1202 PG III

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B3 Combustible Liquid
Class D2B Other Toxic Effects - Skin Irritant

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act. This product and/or all components are listed on the U.S. EPA TSCA Inventory.

Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION**LABEL STATEMENTS**

Hazard Statement : Combustible Liquid.
Irritating to skin.

Handling Statement: Eliminate all ignition sources.
Avoid prolonged exposure to vapours.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 8
Section 14
Section 11



Material Safety Data Sheet

CALCIUM CHLORIDE, FLAKE

A. GENERAL INFORMATION

TRADE NAME (COMMON NAME): FLAKE CALCIUM CHLORIDE		CAS NUMBER: 10043-52-4 (anhydrous)	
CHEMICAL NAME AND/OR SYNONYM: Calcium Chloride, Dihydrate			
FORMULA: CaCl ₂ - 2H ₂ O		MOLECULAR WEIGHT: 147.02	
MANUFACTURER/ADDRESS: GENERAL CHEMICAL CORPORATION 90 East Halsey Road Parsippany, NJ 07054			
CONTACT: Manager, Product Safety	PHONE NUMBER: (973) 515-1840	LAST ISSUE DATE: September, 1994	CURRENT ISSUE DATE: May, 2001

B. FIRST AID MEASURES

		EMERGENCY PHONE NUMBER: (800) 631-8050
EYES:	Flush promptly with plenty of water, continuing for at least 15 minutes. Get medical attention.	
SKIN:	Wash with plenty of water.	
INHALATION:	Remove to fresh air.	
INGESTION:	If conscious, immediately give 2 to 4 glasses of water, and induce vomiting by touching finger to back of throat. Get medical attention for irritation, ingestion, or discomfort from inhalation.	

C. HAZARDS INFORMATION

INHALATION: Dust or mist inhalation may irritate nose, throat, and lungs.	
INGESTION: Low in toxicity. LD ₅₀ (rat): 1.4 g/kg.* - Reference (e) May irritate gastrointestinal tract. *anhydrous basis.	
SKIN: May cause skin irritation. Under conditions of prolonged contact or when moisture is present, superficial burns may result. Contact with abraded skin or cuts can cause severe necrosis.	
EYES: May irritate or burn eyes.	
PERMISSIBLE CONCENTRATION: AIR (SEE SECTION J) Also, no TLV established by ACGIH.	BIOLOGICAL None
UNUSUAL CHRONIC TOXICITY: None.	

C. HAZARDS (Cont.)

FLASH POINT: Not flammable	AUTO IGNITION TEMPERATURE NA	FLAMMABLE LIMITS IN AIR (% BY VOL.) LOWER - NA UPPER - NA
OPEN CUP <input type="checkbox"/> CLOSED CUP <input type="checkbox"/>		
UNUSUAL FIRE AND EXPLOSION HAZARDS See hazard of contact with zinc as in galvanized iron: Section G.		

D. PRECAUTIONS/PROCEDURES

FIRE EXTINGUISHING AGENTS RECOMMENDED: NA	
FIRE EXTINGUISHING AGENTS TO AVOID: NA	
SPECIAL FIREFIGHTING PRECAUTIONS: None.	
VENTILATION: Local exhaust: In packaging and uploading areas, over open processing equipment, and any other places where dusty or misty condition prevails. Natural ventilation: Adequate for other areas.	
NORMAL HANDLING: Avoid contact with eyes, skin or clothing. Avoid breathing mist. Use good personal hygiene and housekeeping.	
STORAGE: Store in a cool, dry area. Prolonged storage may cause product to cake and become wet from atmospheric moisture.	
SPILL OR LEAK (ALWAYS WEAR PERSONAL PROTECTIVE QUIPMENT – SECTION E) Shovel up dry chemical and place in metal drum with a cover. Cautiously spray residue with plenty of water.	
SPECIAL: PRECAUTIONS/PROCEDURES/LABEL INSTRUCTIONS:	SIGNAL WORD WARNING!

E. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: For dusty or misty condition, wear NIOSH-approved mist respirator.
EYES AND FACE: For dusty or misty condition, or when handling solution where there is reasonable probability of eye contact, wear chemical safety goggles and hat. Under these conditions, do not wear contact lenses.
HANDS, ARMS, AND BODY: As a minimum, wear long-sleeve shirt and trousers, boots, and gloves for routine product use. Cotton gloves permitted for dry product, impervious gloves when using solutions.
OTHER CLOTHING AND EQUIPMENT: Eye-wash facility.

F. PHYSICAL DATA

MATERIAL IS AT NORMAL CONDITIONS: LIQUID <input type="checkbox"/> SOLID <input checked="" type="checkbox"/> GAS <input type="checkbox"/> <input type="checkbox"/> _____		APPEARANCE AND COLOR: Small white flakes; odorless.	
BOILING POINT: Unknown °C MELTING POINT: 176 °C	SPECIFIC GRAVITY: (H ₂ O = 1) 0.835 - Reference (b)	VAPOR DENSITY: (AIR =1) NA: water vapor only.	
SOLUBILITY IN WATER: (% BY WEIGHT) 42 (anhydrous) @ 20°C	pH: Neutral or slightly alkaline - Reference (c).	VAPOR PRESSURE: (mm Hg @ 20°C) <input type="checkbox"/> (PSIG) <input type="checkbox"/> NA	
EVAPORATION RATE: (Butyl acetate=1) <input type="checkbox"/> (Ether = 1.0) <input type="checkbox"/> NA	% VOLATILES BY VOLUME: (AT 20°C) NA		

G. REACTIVITY DATA

STABILITY: UNSTABLE <input type="checkbox"/> STABLE <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA
INCOMPATIBILITY (MATERIALS TO AVOID): Sulfuric acid: yields hydrogen chloride gas, which is corrosive, irritating, and reactive. Water-reactive materials, such as sodium: cause an exothermic reaction. Methyl vinyl ether: starts runaway polymerization reaction – Reference (d). Zinc as in galvanized iron: yields hydrogen gas with solutions, which may explode under these conditions. – Reference (d).	
HAZARDOUS DECOMPOSITION PRODUCTS: None.	
HAZARDOUS POLYMERIZATION: MAY OCCUR <input type="checkbox"/> WILL NOT OCCUR <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA

H. HAZARDOUS INGREDIENTS (MIXTURES ONLY)

MATERIAL OR COMPONENT/C.A.S. #	WT.%	HAZARD DATA (See Sect. J)
NA		

I. ENVIRONMENTAL

DEGRADABILITY/AQUATIC TOXICITY:		OCTANOL/WATER PARTITION COEFFICIENT NA
Aquatic Toxicity: TLm96: over 1000 ppm (anhydrous) – Reference (a).		
EPA HAZARDOUS SUBSTANCE? (CLEAN WATER ACT SECT. 311) YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF SO, REPORTABLE QUANTITY:		40 CFR 116-117
WASTE DISPOSAL METHODS (DISPOSER MUST COMPLY WITH FEDERAL, STATE AND LOCAL DISPOSAL OR DISCHARGE LAWS): Treatment or disposal of waste generated by use of this product should be reviewed in terms of applicable federal, state and local laws and regulations. Users are advised to consult with appropriate regulatory agencies before discharge, treatment or disposal.		
RCRA STATUS OF <u>UNUSED</u> MATERIAL IF DISCARDED: Not a "hazardous waste".	HAZARDOUS WASTE NUMBER: (IF APPLICABLE) --	40 CFR 261

J. REFERENCES

PERMISSIBLE CONCENTRATIONS REFERENCES: None.		
REGULATORY STANDARDS	DOT CLASSIFICATION: Not regulated	49 CFR 173
None.		
GENERAL: (a) NIOSH, Registry of Toxic Effects of Chemical Substances, 1979, Accession No. EV 98 00 000. (b) Weast, R.C. editor, CRC Handbook of Chemistry and Physics, 60 th Edition, 1979-80, CRC Press, Inc., Boca Raton 33431. (c) Hawley, G.N., editor, Condensed Chemical Dictionary, 9 th Edition, 1977, Van Nostrand Reinhold, NYC. (d) Brethwick, L., Handbook of Reactive Chemical Hazards, 2 nd Edition, 1979, Butterworths, Boston. (e) General Chemical Corporation tests, unpublished. (A solution of 25 g/100 ml water was used).		

K. ADDITIONAL INFORMATION

None.

GC-1002

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION.

GENERAL CHEMICAL CORPORATION PROVIDES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN.



Material Safety Data Sheet

CALCIUM CHLORIDE, FLAKE

A. GENERAL INFORMATION

TRADE NAME (COMMON NAME): FLAKE CALCIUM CHLORIDE		CAS NUMBER: 10043-52-4 (anhydrous)	
CHEMICAL NAME AND/OR SYNONYM: Calcium Chloride, Dihydrate			
FORMULA: CaCl ₂ - 2H ₂ O		MOLECULAR WEIGHT: 147.02	
MANUFACTURER/ADDRESS: GENERAL CHEMICAL INDUSTRIAL PRODUCTS 90 East Halsey Road Parsippany, NJ 07054			
CONTACT: Manager, Product Safety	PHONE NUMBER: (973) 515-1840	LAST ISSUE DATE: September, 1994	CURRENT ISSUE DATE: March, 2004

B. FIRST AID MEASURES

		EMERGENCY PHONE NUMBER: (800) 631-8050
EYES:	Flush promptly with plenty of water, continuing for at least 15 minutes. Get medical attention.	
SKIN:	Wash with plenty of water.	
INHALATION:	Remove to fresh air.	
INGESTION:	If conscious, immediately give 2 to 4 glasses of water, and induce vomiting by touching finger to back of throat. Get medical attention for irritation, ingestion, or discomfort from inhalation.	

C. HAZARDS INFORMATION

INHALATION: Dust or mist inhalation may irritate nose, throat, and lungs.	
INGESTION: Low in toxicity. LD ₅₀ (rat): 1.4 g/kg.* - Reference (e) May irritate gastrointestinal tract. *anhydrous basis.	
SKIN: May cause skin irritation. Under conditions of prolonged contact or when moisture is present, superficial burns may result. Contact with abraded skin or cuts can cause severe necrosis.	
EYES: May irritate or burn eyes.	
PERMISSIBLE CONCENTRATION: AIR (SEE SECTION J) Also, no TLV established by ACGIH.	BIOLOGICAL None
UNUSUAL CHRONIC TOXICITY: None.	

C. HAZARDS (Cont.)

FLASH POINT: Not flammable	AUTO IGNITION TEMPERATURE NA	FLAMMABLE LIMITS IN AIR (% BY VOL.) LOWER - NA UPPER - NA
OPEN CUP <input type="checkbox"/> CLOSED CUP <input type="checkbox"/>		
UNUSUAL FIRE AND EXPLOSION HAZARDS See hazard of contact with zinc as in galvanized iron: Section G.		

D. PRECAUTIONS/PROCEDURES

FIRE EXTINGUISHING AGENTS RECOMMENDED: NA	
FIRE EXTINGUISHING AGENTS TO AVOID: NA	
SPECIAL FIREFIGHTING PRECAUTIONS: None.	
VENTILATION: Local exhaust: In packaging and uploading areas, over open processing equipment, and any other places where dusty or misty condition prevails. Natural ventilation: Adequate for other areas.	
NORMAL HANDLING: Avoid contact with eyes, skin or clothing. Avoid breathing mist. Use good personal hygiene and housekeeping.	
STORAGE: Store in a cool, dry area. Prolonged storage may cause product to cake and become wet from atmospheric moisture.	
SPILL OR LEAK (ALWAYS WEAR PERSONAL PROTECTIVE QUIPMENT – SECTION E) Shovel up dry chemical and place in metal drum with a cover. Cautiously spray residue with plenty of water.	
SPECIAL: PRECAUTIONS/PROCEDURES/LABEL INSTRUCTIONS:	SIGNAL WORD WARNING!

E. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: For dusty or misty condition, wear NIOSH-approved mist respirator.
EYES AND FACE: For dusty or misty condition, or when handling solution where there is reasonable probability of eye contact, wear chemical safety goggles and hat. Under these conditions, do not wear contact lenses.
HANDS, ARMS, AND BODY: As a minimum, wear long-sleeve shirt and trousers, boots, and gloves for routine product use. Cotton gloves permitted for dry product, impervious gloves when using solutions.
OTHER CLOTHING AND EQUIPMENT: Eye-wash facility.

F. PHYSICAL DATA

MATERIAL IS AT NORMAL CONDITIONS: LIQUID <input type="checkbox"/> SOLID <input checked="" type="checkbox"/> GAS <input type="checkbox"/> <input type="checkbox"/> _____		APPEARANCE AND COLOR: Small white flakes; odorless.	
BOILING POINT: Unknown °C MELTING POINT: 176 °C	SPECIFIC GRAVITY: (H ₂ O = 1) 0.835 - Reference (b)	VAPOR DENSITY: (AIR =1) NA: water vapor only.	
SOLUBILITY IN WATER: (% BY WEIGHT) 42 (anhydrous) @ 20°C	pH: Neutral or slightly alkaline - Reference (c).	VAPOR PRESSURE: (mm Hg @ 20°C) <input type="checkbox"/> (PSIG) <input type="checkbox"/> NA	
EVAPORATION RATE: (Butyl acetate=1) <input type="checkbox"/> (Ether = 1.0) <input type="checkbox"/> NA	% VOLATILES BY VOLUME: (AT 20°C) NA		

G. REACTIVITY DATA

STABILITY: UNSTABLE <input type="checkbox"/> STABLE <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA
INCOMPATIBILITY (MATERIALS TO AVOID): Sulfuric acid: yields hydrogen chloride gas, which is corrosive, irritating, and reactive. Water-reactive materials, such as sodium: cause an exothermic reaction. Methyl vinyl ether: starts runaway polymerization reaction – Reference (d). Zinc as in galvanized iron: yields hydrogen gas with solutions, which may explode under these conditions. – Reference (d).	
HAZARDOUS DECOMPOSITION PRODUCTS: None.	
HAZARDOUS POLYMERIZATION: MAY OCCUR <input type="checkbox"/> WILL NOT OCCUR <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA

H. HAZARDOUS INGREDIENTS (MIXTURES ONLY)

MATERIAL OR COMPONENT/C.A.S. #	WT. %	HAZARD DATA (See Sect. J)
NA		

I. ENVIRONMENTAL

DEGRADABILITY/AQUATIC TOXICITY:		OCTANOL/WATER PARTITION COEFFICIENT NA
Aquatic Toxicity: TLm96: over 1000 ppm (anhydrous) – Reference (a).		
EPA HAZARDOUS SUBSTANCE? (CLEAN WATER ACT SECT. 311) YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF SO, REPORTABLE QUANTITY:		40 CFR 116-117
WASTE DISPOSAL METHODS (DISPOSER MUST COMPLY WITH FEDERAL, STATE AND LOCAL DISPOSAL OR DISCHARGE LAWS): Treatment or disposal of waste generated by use of this product should be reviewed in terms of applicable federal, state and local laws and regulations. Users are advised to consult with appropriate regulatory agencies before discharge, treatment or disposal.		
RCRA STATUS OF <u>UNUSED</u> MATERIAL IF DISCARDED: Not a "hazardous waste".	HAZARDOUS WASTE NUMBER: (IF APPLICABLE) --	40 CFR 261

J. REFERENCES

PERMISSIBLE CONCENTRATIONS REFERENCES: None.		
REGULATORY STANDARDS	DOT CLASSIFICATION: Not regulated	49 CFR 173
None.		
GENERAL: (a) NIOSH, Registry of Toxic Effects of Chemical Substances, 1979, Accession No. EV 98 00 000. (b) Weast, R.C. editor, CRC Handbook of Chemistry and Physics, 60 th Edition, 1979-80, CRC Press, Inc., Boca Raton 33431. (c) Hawley, G.N., editor, Condensed Chemical Dictionary, 9 th Edition, 1977, Van Nostrand Reinhold, NYC. (d) Brethwick, L., Handbook of Reactive Chemical Hazards, 2 nd Edition, 1979, Butterworths, Boston. (e) General Chemical Industrial Products tests, unpublished. (A solution of 25 g/100 ml water was used).		

K. ADDITIONAL INFORMATION

None.

GC-1002

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION.

GENERAL CHEMICAL INDUSTRIAL PRODUCTS PROVIDES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN.



Material Safety Data Sheet

CALCIUM CHLORIDE, FLAKE

A. GENERAL INFORMATION

TRADE NAME (COMMON NAME): FLAKE CALCIUM CHLORIDE		CAS NUMBER: 10043-52-4 (anhydrous)	
CHEMICAL NAME AND/OR SYNONYM: Calcium Chloride, Dihydrate			
FORMULA: CaCl ₂ - 2H ₂ O		MOLECULAR WEIGHT: 147.02	
MANUFACTURER/ADDRESS: GENERAL CHEMICAL INDUSTRIAL PRODUCTS 90 East Halsey Road Parsippany, NJ 07054			
CONTACT: Manager, Product Safety	PHONE NUMBER: (973) 515-1840	LAST ISSUE DATE: September, 1994	CURRENT ISSUE DATE: March, 2004

B. FIRST AID MEASURES

		EMERGENCY PHONE NUMBER: (800) 631-8050
EYES:	Flush promptly with plenty of water, continuing for at least 15 minutes. Get medical attention.	
SKIN:	Wash with plenty of water.	
INHALATION:	Remove to fresh air.	
INGESTION:	If conscious, immediately give 2 to 4 glasses of water, and induce vomiting by touching finger to back of throat. Get medical attention for irritation, ingestion, or discomfort from inhalation.	

C. HAZARDS INFORMATION

INHALATION: Dust or mist inhalation may irritate nose, throat, and lungs.	
INGESTION: Low in toxicity. LD ₅₀ (rat): 1.4 g/kg.* - Reference (e) May irritate gastrointestinal tract. *anhydrous basis.	
SKIN: May cause skin irritation. Under conditions of prolonged contact or when moisture is present, superficial burns may result. Contact with abraded skin or cuts can cause severe necrosis.	
EYES: May irritate or burn eyes.	
PERMISSIBLE CONCENTRATION: AIR (SEE SECTION J) Also, no TLV established by ACGIH.	BIOLOGICAL None
UNUSUAL CHRONIC TOXICITY: None.	

C. HAZARDS (Cont.)

FLASH POINT: Not flammable	AUTO IGNITION TEMPERATURE NA	FLAMMABLE LIMITS IN AIR (% BY VOL.) LOWER - NA UPPER - NA
OPEN CUP <input type="checkbox"/> CLOSED CUP <input type="checkbox"/>		
UNUSUAL FIRE AND EXPLOSION HAZARDS See hazard of contact with zinc as in galvanized iron: Section G.		

D. PRECAUTIONS/PROCEDURES

FIRE EXTINGUISHING AGENTS RECOMMENDED: NA	
FIRE EXTINGUISHING AGENTS TO AVOID: NA	
SPECIAL FIREFIGHTING PRECAUTIONS: None.	
VENTILATION: Local exhaust: In packaging and uploading areas, over open processing equipment, and any other places where dusty or misty condition prevails. Natural ventilation: Adequate for other areas.	
NORMAL HANDLING: Avoid contact with eyes, skin or clothing. Avoid breathing mist. Use good personal hygiene and housekeeping.	
STORAGE: Store in a cool, dry area. Prolonged storage may cause product to cake and become wet from atmospheric moisture.	
SPILL OR LEAK (ALWAYS WEAR PERSONAL PROTECTIVE QUIPMENT – SECTION E) Shovel up dry chemical and place in metal drum with a cover. Cautiously spray residue with plenty of water.	
SPECIAL: PRECAUTIONS/PROCEDURES/LABEL INSTRUCTIONS:	SIGNAL WORD WARNING!

E. PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: For dusty or misty condition, wear NIOSH-approved mist respirator.
EYES AND FACE: For dusty or misty condition, or when handling solution where there is reasonable probability of eye contact, wear chemical safety goggles and hat. Under these conditions, do not wear contact lenses.
HANDS, ARMS, AND BODY: As a minimum, wear long-sleeve shirt and trousers, boots, and gloves for routine product use. Cotton gloves permitted for dry product, impervious gloves when using solutions.
OTHER CLOTHING AND EQUIPMENT: Eye-wash facility.

F. PHYSICAL DATA

MATERIAL IS AT NORMAL CONDITIONS: LIQUID <input type="checkbox"/> SOLID <input checked="" type="checkbox"/> GAS <input type="checkbox"/> <input type="checkbox"/> _____		APPEARANCE AND COLOR: Small white flakes; odorless.	
BOILING POINT: Unknown °C MELTING POINT: 176 °C	SPECIFIC GRAVITY: (H ₂ O = 1) 0.835 - Reference (b)	VAPOR DENSITY: (AIR =1) NA: water vapor only.	
SOLUBILITY IN WATER: (% BY WEIGHT) 42 (anhydrous) @ 20°C	pH: Neutral or slightly alkaline - Reference (c).	VAPOR PRESSURE: (mm Hg @ 20°C) <input type="checkbox"/> (PSIG) <input type="checkbox"/> NA	
EVAPORATION RATE: (Butyl acetate=1) <input type="checkbox"/> (Ether = 1.0) <input type="checkbox"/> NA	% VOLATILES BY VOLUME: (AT 20°C) NA		

G. REACTIVITY DATA

STABILITY: UNSTABLE <input type="checkbox"/> STABLE <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA
INCOMPATIBILITY (MATERIALS TO AVOID): Sulfuric acid: yields hydrogen chloride gas, which is corrosive, irritating, and reactive. Water-reactive materials, such as sodium: cause an exothermic reaction. Methyl vinyl ether: starts runaway polymerization reaction – Reference (d). Zinc as in galvanized iron: yields hydrogen gas with solutions, which may explode under these conditions. – Reference (d).	
HAZARDOUS DECOMPOSITION PRODUCTS: None.	
HAZARDOUS POLYMERIZATION: MAY OCCUR <input type="checkbox"/> WILL NOT OCCUR <input checked="" type="checkbox"/>	CONDITIONS TO AVOID: NA

H. HAZARDOUS INGREDIENTS (MIXTURES ONLY)

MATERIAL OR COMPONENT/C.A.S. #	WT. %	HAZARD DATA (See Sect. J)
NA		

I. ENVIRONMENTAL

DEGRADABILITY/AQUATIC TOXICITY:		OCTANOL/WATER PARTITION COEFFICIENT NA
Aquatic Toxicity: TLm96: over 1000 ppm (anhydrous) – Reference (a).		
EPA HAZARDOUS SUBSTANCE? (CLEAN WATER ACT SECT. 311) YES <input type="checkbox"/> NO <input checked="" type="checkbox"/> IF SO, REPORTABLE QUANTITY:		40 CFR 116-117
WASTE DISPOSAL METHODS (DISPOSER MUST COMPLY WITH FEDERAL, STATE AND LOCAL DISPOSAL OR DISCHARGE LAWS): Treatment or disposal of waste generated by use of this product should be reviewed in terms of applicable federal, state and local laws and regulations. Users are advised to consult with appropriate regulatory agencies before discharge, treatment or disposal.		
RCRA STATUS OF <u>UNUSED</u> MATERIAL IF DISCARDED: Not a "hazardous waste".	HAZARDOUS WASTE NUMBER: (IF APPLICABLE) --	40 CFR 261

J. REFERENCES

PERMISSIBLE CONCENTRATIONS REFERENCES: None.		
REGULATORY STANDARDS	DOT CLASSIFICATION: Not regulated	49 CFR 173
None.		
GENERAL: (a) NIOSH, Registry of Toxic Effects of Chemical Substances, 1979, Accession No. EV 98 00 000. (b) Weast, R.C. editor, CRC Handbook of Chemistry and Physics, 60 th Edition, 1979-80, CRC Press, Inc., Boca Raton 33431. (c) Hawley, G.N., editor, Condensed Chemical Dictionary, 9 th Edition, 1977, Van Nostrand Reinhold, NYC. (d) Brethwick, L., Handbook of Reactive Chemical Hazards, 2 nd Edition, 1979, Butterworths, Boston. (e) General Chemical Industrial Products tests, unpublished. (A solution of 25 g/100 ml water was used).		

K. ADDITIONAL INFORMATION

None.

GC-1002

THIS MATERIAL SAFETY DATA SHEET IS OFFERED SOLELY FOR YOUR INFORMATION, CONSIDERATION AND INVESTIGATION.

GENERAL CHEMICAL INDUSTRIAL PRODUCTS PROVIDES NO WARRANTIES, EITHER EXPRESS OR IMPLIED, AND ASSUMES NO RESPONSIBILITY FOR THE ACCURACY OR COMPLETENESS OF THE DATA CONTAINED HEREIN.



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-03-09

Class B2 Flammable
LiquidClass D2B Other Toxic
Effects - Skin Irritant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **SHELL AVGAS 100 LL**
SYNONYMS: AVIATION GASOLINE
PRODUCT USE: Fuel
MSDS Number: 101-200

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Naphtha (Petroleum), Light Alkylate	64741-66-8	70 - 90	Yes
Toluene	108-88-3	10 - 30	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Blue Colour Clear Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Handling: Flammable Liquid.
Irritating to skin.
Vapours are moderately irritating to the eyes.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: Do not induce vomiting. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Do not give anything by mouth to an unconscious person. Obtain medical attention immediately.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

Firefighting Instructions: Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Product will float and can be reignited on surface of water. Do not use water except as a fog. Use water to cool fire exposed containers. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Always stay away from ends of containers due to explosive potential. Fight fire from maximum distance. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Flashback may occur along vapour trail.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Saturated clothing should be immediately removed to avoid flammability hazard. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. Dispose of recovered material as noted under Disposal Considerations. Explosion and fire is the most immediate problem. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

Handling: Extremely flammable. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Never siphon by mouth. Do not use as a cleaning solvent. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

Storage: Use explosion-proof ventilation to prevent vapour accumulation. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Gasoline: 300 ppm (STEL: 500 ppm)

Toluene (skin): 50 ppm

Skin Notation: The occupational exposure limit is based on the fact that skin and/or eye is a major route of exposure through absorption.

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves (viton, polyvinyl alcohol) should be worn at all times when handling this product. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Blue Colour Clear
Odour:	Typical Gasoline Odour
Odour Threshold:	Not available
Freezing/Pour Point:	Freeze Point = -58 degrees C
Boiling Point:	75 - 170 degrees C
Density:	Not available
Vapour Density (Air = 1):	Not available
Vapour Pressure (absolute):	>285 mm Hg @ 38 degrees C
pH:	Not applicable
Flash Point:	Method Tag Closed Cup <1 degrees C
Lower Explosion Limit:	1.4 % (vol.)
Upper Explosion Limit:	7.6 % (vol.)
Autoignition Temperature:	Not available
Viscosity:	Not available
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{OW}):	Not available
Water Solubility:	Insoluble
Other Solvents:	Hydrocarbon Solvents

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Incompatible Materials:	Avoid strong oxidizing agents.

Conditions of Reactivity:

Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Naphtha (Petroleum), Light Alkylate	LC50 Inhalation Rat >11000 mg/m ³ for 4hours LD50 Dermal Rat >4000 mg/kg LD50 Oral Rat >8000 mg/kg
Toluene	LD50 Oral Rat = 5000 mg/kg LC50 Inhalation Rat = 8000 ppm for 4 hours LD50 Dermal Rabbit = 14000 mg/kg
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Formulation:	This product contains n-hexane.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged or repeated exposure to high vapour concentration or ingestion can cause headache, nausea, dizziness, and central nervous system depression, and in rare cases may sensitize heart muscles causing heart arrhythmia. Peripheral neurotoxicity has been reported in connection with over exposure to n-hexane. This product contains low levels of lead. Chronic, low grade exposure to lead compounds could lead to insomnia, anorexia, nausea and vomiting, diarrhea, anemia, sensory loss and muscular weakness.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. Fish Toxicity: 5 to 40 ppm 96 hr TLm Rainbow Trout Freshwater
Biodegradability:	Not available. Rapid volatilization.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1203
Proper Shipping Name	GASOLINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Additional Information	Marine Pollutant
Shipping Description	GASOLINE Class 3 UN1203 PG II Marine Pollutant

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B2 Flammable Liquid
Class D2B Other Toxic Effects - Skin Irritant

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.

Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION**LABEL STATEMENTS**

Hazard Statement : Flammable Liquid.
Irritating to skin.

Handling Statement: Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 14



Shell Canada Limited

Material Safety Data Sheet

Effective Date: 2002-08-14

Supersedes: 2001-03-09

Class B2 Flammable
LiquidClass D2B Other Toxic
Effects - Skin Irritant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **SHELL AVGAS 100 LL**
SYNONYMS: AVIATION GASOLINE
PRODUCT USE: Fuel
MSDS Number: 101-200

MANUFACTURER

Shell Canada Limited
P.O. Box 100, Station M
400-4th Ave. S.W.
Calgary, AB Canada
T2P 2H5

TELEPHONE NUMBERS**Shell Emergency Number**

1-800-661-7378

CANUTEC 24 HOUR EMERGENCY NUMBER

613-996-6666

For general information:

1-800-661-1600

For MSDS information:

403-691-3982

(From 7:30 to 4:30 Mountain Time)

403-691-2220

This MSDS was prepared by the Toxicology and Product Stewardship Section of Shell Canada Limited.

*An asterisk in the product name designates a trade-mark(s) of Shell Canada Limited, used under license by Shell Canada Products.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component Name	CAS Number	% Range	WHMIS Controlled
Naphtha (Petroleum), Light Alkylate	64741-66-8	70 - 90	Yes
Toluene	108-88-3	10 - 30	Yes

See Section 8 for Occupational Exposure Guidelines.

3. HAZARDS IDENTIFICATION

Physical Description: Liquid Blue Colour Clear Typical Gasoline Odour

Routes of Exposure: Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.

Hazards:

Handling: Flammable Liquid.
Irritating to skin.
Vapours are moderately irritating to the eyes.
Vapours are moderately irritating to the respiratory passages. The liquid when accidentally aspirated into the lungs can cause a severe inflammation of the lung.
Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

For further information on health effects, see Section 11.

4. FIRST AID

Eyes: Flush eyes with water for at least 15 minutes while holding eyelids open. If irritation occurs and persists, obtain medical attention.

Skin: Wash contaminated skin with mild soap and water for 15 minutes. If irritation occurs and persists, obtain medical attention.

Ingestion: Do not induce vomiting. Guard against aspiration into lungs by having the individual turn on to their left side. If vomiting occurs spontaneously keep head below hips to prevent aspiration of liquid into the lungs. Do not give anything by mouth to an unconscious person. Obtain medical attention immediately.

Inhalation: Remove victim from further exposure and restore breathing, if required. Obtain medical attention.

Notes to Physician: The main hazard following accidental ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. If more than 2.0 mL/kg has been ingested, vomiting should be induced with supervision. If symptoms such as loss of gag reflex, convulsions or unconsciousness occur before vomiting, gastric lavage with a cuffed endotracheal tube should be considered.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Dry Chemical
Carbon Dioxide
Foam
Water Fog

Firefighting Instructions: Extremely flammable. Vapour forms a flammable/explosive mixture with air between upper and lower flammable limits. Vapours may travel along ground and flashback along vapour trail may occur. Product will float and can be reignited on surface of water. Do not use water except as a fog. Use water to cool fire exposed containers. Containers exposed to intense heat from fires should be cooled with water to prevent vapour pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure. Always stay away from ends of containers due to explosive potential. Fight fire from maximum distance. Do not enter confined fire space without adequate protective clothing and an approved positive pressure self-contained breathing apparatus. Flashback may occur along vapour trail.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide and unidentified organic compounds may be formed upon combustion.

6. ACCIDENTAL RELEASE MEASURES

Issue warning "Flammable". Eliminate all ignition sources. Isolate hazard area and restrict access. Handling equipment must be grounded. Try to work upwind of spill. Avoid direct contact with material. Saturated clothing should be immediately removed to avoid flammability hazard. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Dike and contain land spills; contain water spills by booming. Use water fog to knock down vapours; contain runoff. Absorb residue or small spills with absorbent material and remove to non-leaking containers for disposal. Recommended materials: Clay or Sand Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. Dispose of recovered material as noted under Disposal Considerations. Explosion and fire is the most immediate problem. Notify appropriate environmental agency(ies).

7. HANDLING AND STORAGE

Handling: Extremely flammable. Avoid excessive heat, sparks, open flames and all other sources of ignition. Fixed equipment as well as transfer containers and equipment should be grounded to prevent accumulation of static charge. Vapours are heavier than air and will settle and collect in low areas and pits, displacing breathing air. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapours are gone. Vapours may accumulate and travel to distant ignition sources and flashback. Do not cut, drill, grind, weld or perform similar operations on or near containers. Empty containers are hazardous, may contain flammable/explosive dusts, residues or vapours. Never siphon by mouth. Do not use as a cleaning solvent. Wash with soap and water prior to eating, drinking, smoking, applying cosmetics or using toilet facilities. Launder contaminated clothing prior to reuse. Use good personal hygiene.

Storage: Use explosion-proof ventilation to prevent vapour accumulation. Keep container tightly closed.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

THE FOLLOWING INFORMATION, WHILE APPROPRIATE FOR THIS PRODUCT, IS GENERAL IN NATURE. THE SELECTION OF PERSONAL PROTECTIVE EQUIPMENT WILL VARY DEPENDING ON THE CONDITIONS OF USE.

OCCUPATIONAL EXPOSURE LIMITS (Current ACGIH TLV/TWA unless otherwise noted):

Gasoline: 300 ppm (STEL: 500 ppm)

Toluene (skin): 50 ppm

Skin Notation: The occupational exposure limit is based on the fact that skin and/or eye is a major route of exposure through absorption.

Mechanical Ventilation: Use explosion-proof ventilation as required to control vapour concentrations. Concentrations in air should be maintained below lower explosive limit at all times or below the recommended threshold limit value if unprotected personnel are involved. Make up air should always be supplied to balance air exhausted (either generally or locally). For personnel entry into confined spaces (i.e. bulk storage tanks) a proper confined space entry procedure must be followed including ventilation and testing of tank atmosphere.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Chemical safety goggles and/or full face shield to protect eyes and face, if product is handled such that it could be splashed into eyes. Provide an eyewash station in the area.

Skin Protection: Impervious gloves (viton, polyvinyl alcohol) should be worn at all times when handling this product. In confined spaces or where the risk of skin exposure is much higher, impervious clothing should be worn. Safety showers should be available for emergency use.

Respiratory Protection: If exposure exceeds occupational exposure limits, use an appropriate NIOSH-approved respirator. Use a NIOSH-approved chemical cartridge respirator with organic vapour cartridges or use a NIOSH-approved supplied-air respirator. For high airborne concentrations, use a NIOSH-approved supplied-air respirator, either self-contained or airline breathing apparatus, operated in positive pressure mode.

9. PHYSICAL DATA

Physical State:	Liquid
Appearance:	Blue Colour Clear
Odour:	Typical Gasoline Odour
Odour Threshold:	Not available
Freezing/Pour Point:	Freeze Point = -58 degrees C
Boiling Point:	75 - 170 degrees C
Density:	Not available
Vapour Density (Air = 1):	Not available
Vapour Pressure (absolute):	>285 mm Hg @ 38 degrees C
pH:	Not applicable
Flash Point:	Method Tag Closed Cup <1 degrees C
Lower Explosion Limit:	1.4 % (vol.)
Upper Explosion Limit:	7.6 % (vol.)
Autoignition Temperature:	Not available
Viscosity:	Not available
Evaporation Rate (n-BuAc = 1):	Not available
Partition Coefficient (K_{OW}):	Not available
Water Solubility:	Insoluble
Other Solvents:	Hydrocarbon Solvents

10. STABILITY AND REACTIVITY

Chemically Stable:	Yes
Hazardous Polymerization:	No
Sensitive to Mechanical Impact:	No
Sensitive to Static Discharge:	Yes
Incompatible Materials:	Avoid strong oxidizing agents.

Conditions of Reactivity:

Avoid excessive heat, open flames and all ignition sources.

11. TOXICOLOGICAL INFORMATION

Ingredient (or Product if not specified)	Toxicological Data
Naphtha (Petroleum), Light Alkylate	LC50 Inhalation Rat >11000 mg/m ³ for 4hours LD50 Dermal Rat >4000 mg/kg LD50 Oral Rat >8000 mg/kg
Toluene	LD50 Oral Rat = 5000 mg/kg LC50 Inhalation Rat = 8000 ppm for 4 hours LD50 Dermal Rabbit = 14000 mg/kg
Routes of Exposure:	Exposure may occur via inhalation, ingestion, skin absorption and skin or eye contact.
Formulation:	This product contains n-hexane.
Irritancy:	This product is expected to be irritating to skin but is not predicted to be a skin sensitizer.
Chronic Effects:	Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. Prolonged or repeated exposure to high vapour concentration or ingestion can cause headache, nausea, dizziness, and central nervous system depression, and in rare cases may sensitize heart muscles causing heart arrhythmia. Peripheral neurotoxicity has been reported in connection with over exposure to n-hexane. This product contains low levels of lead. Chronic, low grade exposure to lead compounds could lead to insomnia, anorexia, nausea and vomiting, diarrhea, anemia, sensory loss and muscular weakness.
Pre-existing Conditions:	Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

12. ECOLOGICAL INFORMATION

Environmental Effects:	Do not allow product or runoff from fire control to enter storm or sanitary sewers, lakes, rivers, streams, or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities. May be harmful to aquatic life. Fish Toxicity: 5 to 40 ppm 96 hr TLm Rainbow Trout Freshwater
Biodegradability:	Not available. Rapid volatilization.

13. DISPOSAL CONSIDERATIONS

Waste management priorities (depending on volumes and concentration of waste) are: 1. recycle (reprocess), 2. energy recovery (cement kilns, thermal power generation), 3. incineration, 4. disposal at a licenced waste disposal facility. Do not attempt to combust waste on-site. Incinerate at a licenced waste disposal site with approval of environmental authority.

14. TRANSPORTATION INFORMATION

Canadian Road and Rail Shipping Classification:

UN Number	UN1203
Proper Shipping Name	GASOLINE
Hazard Class	Class 3 Flammable Liquids
Packing Group	PG II
Additional Information	Marine Pollutant
Shipping Description	GASOLINE Class 3 UN1203 PG II Marine Pollutant

15. REGULATORY INFORMATION

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Class: Class B2 Flammable Liquid
Class D2B Other Toxic Effects - Skin Irritant

DSL/NDSL Status: This product, or all components, are listed on the Domestic Substances List, as required under the Canadian Environmental Protection Act.

Other Regulatory Status: No Canadian federal standards.

16. ADDITIONAL INFORMATION**LABEL STATEMENTS**

Hazard Statement : Flammable Liquid.
Irritating to skin.

Handling Statement: Eliminate all ignition sources.
Wear suitable gloves and eye protection.
Bond and ground transfer containers and equipment to avoid static accumulation.
Avoid prolonged exposure to vapours.
Empty containers are hazardous, may contain flammable / explosive dusts, liquid residue or vapours. Keep away from sparks and open flames.

First Aid Statement : Wash contaminated skin with soap and water.
Flush eyes with water.
If overcome by vapours remove to fresh air.
Do not induce vomiting.
Obtain medical attention.

Revisions: This MSDS has been reviewed and updated.
Changes have been made to:
Section 14

MATERIAL SAFETY DATA SHEET
Revision Date: 06/04/2003

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: Tellus® Oil T 32

MSDS NUMBER: 60532E - 9

PRODUCT CODE(S): 65401

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX. 77210-4453

TELEPHONE NUMBERS

Spill Information: (877) 242-7400

Health Information: (877) 504-9351

MSDS Assistance Number: (877) 276-7285

SECTION 2 PRODUCT/INGREDIENTS

CAS#	CONCENTRATION	INGREDIENTS
		Hydraulic Oil
Mixture	85 - 94.99 %weight	Highly refined petroleum oils
Proprietary	3 - 8.99 %weight	Proprietary additives (contains <1% zinc)

SECTION 3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Appearance & Odor: Pale liquid. Mild odor.

Health Hazards: No known immediate health hazards. High-pressure injection under the skin may cause serious damage.

Physical Hazards: No known physical hazards.

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

Hazard Rating: Least - 0 Slight - 1 Moderate - 2 High - 3

Extreme - 4

Inhalation:

Inhalation of vapors (generated at high temperatures only) or oil mist may

cause mild irritation of the nose, throat, and respiratory tract.

Eye Irritation:

Lubricating oils are generally considered no more than minimally irritating to the eyes.

Skin Contact:

May cause slight irritation of the skin. If irritation occurs, a temporary burning sensation and minor redness and/or swelling may result. Release of the material during high-pressure applications may result in injection under the skin causing possible extensive tissue damage which is difficult to heal.

Other adverse effects not expected from brief skin contact.

Ingestion:

Lubricating oils are generally no more than slightly toxic if swallowed.

Other Health Effects:

Material may release hydrogen sulfide (H₂S), a highly toxic and extremely flammable gas, when heated to 180 Degrees F or higher. H₂S can cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, vomiting, diarrhea, and pulmonary edema. The odor ("rotten egg") threshold is 0.02 ppm. Do not depend on sense of smell for warning; H₂S rapidly deadens the sense of smell.

Signs and Symptoms:

Irritation as noted above. Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

Aggravated Medical Conditions:

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure to this product.

For additional health information, refer to section 11.

SECTION 4 FIRST AID MEASURES

Inhalation:

If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.

Skin:

Remove contaminated clothing and shoes and wipe excess from skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional

treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment.

Eye:

Flush with water. If irritation occurs, get medical attention.

Ingestion:

Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Note to Physician:

In general, emesis induction is unnecessary in high viscosity, low volatility products such as oils and greases.

SECTION 5 FIRE FIGHTING MEASURES

Flash Point [Method]: >350 °F/>176.67 °C [Cleveland Open Cup]

Extinguishing Media:

Material will float and can be re-ignited on surface of water. Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water.

Fire Fighting Instructions:

Material will not burn unless preheated. Do not enter confined fire space without full bunker gear (helmet with face shield, bunker coats, gloves and rubber boots), including a positive pressure, NIOSH approved, self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Protective Measures:

May burn although not readily ignitable.

Wear appropriate personal protective equipment when cleaning up spills.
Refer

to Section 8.

Spill Management:

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

Place in container for proper disposal.

Reporting:

CERCLA: Product is covered by EPA's Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) petroleum exclusion. Releases to air, land, or water are not reportable under CERCLA (Superfund).

CWA: This product is an oil as defined under Section 311 of EPA's Clean Water Act (CWA). Spills into or leading to surface waters that cause a sheen must be reported to the National Response Center, 1-800-424-8802.

SECTION 7 HANDLING AND STORAGE

Precautionary Measures:

Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet. Launder contaminated clothing before reuse. Properly dispose of contaminated leather articles such as shoes or belts that cannot be decontaminated. Avoid heat, open flames, including pilot lights, and strong oxidizing agents. Use explosion-proof ventilation to prevent vapor accumulation. Ground all handling equipment to prevent sparking.

Material may release hydrogen sulfide (H₂S), a highly toxic and extremely flammable gas, when heated to 180 Degrees F or higher. H₂S may collect in the headspace of the container.

Storage:

Store in a cool, dry place with adequate ventilation. Keep away from open flames and high temperatures.

Container Warnings:

Keep containers closed when not in use. Containers, even those that have been emptied, can contain explosive vapors. Do not cut, drill, grind, weld or

perform similar operations on or near containers.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Oil mist, mineral	ACGIH TLV	TWA: 5 mg/m3	STEL: 10 mg/m3
Oil mist, mineral	OSHA PEL	TWA: 5 mg/m3	
Hydrogen sulfide	ACGIH - TLV	TWA: 10 ppm	STEL: 15 ppm
Hydrogen sulfide	OSHA - PEL	TWA: 10 ppm	STEL: 15 ppm
Hydrogen sulfide		Elevated Temperatures	> 180 F.

EXPOSURE CONTROLS

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits.

PERSONAL PROTECTION

Personal protective equipment (PPE) selections vary based on potential exposure conditions such as handling practices, concentration and ventilation.

Information on the selection of eye, skin and respiratory protection for use with this material is provided below.

Eye Protection:

Chemical Goggles, or Safety glasses with side shields

Skin Protection:

Use protective clothing which is chemically resistant to this material.

Selection of protective clothing depends on potential exposure conditions and

may include gloves, boots, suits and other items. The selection(s) should take into account such factors as job task, type of exposure and durability requirements.

Published literature, test data and/or glove and clothing manufacturers indicate the best protection is provided by:

Neoprene, or Nitrile Rubber

Respiratory Protection:

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, an approved respirator must be worn. Respirator selection, use and maintenance should be in accordance with

the requirements of the OSHA Respiratory Protection Standard, 29 CFR 1910.134.

Types of respirator(s) to be considered in the selection process include:

For Mist: Air Purifying, R or P style NIOSH approved respirator.

For Vapors: Air Purifying, R or P style prefilter & organic cartridge, NIOSH approved respirator. Self-contained breathing apparatus for use in

environments with unknown concentrations or emergency situations.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance & Odor: Pale liquid. Mild odor.
Substance Chemical Family: Lubricants
Appearance: Pale liquid.

Flash Point: > 350 °F [Cleveland Open Cup]

Odor: Mild odor.

Pour Point: -20 °F - -40 °F

Specific Gravity: 0.86 - 0.87

Viscosity: > 20 cSt @ 40 °C

SECTION 10 REACTIVITY AND STABILITY

Stability:
Material is stable under normal conditions.

Conditions to Avoid:
Avoid heat and open flames.

Materials to Avoid:
Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products:
Thermal decomposition products are highly dependent on combustion conditions.
A complex mixture of airborne solids, liquids and gases will evolve when this material undergoes pyrolysis or combustion. Aldehydes, Carbon Monoxide, Carbon Dioxide, Hydrogen Sulfide, Ketones and other unidentified organic compounds may be formed upon combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute Toxicity

Dermal LD50 >5.0 g/kg(Rabbit) OSHA: Non-Toxic Based on components(s)

Oral LD50 >5.0 g/kg(Rat) OSHA: Non-Toxic Based on components(s)

Carcinogenicity Classification

Hydraulic Oil

NTP: No IARC: Not Reviewed ACGIH: No OSHA: No

SECTION 12 ECOLOGICAL INFORMATION

Environmental Impact Summary:

There is no ecological data available for this product. However, this product is an oil. It is persistent and does not readily biodegrade. However, it does not bioaccumulate.

SECTION 13 DISPOSAL CONSIDERATIONS

RCRA Information:

Under RCRA, it is the responsibility of the user of the material to determine, at the time of the disposal, whether the material meets RCRA criteria for hazardous waste. This is because material uses, transformations, mixtures, processes, etc. may affect the classification. Refer to the latest EPA, state and local regulations regarding proper disposal.

SECTION 14 TRANSPORT INFORMATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

International Air Transport Association

Not regulated under IATA rules.

International Maritime Organization Classification

Not regulated under International Maritime Organization rules.

SECTION 15 REGULATORY INFORMATION

FEDERAL REGULATORY STATUS

OSHA Classification:

Product is hazardous according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200, because it carries the occupational exposure limit for mineral oil mist.

Ozone Depleting Substances (40 CFR 82 Clean Air Act):

This material does not contain nor was it directly manufactured with any Class I or Class II ozone depleting substances.

Superfund Amendment & Reauthorization Act (SARA) Title III:

There are no components in this product on the SARA 302 list.

SARA Hazard Categories (311/312):

Immediate Health:NO Delayed Health:NO Fire:NO Pressure:NO
Reactivity:NO

SARA Toxic Release Inventory (TRI) (313):

There are no components in this product on the SARA 313 list.

Toxic Substances Control Act (TSCA) Status:

All component(s) of this material is(are) listed on the EPA/TSCA Inventory of Chemical Substances.

Other Chemical Inventories:

Component(s) of this material is (are) listed on the Australian AICS, Canadian DSL, European EINECS,

State Regulation

This material is not regulated by California Prop 65, New Jersey Right-to-Know

Chemical List or Pennsylvania Right-To-Know Chemical List. However for details on your regulation requirements you should contact the appropriate agency in your state.

SECTION 16 OTHER INFORMATION

Revision#: 9
Revision Date: 06/04/2003
Revisions since last change (discussion): This Material Safety Data Sheet (MSDS) has been newly reviewed to fully comply with the guidance contained in the ANSI MSDS standard (ANSI Z400.1-1998). We encourage you to take the opportunity to read the MSDS and review the information contained therein.

SECTION 17 LABEL INFORMATION

READ AND UNDERSTAND MATERIAL SAFETY DATA SHEET BEFORE HANDLING OR DISPOSING OF PRODUCT. THIS LABEL COMPLIES WITH THE REQUIREMENTS OF THE OSHA HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200) FOR USE IN THE WORKPLACE. THIS LABEL IS NOT INTENDED TO BE USED WITH PACKAGING INTENDED FOR SALE TO CONSUMERS AND MAY NOT CONFORM WITH THE REQUIREMENTS OF THE CONSUMER PRODUCT SAFETY ACT OR OTHER RELATED REGULATORY REQUIREMENTS.

PRODUCT CODE(S): 65401

Tellus® Oil T 32

ATTENTION!

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE OIL ACNE OR DERMATITIS.
HIGH-PRESSURE INJECTION UNDER SKIN MAY CAUSE SERIOUS DAMAGE.

Precautionary Measures:

Avoid prolonged or repeated contact with eyes, skin and clothing. Avoid breathing of vapors, fumes, or mist. Use only with adequate ventilation. Wash thoroughly after handling.

FIRST AID

Inhalation: If the victim has difficulty breathing or tightness of the chest, is dizzy, vomiting or unresponsive, give 100% oxygen with rescue breathing or CPR as required and transport to the nearest medical facility.
Skin Contact: Remove contaminated clothing and shoes and wipe excess from

skin. Flush skin with water, then wash with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned. If material is injected under the skin, transport to the nearest medical facility for additional treatment. If redness, swelling, pain and/or blisters occur, transport to the nearest medical facility for additional treatment. Eye Contact: Flush with water. If irritation occurs, get medical attention. Ingestion: Do not induce vomiting. In general, no treatment is necessary unless large quantities of product are ingested. However, get medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Have victim rinse mouth out with water, then drink sips of water to remove taste from mouth.

FIRE

In case of fire, Use water fog, 'alcohol foam', dry chemical or carbon dioxide (CO2) to extinguish flames. Do not use a direct stream of water. Material will float and can be re-ignited on surface of water.

SPILL OR LEAK

Dike and contain spill.

FOR LARGE SPILLS: Remove with vacuum truck or pump to storage/salvage vessels.

FOR SMALL SPILLS: Soak up residue with an absorbent such as clay, sand or other suitable material. Place in non-leaking container and seal tightly for proper disposal.

CONTAINS: Highly refined petroleum oils, Mixture; Proprietary additives (contains <1% zinc), Proprietary

NFPA Rating (Health, Fire, Reactivity): 0, 1, 0

TRANSPORTATION

US Department of Transportation Classification

This material is not subject to DOT regulations under 49 CFR Parts 171-180.

Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

CAUTION: Misuse of empty containers can be hazardous. Empty containers can be hazardous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers might cause fire, explosion or toxic fumes from residues. Do not pressurize or expose to open flames or heat. Keep container closed and drum bungs in place.

Name and Address

SOPUS Products
P.O. Box 4453
Houston, TX 77210-4453

ADMINISTRATIVE INFORMATION

MANUFACTURER ADDRESS: SOPUS Products, P.O. Box 4453, Houston, TX.
77210-4453

Company Product Stewardship & Regulatory Compliance Contact: Timothy W
Childs

Phone Number: (281) 874-7708

THE INFORMATION CONTAINED IN THIS DATA SHEET IS BASED ON THE DATA AVAILABLE
TO

US AT THIS TIME, AND IS BELIEVED TO BE ACCURATE BASED UPON THAT : IT IS
PROVIDED INDEPENDENTLY OF ANY SALE OF THE PRODUCT, FOR PURPOSE OF HAZARD
COMMUNICATION. IT IS NOT INTENDED TO CONSTITUTE PRODUCT PERFORMANCE
INFORMATION, AND NO EXPRESS OR IMPLIED WARRANTY OF ANY KIND IS MADE WITH
RESPECT TO THE PRODUCT, UNDERLYING DATA OR THE INFORMATION CONTAINED HEREIN.
YOU ARE URGED TO OBTAIN DATA SHEETS FOR ALL PRODUCTS YOU BUY, PROCESS, USE
OR

DISTRIBUTE, AND ARE ENCOURAGED TO ADVISE THOSE WHO MAY COME IN CONTACT WITH
SUCH PRODUCTS OF THE INFORMATION CONTAINED HEREIN.

TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH
RESPECT

TO THE PRODUCT, YOU SHOULD CONSULT WITH YOUR LEGAL ADVISOR OR THE
APPROPRIATE

GOVERNMENT AGENCY. WE WILL NOT PROVIDE ADVICE ON SUCH MATTERS, OR BE
RESPONSIBLE FOR ANY INJURY FROM THE USE OF THE PRODUCT DESCRIBED HEREIN. THE
UNDERLYING DATA, AND THE INFORMATION PROVIDED HEREIN AS A RESULT OF THAT
DATA,

IS THE PROPERTY OF SOPUS PRODUCTS AND IS NOT TO BE THE SUBJECT OF SALE OR
EXCHANGE WITHOUT THE EXPRESS WRITTEN CONSENT OF SOPUS PRODUCTS.

38420-11460-100R-06/03/2003

Data Sheet No. S22001 Revision : 23 12 2002

REPLACES S22001 : 22 04 98

This data sheet has been prepared in accordance with the requirements of the Data Sheet Directive 91/155/EEC.

RECOMMENDED USES

Jet A-1 is a refined petroleum product in transit from refineries to distribution terminals, which when supplied will be approved for use :

a fuel for aviation turbine engines designed to run on these fuels when these engines are fitted to aircraft.

If Jet A-1 is used for a purpose not covered in this section, Shell UK Ltd. would be grateful to receive information on the application.

KNOWN MISUSES/ABUSES

Jet A-1 is not to be used as :

a fuel for domestic flueless space heaters ; a solvent or cleaning agent ; as a diesel fuel additive to prevent waxing in cold weather ; or for lighting or brightening fires. It should never be siphoned by sucking the liquid up a tube by mouth, or stored near sources of heat or ignition.

The disposal of Jet A-1 to soil, watercourses and drains is a legal offence.

1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT :	JET A-1
	ALTERNATIVE NAMES :
	DUAL PURPOSE KEROSENE
COMPANY :	SHELL UK OIL PRODUCTS LIMITED
TECHNICAL CONTACT:	PRODUCT HSE DEPARTMENT
ADDRESS :	STANLOW MANUFACTURING COMPLEX, PO BOX 3, ELLESMERE PORT, CH65 4HB
TELEPHONE :	0151-350-4000
EMERGENCY TELEPHONE NUMBER :	0151-350-4595

2: COMPOSITION/INFORMATION ON INGREDIENTS

Jet A-1 is a preparation manufactured from kerosenes derived from crude petroleum, and additives, which do not impart any additional hazard to the finished product.

It is a requirement of H.M. Customs and Excise that all reduced duty fuels contain Coumarin. Rebated fuels marketed within the European Union must also contain C.I. Solvent Yellow 124. Jet A-1 contains both Coumarin and C.I. Solvent Yellow 124 at 2ppm and xx ppm respectively.

The following components, which have health effects, are present at significant concentrations.

Jet A-1 contains the following constituents, which have health effects and are present at significant concentrations.

CONC.	COMPONENT	EINECS	CLASS RISK PHRASES
< 99.9%	Kerosene Unspecified	307-033-2	R10 Flammable Xn R65 Harmful: may cause lung damage if swallowed Xi R38 Irritating to skin N R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Exposure limit values exist for the following constituents:

None

3: HAZARD IDENTIFICATION

Jet A-1 is classified for supply purposes as : Flammable (R10), Harmful (R65: Harmful: may cause lung damage if swallowed), Irritant (R38: Irritating to skin) and Dangerous for the Environment (R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment).

Jet A-1 is a flammable liquid and can readily explode in the presence of electrostatic charges generated, for example, during pumping or tank cleaning or by other sources of ignition or flame impingement on containers.

Exposure to higher vapour concentrations can lead to nausea, headache, drowsiness and dizziness,

The hydrocarbon composition is similar to white spirit, to which an exposure limit applies. Normal exposures in the open air do not, however, present significant health risks provided care is taken to avoid undue exposure to vapours.

Accidental ingestion can lead to chemical burning of the mouth. Ingestion can lead to vomiting and aspiration into the lungs, which can result in chemical pneumonitis, which can be fatal.

Prolonged and repeated skin contact can lead to defatting of the skin, drying, cracking and dermatitis.

Jet A-1 is classified for conveyance purposes as a flammable liquid.

It will not biodegrade in anaerobic conditions and, hence, can be persistent. It contains components which have a high potential to bioaccumulate. It is expected to be slightly toxic to fish.

4: FIRST AID MEASURES

INHALATION

Remove the affected person to fresh air. If breathing has stopped administer artificial respiration. Give cardiac massage if necessary. If the person is breathing, but unconscious, place in the recovery position. Obtain medical assistance immediately.

SKIN

Flush the contaminated skin with water. Use soap if available. Contaminated clothing should be soaked with water, removed, and laundered before reuse.

EYES

Flush the eye with copious quantities of water. If irritation persists refer for medical attention.

INGESTION

DO NOT INDUCE VOMITING. If ingestion is suspected, wash out the mouth with water, and send to hospital immediately. Show this Data Sheet to the physician drawing attention to "Notes for Doctors" in Section 11 below.

5: FIRE-FIGHTING MEASURES

Extinguishants	- Large Fire :	Foam/Water Fog - NEVER USE WATER JET
	- Small Fire :	Foam/Dry Powder/AFFF/CO2/Sand/Earth

6: ACCIDENTAL RELEASE MEASURES

IMMEDIATE EMERGENCY ACTION

Clear people away from the area to a safe place
Do not operate electrical equipment unless flameproof
Summon aid of emergency services if warranted
Treat or refer casualties if necessary

FURTHER ACTION - FIRE

IF SAFE : -
Stop product flow
Use foam, dry powder or carbon dioxide extinguishers
Containers exposed to fire can be cooled by water fog/spray
*** NEVER USE WATER JET ***

FURTHER ACTION - SPILLAGE

IF SAFE : -

Extinguish naked lights, eg cigarettes - AVOID MAKING SPARKS

Position fire fighting equipment

Try to stop the flow of liquid product

Prevent product entering waterways, drains etc. (Covering with wet sacking helps)

Use sand, earth or other suitable material

If product reaches waterways, drains etc. inform local and fire authorities

Reclaim product directly or absorb in suitable medium and transfer to suitable, clearly marked containers

See section 13 for disposal of contaminated product and waste

MARITIME SPILLAGES

Any spillage of Jet A-1 which results in overside pollution must be treated in accordance with the guidelines laid down in the respective Vessel Oil Spill Response Contingency Plan, as required by MARPOL 73/78 Annex 1, Regulation 26. Where the vessel is not required to comply with such legislation, the Owner's and/or Charterer's instructions must be followed. In the absence of any other guidelines, any spillage in territorial/coastal waters must be immediately reported to the appropriate maritime authority, e.g. coast guard, the vessel's local agent if applicable, and the vessel's Owner/Charterer. In international waters, any spillage should be reported to the nearest coastal state, and additional guidance should sought immediately from the vessel's Owner/Charterer.

7: HANDLING AND STORAGE

HANDLING

Jet A-1 is intended to be used in closed systems. When it has to be handled, ensure the operation is carried out in a well ventilated area away from sources of ignition. Electrical continuity is required between the transport and storage vessels during product transfer.

STORAGE

The main considerations relating to the storage of Jet A-1 are the suitability of the storage vessel and the avoidance of sources of ignition.

8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE LIMIT VALUES

The following limits are taken from The Health and Safety Executive's Guidance Note EH40 Occupational Exposure Limits 2002.

UK Occupational Exposure Standards :

None.

RECOMMENDED PROTECTIVE CLOTHING

Impervious gloves and overalls where regular contact is likely, and goggles if there is a risk of splashing

9: PHYSICAL AND CHEMICAL PROPERTIES

Physical State :	Mobile liquid at ambient temperature
Appearance :	Clear water white/straw
Odour :	Characteristic
Acidity/Alkalinity :	Not applicable
Initial Boiling Point :	150 Deg. C.
Flashpoint :	> 38 Deg. C.
Flammability :	Not applicable
Autoflammability :	ca. 220 Deg. C.
Flammability Limits	6 % vol.
- Upper :	1 % vol.
- Lower :	Not applicable
Explosive Properties :	Not applicable
Oxidising Properties :	<0.1 k.Pa
Vapour Pressure @ 20 Deg. C. :	0.77 to 0.81
Relative Density @ 15 Deg. C. :	Very Low
Solubility :	Not available
Water Solubility :	3 to >6 for constituents
Fat solubility/solvent :	> 5
Partition Coefficient, n-octanol water :	1 to 2 cSt.
Vapour Density (Air =1) :	
Viscosity @ 40 Deg. C. :	

10: STABILITY AND REACTIVITY

CONDITIONS TO AVOID

Sources of ignition. Extremes of temperature.

MATERIALS TO AVOID

Strong oxidising agents, eg. chlorates which may be used in agriculture.

DECOMPOSITION PRODUCTS

The substances arising from the thermal decomposition of these products will largely depend upon the conditions bringing about decomposition. The following substances may be expected from normal combustion :

Carbon Dioxide	Polycyclic Aromatic Hydrocarbons
Carbon Monoxide	Unburnt Hydrocarbons
Water	Unidentified Organic and Inorganic Compounds
Particulate Matter	Nitrogen Oxides

11: TOXICOLOGICAL INFORMATION

ACUTE HEALTH HAZARDS AND ADVICE

Jet A-1 is classified as harmful owing to the aspiration hazard and as a skin irritant.

The main hazards are: in the case of inhalation of higher vapour concentrations, of effects on the central nervous system ; in the case of skin contact of, defatting and irritation ; in the unlikely event of ingestion, of aspiration into the lungs with possible resultant chemically induced pneumonia.

Exposure to higher vapour concentrations can lead to nausea, headache, drowsiness and dizziness,

If the product is accidentally ingested, irritation to the gastric mucous membranes can lead to vomiting. If this occurs, there is a high probability of the product being aspirated into the lungs, which can lead to chemical pneumonitis which can be fatal.

INHALATION

Under normal conditions of use Jet A-1 is not expected to present an inhalation hazard.

Precautions :

Inhalation of vapours should be avoided. Where, exceptionally, higher concentrations of the vapour may be encountered, e.g. in the event of a spillage in a badly ventilated area, persons should not be allowed to enter the area, even in an emergency, until the atmosphere has been checked and passed as safe for entry by a competent person.

First Aid :

Remove the affected person to fresh air. If breathing has stopped administer artificial respiration. Give cardiac massage if necessary. If the person is breathing, but unconscious, place in the recovery position. Obtain medical assistance immediately.

SKIN

Jet A-1 is classified as a skin irritant and has a defatting action on the skin.

Precautions :

Avoid contact with the skin by the use of suitable protective clothing.

First Aid :

Flush the contaminated skin with water. Use soap if available. Contaminated clothing should be soaked with water, removed, and laundered before reuse.

EYES

Jet A-1 may cause discomfort to the eye.

Precautions :

If there is a risk of splashing while handling the liquid, suitable eye protection should be used.

First Aid :

Flush the eye with copious quantities of water. If irritation persists refer for medical attention.

INGESTION

Jet A-1 is classified as harmful owing to the aspiration hazard. Accidental ingestion can lead to chemical burning of the mouth. Ingestion can lead to vomiting and aspiration into the lungs, which can result in chemical pneumonitis, which can be fatal.

Precautions :

Accidental ingestion is unlikely. Normal handling and hygiene precautions should be taken to avoid ingestion.

First Aid :

DO NOT INDUCE VOMITING Wash out the mouth with water, and, if ingestion is suspected, send to hospital immediately. Show this Data Sheet to the physician drawing attention to "Notes for Doctors" below.

CHRONIC HEALTH HAZARD AND ADVICE

Prolonged and repeated contact with Jet A-1 can be detrimental to health. The main hazards arise from skin contact and in the inhalation of mists. Skin contact over prolonged periods can lead to defatting of the skin, drying, cracking and possibly dermatitis. Excessive and prolonged inhalation of mists may cause a chronic inflammatory reaction of the lungs and a form of pulmonary fibrosis.

NOTES FOR DOCTORS**HIGH PRESSURE INJECTION INJURIES**

High pressure injection injuries require surgical intervention and possibly steroid therapy to minimise tissue damage and loss of function. Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. PROMPT surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetic, and wide exploration is essential.

INGESTION AND ASPIRATION OF PETROLEUM PRODUCTS

There may be a risk to health where low viscosity products are aspirated into the lungs following vomiting, although this is uncommon in adults. Such aspiration would cause intense local irritation and chemical pneumonitis. Children, and those in whom consciousness is impaired, will be more at risk. Emesis of lubricants is not usually necessary, unless a large amount has been ingested, or some other compound has been dissolved in the product. If this is indicated - for example, when there is rapid onset of CNS depression from a large ingested volume - gastric lavage under controlled hospital conditions, with full protection of the airway is required. Supportive care may include oxygen, arterial blood gas monitoring, respiratory support and, if aspiration has occurred, treatment with corticosteroids and antibiotics. Seizures should be controlled with Diazepam, or appropriate equivalent drug.

12: ECOLOGICAL INFORMATION

Jet A-1 contains kerosene which is classified as toxic to aquatic organisms / may cause long-term adverse effects in the aquatic environment.

AIR

Jet A-1 is a mixture of volatile components, which when released to air will react rapidly with hydroxyl radicals and ozone.

WATER

If released to water, the majority of Jet A-1 will evaporate at a moderate rate but a small proportion will dissolve. Dissolved components will be either absorbed in sediments or evaporate to air. In aerobic water and sediments they will biodegrade, but in anaerobic conditions they will persist. Jet A-1 contains components which have a high potential to bioaccumulate, but is unlikely to persist in the aquatic environment for sufficient time to pose significant hazards.

SOIL

Small volumes released on land will evaporate at a moderate rate, with a proportion of the product being absorbed in the upper soil layers and being subject to biodegradation. Larger volumes may penetrate into anaerobic soil layers in which the product will persist. The product may reach the water table on which it will form a floating layer, and move along with the groundwater flow. In this case the more soluble components, such as aromatics, will cause groundwater contamination.

13: DISPOSAL CONSIDERATIONS

Jet A-1 should be disposed of to a licensed waste contractor. Any disposal route should comply with local byelaws and the requirements of the Environmental Protection Act, 1990. Jet A-1 is subject to the Special Waste Regulations 1996.

14: TRANSPORT INFORMATION

Dangerous for Conveyance

UN Number :	1223
Proper Shipping Name :	Kerosene
Symbol :	Flammable Liquid
Packing Group :	III
Marine Pollutant :	No
IATA/ICAO Hazard Class :	3
IMO Hazard Class :	3.3
Class :	3
Classification Code :	F1
Hazard Identification No. :	30
Hazchem Code :	3 Y

15: REGULATORY INFORMATION

This material has been classified according to the requirements of the Chemicals (Hazard Information and Packaging for Supply) Regulations.

Dangerous for Supply

Symbols :	St. Andrew's Cross Dead Fish and Tree
Categories of danger :	Flammable Harmful Irritant Dangerous for the Environment
Risk Phrases :	R10 Flammable R65 Harmful: may cause lung damage if swallowed R38 Irritating to skin R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment
Safety Phrases :	S2 Keep out of the reach of children S23 Do not breathe vapour S24 Avoid contact with skin S29 Do not empty into drains S43 In case of fire use foam/dry powder/AFFF/CO2 - NEVER USE WATER S61 Avoid release to the environment. Refer to special instructions / safety data sheets S62 If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label
Contains :	kerosene unspecified
Other Information :	Safety data sheet available for professional user on request.

16: OTHER INFORMATION

The references set out below give further information on specific aspects.

LEGISLATION

Consumer Protection Act 1987
Control of Pollution Act 1974
Environmental Protection Act 1990
Factories Act 1961
Health and Safety at Work Act 1974

Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations
Chemical (Hazards, Information, and Packaging for Supply) Regulations
Control of Substances Hazardous to Health Regulations
Dangerous Substances in Harbour Areas Regulations
Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations
Road Traffic (Carriage of Dangerous Substances in Packages etc.) Regulations
Road Traffic (Carriage of Dangerous Substances in Road Tankers and Tank Containers) Regulations
Road Traffic (Training of Drivers of Vehicles Carrying Dangerous Goods) Regulations
Reporting of Injuries, Diseases and Dangerous Occurrences Regulations
Special Waste Regulations

GUIDANCE NOTES

CS/15	The cleaning and gas freeing of tanks containing flammable residues
HS(G)22	Electrical apparatus for use in potentially explosive atmospheres
HS(G)51	The storage of flammable liquids in containers
HS(G)140	The safe use and handling of flammable liquids
HS(G)176	Storing flammable liquids in tanks
HS(G)71	The storage of packaged dangerous substances
EH/40	Occupational Exposure Limits
EH/58	The Carcinogenicity of Mineral Oils
MS24	Health surveillance of occupational skin disease

BRITISH STANDARDS

BS 799	Specification for Oil Burning Equipment
BS 2000	Methods of Test for Petroleum and its Products
BS 2869	Fuel Oils for Oil Engines and Burners for Non-Marine Use
BS 5345	Selection, Installation and Maintenance of Electrical Apparatus for Use in Potentially Explosive Atmospheres
BS 5410	Oil Firing
BS 5958	Control of Undesirable Static Electricity

OTHER LITERATURE

Concawe Report 01/97 Petroleum Products - First Aid Emergency and Medical Advice

Department of the Environment - Waste Management - The Duty of Care - A Code of Practice

European Model Code of Safe Practice in the Storage and Handling of Petroleum Products

Institute of Petroleum Marketing Safety Code

Department of Trade - Code of Portable Tanks and Road Tank Vehicles for the Carriage of Liquid

Dangerous Goods in Ships

ADDRESSES

Concawe, Boulevard du Souverain 165 B - 1160 Brussels, Belgium

Institute of Petroleum, 61 New Cavendish Street, London W1
