### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : PRECISION TM/MC XL EP2

Product code : PXL2P17, PXL2KGL, PXL2DRL, PXL2CBG, PXL2C30,

PXL2, PXL2BLK

Manufacturer or supplier's details

Petro-Canada Lubricants Inc. 2310 Lakeshore Road West Mississauga ON L5J 1K2

Canada

Emergency telephone

number

Suncor Energy: +1 403-296-3000;

Poison Control Centre: Consult local telephone directory for

emergency number(s).

#### Recommended use of the chemical and restrictions on use

Recommended use : PRECISION XL EP greases are high performance, long life,

EP greases designed for trouble-free lubrication of a wide

range of automotive and industrial equipment.

Prepared by : Product Safety: +1 905-804-4752

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Appearance	Stringy, smooth, semi-solid.
Colour	green
Odour	Mild grease like.

#### **Potential Health Effects**

Primary Routes of Entry : Eye contact

Ingestion Inhalation Skin contact

Aggravated Medical

Condition

: None known.

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical Name	CAS-No.	Concentration (%)
Paraffin oils	8012-95-1	70 - 90 %
lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity	72623-85-9	30 - 50 %
distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	10 - 20 %
Long-chain alkyl amine		0.1 - 1 %

#### **SECTION 4. FIRST AID MEASURES**

If inhaled : Move to fresh air.

Artificial respiration and/or oxygen may be necessary.

Seek medical advice.

In case of skin contact : In case of contact, immediately flush eyes or skin with plenty

of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

Wash clothing before reuse.

Seek medical advice.

In the event of a known, or potential, high pressure injection injury, worker should obtain immediate medical evaluation.

In case of eye contact : Remove contact lenses.

Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Obtain medical attention.

If swallowed : Rinse mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

Seek medical advice.

Most important symptoms and effects, both acute and delayed

: First aider needs to protect himself.

### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Unsuitable extinguishing

media

: No information available.

Specific hazards during

firefighting

: Cool closed containers exposed to fire with water spray.

Hazardous combustion

products

: Carbon oxides (CO, CO2), sulphur oxides (SOx), nitrogen oxides (NOx), phosphorus oxides (POx), sulphur compounds (H2S), calcium oxides (CaOx), antimony oxides (SbOx), potassium oxide, aldehydes, sulfides, alkyl mercaptans, diphenylamine, alkenes, smoke and irritating vapours as

products of incomplete combustion.

Further information : Prevent fire extinguishing water from contaminating surface

water or the ground water system.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Evacuate personnel to safe areas.

Material can create slippery conditions.

**Environmental precautions** 

: If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Prevent further leakage or spillage if safe to do so.

Remove all sources of ignition.

Soak up with inert absorbent material. Non-sparking tools should be used. Ensure adequate ventilation.

Contact the proper local authorities.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin, eyes and clothing.

Do not ingest.

Keep away from heat and sources of ignition. Keep container closed when not in use.

Conditions for safe storage : Store in original container.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

# Material Safety Data Sheet PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

Keep in a dry, cool and well-ventilated place.

Keep in properly labelled containers.

To maintain product quality, do not store in heat or direct

sunlight.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Contains no substances with occupational exposure limit values.

**Engineering measures** : No special ventilation requirements. Good general ventilation

should be sufficient to control worker exposure to airborne

contaminants.

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

Filter type : organic vapour filter

Hand protection

Material : neoprene, nitrile, polyvinyl alcohol (PVA), Viton(R).

Remarks : Chemical-resistant, impervious gloves complying with an

approved standard should be worn at all times when handling

chemical products if a risk assessment indicates this is

necessary.

Eye protection : Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : Wash hands and face before breaks and immediately after

handling the product.

Wash contaminated clothing before re-use.

Ensure that eyewash station and safety shower are proximal

to the work-station location.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

Remove and wash contaminated clothing and gloves,

including the inside, before re-use.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

# Material Safety Data Sheet PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

Appearance : Stringy, smooth, semi-solid.

Colour : green

Odour : Mild grease like.

Odour Threshold : No data available
pH : No data available

Pour point : -12 °C (10 °F)Mineral Oil Blend

Boiling point/boiling range : No data available Flash point : 290 °C (554 °F)

Method: Cleveland open cup

Mineral Oil Blend

Fire Point : 300 °C (572 °F)

Mineral Oil Blend

Auto-Ignition Temperature : No data available Evaporation rate : No data available

Flammability : Low fire hazard. This material must be heated before ignition

will occur.

Upper explosion limit : No data available
Lower explosion limit : No data available
Vapour pressure : No data available
Relative vapour density : No data available

Density : 0.9083 kg/l (15 °C / 59 °F)

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

: No data available

Viscosity

Viscosity, kinematic : 219.9 cSt (40 °C / 104 °F)

Mineral Oil Blend

17.9 cSt (100 °C / 212 °F)

Mineral Oil Blend

Explosive properties : Do not pressurise, cut, weld, braze, solder, drill, grind or

expose containers to heat or sources of ignition.

#### **SECTION 10. STABILITY AND REACTIVITY**

Possibility of hazardous

: Hazardous polymerisation does not occur.

reactions

Stable under normal conditions.

Conditions to avoid : No data available

Incompatible materials : Reactive with oxidising agents, reducing agents, acids and

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business. Page: 5 / 9

TM Trademark of Suncor Energy Inc. Used under licence.

### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

alkalis.

Hazardous decomposition

products

: May release COx, NOx, SOx, POx, H2S, CaOx, SbOx, KOx, aldehydes, sulfides, alkyl mercaptans, diphenylamine, alkenes, ammonia, metal oxides, halogenated compounds, smoke and irritating vapours when heated to decomposition.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : Eye contact

exposure

Ingestion
Inhalation
Skin contact

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: No data available

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : Remarks: No data available

**Components:** 

lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high viscosity:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg,

Acute inhalation toxicity : LC50 Rat: > 5.2 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Rabbit: > 2,000 mg/kg,

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg,

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg,

#### Skin corrosion/irritation

**Product:** 

Remarks: No data available

#### **Components:**

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: No skin irritation

#### Serious eye damage/eye irritation

#### **Product:**

Internet: lubricants.petro-canada.ca/msds Petro-Canada is a Suncor Energy business.

### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

Remarks: No data available

#### Components:

#### distillates (petroleum), solvent-dewaxed heavy paraffinic:

Result: No eye irritation

#### Respiratory or skin sensitisation

No data available

#### Germ cell mutagenicity

No data available

#### Carcinogenicity

No data available

#### Reproductive toxicity

No data available

#### STOT - single exposure

No data available

#### STOT - repeated exposure

No data available

#### **Aspiration toxicity**

No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Product:**

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae : Remarks: No data available

Toxicity to bacteria : Remarks: No data available

#### Persistence and degradability

#### **Product:**

Biodegradability : Remarks: No data available

#### Bioaccumulative potential

No data available

# Material Safety Data Sheet PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

Mobility in soil

No data available

Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Offer surplus and non-recyclable solutions to a licensed

disposal company.

Waste must be classified and labelled prior to recycling or

disposal.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of product residue in accordance with the instructions

of the person responsible for waste disposal.

#### **SECTION 14. TRANSPORT INFORMATION**

#### **International Regulation**

IATA-DGR

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**49 CFR** 

Not regulated as a dangerous good

**TDG** 

Not regulated as a dangerous good

#### Special precautions for user

Not applicable

#### **SECTION 15. REGULATORY INFORMATION**

WHMIS Classification : Not controlled.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

The components of this product are reported in the following inventories:

**DSL** On the inventory, or in compliance with the inventory

**TSCA** All chemical substances in this product are either listed on the

### PRECISION TM/MC XL EP2



#### 000003000891

Version 3.0 Revision Date 2015/09/15 Print Date 2015/09/15

TSCA Inventory or are in compliance with a TSCA Inventory

exemption.

**ELINCS** At least one component is not listed in EINECS but all such

components are listed in ELINCS.

#### **SECTION 16. OTHER INFORMATION**

For Copy of (M)SDS

: The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: lubricants.petro-canada.ca/msds

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-

4518

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-

800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax:

1-800-201-6285

For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.