



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	LDG (pictograms)
	B-2, D-2A, D-2B		

Section 1: Chemical Product and Company Identification

Product Name	JET B AVIATION TURBINE FUEL	Code	File # W219
Synonym	Jet B, Jet B DI, International Jet B, International Jet B DI, Jet Fuel JP-4, Jet Fuel F-40, Turbine Fuel, Aviation, Wide Cut Type (CAN/CGSB-3.22)	Validated on	3/3/1999
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canada: Transportation 613-916-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Used as aviation turbine fuel. May contain a fuel system icing inhibitor.		

Section 2: Composition and Information on Ingredients

			Exposure Limits (CCO)		
Name	CAS #	% (W/W)	TLV-TWA (h)	STL	CEILING
1) Complex mixture of aliphatic and aromatic hydrocarbons (C6-C14).	64741-41-8	>99	300 ppm (gasoline)	500 ppm (gasoline)	Not established
2) Proprietary additives.	Not applicable	<0.2	Not established	Not established	Not established
Manufacturer Recommendation	Petro-Canada recommends a working guideline no greater than 1 ppm (3.2 mg/m³) of benzene for 8 hours time weighted average when handling product which may contain benzene; 300 ppm for 8 hours time weighted average and 500 ppm for short term exposure limit when handling Jet B. Consult local authorities for acceptable exposure limits.				
Other Exposure Limits Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3: Hazards Identification

Potential Health Effects:	Inhalation of vapours or mist may cause irritation of nose and throat; headache, nausea, vomiting, dizziness, fatigue, light-headedness, reduced coordination and unconsciousness; central nervous system depression; kidney and liver damage from long-term exposure. May be narcotic in high concentrations. Skin contact may cause drying, cracking, defatting, or inflammation of skin. Prolonged or repeated contact with skin may cause dermatitis. Eye contact may cause irritation, but no permanent damage. Overexposure due to ingestion is unlikely for adults since taste and smell limit the amount swallowed. Harmful or fatal if swallowed. For more information, refer to Section 11.
---------------------------	---

Section 4: First Aid Measures

Eye Contact	Check for and remove any contact lenses. IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. DO NOT use an eye ointment. Seek medical attention if irritation persists.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Get medical attention if redness or irritation occurs.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth-to-mouth resuscitation. Administer oxygen if available. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	Gastric decontamination to prevent absorption is important following a substantial recent ingestion. Is most effective if initiated within 30 minutes. DO NOT induce vomiting without supervision of medical personnel, because of danger of aspirating liquid into lungs. Seek immediate medical attention.
Note to Physician	Aspiration into lungs may cause chemical pneumonitis. Monitor for respiratory distress. If cough or difficulty in breathing develops, evaluate for respiratory tract irritation, bronchitis, or pneumonitis. Monitor blood gases to ensure adequate ventilation. If vital signs become abnormal or symptoms develop obtain a chest x-ray. Prevent further absorption by administer charcoal slurry, aqueous or mixed with saline cathartic or sorbitol. The FDA suggested 2-10 ml of diluent/30 g of charcoal. Usual charcoal dose is 30 to 100 g in adults, 15 to 30 g in children and 1 to 2 g/kg in infants.

Section 5: Fire-fighting Measures

Flammability	Flammable liquid (NFPA).	Flammable Limits	Lower: 1.3%; Upper: 7.1% (NFPA).
Flash Points	Closed Cup: -25°C (-13°F). Tag, ASTM D56.	Auto-ignition Temperature	240°C (464°F)

JET & AVIATION TURBINE FUEL

Page Number: 3

Fire Hazards in Presence of Various Substances	Easily ignites under almost all normal temperature conditions. Extremely flammable in presence of open flames, sparks, shocks, heat, oxidizing materials. Vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks), and may travel considerable distance to sources of ignition and flash back.	Explosion Hazards in Presence of Various Substances	Excessive heat. Do not cut, weld, heat, or drill empty container. Containers may explode in heat of fire. Runoff to sewer may create fire or explosion hazard.
Products of Combustion	Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), sulphur compounds (H ₂ S), smoke and irritating fumes as products of incomplete combustion.		
Fire Fighting Media and Instructions	NAERG96, GUIDE 128, Flammable/combustible liquid (non-polar/water-immiscible). CAUTION: This product has a low flash point, use of water spray when fighting fire may be inefficient. SMALL FIRE: Use DRY chemicals, CO ₂ , water spray or foam. LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1610 meters (1 mile) in all directions. DO NOT extinguish a leaking gas flame unless leak can be stopped. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid flinging spilled material into sewers, streams or other bodies of water. Self-contained breathing apparatus (SCBA) will be required if approaching the fire from downwind, or to enter enclosed areas or buildings.		

Section 6: Accidental Release Measures

Material Release or Spill	NAERG96, GUIDE 128, Flammable/combustible liquid (non-polar/water-immiscible). Evacuate in a downwind direction for at least 300 meters (1000 feet). ELIMINATE ALL IGNITION SOURCES. Ventilate closed spaces before entering. By forced ventilation, maintain concentration of vapour below the range of explosion mixture. Avoid contact, fully-encapsulating, vapour-protective clothing should be worn for spills and leaks with no fire. Stop leak if without risk. Remove the leaking container to an open area and allow it to bleed off into the atmosphere. Use vapour suppressing foam or water spray to reduce vapours; it may reduce vapour, but it may not prevent ignition in closed spaces; isolate area until vapour has dispersed. Contain spill. Absorb with inert absorbents such as dry clay, or diatomaceous earth, or recover using electrically grounded explosion-proof pumps. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.
---------------------------	--

Section 7: Handling and Storage

Handling	Keep away from sources of ignition. In case of insufficient ventilation, wear suitable respiratory equipment. HANDLE AS EXTREMELY FLAMMABLE LIQUID. Electrically ground/bond during the pumping or transfer to avoid static accumulation. DO NOT USE AS CLEANING FLUID OR SIPHON BY MOUTH. Precautions should be taken to minimize skin contact and inhalation. High standards of personal hygiene are necessary. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.
Storage	Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Store in tightly closed containers in cool, dry, isolated and well-ventilated area. Ground all equipments containing material.

Section 8: Exposure Controls/Personal Protection

Engineering Controls	For normal outdoor application, special ventilation is not necessary. For indoor or confined spaces: provide explosion-proof local exhaust ventilation, or other engineer controls, to keep airborne concentration below the allowable threshold limit value. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work station.
Personal Protection	The selection of personal protective equipment varies, depending upon conditions of use:
Eyes	Face shield or chemical splash goggles in case of splashing.
Body	Wear long sleeved clothing to minimize skin contact.
Respiratory	When exposure is likely to exceed recommended exposure limit (see section 2), use NIOSH approved respiratory equipment. Respirator should be selected based on the form and concentration of contaminant in air (refer to NIOSH Pocket Guide for Chemical Hazard for respirator selection). In order to determine the concentration of the contaminant, air sampling is RECOMMENDED AND SHOULD BE PERFORMED BY A HEALTH & SAFETY SPECIALIST (AS PER THE NIOSH Manual of analytical Methods for method of measurement). If air sampling is not practical and concentration is unknown, use positive pressure self-contained breathing apparatus (SCBA). Contact appropriate HEALTH & SAFETY personnel or supplier for assistance.
Hands	For casual contact, polyvinyl alcohol (PVA) gloves are suitable. For direct contact for more than 2 hours, nitrile or viton gloves are recommended.
Feet	Safety boots or shoes.

JET 9 AVIATION TURBINE FUEL

Page Number: 3

Section 9. Physical and Chemical Properties

Physical State and Appearance	Clear liquid.	Viscosity	Not available.
Colour	Clear and colorless.	Pour Point	Freezing Point: $< -61^{\circ}\text{C}$ ($< -80^{\circ}\text{F}$) for Jet B/Jet B D; $< -58^{\circ}\text{C}$ ($< -72^{\circ}\text{F}$) for Jet Fuel F-40.
Odour	Gasoline like.	Softening Point	Not applicable.
Odour Threshold	Not available.	Dropping Point	Not applicable.
Boiling Point	50 to 270°C (122 to 518°F)	Penetration	Not applicable.
Density	0.75 to 0.80 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not measurable. The product is more soluble in oil.
Vapour Density	3.6 (Air = 1)	Ioncity (in water)	Insoluble in water.
Vapour Pressure	21 kPa (158 mmHg) @ 37.8°C (100°F).	Dispersion Properties	Not dispersed in cold water, or hot water.
Volatility	Volatile.	Solubility	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

Section 10. Stability and Reactivity.

Corrosivity	Non corrosive.		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Can react with strong organic oxidizing agents.	Decomposition Products	Releases of CO_x , NO_x , SO_x , H_2S , smoke and irritating fumes when heated to decomposition.

Section 11. Toxicological Information

Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Based on toxicity of gasoline, acute oral toxicity (LD50): 18750 mg/kg (rat).
Chronic or Other Toxic Effects	
Dermal Route:	Prolonged or repeated contact can defat the skin, cause irritation, and lead to the development of dermatitis. Prolonged skin contact has same effects as inhalation. Injuries blood-forming tissue on contact.
Inhalation Route:	Exposure to light hydrocarbons has been associated in animal studies with effects to the central nervous system, peripheral nervous system, liver, and kidneys. The significance of these animal models to predict similar human response is uncertain. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood forming system (particularly bone marrow), and serious blood disorders, such as aplastic anemia and leukemia.
Oral Route:	Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	May irritate the eyes.
Immunotoxicity:	Benzene-Hematologic and immunochemical investigations carried out in 270 workers with chronic exposure to benzene demonstrated changes of the nucleogram and of the area of lymphocyte nuclei and disorders of the humoral immune response revealed by radial immunodiffusion.
Skin Sensitization:	No studies were found.
Respiratory Tract Sensitization:	No studies were found.
Mutagenic:	Benzene is tumorigenic by RTECS criteria.
Reproductive Toxicity:	Based on the available animal data for benzene, Dose: 150 ppm (rat/inhalation/24h/7-14 days of pregnancy) — abnormal development of the musculoskeletal system.
Teratogenicity/Embryotoxicity:	Based on the available animal data, benzene poses a developmental or teratogenicity risk to rats.
Carcinogenicity (ACGIH):	ACGIH A1: confirmed human carcinogen, based on toxicity of benzene.
Carcinogenicity (IARC):	IARC Group 1: carcinogenic to Humans, based on toxicity of benzene.
Carcinogenicity (NTP):	NTP Group 1: known to be a carcinogen, based on toxicity of benzene.
Carcinogenicity (IRIS):	No studies were found.
Carcinogenicity (OSHA):	OSHA Group X: carcinogen defined with no further categorization, based on toxicity of benzene.
Other Considerations	Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood forming system (particularly bone marrow), and serious blood disorders, such as aplastic anemia and leukemia. The epidemiologic literature on benzene and leukemia supports the inference that benzene causes acute myelocytic leukemia.

JET-B AVIATION TURBINE FUEL

Page Number: 6

Section 12. Ecological Information

Environmental Fate	Volatilizes and disperses rapidly. Volatilization is expected to be the dominant fate process. Biodegrade under both aerobic and anaerobic conditions.	Persistence/Bioaccumulation Potential	Floats on water. May be dangerous to aquatic life in high concentrations.
BOD5 and COD	Not available.	Products of Biodegradation	Not available.
Additional Remarks	If released to soil, fuel oil will strongly adsorb. It may biodegrade in water and soil or volatilize from water (half-life of 4.4 to 4.8 hrs from a model river) and moist soil surfaces, but adsorption may attenuate the rate of these processes.		

Section 13. Disposal Considerations

Waste Disposal	Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations. Consult your local or regional authorities.
----------------	--

Section 14. Transport Information

TDG Classification	Shipping Name: Fuel, aviation, turbine engine; UN 1863; Class: 3; Packing Group: II; Label required: Flammable liquid.	Special Provisions for Transport	No additional remark.
--------------------	--	----------------------------------	-----------------------

Section 15. Regulatory Information

Other Regulations	CEPA: This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on DSL. This product may contain trace benzene, a carcinogen, which is listed on NPRI.																							
USEPA: All components of this formulation are listed on TSCA Inventory. This product may contain trace benzene, a carcinogen, which is required to be listed under OSHA hazard communication standard, 29 CFR 1310.1200 (U.S.). Listed on New Jersey Environmental Hazardous Substances List. Benzene is listed on EPCRA or SARA Title III, Section 302/304/311/312 (40 CFR 355/370) for Extremely Hazardous Substances. Benzene is listed on EPCRA or SARA Title III, Section 313 (40 CFR 372) for Toxic Chemicals. Benzene is listed on CERCLA Hazardous Substances (RQ Chemicals) (40 CFR 302.4). Benzene is listed on RCRA (40 CFR 261.33) for Hazardous Waste. Please note that the chemical identity of some or all of the ingredients that may be listed herein is confidential business information and is being withheld as permitted by 29 CFR 1910.1200 and various State Right to Know Laws.																								
DSD/DPD (Europe)	5- Heating may cause an explosion. 12- Extremely flammable. 18- In use, may form flammable/explosive vapor-air mixture. 36/37/38- Irritating to eyes, respiratory system and skin. 40- Possible risks of irreversible effects.		HCS (U.S.A.)	HCS CLASS: Flammable liquid having a flash point lower than 37.8°C (100°F). HCS CLASS: Irritating substance. HCS CLASS: Toxic.																				
ADR (Europe) (Pictograms)			DOT (U.S.A.) (Pictograms)																					
HMIS (U.S.A.)	<table><tr><td>Health Hazard</td><td>(1)</td></tr><tr><td>Fire Hazard</td><td>(3)</td></tr><tr><td>Reactivity</td><td>(0)</td></tr><tr><td>Personal Protection</td><td>(h)</td></tr></table>		Health Hazard	(1)	Fire Hazard	(3)	Reactivity	(0)	Personal Protection	(h)	NFPA (U.S.A.)		Fire Hazard Reactivity Specific hazard	Rating <table><tr><td>0</td><td>Insignificant</td></tr><tr><td>1</td><td>Slight</td></tr><tr><td>2</td><td>Moderate</td></tr><tr><td>3</td><td>High</td></tr><tr><td>4</td><td>Extreme</td></tr></table>	0	Insignificant	1	Slight	2	Moderate	3	High	4	Extreme
Health Hazard	(1)																							
Fire Hazard	(3)																							
Reactivity	(0)																							
Personal Protection	(h)																							
0	Insignificant																							
1	Slight																							
2	Moderate																							
3	High																							
4	Extreme																							

Section 16. Other Information

References Available upon request.

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists
 ADR - Agreement on Dangerous Goods by Road (Europe)
 ASTM - American Society for Testing and Materials
 BOD5 - Biological Oxygen Demand in 5 days
 CAN/CSA B149.2 - Propane Installation Code
 CAS - Chemical Abstract Services
 CEPA - Canadian Environmental Protection Act
 CERCLA - Comprehensive Environmental Response, Compensation and Liability Act
 CFR - Code of Federal Regulations
 CHEM - Chemical Hazard Information and Packaging Approved Supply List
 COD5 - Chemical Oxygen Demand in 5 days
 CPR - Controlled Products Regulations
 DOT - Department of Transport
 DSD - Dangerous Substances Classification and Labeling (Europe)
 DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)
 DSL - Domestic Substances List
 EEC/EU - European Economic Community/European Union
 EINECS - European Inventory of Existing Commercial Chemical Substances
 EPCRA - Emergency Planning and Community Right to Know Act

IRIS - Integrated Risk Information System
 LD50/LC50 - Lethal Dose/Concentration (50%)
 LDLo/LCLo - Lowest Published Lethal Dose/Concentration
 NAERG/20 - North American Emergency Response Guide Book (1996)
 NFPA - National Fire Protection Association
 NIOSH - National Institute for Occupational Safety & Health
 NPRI - National Pollutant Release Inventory
 NSR - New Substances Notification Regulations (Canada)
 NTP - National Toxicology Program
 OSHA - Occupational Safety & Health Administration
 PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 SARA - Superfund Amendments and Reorganization Act
 ED - Single Dose
 STEL - Short Term Exposure Limit (15 minutes)
 TDG - Transportation Dangerous Goods (Canada)
 TDLo/CLo - Lowest Published Toxic Dose/Concentration
 Tm - Median Toxicity Limit
 TLV-TWA - Threshold Limit Value-Time Weighted Average

02/13/02 WED 11:19 FAX 867 873 8332
02/13/02 WED 09:43 FAX 8678739460

DISCOVERY MINING
MATONABEE PET.

012
010

JET 8 AVIATION TURBO FUEL		Page Number: 5
FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide and Rodenticide Act HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer		TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System
For Copy of MSDS Western Canada, telephone: 403-296-7694; fax: 403-296-3763 Ontario & Central Canada, telephone: 1-800-668-0220; fax: 1-800-837-1228 Quebec & Eastern Canada, telephone: 514-640-8398; fax: 514-640-8373		Prepared by Product Safety - TLR on 3/8/1999. Data entry by Product Safety - TLR.
To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.		

Superior
Propane Inc.**MATERIAL SAFETY DATA SHEET** Attn Rod.**SECTION 1 - PRODUCT INFORMATION**

Product Name: Propane
Trade Name: LPG (Liquified Petroleum Gas), LP-Gas
Chemical Formula: C_3H_8

Supplier: Superior Propane Inc.
1111 - 49th Avenue N.E.
Calgary, AB T2E 1V2

WHMIS CLASSIFICATION

Class A - Compressed Gas

Class B, Division 1 - Flammable Gas

Business: (403) 730-7500

Local Market

Emergency Number:

(Non Medical)

Application and Use: Propane is commonly used as a fuel for heating, cooking, automobiles, forklift trucks, crop drying and welding and cutting operations. Propane is used in industry as a refrigerant, solvent and as a chemical feedstock.

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENTS	CAS NO.	% Volume (v/v)	LD50
Propane	74-98-6	90% - 99%	Not Applicable
Propylene	115-07-1	0% - 5%	Not Applicable
Ethane	74-84-0	0% - 5%	Not Applicable
Butane and heavier hydro carbons	106-97-8	0% - 2.5%	Not Applicable

Occupational Exposure Limit:Based upon animal test data, the acute toxicity of this product is expected to be inhalation: 4 hour LC₅₀ = 280,000 ppm (Rat).

Note: Composition is typical for HD-5 Propane per The Canadian General Standard Board CGSB 3.14 National Standard of Canada. Exact composition will vary from shipment to shipment.

SECTION 3 - CHEMICAL AND PHYSICAL DATA

Form: Liquid and vapour while stored under pressure.
Boiling Point: -42°C @ 1 atm.
Freezing Point: -188°C
Evaporation Rate: Rapid (Gas at normal ambient conditions).
Vapour Pressure: 1435 kPa (maximum) @ 37.8°C
Vapour Density: 1.52 (Air = 1)
Coefficient of Water/Oil Distribution: Not available.
pH: Not available.

Solubility in water: Slight, 6.1% by volume @ 17.8°C

Specific Gravity: 0.51 (water = 1)

Appearance/Odour: Colourless liquid and vapour while stored under pressure. Colourless and odourless gas in natural state at any concentration. Commercial propane has an odourant added, ethyl mercaptan, which has an odour similar to: boiling cabbage.

Odour Threshold: 4800 ppm

* With proper handling, transportation and storage, adding a chemical odourant such as eth-merc has proven to be a very effective warning device, but all odourants have certain limitations. The effectiveness of the odourant may be diminished by a person's sense of smell, by competing odours and by oxidation which may cause a potentially dangerous situation.

SECTION 4 - FIRE OR EXPLOSION HAZARD

Flash Point: -103.4°C
Method: Closed cup.
Flammable Limits: Lower 2.4%, Upper 9.5%
Auto Ignition Temperature: 432°C
Products Evolved Due To Heat Or Combustion: Carbon monoxide can be produced when primary air and secondary air are deficient while combustion is taking place.
Fire and Explosive Hazards: Explosive air-vapour mixtures may form if allowed to leak to atmosphere.
Sensitivity To Impact: No.
Sensitivity To Static Discharge: Yes.

Fire Extinguishing Precautions: Use water spray to cool exposed cylinders or tanks. Do not extinguish fire unless the source of the escaping gas that is fueling the fire can be turned off. Fire can be extinguished with carbon dioxide and/or dry chemical (BC). Container metal shells require cooling with water to prevent flame impingement and the weakening of metal. If sufficient water is not available to protect the container shell from weakening, the area will be required to be evacuated. If gas has not ignited, liquid or vapour may be dispersed by water spray or flooding.
Special Fire Fighting Equipment: Protective clothing, hose monitors, fog nozzles, self-contained breathing apparatus.

SECTION 5 - REACTIVITY DATA

Stability: Stable.
Conditions To Avoid: Keep separate from oxidizing agents. Gas explodes spontaneously when mixed with chloride dioxide.
Incompatibility: Remove sources of ignition and observe distance requirements for storage tanks from combustible material, drains and openings to building.

Hazardous Decomposition Products: Deficient primary and secondary air can produce carbon monoxide.
Hazardous Polymerization: Will not occur.

ATT: DOOB

SECTION 6 - TOXICOLOGICAL PROPERTIES OF MATERIAL

ROUTES OF ENTRY:

Inhalation: Simple asphyxiant. No effect at concentrations of 10,000 ppm (peak exposures). Higher concentrations may cause central nervous system disorder and/or damage. Lack of oxygen may cause dizziness, loss of coordination, weakness, fatigue, euphoria, mental confusion, blurred vision, convulsions, breathing failure, coma and death. Breathing high vapour concentrations (saturated vapours) for a few minutes may be fatal. Saturated vapours may be encountered in confined spaces and/or under conditions of poor ventilation. Avoid breathing vapours or mist.
Skin and Eye Contact: Exposure to vapourizing liquid may cause frostbite (cold burns) and permanent eye damage.

Ingestion: Not considered to be a hazard.
Acute Exposure: The acute toxicity of this product is expected to be inhalation: 4 hour LC50=280,000ppm (Rat).
Chronic Exposure: There are no reported effects from long term low level exposure.
Sensitization to Product: Skin-unknown, Respiratory-unknown.
Occupational Exposure Limits: American Conference of Governmental Industrial Hygienists (ACGIH) lists as a simple asphyxiant. ACGIH TLV: 1000 ppm.
Carcinogenicity, Reproductive Toxicity, Teratogenicity, Mutagenicity: No effects reported.

SECTION 7 - PREVENTIVE MEASURES

Eyes: Safety glasses, are recommended when transferring product.
Skin: Insulated gloves required if contact with liquid or liquid cooled equipment is expected. Wear gloves and long sleeves when transferring product.

Inhalation: Where concentration in air would reduce the oxygen level below 18% air or exceed occupational exposure limits in section 6, self-contained breathing apparatus is required.
Ventilation: Explosion proof ventilation equipment required in confined spaces.

SECTION 8 - EMERGENCY AND FIRST AID PROCEDURES

FIRST AID:

Eyes: Should eye contact with liquid occur, flush eyes with lukewarm water for 15 minutes. Obtain immediate medical care.
Skin: In case of "Cold Burn" from contact with liquid, immediately place affected area in lukewarm water and keep at this temperature until circulation returns. If fingers or hands are frostbitten, have the victim hold his hand next to his body such as under the armpit. Obtain immediate medical care.
Ingestion: None considered necessary.
Inhalation: Remove person to fresh air. If breathing is difficult or has stopped, administer artificial respiration. Obtain immediate medical care.

SPILL OR LEAK:

Eliminate leak if possible.
Eliminate source of ignition.
Ensure cylinder is upright.
Disperse vapours with hose streams using fog nozzles. Monitor low areas as propane is heavier than air and can settle into low areas. Remain upwind of leak. Keep people away. Prevent vapour and/or liquid from entering into sewers, basements or confined areas.

SECTION 9 - TRANSPORTATION, HANDLING AND STORAGE

- Transport and store cylinders and tanks secured in an upright position in a ventilated space away from ignition sources (so the pressure relief valve is in contact with the vapour space of the cylinder or tank).
- Cylinders that are not in use must have the valves in the closed position and be equipped with a protective cap or guard.
- Do not store with oxidizing agents, oxygen, or chlorine cylinders.

- Empty cylinders and tanks may contain product residue. Do not pressurize, cut, heat or weld empty containers.
- Transport, handle and store according to applicable federal and provincial codes and regulations.


Transportation of Dangerous Goods (TDG)

- TDG Classification: Flammable Gas 2.1
- TDG Shipping Name: Liquefied Petroleum Gas (Propane)
- TDG Special Provisions: 56, 90, 102
- PIN Number: UN1075

SECTION 10 - PREPARATION

Superior Propane Inc., Regulations & Safety Department. (403) 730-7500 Date prepared: November 2001.
Supersedes: September 1999.

The information contained herein is believed to be accurate. It is provided independently of any sale of the product. It is not intended to constitute performance information concerning the product. No express warranty, implied warranty of merchantability or fitness for a particular purpose is made with respect to the product information contained herein.



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	B-3, D-2B		

Section 1. Chemical Product and Company Identification

Product Name	DIESEL FUEL	Code	W104 SAP: 120, 121, 122, 287
Synonym	Diesel 50, Diesel 50 LS, #1 Diesel, #1 Diesel LS, Diesel LC, Seasonal Diesel, Seasonal Diesel LS, Diesel AA, Domestic Marine Diesel, International marine Diesel, Seasonal Diesel Locomotive, Domestic Marine diesel LS, diesel -20°C (LS), L6D, Low Sulphur Diesel, dyed diesel, marked diesel, coloured diesel.	Validated on	3/2/2001.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Consult Transportation: 613-896-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type.		

Section 2. Composition and Information on Ingredients

			Exposure Limits (ADE-10)		
Name	CAS #	% (W/W)	TLV-TWA (8 h)	STEL	CEILING
1) Diesel oil, 2) Proprietary additives, 3) Aromatic content is 50% maximum (benzene: nil). 4) * Notice of Intended Change (2000): 100 mg/m ³ , skin, A3.	68334-30-5 Not available	>99.9 <0.1	Not established Not established	Not established Not established	Not established Not established
Manufacturer	Not applicable				
Recommendation					
Other Exposure Limits Consult local, state, provincial or territory authorities for acceptable exposure limits.					

Section 3. Hazards Identification

Potential Health Effects	Eye contact may cause mild eye irritation. Skin contact can cause moderate to severe irritation and produce drying, cracking, or defolting dermatitis. Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat. Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure. For more information, refer to Section 11.
--------------------------	--

Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

Section 5. Fire-fighting Measures

Flammability	Class II - combustible liquid (NFPA).	Flammable Limits	LOWER: 0.7%, UPPER: 6%
Flash Points	Diesel Fuel: Closed Cup: >40°C (>104°F) Marine Diesel Fuel: Closed Cup: >60°C (>140°F)	Auto-ignition Temperature	225°C (437°F)
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks, or heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.	Explosion Hazards in Presence of Various Substances	Containers may explode in heat of fire. Do not cut, weld, heat, drill or pressurize empty container. Vapour explosion hazard indoors, outdoors or in sewers. Runoff to sewer may create fire or explosion hazard.
Products of Combustion	Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), sulphur compounds (H ₂ S), water vapour (H ₂ O), smoke and irritating vapours as products of incomplete combustion.		

DIESEL FUEL		Page Number: 2
Fire Fighting Media and Instructions	NAERG98, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a moderate flash point above 40°C. Use of water spray when fighting fire may be inefficient. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. SMALL FIRES: Dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters protective clothing will only provide limited protection.	

Section 6. Accidental Release Measures

Material Release or Spill	NAERG96, GUIDE 128, Flammable Liquids (Non-polar/ Water-immiscible). ELIMINATE ALL IGNITION SOURCES. Avoid contact. Stop leak if without risk. Contain spill. Absorb with inert absorbents, dry clay, or diatomaceous earth. Avoid inhaling dust of diatomaceous earth for it may contain silica in very fine particle size, making this a potential respiratory hazard. Place used absorbent in closed metal containers for later disposal or burn absorbent in a suitable combustion chamber. DO NOT FLUSH TO SEWERS, STREAMS OR OTHER BODIES OF WATER. Check with applicable jurisdiction for specific disposal requirements of spilled material and empty containers. Notify the appropriate authorities immediately.
---------------------------	---

Section 7. Handling and Storage

Handling	Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. DO NOT reuse empty containers without commercial cleaning or reconditioning. Ground/bond line and equipment during pumping or transfer to avoid accumulation of static charge. DO NOT ingest. Do not breathe gas/vapour/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately. Avoid contact with skin and eyes. Practice good personal hygiene. Wash hands after handling and before eating. Launder work clothes frequently. Discard saturated leather goods.
Storage	Store in tightly closed containers in cool, dry, isolated, well-ventilated area, and away from incompatibles. Ground all equipment containing material.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work station.
Personal Protection	The selection of personal protective equipment varies, depending upon conditions of use.
Eyes	Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.
Body	Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.
Respiratory	Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.
Hands	Wear appropriate chemically protective gloves. When handling hot product, ensure gloves are heat resistant and insulated.
Feet	Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Bright oily liquid.	Viscosity	1.3-4.1 cSt @ 40°C (104°F)
Colour	Clear to yellow / brown. Low sulphur diesel fuels (<0.05 wt % sulphur) are colourless to light yellow (and may be dyed red for taxation purposes). Regular sulphur diesel fuels (0.05-0.50 % sulphur) may be colourless to yellow / brown and are usually dyed red for taxation purposes.	Pour Point	Variable, 0°C to -50°C (32°F to -58°F)
Odour	Petroleum oil like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	150-371°C (302-700°F)	Penetration	Not applicable.
Density	0.85 kg/L @ 15°C (Water = 1).	Oil / Water Dist. Coefficient	Not available
Vapour Density	4.5 (Air = 1)	Ionicity (in water)	Not applicable.

DIESEL FUEL		Page Number: 3	
Vapour Pressure	1.0 kPa @ 20°C (7.5 mmHg @ 68°F).	Dispersion Properties	Not available
Volatility	<0.1 (Butyl acetate = 1), less than gasoline.	Solubility	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

Section 10. Stability and Reactivity			
Corrosivity	Not available		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents and acids.	Decomposition Products	May release COx, NOx, SOx, H ₂ S, H ₂ O, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information	
Routes of Entry	Skin contact, eye contact, inhalation, and ingestion.
Acute Lethality	Acute oral toxicity (LD50): 7500 mg/kg (rat).
Chronic or Other Toxic Effects	
Dermal Route:	Skin contact may cause moderate to severe irritation. Repeated exposure would produce drying and cracking or defolating dermatitis.
Inhalation Route:	Inhalation of vapours can cause CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Inhalation can also cause irritation of nose and throat.
Oral Route:	Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	Eye contact may cause mild irritation, but no permanent damage.
Immunotoxicity:	Not available
Skin Sensitization:	This product is not expected to be a skin sensitizer, based on the available data and the known hazards of the components.
Respiratory Tract Sensitization:	This product is not expected to be a respiratory tract sensitizer, based on the available data and the known hazards of the components.
Mutagenic:	This product is not expected to be a mutagen, based on the available data and the known hazards of the components.
Reproductive Toxicity:	This product is not expected to be a reproductive hazard, based on the available data and the known hazards of the components.
Teratogenicity/Embryotoxicity:	This product is not expected to be a teratogen or an embryotoxin, based on the available data and the known hazards of the components.
Carcinogenicity (ACGIH):	ACGIH Notice of Intended Change (2000): proposed A3: animal carcinogen. [Diesel oil]
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	Not available
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	No additional remark.

Section 12. Ecological Information			
Environmental Fate	Not available	Persistence/Bioaccumulation Potential	Not available
BOD5 and COD	Not available	Products of Biodegradation	Not available
Additional Remarks	No additional remark.		

DIESEL FUEL

Page Number: 4

Section 13. Disposal Considerations

Waste Disposal Preferred waste management priorities are: (1) recycle or reprocess; (2) incineration with energy recovery; (3) disposal at licensed waste disposal facility. Ensure that disposal or reprocessing is in compliance with government requirements and local disposal regulations. Consult your local or regional authorities.

Section 14. Transport Information

TDG Classification	Diesel Fuel UN1202 3 III	Special Provisions for Transport	Not applicable.
--------------------	-----------------------------------	----------------------------------	-----------------

Section 15. Regulatory Information

Other Regulations This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	CLASS: Irritating substance. CLASS: Target organ effects. CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 23.3°C (200°F).
------------------	----------------	--------------	---

ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN
---------------------------	---

DOT (U.S.A.) (Pictograms)	
---------------------------	--

HMIS (U.S.A.)

Health Hazard	2
Fire Hazard	2
Reactivity	0
Personal Protection	H

NFPA (U.S.A.)

Health



Fire Hazard

Reactivity

Specific hazard

Rating

0 Insignificant
1 Slight
2 Moderate
3 High
4 Extreme

Section 16. Other Information

References Available upon request.
* Marquage de commerce de Petro-Canada - Trademark

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous Goods by Road (Europe)

ASTM - American Society for Testing and Materials

BOD5 - Biological Oxygen Demand in 5 days

CAN/CSA B148.2 - Pipeline Installation Code

CAS - Chemical Abstract Service

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemical Hazard Information and Packaging Approved Supply List

COD5 - Chemical Oxygen Demand in 5 days

CPR - Controlled Products Regulations

DOT - Department of Transport

DSC - Dangerous Substances Classification and Labeling (Europe)

DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)

DSL - Domestic Substances List

EEBCU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical Substances

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazardous Communication System

HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration at 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG98 - North American Emergency Response Guide Book (1998)

NFPA - National Fire Protection Association

NIOSH - National Institute for Occupational Safety & Health

NPL - National Pollution Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reauthorization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLN - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Materials Information System

For Copy of MSDS

Fuels & Solvents:

Western Canada, telephone: 403-296-4158; fax: 403-296-8551

Ontario & Central Canada, telephone: 1-800-668-0220; fax: 1-800-837-1228

Quebec & Eastern Canada, telephone: 514-640-8308; fax: 514-640-8385

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - 7 AR on 3/2/2001.

Data entry by Product Safety - JWW.

02/13/02 WED 11:14 FAX 867 873 8332

02/13/02 WED 09:40 FAX 8678739460

DISCOVERY MINING

MATONABEE PET.

0007
0005

DIESEL FUEL

Page Num 0005

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.