

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: Jan. 3, 2006
8750 53rd Ave. PHONE: 604-940-6050
Edmonton, AB T6E 5G2 FAX: 604-940-6080

PRODUCT NAME: **550X POLYMER**

PRODUCT USE: Drilling mud additive.

CHEMICAL FAMILY: Anionic water soluble polymer CAS#: Not available

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not a controlled product under WHMIS
WORKPLACE HAZARD: Treat as a nuisance dust.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
TDG CLASSIFICATION: Not applicable
UN NUMBER (PIN): Not applicable
PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>PERCENT</u>	<u>CAS NUMBER</u>	<u>LD₅₀Oral-Rat</u>	<u>LC₅₀Inhal-Rat</u>	<u>ACGIH-TLV</u>
-------------------	----------------	-------------------	--------------------------------	---------------------------------	------------------

Contains no WHMIS controlled ingredients.

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: | EYE CONTACT | SKIN | INHALATION | INGESTION

EYE CONTACT: May cause slight irritation and/or redness.

SKIN CONTACT: May cause slight irritation some cases.

INGESTION: No effects expected.

INHALATION: May cause irritation of the respiratory tract, including sneezing and coughing.

CARCINOGENICITY: No information available.

TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.

Diversity Technologies Corp. is the parent company of
Canamaco-United Supply, Holmes Products, The Drilling Depot and
Westcoast Drilling Supplies

MUTAGENICITY: No information available.
 SYNERGISTIC PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Wash thoroughly with soap and water. If irritation develops or persists, obtain medical attention. Wash contaminated clothing prior to reuse.
 EYE CONTACT: Flush with gently flowing warm water until irritation subsides. If irritation persists, obtain medical attention.
 INGESTION: This product is not considered toxic based on studies on lab animals. Do not induce vomiting. Give 2-3 glasses of water. If symptoms occur, obtain medical attention.
 INHALATION: Move to fresh air. Apply oxygen or artificial respiration as required. If breathing difficulties or distress continues obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	White granular powder; no odour	
SPECIFIC GRAVITY:	Not available	
BOILING POINT (°C):	Not available	
MELTING POINT (°C):	Not available	
SOLUBILITY IN WATER:	Soluble	pH: 4-9 (@ 5 g/l.)
PERCENT VOLATILE BY VOLUME:	Not available	
EVAPORATION RATE:	Not available	
VAPOUR PRESSURE (mmHg):	Not available	
VAPOUR DENSITY (air = 1):	Not available	
BULK DENSITY:	Not available	

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Carbon dioxide, dry chemical, foam, in preference to a water spray.
SPECIAL FIRE FIGHTING PROCEDURES:	Self contained breathing apparatus required for fire fighting personnel. Move containers from the area if possible.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	As with most organic powders, flammable dust clouds may be formed in air. Avoid creating dust. Avoid sources of ignition. Product is extremely slippery when wet.

Diversify Technology's Corp. is the parent company of
 Chemmate Limited Supply, Industrial Products, The Drilling Depot and
 Woodcut Lumber Supplies.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with strong oxidizers. Avoid wet, damp or humid conditions, extremes of temperature, and ignition sources.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon and nitrogen, various hydrocarbons, and/or ammonia upon combustion	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	Use approved dust mask in absence of adequate ventilation. Use approved respirators with dust cartridges if TLV is exceeded.
VENTILATION:	Use in well-ventilated area, or use local exhaust ventilation, process enclosure or other engineering controls to maintain dust level below TLV.
PROTECTIVE GLOVES:	Use gloves, if needed, to avoid prolonged or repeated skin contact.
EYE PROTECTION:	Use safety glasses or goggles.
OTHER PROTECTIVE EQUIPMENT (Specify):	As necessary to prevent contact. Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid prolonged or repeated breathing of dust and contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Cleanse skin thoroughly after contact, before breaks and meals and at end of work period. Product is readily removed from skin by washing thoroughly with soap and water. Store in a cool, dry location away from incompatibles. Store in original container.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Sweep up dry material and flush spill area with water. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. Scrub spill area with dry absorbent and then flush residue with water to eliminate slip hazard. Absorb spills of dilute solutions with inert absorbent. Collect in approved containers for disposal. The product or its solutions should not be allowed to enter waterways without treatment. Spilled solutions can create a hazard because of their slippery nature.

Drill-It-Right Technologies Corp. is the parent company of
Lunar Drilling Supply, Helimax Products, The Drilling Depot and
Western Drilling Supplies.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. It may be possible to dispose of spills of non-hazardous materials in a landfill; check with local operator.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED:	January 3, 2006	BY:	Product safety committee
SUPERSEDES:	January 2005	PHONE:	780-440-4923

Diversity Technologies Corp. is the parent company of
Chemcraft Limited Supply, Bohman Products, The Drilling Depot and
Westcoast Drilling Supplies

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: Dec. 19, 2005
8750 - 53rd Ave. PHONE: 604-940-6050
Edmonton, AB T6E 5G2 FAX: 604-940-6080

PRODUCT NAME: **BIG BEAR ROD GREASE**

PRODUCT USE:	Anti-seize compound	CAS #:	Mixture
CHEMICAL FAMILY:	Mixture		

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not WHMIS regulated.
WORKPLACE HAZARD: Not hazardous under normal conditions of use.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME:	Not TDG regulated.
TDG CLASSIFICATION:	Not applicable.
UN NUMBER (PIN):	Not applicable.
PACKING GROUP:	Not applicable.

SECTION II: HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>% (w/w)</u>	<u>CAS NUMBER</u>	<u>LD₅₀ Oral-Rat</u>	<u>LC₅₀ Inhal-Rat</u>	<u>ACGIH-TLV</u>
Mineral oil	70-80	64742-52-5	Not available	Not available	Not available
Barium Soap	20-30	58201-19-4	Not available	Not available	Not available

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY:	[XX] EYE CONTACT [XX] SKIN [] INHALATION [XX] INGESTION
EYE CONTACT:	May cause slight transient irritation.
SKIN CONTACT:	May cause slight transient irritation.
INGESTION:	No effects known.
INHALATION:	Not a likely source of contact during normal use.
CARCINOGENICITY:	None of the ingredients in the compound are listed by NTP, IARC or OSHA as being carcinogenic.
TERATOGENICITY:	No information available.

University Technologies Corp. is the parent company of
Canadian-United Supply, Hellman Products, The Drilling Depot and
Western Drilling Supplies

REPRODUCTIVE TOXICITY:	No information available.
MUTAGENICITY:	No ingredients listed as mutagenic.
SYNERGISTIC PRODUCTS:	No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT:	Remove by wiping, or with a waterless hand cleaner. Wash with soap and water. Remove and launder contaminated clothing before re-use.
EYE CONTACT:	Immediately flush with gently flowing warm water until all residual material is removed. Remove contact lenses if present. Hold eyelids open to ensure thorough flushing. If irritation persists, obtain medical attention.
INGESTION:	Do not induce vomiting. Rinse mouth. Obtain immediate medical attention. Never give anything by mouth to an unconscious or convulsing victim.
INHALATION:	Move to fresh air. Apply oxygen or artificial respiration as required. If breathing difficulties or distress continues, obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Brown paste; bland odour	
SPECIFIC GRAVITY:	0.90 @ 16°C	
BOILING POINT (°C):	371	
MELTING POINT (°C):	204	
SOLUBILITY IN WATER:	Insoluble	pH: Not available
PERCENT VOLATILE BY VOLUME:	Not available	
EVAPORATION RATE:	Not available	
VAPOUR PRESSURE:	Not available	
VAPOUR DENSITY (air = 1):	Not available	
BULK DENSITY:	Not applicable	

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	188°C
FLAMMABLE LIMITS:	Not available
EXTINGUISHING MEDIA:	Dry chemical, CO ₂ , foam or water spray.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel. Remove containers from fire area, or cool with water spray, if possible.

Diversi-ve Technologies Corp. is the parent company of
 Cincinnati United Supply, Holman Products, The Drilling Depot and
 Western Drilling Supplies

UNUSUAL FIRE AND EXPLOSION HAZARDS:

This product may burn under fire conditions.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Strong oxidizers. Avoid heat, sparks and open flames.	
CONDITIONS OF REACTIVITY:	Contact with incompatibles or ignition sources.	
HAZARDOUS DECOMPOSITION PRODUCTS:	May release CO ₂ , smoke and irritating vapours when heated to decomposition.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	Not required under normal conditions of use.
VENTILATION:	Not required under normal conditions of use.
PROTECTIVE GLOVES:	Suggest neoprene or viton.
EYE PROTECTION:	Safety glasses with side-shields if required.
OTHER PROTECTIVE EQUIPMENT	Protective clothing as required to prevent contact.
(Specify):	Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with skin and eyes. Avoid ingestion. Wash thoroughly before eating, drinking or smoking. Store in cool, dry area away from incompatibles and sources of ignition. Use caution when opening unvented containers. Use in well ventilated area. Store unused material in original container.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Eliminate ignition sources. Scoop up excess, then wipe down the affected area and pick up residual with diatomaceous earth to prevent slipping hazard. Place contaminated material and clean up materials in approved containers for disposal.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the customer to determine if material meets the criteria of hazardous waste at the time of disposal. Do not fill, reuse or empty containers in accordance with local regulations.

Diversified Technologies Corp. is the parent company of
Columbian-United Supply, Bellows Falls, N.H., The Drilling Depot and
Northeast Drilling Supplies.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED: December 20, 2005 BY: Product safety committee
SUPERSEDES: March 31, 2003 PHONE: 780-440-4923

Diversa Technologies Corp. is the parent company of
 Climate Control, Supply, Stabilizer Products, The Drying Dept and
 Westernst Building supplies.

Material Safety Data Sheet / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V4G 1J3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **LINSEED SOAP**
CHEMICAL FAMILY: Lubricating grease
WHMIS CLASSIFICATION: Not regulated
WORK PLACE HAZARD: Not applicable

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not available
PACKAGE GROUP: Not available
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable (Petroleum Lubricating Grease)

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50	LC50
Linseed Soap	100%	Mixture		

SECTION III: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY: (Information not available)

[] Skin, [] Eye Contact, [XXX] Inhalation, [] Ingestion

SKIN CONTACT: Prolonged and repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis.

EYE CONTACT: Not available.

INHALATION: Inhalation of oil mist or vapors from hot grease may cause irritation of the upper respiratory tract. Long term intensive exposure may cause benign lung fibrosis.

INGESTION: Not available.

CHRONIC OVEREXPOSURE: Not determined.

IRRITATION INDEX: SKIN: Not available.

SYMPTOMS OF EXPOSURE: Not available.

EXPOSURE INFORMATION: Oil mist (particulate): 5 mg/M³ (TLV/TWA)
ACGIH 58/89 10 mg/M³ (TLV/STEL) ACGIH 88/89

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing. Wash contaminated skin with mild soap and water. Wipe excess from skin.

EYE CONTACT: Flush eyes with water for at least fifteen (15) minutes.

INHALATION: Remove victim from further exposure. Additional first aid treatment is not ordinarily required.

INGESTION: Do not induce vomiting. Obtain medical attention immediately.

OTHER INSTRUCTIONS: None

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: Semi-solid brown colored grease; slight hydrocarbon odor.

DENSITY (SPECIFIC GRAVITY): 1.0

BOILING POINT: 160°C

MELTING POINT: Not available

WATER SOLUBILITY: Miscible



WESTCOAST DRILLING SUPPLIES LTD.
8080 River Way, Delta, British Columbia, Canada V4G 1L3
Phone: (604) 940-8050 Fax: (604) 940-0060
 toll free: 1-800-665-6645

LINSEED SOAP

Page 2 of 3

% VOLATILE BY VOLUME:	Not available
EVAPORATION RATE:	Not available
VAPOR PRESSURE: (mm Hg)	Not available
VAPOR DENSITY: (Air = 1)	Not available
pH:	9.5
VISCOSITY:	Not available

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	222° C
FLAMMABLE LIMIT:	Not available
AUTO IGNITION TEMP:	343° C
EXTINGUISHING MEDIA:	Dry chemical, carbon dioxide CO ₂ , foam water fog.
SPECIAL FIRE FIGHTING PROCEDURES:	No special procedures - Avoid inhalation of smoke. Caution, spilled material is slippery. Use water to cool fire-exposed containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None currently known.

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []	
INCOMPATIBILITY (CONDITIONS TO AVOID):	Not available.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide; carbon dioxide and dense smoke are produced on combustion. Avoid excessive heat, formation of vapors or mists.
HAZARDOUS POLYMERIZATION:	Will not occur [] May occur [] Not Available

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION:	Under conditions of high heat use an air purifying respirator (mechanical filter with accompanying organic vapor cartridge).
VENTILATION:	Highly recommended for all indoor situations to control fugitive emissions. Concentrations in air should be maintained below the recommended threshold limit value if unprotected personnel are involved.
LOCAL/MAKE-UP AIR:	If oil mist is present or if exposure is exceeded. Should always be supplied to balance air exhausted (either generally or locally).
PROTECTIVE GLOVES:	Impervious gloves (viton, nitrile, PVC neoprene) should be worn at all times when handling this product.
EYE PROTECTION:	Chemical safety goggles and/or full face shield to protect eyes and face. If product is handled such that it could be splashed into eyes.
OTHER PROTECTIVE EQUIPMENT:	Impervious clothing (apron, coveralls) should be worn in confined workspaces or where the risk of skin exposure is much higher.
PERMISSIBLE CONCENTRATIONS:	Not available.



Page 3 of 3

Store in a cool, dry, well ventilated area, away from heat and ignition sources. Avoid excessive heat, formation of oil mist, breathing of vapors and mist of hot oil and prolonged or repeated contact with skin. Launder contaminated clothing prior to reuse. Properly dispose of contaminated leather articles, including shoes, that cannot be decontaminated).

Spilled material is slippery. Isolate hazard area and restrict access. Wear appropriate breathing apparatus (if applicable) and protective clothing. Stop leak only if safe to do so. Contain a land spill by diking. For large spills remove by mechanical means and place in containers. Clean area with appropriate cleaner. Do not allow product to run off from fire control to enter storm or sanitary sewers, lakes, rivers, streams or public waterways. Block off drains and ditches. Provincial regulations require and federal regulations may require that environmental and/or other agencies be notified of a spill incident. Spill area must be cleaned and restored to original condition or to the satisfaction of authorities.

Reclaim or dispose of at a licensed waste disposal company.

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: May 28, 1991

DATE REVISED: April 1, 2000

BY: Product Safety Committee

Review date:

Authorized by