

RECEIVED

By Licence Administrator at 1:15 pm, Jun 15, 2011

Material Safety Data Sheet **Technologies**

Revision Date: 05/02/2008

Issue date: 05/02/2008

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: LePage Speed Set Epoxy -Resin
Product Use: Adhesive
Company address:
Henkel Canada Corporation
6685 Kennedy Rd Suite 1
Mississauga, Ontario L5T 3A5

Item No. : IDH No. 1165245
Region: Canada
Contact Information:
Telephone: 905.696.2770
Emergency telephone: 613-996-6666

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	60-100	None	None	None
Phenyl glycidyl ether 122-60-1	0.1-1	0.1 ppm TWA (skin)	10 ppm TWA 60 mg/m ³ TWA	None

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW**

Physical state: Liquid
Color: Translucent Clear
Odor: None

WHMIS hazard class: D.2.B

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Eye contact, Ingestion, Inhalation, Skin contact

Potential Health Effects

Inhalation: Mild respiratory tract irritation.
Skin contact: Allergic skin reaction. Moderate skin irritation. Itching. Redness.
Eye contact: Moderate eye irritation. Redness.
Ingestion: Not expected under normal conditions of use.

Existing conditions aggravated by exposure: Skin disorders. Skin allergies.

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel. Keep individual calm. Get medical attention if symptoms develop and persist.

Notes to physician: None.

Item No. : IDH No. 1165245

1 of 4

Product name: LePage Speed Set Epoxy -Resin

5. FIRE-FIGHTING MEASURES

Flash point:	Greater than 248.9°C (480°F) Pinsky Martens closed cup
Autoignition temperature:	Not available
Flammable/Explosive limits-lower %:	Not available
Flammable/Explosive limits-upper %:	Not available
Extinguishing media:	Foam, dry chemical or carbon dioxide.
Special fire fighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	In the event of fire, cool tanks with water spray. Closed containers may rupture (due to build up of pressure) when exposed to extreme heat.
Hazardous combustion products:	Oxides of carbon. Irritating organic fragments.
Sensitivity to mechanical impact:	Not available.
Sensitivity to static discharge:	Not available.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions:	Prevent product from entering drains or open waters.
Clean-up methods:	Remove all ignition sources. Immediately contact emergency personnel. Scrape up as much material as possible. Clean residue with soap and water. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Do not breathe mist or vapors. Keep container closed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.
Storage:	Store in original container until ready to use. Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.
Incompatible products:	Refer to Section 10.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Skin protection:	Chemical resistant, impermeable gloves.
Eye/face protection:	Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Translucent Clear
Odor:	None
Odor Threshold:	Not available
Vapor pressure:	0.03 mmHg
pH:	Not applicable
Boiling point/range:	Greater than 260.2°C (500°F)
Melting point/range:	Not available
Specific gravity:	1.17
Vapor density:	Not available
Evaporation rate:	Not available

Solubility in water: Slight
Partition coefficient (n-octanol/water): Not available
VOC content: 0.098% (value for resin and hardener together)

10. STABILITY AND REACTIVITY

Stability: Stable
Hazardous polymerization: Will not occur.
Hazardous decomposition products: None
Incompatibility: Strong acids. Strong bases. Strong oxidizers. Amines.
Conditions to avoid: Excessive heat. Storage with incompatible materials.

11. TOXICOLOGICAL INFORMATION

Product toxicity data: Not available
Toxicologically synergistic products: Not available.

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

Ingredient Toxicity Data & Carcinogen Status

Hazardous components	LD50s & LC50s	Other LD50s and LC50s	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	ACGIH - Carcinogens
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	Oral LD50 (Rat) = 11400 mg/kg	None	No	No	No	No
Phenyl glycidyl ether 122-60-1	Dermal LD50 (Rabbit) = 1500 µL/kg Oral LD50 (Rat) = 3850 mg/kg Inhalation LC50 (Mouse) > 100 ppm	None	No	Group 2B	Yes	A3 - Confirmed animal carcinogen with unknown relevance to humans

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	Allergen, Irritant
Phenyl glycidyl ether 122-60-1	Allergen, Central nervous system, Irritant, Respiratory, Blood, Immune system, Bone Marrow, Reproductive, Some evidence of carcinogenicity

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of in accordance with federal and local regulations.

14. TRANSPORT INFORMATION

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

Canada Transportation of Dangerous Goods - Ground:

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

International Air Transportation (ICAO/IATA):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None

Water Transportation (IMO/IMDG):

Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
Marine pollutant:	None known

15. REGULATORY INFORMATION

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2, 11

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Product Regulations.

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.