RECEIVED

By Licence Administrator at 1:06 pm, Jun 15, 2011

Odor

MATERIAL SAFETY DA

Health 1 Reactivity 0 В

WHITE LITHIUM GREASE - Bulk



NFPA SYMBOL

Light Petroleum

Not Determined

200°C (392°F)

0.95

HMIS SYMBOL

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name:

WHITE LITHIUM GREASE Bulk

Chemical Family:

Mixture

Use:

Petroleum based lubricating grease

Manufacturer/Supplier:

Jet-Lube of Canada Ltd. 3820 - 97 Street NW Edmonton, Alberta

Canada T6E 5S8 Phone: (780) 463-7441

Fax: (780) 463-7454 CCOHS: 1-800-668-4284

Emergency:

CANUTEC PH: (613) 996-6666 Cell: *666 TTY/TDD: 1-888-675-6863

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components CAS NO WT % OSHA PEL **ACGIH TLV** LD50 LC50

Zinc Oxide

1314-13-2 5 - 10 15mg/m³ 10mg/m³

7950mg/kg (oral, mouse) N/A

SECTION 3 - HAZARDS IDENTIFICATION

Route of Entry: Eyes:

Eyes, Inhalation, Ingestion, Skin May cause irritation to eyes.

Inhalation:

Viscous nature may block breathing passages if inhaled.

Indestion: Skin²

OTHER:

May cause diarrhea if indested.

May cause irritation after prolonged skin exposure, especially for

persons with hyper sensitivity

SECTION 4 - FIRST AID MEASURES

Eyes:

Flush with water until all residual material is gone. If irritation

persists, seek medical help

Indestion:

Do not induce vomiting. Wash out mouth. Contact a

physician immediately.

Skin:

Remove by wiping or with a waterless hand cleaner,

followed by washing with soap and water. Clear air passage. If breathing difficulty continues seek

Inhalation:

medical help

SECTION 5 - FIRE FIGHTING MEASURES

Flammability: Extinguishing Media: Nil at ambient temp

Flash Point (COC):

Use dry chemicals, foam, halon, CO2

Explosive Properties:

>221°C (430°F)

Autoignition Temp:

LEL - 0.9% UEL - 7%

Hazardous Combustion Products:

>260°C (500°F)

Oxides of carbon, smoke and irritating vapors as products of incomplete

combustion.

Protective Equipment:

Self-contained breathing apparatus.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Scoop up excess, then wipes down the affected area and pick up residue with diatomaceous earth to avoid a walking hazard.

Environmental Precautions: Do not allow product to enter into drains

SECTION 7 - HANDLING AND STORAGE

Handling Procedures:

No special handling precautions necessary. Do not pressurize, cut, heat or weld empty containers

Storage Requirements:

Store in a cool, well ventilated place

Engineering Controls:

If user's operation generates vapors or mists, use ventilation

to keep exposure to airborne contaminants below the exposure limit. Make up air should always be supplied to balance air removed by exhaust ventilation. Ensure eyewash station and safety shower are close to work station

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment (PPE's):

Respiratory Protection:

None required.

Hand Protection: Eve Protection:

Protective gloves for hypersensitive persons. Protective glasses if applied to moving parts.

Body Protection:

Protective overalls.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Odor Threshold:

Density (Typical):

Boiling Point:

Paste Not Determined

Vapor Pressure:

<0.01 kPa

Vapor Density: <316°C (600°F) Melting Point:

Neutral

0.95 g/cm³ Evaporation Rate (Butyl Acetate = 1.0): <0.01

SECTION 10 - STABILITY AND REACTIVITY

Stability

pH:

Conditions to Avoid:

Chemically stable under normal conditions. No photoreactive agents. Powerful sources of ignition and extreme temperatures.

Specific Gravity (Typical):

Materials to Avoid: Hazardous Decomposition Products: Strong acids and oxidizing agents. May release COx, smoke and irritating vapors when heated to decomposition.

SECTION 11 - TOXICOLOGICAL INFORMATION

Exposure Limit of Material: LC50 of Ingredients, Species and Routes: LD50 of Ingredients, Species and Routes:

See Section 2 See Section 2 Not Available

See Section 2

Teratogenecity, Embryotoxicity and/or Fetotoxicity: Mutagenicity: Not Available Effects of Long-Term (Chronic) Exposure: Long term dermal application may

produce possible skin irritation. Elevated temperatures or mechanical action may form vapors or fumes. Inhalation of oil mists or vapors may cause irritation of the upper respiratory

tract.

Carcinogen: NTP: No IARC: No

OSHA: No

SECTION 12 - ECOLOGICAL INFORMATION

Possible Effects:

Environmental Fate:

May generate oil fractions that could act as a marine pollutant, but is highly unlikely.

Behavior:

Relatively well behaved. Bioaccumulation potential almost nil. Product will float and spread across water, making it a nuisance contaminant

SECTION 13 - DISPOSAL CONSIDERATIONS

Consult federal, provincial and local regulations for disposal of petroleum products. Do not incinerate

SECTION 14 - TRANSPORT INFORMATION

TDG (Canada):

The mixture is not specifically listed in the Canadian Transportation of Dangerous Goods regulations.

Not Regulated

Land & Rail: Marine

Not Regulated

Shipping Name: UN No.: Packing Group:

N/A N/A N/A

Classification: Labeling Requirements: Placard Requirements:

N/A N/A

SECTION 15 - REGULATORY INFORMATION

WHMIS: DSI:

Not Regulated

CPR Compliance:

All components listed

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by those regulations.

SECTION 16 - OTHER INFORMATION

CPR - Controlled Product Regulations

DSL - Domestic Substance List

As of issue date, the information contained herein is accurate and reliable to the best of Jet-Lube of Canada Ltd.'s knowledge. Jet-Lube of Canada Ltd. does not warrant or guarantee its accuracy or reliability and shall not be liable for any loss or damage arising out of the use thereof. It is the users' responsibility to satisfy themselves that the information offered for their consideration is suitable for their particular use.

Prepared by:

Last Date of Revision:

Jet-Lube of Canada Ltd. - Laboratory

June 23, 2010