MATERIAL SAFETY DATA SHEET



102, 17910 – 55 Ave, Surrey, BC, Canada V3S 6C8 • Toll Free **1-866-535-6699** Tel: **604-575-6660** Fax: 604-575-5494 *e-mail: extreme.ron@telus.net*

EXTREME SUPER TROL

EMERGENCY PHONE NO. (604) 575-6660

PAGE 1 OF 4

WHMIS HAZARD INDEX:

DEGREE OF HAZARD: HAZARD RATING:

HEALTH 0 0 **LEAST** FIRE 0 1 **SLIGHT** REACTIVITY 2 0 **MODERATE** B (GLASSES & GLOVES) 3 OTHER: HIGH **EXTREME**

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME: EXTREME SUPER TROL
CHEMICAL IDENTIFICATION: Semi Synthetic Cellulose
MATERIAL USE: Drilling Fluid Additive
WHMIS CLASSIFICATION: Not Regulated
WORK PLACE HAZARD: Not Regulated

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not Dangerous Goods

PACKAGE GROUP:

CAS NUMBER:

MSDS CODE:

Not Applicable

Not Applicable

SECTION 2 HAZARDOUS INGREDIENTS

INGREDIENT: No Hazardous Ingredients PERCENTAGE: N/A

CAS NUMBER: N/A

LD (50): LC (50):

EXTREME SUPER TROL

MATERIAL SAFETY DATA SHEET

SECTION 3 PHYSICAL DATA

APPEARANCE AND ODOUR: Free flowing white powder. No appreciable odour.

DENSITY (SPECIFIC GRAVITY):

BOILING POINT:

MELTING POINT:

SOLUBILITY:

EVAPORATION RATE: (EE=1):

VAPOUR PRESSURE: (MM HG):

VAPOUR DENSITY: (AIR = 1):

1.55

N/A

N/A

N/A

SECTION 4 FIRE AND EXPLOSION

FLASHPOINT: > 350°C

FLAMMABLE LIMIT: Not determined

AUTO IGNITION TEMP: No data

EXTINGUISHING MEDIA: Water, water fog, foam, dry chemical, CO₂

SPECIAL FIRE FIGHTING PROCEDURES: No special requirements

UNUSUAL FIRE AND EXPLOSION HAZARDS: Becomes very slippery when contacted with water.

SECTION 5 REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.): Stable

INCOMPATIBILITY (CONDITIONS TO AVOID): Strong oxidizing agents and caustic solutions.

HAZARDOUS POLYMERIZATION: Will not occur HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon

EXTREME SUPER TROL

MATERIAL SAFETY DATA SHEET

WASTE DISPOSAL:

STORAGE REQUIREMENTS:

SECTION 6	HEALTH HAZARDS
ROUTE OF ENTRY: () SKIN (X) EYE CONTACT	(X)INHALATION (X)INGESTION
SKIN CONTACT: EYE CONTACT: INHALATION:	Generally not irritating Dust may produce some irritation Non irritating in low concentrations. High concentrations may cause mechanical irritation of upper respiratory tract.
INGESTION: SECTION 7	Generally no harmful effects. May cause gastric intestinal discomfort. PREVENTATIVE MEASURES
SECTION 7	FREVENTATIVE WEASURES
SKIN PROTECTION: EYE PROTECTION: VENTILATION: RESPIRATORY PROTECTION: LEAK & SPILL PROCEDURE:	None normally required. Nuisance dust, use goggles. No special requirements. Nuisance dust, use dust mask. Sweep up or vacuum if dry. If wet, pick up with earth or sand.

Dispose of in compliance with local and government regulations.

dry, material becomes slippery when wet.

Keep containers closed when not in use. Keep

EXTREME SUPER TROL

MATERIAL SAFETY DATA SHEET

SECTION 8 FIRST AID MEASURES

SKIN: Wash with soap and water.

EYE: Flush with water at least 15 minutes.

INHALATION: Remove from exposure.

INGESTION: Induce vomiting, give 2 glasses of water. If

adverse symptoms develop seek medical

attention.

SECTION 9 PREPARATION DATE

DATE ISSUED: AUGUST 20, 2009

BY: PRODUCT SAFETY COMMITTEE

THE DATA REPRESENTED HEREIN IS BELIEVED ACCURATE AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.