MATERIAL SAFETY DATA SHEET



15640 Mountainview Dr., Surrey, BC, Canada V3S 0C6 • Toll Free **1-866-535-6699** Tel: **604-535-6699** Fax: 604-535-5493 *e-mail: extreme.ron@telus.net*

EXTREME TORQ-EEZ

EMERGENCY PHONE NO. (604) 535-6699

PAGE 1 OF 4

WHMIS HAZARD INDEX:

DEGREE OF HAZARD: HAZARD RATING:

HEALTH 1 0 **LEAST** FIRE 0 1 **SLIGHT REACTIVITY** 2 1 **MODERATE** B (GLASSES & GLOVES) 3 OTHER: HIGH **EXTREME**

SECTION 1 PRODUCT IDENTIFICATION

PRODUCT NAME: EXTREME TORQ-EEZ

CHEMICAL IDENTIFICATION: Proprietary

MATERIAL USE: Drilling Fluid Lubricant

WHMIS CLASSIFICATION:
WORK PLACE HAZARD:
Non Hazardous
Not Available

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not Dangerous Goods

PACKAGE GROUP:

CAS NUMBER:

MSDS CODE:

Not Available

Not Available

SECTION 2 HAZARDOUS INGREDIENTS

INGREDIENT: None Considered Hazardous

PERCENTAGE: N/A CAS NUMBER: N/A

LD (50): LC (50):

EXTREME TORQ-EEZ

MATERIAL SAFETY DATA SHEET

SECTION 3 PHYSICAL DATA

APPEARANCE AND ODOUR: Amber liquid with mild odour

DENSITY (SPECIFIC GRAVITY): 1.0
BOILING POINT: 100°C

MELTING POINT: Not Determined

SOLUBILITY:

EVAPORATION RATE: (EE=1):

VAPOUR PRESSURE: (MM HG):

VAPOUR DENSITY: (AIR = 1):

pH:

Complete

Not Available

Not Available

9.0 - 10.0

SECTION 4 FIRE AND EXPLOSION

FLASHPOINT: N/A

FLAMMABLE LIMIT: Aqueous Mixture - Non Flammable

AUTO IGNITION TEMP: Not Determined

EXTINGUISHING MEDIA: Dry Chemical, Foam CO₂, Water Spray

SPECIAL FIRE FIGHTING PROCEDURES: None required

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION 5 REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC.): Stable

INCOMPATIBILITY (CONDITIONS TO AVOID): Oxidizing Agents HAZARDOUS POLYMERIZATION: Will not occur

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

EXTREME TORQ-EEZ

MATERIAL SAFETY DATA SHEET

SECTION 6	HEALTH HAZARDS
-----------	-----------------------

ROUTE OF ENTRY:

(X) SKIN (X) EYE CONTACT () INHALATION (X) INGESTION

SKIN CONTACT: Prolonged contact may cause skin irritation.

EYE CONTACT: May be irritating to eyes on direct contact.

INHALATION: Not expected to present a hazard at ambient

temperatures.

INGESTION: May cause nausea and vomiting.

SECTION 7 PREVENTATIVE MEASURES

SKIN PROTECTION: Impervious gloves, protective clothing as required.

EYE PROTECTION: Goggles

VENTILATION: 10 Changes per hour RESPIRATORY PROTECTION: None normally required

LEAK & SPILL PROCEDURE: Dam to prevent spreading. Soak up with

absorbent material. Dispose of with solid waste.

WASTE DISPOSAL: Dispose of in compliance with government

regulation and local requirements.

STORAGE REQUIREMENTS: Store in cool, dry area, away from oxidizing

agents. Keep containers closed when not in use.

EXTREME TORQ-EEZ

MATERIAL SAFETY DATA SHEET

SECTION 8 FIRST AID MEASURES

SKIN: Wash thoroughly with soap and water.

EYE: Flush with water for at least 15 minutes. Seek

medical attention.

INHALATION: No expected problems due to low volatility. INGESTION: Induce vomiting. Give two glasses of water.

Consult a physician at once.

SECTION 9 PREPARATION DATE

DATE ISSUED: AUGUST 20, 1996

BY: PRODUCT SAFETY COMMITTEE

THE DATA REPRESENTED HEREIN IS BELIEVED ACCURATE AND REFLECTS OUR BEST PROFESSIONAL JUDGMENT. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF SUCH DATA, THE RESULTS TO BE OBTAINED FROM THE USE THEREOF, OR THAT ANY SUCH USE DOES NOT INFRINGE ANY PATENT. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS OF USE BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, WE DO NOT ASSUME ANY RESPONSIBILITY FOR THE RESULTS OF SUCH APPLICATION. THIS INFORMATION IS FURNISHED UPON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS OWN DETERMINATION OF THE SUITABILITY OF THE MATERIAL FOR HIS PARTICULAR PURPOSE.

DATE REVISED: AUGUST 20, 2009