

**WESTCOAST DRILLING SUPPLIES LTD.**

8069 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 - Fax: (604) 940-6080

Toll Free: 1-800-665-6645

CAL-SEAL (EA-2)

Page 2 of 2

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMIT:	Not determined
EXTINGUISHING MEDIA:	Use media appropriate for surrounding materials.
SPECIAL FIRE FIGHTING PROCEDURES:	Self contained respirators required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Not applicable

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []	
INCOMPATIBILITY (CONDITIONS TO AVOID):	None
HAZARDOUS DECOMPOSITION PRODUCTS:	None
HAZARDOUS POLYMERIZATION:	Will not occur [XXX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION:	Suggest NIOSH/MESA approved dust mask.
VENTILATION:	Ten (10) changes per hour suggested
PROTECTIVE GLOVES:	Suggest plastic or rubber
EYE PROTECTION:	Suggest goggles.
OTHER PROTECTIVE EQUIPMENT:	Suggest rubber apron.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a dry location to protect product quality. Avoid creating or inhaling dust. Avoid contact with skin, eyes and clothing.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Use protective equipment. Sweep up to remove. Avoid creating or inhaling dust.

WASTE DISPOSAL METHOD:

If not contaminated, reuse product. Get approval from landfill operator to transport to sanitary landfill.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: March, 22, 1989

DATE REVISED: April 1, 2000

BY: Product Safety Committee

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V4G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **CLAY STABILIZER**
PRODUCT USE: Drilling System Additive
CHEMICAL FAMILY: Amine salts

WORK PLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: D-2B
WORK PLACE HAZARD: Skin and Eye Irritant

TRANSPORTATION OF DANGEROUS GOODS (TDG)

TDG CLASSIFICATION: Not Regulated by TDG

SECTION II: HAZARDOUS INGREDIENTS

Ingredient	Percent	CAS Number	LD50 (Oral rat)	LC50 (Dermal rabbit)
Organic Amine	10-30	124-09-4	750 mg/kg	Not determined

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY:
[XXX] Eye Contact, [XXX] Inhalation, [XXX] Ingestion []

SKIN AND EYE CONTACT: Not expected to be problem under normal conditions of use. Liquid may cause minor irritation, burning on prolonged contact with skin. Due to the pH of the material it will irritate eyes on contact. LD50 (skin, rabbit) 3700 mg/kg based on components.

INHALATION: Not expected to be a problem under normal conditions of use.

INGESTION: LD50 (oral, rat) 3000mg/kg based on component concentrations

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: In case of skin contact, immediately flush contacted area for at least fifteen (15) minutes with water. Remove contaminated clothing immediately and launder before reuse. If irritation develops consult a doctor.

EYE CONTACT: In case of contact with eyes, flush with water for at least fifteen (15) minutes. Seek immediate medical attention.

INGESTION: If victim is conscious, give water. Do not induce vomiting. Seek immediate medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: Clear odorless liquid
SPECIFIC GRAVITY: 1.042
BOILING POINT: >100° C
MELTING POINT: <-35° C
SOLUBILITY IN WATER: Soluble
PERCENT VOLATILE BY VOLUME: Not applicable
EVAPORATION RATE: Not applicable
VAPOR PRESSURE (mm Hg): Not applicable
VAPOR DENSITY (Air=1): Not applicable
pH: 9-10

**WESTCOAST DRILLING SUPPLIES LTD.**

8069 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 • Fax: (604) 940-6080

Toll Free: 1-800-665-6645

CLAY STABILIZER

Page 2 of 2

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	>100° C (TCC)
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Water, dry chemical, foam.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained respirators required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None known
HAZARDOUS COMBUSTION PRODUCTS:	CO, CO ₂ , oxides of nitrogen

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []	
INCOMPATIBILITY (MATERIALS TO AVOID):	Strong oxidizing agents
HAZARDOUS DECOMPOSITION PRODUCTS:	CO, on combustion oxides of nitrogen.
HAZARDOUS POLYMERIZATION:	Will not occur [XXX] May occur []

SECTION VIII: PREVENTIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	Suggest NIOSH/MESA approved dust mask
VENTILATION:	Ten (10) changes per hour suggested
PROTECTIVE GLOVES:	Suggest plastic or rubber
EYE PROTECTION:	Suggest goggles
OTHER PROTECTIVE EQUIPMENT (Specify):	Suggest rubber apron

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in cool, dry, well-ventilated place away from incompatible materials keep bags or fiber drums dry at all times. Wash thoroughly after handling. Do not get in eyes, on skin or on clothing.

Do not cut, grind, weld, or drill on or near this container. Containers, even those that have been emptied, will retain product residue, always obey hazard warnings and handled empty containers as if they were full.

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED OR RELEASED:

Wear protective equipment. For small spills, sweep up and dispose of in DOT approved waste containers. For large spills, shovel into DOT approved waste containers. Keep out of sewers, storm drains, surface waters and soil.

WASTE DISPOSAL METHOD:

Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper disposal procedures.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: July 18, 1997

DATE REVISED: April 1, 2000

PHONE: 403-279-8545

BY: Product Safety Committee

Material Safety Data Sheet / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V4G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **SUPER POLY**
CHEMICAL FAMILY: Cellulose Ether
PRODUCT USE: Drilling Mud Additive.
WHMIS CLASSIFICATION: Not a Controlled Product under WHMIS
WORK PLACE HAZARD: Not applicable.

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not applicable.
PACKAGE GROUP: Not applicable.
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable.

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50 LC50
No Hazardous Ingredients.			

SECTION III: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:
☐ Skin, ☐ Eye Contact, ☐ Inhalation, ☐ Ingestion

SKIN CONTACT: May produce slight irritation with prolonged contact with moistened product.
EYE CONTACT: Dust may produce mechanical irritation.
INHALATION: Non-irritating to mucous membranes, however, breathing high concentrations of the dust may cause mechanical irritation of the nose, throat and upper respiratory tract.
INGESTION: Passes through relatively inert. May cause gastro intestinal upset. Oral LD50 > 25 g/kg (rats).

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Wash exposed area with soap and water. If irritation develops seek medical attention.
EYE CONTACT: Flush eyes with running water for at least fifteen (15) minutes. If illness or adverse symptoms develop, seek medical attention.
INHALATION: Remove from exposure. If illness or adverse symptoms develop, seek medical attention.
INGESTION: Give two (2) glasses of water and induce vomiting. If illness or adverse symptoms develop, seek medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: Light colored powder; Odorless.
DENSITY (SPECIFIC GRAVITY): 1.6
BOILING POINT: Not applicable
MELTING POINT: Not applicable
WATER SOLUBILITY: Complete
% VOLATILE BY VOLUME: Negligible
EVAPORATION RATE: Not applicable
VAPOR PRESSURE: (mm Hg) Not applicable
VAPOR DENSITY: (Air = 1) Not applicable

**WESTCOAST DRILLING SUPPLIES LTD.**

8069 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 - Fax: (604) 940-6080

Toll Free: 1-800-665-6645

SUPER POLY

Page 2 of 2

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMIT:	Not determined
EXTINGUISHING MEDIA:	Water, water fog, chemical, carbon dioxide CO ₂ .
SPECIAL FIRE FIGHTING PROCEDURES:	Evacuate area of all necessary personnel. Use self-contained respirators for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	If in a finely divided and suspended state, treat as a flammable dust. Material becomes very slippery when contacted with water.

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []	
INCOMPATIBILITY (CONDITIONS TO AVOID):	Strong oxidizing and caustic solutions.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon Dioxide, Carbon Monoxide
HAZARDOUS POLYMERIZATION:	Will not occur [XXX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION:	Suggest dust mask. Nuisance dust.
VENTILATION:	No special requirements.
PROTECTIVE GLOVES:	None required.
EYE PROTECTION:	Suggest goggles, nuisance dust.
OTHER PROTECTIVE EQUIPMENT:	None required.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid ingestion. Practice reasonable caution and personal cleanliness. Avoid skin and eye contact. Material become slippery when wet.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Vacuum or sweep-up if dry. If wet, pick up with dry material such as sand or dirt. Avoid flushing with water as material becomes slippery.

WASTE DISPOSAL METHOD:

Dispose of material in accordance with local ordinances. Landfill suggested.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: February 20, 1989

DATE REVISED: April 1, 2000

BY: Product Safety Committee

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V4G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **X-TRA GEL**
CHEMICAL FAMILY: Sodium Montmorillonite
WHMIS CLASSIFICATION: Class D-2(A)
WORK PLACE HAZARD: Potential Carcinogen; contains free silica

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not Dangerous Goods
PACKAGE GROUP: Not applicable
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	OSAH PEL	ACGIH TLV
Bentonite		1302-78-9	5 mg/M	Not applicable
Quartz (Silica)		14808-60-7	10 mg/M	0.1 mg/M
Crystobalite		14464-46-1	10 mg/M	0.05 mg/M
Tridymite		15468-32-3	10 mg/M	0.05 mg/M

SECTION III: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:
[] Skin, [] Eye Contact, [XXX] Inhalation, [] Ingestion

ACUTE - SHORT TERM EXPOSURE: Cough if exposed to dust at levels higher than TLV's.
CHRONIC - LONG TERM EXPOSURE: May lead to development of silicosis or other respiratory problems if consistently exposed to free silica containing airborne bentonite.

SECTION IV: FIRST AID MEASURES

No first aid measures are suggested for chronic (long term exposure). For acute (short term exposure) remove patient from dusty environment.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR: Pale gray to buff powder or granules; Odorless.
DENSITY (SPECIFIC GRAVITY): 2.35
BOILING POINT: Not applicable
MELTING POINT: 788° C
WATER SOLUBILITY: Insoluble; forms colloidal suspension.
% VOLATILE BY VOLUME: Not applicable
EVAPORATION RATE: Not applicable
VAPOR PRESSURE: (mm Hg) Not applicable
VAPOR DENSITY: (Air = 1) Not applicable
pH: 7 - 6

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not applicable
FLAMMABLE LIMIT: Not applicable

**WESTCOAST DRILLING SUPPLIES LTD.**

8059 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 - Fax: (604) 940-6080

Toll Free: 1-800-665-6645

X-TRA GEL

Page 2 of 2

EXTINGUISHING MEDIA: Not applicable
SPECIAL FIRE FIGHTING PROCEDURES: Not applicable
UNUSUAL FIRE AND EXPLOSION HAZARDS: Not applicable

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID): None
HAZARDOUS DECOMPOSITION PRODUCTS: None
HAZARDOUS POLYMERIZATION: Will not occur [XXX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators for silica bearing dust.
VENTILATION: Yes if particular; Personal air supply may be useful.
PROTECTIVE GLOVES: None required
EYE PROTECTION: Suggest goggles
OTHER PROTECTIVE EQUIPMENT: None required

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid breathing dust; wear an approved respirator. Practice reasonable caution and personal cleanliness. Avoid eye contact.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Vacuum or sweep up if dry. Avoid flushing with water as material may become extremely slippery.

WASTE DISPOSAL METHOD:

Dispose of material in a manner to prevent generating dust.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: November 10, 1988

DATE REVISED: April 1, 2000

BY: Product Safety Committee

WESTCOAST DRILLING SUPPLIES LTD.
8069 River Way, Delta, British Columbia,
Canada V4G 1L3
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-6645

SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **PELADOW®**
PRODUCT USE: Oil Well Fluid Additive
CHEMICAL FAMILY: Calcium Chloride (>90%)

WORK PLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Class D-2(B)
WORK PLACE HAZARD: Skin and Eye Irritant

TRANSPORTATION OF DANGEROUS GOODS (TDGR)

SHIPPING NAME: Not Regulated Under TDG
TDG CLASSIFICATION: Not applicable
PACKAGE GROUP: Not applicable
PRODUCT IDENTIFICATION NUMBER (PIN): Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50 (oral rat)
Calcium Chloride	91 - 92%	10043-52-4	900-2100 mg / kg (100%)
Sodium Chloride	1 - 2%	7647-14-5	Not available
Potassium Chloride	2-3%	7447-40-7	Not available
Strontium Chloride	1%	10476-85-4	Not available

SECTION III: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:
[XX] Skin, [XX] Eye Contact, [XX] Inhalation, [XX] Ingestion

EYE CONTACT: Dusts may cause moderate to severe eye irritation, with corneal injury that may be slow to heal. When dissolving, the heat produced may cause more intense effects as well as thermal burns.

SKIN CONTACT: Short single exposure not likely to cause significant skin irritation. Prolonged or repeated exposure may cause skin irritation, even a burn. May cause more severe response if skin is damp and/or abraded, or if material is confined to skin. When dissolving, the heat produced may cause more intense effects as well as thermal burns. DOT classification: Noncorrosive.

SKIN ABSORPTION: A single prolonged exposure is not likely to result in the material being absorbed through the skin in harmful amounts. The LD₅₀ for skin absorption in rabbits is >5000 mg / kg.

INGESTION: Single dose oral toxicity is low. Swallowing solids may cause gastro-intestinal irritation or ulceration.

INHALATION: Vapours are unlikely due to physical properties. Dust may cause irritation of upper respiratory tract.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Immediately wash skin with lots of soap and water. Remove contaminated clothing and shoes; wash before reuses. Get medical attention if irritation persists after washing.

EYE CONTACT: *Get immediate medical attention.* Immediately flush eyes with lots of running water for 15 minutes, lifting the upper and lower eyelids occasionally.

**WESTCOAST DRILLING SUPPLIES LTD.**

8069 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 - Fax: (604) 940-6060

Toll Free: 1-800-665-6645

PELADOW®

Page 2 of 3

INGESTION: If conscious, immediately induce vomiting. *Get immediate medical attention. Do not give anything by mouth to an unconscious or convulsing person.*

INHALATION: remove to fresh air. Give artificial respiration if not breathing. *Get immediate medical attention.*

NOTE TO PHYSICIAN: If burn is present, treat as any thermal burn, after decontamination, No specific antidote. Supportive care. Treatment based on judgement of the physician in response to reactions of patient.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOR:	White to off-white powder; odorless.
DENSITY (SPECIFIC GRAVITY):	2.2 g/cc
BOILING POINT:	198° C
MELTING POINT:	Approximately 230° C
WATER SOLUBILITY:	Soluble pH 7-10
% VOLATILE BY VOLUME:	Not applicable
EVAPORATION RATE:	Not applicable
VAPOR PRESSURE: (mm Hg)	0.009 mm Hg 20° C
VAPOR DENSITY: (Air = 1)	Not applicable

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not applicable
FLAMMABLE LIMIT:	Not applicable
EXTINGUISHING MEDIA:	This material is not combustible
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained respirators required for fire-fighting personnel
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None

SECTION VII: REACTIVITY DATA

STABLE [XXX] INSTABLE []

INCOMPATIBILITY (CONDITIONS TO AVOID): (Specific Materials to Avoid) Calcium Chloride will: corrode most metals exposed to air, attack aluminium (and its alloys) and yellow brass; react with sulphuric acid to form hydrogen chloride which is corrosive, irritating, and reactive; give an exothermic reaction with water-reactive materials such as sodium; result in a runaway polymerization reaction with methyl vinyl ether (Bretherick, 1979); and, in solution form react with zinc (galvanizing) to yield hydrogen gas which is explosive (Ibid.). (Bretherick, L. 1979, Handbook of Reactive Chemical Hazards, 2nd Ed.)

HAZARDOUS DECOMPOSITION PRODUCTS: Not Applicable**HAZARDOUS POLYMERIZATION:** Will not occur [XX] May occur []

SECTION VIII: PREVENTATIVE MEASURES

RESPIRATORY PROTECTION:	Approved dust respirator mask
VENTILATION:	Local mechanical exhaust
PROTECTIVE GLOVES:	Rubber gloves.
EYE PROTECTION:	Chemical goggles.
OTHER PROTECTIVE EQUIPMENT:	An eyewash and safety shower should be nearby and ready for use.



WESTCOAST DRILLING SUPPLIES LTD.

8069 River Way, Delta, British Columbia, Canada V4G 1L3

Phone: (604) 940-6050 - Fax: (604) 940-6060

Toll Free: 1-800-665-6645

PELADOW®

Page 3 of 3

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid eye and prolonged skin contact. Always use cool water (temperature less than 27° C), when dissolving calcium chloride. Heat developed by solutions is very high during dissolving and mixing. When exposed to atmosphere, calcium chloride will pick up water and form a solution. Leather clothing and shoes will be damaged by calcium chloride.

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Losses incidental to correct applications of this product in its intended uses are not expected to be harmful to the environment. Wear appropriate safety apparel during clean-up. Avoid entry of large amount of product into sewers, natural waters, and drinking water sources. Due to possible harmful effects. Avoid contact with vegetation, animals and fish life. Recover quickly into suitable, dry sealable containers if reusing. Small quantities may be flushed away with plenty of water. Walking surfaces may remain wet longer due to moisture being held by spilled product - avoid by thoroughly water washing surfaces.

WASTE DISPOSAL METHOD:

Dispose of contaminated product and materials used in cleaning up spills or leaks in a manner approved for this material. Consult appropriate regulatory agencies to ascertain proper disposal procedures

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: December 15, 1994

DATE REVISED: April 1, 2000

BY: Product Safety Committee

NWT SPILL REPORT (*Form NWT 1752/0202*)
(Oil, Gas, Hazardous Chemicals or other Materials)



NWT SPILL REPORT

(Oil, Gas, Hazardous Chemicals or other Materials)

24 – Hour Report Line
Phone: (867) 920-8130
Fax: (867) 873-6924

A Report Date and Time		B Date and Time of spill (if known)		C <input type="checkbox"/> Original Report <input type="checkbox"/> Update no. _____		Spill Number _____	
D Location and map coordinates (if known) and direction (if moving)							
E Partly responsible for spill							
F Product(s) spilled and estimated quantities (provide metric volumes/weights if possible)							
G Cause of spill							
H Is spill terminated? <input type="checkbox"/> yes <input type="checkbox"/> no		I If spill is continuing, give estimated rate		J Is further spillage possible? <input type="checkbox"/> yes <input type="checkbox"/> no		K Extent of contaminated area (in square meters if possible)	
L Factors effecting spill or recovery (weather conditions, terrain, snow cover, etc.)				M Containment (natural depression, dikes, etc.)			
N Action, if any, taken or proposed to contain, recover, clean up or dispose of product(s) and contaminated materials							
O Do you require assistance? <input type="checkbox"/> no <input type="checkbox"/> yes, describe:				P Possible hazards to person, property, or environment; eg: fire, drink water, fish or wildlife			
Q Comments or recommendations						FOR SPILL LINE USE ONLY	
						Lead agency	
						Spill significance	
						Lead Agency contact and time	
						Is this file now closed? <input type="checkbox"/> yes <input type="checkbox"/> no	
Reported by		Position. Employer, Location				Telephone	
Reported to		Position. Employer, Location				Telephone	