

**MATERIAL SAFETY DATA SHEET**

---

Date Prepared: May 17, 2003  
Supersedes: November 05, 2002  
MSDS Number: 08058

---

**1. PRODUCT INFORMATION**

Product Identifier: HYDRAUL 56

Application and Use:  
Transmission and hydraulic fluid

Product Description:

A lubricating oil consisting of a mixture of saturated and unsaturated hydrocarbons derived from paraffinic distillate, and additives.

---

**REGULATORY CLASSIFICATION**

WHMIS:  
Not a controlled product

CEPA: CANADIAN ENVIRONMENTAL PROTECTION ACT  
All components of this product are either on the Domestic Substances List (DSL) or are exempt.

TDG INFORMATION (RAIL/ROAD):  
Not Regulated in Canada.

Please be aware that other regulations may apply.

---

**TELEPHONE NUMBERS**

Emergency 24 hr. (519) 339-2145  
Technical Info. (800) 268-3183

**MANUFACTURER/SUPPLIER:**

IMPERIAL OIL  
Products Division  
111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(416) 968-4441

---

## 2. REGULATED COMPONENTS

The following components are defined in accordance with sub-paragraph 13(a) (i) to (iv) or paragraph 14(a) of the Hazardous Products Act:

NAME	%	CAS #
Not applicable		

---

## 3. TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Physical State: Liquid  
 Specific gravity: not available  
 Viscosity: 9.35 cSt at 100 deg C  
 Vapour Density: not available  
 Boiling Point: 322 to 615 deg C  
 Evaporation rate: <0.1 (1= n-butylacetate)  
 Solubility in water: negligible  
 Freezing/Pour Point: -36 deg C ASTM D97  
 Odour Threshold: not available  
 Vapour Pressure: <1 kPa at 38 deg C  
 Density: 0.89 g/cc at 15 deg C  
 Appearance/odour: Yellow oil, petroleum odour

---

## 4. HEALTH HAZARD INFORMATION

### NATURE OF HAZARD

#### INHALATION:

Negligible hazard at normal temperatures (up to 38 deg C).  
 Elevated temperatures or mechanical action may form vapours, mists or fumes which may be irritating to the eyes, nose, throat and lungs.  
 Avoid breathing vapours or mists.

#### EYE CONTACT:

Slightly irritating, but will not injure eye tissue.

#### SKIN CONTACT:

Low toxicity.  
 Frequent or prolonged contact may irritate the skin.

#### INGESTION:

Low toxicity.

#### ACUTE TOXICITY DATA:

Based on animal testing data from similar materials and products,

the acute toxicity of this product is expected to be:

Oral : LD50 > 5000 mg/kg (Rat)  
Dermal : LD50 > 3160 mg/kg (Rabbit)  
Inhalation : LC50 > 5000 mg/m3 (Rat)

**OCCUPATIONAL EXPOSURE LIMIT:**

**ACGIH recommends:**

For oil mists, 5 mg/m3.

Local regulated limits may vary.

---

## 5. FIRST AID MEASURES

**INHALATION:**

Vapour pressure of this material is low and as such inhalation under normal conditions is usually not a problem. If overexposed to oil mist, remove from further exposure. Administer artificial respiration if breathing has stopped. Keep at rest. Call for prompt medical attention.

**EYE CONTACT:**

Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:**

Flush with large amounts of water. Use soap if available. Remove severely contaminated clothing (including shoes) and launder before reuse. If irritation persists, seek medical attention.

**INGESTION:**

If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

---

## 6. PREVENTIVE AND CORRECTIVE MEASURES

**PERSONAL PROTECTION:**

The selection of personal protective equipment varies, depending upon conditions of use.

In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves.

Where only incidental contact is likely, wear safety glasses with side shields. No other special precautions are necessary provided skin/eye contact is avoided.

Where concentrations in air may exceed the occupational exposure limits

given in Section 4 and where engineering, work practices or other means of exposure reduction are not adequate, approved respirators may be necessary to prevent overexposure by inhalation.

**ENGINEERING CONTROLS:**

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces.

**HANDLING, STORAGE AND SHIPPING:**

Keep containers closed. Handle and open containers with care. Store in a cool, well ventilated place away from incompatible materials. Do not handle or store near an open flame, sources of heat, or sources of ignition. Empty containers may contain product residue. Do not pressurize cut, heat, or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning.

**LAND SPILL:**

Eliminate source of ignition. Keep public away. Prevent additional discharge of material, if possible to do so without hazard. Prevent spills from entering sewers, watercourses or low areas. Contain spilled liquid with sand or earth. Recover by pumping or by using a suitable absorbant. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

**WATER SPILL:**

Remove from surface by skimming or with suitable absorbents. If allowed by local authorities and environmental agencies, sinking and/or suitable dispersants may be used in unconfined waters. Consult an expert on disposal of recovered material. Ensure disposal in compliance with government requirements and ensure conformity to local disposal regulations. Notify the appropriate authorities immediately. Take all additional action necessary to prevent and remedy the adverse effects of the spill.

---

**7. FIRE AND EXPLOSION HAZARD**

Flashpoint and method: 200 deg C COC ASTM D92

Autoignition: 330 deg C Flammable Limits: LEL: NA UEL: NA

**GENERAL HAZARDS:**

Low Hazard; liquids may burn upon heating to temperatures at or above the

flash point.  
Toxic gases will form upon combustion.

**FIRE FIGHTING:**

Use water spray to cool fire exposed surfaces and to protect personnel.  
Shut off fuel to fire.

Use foam, dry chemical or water spray to extinguish fire.  
Respiratory and eye protection required for fire fighting personnel.  
Avoid spraying water directly into storage containers due to danger of  
boilover.  
A self-contained breathing apparatus (SCBA) should be used for all indoor  
fires and any significant outdoor fires. For small outdoor fires, which  
may easily be extinguished with a portable fire extinguisher, use of an  
SCBA may not be required.

**HAZARDOUS COMBUSTION PRODUCTS:**

Smoke, carbon monoxide, carbon dioxide and traces of oxides of sulphur

---

## 8. REACTIVITY DATA

**STABILITY:**

This product is stable. Hazardous polymerization will not occur.

**INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:**

Strong oxidizing agents

**HAZARDOUS DECOMPOSITION:**

none

---

## 9. NOTES

All components of this product are listed on the U.S. TSCA inventory.

.

**REVISION SUMMARY:**

Since 5 November 2002, this MSDS has been revised in Section(s):

3

---

## 10. PREPARATION

Date Prepared: May 17, 2003  
Prepared by: Lubricants & Specialties  
IMPERIAL OIL  
Products Division

111 St Clair Avenue West  
Toronto, Ontario  
M5W 1K3  
(800) 268-3183

---

CAUTION: " The information contained herein relates only to this product or material and may not be valid when used in combination with any other product or material or in any process. If the product is not to be used for a purpose or under conditions which are normal or reasonably foreseeable, this information cannot be relied upon as complete or applicable. For greater certainty, uses other than those described in Section 1 must be reviewed with the supplier. The information contained herein is based on the information available at the indicated date of preparation. This MSDS is for the use of Imperial Oil customers and their employees and agents only. Any further distribution of this MSDS by Imperial Oil customers is prohibited without the written consent of Imperial Oil."