

# UPDATED SPILL CONTINGENCY PLAN

## Appendices

May, 2014



### Greyhound Project

Claims K01191 – K01200.....Map sheet NTS 66A/09

Lat: 64° 38' N Long: 96° 19' W



**PwP consulting**

**Geological Consultant**



To Aura Silver Resources Inc.

57 Main Street N, Suite 206 Brampton, ON L6X 1S9

(905) 456-5436, (fax) 456-7180 cell: (416) 705-3421

[pwppconsulting@bellnet.ca](mailto:pwppconsulting@bellnet.ca)

## NT-NU Spill Report Form

				<b>NT-NU SPILL REPORT</b> OIL, GASOLINE, CHEMICALS AND OTHER HAZARDOUS MATERIALS		<b>NT-NU 24-HOUR SPILL REPORT LINE</b> TEL: (867) 920-8130 FAX: (867) 873-6924 EMAIL: spills@gov.nt.ca	
REPORT LINE USE ONLY							
A	REPORT DATE: MONTH - DAY - YEAR			REPORT TIME		<input type="checkbox"/> ORIGINAL SPILL REPORT, OR <input type="checkbox"/> UPDATE # _____ TO THE ORIGINAL SPILL REPORT	
B	OCCURRENCE DATE: MONTH - DAY - YEAR			OCCURRENCE TIME		<div style="border: 1px solid black; padding: 2px;">REPORT NUMBER</div>	
C	LAND USE PERMIT NUMBER (IF APPLICABLE)			WATER LICENCE NUMBER (IF APPLICABLE)			
D	GEOGRAPHIC PLACE NAME OR DISTANCE AND DIRECTION FROM NAMED LOCATION			REGION <input type="checkbox"/> NWT <input type="checkbox"/> NUNAVUT <input type="checkbox"/> ADJACENT JURISDICTION OR OCEAN			
E	LATITUDE DEGREES      MINUTES      SECONDS			LONGITUDE DEGREES      MINUTES      SECONDS			
F	RESPONSIBLE PARTY OR VESSEL NAME			RESPONSIBLE PARTY ADDRESS OR OFFICE LOCATION			
G	ANY CONTRACTOR INVOLVED			CONTRACTOR ADDRESS OR OFFICE LOCATION			
H	PRODUCT SPILLED			QUANTITY IN LITRES, KILOGRAMS OR CUBIC METRES		U.N. NUMBER	
	SECOND PRODUCT SPILLED (IF APPLICABLE)			QUANTITY IN LITRES, KILOGRAMS OR CUBIC METRES		U.N. NUMBER	
I	SPILL SOURCE			SPILL CAUSE		AREA OF CONTAMINATION IN SQUARE METRES	
J	FACTORS AFFECTING SPILL OR RECOVERY			DESCRIBE ANY ASSISTANCE REQUIRED		HAZARDS TO PERSONS, PROPERTY OR EQUIPMENT	
K	ADDITIONAL INFORMATION, COMMENTS, ACTIONS PROPOSED OR TAKEN TO CONTAIN, RECOVER OR DISPOSE OF SPILLED PRODUCT AND CONTAMINATED MATERIALS						
L	REPORTED TO SPILL LINE BY	POSITION	EMPLOYER	LOCATION CALLING FROM	TELEPHONE		
M	ANY ALTERNATE CONTACT	POSITION	EMPLOYER	ALTERNATE CONTACT LOCATION	ALTERNATE TELEPHONE		
REPORT LINE USE ONLY							
N	RECEIVED AT SPILL LINE BY	POSITION STATION OPERATOR	EMPLOYER	LOCATION CALLED YELLOWKNIFE, NT	REPORT LINE NUMBER (867) 920-8130		
LEAD AGENCY <input type="checkbox"/> EC <input type="checkbox"/> COG <input type="checkbox"/> GNWT <input type="checkbox"/> GN <input type="checkbox"/> ILA <input type="checkbox"/> INAC <input type="checkbox"/> NEB <input type="checkbox"/> TC			SIGNIFICANCE <input type="checkbox"/> MINOR <input type="checkbox"/> MAJOR <input type="checkbox"/> UNKNOWN		FILE STATUS <input type="checkbox"/> OPEN <input type="checkbox"/> CLOSED		
AGENCY		CONTACT NAME		CONTACT TIME		REMARKS	
LEAD AGENCY							
FIRST SUPPORT AGENCY							
SECOND SUPPORT AGENCY							
THIRD SUPPORT AGENCY							

### Instructions for Completing the NT-NU Spill Report Form

This form can be filled out electronically and faxed to the spill line at 867-873-6924. Commencing on January 2, 2007, the form can also be e-mailed as an attachment to [spills@gov.nt.ca](mailto:spills@gov.nt.ca). Until further notice, please verify receipt of e-mail transmissions with a follow-up telephone call. Spills can still be phoned in by calling collect at 867-920-8130.

<b>A. Report Date/Time</b>	The actual date and time that the spill was reported to the spill line. If the spill is phoned in, the Spill Line will fill this out. <b>Please do not fill in the Report Number;</b> the spill line will assign a number after the spill is reported.
<b>B. Occurrence Date/Time</b>	Indicate, to the best of your knowledge, the exact date and time that the spill occurred. Not to be confused with the report date and time (see above).
<b>C. Land Use Permit Number /Water Licence Number</b>	This only needs to be filled in if the activity has been licenced by the Nunavut Water Board and/or if a Land Use Permit has been issued. Applies primarily to mines and mineral exploration sites.
<b>D. Geographic Place Name</b>	In most cases, this will be the name of the city or town in which the spill occurred. For remote locations – outside of human habitations – identify the most prominent geographic feature, such as a lake or mountain and/or the distance and direction from the nearest population center. <b>You must include the geographic coordinates</b> (Refer to Section E).
<b>E. Geographic Coordinates</b>	This only needs to be filled out if the spill occurred outside of an established community such as a mine site. Please note that the location should be stated in degrees, minutes and seconds of Latitude and Longitude.
<b>F. Responsible Party Or Vessel Name</b>	This is the person who was in management/control/ownership of the substance at the time that it was spilled. In the case of a spill from a ship/vessel, include the name of the ship/vessel. Please include full address, telephone number and e-mail. Use box K if there is insufficient space. <b>Please note that, the owner of the spilled substance is ultimately responsible for any spills of that substance, regardless of who may have actually caused the spill.</b>
<b>G. Contractor involved?</b>	Were there any other parties/contractors involved? An example would be a construction company who is undertaking work on behalf of the owner of the spilled substance and who may have contributed to, or directly caused the spill and/or is responding to the spill.
<b>H. Product Spilled</b>	Identify the product spilled; most commonly, it is gasoline, diesel fuel or sewage. For other substances, avoid trade names. Wherever possible, use the chemical name of the substance and further, identify the product using the four digit UN number (eg: UN1203 for gasoline; UN1202 for diesel fuel; UN1863 for Jet A & B)
<b>I. Spill Source</b>	Identify the source of the spill: truck, ship, home heating fuel tank and, if known, the cause (eg: fuel tank overfill, leaking tank; ship ran aground; traffic accident, vandalism, storm, etc.). Provide an estimate of the extent of the contaminated/impacted area (eg: 10 m <sup>2</sup> )
<b>J. Factors Affecting Spill</b>	Any factors which might make it difficult to clean up the spill: rough terrain, bad weather, remote location, lack of equipment. Do you require advice and/or assistance with the cleanup operation? Identify any hazards to persons, property or equipment; for example, a gasoline spill beside a daycare centre would pose a safety hazard to children. Use box K if there is insufficient space.
<b>K. Additional Information</b>	Provide any additional, pertinent details about the spill, such as any peculiar/unique hazards associated with the spilled material. State what action is being taken towards cleaning up the spill; disposal of spilled material; notification of affected parties. If necessary, append additional sheets to the spill report. Number the pages in the same format found in the lower right hand corner of the spill form: eg. "Page 1 of 2", "Page 2 of 2" etc. <b>Please number the pages to ensure that recipients can be certain that they received all pertinent documents.</b> If only the spill report form was filled out, number the form as "Page 1 of 1".
<b>L. Reported to Spill Line by</b>	Include your full name, employer, contact number and the location from which you are reporting the spill. Use box K if there is insufficient space.
<b>M. Alternate Contact</b>	Identify any alternate contacts. This information assists regulatory agencies to obtain additional information if they cannot reach the individual who reported the spill.
<b>N. Report Line Use Only</b>	<b>Leave Blank.</b> This box is for the <b>Spill Line's use only.</b>








## Immediately Reportable Spill Quantities

TDG Class	Substance for NWT 24 Hour Spill Line	Immediately Reportable Quantities
1 2.3 2.4 6.2 7 None	Explosives Compressed gas (toxic) Compressed gas (corrosive) Infectious substances Radioactive Unknown substance	Any amount
2.1 2.2	Compressed gas (flammable) Compressed gas (non-corrosive, non-flammable)	Any amount of gas from containers with a capacity greater than 100 L
3.1 3.2 3.3	Flammable liquids	> 100 L
4.1 4.2 4.3	Flammable solids Spontaneously combustible solids Water reactant	> 25 kg
5.1 9.1	Oxidizing substances Miscellaneous products or substances excluding PCB mixtures	> 50 L or 50 kg
5.2 9.2	Organic peroxides Environmentally hazardous	> 1 L or 1 kg
6.1 8 9.3	Poisonous substances Corrosive substances Dangerous wastes	> 5 L or 5 kg
9.1	PCB mixtures of 5 or more ppm	> 0.5 L or 0.5 kg
None	Other contaminants (e.g. crude oil, drilling fluid, produced water, waste or spent chemicals, used or waste oil, vehicle fluids, waste water, etc.)	> 100 L or 100 kg
None	Sour natural gas (i.e. contains H <sub>2</sub> S) Sweet natural gas	Uncontrolled release or sustained flow of 10 minutes or more

# Material Safety Data Sheets (MSDS) for hazardous materials stored on site



## Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
 	B-3, D-2B	   	

### Section 1. Chemical Product and Company Identification

<b>Product Name</b>	<b>DIESEL FUEL</b>	<b>Code</b>	W104, W293; SAP: 120, 121, 122, 287
<b>Synonym</b>	Seasonal Diesel, #1 Diesel, #2 Heating Oil, #1 Heating Oil, D50, P50, Arctic Diesel, Farm Diesel, Marine Diesel, Low Sulphur Diesel, LSD, Ultra Low Sulphur Diesel, ULSD, Mining Diesel, Naval Distillate, Dyed Diesel, Marked Diesel, Coloured Diesel	<b>Validated on</b>	2/5/2007.
<b>Manufacturer</b>	PETRO-CANADA P.O. Box 2844 150 – 6th Avenue South-West Calgary, Alberta T2P 3E3	<b>In case of Emergency</b>	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
<b>Material Uses</b>	Diesel fuels are distillate fuels suitable for use in high and medium speed internal combustion engines of the compression ignition type. Mining Diesel has a higher flash point requirement, for safe use in underground mines.		

### Section 2. Composition and Information on Ingredients

		Exposure Limits (ACGIH)			
Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	100	Not established	Not established	Not established
Kerosine (petroleum), hydrodesulfurized	64742-81-0		200 mg/m <sup>3</sup>	Not established	Not established
Fuels, diesel	68334-30-5		100 mg/m <sup>3</sup>	Not established	Not established
Fuel oil no. 2	68476-30-2		100 mg/m <sup>3</sup>	Not established	Not established
<b>Manufacturer Recommendation</b>	Avoid prolonged or repeated skin contact to diesel fuels which can lead to dermal irritation and may be associated with an increased risk of skin cancer.				
<b>Other Exposure Limits</b>	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

### Section 3. Hazards Identification.

<b>Potential Health Effects</b>	Combustible liquid. Exercise caution when handling this material. Contact with this product may cause skin and eye irritation. Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death. Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract. For more information refer to Section 11 of this MSDS.
---------------------------------	--

### Section 4. First Aid Measures

<b>Eye Contact</b>	Avoid direct contact. Quickly and gently blot or brush away chemical. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes or until the chemical is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately.
<b>Skin Contact</b>	Avoid direct contact. Wear chemical resistant protective clothing if necessary. Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with warm water and non-abrasive soap for 15-20 minutes or until chemical is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g., watch bands, belts, etc.). Obtain medical attention immediately. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
<b>Inhalation</b>	Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, cardiopulmonary resuscitation (CPR) immediately. Immediately transport victim to an emergency care facility.

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French



<b>DIESEL FUEL</b>		<b>Page Number: 2</b>
<b>Ingestion</b>	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, cardiopulmonary resuscitation (CPR) immediately. Quickly transport victim to an emergency care facility.	
<b>Note to Physician</b>	Not available.	

<b>Section 5. Fire-fighting Measures</b>			
<b>Flammability</b>	Combustible liquid.	<b>Flammable Limits</b>	Lower: 0.7% Upper: 6%
<b>Flash Points</b>	Diesel Fuel: Closed Cup: $\geq 45^{\circ}\text{C}$ (113°F) Marine Diesel Fuel: Closed Cup: $\geq 64^{\circ}\text{C}$ (147°F) Mining Diesel: Closed Cup: $\geq 52^{\circ}\text{C}$ (126°F)	<b>Auto-Ignition Temperature</b>	225°C (437°F)
<b>Fire Hazards in Presence of Various Substances</b>	Flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite.	<b>Explosion Hazards in Presence of Various Substances</b>	Containers may explode in heat of fire. Do not cut, weld, heat, drill or pressurize empty container. Runoff to sewer may create fire or explosion hazard.
<b>Products of Combustion</b>	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), sulphur compounds (H <sub>2</sub> S), smoke and irritating vapours as products of incomplete combustion. See Section 11 (Other Considerations) for information regarding the toxicity of the combustion products.		
<b>Fire Fighting Media and Instructions</b>	<p>NAERG2004, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a moderate flash point above 40°C: Use of water spray when fighting fire may be inefficient.</p> <p>If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.</p> <p>SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.</p> <p>Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.</p>		

<b>Section 6. Accidental Release Measures</b>	
<b>Material Release or Spill</b>	Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Extinguish all ignition sources. Evacuate non-essential personnel. Ventilate area. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Ground and bond all equipment used to clean up the spilled material, as it may be a static accumulator. Avoid contact with spilled material. Avoid breathing vapours or mists of material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately. Ensure clean-up personnel wear appropriate personal protective equipment.

<b>Section 7. Handling and Storage</b>	
<b>Handling</b>	COMBUSTIBLE MATERIAL. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Ensure all equipment is grounded/bonded. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Wear proper personal protective equipment (See Section 8). Avoid confined spaces and areas with poor ventilation. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.
<b>Storage</b>	Store away from heat and sources of ignition. Store in dry, cool, well-ventilated area. Store away from incompatible and reactive materials (See section 5 and 10). Ensure the storage containers are grounded/bonded.

**Section 8. Exposure Controls/Personal Protection**

**Engineering Controls** For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

**Personal Protection** - *The selection of personal protective equipment varies, depending upon conditions of use.*

**Eyes** As a minimum, safety glasses with side shields should be worn when handling this material. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

**Body** If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

**Respiratory** A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

**Hands** If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): nitrile, neoprene, polyvinyl alcohol (PVA), fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

**Feet** Wear appropriate footwear to prevent product from coming in contact with feet and skin.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Bright oily liquid.	<b>Viscosity</b>	1.3 - 4.4 cSt @ 40°C (104°F)
<b>Colour</b>	Clear to yellow / brown (may be dyed for taxation purposes).	<b>Pour Point</b>	Not available.
<b>Odour</b>	Mild petroleum oil like.	<b>Softening Point</b>	Not available.
<b>Odour Threshold</b>	Not available.	<b>Dropping Point</b>	Not available.
<b>Boiling Point</b>	150 to 371°C (302 to 699.8°F)	<b>Penetration</b>	Not available.
<b>Density</b>	0.8 to 0.88 kg/L @ 15°C (59°F)	<b>Oil / Water Dist. Coefficient</b>	Not available.
<b>Vapour Density</b>	4.5 [Air = 1]	<b>Ionicity (in water)</b>	Not available.
<b>Vapour Pressure</b>	1 kPa (7.5 mm Hg) @ 20°C (68°F)	<b>Dispersion Properties</b>	Not available.
<b>Volatility</b>	Semivolatile to volatile.	<b>Solubility</b>	Insoluble in cold water, soluble in non-polar hydrocarbon solvents.

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Not available.		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents and acids.	<b>Decomposition Products</b>	May release COx, NOx, SOx, H2S, smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation and ingestion.
<b>Acute Lethality</b>	<p>Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below:</p> <p><b>Distillates (petroleum), hydrosulfurized middle (64742-80-9):</b> Acute Inhalation toxicity (LC50): 4600 mg/m<sup>3</sup>/4h (rat)</p> <p><b>Kerosine (petroleum), hydrosulfurized (64742-81-0):</b> Acute Oral toxicity (LD50): &gt;5000 mg/kg (rat) Acute Dermal toxicity (LD50): &gt;2000 mg/kg (rabbit) Acute Inhalation toxicity (LC50): &gt;5000 mg/m<sup>3</sup>/4h (rat)</p> <p><b>Fuels, diesel (68334-30-5):</b> Acute Oral toxicity (LD50): 7500 mg/kg (rat) Acute Dermal toxicity (LD50): 24500 mg/kg (mouse)</p>

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

<b>DIESEL FUEL</b>		<b>Page Number: 4</b>	
<b>Fuel oil no. 2 (68476-30-2):</b> Acute Oral toxicity (LD50): 12000 mg/kg (rat)			
<b>Chronic or Other Toxic Effects</b>			
Dermal Route:	This product contains a component (at >= 1%) that can cause skin irritation. Therefore, this product is considered to be a skin irritant. Prolonged or repeated contact may defat and dry skin, and cause dermatitis. (See Other Considerations)		
Inhalation Route:	Inhalation of this product may cause respiratory tract irritation. Inhalation of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.		
Oral Route:	Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract. Ingestion of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.		
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.		
Immunotoxicity:	Not available.		
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.		
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.		
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.		
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.		
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.		
Carcinogenicity (ACGIH):	Considered to be A3 by the ACGIH (Kerosine (petroleum), hydrodesulfurized; Fuels, diesel; Fuel oil no. 2) (See Other Considerations)		
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as group 1, 2A or 2B carcinogens by IARC.		
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.		
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.		
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.		
<b>Other Considerations</b>	Avoid prolonged or repeated skin contact to diesel fuels which can lead to dermal irritation and may be associated with an increased risk of skin cancer. Diesel engine exhaust particulate is probably carcinogenic to humans (IARC Group 2A).		
<b>Section 12. Ecological Information</b>			
<b>Environmental Fate</b>	Not available.	<b>Persistence/Bioaccumulation Potential</b>	Not available.
<b>BOD5 and COD</b>	Not available.	<b>Products of Biodegradation</b>	Not available.
<b>Additional Remarks</b> No additional remark.			









DIESEL FUEL		Page Number: 5																																																	
Section 13. Disposal Considerations																																																			
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.																																																		
Section 14. Transport Information																																																			
TDG Classification	DIESEL FUEL, 3, UN1202, PGIII (CL-TDG)	Special Provisions for Transport	See Transportation of Dangerous Goods Regulations.																																																
Section 15. Regulatory Information																																																			
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).  All components of this formulation are listed on the US EPA-TSCA Inventory.  All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).  This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.  Please contact Product Safety for more information.																																																		
DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	CLASS: Irritating substance. CLASS: Target organ effects. CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).																																																
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	DOT (U.S.A) (Pictograms)	Not evaluated for transport Non évalué pour le transport																																																
HMIS (U.S.A.)	<table><tr><td>Health Hazard</td><td>2*</td></tr><tr><td>Fire Hazard</td><td>2</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>H</td></tr></table>	Health Hazard	2*	Fire Hazard	2	Reactivity	0	Personal Protection	H	NFPA (U.S.A.) <table><tr><td>Health</td><td>2</td><td>2</td><td>0</td><td>Fire Hazard</td></tr><tr><td></td><td>2</td><td>0</td><td></td><td>Reactivity</td></tr><tr><td></td><td></td><td></td><td></td><td>Specific hazard</td></tr></table>	Health	2	2	0	Fire Hazard		2	0		Reactivity					Specific hazard	Rating 0 Insignificant 1 Slight 2 Moderate 3 High 4 Extreme																									
Health Hazard	2*																																																		
Fire Hazard	2																																																		
Reactivity	0																																																		
Personal Protection	H																																																		
Health	2	2	0	Fire Hazard																																															
	2	0		Reactivity																																															
				Specific hazard																																															
Section 16. Other Information																																																			
References	Available upon request. * Marque de commerce de Petro-Canada - Trademark																																																		
Glossary	<table><tr><td>ACGIH - American Conference of Governmental Industrial Hygienists</td><td>HCS - Hazardous Communication System</td></tr><tr><td>ADR - Agreement on Dangerous goods by Road (Europe)</td><td>HMIS - Hazardous Material Information System</td></tr><tr><td>ASTM - American Society for Testing and Materials</td><td>IARC - International Agency for Research on Cancer</td></tr><tr><td>BOD5 - Biological Oxygen Demand in 5 days</td><td>IRIS - Integrated Risk Information System</td></tr><tr><td>CAS - Chemical Abstract Services</td><td>LD50/LC50 - Lethal Dose/Concentration kill 50%</td></tr><tr><td>CEPA - Canadian Environmental Protection Act</td><td>LDLo/LCLo - Lowest Published Lethal Dose/Concentration</td></tr><tr><td>CERCLA - Comprehensive Environmental Response, Compensation and Liability Act</td><td>NFPA - National Fire Prevention Association</td></tr><tr><td>CFR - Code of Federal Regulations</td><td>NIOSH - National Institute for Occupational Safety &amp; Health</td></tr><tr><td>CHIP - Chemical Hazard Information and Packaging Approved Supply List</td><td>NPRI - National Pollutant Release Inventory</td></tr><tr><td></td><td>NSNR - New Substances Notification Regulations (Canada)</td></tr><tr><td>COD - Chemical Oxygen Demand</td><td>NTP - National Toxicology Program</td></tr><tr><td>CPR - Controlled Products Regulations</td><td>OSHA - Occupational Safety &amp; Health Administration</td></tr><tr><td>DOT - Department of Transportation (U.S.A.)</td><td>PEL - Permissible Exposure Limit</td></tr><tr><td>DSCl - Dangerous Substances Classification and Labeling (Europe)</td><td>RCRA - Resource Conservation and Recovery Act</td></tr><tr><td>DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)</td><td>SARA - Superfund Amendments and Reorganization Act</td></tr><tr><td>DSL - Domestic Substance List (Canada)</td><td>STEL - Short Term Exposure Limit (15 minutes)</td></tr><tr><td>EEC/EU - European Economic Community/European Union</td><td>TDG - Transportation Dangerous Goods (Canada)</td></tr><tr><td>EINECS - European Inventory of Existing Commercial Chemical Substances</td><td>TDLo/TCLo - Lowest Published Toxic Dose/Concentration</td></tr><tr><td>EPCRA - Emergency Planning And Community Right-To-Know Act</td><td>TLV-TWA - Threshold Limit Value-Time Weighted Average</td></tr><tr><td>FDA - Food and Drug Administration</td><td>Tlm - Median Tolerance Limit</td></tr><tr><td>FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act</td><td>TSCA - Toxic Substances Control Act</td></tr><tr><td></td><td>USEPA - United States Environmental Protection Agency</td></tr><tr><td></td><td>USP - United States Pharmacopoeia</td></tr><tr><td></td><td>WHMIS - Workplace Hazardous Material Information System</td></tr></table>			ACGIH - American Conference of Governmental Industrial Hygienists	HCS - Hazardous Communication System	ADR - Agreement on Dangerous goods by Road (Europe)	HMIS - Hazardous Material Information System	ASTM - American Society for Testing and Materials	IARC - International Agency for Research on Cancer	BOD5 - Biological Oxygen Demand in 5 days	IRIS - Integrated Risk Information System	CAS - Chemical Abstract Services	LD50/LC50 - Lethal Dose/Concentration kill 50%	CEPA - Canadian Environmental Protection Act	LDLo/LCLo - Lowest Published Lethal Dose/Concentration	CERCLA - Comprehensive Environmental Response, Compensation and Liability Act	NFPA - National Fire Prevention Association	CFR - Code of Federal Regulations	NIOSH - National Institute for Occupational Safety & Health	CHIP - Chemical Hazard Information and Packaging Approved Supply List	NPRI - National Pollutant Release Inventory		NSNR - New Substances Notification Regulations (Canada)	COD - Chemical Oxygen Demand	NTP - National Toxicology Program	CPR - Controlled Products Regulations	OSHA - Occupational Safety & Health Administration	DOT - Department of Transportation (U.S.A.)	PEL - Permissible Exposure Limit	DSCl - Dangerous Substances Classification and Labeling (Europe)	RCRA - Resource Conservation and Recovery Act	DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)	SARA - Superfund Amendments and Reorganization Act	DSL - Domestic Substance List (Canada)	STEL - Short Term Exposure Limit (15 minutes)	EEC/EU - European Economic Community/European Union	TDG - Transportation Dangerous Goods (Canada)	EINECS - European Inventory of Existing Commercial Chemical Substances	TDLo/TCLo - Lowest Published Toxic Dose/Concentration	EPCRA - Emergency Planning And Community Right-To-Know Act	TLV-TWA - Threshold Limit Value-Time Weighted Average	FDA - Food and Drug Administration	Tlm - Median Tolerance Limit	FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act	TSCA - Toxic Substances Control Act		USEPA - United States Environmental Protection Agency		USP - United States Pharmacopoeia		WHMIS - Workplace Hazardous Material Information System
ACGIH - American Conference of Governmental Industrial Hygienists	HCS - Hazardous Communication System																																																		
ADR - Agreement on Dangerous goods by Road (Europe)	HMIS - Hazardous Material Information System																																																		
ASTM - American Society for Testing and Materials	IARC - International Agency for Research on Cancer																																																		
BOD5 - Biological Oxygen Demand in 5 days	IRIS - Integrated Risk Information System																																																		
CAS - Chemical Abstract Services	LD50/LC50 - Lethal Dose/Concentration kill 50%																																																		
CEPA - Canadian Environmental Protection Act	LDLo/LCLo - Lowest Published Lethal Dose/Concentration																																																		
CERCLA - Comprehensive Environmental Response, Compensation and Liability Act	NFPA - National Fire Prevention Association																																																		
CFR - Code of Federal Regulations	NIOSH - National Institute for Occupational Safety & Health																																																		
CHIP - Chemical Hazard Information and Packaging Approved Supply List	NPRI - National Pollutant Release Inventory																																																		
	NSNR - New Substances Notification Regulations (Canada)																																																		
COD - Chemical Oxygen Demand	NTP - National Toxicology Program																																																		
CPR - Controlled Products Regulations	OSHA - Occupational Safety & Health Administration																																																		
DOT - Department of Transportation (U.S.A.)	PEL - Permissible Exposure Limit																																																		
DSCl - Dangerous Substances Classification and Labeling (Europe)	RCRA - Resource Conservation and Recovery Act																																																		
DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)	SARA - Superfund Amendments and Reorganization Act																																																		
DSL - Domestic Substance List (Canada)	STEL - Short Term Exposure Limit (15 minutes)																																																		
EEC/EU - European Economic Community/European Union	TDG - Transportation Dangerous Goods (Canada)																																																		
EINECS - European Inventory of Existing Commercial Chemical Substances	TDLo/TCLo - Lowest Published Toxic Dose/Concentration																																																		
EPCRA - Emergency Planning And Community Right-To-Know Act	TLV-TWA - Threshold Limit Value-Time Weighted Average																																																		
FDA - Food and Drug Administration	Tlm - Median Tolerance Limit																																																		
FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act	TSCA - Toxic Substances Control Act																																																		
	USEPA - United States Environmental Protection Agency																																																		
	USP - United States Pharmacopoeia																																																		
	WHMIS - Workplace Hazardous Material Information System																																																		
For Copy of MSDS	Prepared by Product Safety - JDW on 2/5/2007.																																																		
Continued on Next Page		Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>																																																	
		Available in French																																																	

DIESEL FUEL		Page Number: 6
Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>		Data entry by Product Safety - JDW.
Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228		
For Product Safety Information: (905) 804-4752		
<i>To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</i>		



## Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
 	<b>B-2, D-2A, D-2B</b>	  	

Section 1. Chemical Product and Company Identification			
Product Name	<b>JET B AVIATION TURBINE FUEL</b>		Code W219 SAP: 150, 151, 152
Synonym	Jet B; Jet B DI; JP-4; Jet F-40; NATO F-40; Turbine Fuel, Aviation, Wide Cut Type (Can/CGSB-3.22).		Validated on 9/28/2007.
Manufacturer	PETRO-CANADA P.O. Box 2844 150 – 6th Avenue South-West Calgary, Alberta T2P 3E3		In case of Emergency Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Used as aviation turbine fuel. May contain a fuel system icing inhibitor.		

Section 2. Composition and Information on Ingredients					
			Exposure Limits (ACGIH)		
Name	CAS #	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Complex mixture of petroleum hydrocarbons (C6-C14).	64741-41-9	60-100	Not established	Not established	Not established
Benzene	71-43-2	0.1-0.5	0.5 ppm	2.5 ppm	Not established
Fuel System Icing Inhibitor (FSII) (if added*): Diethylene Glycol Monomethyl Ether	111-77-3	0.1-0.15	Not established	Not established	Not established
Anti-static, antioxidant, corrosion inhibitor and metal deactivator additives. * Please note that Jet B DI, JP-4, Jet F-40 and NATO F-40 all contain Fuel System Icing Inhibitor (FSII).corrosion inhibitor	Not applicable	<0.1	Not applicable	Not applicable	Not applicable
Manufacturer Recommendation	Not applicable				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

Section 3. Hazards Identification.	
Potential Health Effects	Flammable liquid. Exercise caution when handling this material. May cause cancer. May cause teratogenicity/embryotoxicity. Contact with this product may cause skin irritation. Inhalation of vapours can cause irritation of the respiratory tract and CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconsciousness and possibly death. Aspiration into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure. For more information refer to Section 11 of this MSDS.

Section 4. First Aid Measures	
Eye Contact	Avoid direct contact. Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin Contact	As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). Avoid direct contact. Wear chemical protective clothing if necessary. Quickly and gently, blot or brush away excess chemical. Immediately wash with lukewarm, gently flowing water and non-abrasive soap for 15-20 minutes. Immediately obtain medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

JET B AVIATION TURBINE FUEL		Page Number: 2
<b>Ingestion</b>	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. Have victim rinse mouth with water again. If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.	
<b>Note to Physician</b>	Not available	

Section 5. Fire-fighting Measures			
<b>Flammability</b>	Flammable liquid (NFPA).	<b>Flammable Limits</b>	LOWER: 1.3% UPPER: 8% (NFPA)
<b>Flash Points</b>	CLOSED CUP: -31°C (-24°F) (NFPA)	<b>Auto-Ignition Temperature</b>	240°C (464°F) (NFPA)
<b>Fire Hazards in Presence of Various Substances</b>	Flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.		
<b>Products of Combustion</b>	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.		
<b>Fire Fighting Media and Instructions</b>	<p>NAERG2004, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a very low flash point. Use of water spray when fighting fire may be inefficient.</p> <p>If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.</p> <p>SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk.</p> <p>Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles.</p> <p>Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.</p>		

Section 6. Accidental Release Measures	
<b>Material Release or Spill</b>	IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Evacuate non-essential personnel. Extinguish all ignition sources. Ventilate area. Avoid breathing vapours or mists of material. Stop leak if safe to do so. Dike spilled material. Avoid contact with spilled material. Do not allow spilled material to enter sewer systems as vapours may accumulate and may cause an explosion/fire hazard. If spilled in a confined space, ensure appropriate confined space entry protocols are followed. Ensure clean-up personnel wear appropriate personal protective equipment. Use appropriate inert absorbent material to absorb spilled product. Do not use paper or other flammable materials to absorb product. Collect used absorbent for later disposal. Do not allow spilled materials to come into contact with incompatible materials (see Section 10). Ground and bond all equipment used to clean up the spilled material, as it may be a static accumulator. Notify appropriate authorities immediately.

Section 7. Handling and Storage	
<b>Handling</b>	FLAMMABLE MATERIAL. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid inhalation of product vapours or mists. Avoid skin contact. Avoid eye contact. Wear proper personal protective equipment (See Section 8). Ensure all equipment is grounded/bonded. Do not ingest this product. Avoid generating mists. Avoid confined spaces and areas with poor ventilation. Avoid contact with any incompatible or reactive materials. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product.
<b>Storage</b>	Store away from heat and sources of ignition. Store away from incompatible and reactive materials (See section 5 and 10). Ensure the storage containers are grounded/bonded. Keep container tightly closed. Store in dry, cool, well-ventilated area.

**Section 8. Exposure Controls/Personal Protection**

<b>Engineering Controls</b>	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.
<b>Personal Protection</b>	<i>- The selection of personal protective equipment varies, depending upon conditions of use.</i>
<b>Eyes</b>	As a minimum, safety glasses with side shields should be worn when handling this material.
<b>Body</b>	If this material may come into contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information).
<b>Respiratory</b>	A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.
<b>Hands</b>	If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): polyvinyl alcohol (PVA), and fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
<b>Feet</b>	Wear appropriate footwear to prevent product from coming in contact with feet and skin.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Clear liquid.	<b>Viscosity</b>	Not available (similar to Gasoline)
<b>Colour</b>	Clear and colourless.	<b>Pour Point</b>	Freezing point: <-51°C(<-60°F) for all types of Jet B including F40.
<b>Odour</b>	Gasoline like.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	50 to 270°C (122 to 518°F)	<b>Penetration</b>	Not applicable.
<b>Density</b>	0.75 to 0.80 kg/L @ 15°C (59°F).	<b>Oil / Water Dist. Coefficient</b>	Not available
<b>Vapour Density</b>	3.5 (Air = 1)	<b>Ionicity (in water)</b>	Not available
<b>Vapour Pressure</b>	21 kPa (158 mmHg) @ 37.8°C (100°F).	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	Volatile.	<b>Solubility</b>	Insoluble in water. Partially miscible in some alcohols. Miscible in other petroleum solvents.

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Not available		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents, diborane, and halogen compounds.	<b>Decomposition Products</b>	May release COx, NOx, SOx, aldehydes, ketones, smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation and ingestion.
<b>Acute Lethality</b>	Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below:  <u>Benzene (71-43-2):</u> Acute oral toxicity (LD50): 930 mg/kg (rat). Acute dermal toxicity (LD50): >9400 mg/kg (rabbit). Acute inhalation toxicity (LC50): 13200 ppm/4h (rat).  <u>Diethylene Glycol Monomethyl Ether (111-77-3):</u> Acute oral toxicity (LD50): 4140-5180 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >50000 mg/m³/4h (rat).

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French








JET B AVIATION TURBINE FUEL		Page Number: 5																				
<b>Section 14. Transport Information</b>																						
<b>TDG Classification</b>	FUEL, AVIATION, TURBINE ENGINE, 3, UN1863, PGII (CL-TDG)	<b>Special Provisions for Transport</b>	See Transportation of Dangerous Goods Regulations.																			
<b>Section 15. Regulatory Information</b>																						
<b>Other Regulations</b>	<p>This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).</p> <p>All components of this formulation are listed on the US EPA-TSCA Inventory.</p> <p>All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).</p> <p>This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.</p> <p>Please contact Product Safety for more information.</p>																					
<b>DSD/DPD (Europe)</b>	Not evaluated.	<b>HCS (U.S.A.)</b>	HCS Class: Flammable liquid having a flash point lower than 37.8°C (100°F). HCS Class: May cause cancer. HCS Class: Target organ effects. HCS Class: Irritating substance.																			
<b>ADR (Europe) (Pictograms)</b>	NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	<b>DOT (U.S.A) (Pictograms)</b>	Not evaluated for transport Non évalué pour le transport																			
<b>HMIS (U.S.A.)</b>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 33%; padding: 2px;">Health Hazard</td> <td style="width: 10%; text-align: center; padding: 2px;">2*</td> <td rowspan="4" style="width: 10%; text-align: center; vertical-align: middle;">           NFPA (U.S.A.)  <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center; margin-right: 5px;">             Health 2           </div> <div style="text-align: center; margin-right: 5px;">             Fire Hazard 3           </div> <div style="text-align: center;">             Reactivity 0           </div> </div> </td> <td style="width: 10%; text-align: center; padding: 2px;">Rating</td> <td style="width: 37%; padding: 2px;">0 Insignificant</td> </tr> <tr> <td style="padding: 2px;">Fire Hazard</td> <td style="text-align: center; padding: 2px;">3</td> <td style="padding: 2px;">1 Slight</td> </tr> <tr> <td style="padding: 2px;">Reactivity</td> <td style="text-align: center; padding: 2px;">0</td> <td style="padding: 2px;">2 Moderate</td> </tr> <tr> <td style="padding: 2px;">Personal Protection</td> <td style="text-align: center; padding: 2px;">H</td> <td style="padding: 2px;">3 High</td> </tr> <tr> <td colspan="3"></td> <td></td> <td style="padding: 2px;">4 Extreme</td> </tr> </table>			Health Hazard	2*	NFPA (U.S.A.) <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center; margin-right: 5px;">             Health 2           </div> <div style="text-align: center; margin-right: 5px;">             Fire Hazard 3           </div> <div style="text-align: center;">             Reactivity 0           </div> </div>	Rating	0 Insignificant	Fire Hazard	3	1 Slight	Reactivity	0	2 Moderate	Personal Protection	H	3 High					4 Extreme
Health Hazard	2*	NFPA (U.S.A.) <div style="display: flex; align-items: center; justify-content: center;"> <div style="text-align: center; margin-right: 5px;">             Health 2           </div> <div style="text-align: center; margin-right: 5px;">             Fire Hazard 3           </div> <div style="text-align: center;">             Reactivity 0           </div> </div>	Rating	0 Insignificant																		
Fire Hazard	3		1 Slight																			
Reactivity	0		2 Moderate																			
Personal Protection	H		3 High																			
				4 Extreme																		
<b>Section 16. Other Information</b>																						
<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark																					
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; border: none;"> <b>Glossary</b>            ACGIH - American Conference of Governmental Industrial Hygienists            ADR - Agreement on Dangerous goods by Road (Europe)            ASTM - American Society for Testing and Materials            BOD5 - Biological Oxygen Demand in 5 days            CAS - Chemical Abstract Services            CEPA - Canadian Environmental Protection Act            CERCLA - Comprehensive Environmental Response, Compensation and Liability Act            CFR - Code of Federal Regulations            CHIP - Chemical Hazard Information and Packaging Approved Supply List            COD - Chemical Oxygen Demand            CPR - Controlled Products Regulations            DOT - Department of Transportation (U.S.A.)            DSCl - Dangerous Substances Classification and Labeling (Europe)            DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)            DSL - Domestic Substance List (Canada)            EEC/EU - European Economic Community/European Union            EINECS - European Inventory of Existing Commercial Chemical Substances            EPCRA - Emergency Planning And Community Right-To-Know Act            FDA - Food and Drug Administration            FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act         </td> <td style="width: 50%; vertical-align: top; border: none;">           HCS - Hazardous Communication System            HMIS - Hazardous Material Information System            IARC - International Agency for Research on Cancer            IRIS - Integrated Risk Information System            LD50/LC50 - Lethal Dose/Concentration kill 50%            LDLo/LCLo - Lowest Published Lethal Dose/Concentration            NFPA - National Fire Prevention Association            NIOSH - National Institute for Occupational Safety &amp; Health            NPRI - National Pollutant Release Inventory            NSNR - New Substances Notification Regulations (Canada)            NTP - National Toxicology Program            OSHA - Occupational Safety &amp; Health Administration            PEL - Permissible Exposure Limit            RCRA - Resource Conservation and Recovery Act            SARA - Superfund Amendments and Reorganization Act            STEL - Short Term Exposure Limit (15 minutes)            TDG - Transportation Dangerous Goods (Canada)            TDLo/TCLo - Lowest Published Toxic Dose/Concentration            TLV-TWA - Threshold Limit Value-Time Weighted Average            Tlm - Median Tolerance Limit            TSCA - Toxic Substances Control Act            USEPA - United States Environmental Protection Agency            USP - United States Pharmacopoeia            WHMIS - Workplace Hazardous Material Information System         </td> </tr> </table>				<b>Glossary</b> ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemical Hazard Information and Packaging Approved Supply List COD - Chemical Oxygen Demand CPR - Controlled Products Regulations DOT - Department of Transportation (U.S.A.) DSCl - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List (Canada) EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning And Community Right-To-Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act	HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLV-TWA - Threshold Limit Value-Time Weighted Average Tlm - Median Tolerance Limit TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System																	
<b>Glossary</b> ACGIH - American Conference of Governmental Industrial Hygienists ADR - Agreement on Dangerous goods by Road (Europe) ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days CAS - Chemical Abstract Services CEPA - Canadian Environmental Protection Act CERCLA - Comprehensive Environmental Response, Compensation and Liability Act CFR - Code of Federal Regulations CHIP - Chemical Hazard Information and Packaging Approved Supply List COD - Chemical Oxygen Demand CPR - Controlled Products Regulations DOT - Department of Transportation (U.S.A.) DSCl - Dangerous Substances Classification and Labeling (Europe) DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe) DSL - Domestic Substance List (Canada) EEC/EU - European Economic Community/European Union EINECS - European Inventory of Existing Commercial Chemical Substances EPCRA - Emergency Planning And Community Right-To-Know Act FDA - Food and Drug Administration FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act	HCS - Hazardous Communication System HMIS - Hazardous Material Information System IARC - International Agency for Research on Cancer IRIS - Integrated Risk Information System LD50/LC50 - Lethal Dose/Concentration kill 50% LDLo/LCLo - Lowest Published Lethal Dose/Concentration NFPA - National Fire Prevention Association NIOSH - National Institute for Occupational Safety & Health NPRI - National Pollutant Release Inventory NSNR - New Substances Notification Regulations (Canada) NTP - National Toxicology Program OSHA - Occupational Safety & Health Administration PEL - Permissible Exposure Limit RCRA - Resource Conservation and Recovery Act SARA - Superfund Amendments and Reorganization Act STEL - Short Term Exposure Limit (15 minutes) TDG - Transportation Dangerous Goods (Canada) TDLo/TCLo - Lowest Published Toxic Dose/Concentration TLV-TWA - Threshold Limit Value-Time Weighted Average Tlm - Median Tolerance Limit TSCA - Toxic Substances Control Act USEPA - United States Environmental Protection Agency USP - United States Pharmacopoeia WHMIS - Workplace Hazardous Material Information System																					
<b>For Copy of MSDS</b> Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>  Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228  For Product Safety Information: (905) 804-4752		Prepared by Product Safety - RS on 9/28/2007. Data entry by Product Safety - DSR.																				
Continued on Next Page		Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>																				
Available in French																						

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*



# Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	A, B-1		

Section 1. Chemical Product and Company Identification			
Product Name		PROPANE	
Synonym		Propane HD-5, Propane commercial, Liquefied Petroleum Gas (LPG), C3H8, CGSB Propane Grade 1, CGSB Propane Grade 2, odourized propane, stench propane, automotive propane.	
Manufacturer		PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	
Material Uses		Propane is used as a fuel gas, refrigerant, automotive fuel and as a raw material for organic synthesis. The grade determines the propane content. It is supplied as pressurized liquid in tanks.	
		Code	W222 SAP: 169
		Validated on	9/28/2006.
		In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).

Section 2. Composition and Information on Ingredients					
Name	CAS #	% (V/V)	Exposure Limits (ACGIH)		
			TLV-TWA(8 h)	STEL	CEILING
HD-5 Propane	74-98-6	>90	1000 ppm	Not established	Not established
Propane	115-07-1	<5	500 ppm	Not established	Not established
Propene					
Commercial Propane	74-98-6	>75	1000 ppm	Not established	Not established
Propane	115-07-1	<20	500 ppm	Not established	Not established
Propene					
Both grades may contain:					
Ethane	74-84-0	<6	1000 ppm	Not established	Not established
Butane +	106-97-8	<5	1000 ppm	Not established	Not established
<b>Manufacturer Recommendation</b>	At high concentrations, can displace oxygen and cause asphyxiation. A minimum requirement of 19.5% of oxygen at sea level (148 torr O <sub>2</sub> , dry air) is recommended.				
<b>Other Exposure Limits</b>	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

Section 3. Hazards Identification.	
<b>Potential Health Effects</b>	The product is contained under pressure. Do not puncture, incinerate or heat container as contents may explode. Flammable gas. Exercise caution when handling this material. At high concentrations, can displace oxygen and cause asphyxiation. A minimum requirement of 19.5% of oxygen at sea level (148 torr O <sub>2</sub> , dry air) is recommended. Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death. Contact with gas or liquified gas may cause burns and frostbite. Ingestion is not an applicable route of exposure for gases. For more information refer to Section 11 of this MSDS.

Section 4. First Aid Measures	
<b>Eye Contact</b>	No effects expected. If irritation does occur, remove source of contamination or move victim to fresh air. If irritation persists, obtain medical advice. If frostbite has occurred, quickly remove victim from source of contamination. Immediately and briefly, flush with lukewarm, gently flowing water. DO NOT attempt to rewarm. Cover both eyes with a sterile dressing. DO NOT allow victim to drink alcohol or smoke. Quickly transport victim to an emergency care facility.
<b>Skin Contact</b>	As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). No health effects expected. If irritation does occur, flush with lukewarm, gently flowing water for 5 minutes. If irritation persists, obtain medical advice. If frostbite has occurred, quickly remove victim from source of contamination and briefly flush with lukewarm, gently flowing water. DO NOT attempt to rewarm the affected area on site. DO NOT rub area or apply direct heat. Gently remove clothing or jewellery that may restrict circulation. Carefully cut around any clothing that sticks to the skin, and remove the rest of the garment. Loosely cover the affected area with a sterile dressing. DO NOT allow victim to drink alcohol or smoke. Quickly transport victim to an emergency care facility.

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

PROPANE		Page Number: 2	
Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.		
Ingestion	Ingestion is not an applicable route of exposure for gases.		
Note to Physician	Not available		
Section 5. Fire-fighting Measures			
Flammability	Class I - flammable gas (NFPA).	Flammable Limits	Lower: 2.1%; Upper: 9.5%, (NFPA).
Flash Points	CLOSED CUP: -104°C (-155°F).	Auto-Ignition Temperature	450°C (842°F), (NFPA).
Fire Hazards in Presence of Various Substances	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. Rapid escape of vapours may generate static charge causing ignition. May accumulate in confined spaces.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire. Vapour explosion hazard indoors, outdoors or in sewers. Propane may form explosive mixtures with air.
Products of Combustion	Carbon oxides (CO, CO2), acrid smoke and irritating vapours as products of incomplete combustion.		
Fire Fighting Media and Instructions	NAERG2004, GUIDE 115, Flammable Gas: CAUTION: This product has a low flash point, use of water spray when fighting fire may be inefficient. SMALL FIRE: Use DRY chemicals, CO2, water spray or foam. LARGE FIRE: Use water spray, fog or foam. DO NOT use water jet. If tank, rail car or tank truck is involved in a fire, ISOLATE for 1600 meters (1 mile) in all directions; also, consider initial evacuation for 1600 meters (1 mile) in all directions. DO NOT extinguish a leaking gas flame unless leak can be stopped. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Self-contained breathing apparatus (SCBA) will be required if approaching the fire from downwind, or to enter enclosed areas or buildings. Handle damaged cylinders with extreme care.		
Section 6. Accidental Release Measures			
Material Release or Spill	IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Notify appropriate authorities immediately. Evacuate non-essential personnel. Stop leak if safe to do so. Avoid contact with spilled material. Avoid breathing vapours or mists of material. Ventilate area. Ensure clean-up personnel wear appropriate personal protective equipment.		
Section 7. Handling and Storage			
Handling	EXTREMELY FLAMMABLE GAS. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Ensure all equipment is grounded/bonded. Avoid confined spaces and areas with poor ventilation. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours. Wear proper personal protective equipment (See Section 8). Rapid escape of vapour may generate static charge causing ignition. Use spark-proof electrical equipment. Do not allow escaping compressed gas or liquid to come in contact with skin or eyes as it can cause frostbite. SPECIAL PRECAUTIONS: Sludges and tank scale from propane storage tanks, trucks and rail cars, and filters/screens may contain naturally occurring radioactive material ("NORM") in the form of lead 210. Similarly, equipment used for the transfer of propane such as product pipelines, pumps and compressors, may have detectable levels of radioactive lead 210 on inner surfaces. Workers involved in cleaning, repair or other maintenance on inner surfaces of such equipment should avoid breathing dust generated from such activities. Suitable codes of practice should be developed for these activities, detailing appropriate occupational hygiene and disposal practices.		
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Store away from heat and sources of ignition. Store as flammable material. Compressed gases should be stored in a separate safety storage cabinet or room. Avoid direct sunlight. Keep container tightly closed. Store in dry, cool, well-ventilated area. Ensure the storage containers are grounded/bonded.		
Section 8. Exposure Controls/Personal Protection			
Engineering Controls	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.		
Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.			
Eyes	As a minimum, safety glasses with side shields should be worn when handling this material.		
Body	If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)		
Respiratory	Always wear NIOSH-approved self-contained breathing apparatus when handling this material.		
Continued on Next Page		Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>	
		Available in French	



PROPANE

Page Number: 3

**Hands** Wear appropriate chemically protective gloves. Wear insulated gloves to prevent frostbite.

**Feet** Wear appropriate footwear to prevent product from coming in contact with feet and skin.

**Section 9. Physical and Chemical Properties**

<b>Physical State and Appearance</b>	Gas at room temperature; liquid when stored under pressure.	<b>Viscosity</b>	Not applicable
<b>Colour</b>	Colourless.	<b>Pour Point</b>	Not applicable.
<b>Odour</b>	Propane is an odourless gas. Odourized propane will contain up to 28 g ethyl mercaptan per 1000 L of propane.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Odour is not an adequate warning to prevent overexposure to propane. Prolonged exposure to mercaptans can cause olfactory desensitization.	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	-42°C (-44°F)	<b>Penetration</b>	Not applicable.
<b>Density</b>	508 kg/m <sup>3</sup> @ 15°C (59°F)	<b>Oil / Water Dist. Coefficient</b>	Not available
<b>Vapour Density</b>	1.56 (air=1)	<b>Ionicity (in water)</b>	Not available
<b>Vapour Pressure</b>	10763 mmHg (1435 kPa) @ 38°C (100°F)	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	Volatile	<b>Solubility</b>	Slightly soluble in water.

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Not available		
<b>Stability</b>	The product is stable under normal handling and storage conditions.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents and halogenated compounds.	<b>Decomposition Products</b>	May release CO <sub>x</sub> , acrid smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Inhalation, skin contact and eye contact.
<b>Acute Lethality</b>	Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below:  <u>Propene (115-07-1):</u> Acute inhalation toxicity (LC50): >50000 ppm/4h (rat).  <u>Butane (106-97-8):</u> Acute inhalation toxicity (LC50): 276000 ppm/4h (rat).
<b>Chronic or Other Toxic Effects</b>	
Dermal Route:	Contact with gas or liquefied gas may cause burns and frostbite to the skin.
Inhalation Route:	At high concentrations, can displace oxygen and cause asphyxiation. A minimum requirement of 19.5% of oxygen at sea level (148 torr O <sub>2</sub> , dry air) is recommended. Inhalation of this product may cause respiratory tract irritation. Inhalation of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.
Oral Route:	Ingestion is not an applicable route of exposure for gases.
Eye Irritation/Inflammation:	Contact with gas or liquefied gas may cause burns and frostbite to the eyes.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

PROPANE		Page Number: 4
Reproductive Toxicity:	This product is not known to contain any components at $\geq 0.1\%$ that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.	
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at $\geq 0.1\%$ that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.	
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at reportable quantities that are listed as Group A1 or A2 carcinogens by ACGIH.	
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.	
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.	
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.	
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.	
Other Considerations	No additional remark.	

Section 12. Ecological Information			
Environmental Fate	Not available	Persistence/Bioaccumulation Potential	Not available
BOD5 and COD	Not available	Products of Biodegradation	Not available
Additional Remarks No additional remark.			

Section 13. Disposal Considerations	
Waste Disposal	Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.

Section 14. Transport Information			
TDG Classification	PROPANE, 2.1, UN1978 (CL-TDG)	Special Provisions for Transport	See Transportation of Dangerous Goods Regulations.

Section 15. Regulatory Information																																
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).																															
	All components of this formulation are listed on the US EPA-TSCA Inventory.																															
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).																															
	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.																															
Please contact Product Safety for more information.																																
DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	HCS Class: Flammable gas.																													
ADR (Europe) (Pictograms)	NOT EVALUATED FOR EUROPEAN TRANSPORT  NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	DOT (U.S.A) (Pictograms)	Not evaluated for transport  Non évalué pour le transport																													
HMIS (U.S.A.)	<table><tr><td>Health Hazard</td><td>1*</td></tr><tr><td>Fire Hazard</td><td>4</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>K</td></tr></table>	Health Hazard	1*	Fire Hazard	4	Reactivity	0	Personal Protection	K	<table><tr><td>NFPA (U.S.A.)</td><td><table><tr><td>4</td><td>Fire Hazard</td></tr><tr><td>1</td><td>Reactivity</td></tr><tr><td>0</td><td>Specific hazard</td></tr></table></td><td>Rating</td><td>0 Insignificant</td></tr><tr><td>Health</td><td></td><td>1 Slight</td></tr><tr><td></td><td></td><td>2 Moderate</td></tr><tr><td></td><td></td><td>3 High</td></tr><tr><td></td><td></td><td>4 Extreme</td></tr></table>	NFPA (U.S.A.)	<table><tr><td>4</td><td>Fire Hazard</td></tr><tr><td>1</td><td>Reactivity</td></tr><tr><td>0</td><td>Specific hazard</td></tr></table>	4	Fire Hazard	1	Reactivity	0	Specific hazard	Rating	0 Insignificant	Health		1 Slight			2 Moderate			3 High			4 Extreme
Health Hazard	1*																															
Fire Hazard	4																															
Reactivity	0																															
Personal Protection	K																															
NFPA (U.S.A.)	<table><tr><td>4</td><td>Fire Hazard</td></tr><tr><td>1</td><td>Reactivity</td></tr><tr><td>0</td><td>Specific hazard</td></tr></table>	4	Fire Hazard	1	Reactivity	0	Specific hazard	Rating	0 Insignificant																							
4	Fire Hazard																															
1	Reactivity																															
0	Specific hazard																															
Health		1 Slight																														
		2 Moderate																														
		3 High																														
		4 Extreme																														

**Section 16. Other Information**

**References** Available upon request.  
\* Marque de commerce de Petro-Canada - Trademark

**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists	HCS - Hazardous Communication System
ADR - Agreement on Dangerous goods by Road (Europe)	HMIS - Hazardous Material Information System
ASTM - American Society for Testing and Materials	IARC - International Agency for Research on Cancer
BOD5 - Biological Oxygen Demand in 5 days	IRIS - Integrated Risk Information System
CAS - Chemical Abstract Services	LD50/LC50 - Lethal Dose/Concentration kill 50%
CEPA - Canadian Environmental Protection Act	LDLo/LCLo - Lowest Published Lethal Dose/Concentration
CERCLA - Comprehensive Environmental Response, Compensation and Liability Act	NFPA - National Fire Prevention Association
CFR - Code of Federal Regulations	NIOSH - National Institute for Occupational Safety & Health
CHIP - Chemical Hazard Information and Packaging Approved Supply List	NPRI - National Pollutant Release Inventory
COD - Chemical Oxygen Demand	NSNR - New Substances Notification Regulations (Canada)
CPR - Controlled Products Regulations	NTP - National Toxicology Program
DOT - Department of Transportation (U.S.A.)	OSHA - Occupational Safety & Health Administration
DSCL - Dangerous Substances Classification and Labeling (Europe)	PEL - Permissible Exposure Limit
DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)	RCRA - Resource Conservation and Recovery Act
DSL - Domestic Substance List (Canada)	SARA - Superfund Amendments and Reorganization Act
EEC/EU - European Economic Community/European Union	STEL - Short Term Exposure Limit (15 minutes)
EINECS - European Inventory of Existing Commercial Chemical Substances	TDG - Transportation Dangerous Goods (Canada)
EPCRA - Emergency Planning And Community Right-To-Know Act	TDLo/TCLo - Lowest Published Toxic Dose/Concentration
FDA - Food and Drug Administration	TLV-TWA - Threshold Limit Value-Time Weighted Average
FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act	Tm - Median Tolerance Limit
	TSCA - Toxic Substances Control Act
	USEPA - United States Environmental Protection Agency
	USP - United States Pharmacopoeia
	WH-MIS - Workplace Hazardous Material Information System

**For Copy of MSDS**Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752








Prepared by Product Safety - JDW on 9/28/2006.

Data entry by Product Safety - DSR.

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*



# Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
 	B-2, D-2A, D-2B	   	

Section 1. Chemical Product and Company Identification					
Product Name		GASOLINE, UNLEADED		Code	W102E
Synonym		Regular, Unleaded Gasoline (US Grade), Mid-Grade, Plus, Super, WinterGas, SummerGas, Supreme, SuperClean WinterGas, RegularClean, PlusClean, Premium, marked or dyed gasoline, Super Premium (94 RO), TORUL, transitional quality regular unleaded, BOB, Blendstock for Oxygenate Blending		Validated on	7/4/2005.
Manufacturer		PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3		In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses		Unleaded gasoline is used in spark ignition engines including motor vehicles, inboard and outboard boat engines, small engines such as chain saws and lawn mowers, and recreational vehicles.			

Section 2. Composition and Information on Ingredients					
			Exposure Limits (ACGIH)		
Name	CAS #	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Gasoline	8006-61-9	85-100	300 ppm	500 ppm	Not established
Methyl tert-butyl ether	1634-04-4	0-15	50 ppm	Not established	Not established
Benzene	71-43-2	<1.5	0.5 ppm	2.5 ppm	Not established
Note: Petro-Canada does not use MTBE in the manufacturing of its gasoline, however MTBE can be introduced from time to time through the use of external gasoline blendstocks.					
Manufacturer	Not applicable				
Recommendation					
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

Section 3. Hazards Identification.	
Potential Health Effects	Flammable liquid. Exercise caution when handling this material. May cause cancer. May cause heritable genetic effects (mutagenicity). This product contains an ingredient or ingredients, which have been shown to cause chronic toxic effects. Contact with this product may cause skin and eye irritation. Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death. Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract. For more information refer to Section 11 of this MSDS.

Section 4. First Aid Measures	
Eye Contact	Avoid direct contact. Quickly and gently blot or brush away chemical. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes or until the chemical is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately.
Skin Contact	Avoid direct contact. Wear chemical resistant protective clothing if necessary. Quickly and gently, blot or brush away excess chemical. Wash gently and thoroughly with warm water and non-abrasive soap for 15-20 minutes or until chemical is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g., watch bands, belts, etc.). Obtain medical attention immediately. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, cardiopulmonary resuscitation (CPR) immediately. Immediately transport victim to an emergency care facility.

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

<b>GASOLINE, UNLEADED</b>		<b>Page Number: 2</b>
<b>Ingestion</b>	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Repeat administration of water. If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, cardiopulmonary resuscitation (CPR) immediately. Quickly transport victim to an emergency care facility.	
<b>Note to Physician</b>	Not available	

<b>Section 5. Fire-fighting Measures</b>			
<b>Flammability</b>	Flammable liquid (NFPA).		<b>Flammable Limits</b> Lower: 1.3%; Upper: 7.6% (NFPA).
<b>Flash Points</b>	Closed Cup: -50 to -38°C (-58 to -36°F), ASTM D56 Standard Test Method for Flash Point by Tag Closed Tester.		<b>Auto-Ignition Temperature</b> 257°C (495°F) (NFPA).
<b>Fire Hazards in Presence of Various Substances</b>	Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. Rapid escape of vapour may generate static charge causing ignition. May accumulate in confined spaces.		<b>Explosion Hazards in Presence of Various Substances</b> Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire. Vapours may form explosive mixtures with air.
<b>Products of Combustion</b>	Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), polynuclear aromatic hydrocarbons, phenols, smoke and irritating vapours as products of incomplete combustion.  See Section 11 (Other Considerations) for information regarding the toxicity of the combustion products.		
<b>Fire Fighting Media and Instructions</b>	NAERG2004 GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a very low flash point. Use of water spray when fighting fire may be inefficient. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. SMALL FIRES: Dry chemical, CO <sub>2</sub> , water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.		

<b>Section 6. Accidental Release Measures</b>	
<b>Material Release or Spill</b>	IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Evacuate non-essential personnel. Ventilate area. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Ensure clean-up personnel wear appropriate personal protective equipment. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Avoid breathing vapours or mists of material. Ground and bond all equipment used to clean up the spilled material, as it may be a static accumulator. Notify appropriate authorities immediately.

<b>Section 7. Handling and Storage</b>	
<b>Handling</b>	FLAMMABLE MATERIAL. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Wear proper personal protective equipment (See Section 8). Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Ensure all equipment is grounded/bonded. Avoid confined spaces and areas with poor ventilation. Do not ingest this product.
<b>Storage</b>	Store as flammable material. Store away from incompatible and reactive materials (See section 5 and 10). Store away from heat and sources of ignition. Store in dry, cool, well-ventilated area. Keep container tightly closed. Ensure the storage containers are grounded/bonded. Avoid direct sunlight.



GASOLINE, UNLEADED

Page Number: 3

Section 8. Exposure Controls/Personal Protection

Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

Personal Protection

The selection of personal protective equipment varies, depending upon conditions of use.

Eyes

As a minimum, safety glasses with side shields should be worn when handling this material.

Body

If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory

A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hands

If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): polyvinyl alcohol (PVA), fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns.

Feet

Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties

Physical State and Appearance

Clear liquid.

Viscosity

Not available.

Colour

Clear to slightly yellow, undyed liquid. May be dyed red for taxation purposes.

Pour Point

Not applicable.

Odour

Gasoline. MTBE has a terpene-like odour.

Softening Point

Not applicable.

Odour Threshold

Less than 1 ppm.

Dropping Point

Not applicable.

Boiling Point

25 to 220°C (77 to 428°F) Initial boiling point by ASTM D86 Standard Test Method.

Penetration

Not applicable.

Density

0.685 - 0.80 kg/L @ 15°C (59°F).

Oil / Water Dist. Coefficient

Not available

Vapour Density

3 to 4 (Air = 1) (NFPA).

Ionicity (in water)

Not available

Vapour Pressure

<107 kPa @ 37.8°C (100°F)

Dispersion Properties

Not available

Volatility

Volatile.

Solubility

Hydrocarbon components virtually insoluble in water. Soluble in alcohol, ether, chloroform, and benzene. Dissolves fats, oils and natural resins.

Section 10. Stability and Reactivity

Corrosivity

Non corrosive.

Stability

The product is stable under normal handling and storage conditions.

Hazardous Polymerization

Will not occur under normal working conditions.

Incompatible Substances / Conditions to Avoid

Reactive with oxidizing agents, acids, interhalogens and uranium hexafluoride.

Decomposition Products

May release COx, NOx, phenols, polynuclear aromatic hydrocarbons, acrid smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information

Routes of Entry

Skin contact, eye contact, inhalation, and ingestion.

Acute Lethality

Gasoline (8006-61-9):

Acute Oral toxicity (LD50): 13600 mg/kg (rat)

Acute Dermal toxicity (LD50): >5000 mg/kg (rabbit)

MTBE (1634-04-4):

Acute Oral toxicity (LD50): 2963 mg/kg (rat)

Acute Dermal toxicity (LD50): >6800 mg/kg (rabbit)

Acute Inhalation toxicity (LC50): 23576 ppm/4h (rat)

Benzene (71-43-2):

Continued on Next Page

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Available in French

GASOLINE, UNLEADED

Page Number: 4

Acute Oral toxicity (LD50): 930 mg/kg (rat)

Acute Dermal toxicity (LD50): >9400 mg/kg (rabbit)

Acute Inhalation toxicity (LC50): 13229 ppm/4h (rat)

Chronic or Other Toxic Effects

Dermal Route:

Contact may cause skin irritation. Prolonged or repeated contact may defat and dry skin, and cause dermatitis.

Inhalation Route:

Inhalation of this product may cause respiratory tract irritation. Inhalation of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.

Oral Route:

Ingestion of this product may cause gastro-intestinal irritation. Aspiration of this product may result in severe irritation or burns to the respiratory tract. Ingestion of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.

Eye Irritation/Inflammation:

Contact may cause eye irritation.

Immunotoxicity:

Not available

Skin Sensitization:

Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.

Respiratory Tract Sensitization:

Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.

Mutagenic:

This product contains a component(s) at >= 0.1% that has been shown to cause mutagenicity in laboratory tests. Therefore, this product is considered to be a mutagen. (Benzene)

Reproductive Toxicity:

This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.

Teratogenicity/Embryotoxicity:

This product is not known to contain any components at >= 0.1% that have been shown to cause teratogenicity and/or embryotoxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a teratogen/embryotoxin.

Carcinogenicity (ACGIH):

This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic.

[Considered to be A1 by the ACGIH. Benzene (71-43-2)]

[Considered to be A3 by the ACGIH. Gasoline (8006-61-9), MTBE (1634-04-4)]

Carcinogenicity (IARC):

This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic.

[Considered to be carcinogenic to humans (group 1) by IARC. Benzene (71-43-2)]

[Considered to be carcinogenic to humans (group 2B) by IARC. Gasoline (8006-61-9)]

Carcinogenicity (NTP):

This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic.

[Known to be a human carcinogen according to NTP. Benzene (71-43-2)]

Carcinogenicity (IRIS):

This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic.

[Considered to be carcinogenic by IRIS. Benzene (71-43-2)]

Carcinogenicity (OSHA):

This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic.

[Considered to be carcinogenic by OSHA. Benzene (71-43-2)]

Other Considerations

Gasoline engine exhaust is possibly carcinogenic to humans (IARC Group 2B).

Section 12. Ecological Information

Environmental Fate

Not available

Persistence/Bioaccumulation Potential

Not available

BOD5 and COD

Not available

Products of Biodegradation

Not available

Additional Remarks

No additional remark.

<b>GASOLINE, UNLEADED</b>		<b>Page Number: 5</b>									
<b>Section 13. Disposal Considerations</b>											
<b>Waste Disposal</b>	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.										
<b>Section 14. Transport Information</b>											
<b>TDG Classification</b>	GASOLINE, 3, UN1203, PGII (CL-TDG)	<b>Special Provisions for Transport</b>	See Transportation of Dangerous Goods Regulations.								
<b>Section 15. Regulatory Information</b>											
<b>Other Regulations</b>	<p>This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).</p> <p>All components of this formulation are listed on the US EPA-TSCA Inventory.</p> <p>All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).</p> <p>This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.</p> <p>Please contact Product Safety for more information.</p>										
<b>DSD/DPD (Europe)</b>	Not evaluated.	<b>HCS (U.S.A.)</b>	CLASS: Contains material which may cause cancer. CLASS: Flammable liquid having a flash point lower than 37.8°C (100°F). CLASS: Irritating substance. CLASS: Target organ effects.								
<b>ADR (Europe) (Pictograms)</b>	NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.	<b>DOT (U.S.A) (Pictograms)</b>	Not evaluated for transport Non évalué pour le transport								
<b>HMIS (U.S.A.)</b>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">Health Hazard</td> <td style="width: 50%; text-align: center;">(2+)</td> </tr> <tr> <td>Fire Hazard</td> <td style="text-align: center;">(3)</td> </tr> <tr> <td>Reactivity</td> <td style="text-align: center;">(0)</td> </tr> <tr> <td>Personal Protection</td> <td style="text-align: center;">(H)</td> </tr> </table>	Health Hazard	(2+)	Fire Hazard	(3)	Reactivity	(0)	Personal Protection	(H)	<b>NFPA (U.S.A.)</b> <div style="display: flex; align-items: center; justify-content: center;"> <div style="margin-right: 10px;">Health</div> <div style="border: 1px solid black; padding: 5px; text-align: center;"> <div style="display: flex; justify-content: space-between; width: 100%;"> <span>3</span> <span>Fire Hazard</span> </div> <div style="display: flex; justify-content: space-between; width: 100%;"> <span>2</span> <span>Reactivity</span> </div> <div style="display: flex; justify-content: space-between; width: 100%;"> <span>0</span> <span>Specific hazard</span> </div> </div> </div>	<b>Rating</b> 0 Insignificant 1 Slight 2 Moderate 3 High 4 Extreme
Health Hazard	(2+)										
Fire Hazard	(3)										
Reactivity	(0)										
Personal Protection	(H)										
<b>Section 16. Other Information</b>											
<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark										
<b>Glossary</b> <div style="display: flex; flex-wrap: wrap;"> <div style="width: 50%;">           ACGIH - American Conference of Governmental Industrial Hygienists            ADR - Agreement on Dangerous goods by Road (Europe)            ASTM - American Society for Testing and Materials            BOD5 - Biological Oxygen Demand in 5 days            CAS - Chemical Abstract Services            CEPA - Canadian Environmental Protection Act            CERCLA - Comprehensive Environmental Response, Compensation and Liability Act            CFR - Code of Federal Regulations            CHIP - Chemical Hazard Information and Packaging Approved Supply List            COD - Chemical Oxygen Demand            CPR - Controlled Products Regulations            DOT - Department of Transportation (U.S.A.)            DSCCL - Dangerous Substances Classification and Labeling (Europe)            DSD/DPD - Dangerous Substance or Dangerous Preparations Directives (Europe)            DSL - Domestic Substance List (Canada)            EEC/EU - European Economic Community/European Union            EINECS - European Inventory of Existing Commercial Chemical Substances            EPCRA - Emergency Planning And Community Right-To-Know Act            FDA - Food and Drug Administration            FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act         </div> <div style="width: 50%;">           HCS - Hazardous Communication System            HMIS - Hazardous Material Information System            IARC - International Agency for Research on Cancer            IRIS - Integrated Risk Information System            LD50/LC50 - Lethal Dose/Concentration kill 50%            LDLo/LCLo - Lowest Published Lethal Dose/Concentration            NFPA - National Fire Prevention Association            NIOSH - National Institute for Occupational Safety &amp; Health            NPRI - National Pollutant Release Inventory            NSNR - New Substances Notification Regulations (Canada)            NTP - National Toxicology Program            OSHA - Occupational Safety &amp; Health Administration            PEL - Permissible Exposure Limit            RCRA - Resource Conservation and Recovery Act            SARA - Superfund Amendments and Reorganization Act            STEL - Short Term Exposure Limit (15 minutes)            TDG - Transportation Dangerous Goods (Canada)            TDLo/TCLo - Lowest Published Toxic Dose/Concentration            TLV-TWA - Threshold Limit Value-Time Weighted Average            TLM - Median Tolerance Limit            TSCA - Toxic Substances Control Act            USEPA - United States Environmental Protection Agency            USP - United States Pharmacopoeia            WHMIS - Workplace Hazardous Material Information System         </div> </div>											
<b>For Copy of MSDS</b>		<b>Prepared by Product Safety - JDW on 7/4/2005.</b>									
Continued on Next Page		Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a> Available in French									

GASOLINE, UNLEADED		Page Number: 6
Internet: <a href="http://www.petro-canada.ca/msds">www.petro-canada.ca/msds</a>		Data entry by Product Safety - JDW.
Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228		
For Product Safety Information: (905) 804-4752		
<p><i>To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.</i></p>		