

train prepare prevent respond

The Rain Drain[™] will continuously filter out rain water while containing hydrocarbons.



Berm Filtration System



Rain Drain™

Enabling your secondary containment berm to contain minor leaks or spills of hazardous materials, the RainDrain will continuously filter out rain water while containing hydrocarbons.

Features

- > Filters rainwater down to 10 PPM in compliance with EPA regulation 40CFR112.7
- > Go-no-go filtration system will automatically stop the discharge of water when full of hydrocarbons eliminating the need for monitoring
- > Easy installation within minutes
- > Includes a ball valve with sight glass to examine liquid levels & content
- > Rugged anodized aluminum filter casing
- > Discharge end molded cap with 3/8" discharge port
- > Feed end molded cap with 3/4" camlock inlet
- > Replacement filter media kits available in packages of 6

Specifications

	Large	Small
Capacity	4.8 USG 16.65 L	2.2 USG 8.32 L
Flow Rate	2.5 - 3.5 USGPM	2 - 3 USGPM

Components

- > Filter casing with molded caps and camlock inlet
- >1 Pre-packaged spare filter media kit with used
- > cartridge disposal bag
- > Ball valve with hose and sightglass
- >8 foot chemical hose
- > Bulkhead fitting for the berm



> go to > call