

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
(A) (T)	B-2, D-2A, D-2B		

Section 1. C	hemical Product and Company Identification		
Product Name	JET B AVIATION TURBINE FUEL	Code	W219 SAP: 150, 151, 152
Synonym	Jet B; Jet B DI; JP-4; Jet F-40; NATO F-40; Turbine Fuel, Aviation, Wide Cut Type (Can/CGSB-3.22).	Validated of	on 9/28/2007.
Manufacturer	PETRO-CANADA P.O. Box 2844 150 – 6th Avenue South-West Calgary, Alberta T2P 3E3	In case of Emergency	Canutec Transportation: 613-996-6666 Poison Control Centre:
Material Uses	Used as aviation turbine fuel. May contain a fuel system icing inhibitor.		Consult local telephone directory for emergency number(s).

Section 2. Com	position and Information o	on Ingredien	its	Fyn	osure Limits (ACGIH)	
	Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Complex mixture of p C14). Benzene	petroleum hydrocarbons (C6-	64741-41-9 71-43-2	60-100 0.1-0.5	Not established 0.5 ppm	Not established 2.5 ppm	Not established Not
Fuel System Icing Inhibitor (FSII) (if added*): Diethylene Glycol Monomethyl Ether		111-77-3	0.1-0.15	Not established	Not	established Not
Anti-static, antioxidant, corrosion inhibitor and metal deactivator additives. * Please note that Jet B DI, JP-4, Jet F-40 and NATO F-40 all contain Fuel System Icing Inhibitor (FSII).corrosion inhibitor		Not applicable	<0.1	Not applicable	established Not applicable	established Not applicable
Manufacturer Recommendation	Not applicable	1	1		1	1
Other Exposure Limits	Consult local, state, provincial	or territory au	thorities for a	acceptable exposure	limits.	

Section 3. Hazards Identification.

Potential Health Effects Flammable liquid. Exercise caution when handling this material. May cause cancer. May cause teratogenicity/embryotoxicity. Contact with this product may cause skin irritation. Inhalation of vapours can cause irritation of the respiratory tract and CNS depression with symptoms of nausea, headaches, vomiting, dizziness, fatigue, light-headedness, reduced coordination, unconciousness and possibly death. Aspiration into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure. For more information refer to Section 11 of this MSDS.

Section 4. Fi	rst Aid Measures
Eye Contact	Avoid direct contact. Quickly and gently blot or brush chemical off the face. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open. If a contact lens is present, DO NOT delay irrigation or attempt to remove the lens. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately obtain medical attention.
Skin Contact	As quickly as possible, remove contaminated clothing, shoes and leather goods (e.g., watchbands, belts, etc.). Avoid direct contact. Wear chemical protective clothing if necessary. Quickly and gently, blot or brush away excess chemical. Immediately wash with lukewarm, gently flowing water and non-abrasive soap for 15-20 minutes. Immediately obtain medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Inhalation	Take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate protective equipment). If breathing has stopped, trained personnel should begin artificial respiration (AR) or, if the heart has stopped, immediately start cardiopulmonary resuscitation (CPR) or automated external defibrillation (AED). Quickly transport victim to an emergency care facility.
Continued on Nex	Page Internet: www.petro-canada.ca/msds Available in French

JET B AVIATION TUR	RBINE FUEL	Page Number: 2
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMI mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs reduce risk of aspiration. Repeat administration of water. Have victi breathing has stopped, trained personnel should begin artificial respiration immediately start cardiopulmonary resuscitation (CPR) or automated e transport victim to an emergency care facility.	ITING. Have victim drink 240 to 300 naturally, have victim lean forward to m rinse mouth with water again. If on (AR) or, if the heart has stopped,
Note to Physician	Not available	·

Section 5. Fire-	fighting Measures		
Flammability	Flammable liquid (NFPA).	Flammable Limits	LOWER: 1.3% UPPER: 8% (NFPA)
Flash Points	CLOSED CUP: -31°C (-24°F) (NFPA)	Auto-Ignition Temperature	240°C (464°F) (NFPA)
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.		
Fire Fighting Media and Instructions	NAERG2004, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a very low flash point: Use of water spray when fighting fire may be inefficient. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. SMALL FIRES: Dry chemical, CO2, water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks.		
	For massive fire, use unmanned hose holders let fire burn. Wear positive pressure self-c protective clothing will only provide limited pro	ontained breathing	

Section 6. Accidental Release Measures

Material Release or Spill

IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Evacuate non-essential personnel. Extinguish all ignition sources. Ventilate area. Avoid breathing vapours or mists of material. Stop leak if safe to do so. Dike spilled material. Avoid contact with spilled material. Do not allow spilled material to enter sewer systems as vapours may accumulate and may cause an explosion/fire hazard. If spilled in a confined space, ensure appropriate confined space entry protocols are followed. Ensure clean-up personnel wear appropriate personal protective equipment. Use appropriate inert absorbent material to absorb spilled product. Do not use paper or other flammable materials to absorb product. Collect used absorbent for later disposal. Do not allow spilled materials to come into to contact with incompatible materials (see Section 10). Ground and bond all equipment used to clean up the spilled material, as it may be a static accumulator. Notify appropriate authorities immediately.

Section 7. Hand	dling and Storage
Handling	FLAMMABLE MATERIAL. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid inhalation of product vapours or mists. Avoid skin contact. Avoid eye contact. Wear proper personal protective equipment (See Section 8). Ensure all equipment is grounded/bonded. Do not ingest this product. Avoid generating mists. Avoid confined spaces and areas with poor ventilation. Avoid contact with any incompatible or reactive materials. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product.
Storage	Store away from heat and sources of ignition. Store away from incompatible and reactive materials (See section 5 and 10). Ensure the storage containers are grounded/bonded. Keep container tightly closed. Store in dry, cool, well-ventilated area.

JET B AVIATION TURBINE FUEL Page Number: 3

Section 8. Exposure Controls/Personal Protection

Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station

Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.

Eyes As a minimum, safety glasses with side shields should be worn when handling this material.

Body If this material may come into contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information).

Respiratory A NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): polyvinyl alcohol (PVA), and fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Phy	sical and Chemical Properties		
Physical State and Appearance	Clear liquid.	Viscosity	Not available (similar to Gasoline)
Colour	Clear and colourless.	Pour Point	Freezing point: <-51°C(<-60°F) for all types of Jet B including F40.
Odour	Gasoline like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	50 to 270°C (122 to 518°F)	Penetration	Not applicable.
Density	0.75 to 0.80 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not available
Vapour Density	3.5 (Air = 1)	Ionicity (in water)	Not available
Vapour Pressure	21 kPa (158 mmHg) @ 37.8°C (100°F).	Dispersion Properties	; Not available
Volatility	Volatile.	Solubility	Insoluble in water. Partially miscible in some alcohols. Miscible in other petroleum solvents.

Section 10. Stal	oility and Reactivity		
Corrosivity	Not available		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents, diborane, and halogen compounds.	Decomposition Products	May release COx, NOx, SOx, aldehydes, ketones, smoke and irritating vapours when heated to decomposition.

Section 11. Toxico	ological Information
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below:
	Benzene (71-43-2): Acute oral toxicity (LD50): 930 mg/kg (rat). Acute dermal toxicity (LD50): >9400 mg/kg (rabbit). Acute inhalation toxicity (LC50): 13200 ppm/4h (rat).
	<u>Diethylene Glycol Monomethyl Ether (111-77-3):</u> Acute oral toxicity (LD50): 4140-5180 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >50000 mg/m³/4h (rat).

Continued on Next Page Internet: www.petro-canada.ca/msds Available in French

JET B AVIATION TURBINE FUEL	Page Number: 4
Chronic or Other Toxic Effect	ts
Dermal Route:	This product contains a component (at >= 1%) that can cause skin irritation. Therefore, this product is considered to be a skin irritant. Prolonged or repeated contact may defat and dry skin, and cause dermatitis.
Inhalation Route:	Ingestion of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs).
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	Benzene is tumorigenic by RTECS criteria.
Reproductive Toxicity:	This product is not known to contain any components at >= 0.1% that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product contains a component(s) at >= 0.1% that has been shown to cause teratogenicity and/or embryotoxicity in laboratory tests. Therefore, this product is considered to be a teratogen/embryotoxin [Diethylene Glycol Monomethyl Ether].
Carcinogenicity (ACGIH):	This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic. (Considered to be A1 by the ACGIH. Benzene, 71-43-2)
Carcinogenicity (IARC):	This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic. (Considered to be carcinogenic to humans (group 1) by IARC. Benzene, 71-43-2)
Carcinogenicity (NTP):	This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic. (Known to be a human carcinogen according to NTP. Benzene, 71-43-2)
Carcinogenicity (IRIS):	This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic. (Considered to be carcinogenic by IRIS. Benzene, 71-43-2)
Carcinogenicity (OSHA):	This product contains the following chemical(s) at >=0.1% that are listed as carcinogenic compounds. Therefore this product is considered to be carcinogenic. (Considered to be carcinogenic by OSHA. Benzene, 71-43-2)

Section 12. Ed	cological Information			
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available	
BOD5 and COD	Not available	Products of Biodegradation	Not available	

Section 13. Disposal Considerations			
Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.		

No additional remark.

Other Considerations

JET B AVIATION TURBINE FUEL Page Number: 5

Section 14. Transport Information

TDG Classification FUEL, AVIATION, TURBINE ENGINE, 3,

UN1863, PGII (CL-TDG)

Special Provisions for Transport

See Transportation of Dangerous Goods

Regulations.

Section 15. Regulatory Information

Other Regulations This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).

All components of this formulation are listed on the US EPA-TSCA Inventory.

All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

Please contact Product Safety for more information.

DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	HCS Class: Flammable liquid having a flash point lower than 37.8°C (100°F). HCS Class: May cause cancer. HCS Class: Target organ effects. HCS Class: Irritating substance.
ADR (Europe) (Pictograms)	EUROPEAN IRANSPORT	DOT (U.S.A) (Pictograms)	Not evaluated for transport
	NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.		Non évalué pour le transport

HMIS (U.S.A.)

Health Hazard	2*
Fire Hazard	3
Reactivity	0
Personal Protection	H

NFPA (U.S.A.)

Health 2 0 Reactivity

Specific hazard

Rating 0 Insignificant

- 1 Slight
- 2 Moderate3 High
- 4 Extreme

Section 16. Other Information

References

Available upon request.

* Marque de commerce de Petro-Canada - Trademark

Glossarv

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe)

ASTM - American Society for Testing and Materials

BOD5 - Biological Oxygen Demand in 5 days

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation

and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemical Hazard Information and Packaging Approved Supply

List

COD - Chemical Oxygen Demand

CPR - Controlled Products Regulations

DOT - Department of Transportation (U.S.A.)

DSCL - Dangerous Substances Classification and Labeling (Europe)
DSD/DPD - Dangerous Substance or Dangerous Preparations

Directives (Europe)

DSL - Domestic Substance List (Canada)

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical

Substances

EPCRA - Emergency Planning And Community Right-To-Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide, and Rodenticide Act

HCS - Hazardous Communication System

HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health

NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reorganization Act

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLV-TWA - Threshold Limit Value-Time Weighted Average

TLm - Median Tolerance Limit

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

For Copy of MSDS

Internet: www.petro-canada.ca/msds

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - RS on 9/28/2007.

Data entry by Product Safety - DSR.

Continued on Next Page

Internet: www.petro-canada.ca/msds

Available in French

JET B AVIATION TURBINE FUEL Page Number: 6

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.