

Material Safety Data Sheet


PROPANE



1. Product and company identification

Product name	: PROPANE
Synonym	: Propane HD-5, Propane commercial, Liquified Petroleum Gas (LPG), C3H8, CGSB Propane Grade 1, CGSB Propane Grade 2, odourized propane, stench propane, automotive propane.
Code	: W222
Material uses	: Propane is used as a fuel gas, refrigerant and as a raw material for organic synthesis. It is also used as a laboratory gas. The grade determines the propane content. It is supplied as pressurized liquid in tanks.
Manufacturer	: PETRO-CANADA P.O. Box 2844 150 – 6th Avenue South-West Calgary, Alberta T2P 3E3
<u>In case of emergency</u>	: Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).

2. Hazards identification

Physical state	: Gas at room temperature; liquid when stored under pressure.
Odour	: Propane is an odourless gas. Odourized propane will contain up to 28 g Ethyl Mercaptan per 1000 L of propane.
WHMIS (Canada)	:  Class A: Compressed gas. Class B-1: Flammable gas.
OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Emergency overview	: CAUTION! EXTREMELY FLAMMABLE GAS. MAY CAUSE FLASH FIRE. HIGH PRESSURE GAS. Contains gas under pressure. Extremely flammable gas. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Keep away from heat, sparks and flame. Do not puncture or incinerate container. Avoid breathing gas. Avoid contact with skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. At high concentrations, this product can displace oxygen and cause asphyxiation therefore a minimum requirement of 19.5 % oxygen at sea level is recommended.
Routes of entry	: Dermal contact. Eye contact. Inhalation.
<u>Potential acute health effects</u>	
Inhalation	: Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death.
Ingestion	: As this product is a gas, refer to the inhalation section.
Skin	: Contact with rapidly expanding gas may cause burns or frostbite.
Eyes	: Contact with rapidly expanding gas may cause burns or frostbite.
<u>Potential chronic health effects</u>	
Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: Not listed as carcinogenic by OSHA, NTP or IARC.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 1/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.

PROPANE	Page Number: 2										
2. Hazards identification											
Developmental effects Fertility effects Medical conditions aggravated by over-exposure	: No known significant effects or critical hazards. : No known significant effects or critical hazards. : Overexposure may lead to cardiac sensitization.										
See toxicological information (Section 11)											
3. Composition/information on ingredients											
Name Propane Propene Butane Ethane	<table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>CAS number</u></th> <th style="text-align: left;"><u>%</u></th> </tr> </thead> <tbody> <tr> <td>74-98-6</td> <td>90 - 100</td> </tr> <tr> <td>115-07-1</td> <td>1 - 5</td> </tr> <tr> <td>106-97-8</td> <td>1 - 5</td> </tr> <tr> <td>74-84-0</td> <td>1 - 2.5</td> </tr> </tbody> </table>	<u>CAS number</u>	<u>%</u>	74-98-6	90 - 100	115-07-1	1 - 5	106-97-8	1 - 5	74-84-0	1 - 2.5
<u>CAS number</u>	<u>%</u>										
74-98-6	90 - 100										
115-07-1	1 - 5										
106-97-8	1 - 5										
74-84-0	1 - 2.5										
There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.											
4. First-aid measures											
Eye contact Skin contact Inhalation Ingestion Protection of first-aiders Notes to physician	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately. : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. To avoid the risk of static discharges and gas ignition, soak contaminated clothing thoroughly with water before removing it. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately. : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately. : As this product is a gas, refer to the inhalation section. : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.										
5. Fire-fighting measures											
Flammability of the product Extinguishing media Suitable Not suitable Special exposure hazards Products of combustion Special protective equipment for fire-fighters	: Class I - flammable gas (NFPA). : Use an extinguishing agent suitable for the surrounding fire. : None known. : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. If involved in fire, shut off flow immediately if it can be done without risk. If this is impossible, withdraw from area and allow fire to burn. Fight fire from protected location or maximum possible distance. : Carbon oxides (CO, CO ₂), smoke and irritating vapours as products of incomplete combustion. : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.										
Date of issue : 3/30/2012. Internet: www.petro-canada.ca/msds Page: 2/7 Petro-Canada is a Suncor Energy business TM Trademark of Suncor Energy Inc. Used under licence.											

PROPANE

Page Number: 3

5 . Fire-fighting measures

Special remarks on fire hazards

Extremely flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. Rapid escape of vapour may generate static charge causing ignition. May accumulate in confined spaces.

Special remarks on explosion hazards

Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Containers may explode in heat of fire. Vapour explosion hazard indoors, outdoors or in sewers. Propane may form explosive mixtures with air.

6 . Accidental release measures

Personal precautions

Accidental releases pose a serious fire or explosion hazard. Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment.

Large spill

Immediately contact emergency personnel. Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7 . Handling and storage

Handling

Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container. Ensure all equipment is grounded/bonded.

SPECIAL PRECAUTIONS: Sludges and tank scale from petroleum storage tanks, trucks, rail cars, and filters/screens may contain naturally occurring radioactive material ("NORM") in the form of radon 226 and it's progeny including lead 210. Similarly, equipment used for the transfer of petroleum product such as pipelines, pumps and compressors, may have detectable levels of radioactive lead on inner surfaces. Workers involved in cleaning, descaling, repair or other maintenance on inner surfaces of such equipment should avoid breathing and ingesting of dust generated from such activities. Similarly, gas freeing of pipelines, pumps, vessels and compressors may put workers at risk of inhalation of radon gas. Suitable codes of practice should be developed for these activities, detailing appropriate occupational hygiene, personal protective equipment and disposal practices.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Eliminate all ignition sources. Keep container tightly closed and sealed until ready for use. Ensure the storage containers are grounded/bonded.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 3/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.

PROPANE	Page Number: 4
----------------	-----------------------

8 . Exposure controls/personal protection

Ingredient	Exposure limits
Propane	ACGIH TLV (United States). TWA: 1000 ppm 8 hour(s).
Propene	ACGIH TLV (United States). TWA: 500 ppm 8 hour(s).
Butane	ACGIH TLV (United States). TWA: 1000 ppm 8 hour(s).
Ethane	ACGIH TLV (United States). TWA: 1000 ppm 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: NIOSH-approved self-contained breathing apparatus.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Recommended: Wear insulated gloves to prevent frostbite.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state	: Gas at room temperature; liquid when stored under pressure.
Flash point	: Closed cup: -104°C (-155.2°F)
Auto-ignition temperature	: 450°C (842°F) (NFPA)
Flammable limits	: Lower: 2.1% (NFPA) Upper: 9.5% (NFPA)
Colour	: Colourless.
Odour	: Propane is an odourless gas. Odourized propane will contain up to 28 g Ethyl Mercaptan per 1000 L of propane.
Odour threshold	: Not available.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 4/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.

PROPANE

Page Number: 5

9 . Physical and chemical properties

pH	: Not available.
Boiling/condensation point	: -42°C (-43.6°F)
Melting/freezing point	: Not available.
Relative density	: Not available.
Vapour pressure	: 1434.9 kPa (10763 mm Hg) @ 38°C (100°F)
Vapour density	: 1.56 [Air = 1]
Volatility	: Volatile.
Evaporation rate	: Not available.
Viscosity	: Not available.
Pour point	: Not available.
Solubility	: Not available.

10 . Stability and reactivity

Chemical stability	: The product is stable.
Hazardous polymerisation	: Under normal conditions of storage and use, hazardous polymerisation will not occur.
Materials to avoid	: Reactive with oxidising agents and halogenated compounds.
Hazardous decomposition products	: May release COx, smoke and irritating vapours when heated to decomposition.

11 . Toxicological informationAcute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butane	LC50 Inhalation Gas.	Rat	658000 mg/m ³	4 hours

Conclusion/Summary : Not available.

Chronic toxicity

Conclusion/Summary : Not available.

Irritation/Corrosion

Conclusion/Summary : Not available.

Sensitiser

Conclusion/Summary : Not available.

Carcinogenicity

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Propene	A4	3	-	-	-	-

Mutagenicity

Conclusion/Summary : Not available.

Teratogenicity

Conclusion/Summary : Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 5/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.

PROPANE

Page Number: 6


12 . Ecological information**Environmental effects** : No known significant effects or critical hazards.**Aquatic ecotoxicity****Conclusion/Summary** : Not available.**Biodegradability****Conclusion/Summary** : Not available.**13 . Disposal considerations**

Waste disposal : The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Empty pressure vessels should be returned to the supplier. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN1978	PROPANE	2.1	-		-
DOT Classification	Not available.	Not available.	Not available.	-		-

PG* : Packing group

15 . Regulatory information**United States**

HCS Classification : Compressed gas
Flammable gas

Canada

WHMIS (Canada) : Class A: Compressed gas.
Class B-1: Flammable gas.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

Canada inventory : All components are listed or exempted.

United States inventory (TSCA 8b) : All components are listed or exempted.

Europe inventory : All components are listed or exempted.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 6/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.

PROPANE

Page Number: 7

16 . Other information

Label requirements : EXTREMELY FLAMMABLE GAS, MAY CAUSE FLASH FIRE, HIGH PRESSURE GAS.

**Hazardous Material
Information System (U.S.A.)** :

Health	2
Flammability	4
Physical hazards	2
Personal protection	K

**National Fire Protection
Association (U.S.A.)** :

**References**

: Available upon request.
™ Trademark of Suncor Energy Inc. Used under licence.

Date of printing

: 10/24/2013.

Date of issue

: 30 March 2012

Date of previous issue

: 3/31/2009.

Responsible name: **Product Safety - DSR**

✔ Indicates information that has changed from previously issued version.

For Copy of (M)SDS: Internet: www.petro-canada.ca/msds

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue : 3/30/2012.

Internet: www.petro-canada.ca/msds

Page: 7/7

Petro-Canada is a Suncor Energy business

™ Trademark of Suncor Energy Inc. Used under licence.



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 1 of 8

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: MOBILUX EP 2
Product Description: Base Oil and Additives
MSDS Number: 6482
Product Code: 2015A0208050
Intended Use: Grease

COMPANY IDENTIFICATION

Supplier: Imperial Oil Downstream
240 4th Avenue
Calgary, ALBERTA: T2P 3M9 Canada
24 Hour Environmental / Health Emergency: 1-866-232-9563
Telephone:
Transportation Emergency Phone Number: 1-866-232-9563
Product Technical Information: 1-800-268-3183
Supplier General Contact: 1-800-567-3776

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

No Reportable Hazardous Substance(s) or Complex Substance(s).

SECTION 3 HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines see Section 15.

HEALTH EFFECTS

Excessive exposure may result in eye, skin, or respiratory irritation. High-pressure injection under skin may cause serious damage.

NFPA Hazard ID:	Health: 0	Flammability: 1	Reactivity: 0
HMIS Hazard ID:	Health: 0	Flammability: 1	Reactivity: 0

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 4 FIRST AID MEASURES

INHALATION

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 2 of 8

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Aldehydes, Oxides of carbon, Smoke, Fume, Sulphur oxides, Incomplete combustion products

FLAMMABILITY PROPERTIES

Flash Point [Method]: >204°C (400°F) [EST. FOR OIL, ASTM D-92 (COC)]

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/D

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 3 of 8

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

SPILL MANAGEMENT

Land Spill: Allow spilled material to solidify and shovel it up into a suitable container for recycle or disposal. Scrape up spilled material with shovels into a suitable container for recycle or disposal.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7

HANDLING AND STORAGE

HANDLING

Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

STORAGE

Do not store in open or unlabelled containers.

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.

Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications.



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 4 of 8

handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practise good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Solid
Form: Semi-fluid
Colour: Brown
Odour: Characteristic
Odour Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 0.92
Flash Point [Method]: >204°C (400°F) [EST. FOR OIL, ASTM D-92 (COO)]



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 5 of 8

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
Autoignition Temperature: N/D
Boiling Point / Range: > 316°C (600°F)
Vapour Density (Air = 1): N/D
Vapour Pressure: < 0.013 kPa (0.1 mm Hg) at 20°C
Evaporation Rate (n-butyl acetate = 1): N/D
pH: N/A
Log Pow (n-Octanol/Water Partition Coefficient): > 3.5
Solubility in Water: Negligible
Viscosity: 150 cSt (150 mm²/sec) at 40°C
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: N/D
DMSO Extract (mineral oil only), IP-346: < 3 %wt
Decomposition Temperature: N/D

NOTE: Most physical properties above are for the oil component in the material.

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Route of Exposure	Conclusion / Remarks
Inhalation	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
Eye	
Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.



Product Name: MOBILUX EP 2
 Revision Date: 22 Jan 2015
 Page 6 of 8

CHRONIC/OTHER EFFECTS

Contains:

Base oil severely refined; Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

CMR Status:

Chemical Name	CAS Number	List Citations
SOLVENT DEWAXED RESIDUAL OIL (PETROLEUM)	647 42-62-7	1, 6

--REGULATORY LISTS SEARCHED--

1 = IARC 1
 2 = IARC 2A

3 = IARC 2B
 4 = ACGIH ALL

5 = ACGIH A1
 6 = ACGIH A2

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land
 Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component -- Expected to be inherently biodegradable

BIOACCUMULATION POTENTIAL

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.



Product Name: MOBILUX EP 2
 Revision Date: 22 Jan 2015
 Page 7 of 8

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION

LAND (TDG): Not Regulated for Land Transport

LAND (DOT): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transport

SECTION 15 REGULATORY INFORMATION

WHMIS Classification: Not controlled

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the (M)SDS contains all the information required by the Controlled Products Regulations.

CEPA: All components of this material are either on the Canadian Domestic Substances List (DSL), exempt, or have been notified under CEPA.

Listed or exempt from listing/notification on the following chemical inventories: DSL, IECSC, KECI, PICCS, TSCA

Special Cases:

Inventory	Status
AICS	Restrictions Apply

The Following Ingredients are Cited on the Lists Below:

Chemical Name	CAS Number	List Citations
ZINC DITHIOPHOSPHATE	68649-42-3	6



Product Name: MOBILUX EP 2
Revision Date: 22 Jan 2015
Page 8 of 8

--REGULATORY LISTS SEARCHED--
1 = TSCA 4 3 = TSCA 5a 5 = TSCA 12b
2 = TSCA 5a2 4 = TSCA 6 6 = NPRI

SECTION 16 OTHER INFORMATION

N/D = Not determined, N/A = Not applicable

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Changes:

Section 06: Protective Measures information was modified.

Section 11: Tox Table - Header information was modified.

Section 06: Accidental Release - Protective Measures - Header information was added.

Section 11: Chemical Name - Header information was added.

Section 11: CAS Number - Header information was added.

Section 11: List Citation - Header information was added.

Section 11: Tox List Cited Table information was added.

WHMIS Classification: Not controlled

The information and recommendations contained herein are, to the best of Imperial Oil's knowledge and belief, accurate and reliable as of the date issued. Imperial Oil assumes no responsibility for accuracy of information unless the document is the most current available from an official Imperial Oil distribution system. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.

DGN: 5006468 (1012446)

Copyright 2002 Imperial Oil Limited, All rights reserved

Prepared by: Imperial Oil Limited, IH and Product Safety



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 1 of 9

MATERIAL SAFETY DATA SHEET

SECTION 1 PRODUCT AND COMPANY IDENTIFICATION

PRODUCT

Product Name: Z-50 PIPE DOPE
Product Description: Base Oil and Additives
MSDS Number: 8503
Product Code: 2015A020X010
Intended Use: Sealant

COMPANY IDENTIFICATION

Supplier: Imperial Oil Products Division
240 4th Avenue
Calgary, ALBERTA T2P 3M9 Canada
24 Hour Environmental / Health Emergency 1-866-232-9563
Telephone
Transportation Emergency Phone Number 1-866-232-9563
Product Technical Information 1-800-268-3183
Supplier General Contact 1-800-567-3776

SECTION 2 COMPOSITION / INFORMATION ON INGREDIENTS

No Reportable Hazardous Substance(s) or Complex Substance(s).

SECTION 3 HAZARDS IDENTIFICATION

This material is not considered to be hazardous according to regulatory guidelines see Section 15.

HEALTH EFFECTS

Low order of toxicity. Excessive exposure may result in eye, skin, or respiratory irritation. High-pressure injection under skin may cause serious damage.

NFPA Hazard ID:	Health: 1	Flammability: 1	Reactivity: 1
HMIS Hazard ID:	Health: 1	Flammability: 1	Reactivity: 1

NOTE: This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 4 FIRST AID MEASURES

INHALATION

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 2 of 9

SKIN CONTACT

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

SECTION 5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Appropriate Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Inappropriate Extinguishing Media: Straight streams of water

FIRE FIGHTING

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Smoke, Fume, Aldehydes, Sulphur oxides, Incomplete combustion products, Oxides of carbon, Metal Oxides

FLAMMABILITY PROPERTIES

Flash Point [Method]: >221°C (430°F) [ASTM D-92]

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

Autoignition Temperature: >260°C (500°F)

SECTION 6 ACCIDENTAL RELEASE MEASURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 3 of 9

SPILL MANAGEMENT

Land Spill: Scrape up spilled material with shovels into a suitable container for recycle or disposal.

Water Spill: Stop leak if you can do so without risk. Warn other shipping. Material will sink. Consult an expert. No immediate action required.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

SECTION 7 HANDLING AND STORAGE

HANDLING

Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

STORAGE

Do not store in open or unlabelled containers.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Substance Name	Form	Limit/Standard			Note	Source
MICA	Respirable fraction	TWA	3 mg/m3			ACGIH

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 4 of 9

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practise good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

GENERAL INFORMATION

Physical State: Solid
Form: Semi-fluid
Colour: Grey
Odour: Characteristic
Odour Threshold: N/D

IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 1.59
Flash Point [Method]: >221°C (430°F) [ASTM D-92]
Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0
Autoignition Temperature: >260°C (500°F)
Boiling Point / Range: < 316°C (601°F) [Estimated]
Vapour Density (Air = 1): N/D
Vapour Pressure: < 0.013 kPa (0.1 mm Hg) at 20°C [Estimated]
Evaporation Rate (n-butyl acetate = 1): < 0.01
pH: N/D



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 5 of 9

Log Pow (n-Octanol/Water Partition Coefficient): N/A
Solubility in Water: Negligible
Viscosity: [N/D at 40°C]
Oxidizing Properties: See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D
Melting Point: 196 °C (385 °F)
Decomposition Temperature: N/D

NOTE: Most physical properties above are for the oil component in the material.

SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

CONDITIONS TO AVOID: Excessive heat, High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Route of Exposure	Conclusion / Remarks
Inhalation	
Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures. Based on assessment of the components.
Ingestion	
Toxicity (Rat): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Skin	
Toxicity (Rabbit): LD50 > 5000 mg/kg	Minimally Toxic. Based on test data for structurally similar materials.
Irritation (Rabbit): Data available.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
Eye	
Irritation (Rabbit): Data available.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.

CHRONIC/OTHER EFFECTS

Contains:

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test



Product Name: Z-50 PIPE DOPE
 Revision Date: 20 Sep 2012
 Page 6 of 9

animals.

Additional information is available by request.

CMR Status: None.

Chemical Name	CAS Number	List Citations
MICA	12001-26-2	4.

--REGULATORY LISTS SEARCHED--

1 = IARC 1
 2 = IARC 2A

3 = IARC 2B
 4 = ACGIH ALL

5 = ACGIH A1
 6 = ACGIH A2

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data available for the material, the components of the material, and similar materials.

ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component -- Expected to be inherently biodegradable.

BIOACCUMULATION POTENTIAL

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

REGULATORY DISPOSAL INFORMATION

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain



Product Name: Z-50 PIPE DOPE
 Revision Date: 20 Sep 2012
 Page 7 of 9

residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION

LAND (TDG): Not Regulated for Land Transport

LAND (DOT): Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

AIR (IATA): Not Regulated for Air Transport

SECTION 15 REGULATORY INFORMATION

WHMIS Classification: Not controlled

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and the (M)SDS contains all the information required by the Controlled Products Regulations.

CEPA: All components of this material are either on the Canadian Domestic Substances List (DSL), exempt, or have been notified under CEPA.

Complies with the following national/regional chemical inventory requirements: AICS, DSL, IECSC, KECI, PICCS

The Following Ingredients are Cited on the Lists Below:

Chemical Name	CAS Number	List Citations
ZINC	7440-66-6	6

--REGULATORY LISTS SEARCHED--

1 = TSCA 4
 2 = TSCA 5a2

3 = TSCA 5e
 4 = TSCA 6

5 = TSCA 12b
 6 = NPRI

SECTION 16 OTHER INFORMATION

N/D = Not determined, N/A = Not applicable



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 8 of 9

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Revision Changes:

Section 06: Notification Procedures - Header was modified.
Section 10: Materials To Avoid - Header was modified.
Section 11: Acute Toxicity Table Header was modified.
Section 09: Phys/Chem Properties Note was modified.
Section 09: Colour was modified.
Section 11: Ingestion Acute Lethality - Header was modified.
Section 11: Inhalation - Header was modified.
Section 09: Boiling Point C(F) was modified.
Section 09: Evaporation Rate - Header was modified.
Section 08: Personal Protection - Header was modified.
Section 08: Comply with applicable regulations phrase was modified.
Section 09: Vapour Pressure - Header was modified.
Section 09: Vapour Pressure was modified.
Section 11: Inhalation Lethality Test Data was modified.
Section 11: Inhalation Irritation Test Data was modified.
Section 05: Hazardous Combustion Products was modified.
Section 06: Accidental Release- Spill Management- Water was modified.
Section 09: Relative Density - Header was modified.
Section 09: Flash Point C(F) was modified.
Section 14: Sea (IMDG) - Header was modified.
Section 14: Air (IATA) - Header was modified.
Section 14: LAND (TDG) - Header was modified.
Section 14: LAND (DOT) - Header was modified.
Section 14: LAND (DOT) - Default was modified.
Section 14: LAND (TDG) Default was modified.
Section 14: Sea (IMDG) - Default was modified.
Section 14: Air (IATA) - Default was modified.
Section 15: National Chemical Inventory Listing - Header was modified.
Section 15: National Chemical Inventory Listing was modified.
Hazard Identification: Hazards Note was modified.
Section 16: CA Prepared by - Header was modified.
Section 09: Section 9 Footnotes was modified.
Section 09: Oxidizing Properties was modified.
Section 15: Canadian List Citations Table was modified.
Section 01: Company Contact Methods Sorted by Priority was modified.
Section 06: Protective Measures was added.
Section 06: Accidental Release - Protective Measures - Header was added.
Section 09: Form - Header was added.
Section 09: Physical State was added.
Section 09: Decomposition Temperature was added.
Section 09: Decomposition Temp - Header was added.
Section 09: Vapour Pressure was added.
Section 01: Product Code was added.
Section 01: Product Code - Header was added.
Section 09: Form - Header was deleted.
Section 09: Physical State was deleted.

WHMIS Classification: Not controlled



Product Name: Z-50 PIPE DOPE
Revision Date: 20 Sep 2012
Page 9 of 9

The information and recommendations contained herein are, to the best of Imperial Oil's knowledge and belief, accurate and reliable as of the date issued. Imperial Oil assumes no responsibility for accuracy of information unless the document is the most current available from an official Imperial Oil distribution system. The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted.

DGN: 5007465 (1015931)

Copyright 2002 Imperial Oil Limited, All rights reserved

Prepared by: Imperial Oil Limited, IH and Product Safety



WESTWAY FEED PRODUCTS, INC.
3315 2nd AVE. N
LETHBRIDGE, AB
(800)563-6371

MATERIAL SAFETY DATA SHEET

REVISED JUNE 28, 2007

SECTION I: PRODUCT IDENTIFICATION

DESCRIPTION: CSB (CONCENTRATED SEPARATOR BY-PRODUCT)

USE: ANIMAL FEED

MANUFACTURER: WESTWAY FEED PRODUCTS, INC.
 3315 2nd AVE. N.
 LETHBRIDGE, AB, CANADA
 T1H 0C7

EMERGENCY CONTACT: WESTWAY FEED PRODUCTS, INC.
 TECHNICAL SERVICES
 DON MANN (403)660-4416

SECTION II: HAZARDOUS MATERIAL IDENTIFICATION

HAZARD DESCRIPTION: 1. STICKY SYRUP
 2. CAN REACT EXOTHERMALLY IF STORED AT HIGH TEMPERATURES.

COMPONENT 1 COMPONENT 2 COMPONENT 3

CHEMICAL NAME:	SUCROSE	PLANT NON-SUCROSES	WATER
CHEMICAL FORMULA:	C H O	N.A.	H O
PERCENT OF PRODUCT:	12%	68%	20%

SECTION III: PHYSICAL AND CHEMICAL DATA

DESCRIPTION: DARK BROWN SYRUP

DECOMPOSITION: SLOW DECOMPOSITION ABOVE 186 C

VOLATILITY: NIL

SPECIFIC GRAVITY: 1.41

SOLUBILITY: SOLUBLE IN WARM WATER IN ALL PROPORTIONS

pH: 8-9 IN WATER SOLUTION

REACTIVITY: NIL AT NORMAL TEMPERATURE AND USE. CAN REACT EXOTHERMALLY UNDER PROPER CONDITIONS OF INVERT, AMINO ACIDS, AND TEMPERATURES.

PAGE 1 OF 2

SPECIAL PROTECTION INFORMATION:

PROTECTIVE GLOVES:	N/A
EYE PROTECTION:	N/A
RESPIRATORY PROTECTION:	BREATHING APPARATUS MUST BE USED WHEN ENTERING STORAGE TANKS UNLESS THOROUGHLY VENTILLATED.
LOCAL EXHAUST:	STORAGE TANKS SHOULD BE VENTILATED BEFORE ENTRY.
OTHER EQUIPMENT:	LIFE LINE SHOULD BE WORN WHEN ENTERING TANKS.

REACTIVITY DATA:

INCOMPATIBLE MATERIALS:	N/A
STABILITY:	STABLE WHEN STORED AT LESS THAN 140 F
HAZARDOUS POLYMERIZATION:	N/A
HAZARDOUS DECOMPOSTION:	N/A

SPILL OR LEAK PROCEDURES:

WASH WITH WATER OR PICK UP WITH ABSORBENT MATERIALS. PREVENT ENTRY TO WATER WAYS WHERE BOD IS A CONCERN.

SPECIAL INFORMATION: NONE

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED ON DATA BELIEVED TO BE CORRECT. NO WARRANTY IS EXPRESSED OR IMPLIED.



550RD 550X POLYMER

DESCRIPTION

550RD/550X is a highly dispersible, slightly anionic, dry synthetic polymer that minimizes fisheyes when mixing allowing for more consistent yields and less waste in minimal shear environments. Requires minimal shearing to yield very consistently and quickly compared to semi synthetic or natural polymers.

PRIMARY FUNCTIONS

- High viscosity for cuttings transport with minimal product usage
- Nontoxic for use in environmentally sensitive applications

SECONDARY FUNCTIONS

These functions serve as supplemental benefits of this products use when mixed accordingly.

- Reduced torque and tubular wear compared to straight water applications
- Increased rate of penetration in directional and horizontal wells
- Reduction in storage on site, volume of supplies and transport costs over liquid product
- Shale and clay encapsulation that reduces swelling and increases well bore stability

MIXING

550RD 550X can be mixed readily in fresh water. Sprinkle slowly onto agitated, turbulent water. Hydration is almost immediate. 1-1.5 kg/m³ is generally sufficient for normal vertical drilling applications. In unconsolidated or broken formations that are prone to sloughing or in water reactive clay or shale the concentration should be increased to 1.5-2.5kg/m³. This product is sensitive to high salinity, if mixing in salt water contact Di-Corp rep for specialized instruction.

ENVIRONMENT

Dangerous components: None

Potentially dangerous impurities: None

Physical properties: White solid at 20 Degrees C

Measures to be taken after leakage or accidental spilling: Wash abundantly with water and bleach

Inflammability or danger of explosion: None

Poisonous properties: Non-toxic, slightly basic

First Aid measures: Wash with water

PACKAGING

20 kg. High impact plastic pail with handle.



**SECTION I: IDENTIFICATION OF PRODUCT**

COMPANY: **Diversity Technologies Corp.** DATE: **Nov. 22, 2011**
8750 – 53rd Ave. PHONE: **780-440-4923**
Edmonton, AB T6E 5G2 FAX: **780-469-1899**

PRODUCT NAME: **BIG BEAR ROD GREASE**

PRODUCT USE: Anti-seize compound
 CHEMICAL FAMILY: Mixture CAS #: Mixture

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not WHMIS regulated.
 WORKPLACE HAZARD: Not hazardous under normal conditions of use.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not TDG regulated.
 TDG CLASSIFICATION: Not applicable.
 UN NUMBER (PIN): Not applicable.
 PACKING GROUP: Not applicable.

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	% (w/w)	CAS NUMBER	LD ₅₀ Oral-Rat	LC ₅₀ Inhal-Rat	ACGIH-TLV
Mineral oil	70-80	64742-52-5	Not available	Not available	Not available
Barium soap	20-30	68201-19-4	Not available	Not available	Not available

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: [XX] EYE CONTACT [XX] SKIN [] INHALATION [XX] INGESTION
 EYE CONTACT: May cause slight transient irritation.
 SKIN CONTACT: May cause slight transient irritation.
 INGESTION: No effects known.
 INHALATION: Not a likely source of contact during normal use.
 CARCINOGENICITY: None of the ingredients in the compound are listed by NTP, IARC or OSHA as being carcinogenic.
 TERATOGENICITY: No information available.
 REPRODUCTIVE TOXICITY: No information available.
 MUTAGENICITY: No ingredients listed as mutagenic.
 SYNERGISTIC PRODUCTS: No information available.



+ MATERIAL SAFETY DATA SHEET +

BIG BEAR ROD GREASE

SECTION IV: FIRST AID MEASURES

SKIN CONTACT:	Remove by wiping, or with a waterless hand cleaner. Wash with soap and water. Remove and launder contaminated clothing before re-use.
EYE CONTACT:	Immediately flush with gently flowing warm water until all residual material is removed. Remove contact lenses if present. Hold eyelids open to ensure thorough flushing. If irritation persists, obtain medical attention.
INGESTION:	Do not induce vomiting. Rinse mouth. Obtain immediate medical attention. Never give anything by mouth to an unconscious or convulsing victim.
INHALATION:	Move to fresh air. Apply oxygen or artificial respiration as required. If breathing difficulties or distress continues, obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Brown paste; bland odour	
SPECIFIC GRAVITY:	0.90 @ 16°C	
BOILING POINT (°C):	371	
MELTING POINT (°C):	204	
SOLUBILITY IN WATER:	Insoluble	pH: Not available
PERCENT VOLATILE BY VOLUME:	Not available	
EVAPORATION RATE:	Not available	
VAPOUR PRESSURE :	Not available	
VAPOUR DENSITY (air = 1):	Not available	
BULK DENSITY:	Not applicable	

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	188°C (D-92)
FLAMMABLE LIMITS:	Not available
EXTINGUISHING MEDIA:	Dry chemical, CO ₂ , foam or water spray.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire-fighting personnel. Remove containers from fire area, or cool with water spray, if possible.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	This product may burn under fire conditions.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Strong oxidizers. Avoid heat, sparks and open flames.	
CONDITIONS OF REACTIVITY:	Contact with incompatibles or ignition sources.	



HAZARDOUS DECOMPOSITION PRODUCTS: May release CO_x, smoke and irritating vapours when heated to decomposition.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR [XX] MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Not required under normal conditions of use.
VENTILATION: Not required under normal conditions of use.
PROTECTIVE GLOVES: Suggest neoprene or viton.
EYE PROTECTION: Safety glasses with side-shields if required.
OTHER PROTECTIVE EQUIPMENT (Specify): Protective clothing as required to prevent contact.
Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with skin and eyes. Avoid ingestion. Wash thoroughly before eating, drinking or smoking. Store in cool, dry area away from incompatibles and sources of ignition. Use caution when opening unvented containers. Use in well-ventilated area. Store unused material in original container.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Eliminate ignition sources. Scoop up excess, then wipe down the affected area and pick up residual with diatomaceous earth to prevent slipping hazard. Place contaminated material and clean up materials in approved containers for disposal.

WASTE DISPOSAL METHOD

Dispose/incinerate in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. Dispose of, or recycle, empty containers in accordance with local regulations.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED: Nov. 22, 2011
SUPERSEDES: Dec. 9, 2008
BY: Regulatory Affairs
PHONE: 780-440-4923

**SECTION I: IDENTIFICATION OF PRODUCT**

COMPANY: **Diversity Technologies Corp.** DATE: **November 22, 2011**
8750 – 53rd Ave. PHONE: **780-440-4923**
Edmonton, AB T6E 5G2 FAX: **780-469-1899**

PRODUCT NAME: **LINSEED SOAP**

PRODUCT USE: **Lubricant.**

CHEMICAL FAMILY: **Fatty acids.** CAS#: **Not available**

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: **Not WHMIS controlled.**

WORKPLACE HAZARD: **Not applicable**

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: **Not regulated under TDG**

TDG CLASSIFICATION: **Not applicable**

UN NUMBER (PIN): **Not applicable**

PACKING GROUP: **Not applicable**

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	CAS NUMBER	LD ₅₀ Oral-Rat	LC ₅₀ Inhal-Mouse	ACGIH-TLV
No hazardous ingredients available.					

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: ☐ EYE CONTACT ☐ SKIN ☐ INHALATION ☐ INGESTION

EYE CONTACT: May cause slight irritation.

SKIN CONTACT: May cause slight irritation.

INGESTION: No information available. Not considered toxic based on information available for similar materials.

INHALATION: Not a likely source of contact during normal use.

CARCINOGENICITY: No information available.

TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.

MUTAGENICITY: No information available.

SYNERGISTIC PRODUCTS: No information available.

LINSEED SOAP

1



+ MATERIAL SAFETY DATA SHEET +

LINSEED SOAP

SECTION IV: FIRST AID MEASURES

SKIN CONTACT:	Wipe away excess. Remove contaminated clothing and wash affected area thoroughly with soap and water. If irritation develops or persists, obtain medical attention.
EYE CONTACT:	Immediately flush with gently flowing warm water until material is removed and irritation ceases. If irritation persists, obtain medical attention.
INGESTION:	If conscious give 1 to 2 glasses of water and induce vomiting; keep head below hips to prevent aspiration of vomitus. Obtain medical attention. Never give anything by mouth if patient is unconscious, rapidly losing consciousness or convulsing.
INHALATION:	Move to fresh air. Apply oxygen or artificial respiration if required. If breathing difficulties, or distress, continue obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR:	Brown paste; slight soapy odour
SPECIFIC GRAVITY:	Not applicable
BOILING POINT (°C):	100
MELTING POINT (°C):	0
SOLUBILITY IN WATER:	Soluble
PERCENT VOLATILE BY VOLUME:	Not applicable
EVAPORATION RATE:	Not applicable
VAPOUR PRESSURE (mmHg):	Not applicable
VAPOUR DENSITY (air = 1):	Not applicable
BULK DENSITY	Not applicable
	pH: 9.5 – 11.5

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT:	Not flammable
FLAMMABLE LIMITS:	Not applicable
EXTINGUISHING MEDIA:	Use media suitable for packaging and surrounding materials.
SPECIAL FIRE FIGHTING PROCEDURES:	Self-contained breathing apparatus required for fire fighting personnel.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	None known.

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX]	UNSTABLE []
------------	-------------	--------------



INCOMPATIBILITY (CONDITIONS TO AVOID):	None known.	
CONDITIONS OF REACTIVITY:	None known.	
HAZARDOUS DECOMPOSITION PRODUCTS:	Not determined.	
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX]	MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	Not applicable.
VENTILATION:	Not applicable.
PROTECTIVE GLOVES:	Personal preference.
EYE PROTECTION:	Safety glasses with side-shields recommended.
OTHER PROTECTIVE EQUIPMENT (Specify):	Wear clothing adequate to protect against exposure. Ensure eye-wash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Wash thoroughly after handling. Avoid contact with eyes, skin or clothing. Launder contaminated clothing before reuse. No specific storage requirements.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Scoop up excess material. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. Wipe up remaining spill with absorbent compound to prevent slipping hazard.

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. This material can be landfilled in most areas; check with local operator. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal.

SECTION IX: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED:	Nov. 22, 2011
SUPERSEDES:	Dec. 9, 2008
BY:	780-440-4923
PHONE:	Regulatory Affairs

MATERIAL SAFETY DATA SHEET

SECTION I: IDENTIFICATION OF PRODUCT

COMPANY: **Diversity Technologies Corp.** DATE: Jan. 3, 2006
8750 – 53rd Ave. PHONE: 604-940-6050
Edmonton, AB T6E 5G2 FAX: 604-940-6080

PRODUCT NAME: **G-STOP**

PRODUCT USE: Drilling mud additive.
 CHEMICAL FAMILY: Polyacrylamide CAS#: Not available

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

WHMIS CLASSIFICATION: Not a controlled product under WHMIS
 WORKPLACE HAZARD: Treat as a nuisance dust.

TRANSPORTATION OF DANGEROUS GOODS (TDG)

PROPER SHIPPING NAME: Not regulated under TDG
 TDG CLASSIFICATION: Not applicable
 UN NUMBER (PIN): Not applicable
 PACKING GROUP: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	CAS NUMBER	LD ₅₀ Oral-Rat	LC ₅₀ Inhal-Rat	ACGIH-TLV
Contains no WHMIS controlled ingredients.					

SECTION III: HEALTH HAZARDS

ROUTE OF ENTRY: ☐ EYE CONTACT ☐ SKIN ☐ INHALATION ☐ INGESTION

EYE CONTACT: May cause slight irritation and/or redness.

SKIN CONTACT: May cause slight irritation some cases.

INGESTION: Low acute oral toxicity. May cause nausea and vomiting.

INHALATION: May cause irritation of the respiratory tract, including sneezing and coughing.

CARCINOGENICITY: No information available.

TERATOGENICITY: No information available.

REPRODUCTIVE TOXICITY: No information available.

Diversity Technologies Corp. is the parent company of
 Canamara-United Supply, Hollimex Products, The Drilling Depot and
 Westcoast Drilling Supplies

G-Stop

Page 2 of 4

MUTAGENICITY: No information available.
SYNERGISTIC
PRODUCTS: No information available.

SECTION IV: FIRST AID MEASURES

SKIN CONTACT: Wash thoroughly with soap and water. If irritation develops or persists, obtain medical attention. Wash contaminated clothing prior to re-use.
EYE CONTACT: Flush with gently flowing warm water until irritation subsides. If irritation persists, obtain medical attention.
INGESTION: Do not induce vomiting. Give 2-3 glasses of water. If symptoms occur, obtain medical attention. Never give anything by mouth if patient is unconscious, rapidly losing consciousness or convulsing.
INHALATION: Move to fresh air. Apply oxygen or artificial respiration as required. If breathing difficulties or distress continues obtain medical attention.

SECTION V: PHYSICAL DATA

APPEARANCE AND ODOUR: White granular powder; no odour
SPECIFIC GRAVITY: 0.8
BOILING POINT (°C): Not available
MELTING POINT (°C): Not available
SOLUBILITY IN WATER: Insoluble pH: Not applicable
PERCENT VOLATILE BY VOLUME: Not available
EVAPORATION RATE: Not available
VAPOUR PRESSURE (mmHg): Not available
VAPOUR DENSITY (air = 1): Not available
BULK DENSITY: Not available

SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Not applicable
FLAMMABLE LIMITS: Not applicable
EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, foam, in preference to a water spray.
SPECIAL FIRE FIGHTING PROCEDURES: Self contained breathing apparatus required for fire fighting personnel. Move containers from fire area if possible.
UNUSUAL FIRE AND EXPLOSION HAZARDS: As with most organic powders, flammable dust clouds may be formed in air. Avoid creating dust. Avoid sources of ignition.

Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies

G-Stop

Page 3 of 4

SECTION VII: REACTIVITY DATA

STABILITY:	STABLE [XX] UNSTABLE []
INCOMPATIBILITY (CONDITIONS TO AVOID):	Avoid contact with strong oxidizers. Avoid wet, damp or humid conditions, extremes of temperature, and ignition sources.
HAZARDOUS DECOMPOSITION PRODUCTS:	Oxides of carbon and nitrogen, various hydrocarbons, and/or hydrogen cyanide upon combustion
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR [XX] MAY OCCUR []

SECTION VIII: PREVENTATIVE MEASURES

SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:	Use approved dust mask in absence of adequate ventilation. Use approved respirators with dust cartridges if TLV is exceeded.
VENTILATION:	Use in well-ventilated area, or use local exhaust ventilation, process enclosure or other engineering controls to maintain dust level below TLV.
PROTECTIVE GLOVES:	Use gloves, if needed, to avoid prolonged or repeated skin contact.
EYE PROTECTION:	Use safety glasses or goggles.
OTHER PROTECTIVE EQUIPMENT (Specify):	As necessary to prevent contact. Ensure eyewash station and emergency shower are available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid prolonged or repeated breathing of dust and contact with skin. Remove contaminated clothing; launder or dry-clean before reuse. Cleanse skin thoroughly after contact, before breaks and meals and at end of work period. Product is readily removed from skin by washing thoroughly with soap and water. Store in a cool, dry location away from incompatibles. Store in original container.

STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Use appropriate safety equipment. Avoid creating dust clouds. Remove ignition sources. Sweep up or vacuum dry material and flush spill area with water. Collect uncontaminated material for repackaging. Collect contaminated material in approved containers for disposal. This product or its solutions should not be allowed to enter waterways without treatment.

Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies

G-Stop

Page 4 of 4

WASTE DISPOSAL METHOD

Dispose in accordance with federal, provincial and local regulations. It is the responsibility of the end-user to determine if material meets the criteria of hazardous waste at the time of disposal. It may be possible to dispose of spills of non-hazardous materials in a landfill; check with local operator.

SECTION IX: PREPARATION

THE INFORMATION CONTAINED HEREIN IS GIVEN IN GOOD FAITH,
BUT NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE.

DATE ISSUED:	January 3, 2006	BY:	Product safety committee
SUPERSEDES:	March 31, 2003	PHONE:	780-440-4923

**Diversity Technologies Corp. is the parent company of
Canamara-United Supply, Hollimex Products, The Drilling Depot and
Westcoast Drilling Supplies**



Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Gulf Harmony AW Hydraulic 22
 Product Number: 334225
 Synonyms: Antiwear Hydraulic Fluid, Petroleum Based Lubricant
 Chemical Name: Hydrotreated heavy paraffinic distillate
 Chemical Family: Petroleum Distillate
 CAS Number: Blend

Company Identification

Gulf Oil LP/Nu-Tier Brands, Inc.
 Tulsa, OK
 TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
 CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

Chemical Name	Amount	CAS Number
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	> 98.0 %	64742-65-0
ADDITIVES	< 2.0 %	Blend

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

```

***** EMERGENCY OVERVIEW *****
*
* Not expected to cause a severe emergency hazard.
*
*****
  
```




Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

NFPA Rating - Health: 1
 Flammability: 1
 Reactivity: 0
 Special Hazard: N/A

POTENTIAL HEALTH EFFECTS

EYE:
Contact may cause eye irritation and redness.

SKIN:
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION:
Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

INGESTION:
Small amounts swallowed during normal handling operations are not likely to cause injury.

CHRONIC EFFECTS:
No adverse effects have been documented in humans as a result of chronic exposure.

CARCINOGENICITY INFORMATION:
Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:
Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:
Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.



Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

INHALATION FIRST AID:
Remove to fresh air.

If not breathing, give artificial respiration.

INGESTION FIRST AID:
If vomiting should occur spontaneously, keep airway clear.

NOTES TO PHYSICIAN:
Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES
COC Flash Point: 210° C (410.0° F)
Autoignition Temperature: > 315.6° C (> 600.1° F)

FLAMMABLE LIMITS IN AIR
LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:
Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

FIRE FIGHTING INSTRUCTIONS:
As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:
Fumes, smoke and carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):
Wear appropriate personal protective equipment.

INITIAL CONTAINMENT:
Absorb spills with inert material.

LARGE SPILLS PROCEDURE:
Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.



Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

SMALL SPILLS PROCEDURE:

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

Keep container closed to avoid contamination.

STORAGE PRECAUTIONS:

Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

EXPOSURE GUIDELINES:

No Information Available.



Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Characteristic
BOILING POINT: >425° F
VAPOR PRESSURE: Nil mm Hg
VAPOR DENSITY: >1 (Air = 1)
SOLUBILITY IN WATER: Nil
SPECIFIC GRAVITY: Not Determined (Water = 1)
MELTING/FREEZING POINT ...: N/A °F
% VOLATILES: Nil %
VISCOSITY: 22 cSt at 40 Deg C

10. STABILITY AND REACTIVITY

STABILITY:
Stable.

POLYMERIZATION:
Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:
Avoid contact with strong oxidizing agents.

DECOMPOSITION:
In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:
Minimal irritation on contact.

SKIN EFFECTS:
Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

ACUTE ORAL EFFECTS:
Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS:
Low acute toxicity expected on inhalation.

MISCELLANEOUS:
Please contact supplier for additional toxicological information.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:
Ecotoxicological Information: No specific aquatic data available for this product.



Gulf Harmony AW Hydraulic 22

Material Safety Data Sheet

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

CONTAINER DISPOSAL:

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Gulf Harmony AW Hydraulic 22
D.O.T. SHIPPING NAME ...: Not regulated by DOT

15. REGULATORY INFORMATION

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

16. OTHER INFORMATION

REASON FOR ISSUE ...: NEW
APPROVAL DATE: May 9, 2011
SUPERCEDES DATE:
RTN NUMBER

ADDITIONAL INFORMATION:

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gulf Oil LP. The data on this sheet are related only to the specific material designated herein. Gulf Oil LP assumes no legal responsibility for use or reliance upon these data.

END OF MSDS



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Gulf Harmony AW Hydraulic 32
 Product Number: 334227
 Synonyms: Antiwear Hydraulic Fluid, Petroleum Based Lubricant
 Chemical Name: Hydrotreated heavy paraffinic distillate
 Chemical Family: Petroleum Distillate
 CAS Number: Blend

Company Identification

Gulf Oil LP/Nu-Tier Brands, Inc.
 Tulsa, OK
 TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
 CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

Chemical Name	Amount	CAS Number
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	> 98.0 %	64742-65-0
ADDITIVES	< 2.0 %	Blend

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****
 *
 * Not expected to cause a severe emergency hazard. *
 *



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

NFPA Rating - Health: 1
 Flammability: 1
 Reactivity: 0
 Special Hazard: N/A

POTENTIAL HEALTH EFFECTS

EYE:
Contact may cause eye irritation and redness.

SKIN:
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION:
Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

INGESTION:
Small amounts swallowed during normal handling operations are not likely to cause injury.

CHRONIC EFFECTS:
No adverse effects have been documented in humans as a result of chronic exposure.

CARCINOGENICITY INFORMATION:
Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:
Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:
Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

INHALATION FIRST AID:
Remove to fresh air.

If not breathing, give artificial respiration.

INGESTION FIRST AID:
If vomiting should occur spontaneously, keep airway clear.

NOTES TO PHYSICIAN:
Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES
COC Flash Point: 215.8° C (420.3° F)
Autoignition Temperature: > 315.6° C (> 600.1° F)

FLAMMABLE LIMITS IN AIR
LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:
Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

FIRE FIGHTING INSTRUCTIONS:
As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:
Fumes, smoke and carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):
Wear appropriate personal protective equipment.

INITIAL CONTAINMENT:
Absorb spills with inert material.

LARGE SPILLS PROCEDURE:
Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

SMALL SPILLS PROCEDURE:

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

Keep container closed to avoid contamination.

STORAGE PRECAUTIONS:

Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

EXPOSURE GUIDELINES:

No Information Available.



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Characteristic
BOILING POINT: >425 F
VAPOR PRESSURE: Nil mm Hg
VAPOR DENSITY: >1 (Air = 1)
SOLUBILITY IN WATER: Nil
SPECIFIC GRAVITY: 0.861 at 60 deg F (Water = 1)
BULK DENSITY: 7.17 Pounds per Gallon at 60 Deg F
MELTING/FREEZING POINT ...: N/A F
% VOLATILES: Nil %
VISCOSITY: 32 cSt at 40 Deg C

10. STABILITY AND REACTIVITY

STABILITY:
Stable.

POLYMERIZATION:
Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:
Avoid contact with strong oxidizing agents.

DECOMPOSITION:
In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:
Minimal irritation on contact.

SKIN EFFECTS:
Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

ACUTE ORAL EFFECTS:
Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS:
Low acute toxicity expected on inhalation.

MISCELLANEOUS:
Please contact supplier for additional toxicological information.



Gulf Harmony AW Hydraulic 32

Material Safety Data Sheet

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Ecotoxicological Information: No specific aquatic data available for this product.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

CONTAINER DISPOSAL:

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Gulf Harmony AW Hydraulic 32

D.O.T. SHIPPING NAME ...: Not regulated by DOT

15. REGULATORY INFORMATION

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

16. OTHER INFORMATION

REASON FOR ISSUE: NEW

APPROVAL DATE: May 9, 2011

SUPERCEDES DATE:

RTN NUMBER:

ADDITIONAL INFORMATION:

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gulf Oil LP. The data on this sheet are related only to the specific material designated herein. Gulf Oil LP assumes no legal responsibility for use or reliance upon these data.

END OF MSDS



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Gulf Harmony AW Hydraulic 46
 Product Number: 334229
 Synonyms: Antiwear Hydraulic Fluid, Petroleum Based Lubricant
 Chemical Name: Hydrotreated heavy paraffinic distillate
 Chemical Family: Petroleum Distillate
 CAS Number: Blend

Company Identification

Gulf Oil LP/Nu-Tier Brands, Inc.
 Tulsa, OK
 TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
 CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

Chemical Name	Amount	CAS Number
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	> 98.0 %	64742-65-0
ADDITIVES	< 2.0 %	Blend

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

***** EMERGENCY OVERVIEW *****
 *
 * Not expected to cause a severe emergency hazard. *
 *



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

NFPA Rating - Health: 1
 Flammability: 1
 Reactivity: 0
 Special Hazard: N/A

POTENTIAL HEALTH EFFECTS

EYE:
Contact may cause eye irritation and redness.

SKIN:
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION:
Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

INGESTION:
Small amounts swallowed during normal handling operations are not likely to cause injury.

CHRONIC EFFECTS:
No adverse effects have been documented in humans as a result of chronic exposure.

CARCINOGENICITY INFORMATION:
Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:
Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:
Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

INHALATION FIRST AID:
Remove to fresh air.

If not breathing, give artificial respiration.

INGESTION FIRST AID:
If vomiting should occur spontaneously, keep airway clear.

NOTES TO PHYSICIAN:
Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES
COC Flash Point: 221^o C (430^o F)
Autoignition Temperature: > 315.6^o C (> 600.1^o F)

FLAMMABLE LIMITS IN AIR
LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:
Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

FIRE FIGHTING INSTRUCTIONS:
As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:
Fumes, smoke and carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):
Wear appropriate personal protective equipment.

INITIAL CONTAINMENT:
Absorb spills with inert material.

LARGE SPILLS PROCEDURE:
Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

SMALL SPILLS PROCEDURE:

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

Keep container closed to avoid contamination.

STORAGE PRECAUTIONS:

Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

EXPOSURE GUIDELINES:

No Information Available.



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Characteristic
BOILING POINT: >425° F
VAPOR PRESSURE: Nil mm Hg
VAPOR DENSITY: >1 (Air = 1)
SOLUBILITY IN WATER: Nil
SPECIFIC GRAVITY: Not Determined (Water = 1)
MELTING/FREEZING POINT ...: N/A °F
% VOLATILES: Nil %
VISCOSITY: 46 cSt at 40 Deg C

10. STABILITY AND REACTIVITY

STABILITY:
Stable.

POLYMERIZATION:
Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:
Avoid contact with strong oxidizing agents.

DECOMPOSITION:
In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:
Minimal irritation on contact.

SKIN EFFECTS:
Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

ACUTE ORAL EFFECTS:
Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS:
Low acute toxicity expected on inhalation.

MISCELLANEOUS:
Please contact supplier for additional toxicological information.



Gulf Harmony AW Hydraulic 46

Material Safety Data Sheet

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Ecotoxicological Information: No specific aquatic data available for this product.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

CONTAINER DISPOSAL:

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Gulf Harmony AW Hydraulic 46

D.O.T. SHIPPING NAME ...: Not regulated by DOT

15. REGULATORY INFORMATION

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

16. OTHER INFORMATION

REASON FOR ISSUE: NEW

APPROVAL DATE: May 9, 2011

SUPERCEDES DATE:

RTN NUMBER:

ADDITIONAL INFORMATION:

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gulf Oil LP. The data on this sheet are related only to the specific material designated herein. Gulf Oil LP assumes no legal responsibility for use or reliance upon these data.

END OF MSDS



Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identification

Product Name: Gulf Harmony AW Hydraulic 68
 Product Number: 334231
 Synonyms: Antiwear Hydraulic Fluid, Petroleum Based Lubricant
 Chemical Name: Hydrotreated heavy paraffinic distillate
 Chemical Family: Petroleum Distillate
 CAS Number: Blend

Company Identification

Gulf Oil LP/Nu-Tier Brands, Inc.
 Tulsa, OK
 TECHNICAL CONTACT NUMBER: 918-550-8026, Ext. 507
 CHEMTREC: EMERGENCY CONTACT 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT LISTING:

Chemical Name	Amount	CAS Number
HYDROTREATED PARAFFINIC DISTILLATE, DEWAXED	> 98.0 %	64742-65-0
ADDITIVES	< 2.0 %	Blend

(See Section 8 for exposure guidelines)

(See Section 15 for regulatory information)

HAZARDS DISCLOSURE

This product contains no known hazardous materials as defined by the OSHA Hazard Communication Standard 29 CFR 1910.1200.

As defined under Sara 311 and 312, this product contains no known hazardous materials.

3. HAZARDS IDENTIFICATION

```

***** EMERGENCY OVERVIEW *****
*
* Not expected to cause a severe emergency hazard.
*
*****
  
```




Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

HMIS Rating - Health: 1
 Flammability: 1
 Reactivity: 0

NFPA Rating - Health: 1
 Flammability: 1
 Reactivity: 0
 Special Hazard: N/A

POTENTIAL HEALTH EFFECTS

EYE:
Contact may cause eye irritation and redness.

SKIN:
Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION:
Inhalation of vapors or mist may be mildly irritating to the nose, throat, and respiratory tract.

INGESTION:
Small amounts swallowed during normal handling operations are not likely to cause injury.

CHRONIC EFFECTS:
No adverse effects have been documented in humans as a result of chronic exposure.

CARCINOGENICITY INFORMATION:
Based on OSHA 1910.1200 and IARC study requirements, this product does not require labeling.

4. FIRST AID MEASURES

EYE CONTACT FIRST AID:
Flush eye with water for 15 minutes.

Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:
Wash skin with soap and water.

Thoroughly wash (or discard) clothing and shoes before reuse.



Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

INHALATION FIRST AID:
Remove to fresh air.

If not breathing, give artificial respiration.

INGESTION FIRST AID:
If vomiting should occur spontaneously, keep airway clear.

NOTES TO PHYSICIAN:
Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES
COC Flash Point: 232° C (450° F)
Autoignition Temperature: > 315.6° C (> 600.1° F)

FLAMMABLE LIMITS IN AIR
LEL: N/A
UEL: N/A

EXTINGUISHING MEDIA:
Carbon dioxide, foam, or dry powder. Water may be used to cool below flash point.

FIRE FIGHTING INSTRUCTIONS:
As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH (approved or equivalent) and full protective gear.

COMBUSTION PRODUCTS:
Fumes, smoke and carbon monoxide.

6. ACCIDENTAL RELEASE MEASURES

SAFEGUARDS (PERSONNEL):
Wear appropriate personal protective equipment.

INITIAL CONTAINMENT:
Absorb spills with inert material.

LARGE SPILLS PROCEDURE:
Contain spilled material.

Large spillage should be dammed-off and pumped into containers.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.



Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

SMALL SPILLS PROCEDURE:

Clean up area by absorbent material.

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

7. HANDLING AND STORAGE

HANDLING (PERSONNEL):

DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Wash hands thoroughly after handling.

HANDLING (PHYSICAL ASPECTS):

Store in a cool dry area.

Keep container closed to avoid contamination.

STORAGE PRECAUTIONS:

Keep container closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS:

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical ventilation to maintain exposure below PEL/TLV (s).

EYE / FACE PROTECTION REQUIREMENTS:

Where contact with this material is likely, eye protection is recommended.

SKIN PROTECTION REQUIREMENTS:

When prolonged or frequently repeated contact could occur, use protective clothing impervious to this material.

RESPIRATORY PROTECTION REQUIREMENTS:

When there is potential for airborne exposures in excess of applicable limits, wear NIOSH/MSHA approved respiratory protection.

EXPOSURE GUIDELINES:

No Information Available.



Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

9. PHYSICAL AND CHEMICAL PROPERTIES

FORM: Liquid
COLOR: Amber
ODOR: Characteristic
BOILING POINT: >425° F
VAPOR PRESSURE: Nil mm Hg
VAPOR DENSITY: >1 (Air = 1)
SOLUBILITY IN WATER: Nil
SPECIFIC GRAVITY: Not Determined (Water = 1)
MELTING/FREEZING POINT ...: N/A °F
% VOLATILES: Nil %
VISCOSITY: 68 cSt at 40 Deg C

10. STABILITY AND REACTIVITY

STABILITY:
Stable.

POLYMERIZATION:
Hazardous polymerization will not occur.

INCOMPATIBILITY WITH OTHER MATERIALS:
Avoid contact with strong oxidizing agents.

DECOMPOSITION:
In the case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

11. TOXICOLOGICAL INFORMATION

EYE EFFECTS:
Minimal irritation on contact.

SKIN EFFECTS:
Practically non-toxic if absorbed. May cause mild irritation with prolonged and repeated exposure.

ACUTE ORAL EFFECTS:
Tests on similar materials indicate low order of acute oral toxicity.

ACUTE INHALATION EFFECTS:
Low acute toxicity expected on inhalation.

MISCELLANEOUS:
Please contact supplier for additional toxicological information.



Gulf Harmony AW Hydraulic 68

Material Safety Data Sheet

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL HAZARDS:

Ecotoxicological Information: No specific aquatic data available for this product.

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Treat or dispose of waste material in accordance with all local, state/provincial, and national requirements.

Do not flush to surface water or sanitary sewer system.

CONTAINER DISPOSAL:

Empty drums should be completely drained, properly bunged and promptly shipped to the supplier or a drum reconditioner.

All other containers should be disposed of in an environmentally safe manner.

14. TRANSPORTATION INFORMATION

PRODUCT LABEL: Gulf Harmony AW Hydraulic 68

D.O.T. SHIPPING NAME ...: Not regulated by DOT

15. REGULATORY INFORMATION

MISCELLANEOUS INFORMATION:

This material or all of its components are listed on the Inventory of Existing Chemical Substances under the Toxic Substance Control Act (TSCA).

16. OTHER INFORMATION

REASON FOR ISSUE: NEW

APPROVAL DATE: May 9, 2011

SUPERCEDES DATE:

RTN NUMBER:

ADDITIONAL INFORMATION:

The data in this Material Safety Data Sheet relates only to the specific material designated herein.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Gulf Oil LP. The data on this sheet are related only to the specific material designated herein. Gulf Oil LP assumes no legal responsibility for use or reliance upon these data.

END OF MSDS

USED OIL

MATERIAL SAFETY DATA SHEET



SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: USED OIL

SYNONYMS: Waste oil; Used lubricating oil; Oil and water mixture

**PRODUCT PART
NUMBER(S):** Not applicable.

PRODUCT USE: Oil or water mixture for re-refining or reprocessing.
If this product is used in combination with other products, refer to the
Material Safety Data Sheets for those products.

**24-HOUR EMERGENCY PHONE NUMBERS
MEDICAL AND TRANSPORTATION (SPILL):**
1-800-468-1760

These numbers are for
emergency use only. If
you desire non-emergency
product information,
please call a phone
number listed below.

MANUFACTURER/ SUPPLIER: Safety-Kleen Systems, Inc.
5400 Legacy Drive
Cluster II, Building 3
Plano, Texas 75024
USA
1-800-669-5740
www.Safety-Kleen.com

TECHNICAL INFORMATION: 1-800-669-5740 Press 1 then 1 then Extension 7500

MSDS FORM NUMBER: 81451

ISSUE: September 20, 2007

ORIGINAL ISSUE: January 15, 1990

SUPERSEDES: June 11, 2007

PREPARED BY: Product MSDS Coordinator

APPROVED BY: MSDS Task Force

Revision 9/07; MSDS Form No. 81451 - Page 1 of 10

USED OIL MATERIAL SAFETY DATA SHEET

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

WT%	NAME	SYNONYM	CAS NO.	OSHA PEL		ACGIH TLV ⁽¹⁾		LD ^a	LC ^b
				TWA	STEL	TWA	STEL		
80 to 100	Lubricating oils, used	Used oil	70514-12-4	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
0 to 20*	Water/solids	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
0 to 10*	Hydrocarbon solvents. May include gasoline, diesel fuel, jet fuel, mineral spirits, etc.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
0 to 1.5*	Metals. May include lead, iron, zinc, copper, chromium, arsenic, nickel, and others: each below 1.0 WT%.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
0 to 1.0*	Polynuclear aromatics. May include naphthalene, fluoranthene, phenanthrene, pyrene, and others: each below 0.3 WT%.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.
0 to 0.5*	Chlorinated solvents.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.	N. Av.

N. Av. = Not Available

*Even though the concentration range does not fall under the ranges prescribed by WHMIS, this is the actual range which varies with each batch of the product.

^aOral-Rat LD₅₀ (mg/kg)

^bInhalation-Rat LC₅₀

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

APPEARANCE

Liquid, black and viscous (thick), petroleum odor.

WARNING!

PHYSICAL HAZARDS

Combustible liquid.

HEALTH HAZARDS

May be harmful if inhaled.

May be harmful if absorbed through skin.

May be harmful or fatal if swallowed.

May irritate the respiratory tract (nose, throat, and lungs), eyes, and skin.

Suspect cancer hazard. Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.

Contains material which can cause birth defects.

Contains material which can cause central nervous system damage.

ENVIRONMENTAL HAZARDS

Product may be toxic to fish, plants, wildlife, and/or domestic animals.

Revision 9/07; MSDS Form No. 81451 - Page 2 of 10

**USED OIL
MATERIAL SAFETY DATA SHEET**

POTENTIAL HEALTH EFFECTS

Effects may vary depending on material composition. Typical effects may include:

INHALATION (BREATHING): High concentrations of vapor or mist may be harmful if inhaled. High concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

EYES: May cause irritation.

SKIN: May cause irritation. Product may be absorbed through the skin and cause harm as noted under **INHALATION (BREATHING)**.

INGESTION (SWALLOWING): May be harmful or fatal if swallowed. May cause throat irritation, nausea, vomiting, and central nervous system effects as noted under **INHALATION (BREATHING)**. Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Individuals with pre-existing cardiovascular, liver, kidney, respiratory tract (nose, throat, and lungs), central nervous system, eye, and/or skin disorders may have increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause oil pneumonia, lung tissue inflammation, fibrous tissue formation, and/or toxic effects as noted under **INHALATION (BREATHING)**. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis).

CANCER INFORMATION: This product contains mineral oils, untreated or mildly treated, which can cause cancer. This product may contain hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics which can cause cancer. Risk of cancer depends on duration and level of exposure. For more information, see **SECTION 11: CARCINOGENICITY**.

POTENTIAL ENVIRONMENTAL EFFECTS

Product may be toxic to fish, plants, wildlife, and/or domestic animals.

Also see **SECTION 12: ECOLOGICAL INFORMATION**.

Revision 9/07; MSDS Form No. 81451 - Page 3 of 10

**USED OIL
MATERIAL SAFETY DATA SHEET****SECTION 4: FIRST AID MEASURES**

INHALATION: (BREATHING)	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.
EYES:	If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.
SKIN:	Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.
INGESTION: (SWALLOWING)	Do NOT induce vomiting. Immediately get medical attention. Call 1-800-468-1760 for additional information. If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by mouth.
NOTE TO PHYSICIANS:	Treat symptomatically and supportively. Treatment may vary with condition of victim and specifics of incident. Call 1-800-468-1760 for additional information.

SECTION 5: FIRE FIGHTING MEASURES


FLASH POINT:	>200°F (93°C) (minimum) Pensky-Martens Closed Cup
FLAMMABLE LIMITS IN AIR:	Not available.
AUTOIGNITION TEMPERATURE:	Not available.
HAZARDOUS COMBUSTION PRODUCTS:	Decomposition and combustion materials may be toxic. Burning may produce phosgene gas, nitrogen oxides, carbon monoxide, and unidentified organic compounds.
CONDITIONS OF FLAMMABILITY:	Heat, sparks, or flame. Product may burn but does not ignite readily.
EXTINGUISHING MEDIA:	Use carbon dioxide, regular foam, dry chemical, water spray, or water fog.

Revision 9/07; MSDS Form No. 81451 - Page 4 of 10

USED OIL MATERIAL SAFETY DATA SHEET

NFPA 704 HAZARD IDENTIFICATION:

This information is intended solely for the use by individuals trained in this system.



FIRE FIGHTING INSTRUCTIONS:

Keep storage containers cool with water spray. A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE AND EXPLOSION HAZARDS:

Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Product is not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface waters and sewers. Contain spill as a liquid for possible recovery, or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **SECTION 15: REGULATORY INFORMATION**.

Revision 9/07; MSDS Form No. 81451 - Page 5 of 10

**USED OIL
MATERIAL SAFETY DATA SHEET**

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, storage tanks, tanker trucks, and rail tank cars should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

SHIPPING AND STORING: Keep container tightly closed when not in use and during transport. Do not pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORT INFORMATION** for Packing Group information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Use general ventilation, process enclosures, local exhaust ventilation, or other engineering controls to control air-borne levels. Where explosive mixtures may be present, equipment safe for such locations should be used.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY PROTECTION: A respiratory protection program which meets USA's OSHA General Industry Standard 29 CFR 1910.134 or Canada's CSA Standard Z94.4-M1982 requirements must be followed whenever workplace conditions warrant a respirator's use. Consult a qualified Industrial Hygienist or Safety Professional for respirator selection guidance.

EYE PROTECTION: Wearing chemical goggles is recommended. Contact lens may be worn with eye protection.

SKIN PROTECTION: Where prolonged or repeated skin contact is likely, wear neoprene, nitrile (4 mil minimum), PVC (polyvinyl chloride), or equivalent protective gloves; wearing natural rubber or equivalent gloves is not recommended.

When product is heated and skin contact is likely, wear heat-insulating gloves, boots, and other protective clothing.

To avoid prolonged or repeated contact with product where spills and splashes are likely, wear appropriate chemical-resistant faceshield, boots, apron, whole body suits, or other protective clothing.

Revision 9/07; MSDS Form No. 81451 - Page 6 of 10

**USED OIL
MATERIAL SAFETY DATA SHEET**

PERSONAL HYGIENE: Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or protective equipment if they cannot be thoroughly cleaned. Discard leather articles, such as shoes, saturated with the product.

OTHER PROTECTIVE EQUIPMENT: Where spills and splashes are likely, facilities storing or using this product should be equipped with an emergency eyewash and shower, both equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE, APPEARANCE, AND ODOR: Liquid, black and viscous (thick), petroleum odor.

ODOR THRESHOLD: Not available.

MOLECULAR WEIGHT: Not applicable.

SPECIFIC GRAVITY: 0.8 to 1.0 at 60°F (15.6°C) (water = 1)

DENSITY: 6.7 to 8.3 LB/US gal (800 to 1000 g/l) (approximately)

VAPOR DENSITY: greater than 1 (air = 1) (based on kerosene)

VAPOR PRESSURE: Not available.

BOILING POINT: Not available.

FREEZING/MELTING POINT: Not available.

pH: Not applicable.

EVAPORATION RATE: less than 1 (butyl acetate = 1)

SOLUBILITY IN WATER: Slight.

FLASH POINT: >200°F (93°C) (minimum) Pensky-Martens Closed Cup

FLAMMABLE LIMITS IN AIR: Not available.

AUTOIGNITION TEMPERATURE: Not available.

Revision 9/07; MSDS Form No. 81451 - Page 7 of 10

**USED OIL
MATERIAL SAFETY DATA SHEET****SECTION 10: STABILITY AND REACTIVITY**

STABILITY:	Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.
INCOMPATIBILITY:	Avoid acids, alkalis, oxidizing agents, reducing agents, reactive halogens, or reactive metals.
REACTIVITY:	Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.
HAZARDOUS DECOMPOSITION PRODUCTS:	None under normal temperatures and pressures. Also see SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.

SECTION 11: TOXICOLOGICAL INFORMATION

SENSITIZATION:	Based on best current information, there may be known human sensitization associated with this product.
MUTAGENICITY:	Based on best current information, there may be mutagenicity associated with this product.
CARCINOGENICITY:	Mineral oils, untreated or mildly treated are listed by IARC as a known carcinogen. Mineral oils, untreated or mildly treated are classified by NTP as having limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals.

There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are listed by OSHA as known carcinogens. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are listed by IARC as known, probable, or possible carcinogens. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are classified by NTP as known carcinogens or as having limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals. There may be hydrocarbon and chlorinated solvents; metals, and polynuclear aromatics present in this product which are recognized by ACGIH as confirmed or suspected human carcinogens.

Also see **SECTION 3: CANCER INFORMATION.**

Revision 9/07; MSDS Form No. 81451 - Page 8 of 10

USED OIL MATERIAL SAFETY DATA SHEET

REPRODUCTIVE TOXICITY: Based on best current information, there may be reproductive toxicity associated with this product.

TERATOGENICITY: Based on best current information, there may be teratogenicity associated with this product.

TOXICOLOGICALLY SYNERGISTIC PRODUCT(S): Based on best current information, there may be toxicologically synergistic products associated with this product.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: Not available.

OCTANOL/WATER PARTITION COEFFICIENT: Not available.

VOLATILE ORGANIC COMPOUNDS: Not available.
As per 40 CFR Part 51.100(s).

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding proper recycling or disposal.

SECTION 14: TRANSPORT INFORMATION

DOT: Not regulated.

TDG: Not regulated.

EMERGENCY RESPONSE GUIDE NUMBER: Not applicable.
Reference *North American Emergency Response Guidebook*

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS SARA SECTIONS 302 AND 304: Based on the ingredient(s) listed in **SECTION 2**, this product does not contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

Revision 9/07; MSDS Form No. 81451 - Page 9 of 10

USED OIL MATERIAL SAFETY DATA SHEET

SARA SECTIONS 311 AND 312:	This product poses the following physical and health hazards as defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA): Immediate (Acute) Health Hazard Delayed (Chronic) Health Hazard
SARA SECTION 313:	This product may contain "toxic" chemicals subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.
CERCLA:	This product may contain "hazardous substances" listed pursuant to Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4.
TSCA:	Not available.
CALIFORNIA:	This product is not for sale or use in the State of California.
CANADIAN REGULATIONS	
WHMIS:	Not regulated
CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA):	Not available.

SECTION 16: OTHER INFORMATION

REVISION INFORMATION: Change from MSIS to MSDS.

LABEL/OTHER INFORMATION: Not available.

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product as supplied to the user.



©2007 Safety-Kleen Systems, Inc.

Revision 9/07; MSDS Form No. 81451 - Page 10 of 10

Appendix 3: Daily Fuel Inspection Record

Daily Fuel Inspection Record

[illegible]

Appendix 4: NT-NU Spill Report Form

Instructions for Completing the NT-NU Spill Report Form

This form can be filled out electronically and e-mailed as an attachment to spills@gov.nt.ca. Until further notice, please verify receipt of e-mail transmissions with a follow-up telephone call to the spill line. Forms can also be printed and faxed to the spill line at 867-873-6924. Spills can still be phoned in by calling collect at 867-920-8130.

A. Report Date/Time	The actual date and time that the spill was reported to the spill line. If the spill is phoned in, the Spill Line will fill this out. Please do not fill in the Report Number: the spill line will assign a number after the spill is reported.
B. Occurrence Date/Time	Indicate, to the best of your knowledge, the exact date and time that the spill occurred. Not to be confused with the report date and time (see above).
C. Land Use Permit Number /Water Licence Number	This only needs to be filled in if the activity has been licenced by the Nunavut Water Board and/or if a Land Use Permit has been issued. Applies primarily to mines and mineral exploration sites.
D. Geographic Place Name	In most cases, this will be the name of the city or town in which the spill occurred. For remote locations – outside of human habitations – identify the most prominent geographic feature, such as a lake or mountain and/or the distance and direction from the nearest population center. You must include the geographic coordinates (Refer to Section E).
E. Geographic Coordinates	This only needs to be filled out if the spill occurred outside of an established community such as a mine site. Please note that the location should be stated in degrees, minutes and seconds of Latitude and Longitude.
F. Responsible Party Or Vessel Name	This is the person who was in management/control/ownership of the substance at the time that it was spilled. In the case of a spill from a ship/vessel, include the name of the ship/vessel. Please include full address, telephone number and e-mail. Use box K if there is insufficient space. Please note that, the owner of the spilled substance is ultimately responsible for any spills of that substance, regardless of who may have actually caused the spill.
G. Contractor involved?	Were there any other parties/contractors involved? An example would be a construction company who is undertaking work on behalf of the owner of the spilled substance and who may have contributed to, or directly caused the spill and/or is responding to the spill.
H. Product Spilled	Identify the product spilled; most commonly, it is gasoline, diesel fuel or sewage. For other substances, avoid trade names. Wherever possible, use the chemical name of the substance and further, identify the product using the four digit UN number (eg: UN1203 for gasoline; UN1202 for diesel fuel; UN1863 for Jet A & B)
I. Spill Source	Identify the source of the spill: truck, ship, home heating fuel tank and, if known, the cause (eg: fuel tank overflow, leaking tank; ship ran aground; traffic accident, vandalism, storm, etc.). Provide an estimate of the extent of the contaminated/impacted area (eg: 10 m ²)
J. Factors Affecting Spill	Any factors which might make it difficult to clean up the spill: rough terrain, bad weather, remote location, lack of equipment. Do you require advice and/or assistance with the cleanup operation? Identify any hazards to persons, property or environment: for example, a gasoline spill beside a daycare centre would pose a safety hazard to children. Use box K if there is insufficient space.
K. Additional Information	Provide any additional, pertinent details about the spill, such as any peculiar/unique hazards associated with the spilled material. State what action is being taken towards cleaning up the spill; disposal of spilled material; notification of affected parties. If necessary, append additional sheets to the spill report. Number the pages in the same format found in the lower right hand corner of the spill form: eg. "Page 1 of 2", "Page 2 of 2" etc. Please number the pages to ensure that recipients can be certain that they received all pertinent documents. If only the spill report form was filled out, number the form as "Page 1 of 1".
L. Reported to Spill Line by	Include your full name, employer, contact number and the location from which you are reporting the spill. Use box K if there is insufficient space.
M. Alternate Contact	Identify any alternate contacts. This information assists regulatory agencies to obtain additional information if they cannot reach the individual who reported the spill.
N. Report Line Use Only	Leave Blank. This box is for the Spill Line's use only.



Canada

NT-NU SPILL REPORT

OIL, GASOLINE, CHEMICALS AND OTHER HAZARDOUS MATERIALS

NT-NU 24-HOUR SPILL REPORT LINE

TEL: (867) 920-8130

FAX: (867) 873-6924

EMAIL: spills@gov.nt.ca

REPORT LINE USE ONLY

A	REPORT DATE: MONTH – DAY – YEAR		REPORT TIME		<input type="checkbox"/> ORIGINAL SPILL REPORT, OR <input type="checkbox"/> UPDATE # _____ TO THE ORIGINAL SPILL REPORT	REPORT NUMBER _____	
	OCCURRENCE DATE: MONTH – DAY – YEAR		OCCURRENCE TIME				
C	LAND USE PERMIT NUMBER (IF APPLICABLE)			WATER LICENCE NUMBER (IF APPLICABLE)			
D	GEOGRAPHIC PLACE NAME OR DISTANCE AND DIRECTION FROM NAMED LOCATION				REGION <input type="checkbox"/> NWT <input type="checkbox"/> NUNAVUT <input type="checkbox"/> ADJACENT JURISDICTION OR OCEAN		
E	LATITUDE DEGREES MINUTES SECONDS			LONGITUDE DEGREES MINUTES SECONDS			
F	RESPONSIBLE PARTY OR VESSEL NAME		RESPONSIBLE PARTY ADDRESS OR OFFICE LOCATION				
G	ANY CONTRACTOR INVOLVED		CONTRACTOR ADDRESS OR OFFICE LOCATION				
H	PRODUCT SPILLED		QUANTITY IN LITRES, KILOGRAMS OR CUBIC METRES		U.N. NUMBER		
	SECOND PRODUCT SPILLED (IF APPLICABLE)		QUANTITY IN LITRES, KILOGRAMS OR CUBIC METRES		U.N. NUMBER		
I	SPILL SOURCE		SPILL CAUSE		AREA OF CONTAMINATION IN SQUARE METRES		
J	FACTORS AFFECTING SPILL OR RECOVERY		DESCRIBE ANY ASSISTANCE REQUIRED		HAZARDS TO PERSONS, PROPERTY OR ENVIRONMENT		
K	ADDITIONAL INFORMATION, COMMENTS, ACTIONS PROPOSED OR TAKEN TO CONTAIN, RECOVER OR DISPOSE OF SPILLED PRODUCT AND CONTAMINATED MATERIALS						
L	REPORTED TO SPILL LINE BY	POSITION	EMPLOYER	LOCATION CALLING FROM	TELEPHONE		
M	ANY ALTERNATE CONTACT	POSITION	EMPLOYER	ALTERNATE CONTACT LOCATION	ALTERNATE TELEPHONE		
REPORT LINE USE ONLY							
N	RECEIVED AT SPILL LINE BY	POSITION STATION OPERATOR	EMPLOYER	LOCATION CALLED YELLOWKNIFE, NT	REPORT LINE NUMBER (867) 920-8130		
LEAD AGENCY <input type="checkbox"/> EC <input type="checkbox"/> CCG <input type="checkbox"/> GNWT <input type="checkbox"/> GN <input type="checkbox"/> ILA <input type="checkbox"/> INAC <input type="checkbox"/> NEB <input type="checkbox"/> TC			SIGNIFICANCE <input type="checkbox"/> MINOR <input type="checkbox"/> MAJOR <input type="checkbox"/> UNKNOWN		FILE STATUS <input type="checkbox"/> OPEN <input type="checkbox"/> CLOSED		
AGENCY		CONTACT NAME	CONTACT TIME	REMARKS			
LEAD AGENCY							
FIRST SUPPORT AGENCY							
SECOND SUPPORT AGENCY							
THIRD SUPPORT AGENCY							

PAGE 1 OF _____