Material Safety Data Sheet





1. Product and company identification

Common name : PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL

Code : 410-344, MOSP53; 410-341, MOSP13; 410-342, MOSP14; 410-343, MOSP25

Material uses : Supreme is designed for the lubrication of all gasoline, propane and CNG engines where

the manufacturer recommends the use of API SM quality oils. SAE 5W-30 and 10W-30

grades also meet the requirements of ILSAC GF-4.

Manufacturer : PETRO-CANADA

P.O. Box 2844 Calgary, Alberta

T2P 3E3

In case of emergency : Petro-Canada: 403-296-3000

Canutec Transportation:

613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

2. Hazards identification

Odour : Mild petroleum oil like.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and

available for employees and other users of this product.

Emergency overview: No specific hazard.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eyes: Slightly irritating to the eyes.

Skin : Slightly irritating to the skin.

Inhalation: No known significant effects or critical hazards.

Ingestion : No known significant effects or critical hazards.

Medical conditions aggravated by over-

exposure

 Repeated skin exposure can produce local skin destruction or dermatitis. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation

See toxicological information (section 11)

3. Composition/information on ingredients

Name
Mixture of severely hydrotreated and hydrocracked base oil (petroleum).

CAS number

Mixture

-

The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8,

The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-52-5, 64742-54-7, 72623-84-8 72623-85-9, 72623-86-0, 72623-87-1, 178603-64-0, 178603-65-1, 178603-66-2, 445411-73-4

4. First-aid measures

Eye contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Skin contact: Wash skin thoroughly with soap and water or use recognised skin cleanser. Get medical attention if irritation occurs. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Inhalation: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion
 Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially dangerous quantities of this material have been swallowed, call a physician immediately.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

Continued on Next Page Internet: www.petro-canada.ca/msds Page: 1/6

PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL Page Number: 2

5. Fire-fighting measures

Flammability of the product

: May be combustible at high temperature.

Products of combustion

: Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus oxides (POx), calcium oxides (CaOx), zinc oxides (ZnOx), molybdenum oxides (MoOx), boron oxides, smoke and irritating vapours as products of incomplete combustion.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: No specific hazard.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire

: Low fire hazard. This material must be heated before ignition will occur.

hazards Special remarks on Low life nazard. This material must be neated before ignition will occur.

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

6. Accidental release measures

Personal precautions

: Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment.

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and

Methods for cleaning up

: If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain material to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

7. Handling and storage

Handling

: Keep away from heat. Keep away from sources of ignition. Empty containers pose a fire risk. Evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapour/spray. Wear suitable protective clothing. If ingested, seek medical advice immediately and show the container or the label. Keep away from incompatibles such as oxidising agents, acids.

Storage

Keep container tightly closed. Store away from incompatible materials (see section 10). Keep container in a cool, well-ventilated area.

8. Exposure controls/personal protection

Product name

Exposure limits

Mixture of severely hydrotreated and hydrocracked base oil (petroleum).

ACGIH TLV (United States). Notes: (oil mist)

TWA: 5 mg/m³ 8 hour/hours.

STEL: 10 mg/m³ 15 minute/minutes.

Consult local authorities for acceptable exposure limits.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control airborne levels. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protection

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Continued on Next Page

PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL Page Number: 3

Exposure controls/personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Recommended: organic vapour filter

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Recommended: neoprene, nitrile, polyvinyl alcohol (PVA), Viton.

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash

contaminated clothing before reusing. Ensure that eyewash stations and safety showers

are close to the workstation location.

Physical and chemical properties

Physical state : Viscous liquid.

Flash point Open cup:>227°C (440.6°F) (Cleveland.).

Auto-ignition temperature : Not available. Flammable limits : Not available.

Colour Light amber.

Odour : Mild petroleum oil like.

: Not applicable. **Boiling/condensation point** : Not available.

Pour Point 5W-30: -45°C (-49°F) **10W-30**: -36°C (-33°F) **10W-40**: -36°C (-33°F) 20W-50:

-24°C (-11°F)

Melting/freezing point Not available.

0.856 to 0.8784 kg/L @ 15°C (59°F) Relative density

Not available. Vapour pressure Not available. Vapour density **Volatility** : Not available **Odour threshold** : Not available. Not available. **Evaporation rate**

5W-30: 61.8 cSt @ 40°C (104°F), 10.4 cSt @ 100°C (212°F), VI=159; 10W-30: 66.0 **Viscosity**

cSt @ 40°C (104°F), 10.2 cSt @ 100°C (212°F), VI=141; 10W-40: 94.9 cSt @ 40°C (104°F), 13.9 cSt @ 100°C (212°F), VI=149; **20W-50**: 170.8 cSt @ 40°C (104°F), 18.9

cSt @ 100°C (212°F), VI=125

Solubility Insoluble in water.

Not available. LogKow **Softening Point** : Not available. **Dropping Point** : Not available. **Penetration** Not available. Not available. Physical/chemical

10. Stability and reactivity

properties comments

Stability and reactivity : The product is stable.

: Not available. Conditions of instability

Incompatibility with various Reactive with oxidising agents and acids.

substances

Hazardous decomposition May release COx, H2S, alkyl mercaptans, methacrylate monomers, smoke and irritating vapours when heated to decomposition. products

: Will not occur. **Hazardous polymerisation**

Continued on Next Page Page: 3/6 Internet: www.petro-canada.ca/msds

PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL Page Number: 4

11. Toxicological information

Toxicity data

Product/ingredient name Result **Species Test** Route Mixture of severely hydrotreated LD50 >5000 mg/kg Oral Rat LD50 Dermal and hydrocracked base oil >2000 mg/kg Rabbit (petroleum). LC50 $>2500 \text{ mg/m}^3 (4)$ Inhalation Rat hour/hours)

Specific effects

Carcinogenic effects
: Not listed as carcinogenic by OSHA, NTP or IARC.

Mutagenic effects
: No known significant effects or critical hazards.

Teratogenicity /
Reproductive toxicity

Sensitisation

Ingestion: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.

Eyes : Slightly irritating to the eyes.

Skin : Slightly irritating to the skin.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity data

Product/ingredient name Species Period Result

Environmental precautions: No known significant effects or critical hazards.

Bioconcentration factor

BOD and COD

Biodegradable/OECD

Mobility

Not available.

Not available.

Not available.

Not available.

Not available.

Not available.

products of biodegradation

13. Disposal considerations

Disposal should be in accordance with applicable regional, national and local laws and regulations. Local regulations may be more stringent than regional or national requirements.

The information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Continued on Next Page

Internet: www.petro-canada.ca/msds

Page: 4/6

PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL

14. Transport information

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
DOT Classification	Not available.	Not available.	Not available.	-		-

PG*: Packing group

15. Regulatory information

United States

HCS Classification : Not regulated.U.S. Federal regulations : Not available.

<u>Canada</u>

WHMIS (Canada) : Not controlled under WHMIS (Canada).

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

EU regulations

Risk phrases: This product is not classified according to EU legislation.

International regulations

International lists

CANADA INVENTORY (DSL) : Not determined.

EC INVENTORY (EINECS/ELINCS) : Listed
TSCA 8(b) inventory : Listed

16. Other information

Hazardous Material Information System (U.S.A.)

Health 1
Fire hazard 1
Reactivity 0
Personal protection B

National Fire Protection Association (U.S.A.)

Health 1 0 Instability
Special

References: Available upon request.

* Marque de commerce de Petro-Canada - Trademark

Date of printing : 7/28/2006.

Date of issue : 7/24/2006.

Date of previous issue : No previous validation.

Responsible name : Product Safety - JDW

Version : 1

For Copy of (M)SDS : The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous)

products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Continued on Next Page

Internet: www.petro-canada.ca/msds

Page: 5/6

Page Number: 5

PETRO-CANADA SUPREME 5W-30, 10W-30, 10W-40, 20W-50 MOTOR OIL

16. Other information

Internet: www.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax: 1-800-

Page Number: 6

201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.