MATERIAL SAFETY DATA SHEET

WHMIS HAZARD INDEX: D2A PRODUCT CODE: **INSIGNIFICANT** REACTIVITY SLIGHT 0 2 **MODERATE SPECIAL** 0 HIGH TOXICITY 3 **EXTREME SECTION 1** LOCATION SECTION 6 **TOXICOLOGY** TOPCO OILSITE PRODUCTS LTD. **ROUTE OF ENTRY:** SKIN & EYE CONTACT BAY 5, 3401 - 19 STREET N.E. CALGARY, ALBERTA CANADA T2E 6S8 CHRONIC EFFECTS: MAY CAUSE IRRITATION AND POSSIBLE DERMATITIS IN PHONE (403) 219-0255 SENSITIVE INDIVIDUALS (403) 291-3042 FAX **ACUTE TOXICOLOGY:** TRADE NAME: **ALLSTAR** NO DATA AVAILABLE MATERIAL USE: **LUBRICATE & SEAL DRILL COLLAR THREADS SECTION 7 PREVENTION MEASURES SECTION 2 HAZARDOUS INGREDIENTS** GLOVES: APPROX RUBBER OR CLOTH COMPOSITION **CONCENTRATION** <u>C.A.S.</u> **EXP.LIMITS GRAPHITE** 7782-42-5 5 - 15%N/A EYE PROTECTION: POWDERED LEAD 55 - 70% 7439-92-1 N/A GOGGLES RECOMMENDED 5 - 10%TALC 1480-7966 N/A **VENTILATION: SECTION 3 CHEMICAL & PHYSICAL PROPERTIES** LOCAL EXHAUST NAME: RESPIRATORY PROTECITON: PETROLEUM HYDROCARBON WITH ADDITIVES NONE REQUIRED ODOUR: **LEAK & SPILL PROCEDURE:** MILD PETROLEUM PREVENT MATERIAL FROM ENTERING WATERCOURSES BY CONTAINING WITH SAND OR EARTH. COLOUR: **BLACK PASTE WASTE DISPOSAL:** PHYSICAL STATE: DISPOSE IN COMPLIANCE WITH GOVERNMENT SEMI-SOLID REGULATIONS AND LOCAL REQUIREMENTS. SPECIFIC GRAVITY: STORAGE REQUIREMENTS: COOL, DRY AREA, AWAY FROM SOURCES OF HEAT. 2.4 g./c.c. **BOILING POINT: SECTION 8 FIRST AID MEASURES** 260°C+ (500°F) SKIN-SOLUBILITY: WASH THOROUGHLY WITH SOAP AND WARM WATER NONE **SECTION 4 FIRE & EXPLOSION HAZARDS** FLUSH WITH WATER FOR AT LEAST 15 MINUTES USE WATER ONLY AS A FOG. "FIRE FIGHTERS SHOULD USE SELF-VAPOUR PRESSURE IS NEGLIGIBLE. REMOVE VICTIM FROM CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE **FURTHER EXPOSURE** OPERATED IN POSITIVE PRESSURE DEMAND. INGESTION: **UNUSUAL FIRE & EXPLOSION HAZARDS:** DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION NONE IMMEDIATELY. PREPARATION DATE FLASH POINT: **SECTION 9** GREATER THAN 171°C (340°F) ASTM D-92 PREPARED BY: ALAN S. HUEHN **GENERAL MANAGER EXTINGUISHING AGENTS:** TOPCO OILSITE PRODUCTS LTD. DRY CHEMICAL, WATERFOG, CO2, FOAM, SAND/EARTH DATE: March 1, 2011 **SECTION 5** REACTIVITY DATA

THE DATA PRESENTED HEREIN IS BELIEVED ACCURATE FOR THE SPECIFIC MATERIAL BUT IS IN NO WAY GUARANTEED. THE INFORMATION HEREIN MAY NOT BE APPLICABLE IF THE SPECIFIC MATERIAL IS USED IN COMBINATION WITH OTHER MATERIAL. TOPCO SALES ASSUMES NO RESPONSIBILITY AND MAKES NO WARRANTY IN CONNECTION WITH ANY USE FOR THE SPECIFIC MATERIAL. OTHER OR ADDITIONAL SAFETY MEASURES TO THOSE INDICATED MAY BE REQUIRED. THE USSER, THEREFORE,

ASSUMES FULL RESPONSIBILTY, BOTH AS TO PERSONS AND AS TO PROPERTY, FOR THE USE OF THESE MATERIALS

PRODUCT NOT TDG REGULATED AS PER WHMIS STANDARD.

CHEMICAL STABILITY: YES

STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON MONOXIDE. CARBON DIOXIDE. OXIDES OF LEAD

INCOMPATIBILITY: