

Marine Enamel Gloss Alkyd Rust-Resistant White Base**Section 1: MANUFACTURER/PREPARER INFORMATION & HAZARD WARNINGS**

Cloverdale Paint Inc.
6950 King George Hwy.,
Surrey, BC, Canada.

EMERGENCY PHONE
(613) 996-6666

INFORMATION PHONE
(604) 596-6261

DATE ISSUED/REVISED
Sep 16, 2004

LAST VALIDATED ON
Aug 20, 2010

WHMIS HAZARD SYMBOLS & DEFINITIONS

Class B: Combustible & flammable material

Class D-2: Poisonous & infectious material, other toxic effects

Section 2: HEALTH HAZARD DATA**ROUTES OF ENTRY/SIGNS & SYMPTOMS OF ACUTE EXPOSURE:**

EYES: May cause severe irritation, tearing, redness and blurred vision. **SKIN:** May cause irritation. May dry and defat skin causing cracks, irritation and dermatitis. **INHALATION:** May cause respiratory irritation, dizziness, breathing difficulty, headaches and loss of co-ordination. **INGESTION:** May cause gastrointestinal irritation, vomiting, nausea and diarrhea.

Chronic Effects: No chronic health hazards. **Carcinogens:** None reported. **Medical Conditions Aggravated by Exposure:** Anesthesia, respiratory tract irritation, dermatitis, nausea, vomiting.

EMERGENCY & FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes. Seek medical attention. **SKIN:** Wash thoroughly with mild soap and water. **INHALATION:** Move person to fresh air. If breathing stops, apply artificial respiration and seek immediate medical attention. **INGESTION:** Do not induce vomiting. Aspiration of solvents in this product can cause inflammation of the lungs.

Section 3: PREVENTATIVE MEASURES

Respiratory Protection: NIOSH approved for organic vapours and particulate matter.

Ventilation: General mechanical ventilation or local exhaust should be suitable to keep vapour concentrations below TLV. Ventilation equipment must be explosion proof. Make up air should be supplied to balance air exhausted

Gloves: Solvent impervious e.g. Viton, Nitrile, PVC. **Eye Protection:** Chemical safety glasses, goggles or face shield. **Other Protective Measures:** Use impermeable aprons and protective clothing whenever possible to prevent skin contact.

Work/Hygienic Practices: Launder contaminated clothing prior to re-use. Use good personal hygiene. Eye washes and safety showers in the workplace are recommended.

Handling and Storing: Combustible. Store in a cool, dry, well ventilated area away from heat and ignition sources. Keep containers closed when not in use. Avoid breathing vapours or mist and prolonged or repeated contact with skin. Product is a static accumulator. Transfer equipment should be grounded or bonded. **OTHER PRECAUTIONS:** Smoking in the area where this material is used must be strictly prohibited.

KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS.

N/A=Not Applicable. N/E=Not Evaluated/Established. N/R=Not Reported by Manufacturer.

Continued on Page 2

Section 4: HAZARDOUS COMPONENTS & EXPOSURE LIMITS

Hazardous Component Name	CAS #	OSHA PEL	ACGIH-TLV	Other Limit	% Wt
Stoddard Solvent	8052-41-5	N/R	100 ppm	N/R	15-40

§ indicates a toxic chemical subject to the reporting requirements of SARA Title III, Section 313.

† indicates a chemical known to the State of California to cause cancer, birth defects or other reproductive harm per Proposition 65.

Section 5: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	N/E	Specific Gravity:	1.13
Vapor Pressure:	N/E	Percent Volatile:	N/E
Vapor Density (Air=1):	>1	Evaporation Rate:	n-Butyl Acetate=slower
Solubility in Water:	Insoluble	pH:	N/A
Appearance/Odor:	Moderately thick liquid/Aromatic odour.		

Section 6: FIRE & EXPLOSION HAZARD DATA

Flash Point (Method):	42°C (TCC) FLAMMABLE	Flammable Limits. LEL: 1.0%	UEL: 6.0%
Extinguishing Media:	Foam, CO ₂ , dry chemical, water fog.		

Special Firefighting Procedures: Respiratory equipment should be worn to avoid inhalation of concentrated vapours. Water should not be used except as a fog to keep nearby containers cool.

Unusual Fire and Explosion Hazards: Handle as a combustible liquid. Vapours form an explosive mixture in air between the upper and lower explosive limits which can be ignited by many sources such as pilot lights, open flames, electrical boxes and switches. Vapours may travel along the ground and flashback along vapour trail may occur.

Section 7: REACTIVITY DATA

Stability: Stable. **Hazardous Polymerisation:** Will not occur. **Conditions to Avoid:** Excessive heat, poor ventilation, corrosive atmospheres, excessive aging. **Incompatibility:** Alkaline materials, strong acids and oxidizing agents. **Hazardous Decomposition Products:** Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen.

Section 8: SPILLS, DISPOSAL & ADDITIONAL INFORMATION

Spill/Leak Procedures: Eliminate ignition sources. Provide good ventilation or wear appropriate breathing apparatus. Absorb small spills with non-flammable absorbent. Contain spills by diking with non-flammable absorbent. Notify environmental agency.

Waste Disposal: Reclaim or dispose of through a licensed waste disposal company according to Federal, Provincial and local regulations.

Additional Information: HMIS Hazard Codes (U.S.): Health-1, Flammability-1, Reactivity-1.

This MSDS has been compiled in good faith by MSDS Rx from original manufacturer's data to comply with US OSHA and WHMIS regulations. Any variation between this MSDS and the manufacturer's original MSDS is the sole responsibility of MSDS Rx. Since the conditions under which this product may be used are beyond our control, neither MSDS Rx, its client, or the manufacturer assumes any liability for any results or effects of its use or application. Email MSDS Rx at info@msdsrx.com. E&OE.