



POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

POLY-DRILL PD1300

STATEMENT OF HAZARDOUS NATURE

Not considered a hazardous substance according to the Controlled Products Regulations

SUPPLIER


Company: Poly- Drill
Address:
2192 - 8800 Venture Ave SE
Calgary
Alberta, T3S 0A2
CAN
Telephone: +1 403 259 5112
Emergency Tel: +1 403 540 7080
Fax: +1 403 255 7185

PRODUCT USE

Flocculant.

Section 2 - HAZARDS IDENTIFICATION

CHEMWATCH HAZARD RATINGS



CANADIAN WHMIS SYMBOLS

None

EMERGENCY OVERVIEW

RISK

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet

Review Date: 9-Oct-2008

NA517EC

CHEMWATCH 15-6632

Version No:2.0

CD 2010/1 Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.

EYE

■ Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).

SKIN

■ The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.

■ The liquid may be miscible with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives .

■ The material may accentuate any pre-existing dermatitis condition.

INHALED

■ The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.

■ Inhalation hazard is increased at higher temperatures.

■ Not normally a hazard due to non-volatile nature of product.

■ Inhalation of oil droplets/ aerosols may cause discomfort and may produce chemical pneumonitis.

CHRONIC HEALTH EFFECTS

■ Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
mineral oil	Not avail.	

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- Seek medical advice.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 3 of 10
Section 4 - FIRST AID MEASURES

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.
- Transport to hospital, or doctor.

NOTES TO PHYSICIAN

- Treat symptomatically.
- Heavy and persistent skin contamination over many years may lead to dysplastic changes. Pre-existing skin disorders may be aggravated by exposure to this product.
- In general, emesis induction is unnecessary with high viscosity, low volatility products, i.e. most oils and greases.
- High pressure accidental injection through the skin should be assessed for possible incision, irrigation and/or debridement.

NOTE: Injuries may not seem serious at first, but within a few hours tissue may become swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Product may be forced through considerable distances along tissue planes.

Section 5 - FIRE FIGHTING MEASURES

Vapour Pressure (kPa): Not Available
Upper Explosive Limit (%): Not Available
Specific Gravity (water=1): 1.05
Lower Explosive Limit (%): Not Available

EXTINGUISHING MEDIA

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.
- Use water delivered as a fine spray to control fire and cool adjacent area.
- Avoid spraying water onto liquid pools.
- Do not approach containers suspected to be hot.
- Cool fire exposed containers with water spray from a protected location.
- If safe to do so, remove containers from path of fire.

GENERAL FIRE HAZARDS/HAZARDOUS COMBUSTIBLE PRODUCTS

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632

Version No:2.0

CD 2010/1 Page 4 of 10

Section 5 - FIRE FIGHTING MEASURES

Combustion products include: carbon dioxide (CO₂), nitrogen oxides (NO_x), other pyrolysis products typical of burning organic material.

CARE: Water in contact with hot liquid may cause foaming and a steam explosion with wide scattering of hot oil and possible severe burns. Foaming may cause overflow of containers and may result in possible fire.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

PERSONAL PROTECTION

Glasses:
Chemical goggles.

Gloves:
When handling larger quantities:

Respirator:
Type A Filter of sufficient capacity

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Slippery when spilt.
- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal.

MAJOR SPILLS

- Slippery when spilt.
- Moderate hazard.
- Clear area of personnel and move upwind.
 - Alert Fire Brigade and tell them location and nature of hazard.
 - Wear breathing apparatus plus protective gloves.
 - Prevent, by any means available, spillage from entering drains or water course.
 - No smoking, naked lights or ignition sources.
 - Increase ventilation.
 - Stop leak if safe to do so.
 - Contain spill with sand, earth or vermiculite.
 - Collect recoverable product into labelled containers for recycling.
 - Absorb remaining product with sand, earth or vermiculite.
 - Collect solid residues and seal in labelled drums for disposal.
 - Wash area and prevent runoff into drains.
 - If contamination of drains or waterways occurs, advise emergency services.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.
- DO NOT enter confined spaces until atmosphere has been checked.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.
- Keep containers securely sealed when not in use.

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 5 of 10
Section 7 - HANDLING AND STORAGE

- Avoid physical damage to containers.
- Always wash hands with soap and water after handling.
- Work clothes should be laundered separately.
- Use good occupational work practice.
- Observe manufacturer's storing and handling recommendations.
- Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.

RECOMMENDED STORAGE METHODS

- Metal can or drum
- Packaging as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

STORAGE REQUIREMENTS

- Store in original containers.
- Keep containers securely sealed.
- No smoking, naked lights or ignition sources.
- Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- Observe manufacturer's storing and handling recommendations.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



+: May be stored together
O: May be stored together with specific precautions
X: Must not be stored together

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

US OSHA Permissible Exposure Levels (PELs)

Z	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	Max excursion ppm	Max excursion mg/m ³	Max excursion duration (mins)	TWA F/CC
---	----------	------------	--------------------------	-------------	---------------------------	-------------	---------------------------	-------------------------	---------------------------------------	--	-------------

Z1 Oil mist, mineral

5

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Notes
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	mineral oil (Mineral oil (mist))		5		10	

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 6 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Notes
Canada - Northwest Territories Occupational Exposure Limits (English)	mineral oil (Oil Mist, mineral)		5		10	
US NIOSH Recommended Exposure Limits (RELs)	mineral oil (Oil mist (mineral))		5		10	
US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants	mineral oil (Oil mist, mineral)		5			
Canada - Ontario Occupational Exposure Limits	mineral oil (Oil, mineral - Mist)		5		10	
Canada - Alberta Occupational Exposure Limits	mineral oil (Oil mist, mineral)		5		10	
US - Idaho - Limits for Air Contaminants	mineral oil (Oil mist, mineral)		5			
US - Vermont Permissible Exposure Limits Table Z- 1- A Transitional Limits for Air Contaminants	mineral oil (Oil mist, mineral)		5			
US - Vermont Permissible Exposure Limits Table Z- 1- A Final Rule Limits for Air Contaminants	mineral oil (Oil mist, mineral)		5			
US - Alaska Limits for Air Contaminants	mineral oil (Oil mist, mineral)		5			
Canada - Nova Scotia Occupational Exposure Limits	mineral oil (Oil mist - mineral)		5		10	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mineral oil (Oil mist, mineral)	-	5	-	10	
US - Washington Permissible exposure limits of air contaminants	mineral oil (Oil mist mineral (particulate))		5		10	
Canada - Prince Edward Island Occupational Exposure Limits	mineral oil (Oil mist - mineral)		5		10	TLV Basis: lung. As sampled by method that does not collect vapor.

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 7 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Notes
Canada - British Columbia Occupational Exposure Limits	mineral oil (Oil mist - mineral, severely refined)		1			
US - Minnesota Permissible Exposure Limits (PELs)	mineral oil (Oil mist, mineral)		5			
US OSHA Permissible Exposure Levels (PELs) - Table Z1	mineral oil (Oil mist, mineral)		5			
US ACGIH Threshold Limit Values (TLV)	mineral oil (Oil mist - mineral)		5		10	TLV Basis: lung. As sampled by method that does not collect vapor.

MATERIAL DATA

POLY-DRILL PD1300:
Not available

MINERAL OIL:

■ Human exposure to oil mist alone has not been demonstrated to cause health effects except at levels above 5 mg/m³ (this applies to particulates sampled by a method that does not collect vapour). It is not advisable to apply this standard to oils containing unknown concentrations and types of additive.

PERSONAL PROTECTION



EYE

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

HANDS/FEET

- Wear general protective gloves, eg. light weight rubber gloves.

OTHER

- No special equipment needed when handling small quantities.

OTHERWISE:

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632

Version No:2.0

CD 2010/1 Page 8 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- Overalls.
- Barrier cream.
- Eyewash unit.

RESPIRATOR

■ Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Breathing Zone Level ppm (volume)	Maximum Protection Factor	Half- face Respirator	Full- Face Respirator
1000	10	A- AUS	-
1000	50	-	A- AUS
5000	50	Airline *	-
5000	100	-	A- 2
10000	100	-	A- 3
	100+		Airline**

* - Continuous Flow

** - Continuous-flow or positive pressure demand.

The local concentration of material, quantity and conditions of use determine the type of personal protective equipment required.

Use appropriate NIOSH-certified respirator based on informed professional judgement. In conditions where no reasonable estimate of exposure can be made, assume the exposure is in a concentration IDLH and use NIOSH-certified full face pressure demand SCBA with a minimum service life of 30 minutes, or a combination full facepiece pressure demand SAR with auxiliary self-contained air supply. Respirators provided only for escape from IDLH atmospheres shall be NIOSH-certified for escape from the atmosphere in which they will be used.

ENGINEERING CONTROLS

■ General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.

Mixes with water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	360-900 cps cSt@ 24°C
Boiling Range (°C)	96	Solubility in water (g/L)	Miscible
Flash Point (°C)	>93 (PMCC)	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	8
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	1.05
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	Not Available
Volatile Component (%vol)	23.97 (VOC)	Evaporation Rate	Not Applicable

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632
Version No:2.0
CD 2010/1 Page 9 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Off-white opaque liquid with a hydrocarbon odour; mixes with water.

Section 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

STORAGE INCOMPATIBILITY

- Avoid contamination of water, foodstuffs, feed or seed.

CARE: Water in contact with heated material may cause foaming or a steam explosion with possible severe burns from wide scattering of hot material. Resultant overflow of containers may result in fire.

- Avoid reaction with oxidising agents.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

Poly-Drill PD1300

TOXICITY AND IRRITATION

- unless otherwise specified data extracted from RTECS - Register of Toxic Effects of Chemical Substances.

TOXICITY

Oral (Rat) LD50: >5000 mg/kg

IRRITATION

Section 12 - ECOLOGICAL INFORMATION

Refer to data for ingredients, which follows:

POLY-DRILL PD1300:

1% aqueous solution of a similar product:

Sheepshead Minnow (96hrs) LC50: >1000 mg/l

Rainbow Trout (96hrs) LC50: >1000 mg/l

Daphnia magna (48hrs) LC50: 270 mg/l

MINERAL OIL:

- DO NOT discharge into sewer or waterways.

May be harmful to fauna if not disposed of according to Section 13 and legislative requirements. [AMC]

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Instructions

All waste must be handled in accordance with local, state and federal regulations.

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

continued...

POLY-DRILL PD1300

Chemwatch Material Safety Data Sheet
Review Date: 9-Oct-2008
NA517EC

CHEMWATCH 15-6632

Version No:2.0

CD 2010/1 Page 10 of 10

Section 13 - DISPOSAL CONSIDERATIONS

- Bury or incinerate residue at an approved site.
- Recycle containers if possible, or dispose of in an authorised landfill.

Section 14 - TRANSPORTATION INFORMATION

NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS: TDG, IATA, IMDG

Section 15 - REGULATORY INFORMATION

REGULATIONS

Regulations for ingredients

No data for Poly-Drill PD1300 (CW: 15-6632)

No data for mineral oil (CAS: , Not avail)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

Section 16 - OTHER INFORMATION

■ Classification of the mixture and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. A list of reference resources used to assist the committee may be found at:
www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

■ For detailed advice on Personal Protective Equipment, refer to the following Canadian Standards:

CAN/CSA-Z195 - Protective Footwear

Z195.1 - Guideline on Selection, Use, and Care of Protective Footwear

CAN/CSA-Z94.3 - Industrial Eye and Face Protectors

Z94.3.1 - Protective Eyewear User's Guide

CSA-Z94.4 - Selection, Use, and Care of Respirators

CAN/CSA-Z180.1 - Compressed Breathing Air and Systems.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 9-Oct-2008

Review Date: 9-Oct-2008

Print Date: 15-Feb-2010