# Material Safety Data Sheet

PETRO-CANADA ANTIFREEZE



#### 1. Product and company identification

: PETRO-CANADA ANTIFREEZE **Product name** 

: Universal Antifreeze, Radiator Antifreeze, Diesel Antifreeze, Petro-Canada Antifreeze-Synonym Coolant, Petro-Canada Heavy Duty Antifreeze-Coolant, Pre-Mix Antifreeze, Petro-

Canada Premium Radiator Antifreeze, Diesel Engine Coolant, Pre-Mixed Radiator

Antifreeze/Coolant Petro-Canada.

: W269 Code

**Material uses** : Used as an engine antifreeze coolant.

Manufacturer : PETRO-CANADA P.O. Box 2844

150 - 6th Avenue South-West

Calgary, Alberta

T2P 3E3

Petro-Canada: 403-296-3000 In case of emergency

Canutec Transportation: 613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

#### **Hazards identification** 2.

: Clear viscous liquid. **Physical state** 

**Odour** Odourless.

WHMIS (Canada)

Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

**OSHA/HCS** status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

**Emergency overview** : CAUTION!

> MAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.

> May be harmful if swallowed. Slightly irritating to the eyes and skin. Avoid exposure obtain special instructions before use. Do not breathe vapour or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that may cause target organ damage, based on animal data. Contains material which may cause birth defects, based on animal data. Contains material which may cause developmental

abnormalities, based on animal data. Avoid exposure during pregnancy. Wash thoroughly after handling.

**Routes of entry** 

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects **Inhalation** 

: Inhalation of this product may cause respiratory tract irritation.

: Harmful if swallowed. Ingestion of this product may cause gastro-intestinal irritation, Ingestion

nausea, vomiting, abdominal pain, and diarrhea. Ingestion of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe

overexposure; coma and death.

Skin Slightly irritating to the skin. Slightly irritating to the eyes. **Eyes** 

Potential chronic health effects

Date of issue: 3/11/2010. Internet: www.petro-canada.ca/msds Page: 1/7

Petro-Canada is a Suncor Energy business ™ Trademark of Suncor Energy Inc. Used under licence.

### 2. Hazards identification

**Chronic effects** 

: Contains material that may cause target organ damage, based on animal data.

Carcinogenicity

No known significant effects or critical hazards.

Mutagenicity

: No known significant effects or critical hazards.

Teratogenicity

: Contains material which may cause birth defects, based on animal data.

**Developmental effects** 

Contains material which may cause developmental abnormalities, based on animal data.

**Fertility effects** 

: No known significant effects or critical hazards.

**Target organs** 

: The substance may be toxic to kidneys and liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

## 3. Composition/information on ingredients

NameCAS number%Ethylene glycol107-21-145 - 50

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First-aid measures

**Eye contact** 

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

**Skin contact** 

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

 No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

Flammability of the product

: Non-flammable.

**Extinguishing media** 

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Petro-Canada is a Suncor Energy business

### 5. Fire-fighting measures

**Products of combustion** 

 Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Page Number: 3

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### 6. Accidental release measures

**Personal precautions** 

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### 8. Exposure controls/personal protection

Ingredient	Exposure limits
Ethylene glycol	ACGIH TLV (United States). CEIL: 100 mg/m³, (aerosol)

#### Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Date of issue: 3/11/2010. Internet: www.petro-canada.ca/msds Page: 3/7

Petro-Canada is a Suncor Energy business

### 8. Exposure controls/personal protection

#### **Engineering measures**

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Personal protection**

#### Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour filter

#### **Hands**

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Recommended: neoprene, nitrile, polyvinyl chloride (PVC). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they

should be changed.

#### **Eyes**

 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

#### Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

# Environmental exposure controls

Relative density

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### 9. Physical and chemical properties

Physical state : Clear viscous liquid.

Flash point : Not available.

Auto-ignition temperature : Not available.

Flammable limits : Not available.

Colour : Yellow.

Odour : Odourless.

Odour : Odourless.

Odour threshold : Not available.

pH : Not available.

Boiling/condensation point : 129°C (264.2°F)

Melting/freezing point : -37°C (-34.6°F)

Vapour pressure : 0.008 kPa (0.06 mm Hg)

Vapour density : 2.1 [Air = 1]
Volatility : Not available.
Evaporation rate : Not available.
Viscosity : Not available.
Pour point : Not available.

Date of issue : 3/11/2010. Internet: www.petro-canada.ca/msds

: 1.06 to 1.09

Page: 4/7

Petro-Canada is a Suncor Energy business

PETRO-CANADA ANTIFREEZE Page Number: 5

### 9. Physical and chemical properties

**Solubility** : Soluble in water, methanol and diethyl ether.

### 10. Stability and reactivity

Chemical stability

: The product is stable.

**Hazardous polymerisation** 

: Under normal conditions of storage and use, hazardous polymerisation will not occur.

**Materials to avoid** 

: Reactive with oxidising agents, acids and alkalis.

**Hazardous decomposition** 

: May release COx, smoke and irritating vapours when heated to decomposition.

products

## 11. Toxicological information

**Acute toxicity** 

Product/ingredient name Result Species Dose Exposure

Ethylene glycol LD50 Dermal Rabbit 9530 mg/kg - LD50 Oral Rat 4700 mg/kg -

LC50 Inhalation Rat 2725 mg/m³ 4 hours

Dusts and mists

Conclusion/Summary

: Not available.

**Chronic toxicity** 

**Conclusion/Summary**: Not available.

**Irritation/Corrosion** 

**Conclusion/Summary**: Not available.

**Sensitiser** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

Classification

Product/ingredient name ACGIH IARC EPA NIOSH NTP OSHA

Ethylene glycol A4 - - - - - -

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Teratogenicity** 

**Conclusion/Summary**: Not available.

Reproductive toxicity

**Conclusion/Summary**: Not available.

## 12. Ecological information

**Environmental effects**: No known significant effects or critical hazards.

**Aquatic ecotoxicity** 

**Conclusion/Summary** : Not available.

**Biodegradability** 

**Conclusion/Summary**: Not available.

Petro-Canada is a Suncor Energy business ™ Trademark of Suncor Energy Inc. Used under licence.

### 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

### 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
DOT Classification	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Ethylene glycol based coolant)	9	III	***************************************	Special provisions In single containers of 5000 lbs capacity or less this product is exempt from DOT regulations (not regulated).

PG\*: Packing group

### 15. Regulatory information

**United States** 

**HCS Classification** : Target organ effects

<u>Canada</u>

WHMIS (Canada) : Class D-1B: Material causing immediate and serious toxic effects (Toxic).

Class D-2A: Material causing other toxic effects (Very toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### International regulations

Canada inventory : All components are listed or exempted.
United States inventory : All components are listed or exempted.

(TSCA 8b)

OCA ODJ


**Europe inventory** : Not determined.

### 16. Other information

**Label requirements** 

EMAY BE HARMFUL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA. POSSIBLE DEVELOPMENTAL HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE ADVERSE DEVELOPMENTAL EFFECTS, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Date of issue: 3/11/2010. Internet: www.petro-canada.ca/msds

Page: 6/7

Petro-Canada is a Suncor Energy business

### 16. Other information

National Fire Protection Association (U.S.A.)

**References** : Available upon request.

<sup>™</sup> Trademark of Suncor Energy Inc. Used under licence.

Date of printing : 3/11/2010.

Date of issue : 11 March 2010

Date of previous issue : No previous validation.

Responsible name : Product Safety - JDW

Indicates information that has changed from previously issued version.

For Copy of (M)SDS : Internet: www.petro-canada.ca/msds

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue: 3/11/2010. Internet: www.petro-canada.ca/msds Page: 7/7