Material Safety Data Sheet



PRODURO ™ TO-4+ XL SYNTHETIC BLEND LO-TEMP (TRANSMISSION/DRIVE TRAIN OIL)

Product and company identification 1.

: PRODURO ™ TO-4+ XL SYNTHETIC BLEND LO-TEMP (TRANSMISSION/DRIVE Product name

TRAIN OIL)

: PD4XLLT, 420-037 Code

Material uses : An SAE 0W-20 grade multipurpose transmission, hydraulic, wet brake and final drive fluid

intended for use where Caterpillar TO-4 quality oils are recommended.

: Petro-Canada Lubricants Inc. Manufacturer

2310 Lakeshore Road West

Mississauga, Ontario Canada L5J 1K2

: Suncor Energy: 403-296-3000 In case of emergency

Canutec Transportation: 613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

Hazards identification

Physical state : Viscous liquid.

Odour : Hydrocarbon.

: Not controlled under WHMIS (Canada). WHMIS (Canada)

: While this material is not considered hazardous by the OSHA Hazard Communication OSHA/HCS status

Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and

available for employees and other users of this product.

: No specific hazard. **Emergency overview**

: Dermal contact. Eye contact. Inhalation. Ingestion. Routes of entry

Potential acute health effects

: No known significant effects or critical hazards. Inhalation

: No known significant effects or critical hazards. Ingestion

: Slightly irritating to the skin. Skin : Slightly irritating to the eyes. Eyes

Potential chronic health effects

: No known significant effects or critical hazards. Chronic effects

: Not listed as carcinogenic by OSHA, NTP or IARC. Carcinogenicity

: No known significant effects or critical hazards. Mutagenicity

: No known significant effects or critical hazards. Teratogenicity

: No known significant effects or critical hazards. **Developmental effects**

: No known significant effects or critical hazards. Fertility effects

: Repeated or prolonged contact with spray or mist may produce chronic eye irritation and Medical conditions

severe skin irritation. Repeated skin exposure can produce local skin destruction or aggravated by overexposure

See toxicological information (Section 11)

3. Composition/information on ingredients

CAS number % Name

Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and synthetic hydrocarbons.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Internet: lubricants.petro-canada.ca/msds Date of issue: 8/19/2011.

™ Trademark of Suncor Energy Inc. Used under licence. Petro-Canada is a Suncor Energy business

PRODURO ™ TO-4* XL SYNTHETIC BLEND LO-TEMP (TRANSMISSION/DRIVE TRAIN OIL)

3. Composition/information on ingredients

The base oil may be a mixture of the following CAS#s: 8042-47-5, 64742-46-7, 64742-47-8, 64742-53-6, 64742-54-7, 64742-55-8, 72623-84-8, 72623-85-9, 72623-86-0, 72623-87-1, 178603-64-0, 178603-65-1, 178603-66-2, 445411-73-4

4. First-aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Page Number: 2

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product

: May be combustible at high temperature.

Extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

Suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Products of combustion

: Carbon oxides (CO, CO2), sulphur oxides (SOx), phosphorus oxides (POx), calcium oxides (CaOx), zinc oxides (ZnOx), nitrogen oxides (NOx), aldehydes, ketones, smoke and irritating vapours as products of incomplete combustion.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

: Low fire hazard. This material must be heated before ignition will occur.

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

6. Accidental release measures

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Date of issue : 8/19/2011.

Internet: lubricants.petro-canada.ca/msds

Page: 2/7

Petro-Canada is a Suncor Energy business

Page Number: 3

6. Accidental release measures

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Ingredient	Exposure limits			
Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and synthetic hydrocarbons.	ACGIH TLV (United States). Notes: (Mineral oil) TWA: 5 mg/m³, (Inhalable fraction) 8 hour(s).			

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour filter

Date of issue: 8/19/2011.

Internet: lubricants.petro-canada.ca/msds

Page: 3/7

Petro-Canada is a Suncor Energy business

Exposure controls/personal protection 8 .

: Chemical-resistant, impervious gloves complying with an approved standard should be Hands

worn at all times when handling chemical products if a risk assessment indicates this is

necessary.

Recommended: neoprene, nitrile, polyvinyl alcohol (PVA), Viton®.

: Safety eyewear complying with an approved standard should be used when a risk Eyes

assessment indicates this is necessary to avoid exposure to liquid splashes, mists or

: Personal protective equipment for the body should be selected based on the task being Skin

performed and the risks involved and should be approved by a specialist before handling

this product.

Environmental exposure

Melting/freezing point

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases,

fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

Physical and chemical properties 9 .

: Viscous liquid. Physical state

Flash point : Open cup: 209°C (408.2°F) [Cleveland.]

Auto-ignition temperature : Not available.

: Not available. Flammable limits

Colour : Amber. : Hydrocarbon. Odour : Not available. Odour threshold

: Not available. : Not available. Boiling/condensation point : Not available.

: 0.8519 kg/L @ 15°C (59°F) Relative density

: Not available. Vapour pressure Vapour density Not available. : Not available. Volatility : Not available. **Evaporation rate**

: 35.1 cSt @ 40°C (104°F), 7.4 cSt @ 100°C (212°F), VI=184 Viscosity

: -51°C (-60°F) Pour point : Insoluble in water. Solubility

10. Stability and reactivity

Chemical stability : The product is stable.

: Under normal conditions of storage and use, hazardous polymerisation will not occur. Hazardous polymerisation

: Reactive with oxidising agents and acids. Materials to avoid

: May release COx, CaOx, SOx, POx, ZnOx, H2S, aldehydes, alkyl mercaptans, sulfides, Hazardous decomposition methacrylate monomers, smoke and irritating vapours when heated to decomposition. products

11. Toxicological information

Acute toxicity

Dose Exposure Result Species Product/ingredient name

Date of issue: 8/19/2011. Internet: lubricants.petro-canada.ca/msds ™ Trademark of Suncor Energy Inc. Used under licence.

Petro-Canada is a Suncor Energy business

PRODURO ™ TO-4* XL SYNTHETIC BLEND LO-TEMP (TRANSMISSION/DRIVE TRAIN

Page Number: 5

11. Toxicological information

Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and

LD50 Dermal

Rabbit

>2000 mg/kg

synthetic hydrocarbons.

LD50 Oral LC50 Inhalation

Dusts and mists

Rat >5000 mg/kg Rat >5.2 mg/l

4 hours

Conclusion/Summary

: Not available.

Chronic toxicity

Conclusion/Summary

: Not available.

Irritation/Corrosion

Conclusion/Summary

: Not available.

Sensitiser

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Classification

Product/ingredient name

ACGIH

A4

IARC

EPA

NIOSH

NTP

OSHA

Mixture of severely hydrotreated and

hydrocracked base oil (petroleum) and

synthetic hydrocarbons.

Mutagenicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary

: Not available.

12. Ecological information

Environmental effects

: No known significant effects or critical hazards.

Aquatic ecotoxicity

Conclusion/Summary

: Not available.

Biodegradability

Conclusion/Summary

: Not available.

Other adverse effects

No known significant effects or critical hazards.

Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Date of issue: 8/19/2011.

Internet: lubricants.petro-canada.ca/msds

Petro-Canada is a Suncor Energy business

PRODURO ™ TO-4" XL SYNTHETIC BLEND LO-TEMP (TRANSMISSION/DRIVE TRAIN

OIL)

Page Number: 6

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	Not regulated.	-	-	-		-
DOT Classification	Not available.	Not available.	Not available.	-		-

PG*: Packing group

15 . Regulatory information

United States

HCS Classification

: Not regulated.

Canada

WHMIS (Canada)

: Not controlled under WHMIS (Canada).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

Canada inventory

: All components are listed or exempted.

United States inventory

: All components are listed or exempted.

(TSCA 8b) Europe inventory

: All components are listed or exempted.

16. Other information

Hazardous Material Information System (U.S.A.)

1 Health 1 **Flammability** 0 Physical hazards В Personal protection

National Fire Protection Association (U.S.A.)

Flammability Health ' Instability Special

References

Available upon request.

™ Trademark of Suncor Energy Inc. Used under licence.

Date of printing

: 8/19/2011.

Date of issue

: 19 August 2011

Date of previous issue

: 6/1/2009.

Responsible name

Indicates information that has changed from previously issued version.

: Product Safety - DSR

For Copy of (M)SDS

: The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Date of issue: 8/19/2011.

Internet: lubricants.petro-canada.ca/msds

Page: 6/7

Petro-Canada is a Suncor Energy business

16. Other information

Internet: lubricants.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: 1-800-378-4518 Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of issue: 8/19/2011.

Petro-Canada is a Suncor Energy business

Page: 7/7

™ Trademark of Suncor Energy Inc. Used under licence.

Internet: lubricants.petro-canada.ca/msds