Polaris Sales Inc. **Emergency:** 800-424-9300

2100 Highway 55 Medina, MN 55340 Information: 763-542-0500

**SECTION 1** CHEMICAL PRODUCT IDENTIFICATION

**POLARIS ANTIFREEZE 50/50 PRE-MIX PG** Product:

Synonyms/Other: Not applicable.

Part Number: 2875041, 2875042, 8570099

**MSDS Number:** 

**Product Type:** Propylene glycol based coolant/antifreeze

Preparation/Revision Date: 07/30/2007

**SECTION 2** COMPOSITION INFORMATION **INGREDIENTS** CAS# **OSHA OSHA ACGIH** SKIN % **TWA STEL** TWA Propylene Glycol 57-55-6 47-48 Not Not Not NO established established established Proprietary additives 0.5 - 1.5Not Not Not NO established established established Water 7732-18-5 49 NO Comments: Not applicable.

**SECTION 3 HAZARDOUS IDENTIFICATION** 

Direct contact may cause irritation, redness, tearing and blurred vision. Eye contact:

Skin contact: Prolonged contact may cause skin irritation.

Inhalation: Information not available.

Ingestion: Slightly toxic by ingestion; ingesting large amounts may cause central nervous

system effects.

**SECTION 4** FIRST AID MEASURES

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Hold

eyelids apart while flushing to rinse entire surface of eye and lids with water.

Get medical attention.

Skin contact: Wash skin with soap and water.

Inhalation: If irritation, headache, nausea, or drowsiness occurs, remove to fresh air. Get

medicla attention if breathing becomes difficult or respiratory irritation persists. If large quantity is ingested give a pint of water and induce vomiting only if

Ingestion:

victim is completely conscious and alert. Seek immediate medical attention.

**SECTION 5** FIRE FIGHTING MEASURES

Flash point: None

Flammable limits: Not applicable.

Extinguishing media: Use water spray, dry chemical, alcohol-resistant foam, all purpose AFFF or

carbon dioxide to extinguish fire.

Special firefighting procedures:

Evacuate area and fight fire from a safe distance. If leak or spill has not ignited, ventilate area and use water spray to disperse gas or vapor and to protect

personnel attempting to stop a leak.

Use water spray to cool adjacent structures and to protect personnel. Shut off source of flow if possible (safely). Stay away from storage tank ends. Withdraw immediately in case of rising sound from venting safety device or any discoloration of storage tank due to fire.

Fire fighters must wear MSHA/NIOSH approved positive pressure breathing

apparatus (SCBA) with full face mask and full protective equipment.

**Unusual fire &** explosion hazards:

Dense smoke may be generated while burning. Toxic fumes, gases or vapors may evolve on burning. Heavy flammable vapors may settle along ground level and low spots to create an invisible fire hazard. The vapors may extend to

sources of ignition and flash back.

Byproducts of

combustion: Fires involving this product may release COx, NOx, SOx, reactive hydrocarbons

and irritating vapors.

Autoignition

temperature: Information not available.

**Explosion data:** Not determined. Care should always be exercised in dust/mist areas.

Other: Not applicable

#### **SECTION 6** ACCIDENTAL RELEASE MEASURES

Spill control Contain fluid with noncombustible absorbent material and place into container procedures (land):

for disposal. For large spills: Contain fluid with noncombustible absorbent material. Use plastic shovel to put material into containers. Eliminate all sources of ignition. Prevent fluid from running into storm sewers or natural

waterways.

Spill control

procedures (water): Material will readily mix with water. If a large spill occurs notify appropriate

authorities (normally the National Response Center or Coast Guard).

Dispose according to applicable local, state and federal laws. Contact local or Waste disposal

method: state agencies to obtain information on recycling.

Other: Not applicable.

#### **SECTION 7 HANDLING AND STORAGE**

Handling procedures: Wash thoroughly after handling. Store containers closed and away from

extreme temperatures. Keep out of the reach of children.

#### **EXPOSURE CONTROLS / PERSONAL PROTECTION SECTION 8**

Applicable mainly to persons in repeated contact situations such as packaging Personal protection:

of product, service/maintenance, and cleanup/spill control personnel.

Respiratory protection: None special.

Eye protection: Chemical goggles or face shield.

Hand protection: Impervious gloves such as neoprene or nitrile rubber to avoid skin sensitization

and absorption.

Other protection: Use of an apron and overboots of chemically impervious materials such as

neoprene or nitrile rubber is recommended.

Local control

measures: Use adequate ventilation when working with material in an enclosed area.

Mechanical methods such as fume hoods or area fans may be used to reduce

localized vapor/mist areas.

Other: Consumption of food and drink should be avoided in work areas where product

is present. Always wash hands and face with soap and water before eating,

drinking or smoking.

#### **SECTION 9** PHYSICAL AND CHEMICAL PROPERTIES

Vapor pressure: <0.1 mmHg API gravity: Not determined. Specific gravity: Not determined.

Solubility in water: 100%

Percent volatile(VOC):

**Evaporation rate** 

Not applicable.

(n-Butyl Acetate=1): Not applicable. Appearance: Clear pink liquid Viscosity: Not determined.

221F **Boiling point:** 

PH: 10.5-10.8

**SECTION 10** STABILITY AND REACTIVITY

Stability: Material is stable at room temperatures and pressure. Conditions to avoid: Avoid high temperatures and product contamination.

Incompatibility with

other materials: Avoid contact with acids and oxidizing materials. Also avoid contact with

caustics and aliphatic amines.

Decomposition

products: Smoke, carbon monoxide, carbon dioxide, reactive hydrocarbons and irritating

vapors.

Hazardous

Will not occur. polymerization: Other: Not applicable.

#### **SECTION 11 TOXICOLOGICAL INFORMATION**

Oral toxicity: May cause general anesthesia, convulsions and changes in surface EEG.

**Dermal toxicity:** Contact may result in skin irritation.

Inhalation toxicity: Information not available.

Carcinogenicity/Chronic

Material contains items not listed by OSHA, IARC or NTP.

toxicity:

Mutagenicity: Information not available. Reproductive toxicity: Information not available.

### **ECOLOGICAL INFORMATION SECTION 12**

**Environmental toxicity:** Information not available. **Environmental fate:** Information not available.

#### **DISPOSAL CONSIDERATIONS SECTION 13**

Waste disposal

method:

Dispose according to applicable local, state and federal laws. Contact local or

state agencies to obtain information on recycling.

#### **SECTION 14** TRANSPORT INFORMATION

U.S. DOT shipping

description:

Not regulated

U.S. DOT identification

number: U.S. DOT hazard Not applicable

Not applicable. classification:

Packaging class: Not applicable.

#### **SECTION 15 REGULATORY INFORMATION**

Clean water act/oil

pollution act: Contact the National Response Center at 800-424-8802 in the case of a spill

that enters waterways.

SARA Title III: Section 302/304 extremely hazardous substances: None

**OSHA Regulations:** This product contains propylene glycol that is an OSHA regulated hazardous

substance.

Section 311, 312 hazard categorization:

Acute (immediate health effects): YES Chronic (delayed health effects): NO Fire (hazard): NO Reactivity (hazard): NO Pressure (sudden release hazard): NO

Section 313 toxic chemicals: None

**CERCLA:** For stationary sources – reportable quantity:

Not applicable.

For moving sources - reportable quantity:

Not applicable.

SECTION 16	OTHER INFORMATION		
	NFPA 704	NPCA-HMIS	KEY
HEALTH:	0	0	0 = Minimal
FIRE:	1	1	1 = Slight
REACTIVITY:	0	0	2 = Moderate
SPECIFIC HAZARD:	N/A	N/A	3 = Serious
PROTECTION INDEX:	N/A	В	4 = Severe

This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used. Polaris must rely on information provided by those materials manufacturers or distributors.

Creation date: 02/26/2004

File: Polaris Antifreeze 50/50 Pre-Mix PG (1449)

Version:

INFORMATION PROVIDED IN THIS MSDS IS CONSIDERED ACCURATE AND RELIABLE BASED ON INFORMATION ISSUED FROM INTERNAL AND OUTSIDE SOURCES TO THE BEST OF POLARIS'S KNOWLEDGE. HOWEVER, POLARIS MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, OF MERCHANTABILITY OR FITNESS FOR THE PARTICULAR PURPOSE, REGARDING THE ACCURACY OF SUCH INFORMATION OR THE RESULT TO BE OBTAINED FROM THE USE THEREOF, OR AS TO THE SUFFICIENCY OF THE INFORMATION HEREIN PRESENTED. POLARIS ASSUMES NO RESPONSIBILITY FOR INJURY TO RECIPIENT OR TO THIRD PERSONS OR FOR ANY DAMAGE TO ANY PROPERTY AND RECIPIENT ASSUMES ALL SUCH RISKS.

Revisions / Comments: MSDS reviewed: 07/30/2007