

MATERIAL SAFETY DATA SHEET

WHMIS HAZARD INDEX: D2A 0 INSIGNIFICANT 1 SLIGHT 2 MODERATE 3 HIGH 4 EXTREME	PRODUCT CODE: FIRE 1 REACTIVITY 0 SPECIAL 0 TOXICITY 1								
SECTION 1 LOCATION <div style="text-align: center;"> TOPCO OILSITE PRODUCTS LTD. BAY 5, 3401 – 19 STREET N.E. CALGARY, ALBERTA CANADA T2E 6S8 PHONE (403) 219-0255 FAX (403) 291-3042 </div>	SECTION 6 TOXICOLOGY ROUTE OF ENTRY: SKIN & EYE CONTACT. CHRONIC EFFECTS: MAY CAUSE IRRITATION AND POSSIBLE DERMATITIS IN SENSITIVE INDIVIDUALS ACUTE TOXICOLOGY: NO DATA AVAILABLE								
TRADE NAME: ZINCOTE MATERIAL USE: LUBRICATE & SEAL TOOL JOINT THREADS	SECTION 7 PREVENTION MEASURES GLOVES: RUBBER OR CLOTH EYE PROTECTION: GOGGLES RECOMMENDED VENTILATION: LOCAL EXHAUST RESPIRATORY PROTECTION: NONE REQUIRED LEAK & SPILL PROCEDURE: PREVENT MATERIAL FROM ENTERING WATERCOURSES BY CONTAINING WITH SAND OR EARTH. WASTE DISPOSAL: DISPOSE IN COMPLIANCE WITH GOVERNMENT REGULATIONS AND LOCAL REQUIREMENTS. STORAGE REQUIREMENTS: COOL, DRY AREA, AWAY FROM SOURCES OF HEAT								
SECTION 2 HAZARDOUS INGREDIENTS <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left; border-bottom: 1px solid black;">COMPOSITION</th> <th style="text-align: center; border-bottom: 1px solid black;">APPROX. CONCENTRATION</th> <th style="text-align: center; border-bottom: 1px solid black;">C.A.S.</th> <th style="text-align: center; border-bottom: 1px solid black;">EXP.LIMITS</th> </tr> </thead> <tbody> <tr> <td>ZINC DUST</td> <td style="text-align: center;">40% - 60%</td> <td style="text-align: center;">7440-66-6</td> <td style="text-align: center;">N/A</td> </tr> </tbody> </table>	COMPOSITION	APPROX. CONCENTRATION	C.A.S.	EXP.LIMITS	ZINC DUST	40% - 60%	7440-66-6	N/A	SECTION 8 FIRST AID MEASURES SKIN: WASH THOROUGHLY WITH SOAP AND WARM WATER EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES INHALATION: VAPOUR PRESSURE IS NEGLIGIBLE. REMOVE VICTIM FROM FURTHER EXPOSURE INGESTION: DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION IMMEDIATELY.
COMPOSITION	APPROX. CONCENTRATION	C.A.S.	EXP.LIMITS						
ZINC DUST	40% - 60%	7440-66-6	N/A						
SECTION 3 CHEMICAL & PHYSICAL PROPERTIES NAME: PETROLEUM HYDROCARBON WITH ADDITIVES ODOUR: MILD PETROLEUM COLOUR: LIGHT GREY PASTE PHYSICAL STATE: SEMI-SOLID SPECIFIC GRAVITY: 1.6 g./c.c. BOILING POINT: 260°C + (500°F) SOLUBILITY: NONE	SECTION 9 PREPARATION DATE PREPARED BY: ALAN S. HUEHN GENERAL MANAGER TOPCO OILSITE PRODUCTS LTD. DATE: March 1, 2011								
SECTION 4 FIRE & EXPLOSION HAZARDS PROCEDURES: USE WATER ONLY AS A FOG. "FIRE FIGHTERS SHOULD USE SELF-CONTAINED BREATHING APPARATUS WITH FULL FACE PIECE OPERATED IN POSITIVE PRESSURE DEMAND. UNUSUAL FIRE & EXPLOSION HAZARDS: NONE FLASH POINT: GREATER THAN 171°C (340°F) ASTM D-92 EXTINGUISHING AGENTS: DRY CHEMICAL, WATERFOG, CO2, FOAM, SAND/EARTH	PRODUCT NOT TDG REGULATED AS PER WHMIS STANDARD.								
SECTION 5 REACTIVITY DATA CHEMICAL STABILITY: YES INCOMPATIBILITY STRONG OXIDIZING AGENTS HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE, CARBON DIOXIDE, OXIDES OF ZINC									
THE DATA PRESENTED HEREIN IS BELIEVED ACCURATE FOR THE SPECIFIC MATERIAL BUT IS IN NO WAY GUARANTEED. THE INFORMATION HEREIN MAY NOT BE APPLICABLE IF THE SPECIFIC MATERIAL IS USED IN COMBINATION WITH OTHER MATERIAL. TOPCO SALES ASSUMES NO RESPONSIBILITY AND MAKES NO WARRANTY IN CONNECTION WITH ANY USE FOR THE SPECIFIC MATERIAL. OTHER OR ADDITIONAL SAFETY MEASURES TO THOSE INDICATED MAY BE REQUIRED. THE USER, THEREFORE, ASSUMES FULL RESPONSIBILITY, BOTH AS TO PERSONS AND AS TO PROPERTY, FOR THE USE OF THESE MATERIALS.									