# Material Safety Data Sheet

VULTREX TM API MODIFIED THREAD COMPOUND



### Product and company identification

: VULTREX TM API MODIFIED THREAD COMPOUND **Product name** 

: VULTHRD, 650-674 Code

Vultrex API Modified Thread Compound is used in drilling operations for the lubrication of **Material uses** 

casing, tubing, and line pipe, as protection for threads and as a sealant against drilling

fluids.

**Manufacturer** PETRO-CANADA

P.O. Box 2844

150 - 6th Avenue South-West

Calgary, Alberta

T2P 3E3

Petro-Canada: 403-296-3000 In case of emergency

Canutec Transportation:

613-996-6666

Poison Control Centre: Consult local telephone directory for emergency number(s).

#### Hazards identification 2

: Paste. **Physical state** 

**Odour** Light petroleum odour.

Class D-2A: Material causing other toxic effects (Very toxic). WHMIS (Canada)

Class D-2B: Material causing other toxic effects (Toxic).

**OSHA/HCS** status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

**Emergency overview** MAY CAUSE EYE AND SKIN IRRITATION. SUSPECT CANCER HAZARD -

CONTAINS MATERIAL WHICH MAY CAUSE CANCER. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA. POSSIBLE REPRODUCTIVE HAZARD. CONTAINS MATERIAL THAT MAY CAUSE ADVERSE REPRODUCTIVE EFFECTS. CONTAINS MATERIAL WHICH

CAN CAUSE HERITABLE GENETIC EFFECTS.

Slightly irritating to the eyes and skin. Avoid exposure - obtain special instructions before use. Do not breathe vapour or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Contains material which may cause cancer. Risk of cancer depends on duration and level of exposure. Contains material which can cause heritable genetic effects. Contains material which may cause birth defects, based on animal data. Avoid exposure during pregnancy. Contains material which may impair

male fertility, based on animal data. Wash thoroughly after handling.

**Routes of entry** 

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation

: No known significant effects or critical hazards.

Ingestion

: Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This may result in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (an accumulation of fluid in the lungs). Ingestion may produce a laxative effect.

Skin Slightly irritating to the skin. **Eves** Slightly irritating to the eyes.

Potential chronic health effects

**Chronic effects** : This product contains an ingredient or ingredients, which have been shown to cause

chronic toxic effects.

Carcinogenicity Contains material which may cause cancer. Risk of cancer depends on duration and

level of exposure.

Mutagenicity Contains material which can cause heritable genetic effects.

**Teratogenicity** Contains material which may cause birth defects, based on animal data.

**Developmental effects** : No known significant effects or critical hazards.

Date of issue: 6/29/2009. Internet: lubricants.petro-canada.ca/msds Page: 1/7

### 2. Hazards identification

**Fertility effects** 

Medical conditions aggravated by over-exposure

- : Contains material which may impair male fertility, based on animal data.
- : Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated skin exposure can produce local skin destruction or dermatitis.

See toxicological information (section 11)

# 3. Composition/information on ingredients

Name	CAS number	<u>%</u>
Lead, elemental	7439-92-1	<30
Graphite	7782-42-5	<20
Copper	7440-50-8	<10
Lime	1305-78-8	<10
Zinc	7440-66-6	11 - 13

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First-aid measures

Eye contact

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician

: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

# 5. Fire-fighting measures

Flammability of the product

: May be combustible at high temperature.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Products of combustion** 

: Carbon oxides (CO, CO2), smoke and irritating vapours as products of incomplete combustion.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on fire hazards

: Low fire hazard. This material must be heated before ignition will occur.

Date of issue : 6/29/2009.

Internet: lubricants.petro-canada.ca/msds

Page: 2/7

### 5. Fire-fighting measures

Special remarks on explosion hazards

: Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.

### 6. Accidental release measures

**Personal precautions** 

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods for cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### 7. Handling and storage

**Handling** 

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Storage** 

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

# 8. Exposure controls/personal protection

Ingredient	Exposure limits
Lead, elemental	ACGIH TLV (United States).
	TWA: 0.05 mg/m <sup>3</sup> 8 hour(s).
Graphite	ACGIH TLV (United States).
	TWA: 2 mg/m³ 8 hour(s). Form: Respirable fraction
Copper	ACGIH TLV (United States).
	TWA: 1 mg/m³ Form: Dust and mist as Cu
	TWA: 0.2 mg/m³ Form: Fume
Lime	ACGIH TLV (United States).
	TWA: 2 mg/m³ 8 hour(s).

Consult local authorities for acceptable exposure limits.

#### **Exposure controls/personal protection** 8.

**Recommended monitoring** procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

**Engineering measures** 

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### Personal protection

Respiratory

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: organic vapour filter

**Hands** 

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is

Recommended: neoprene, nitrile. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.

**Eyes** 

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

Colour

**Melting/freezing point** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Physical and chemical properties 9

**Physical state** : Paste.

Flash point Mineral Oil Blend: Open cup: 250°C (482°F) [Cleveland.]

**Auto-ignition temperature** >260°C (>500°F) Flammable limits : Lower: 0.9%

Upper: 7% Brown-black.

**Odour** Light petroleum odour.

**Odour threshold** Not available. pН : Not available. : >274°C (>525.2°F) **Boiling/condensation point** 

Not available. Relative density Mineral Oil Blend: 0.8741 kg/L @ 15°C (59°F)

Not available. Vapour pressure Vapour density Not available. **Volatility** Not available. **Evaporation rate** Not available.

**Viscosity** : Mineral Oil Blend: 103.3 cSt @ 40°C (104°F), 11.50 cSt @ 100°C (212°F), VI=98

Page: 4/7 Date of issue: 6/29/2009. Internet: lubricants.petro-canada.ca/msds

**VULTREX TM API MODIFIED THREAD COMPOUND** 

Page Number: 5

### 9. Physical and chemical properties

Pour Point : Mineral Oil Blend: -15°C (5°F)

Penetration : 325 (60 strokes) @ 25°C (77°F)

Dropping Point : 138°C (280°F)

Solubility : Insoluble in water.

## 10. Stability and reactivity

**Chemical stability** : The product is stable.

**Hazardous polymerisation**: Under normal conditions of storage and use, hazardous polymerisation will not occur.

**Materials to avoid** : Reactive with oxidising agents and acids.

Hazardous decomposition : May release COx, NOx, SOx, hydrocarbons, smoke and irritating vapours when heated

to decomposition.

# 11. Toxicological information

**Acute toxicity** 

products

**Conclusion/Summary** : Not available.

Chronic toxicity

**Conclusion/Summary**: Not available.

**Irritation/Corrosion** 

**Conclusion/Summary**: Not available.

**Sensitiser** 

**Conclusion/Summary**: Not available.

**Carcinogenicity** 

**Conclusion/Summary**: Not available.

**Classification** 

Product/ingredient nameACGIHIARCEPANIOSHNTPOSHALead, elementalA32AB-Possible-

**Mutagenicity** 

**Conclusion/Summary**: Not available.

**Teratogenicity** 

**Conclusion/Summary**: Not available.

Reproductive toxicity

**Conclusion/Summary**: Not available.

### 12. Ecological information

**Environmental effects**: No known significant effects or critical hazards.

**Aquatic ecotoxicity** 

Conclusion/Summary : Not available.

**Biodegradability** 

**Conclusion/Summary**: Not available.

Other adverse effects: No known significant effects or critical hazards.

### 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

### 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	UN3077	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Copper metal powder)	9	III		
<b>DOT Classification</b>	Not available.	Not available.	Not available.	-		-

PG\*: Packing group

### 15. Regulatory information

**United States** 

**HCS Classification** : Carcinogen

<u>Canada</u>

WHMIS (Canada)
 Class D-2A: Material causing other toxic effects (Very toxic).
 Class D-2B: Material causing other toxic effects (Toxic).

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

#### **EU regulations**

Hazard symbol or symbols



Risk phrases : R61- May cause harm to the unborn child.

R62- Possible risk of impaired fertility.

R20/22- Also harmful by inhalation and if swallowed.

R33- Danger of cumulative effects.

R50/53- Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases : S53- Avoid exposure - obtain special instructions before use.

S2- Keep out of the reach of children.

S45- In case of accident or if you feel unwell, seek medical advice immediately (show

the label where possible).

S60- This material and its container must be disposed of as hazardous waste.

S61- Avoid release to the environment. Refer to special instructions/safety data sheet.

International regulations

**Canada inventory** : All components are listed or exempted.

**VULTREX TM API MODIFIED THREAD COMPOUND** 

### Page Number: 7

### 15. Regulatory information

United States inventory

: All components are listed or exempted.

(TSCA 8b)

**Europe inventory** 


: All components are listed or exempted.

### 16. Other information

**Label requirements** 

: MAY CAUSE EYE AND SKIN IRRITATION. SUSPECT CANCER HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE CANCER. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA. POSSIBLE REPRODUCTIVE HAZARD. CONTAINS MATERIAL THAT MAY CAUSE ADVERSE REPRODUCTIVE EFFECTS. CONTAINS MATERIAL WHICH CAN CAUSE HERITABLE GENETIC EFFECTS.

Hazardous Material Information System (U.S.A.)



National Fire Protection Association (U.S.A.)



**References**: Available upon request.

TMMC Marque de commerce de Petro-Canada - Trademark

Date of printing : 6/29/2009.

Date of issue : 29 June 2009

Date of previous issue : No previous validation.

Responsible name : Product Safety - JDW

✓ Indicates information that has changed from previously issued version.

For Copy of (M)SDS : Internet: lubricants.petro-canada.ca/msds

Lubricants:

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850; fax: 1-800-201-6285 Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 1-800-201-6285

For Product Safety Information: (905) 804-4752

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.