03032008



HENKEL CANADA CORPORATION 6685 KENNEDY ROAD SUITE 1 MISSISSAUGA, ONTARIO CANADA L5T 3A5 (905) 696-2770

PRODUCT : LEPAGE PRES-TITE GREEN LATEX CONTACT CEMENT

SECTION 01: PRODUCT INFORMATION

MANUFACTURER.....HENKEL CANADA CORPORATION

6685 KENNEDY ROAD SUITE 1 MISSISSAUGA, ONTARIO

CANADA ; L5T 3A5 (905) 696-2770

AFTER HOURS - CANUTEC (613) 996-6666

WHMIS CLASSIFICATION.....NONE

T.D.G. CLASSIFICATION.....NOT REGULATED

PRODUCT NAME......LEPAGE PRES-TITE GREEN LATEX CONTACT CEMENT

CHEMICAL FAMILY......WATER BASED RUBBER LATEX MATERIAL USE........................WOODWORKING ADHESIVE

SECTION 02: HAZARDOUS INGREDIENTS

LD/50, ROUTE, SPECIES LC/50, ROUTE, SPECIES HAZARDOUS INGREDIENTS EXPOSURE LEVELS C.A.S. #

Considered non-hazardous as per WHMIS regulations.

Not available

SECTION 03: PHYSICAL DATA

PHYSICAL STATE.....Liquid

APPEARANCE & ODOUR.....Off-white liquid. Slight odour

ODOUR THRESHOLD (ppm) ... Not available VAPOUR PRESSURE (mm Hg) ... Not available VAPOUR DENSITY (AIR=1).....Not available

BY VOLUME BY WEIGHT

EVAPORATION RATE......Not available

BOILING POINT (deg C)......212 DEG F (100 DEG C) to 234 DEG F (112 DEG C)

pH.....Not available

SPECIFIC GRAVITY.....1.1 SOLUBILITY IN WATER (% W/W).....Miscible COEFFICIENT OF WATER/OIL.....Not available

DISTRIBUTION

SECTION 04: FIRE & EXPLOSION DATA

FLAMMABILITY......No

IF YES, UNDER WHICH

CONDITIONS?

EXTINGUISHING MEDIA......Carbon dioxide, dry chemical, foam

SPECIAL PROCEDURES......Firefighters should wear the usual protective gear; self-contained

breathing apparatus. FLASH POINT (C), METHOD.....Not applicable

AUTO IGNITION TEMPERATURE......Not available UPPER FLAMMABLE LIMIT (% VOL) ... Not applicable LOWER FLAMMABLE LIMIT (% VOL) ... Not applicable

HAZARDOUS COMBUSTION PRODUCTS....Carbon monoxide, carbon dioxide, chlorine compounds, hydrocarbons of

indeterminate nature (depending on conditions).

EXPLOSION DATA

SENSITIVITY TO STATIC......No

DISCHARGE

SENSITIVITY TO IMPACT.....No

SECTION 05: REACTIVITY DATA

COMPATIBILITY WITH OTHER SUBSTANCES:

NO, WHICH ONES?..... Materials that react with water, copper, zinc and their salts, all acids.

REACTIVITY CONDITIONS ?...... Reacts with acids to produce heat.

HAZARDOUS PRODUCTS OF......Stable under normal temperature and pressure. Oxides of carbon (CO,CO2) at

high temperatures. Chlorine compounds

TION 06: TOXICOLOGICAL PROPERTIES

ROUTE OF ENTRY:

SKIN CONTACT..... May cause mild irritation, especially on prolonged contact.

SKIN ABSORPTION......No data

EYE CONTACT..... May cause slight irritation.

# PRODUCT : LEPAGE PRES-TITE GREEN LATEX CONTACT CEMENT

#### SECTION 06: TOXICOLOGICAL PROPERTIES

INHALATION......High vapour concentrations are irritating to the eyes and the respiratory

tract.

INGESTION......May cause irritation of the gastrointestinal tract. EFFECTS OF ACUTE EXPOSURE......Possible skin, eye, and respiratory tract irritation. EFFECTS OF CHRONIC EXPOSURE.....May aggravate existing eye, skin, and lung conditions.

LD 50 OF MATERIAL, SPECIES &....Not available ROUTE

LC 50 OF MATERIAL, SPECIES &.... Not available

ROUTE

EXPOSURE LIMIT OF MATERIAL.....Not available

IRRITANCY OF MATERIAL...........Refer to route of entry SENSITIZING CAPABILITY OF.......Not applicable

MATERIAL

CARCINOGENICITY OF MATERIAL.....None known MUTAGENICITY OF MATERIAL.....Not available TERATOGENICITY OF MATERIAL.....Not available REPRODUCTIVE EFFECTS......Not available SYNERGISTIC MATERIALS.....Not available

### SECTION 07: PREVENTATIVE MEASURES

GLOVES/ TYPE......Protective rubber gloves to minimize skin contact.

RESPIRATORY/TYPE......None required under normal use. Use a NIOSH/MSHA approved respirator

whenever mist or spray is generated.

..... Safety glasses with side-shields

FOOTWEAR/TYPE...... Standard work shoes. CLOTHING/TYPE..... Standard work clothes.

LEAK/SPILL......Spills should be taken up with suitable absorbent and placed in

containers. Spill area can be washed with water; collect wash water for

approved disposal. Do not flush to storm sewer or waterway.

emptied container retains product residues all labelled hazard precautions must be observed.

HANDLING PROCEDURES AND.........Avoid contact with eyes, skin, and clothing. Use with adequate ventilation EQUIPMENT and employ respiratory protection where spray or mist may be generated.

Wash thoroughly after handling.

STORAGE NEEDS...... Keep container closed when not in use. Store in a cool and dry place, for

product integrity.

SPECIAL SHIPPING INSTRUCTIONS....Not regulated

## SECTION 08: FIRST AID MEASURES

EYE CONTACT...... Immediately flush eyes with large amounts of water until irritation

subsides. Seek medical attention immediately.

INGESTION......If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical

attention.

medical attention if irritation occurs or persists.

## SECTION 09: PREPARATION INFORMATION

..... Regulatory Affairs

TELEPHONE NUMBER: ..... (440) 937-7000

concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, express or implied, is made by Henkel Canada Corporation as to the effects of such use, the results obtained, or the safety and toxicity of the product nor does Henkel Canada Corporation assume any liability arising out of use, by others, of the product referred to herein. The

information herein is not to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstan ces exist or because of applicable

laws or government regulations.

PREPARATION DATE......FEB 22/2005 Rev 030308

CANUTEC EMERGENCY (613) 996-6666