N.L. Collar Compound

Topco Sales Bay 5, 19 Street N.E. Calgary, Alberta T2E 6S8	EMERGENCY PHONE (403) 291-0255	Information Phone (403) 291-0255	
	DATE ISSUED/REVISED Jun 1, 1996	LAST VALIDATED ON Aug 23, 2010	



Class D-2: Poisonous & infectious material: other toxic effects

Section 2: HEALTH HAZARD DATA

ROUTES OF ENTRY/SIGNS & SYMPTOMS OF ACUTE EXPOSURE:

EYES / SKIN / INHALATION / INGESTION: No data available. Route of entry, skin and eye contact.

Chronic Effects: May cause irritation and possible dermatitis in sensitive individuals. Carcinogens: N/R. Medical Conditions Aggravated by Exposure: N/R.

EMERGENCY & FIRST AID PROCEDURES:

EYES: Flush with water for at least 15 minutes. **SKIN:** Wash thoroughly with soap and warm water. **INHALATION:** Vapour pressure is negligible. Remove victim from further exposure. **INGESTION:** DO NOT INDUCE VOMITING. Contact physician immediately.

Section 3: PREVENTATIVE MEASURES

Respiratory Protection: None required.

Ventilation: Local exhaust.

Gloves: Rubber or cloth gloves. Eye Protection: Goggles recommended. Other Protective Measures: N/R.

Work/Hygienic Practices: N/R

Handling and Storing: Store in cool, dry area, away from sources of heat.

KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS. N/A=Not Applicable. N/E=Not Evaluated/Established. N/R=Not Reported by Manufacturer.

Continued on Page 2

Section 4: HAZARDOUS COMPONENTS & EXPOSURE LIMITS							
Hazardous Component Name	CAS#	OSHA PEL	ACGIH-TLV	Other Limit	% Wt		
Copper dust Graphite Zinc dust	1317-38-0 7782-42-5 7440-66-6	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A	5-10 15-25 15-30		

§ indicates a toxic chemical subject to the reporting requirements of SARA Title III, Section 313.

† indicates a chemical known to the State of California to cause cancer, birth defects or other reproductive harm per Proposition 65.

Section 5: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:

260°C+

Specific Gravity:

1.87 g/c.c.

Vapor Pressure:

N/R

Percent Volatile:

N/R N/R

Vapor Density (Air=1):

N/R None **Evaporation Rate:** pH:

N/R

Solubility in Water: Appearance/Odor:

Copper coloured paste/Mild petroleum odour.

Section 6: FIRE & EXPLOSION HAZARD DATA

Flash Point (Method):

> 171°C (ASTM D-92)

Flammable Limits. LELN/R UEL: N/R

Extinguishing Media:

Dry chemical, water fog, CO2, foam, sand/earth.

Special Firefighting

Procedures:

Use water only as a fog. Fire fighters should use self-contained breathing apparatus with full

face piece operated in pressure demand.

Unusual Fire and

None.

Explosion Hazards:

Section 7: REACTIVITY DATA

Stability: Stable. Hazardous Polymerisation: Will not occur. Conditions to Avoid: N/R. Incompatibility: Strong oxidising agents. Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of zinc.

Section 8: SPILLS, DISPOSAL & ADDITIONAL INFORMATION

Spill/Leak

Prevent material from entering watercourses by containing with sand or earth.

Procedures:

Waste

Dispose in compliance with government regulations and local requirements.

Disposal:

Additional

None.

Information:

The information contained in this EndUser Material Safety Data Sheet™ has been compiled by MSDS Rx from original manufacturer's data. Efforts have been made by MSDS Rx to check for completeness and accuracy. MSDS Rx and no other entity is responsible for any variations between the original manufacturer's data sheet and the content of the EndUser MSDS™. Since the conditions under which this information may be applied are beyond our control, neither the manufacturer nor MSDS Rx assumes any liability for any results or effects of its use or application. E&OE.