

Siloo Glass Cleaner**Section 1: MANUFACTURER/PREPARER INFORMATION & HAZARD WARNINGS**

CRC Canada, Inc.
1246 Lorimar Drive, Unit #2,
Mississauga, Ontario, Canada

EMERGENCY PHONE
(613) 996-6666

INFORMATION PHONE
(905) 670-2291

DATE ISSUED/REVISED
Jun 16, 2007

LAST VALIDATED ON
Aug 17, 2010

WHMIS HAZARD SYMBOLS & DEFINITIONS

Class B: Combustible & flammable material

Class D-2: Poisonous & infectious material: other toxic effects

Section 2: HEALTH HAZARD DATA**ROUTES OF ENTRY/SIGNS & SYMPTOMS OF ACUTE EXPOSURE:**

EYES: Will cause burning sensation. **SKIN:** May cause irritation. **INHALATION:** May cause headache, mucous membrane irritation. **INGESTION:** Not considered a primary route of entry.

Chronic Effects: Extended skin contact may cause dermatitis. **Carcinogens:** None listed by IARC, NTP or OSHA. **Medical Conditions Aggravated by Exposure:** N/A.

EMERGENCY & FIRST AID PROCEDURES:

EYES: Flush with water for 15 minutes. **SKIN:** Wash with soap and water. **INHALATION:** Remove to fresh air. **INGESTION:** Induce vomiting. Call a physician.

Section 3: PREVENTATIVE MEASURES

Respiratory Protection: N/A.

Ventilation: Not normally a problem.

Gloves: Rubber gloves. **Eye Protection:** Safety glasses. **Other Protective Measures:** N/A.

Work/Hygienic Practices: N/A

Handling and Storing: Store in a cool, dry area. Aerosol cans may explode if heated above 120°F.

KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS.

N/A=Not Applicable. N/E=Not Evaluated/Established. N/R=Not Reported by Manufacturer.

Continued on Page 2

Section 4: HAZARDOUS COMPONENTS & EXPOSURE LIMITS

Hazardous Component Name	CAS #	OSHA PEL	ACGIH-TLV	Other Limit	% Wt
Isobutane	75-28-5	N/A	N/A	1000 ppm (skin)	< 10
Water	7732-18-5	N/A	N/A	N/A	> 99
§ 2-Butoxy Ethanol	111-76-2	25ppm	25 ppm	N/R	< 10
Propane	74-98-6	1000 ppm	N/A	N/R	< 10

§ indicates a toxic chemical subject to the reporting requirements of SARA Title III, Section 313.

† indicates a chemical known to the State of California to cause cancer, birth defects or other reproductive harm per Proposition 65.

Section 5: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	212° F	Specific Gravity:	0.9891
Vapor Pressure:	N/E	Percent Volatile:	< 12% VOC
Vapor Density (Air=1):	Water	Evaporation Rate:	N/R
Solubility in Water:	Soluble	pH:	9.7
Appearance/Odor:	Clear liquid/Ammonia odour.		

Section 6: FIRE & EXPLOSION HAZARD DATA

Flash Point (Method): < 20°F (TCC) **Flammable Limits. LEL:** 1.8% **UEL:** 9.5%

Extinguishing Media: Dry chemical.

Special Firefighting Procedures: N/R

Unusual Fire and Explosion Hazards: Aerosol cans may explode if heated above 120°F.

Section 7: REACTIVITY DATA

Stability: Stable. **Hazardous Polymerisation:** Will not occur. **Conditions to Avoid:** N/R. **Incompatibility:** N/A.
Hazardous Decomposition Products: Thermal -- NH₃, carbon monoxide.

Section 8: SPILLS, DISPOSAL & ADDITIONAL INFORMATION

Spill/Leak Procedures: Ventilate area, remove sources of ignition. Absorb on inert material.

Waste Disposal: All used and unused product should be disposed of in conformance with local, provincial and federal regulations.

Additional Information: None.

This MSDS has been compiled in good faith by MSDS Rx from original manufacturer's data to comply with US OSHA and WHMIS regulations. Any variation between this MSDS and the manufacturer's original MSDS is the sole responsibility of MSDS Rx. Since the conditions under which this product may be used are beyond our control, neither MSDS Rx, its client, or the manufacturer assumes any liability for any results or effects of its use or application. Email MSDS Rx at info@msdsrx.com. E&OE.