



Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
 	B-3, D-2B (D-2A)* (See Section 15)	   	

Nunavut Water Board

MAY 11 2005

Public Registry

Section 1. Chemical Product and Company Identification

Product Name	JET A/A-1 AVIATION TURBINE FUEL	Code	W213 SAP: 149
Synonym	Jet A-1; Jet A-1-DI; Aviation Turbine Kerosene (ATK); JP-8; NATO F-34; Jet F-34; Turbine Fuel, Aviation, Kerosene Type (CAN/CGSB-3.23)	Validated on	11/8/2004.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Used as aviation turbine fuel. May contain a fuel system icing inhibitor. In the arctic, Jet A-1 may also be used as diesel fuel and heating oil.		

Section 2. Composition and Information on Ingredients

			Exposure Limits (ACGIH)		
Name	CAS #	% (V/V)	TLV-TWA(8 h)	STEL	CEILING
Complex mixture of petroleum hydrocarbons (C9-C16)**(Kerosene) **Aromatic content is 25% maximum (benzene: nil).	8008-20-6	99.9	200 mg/m ³ (***)	Not established	Not established
Fuel System Icing Inhibitor (FSII) (if added*): Diethylene Glycol Monomethyl Ether	111-77-3	≤0.15	Not established	Not established	Not established
Anti-static, antioxidant and metal deactivator additives. * Please note that Jet A-1-DI, JP-8, Jet F-34 and NATO F-34 all contain Fuel System Icing Inhibitor.	Not applicable	<0.1	Not applicable	Not applicable	Not applicable
Manufacturer Recommendation	***Application of this TLV is restricted to conditions in which there are negligible aerosol exposures.				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

Section 3. Hazards Identification.

Potential Health Effects	Combustible liquid. Exercise caution when handling this material. May cause teratogenicity/embryotoxicity. Contact with this product may cause skin irritation. Inhalation of this product may cause respiratory tract irritation and Central Nervous System (CNS) Depression, symptoms of which may include; weakness, dizziness, slurred speech, drowsiness, unconsciousness and in cases of severe overexposure; coma and death. Aspiration of liquid drops into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure. For more information refer to Section 11 of this MSDS.
--------------------------	---

Section 4. First Aid Measures

Eye Contact	Quickly and gently, blot or brush away excess chemical. Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 20-30 minutes, by the clock, while holding the eyelid(s) open.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	NEVER give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. DO NOT INDUCE VOMITING. Have victim drink 240 to 300 mL (8 to 10 oz) of water to dilute material in stomach. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Seek medical attention.
Note to Physician	Not available

Section 5. Fire-fighting Measures

Flammability	Class II - combustible liquid (NFPA).	Flammable Limits	LOWER: 0.7% UPPER: 5%
Flash Points	CLOSED CUP: >38°C (100°F) Tag (ASTM D56)	Auto-Ignition Temperature	210°C (410°F)
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks, and heat. Vapours are heavier than air and may travel considerable distance to sources of ignition and flash back. This product can accumulate static charge and ignite. May accumulate in confined spaces.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.
Products of Combustion	Carbon oxides (CO, CO ₂), nitrogen oxides (NO _x), sulphur oxides (SO _x), smoke and irritating vapours as products of incomplete combustion.		
Fire Fighting Media and Instructions	NAERG96, GUIDE 128, Flammable liquids (Non-polar/Water-immiscible). CAUTION: This product has a very low flash point: Use of water spray when fighting fire may be inefficient. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. SMALL FIRES: Dry chemical, CO₂, water spray or regular foam. LARGE FIRES: Water spray, fog or regular foam. Do not use straight streams. Move containers from fire area if you can do it without risk. Fires Involving Tanks or Car/Trailer Loads: Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Cool containers with flooding quantities of water until well after fire is out. Withdraw immediately in case of rising sound from venting devices or any discolouration of tank. ALWAYS stay away from the ends of tanks. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn. Wear positive pressure self-contained breathing apparatus (SCBA). Structural firefighters' protective clothing will only provide limited protection.		

Section 6. Accidental Release Measures

Material Release or Spill	IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Evacuate non-essential personnel. Extinguish all ignition sources. Ventilate area. Stop leak if safe to do so. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Do not allow spilled material to enter sewer systems as vapours may accumulate and may cause an explosion/fire hazard. Ground and bond all equipment used to clean up the spilled material, as it may be a static accumulator. If spilled in a confined space, ensure appropriate confined space entry protocols are followed. Ensure clean-up personnel wear appropriate personal protective equipment. Collect used absorbent for later disposal. Use appropriate inert absorbent material to absorb spilled product. Do not use paper or other flammable materials to absorb product. Avoid breathing vapours or mists of material. Notify appropriate authorities immediately.
----------------------------------	--

Section 7. Handling and Storage

Handling	COMBUSTIBLE MATERIAL. Handle with care. Avoid contact with any sources of ignition, flames, heat, and sparks. Wear proper personal protective equipment (See Section 8). Ensure all equipment is grounded/bonded. Avoid confined spaces and areas with poor ventilation. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product.
Storage	Store away from heat and sources of ignition. Store away from incompatible and reactive materials (See section 5 and 10). Ensure the storage containers are grounded/bonded. Keep container tightly closed. Store in dry, cool, well-ventilated area.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.
Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.	
Eyes	As a minimum, safety glasses with side shields should be worn when handling this material.
Body	If this material may come in contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information.)

Respiratory A minimum of NIOSH-approved air-purifying respirator with an organic vapour cartridge or canister with a dust, fume or mist filter (R, or P series) may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. A NIOSH-approved positive-pressure, air-supplied respirator or self-contained breathing apparatus may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Hands If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): Polyvinyl alcohol (PVA), Fluoro-elastomer. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Clear liquid.	Viscosity	1.0-1.9 cSt @ 40°C (104°F)
Colour	Clear and colourless.	Pour Point	<-51°C (<-60°F)
Odour	Kerosene-like.	Softening Point	Not applicable.
Odour Threshold	Not available	Dropping Point	Not applicable.
Boiling Point	150 to 300°C (302 to 572°F)	Penetration	Not applicable.
Density	0.8 to 0.82 kg/L @ 15°C (59°F).	Oil / Water Dist. Coefficient	Not available
Vapour Density	4.5 (Air = 1)	Ionicity (in water)	Not available
Vapour Pressure	0.70 kPa @ 20°C (5.25 mmHg @ 68°F)	Dispersion Properties	Not available
Volatility	Low than gasoline.	Solubility	Insoluble in water. Partially miscible in some alcohols. Miscible in other petroleum solvents.

Section 10. Stability and Reactivity

Corrosivity	Not available		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with strong oxidizing agents, nitric acid, chlorosulfonic acid, and calcium hypochlorite.	Decomposition Products	May release CO _x , NO _x , SO _x , aldehydes, ketones, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information

Routes of Entry	Skin contact, eye contact, inhalation and ingestion.
Acute Lethality	Kerosene Acute oral toxicity (LD50): >5000 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >5000 mg/m³/4h (rat). Diethylene Glycol Monomethyl Ether Acute oral toxicity (LD50): 4140-5180 mg/kg (rat). Acute dermal toxicity (LD50): >2000 mg/kg (rabbit). Acute inhalation toxicity (LC50): >50000 mg/m³/4h (rat).
Chronic or Other Toxic Effects	
Dermal Route:	This product contains a component (at >= 1%) that can cause skin irritation (Kerosene, CASRN 8008-20-6). Therefore, this product is considered to be a skin irritant.
Inhalation Route:	Inhalation of this product may cause Central Nervous System (CNS) Depression, symptoms of which may include; headache, nausea, dizziness, light-headedness and vomiting.
Oral Route:	Aspiration into the lungs may produce potentially fatal chemical pneumonitis (fluid in the lungs), severe lung damage, or respiratory failure.
Eye Irritation/Inflammation:	Eye contact can cause irritation.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.

Mutagenic:	This product is not known to contain any components at $\geq 0.1\%$ that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.
Reproductive Toxicity:	This product is not known to contain any components at $\geq 0.1\%$ that have been shown to cause reproductive toxicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a reproductive toxin.
Teratogenicity/Embryotoxicity:	This product contains a component(s) at $\geq 0.1\%$ that has been shown to cause teratogenicity and/or embryotoxicity in laboratory tests (Diethylene Glycol Monomethyl Ether, CASRN 111-77-3). Therefore, this product is considered to be a teratogen/embryotoxin.
Carcinogenicity (ACGIH):	ACGIH A3: Confirmed animal carcinogen with unknown relevance to human (kerosene, CASRN 8008-20-6).
Carcinogenicity (IARC):	IARC Group 3: Not classifiable as a human carcinogen (kerosene, CASRN 8008-20-6).
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
Other Considerations	Chronic exposure to some of the hazardous components of this product may result in damage to the following organs and/or systems: kidney.

Section 12. Ecological Information

Environmental Fate	Not available	Persistence/Bioaccumulation Potential	Not available
BOD5 and COD	Not available	Products of Biodegradation	Not available
Additional Remarks No additional remark.			

Section 13. Disposal Considerations

Waste Disposal	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.
-----------------------	--

Section 14. Transport Information

TDG Classification	FUEL, AVIATION, TURBINE ENGINE, 3, UN1863, PGIII	Special Provisions for Transport	Not applicable.
---------------------------	--	---	-----------------

Section 15. Regulatory Information

Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List). The WHMIS classification of Jet A/A-1 is B3, D2B. The WHMIS classification of Jet A/A-1-DI, JP-8, Jet F-34 and NATO F-34, which all contain FSII (Diethylene Glycol Monomethyl Ether), is B3, D2A, D2B. All components of this formulation are listed on the US EPA-TSCA Inventory. All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS). This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. Please contact Product Safety for more information.		
DSD/DPD (Europe)	Not evaluated.	HCS (U.S.A.)	CLASS: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F). CLASS: Irritating substance. Target Organ Effects* (Only applies to: Jet A/A-1-DI, JP8, Jet F-34 and NATO F-34)

ADR (Europe) (Pictograms)		NOT EVALUATED FOR EUROPEAN TRANSPORT NON ÉVALUÉ POUR LE TRANSPORT EUROPÉEN.		DOT (U.S.A) (Pictograms)																				
HMIS (U.S.A.)		<table><tr><td>Health Hazard</td><td>2/2*</td></tr><tr><td>Fire Hazard</td><td>2</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>H</td></tr></table>		Health Hazard	2/2*	Fire Hazard	2	Reactivity	0	Personal Protection	H	NFPA (U.S.A.)		<table><tr><td rowspan="3">Health</td><td>2</td><td>Fire Hazard</td></tr><tr><td>2</td><td>0 Reactivity</td></tr><tr><td colspan="2">Specific hazard</td></tr></table>		Health	2	Fire Hazard	2	0 Reactivity	Specific hazard		Rating	0 Insignificant
Health Hazard	2/2*																							
Fire Hazard	2																							
Reactivity	0																							
Personal Protection	H																							
Health	2	Fire Hazard																						
	2	0 Reactivity																						
	Specific hazard																							
							1 Slight																	
							2 Moderate																	
							3 High																	
							4 Extreme																	

Section 16. Other Information

References Available upon request.
* Marque de commerce de Petro-Canada - Trademark

Glossary

ACGIH - American Conference of Governmental Industrial Hygienists	IRIS - Integrated Risk Information System
ADR - Agreement on Dangerous goods by Road (Europe)	LD50/LC50 - Lethal Dose/Concentration kill 50%
ASTM - American Society for Testing and Materials	LDLo/LCLo - Lowest Published Lethal Dose/Concentration
BOD5 - Biological Oxygen Demand in 5 days	NAERG'96 - North American Emergency Response Guide Book (1996)
CAN/CGA B149.2 Propane Installation Code	NFPA - National Fire Prevention Association
CAS - Chemical Abstract Services	NIOSH - National Institute for Occupational Safety & Health
CEPA - Canadian Environmental Protection Act	NPRI - National Pollutant Release Inventory
CERCLA - Comprehensive Environmental Response, Compensation and Liability Act	NSNR - New Substances Notification Regulations (Canada)
CFR - Code of Federal Regulations	NTP - National Toxicology Program
CHIP - Chemicals Hazard Information and Packaging Approved Supply List	OSHA - Occupational Safety & Health Administration
COD5 - Chemical Oxygen Demand in 5 days	PEL - Permissible Exposure Limit
CPR - Controlled Products Regulations	RCRA - Resource Conservation and Recovery Act
DOT - Department of Transport	SARA - Superfund Amendments and Reorganization Act
DSCL - Dangerous Substances Classification and Labeling (Europe)	SD - Single Dose
DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)	STEL - Short Term Exposure Limit (15 minutes)
DSL - Domestic Substance List	TDG - Transportation Dangerous Goods (Canada)
EEC/EU - European Economic Community/European Union	TDLo/TCLo - Lowest Published Toxic Dose/Concentration
EINECS - European Inventory of Existing Commercial Chemical Substances	TLM - Median Tolerance Limit
EPCRA - Emergency Planning and Community Right to Know Act	TLV-TWA - Threshold Limit Value-Time Weighted Average
FDA - Food and Drug Administration	TSCA - Toxic Substances Control Act
FIFRA - Federal Insecticide, Fungicide and Rodenticide Act	USEPA - United States Environmental Protection Agency
HCS - Hazard Communication Standard	USP - United States Pharmacopoeia
HMIS - Hazardous Material Information System	WHMIS - Workplace Hazardous Material Information System
IARC - International Agency for Research on Cancer	

For Copy of MSDS

Internet: www.petro-canada.ca/msds

Fuels & Solvents:

Western Canada, Ontario & Central Canada, telephone: 1-800-668-0220; fax: 1-800-837-1228

Quebec & Eastern Canada, telephone: 514-640-8308; fax: 514-640-8385

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - TLM on 11/8/2004.

Data entry by Product Safety - RS.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



Material Safety Data Sheet

MSDS ID NO.: 0133SPE012
Revision date: 01/30/2004

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name: SSA Propane
Synonyms: Liquefied Petroleum Gas, SSA; LPG, SSA; Propane, SSA; SSA Liquefied Petroleum Gas
Chemical Family: Aliphatic Hydrocarbon
Formula: CH₃CH₂CH₃

Supplier:
Speedway/Superamerica LLC
P O BOX 1500
ENON OH 45501

Other information: 419-421-3070
Emergency telephone number: 877-627-5463

2. COMPOSITION/INFORMATION ON INGREDIENTS

Propane is an aliphatic petroleum hydrocarbon. Ethyl mercaptan (15-25 ppm) is added as an odorant. The odor threshold of the mercaptan is 1 ppb.

Product information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
SSA Propane	74-98-6	100	= 2500 ppm TWA	= 1000 ppm TWA = 1800 mg/m ³ TWA	

Component Information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Propane	74-98-6	90-100	= 2500 ppm TWA	= 1000 ppm TWA = 1800 mg/m ³ TWA	
Propylene	115-07-1	1-5			ACGIH Simple asphyxiant
Ethane	74-84-0	000.5000 - 003.0000			ACGIH Simple asphyxiant*
Butane & Heavier	Mixture	0-2.5			
Sulfur	7704-34-9	< 000.0100			

Notes: The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

PROPANE IS A COLORLESS GAS OR LIQUID STENCHED WITH A FOUL SULFUR SMELLING ODORANT. IT IS SHIPPED OR TRANSPORTED AS A LIQUIFIED GAS UNDER PRESSURE. THIS PRODUCT IS EXTREMELY FLAMMABLE AND EXPLOSIVE. AT HIGH CONCENTRATIONS THIS PRODUCT IS A SIMPLE ASPHYXIANT, WHICH DISPLACES OXYGEN FROM THE BREATHING ATMOSPHERE. MAY CAUSE SKIN AND EYE BURNS UPON LIQUID CONTACT. LARGE RELEASES CAN CREATE A FLAMMABLE VAPOR CLOUD.

OSHA WARNING LABEL:

DANGER!
EXTREMELY FLAMMABLE.
LIQUID AND GAS UNDER PRESSURE.
LIQUID CAN CAUSE FROST BURNS.

CONSUMER WARNING LABEL:

A CONSUMER WARNING LABEL IS NOT APPLICABLE FOR THIS PRODUCT.

Inhalation: Product is an anesthetic at high concentrations, producing dizziness, headache, incoordination and narcosis; extremely high concentrations can cause asphyxiation and death by displacement of oxygen from the breathing atmosphere.

Ingestion: Ingestion not likely.

Skin contact: Vapor is generally non-irritating to skin. Direct contact with liquified product can cause "cold burn" or frostbite.

Eye contact: Vapor is generally non-irritating to eyes. Direct contact with liquified product can cause "cold burn" or frostbite.

Carcinogenic Evaluation:

Product information

Name	IARC:	NTP:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
SSA Propane 74-98-6	NE			

Notes: The International Agency for Research on Cancer (IARC) has not evaluated this product.

Component Information

Name	IARC:	NTP:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Propylene 115-07-1			A4 - Not Classifiable as a Human Carcinogen	

Notes: The International Agency for Research on Cancer (IARC) has concluded that propylene is not classifiable as to its carcinogenicity to humans (Group 3).

4. FIRST AID MEASURES

Inhalation: If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician.

Skin contact: If liquified product has caused a "frost burn", remove contaminated clothing. Thaw frostbitten areas slowly with lukewarm water or by wrapping affected areas with blankets. Do not rub affected areas. Let circulation reestablish itself naturally, exercising area if possible. Call a physician.

Ingestion:	Ingestion not likely. If swallowed, immediately call a physician.
Eye contact:	Liquid: Flush with large amounts of tepid water for at least 15 minutes. Immediately call a physician. Gas: Call a physician if symptoms or irritation occur.
Medical conditions aggravated by exposure:	Inhalation of high vapor concentrations of components of this product in animals has produced cardiac sensitization. Such sensitization may cause changes in heart rhythms. This latter effect was shown to be enhanced by oxygen deficiency or the injection of adrenalin-like agents.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	For small fires, Class B fire extinguishing media such as CO2, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFF/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.
Specific hazards:	This product has been determined to be a flammable gas/liquid per the OSHA Hazard Communication Standard, and should be handled accordingly. For additional fire related information see NFPA 30 or North American Emergency Response Guide 115.
Special protective equipment for firefighters:	Bleve's (boiling liquid expanding vapor explosions) can occur when a liquid in a pressurized container in close proximity to a fire reaches a temperature well above its boiling point. Its effect could lead to a catastrophic failure of the vessel resulting in flying equipment fragments, a shock wave and a fireball causing serious damage and death. Isolate hazard area. If safe to do so, stop the flow of gas and allow fire to burn out. Extinguishing the flame before shutting off the supply can cause the formation of explosive mixtures. In some cases it may be preferred to allow the flame to continue to burn. Use extreme caution when fighting liquefied petroleum gas fires. Keep surrounding area cool with water spray from a distance and prevent further ignition of combustible material. Avoid use of solid water streams. Contact with water and liquified product can cause increased vaporization.
Flash point:	-156 F
Autoignition temperature:	871 F
Flammable limits in air - lower (%):	2.1
Flammable limits in air - upper (%):	9.5
<u>NFPA rating:</u>	<u>HMIS classification:</u>
Health: 1	Health: 1
Flammability: 4	Flammability: 4
Reactivity: 0	Reactivity: 0
Other: -	Special: *See Section 8 for guidance in selection of personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Leaking containers should be moved outdoors or to well-ventilated area and contents transferred to a suitable container. Product vapor is heavier than air and can collect in low areas that are without sufficient ventilation. Advise authorities and National Response Center (800-424-8802) if substance has entered a watercourse or sewer.
------------------------------	---

7. HANDLING AND STORAGE

Handling:

Product is stored as a liquid but used in the gaseous state. Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Avoid overpressurizing or overfilling cylinders. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues.

Avoid repeated and prolonged skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Engineering measures:	Local or general exhaust required in an enclosed area or with inadequate ventilation.
Respiratory protection:	Use atmosphere supplying respirators in the event of oxygen deficiency, when material produces vapors that exceed permissible limits or when excessive vapors are generated. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.
Skin and body protection:	Wear insulated gloves to prevent skin contact and frostbite.
Eye protection:	Use goggles or face-shield if there is a potential for splashing.
Hygiene measures:	Use mechanical ventilation equipment that is explosion-proof.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	Colorless Liquified Gas
Physical state (Solid/Liquid/Gas):	Liquid
Substance type (Pure/Mixture):	Pure
Color:	Colorless
Odor:	Rotten-egg.
Molecular weight:	Not determined.
pH:	No data available.
Boiling point/range:	-43.7 F
Melting point/range:	-305.8 F
Decomposition temperature:	Not applicable.
Specific gravity:	.51 Liquid
Density:	4.4 lbs/gal @ 32 F
Bulk density:	No data available.
Vapor density:	1.56
Vapor pressure:	7600 mm Hg @ 80 F 147 PSI @ 80 F
Evaporation rate:	No data available.
Solubility:	Moderate 6.5%
Solubility in other solvents:	No data available.
Partition coefficient (n-octanol/water):	No data available.
VOC content(%):	No data available.
Viscosity:	No data available.

10. STABILITY AND REACTIVITY

Stability:

The material is stable at 70 F, 760 mm pressure.

Polymerization: Will not occur.

Hazardous decomposition products: Combustion produces carbon monoxide.

Materials to avoid: Strong oxidizers such as nitrates, perchlorates, chlorine, fluorine.

Conditions to avoid: Sources of heat or ignition.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Product information

Name	CAS Number	Inhalation:	Dermal:	Oral:
SSA Propane	74-98-6	>4000,000 ppm for 6 hr [Rat]	n/a	n/a

Some of the major components of this product are considered to be simple asphyxiant gases without significant potential for systemic toxicity. At high concentrations these gases act as asphyxiants by diluting and displacing oxygen. Symptoms of persons exposed to oxygen deficient atmospheres include headache, dizziness, incoordination, cyanosis and narcosis. Extremely high concentrations can produce unconsciousness followed by death.

At extremely high concentrations and excessive exposure conditions components of this product may produce cardiac sensitization.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects: Liquid product is not toxic to aquatic life or waterfowl. The aquatic 96 hour TLM for propane is >100 ppm.

13. DISPOSAL CONSIDERATIONS

Cleanup Considerations: This product as produced is not specifically listed as an EPA RCRA hazardous waste according to federal regulations (40 CFR 261). However, when discarded or disposed of, it may meet the criteria of an "ignitable" hazardous waste (D001). This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Bleeding off small amounts of this product into the atmosphere or controlled incineration of large amounts are potential disposal methods provided all regulatory requirements are met.

14. TRANSPORT INFORMATION

49 CFR 172.101:

DOT:

Transport Information: This material when transported via US commerce would be regulated by DOT Regulations.

Proper shipping name: Propane
UN/Identification No: UN 1978
Hazard Class: 2.1

MSDS ID NO.: 0133SPE012

Product name: SSA Propane

Page 5 of 9

Packing group:
DOT reportable quantity (lbs):

Not applicable.
Not applicable.

TDG (Canada):

Proper shipping name:
UN/Identification No:
Hazard Class:
Packing group:
Regulated substances:

Propane
UN 1978
2.1
Not applicable.
Not applicable.

15. REGULATORY INFORMATION

Federal Regulatory Information:

US TSCA Chemical Inventory Section 8(b):

This product and/or its components are listed on the TSCA Chemical Inventory.

OSHA Hazard Communication Standard:

This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

EPA Superfund Amendment & Reauthorization Act (SARA):

SARA Section 302:

This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Propane	NA
Propylene	NA
Ethane	NA
Butane & Heavier	NA
Sulfur	NA

SARA Section 304:

This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Propane	NA
Propylene	NA
Ethane	NA
Butane & Heavier	NA
Sulfur	NA

SARA Section 311/312:

The following EPA hazard categories apply to this product:

Acute Health Hazard.
Fire Hazard.
Sudden Release Of Pressure.

SARA Section 313:

This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name	CERCLA/SARA 313 Emission reporting:
Propane	None
Propylene	= 1.0 percent de minimis concentration
Ethane	None
Butane & Heavier	None
Sulfur	None

State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

MSDS ID NO.: 0133SPE012

Product name: SSA Propane

Propane

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 1594
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1594
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Propylene

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 1609
Pennsylvania Right-To-Know:	environmental hazard
Massachusetts Right-To Know	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree
New Jersey - Environmental Hazardous Substances List:	SN 1609
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

Ethane

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 0834
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - fourth degree

New Jersey - Environmental Hazardous
Substances List:
Illinois - Toxic Air Contaminants
New York - Reporting of Releases Part 597 -
List of Hazardous Substances:

SN 0834; NJ uses UN1035 for reporting purposes

Not Listed

Not Listed

Butane & Heavier

Louisiana Right-To-Know:
California Proposition 65:
New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida substance List:
Rhode Island Right-To-Know:
Michigan critical materials register list:
Massachusetts Extraordinarily Hazardous
Substances:

Not Listed

Not Listed

Not Listed.

Not Listed.

Not Listed.

Not Listed.

Not Listed

Not Listed.

Not Listed

California - Regulated Carcinogens:

Not Listed

Pennsylvania RTK - Special Hazardous
Substances:

Not Listed

New Jersey - Special Hazardous Substances:

Not Listed

New Jersey - Environmental Hazardous
Substances List:

Not Listed

Illinois - Toxic Air Contaminants

Not Listed

New York - Reporting of Releases Part 597 -

Not Listed

List of Hazardous Substances:

Sulfur

Louisiana Right-To-Know:
California Proposition 65:
New Jersey Right-To-Know:
Pennsylvania Right-To-Know:
Massachusetts Right-To Know:
Florida substance List:
Rhode Island Right-To-Know:
Michigan critical materials register list:
Massachusetts Extraordinarily Hazardous
Substances:

Not Listed

Not Listed

sn 1757

[present]

Present

Not Listed.

Flammable

Not Listed.

Not Listed

California - Regulated Carcinogens:

Not Listed

Pennsylvania RTK - Special Hazardous
Substances:

Not Listed

New Jersey - Special Hazardous Substances:

Not Listed

New Jersey - Environmental Hazardous
Substances List:

Not Listed

Illinois - Toxic Air Contaminants

Not Listed

New York - Reporting of Releases Part 597 -

Not Listed

List of Hazardous Substances:

Canadian Regulatory Information:

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or the Non Domestic Substance List (NDSL).

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Propane	A; B1	
Propylene	A; B1	
Ethane	A; B1	
Sulfur	B4	

16. OTHER INFORMATION

Additional Information: No data available.

Prepared by: Craig M. Parker Manager, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Speedway SuperAmerica (SSA) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. SSA assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

End of Safety Data Sheet