

### **Material Safety Data Sheet**

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	Not controlled		

Section 1. Cl	Section 1. Chemical Product and Company Identification				
Product Name	PURITY* FG AW HYDRAULIC FLUID 32, 46, 68, 100	Code	491-010, PFAW32 491-011, PFAW46 491-012, PFAW68 491-013, PFAW100		
Synonym	Not available	Validated			
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergenc	Petro-Canada: y403-296-3000 Canutec Transportation: 613-996-6666		
Material Uses	PURITY FG AW Hydraulic Fluid 32, 46, 68, 100 are food grade hydraulic fluids and light gear oils.  NSF H1 Registered.  All components comply with FDA 21 CFR 178.3570 " Lubricants with Incidental Food Contact". It is intended for application on industrial		Poison Control Centre: Consult local telephone directory for emergency number(s).		
	and food equipment. It should not be added directly to the food product.				

Section 2. Composition and Information on Ingredients						
				Expo	osure Limits (ACGII	1)
	Name	CAS#	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Mixture of severely hydrotreated and hydrocracked base oil (petroleum) and other proprietary, non-hazardous additives.		Mixture	100	5 mg/m³ (oil mist)	10 mg/m³ (oil mist)	Not established
Manufacturer Not applicable Recommendation						
Other Exposure Consult local, state, provincial or territory authorities for acceptable exposure limits.  Limits						

Section 3. Hazards Identification.				
Potential Health	Prolonged or repeated contact may cause skin irritation, defatting, drying and dermatitis. Not expected to			
Effects	cause more than slight skin or eye irritation. With its relatively low vapour pressure, this product is not			
	expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or			

subjected to mechanical actions which produce vapours or mists, inhalation may cause respiratory tract irritation. Ingestion may produce a laxative effect. For more information refer to Section 11 of this MSDS.

Section 4. First Aid Measures		
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.	
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention	
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.	
Ingestion DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.		
Note to Physician Not available		

Continued on Next Page Internet: www.petro-canada.ca/msds Available in French

PURITY* FG AW H	YDRAULIC FLUID 32, 46, 68, 100		Page Number: 2	
Section 5. Fire	Section 5. Fire-fighting Measures			
Flammability	May be combustible at high temperature.	Flammable Limits	Not available	
Flash Points	OPEN CUP: ≥200°C (392°F) (Cleveland)	Auto-Ignition Temperature	Not available	
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container. Containers may explode in heat of fire.	
Products of Combustion	roducts of Carbon oxides (CO, CO2), nitrogen oxides (NOx), sulphur oxides (SOx), phosphorus compounds (POx)			
Fire Fighting Media and Instructions	NAERG96, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals,			

### Section 6. Accidental Release Measures

for fire fighting personnel.

## Material Release or Spill

Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.

foam, water spray or CO2. LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required

Section 7.	Section 7. Handling and Storage			
Handling	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.			
Storage	Store away from incompatible and reactive materials (See section 5 and 10). Keep container tightly closed. Store in dry, cool, well-ventilated area.			

### Section 8. Exposure Controls/Personal Protection

## Engineering Controls

For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.

### Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use

Eyes Eye protection (i.e., safety glasses, safety goggles and/or face shield) should be determined based on conditions of use. If product is used in an application where splashing may occur, the use of safety goggles and/or a face shield should be considered.

Body Wear appropriate clothing to prevent skin contact. As a minimum long sleeves and trousers should be worn.

# **Respiratory** Where concentrations in air may exceed the occupational exposure limits given in Section 2 (and those applicable to your area) and where engineering, work practices or other means of exposure reduction are not adequate, NIOSH approved respirators may be necessary to prevent overexposure by inhalation.

**Hands** Wear appropriate chemically protective gloves. When handling hot product ensure gloves are heat resistant and insulated.

Feet Wear appropriate footwear to prevent product from coming in contact with feet and skin.

PURITY* FG AW HYDRAULIC FLUID 32, 46, 68, 100	Page Number: 3
---	----------------

Section 9. Physical and Chemical Properties					
Physical State and Appearance	<b>d</b> Viscous liquid.	Viscosity	32: 29.8 cSt @ 40°C (104°F), 5.2 cSt @ 100°C (212°F), VI=101 46: 45.4 cSt @ 40°C (104°), 6.8 cSt @ 100°C (212°F), VI=102 68: 63.3 cSt @ 40° (104°F), 8.4 cSt @ 100°C (212°F), VI=102 100: 101.5 cSt @ 40° (104°F), 11.5 cSt @ 100°C (212°F), VI=99		
Colour	Colourless.	Pour Point	32: -18°C 46: -18°C 68: -18°C 100: -15°C		
Odour	Mild petroleum oil like.	Softening Point	Not applicable.		
Odour Threshold	Not available	<b>Dropping Point</b>	Not applicable.		
Boiling Point	Not available	Penetration	Not applicable.		
Density	0.8629 - 0.8731 kg/L @ 15°C	Oil / Water Dist. Coefficient	Not available		
Vapour Density	Not available	Ionicity (in water)	Not available		
Vapour Pressure	Negligible at ambient temperature and pressure.	Dispersion Properties	Not available		
Volatility	Non-volatile.	Solubility	Insoluble in water.		

Section 10. Stability and Reactivity			
Corrosivity	Not available		
Stability	The product is stable under normal handling and storage conditions.	Hazardous Polymerization	Will not occur under normal working conditions.
Incompatible Substances / Conditions to Avoid	Reactive with oxidizing agents, acids and alkalis.	Decomposition Products	May release COx, NOx, SOx, POx, SiOx, formaldehyde, smoke and irritating vapours when heated to decomposition.

Section 11. Toxicological Information				
Routes of Entry	Skin contact, eye contact, inhalation and ingestion.			
Acute Lethality	Acute toxicity information is not available for the product as a whole, therefore, data for some of the ingredients is provided below:  Acute Oral toxicity (LD50): >5000 mg/kg (rat)  Acute Dermal toxicity (LD50): >2000 mg/kg (rabbit)  Acute Inhalation toxicity (LC50): >2500 mg/m³/4h (rat)			
<b>Chronic or Other Toxic Ef</b>	fects			
Dermal Route:	Prolonged or repeated contact may defat and dry skin, and cause dermatitis. Short-term exposur is expected to cause only slight irritation, if any.			
Inhalation Route:	With its relatively low vapour pressure, this product is not expected be inhaled in any appreciable quantity at ambient conditions. If heated to high temperatures or subjected to mechanical action which produce vapours or mists, inhalation may cause respiratory tract irritation			
Oral Route:	Ingestion of this product may lead to aspiration of the liquid, especially if vomiting occurs. This maresult in chemical pneumonitis (inflammation of the lungs) and/or pulmonary edema (a accumulation of fluid in the lungs). May produce a laxative effect.			
Eye Irritation/Inflammation:	Short-term exposure is expected to cause only slight irritation, if any.			
Immunotoxicity:	Not available			
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available dat and the known hazards of the components.			
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon th available data and the known hazards of the components.			
Mutagenic:	This product is not known to contain any components at >= 0.1% that have been shown to caus mutagenicity. Therefore, based upon the available data and the known hazards of th components, this product is not expected to be a mutagen.			
Continued on Next Page	Internet: www.petro-canada.ca/msds Available in French			

PURITY* FG AW HYDRAULIC FLU	IID 32, 46, 68, 100	Page Number: 4
Reproductive Toxicity:	This product is not known to contain any components at > reproductive toxicity. Therefore, based upon the available components, this product is not expected to be a reproduct	ole data and the known hazards of the
Teratogenicity/Embryotoxicity:	This product is not known to contain any components at > teratogenicity and/or embryotoxicity. Therefore, based u hazards of the components, this product is not expected to	pon the available data and the known
Carcinogenicity (ACGIH):	This product is not known to contain any chemicals at report A1 or A2 carcinogens by ACGIH.	rtable quantities that are listed as Group
Carcinogenicity (IARC):	This product is not known to contain any chemicals at report, 2A, or 2B carcinogens by IARC.	rtable quantities that are listed as Group
Carcinogenicity (NTP):	This product is not known to contain any chemicals at r carcinogens by NTP.	reportable quantities that are listed as
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at r carcinogens by IRIS.	reportable quantities that are listed as
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at r carcinogens by OSHA.	reportable quantities that are listed as
Other Considerations	No additional remark.	•

Section 12. Ecological Information					
Environmental Fate	Not available	Persistance/ Bioaccumulation Potential	Not available		
BOD5 and COD	Not available	Products of Biodegradation	Not available		
Additional Remarks	No additional remark.				

### Section 13. Disposal Considerations

**Waste Disposal** 

Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.

Section 14. Transport Information				
<b>TDG Classification</b> Not a hazardous material for transport according to the TDG Regulations. (Canada)				

	(Canada)	•			
Section 15. Reg	gulatory Information				
Other Regulations	This product is acceptable for use under the provisions of WHMIS-CPR. All components of this formulation are listed on the CEPA-DSL (Domestic Substances List).				
	All components of this formulation are listed on the US EPA-TSCA Inventory.				
	All components of this product are on the European Inventory of Existing Commercial Chemical Substances (EINECS).				
	German Water Hazard Classification (Verwaltungsvorschrift wassergefährdende Stoffe - VwVwS) WGK=1				
	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.				
Please contact Product Safety for more information.					
DSD/DPD (Europe	D/DPD (Europe)Not classified under the Dangerous Substances or Dangerous Preparations Directives.		Does not meet the definitions of a health or physical hazard according to the OSHA - Hazard Communication Standard. (United States)		
ADR (Europe) (Pictograms)		DOT (U.S.A) (Pictograms)			
HMIS (U.S.A.)	Health Hazard  Fire Hazard  Reactivity  1  NFPA (U	, , , , , , , , , , , , , , , , , , , ,	Rating 0 Insignificant 1 Slight 2 Moderate		
Continued on Next Page Internet: www.petro-canada.ca/msds Available in					

### Section 16. Other Information

References

Available upon request.

\* Marque de commerce de Petro-Canada - Trademark

#### **Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists

ADR - Agreement on Dangerous goods by Road (Europe)

ASTM - American Society for Testing and Materials BOD5 - Biological Oxygen Demand in 5 days

CAN/CGA B149.2 Propane Installation Code

CAS - Chemical Abstract Services

CEPA - Canadian Environmental Protection Act

CERCLA - Comprehensive Environmental Response, Compensation

and Liability Act

CFR - Code of Federal Regulations

CHIP - Chemicals Hazard Information and Packaging Approved Supply List

COD5 - Chemical Oxygen Demand in 5 days

CPR - Controlled Products Regulations

**DOT - Department of Transport** 

DSCL - Dangerous Substances Classification and Labeling (Europe)

DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)

**DSL - Domestic Substance List** 

EEC/EU - European Economic Community/European Union

EINECS - European Inventory of Existing Commercial Chemical

Substances

EPCRA - Emergency Planning and Community Right to Know Act

FDA - Food and Drug Administration

FIFRA - Federal Insecticide, Fungicide and Rodenticide Act

HCS - Hazardous Communication System HMIS - Hazardous Material Information System

IARC - International Agency for Research on Cancer

IRIS - Integrated Risk Information System

LD50/LC50 - Lethal Dose/Concentration kill 50%

LDLo/LCLo - Lowest Published Lethal Dose/Concentration

NAERG'96 - North American Emergency Response Guide Book (1996)

NFPA - National Fire Prevention Association

NIOSH - National Institute for Occupational Safety & Health

NPRI - National Pollutant Release Inventory

NSNR - New Substances Notification Regulations (Canada)

NTP - National Toxicology Program

OSHA - Occupational Safety & Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

SARA - Superfund Amendments and Reorganization Act

SD - Single Dose

STEL - Short Term Exposure Limit (15 minutes)

TDG - Transportation Dangerous Goods (Canada)

TDLo/TCLo - Lowest Published Toxic Dose/Concentration

TLm - Median Tolerance Limit

TLV-TWA - Threshold Limit Value-Time Weighted Average

TSCA - Toxic Substances Control Act

USEPA - United States Environmental Protection Agency

USP - United States Pharmacopoeia

WHMIS - Workplace Hazardous Material Information System

### For Copy of MSDS

The Canadian Controlled Products Regulations (CPR) (Under the Hazardous Products Act, part of the WHMIS legislation) only apply to WHMIS Controlled (i.e., hazardous) products. Therefore, the CPR and the 3-year update rule specified therein do not apply to WHMIS Non-Controlled products. Although this is true, customarily Petro-Canada reviews and updates Non-Controlled product MSDS if a customer requests such an update. These Non-Controlled product updates are given a lower priority than Controlled products but are handled as soon as practicable. If you would like to verify if the MSDS you have is the most current, or you require any further information, please contact:

Internet: www.petro-canada.ca/msds

Lubricants

Western Canada, telephone: 1-800-661-1199; fax: (780) 464-9564

Ontario & Central Canada, telephone: 1-800-268-5850 and (905) 822-4222; fax

1-800-201-6285

Quebec & Eastern Canada, telephone: 1-800-576-1686; fax: 800-201-6285

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 11/28/2003.

Data entry by Product Safety - RS.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.