



## **MATERIAL SAFETY DATA SHEET**

### **Sulfuric Acid**

For additional information on shipping regulations affecting this material, contact the information number found in Section 1.

## **15. REGULATORY INFORMATION**

### **TOXIC SUBSTANCES CONTROL ACT (TSCA)**

**TSCA INVENTORY STATUS:** Listed on the TSCA Inventory.

**OTHER TSCA ISSUES:** None.

### **SARA TITLE III/CERCLA**

"Reportable Quantities" (RQs) and/or "Threshold Planning Quantities" (TPQs) exist for the following ingredients.

<b><u>INGREDIENT NAME</u></b>	<b><u>SARA/CERCLA RQ (lb)</u></b>	<b><u>SARA EHS TPQ (lb)</u></b>
Sulfuric acid	1000	1000

Spills or releases resulting in the loss of any ingredient at or above its RQ requires immediate notification to the National Response Center [(800) 424-8802] and to your Local Emergency Planning Committee.

**SECTION 311 HAZARD CLASS:** Immediate.

### **SARA 313 TOXIC CHEMICALS:**

The following ingredients are SARA 313 "Toxic Chemicals" and may be subject to annual reporting requirements. CAS numbers and weight percents are found in Section 2.

<b><u>INGREDIENT NAME</u></b>	<b><u>COMMENT</u></b>
Sulfuric acid	None

### **STATE RIGHT-TO-KNOW**

In addition to the ingredients found in Section 2, the following are listed for state right-to-know purposes.

<b><u>INGREDIENT NAME</u></b>	<b><u>WEIGHT %</u></b>	<b><u>COMMENT</u></b>
No ingredients listed in this section.		

### **ADDITIONAL REGULATORY INFORMATION:**

"Strong inorganic acid mists containing sulfuric acid" has been listed on California Proposition 65 as a cancer-causing agent.

### **WHMIS CLASSIFICATION (CANADA):**

Listed on Canadian DSL and EU EINECS.

### **FOREIGN CHEMICAL CONTROL INVENTORY STATUS:**

Listed on the Canadian DSL and EU EINECS.

## **16. OTHER INFORMATION**

**CURRENT ISSUE DATE:** May, 2003

MSDS Number: GC-2000

Current Issue Date: May, 2003

Page 6 of 7



## MATERIAL SAFETY DATA SHEET

Sulfuric Acid


---

**PREVIOUS ISSUE DATE:** November, 2001

**CHANGES TO MSDS FROM PREVIOUS ISSUE DATE ARE DUE TO THE FOLLOWING:**

Addition of Prop 65 listing.

**OTHER INFORMATION:** None



**Poly-Drill Drilling Systems**  
1824 - 104 Avenue, S.W.  
Calgary, Alberta, Canada T2W-OA8  
(403) 259-5112 FAX (403) 255-7185  
email: polydril@telus.net  
[www.poly-drill.com](http://www.poly-drill.com)

**poly-drill.com**

## MATERIAL SAFETY DATA SHEET/FICHE SIGNALÉTIQUE

### 1. PRODUCT IDENTIFICATION

PRODUCT TRADE NAME: Poly-Drill 133-X  
PRODUCT DESCRIPTION: LIQUID ANIONIC POLYMER  
CHEMICAL DESCRIPTION: Polymer, Surfactant(s), Water, Hydrocarbon solvent  
UPDATED: March 15, 2004

#### NFPA704M/HMIS RATING

HEALTH: 0/1 FLAMMABILITY: 1/1 REACTIVITY: 0/0 OTHER:  
0=Insignificant 1=Slight 2=Moderate 3=High 4=Extreme

### 2. COMPOSITION

A liquid polymer: Evaluation of the ingredient(s) has found no ingredient(s) hazardous as per WHMIS regulations. None of the substances in this product are hazardous.

### 3. PHYSICAL DATA

Flash Point: >100°C (PMCC)  
Specific Gravity (@ 25°C.): 1.08  
Solubility in Water: Emulsifiable  
pH: 8.1 (1.0% solution)  
Freeze Point: -10 °C (14 Degrees F)  
Density (g/ml): 1.08 at 25 °C  
Physical State: Liquid  
Appearance: Blue liquid  
Odor: Hydrocarbon

Note: These physical properties are typical values for this product.

### 4. FIRE AND EXPLOSION DATA

**INCOMPATIBILITY:** Avoid contact with strong oxidizers (eg. Chlorine, peroxides, chromates, nitric acid, perchlorates, concentrated oxygen, permanganates) which can generate heat, fires, explosions and the release of toxic fumes.

**THERMAL DECOMPOSITION PRODUCTS:** In the event of combustion CO, oxides of carbon (COx), oxides of nitrogen (NOx) may be formed. Do not breathe smoke or fumes. Wear suitable protective equipment.

### 5. FIRE FIGHTING MEASURES

FLASH POINT: >100°C (PMCC)

**EXTINGUISHING MEDIA:** Based on the NFPA guide, use dry chemical, foam, carbon dioxide or other extinguishing agent suitable for Class B fires. Use water to cool containers exposed to fire. For larger fires, use water spray or fog, thoroughly drenching the burning material.

**UNSUITABLE EXTINGUISHING MEDIA:**  
Do not use water unless flooding amounts are available.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** May evolve oxides of nitrogen (NOx) under fire conditions.

## **6. HEALTH HAZARD DATA**

### **EMERGENCY OVERVIEW:**

**CAUTION:** May cause irritation to skin and eyes. Avoid contact with skin, eyes and clothing. Do not take internally.

Empty containers may contain residual product. Do not reuse container unless properly reconditioned.

**PRIMARY ROUTE(S) OF EXPOSURE:** Eye & Skin

**EYE CONTACT:** Can cause mild to moderate irritation

**SKIN CONTACT:** Can cause mild, short-lasting irritation

**SYMPTOMS OF EXPOSURE:** A review of available data does not identify any symptoms from exposure not previously mentioned.

**AGGRAVATION OF EXISTING CONDITIONS:** A review of available data does not identify any worsening of existing conditions.

## **7. EMERGENCY AND FIRST AID PROCEDURES**

**SKIN:** Wash exposed area with soap and water. If irritation or abnormalities persist, call a physician.

**EYE:** Immediately flush eyes with water for 15 minutes, if irritation or abnormalities persist, call a physician.

**INHALATION:** Remove to fresh air. If breathing becomes difficult, give oxygen and call a physician.

**INGESTION:** Do not induce vomiting. Call a physician immediately.

**CAUTION:** If unconscious, having trouble breathing or in convulsions, do not induce vomiting or give water. Call for medical assistance immediately.

## **8. HANDLING, ACCIDENTAL RELEASE MEASURES & DISPOSAL CONSIDERATIONS**

**Storage:** Keep container tightly closed when not in use.

### **DISPOSAL:**

In Ontario, the waste class under Regulation 347 is: 233L

### **SMALL SPILLS:**

Soak up spill with absorbent material. Place residues in a suitable, covered, properly labeled container. Wash affected area.

### **LARGE SPILLS:**

Contain liquid using absorbent material, by digging trenches or by dyking. Reclaim into recovery or salvage drums or tank truck for proper disposal. Contact approved waste hauler for disposal of contaminated recovered material. Dispose of material in compliance with regulations indicated.

Dispose of wastes in an approved incinerator or waste treatment/disposal site, in accordance with all applicable regulations. Do not dispose of wastes in local sewer or with normal garbage.

## ENVIRONMENTAL PRECAUTIONS

This product should NOT be directly discharged into lakes, ponds, streams, waterways or public water supplies.

As a non-hazardous liquid waste, it should be solidified with stabilizing agents (such as sand, fly ash, or cement) so that no free liquid remains before disposal to an industrial waste landfill. A non-hazardous liquid waste can also be incinerated in accordance with local, state, provincial and federal regulations.

## 9. INDUSTRIAL HYGIENE CONTROL MEASURES

### OCCUPATIONAL EXPOSURE LIMITS:

This product does not contain any substance that has an established exposure limit.

Respiratory Protection: None normally required.

For large spills, entry into large tanks, vessels or enclosed small spaces with inadequate ventilation, a positive pressure, self-contained breathing apparatus is recommended.

Ventilation: General ventilation is recommended.

Eye Protection: Safety glasses, if personally preferred

Gloves: Generally not necessary. Personal preference. Examples of impermeable gloves available on the market are neoprene, nitrile, PVC, natural rubber, viton, and butyl (compatibility studies have not been performed).

If clothing is contaminated, remove clothing and thoroughly wash the affected area. Launder contaminated clothing before reuse.

## 10. TOXICOLOGICAL PROPERTIES

### SENSITIZATION:

This product is not expected to be a sensitizer.

A "LC50-96" Pass/Fail Bioassay test. This test determines the lethality of a fluid on young aquatic organisms. The fluid fails if 50% or more of the animals are dead after 96 hours in the fluid.

96 hour static acute LC50 to Rainbow Trout = Greater than 1,000 mg/L

96 hour no observed effect concentration = 125 mg/L based on no mortality or abnormal effects

96 hour static acute LC50 to Sheepshead Minnow = Greater than 1,000 mg/L

96 hour no observed effect concentration = 1,000 mg/L (highest concentration tested) based on no mortality or abnormal effects.

96 hour static acute LC50 to Mysid Shrimp = 400 mg/L

96 hour no observed effect concentration = 180 mg/L based on no mortality or abnormal effects.

96 hour static acute LC50 to Daphnia Magna - 400 mg/L

96 hour no observed effect concentration = 56 mg/L (lowest concentration tested) based on no mortality or abnormal effects.

---

## Microtoxicity

The Microtox bioassay has been established as the reference test for mud additive toxicity testing.

Test Method: Luminescent Bacteria, IC50@ 15 min

Reference: Appendix 1: Microtox Bioassay Procedure, Drilling Waste Management, Guide G50. 1993. Alberta Energy and Utilities Board, Calgary, AB, Canada.

Sample: Poly Drill 1330, sample #97324-1 for test #970723, 97/05/09 by D. Lintott

Preparation: Sample was diluted to 2 g/L, which formed thick, slightly cloudy liquid. The sample was then centrifuged for 1 hour.

Test Results:

SAMPLE	TREATMENT	%CTL	IC20%	IC50	RESULT
97324-1	None	N/A	14 (9-22)	>91	PASS

The following results are for a 1% aqueous solution of product.

**CARCINOGENICITY:**

None of the substances in this product are listed as carcinogens by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) or the American Conference of Government Industrial Hygienists (ACGIH).

**HUMAN HAZARD CHARACTERIZATION:**

Based on our Hazard Characterization, the potential human hazard is: LOW

**ENVIRONMENTAL HAZARD AND EXPOSURE CHARACTERIZATION:**

Based on our Hazard Characterization, the potential environmental hazard is: LOW.

**11. DEPARTMENT OF TRANSPORTATION INFORMATION**

PROPER SHIPPING NAME/HAZARD CLASS MAY VARY BY PACKAGING, PROPERTIES, AND MODE OF TRANSPORTATION. TYPICAL PROPER SHIPPING NAMES FOR THIS PRODUCT ARE:

ALL TRANSPORTATION MODES: PRODUCT IS NOT REGULATED DURING TRANSPORTATION

Shipping Name: Liquid Drilling Additive

Hazard Class: Not hazardous

Cautionary Labeling: None required

**14. OTHER INFORMATION**

This information contained herein is given in good faith, but no warranty, expressed or implied is made

# Material Safety Data / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.  
8069 River Way, Delta, British Columbia,  
Canada V4C 1L3  
Ph. (604) 940-6050 Fax (604) 940-6000

EMERGENCY 1-800-585-8645

## SECTION I: IDENTIFICATION OF PRODUCT

PRODUCT NAME: **550X® POLYMER**

CHEMICAL FAMILY: Anionic water soluble polymer  
PRODUCT USE: Drilling mud additive  
WHMIS CLASSIFICATION: Not WHMIS regulated

## TRANSPORTATION OF DANGEROUS GOODS (TDGR)

CLASSIFICATION: Not applicable  
PACKAGE GROUP: Not applicable  
UN NUMBER (PDN): Not applicable

## SECTION II: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENTAGE	CAS NUMBER	LD50	LC50
Copolymer of Acrylamide and Sodium Acrylate		25085-02-3		
Acrylamide	0.1000	79-06-1		

## SECTION III: HEALTH HAZARDS

### ROUTES OF ENTRY

[XXX] Skin [XXX] Eye Contact [XXX] Inhalation [XXX] Ingestion

### THRESHOLD LIMIT VALUE: SKIN CONTACT:

Not determined  
No effects of exposure expected due to contact.  
Prolonged contact may cause slight skin irritation or dermatitis in some individuals.

### EYE CONTACT:

No effects of exposure expected with the exception of mechanical irritation.

### INGESTION:

No adverse effects expected.

### INHALATION:

Product may swell in throat causing choking.  
May cause sneezing, slight irritation of nose and throat.

## SECTION IV: FIRST AID MEASURES

### SKIN CONTACT:

Wash with soap and water as a precaution. In case of persistent skin irritation, consult a physician.

### EYE CONTACT:

Rinse thoroughly with plenty of water, also under the eyelid. In case of persistent eye irritation, consult a physician.

### INGESTION:

The product is not considered toxic based on studies on laboratory animals. Do not induce vomiting, give 2-3 glasses of water.

### INHALATION:

Move to fresh air. If not breathing give artificial respiration.  
Seek medical attention.

# Material Safety Data / Fiche signalétique

## WESTCOAST DRILLING SUPPLIES LTD.

8089 River Way, Delta, British Columbia,  
Canada V4O 1L8  
Ph: (604) 940-6050 Fax (604) 940-8080

EMERGENCY 1-800-665-667

## 550X® POLYMER

Page 2 of 4

### SECTION V: PHYSICAL DATA

APPEARANCE	White granular solid
ODOR	None
SPECIFIC GRAVITY	0.8 at 25° C (77 F)
BOILING POINT (°C)	Not applicable
MELTING POINT (°C)	Not determined
SOLUBILITY IN WATER	Forms a gel
PERCENT VOLATILE BY VOLUME	Not determined
EVAPORATION RATE	Not determined
VAPOR PRESSURE (mm Hg)	Not determined
VAPOR DENSITY (Air=1)	Not determined
pH	4 - 9 @ 5g/L

### SECTION VI: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT	93° C (200 F)
FLAMMABLE LIMITS	Not determined
EXTINGUISHING MEDIA	Dry Chemical, Carbon Dioxide
SPECIAL FIRE FIGHTING PROCEDURES	Aqueous solutions or powders that become wet render surfaces extremely slippery.
UNUSUAL FIRE AND EXPLOSION HAZARDS	No special equipment required.

### SECTION VII: REACTIVITY DATA

STABILITY	[XXX] Stable [ ] Unstable
INCOMPATIBILITY (Conditions to avoid)	Oxidizing agents
CONDITIONS OF REACTIVITY	Not known
HAZARDOUS DECOMPOSITION PRODUCTS	NO <sub>x</sub> , CO <sub>x</sub>
HAZARDOUS POLYMERIZATION	[XXX] Will not occur [ ] May occur



# Material Safety Data / Fiche signalétique

WESTCOAST DRILLING SUPPLIES LTD.  
8069 River Way, Delta, British Columbia,  
Canada V8G 1L3  
Ph. (604) 940-6050 Fax (604) 940-6080

EMERGENCY 1-800-665-8641

## SS0X POLYMER

Page 4 of 4

### SECTION X: PREPARATION

The information contained herein is given in good faith, but no warranty, expressed or implied is made.

DATE ISSUED: August, 2001

DATE REVISED: August, 1998

BY: Product Safety Committee

### AMENDMENT HAZARDOUS INGREDIENTS (SS0X)

Material or component	WT% Hazard data
COPOLYACRYLAMIDE/SODIUM ACRYLATE	Not considered hazardous

### ENVIRONMENTAL

DEGRADABILITY/AQUATIC TOXICITY:  
OCTANOL/WATER PARTITION COEFFICIENT  
WASTE DISPOSAL METHODS:

Not determined  
Not determined  
Incineration and/or disposal in Chemical Landfill.  
Disposer must comply with federal, provincial and local  
disposal or discharge laws.

RCRA STATUS OF UNUSED MATERIAL  
IF DISCARDED:  
HAZARDOUS WASTE NUMBER:

Not a "Hazardous Waste"  
Not available

REPORTABLE QUANTITY:  
THRESHOLD PLANNING QUANTITY:  
TOXIC CHEMICAL RELEASE REPORTING:

EPA 40 CFR (CERCLA 102):	Not applicable
EPA 40 CFR 355 (SARA 301-304):	Not applicable
EPA 40 CFR 372 (SARA 311-313):	Not applicable

EPA HAZARD CLASSIFICATION CODE:

ACUTE - Yes	CHRONIC - No
PIRE - No	PRESSURE - No
	REACTIVE - No

HMS AND NFPA RATINGS:  
HEALTH  
FLAMMABILITY  
REACTIVITY  
SPECIAL

HMS	NFPA
1	1
0	0
1	1
Not applicable	Not applicable

# Material Safety Data / Fiche signalétique

**WESTCOAST DRILLING SUPPLIES LTD.**  
 8069 River Way, Delta, British Columbia,  
 Canada V4G 1L3  
 Ph. (604) 940-8050 Fax (604) 940-6080

EMERGENCY 1-800-685-8845

**550X® POLYMER**

Page 3 of 4

## SECTION VIII: PREVENTIVE MEASURES

### SPECIAL PROTECTION INFORMATION

#### RESPIRATORY PROTECTION

Dust masks are recommended where concentration of total dust is more than 10 mg/m<sup>3</sup>

#### VENTILATION

General mechanical

#### PROTECTIVE GLOVES

Chemically resistant

#### EYE PROTECTION

Safety glasses with side shields

#### OTHER PROTECTIVE EQUIPMENT (Specify)

Not known

### ACCIDENTAL RELEASE MEASURES

#### STEPS TO BE TAKEN IN CASE THE MATERIAL IS SPILLED OR RELEASED

Do not flush with water. Clean up promptly by sweeping or vacuum.  
 Keep in suitable and closed containers for disposal.  
 After cleaning, flush away trace with water.

### PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Wash hands before breaks and at the end of the day. Keep in a cool dry place (0 - 30 °C)

### WASTE DISPOSAL METHOD

Can be land filled or incinerated, when in compliance with local, provincial and federal regulations.

## SECTION IX: TOXICOLOGICAL INFORMATION

#### CARCINOGENICITY

Not determined

#### REPRODUCTIVE TOXICITY

Not determined

#### TERATOGENICITY

Not determined

#### MUTAGENICITY

Not determined

#### DEVELOPMENTAL TOXICITY

Not determined

#### CHRONIC EFFECTS:

This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.



# Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Protective Clothing	TDG (pictograms)
	D-2A, D-2B		

## Section 1. Chemical Product and Company Identification

Product Name	<b>PETRO-CANADA ANTIFREEZE</b>	Code	W269
Synonym	Universal Antifreeze, Radiator Antifreeze, Diesel Antifreeze, Petro-Canada Antifreeze-Coolant, Petro-Canada Heavy Duty Antifreeze-Coolant, Pre-Mix Antifreeze, Petro-Canada Premium Radiator Antifreeze, Diesel Engine Coolant, Pre-Mixed Radiator Antifreeze/Coolant Petro-Canada.	Validated on	5/11/2005.
Manufacturer	PETRO-CANADA P.O. Box 2844 Calgary, Alberta T2P 3E3	In case of Emergency	Petro-Canada: 403-296-3000 Canutec Transportation: 613-996-6666 Poison Control Centre: Consult local telephone directory for emergency number(s).
Material Uses	Used as an engine antifreeze coolant.		

## Section 2. Composition and Information on Ingredients

			Exposure Limits (ACGIH)		
Name	CAS #	% (W/W)	TLV-TWA(8 h)	STEL	CEILING
Ethylene glycol	107-21-1	≥45	Not established	Not established	100 mg/m <sup>3</sup>
Sodium tetraborate pentahydrate (Diesel Engine Coolant only)	12179-04-3	≤5	1 mg/m <sup>3</sup>	Not established	(aerosol) Not established
Manufacturer Recommendation	Not applicable				
Other Exposure Limits	Consult local, state, provincial or territory authorities for acceptable exposure limits.				

## Section 3. Hazards Identification.

Potential Health Effects	Contact with this product may cause eye irritation. Not expected to cause more than slight skin irritation. Inhalation of this product may cause respiratory tract irritation. Ingestion may be extremely hazardous. May cause teratogenicity/embryotoxicity. May cause damage to reproductive organs. For more information refer to Section 11 of this MSDS.
--------------------------	---

## Section 4. First Aid Measures

Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.
Skin Contact	Remove contaminated clothing - launder before reuse. Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform artificial respiration. Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting because of danger of aspirating liquid into lungs. Seek medical attention.
Note to Physician	Not available

## Section 5. Fire-fighting Measures

Flammability	May be combustible at high temperature.	Flammable Limits	Lower: 3.2%, Upper: 15.3%
Flash Points	Closed Cup: 116°C (241°F) (Tagliabue) Open Cup: 116°C (241°F) (Cleveland)	Auto-Ignition Temperature	413°C (775°F)
Fire Hazards in Presence of Various Substances	Low fire hazard. This material must be heated before ignition will occur.	Explosion Hazards in Presence of Various Substances	Do not cut, weld, heat, drill or pressurize empty container.

<b>Products of Combustion</b>	Carbon oxides (CO, CO <sub>2</sub> ), smoke and irritating vapours as products of incomplete combustion.
<b>Fire Fighting Media and Instructions</b>	NAERG2004, GUIDE 171, Substances (low to moderate hazard). If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (0.5 mile) in all directions; also, consider initial evacuation for 800 meters (0.5 mile) in all directions. Shut off fuel to fire if it is possible to do so without hazard. If this is impossible, withdraw from area and let fire burn out under controlled conditions. Withdraw immediately in case of rising sound from venting safety device or any discolouration of tank due to fire. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. SMALL FIRE: use DRY chemicals, foam, water spray or CO <sub>2</sub> . LARGE FIRE: use water spray, fog or foam. For small outdoor fires, portable fire extinguishers may be used, and self contained breathing apparatus (SCBA) may not be required. For all indoor fires and any significant outdoor fires, SCBA is required. Respiratory and eye protection are required for fire fighting personnel.

### Section 6. Accidental Release Measures

<b>Material Release or Spill</b>	IN THE EVENT OF A LARGE SPILL CONSIDER THE FOLLOWING CONTROL MEASURES: Consult current National Emergency Response Guide Book (NAERG) for appropriate spill measures if necessary. Extinguish all ignition sources. Stop leak if safe to do so. Dike spilled material. Use appropriate inert absorbent material to absorb spilled product. Collect used absorbent for later disposal. Ventilate area. Ensure clean-up personnel wear appropriate personal protective equipment. Avoid breathing vapours or mists of material. Avoid contact with spilled material. Avoid contaminating sewers, streams, rivers and other water courses with spilled material. Notify appropriate authorities immediately.
----------------------------------	---

### Section 7. Handling and Storage

<b>Handling</b>	Avoid contact with any sources of ignition, flames, heat, and sparks. Avoid confined spaces and areas with poor ventilation. Avoid skin contact. Avoid eye contact. Avoid inhalation of product vapours or mists. Do not ingest this product. Wear proper personal protective equipment (See Section 8). Empty containers may contain product residue. Do not pressurize, cut, heat, or weld empty containers. Do not reuse containers without commercial cleaning and/or reconditioning. Personnel who handle this material should practice good personal hygiene during and after handling to help prevent accidental ingestion of this product. Properly dispose of contaminated leather articles including shoes that cannot be decontaminated.
<b>Storage</b>	Store in dry, cool, well-ventilated area. Store away from heat and sources of ignition. Keep container tightly closed. Store away from incompatible and reactive materials (See section 5 and 10).

### Section 8. Exposure Controls/Personal Protection

<b>Engineering Controls</b>	For normal application, special ventilation is not necessary. If user's operations generate vapours or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Make-up air should always be supplied to balance air removed by exhaust ventilation. Ensure that eyewash station and safety shower are close to work-station.
<b>Personal Protection - The selection of personal protective equipment varies, depending upon conditions of use.</b>	
<b>Eyes</b>	Chemical splash goggles should be worn when handling this material.
<b>Body</b>	If this material may come into contact with the body during handling and use, we recommend wearing appropriate protective clothing to prevent contact with the skin. (Contact your PPE provider for more information).
<b>Respiratory</b>	A minimum of NIOSH-approved air-purifying respirator with a organic vapour cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstances where air-purifying respirators may not provide adequate protection.
<b>Hands</b>	If this material may come in contact with the hands during handling and use, we recommend wearing gloves of the following material(s): Neoprene, Polyvinyl chloride (PVC). Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns.
<b>Feet</b>	Wear appropriate footwear to prevent product from coming in contact with feet and skin.

### Section 9. Physical and Chemical Properties

<b>Physical State and Appearance</b>	Clear viscous liquid.	<b>Viscosity</b>	Not available
<b>Colour</b>	Green.	<b>Pour Point</b>	Not available
<b>Odour</b>	Odourless.	<b>Softening Point</b>	Not applicable.
<b>Odour Threshold</b>	Not available	<b>Dropping Point</b>	Not applicable.
<b>Boiling Point</b>	129 to 197°C (264 to 387°F)	<b>Penetration</b>	Not applicable.
<b>Density</b>	1.07 to 1.145 (Water = 1)	<b>Oil / Water Dist. Coefficient</b>	Not available

<b>Vapour Density</b>	2.1 (Air=1).	<b>Ionicity (in water)</b>	Not available
<b>Vapour Pressure</b>	0.06 mmHg @ 20°C (68°F).	<b>Dispersion Properties</b>	Not available
<b>Volatility</b>	0% (w/w)	<b>Solubility</b>	Soluble in water, methanol and diethyl ether.

**Section 10. Stability and Reactivity**

<b>Corrosivity</b>	Not available		
<b>Stability</b>	The product is stable.	<b>Hazardous Polymerization</b>	Will not occur under normal working conditions.
<b>Incompatible Substances / Conditions to Avoid</b>	Reactive with oxidizing agents, acids, alkalis, perchloric acid, phosphorus and silvered copper wires carrying DC current.	<b>Decomposition Products</b>	May release COx, acrid smoke and irritating vapours when heated to decomposition.

**Section 11. Toxicological Information**

<b>Routes of Entry</b>	Skin contact, eye contact, inhalation and ingestion.
<b>Acute Lethality</b>	<u>Ethylene glycol (107-21-1):</u> LD50: 4700 mg/kg (oral/rat). LD50: 9530 mg/kg (dermal/rabbit).  <u>Sodium tetraborate pentahydrate (12179-04-3):</u> LD50: 3200-3500 mg/kg (oral/rat) (Boric acid). [Sodium tetraborate pentahydrate]
<b>Chronic or Other Toxic Effects</b>	
Dermal Route:	Short-term exposure is expected to cause only slight irritation, if any.
Inhalation Route:	Inhalation of this product may cause respiratory tract irritation.
Oral Route:	Extremely dangerous in case of ingestion.
Eye Irritation/Inflammation:	This product contains a component (at $\geq 1\%$ ) that can cause eye irritation. Therefore, this product is considered to be an eye irritant.
Immunotoxicity:	Not available
Skin Sensitization:	Contact with this product is not expected to cause skin sensitization, based upon the available data and the known hazards of the components.
Respiratory Tract Sensitization:	Contact with this product is not expected to cause respiratory tract sensitization, based upon the available data and the known hazards of the components.
Mutagenic:	This product is not known to contain any components at $\geq 0.1\%$ that have been shown to cause mutagenicity. Therefore, based upon the available data and the known hazards of the components, this product is not expected to be a mutagen.
Reproductive Toxicity:	Borates are possible reproductive toxins based upon available animal ingestion studies in several species. These studies usually involved high doses, over prolonged periods of time. A human study following occupational exposure to borate by inhalation concluded that, no adverse effects to reproduction were found in this population, under the conditions of this study.
Teratogenicity/Embryotoxicity:	This product contains a component(s) at $\geq 0.1\%$ that has been shown to cause teratogenicity and/or embryotoxicity in laboratory tests. Therefore, this product is considered to be a teratogen/embryotoxin (Ethylene glycol).
Carcinogenicity (ACGIH):	ACGIH A4: not classifiable as a human carcinogen (Ethylene glycol). This product is not known to contain any chemicals at reportable quantities that are listed as Group A1, A2, or A3 carcinogens by ACGIH.
Carcinogenicity (IARC):	This product is not known to contain any chemicals at reportable quantities that are listed as Group 1, 2A, or 2B carcinogens by IARC.
Carcinogenicity (NTP):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by NTP.
Carcinogenicity (IRIS):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by IRIS.
Carcinogenicity (OSHA):	This product is not known to contain any chemicals at reportable quantities that are listed as carcinogens by OSHA.
<b>Other Considerations</b>	The substance may be toxic to kidneys and liver. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated exposure to a highly toxic material may produce general deterioration of health by an accumulation in one or many human organs.

**Section 12. Ecological Information**

<b>Environmental Fate</b>	Not available	<b>Persistence/Bioaccumulation Potential</b>	Not available
<b>BOD5 and COD</b>	Not available	<b>Products of Biodegradation</b>	Not available
<b>Additional Remarks</b>	No additional remark.		


**Section 13. Disposal Considerations**

<b>Waste Disposal</b>	Spent/ used/ waste product may meet the requirements of a hazardous waste. Consult your local or regional authorities. Ensure that waste management processes are in compliance with government requirements and local disposal regulations.
-----------------------	--

**Section 14. Transport Information**

<b>TDG Classification</b>	Not a hazardous material for transport according to the TDG Regulations. (Canada)	<b>Special Provisions for Transport</b>	Not applicable.
---------------------------	---	---	-----------------

**Section 15. Regulatory Information**

<b>Other Regulations</b>		All of the components of this product are on the Domestic Substances List (DSL), are considered to be on the DSL, or are exempt from the New Substance Notification (NSN) requirements.																	
		All components of this formulation are listed on the US EPA-TSCA Inventory.																	
		This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.																	
		Please contact Product Safety for more information.																	
<b>DSD/DPD (Europe)</b> Not evaluated.		<b>HCS (U.S.A.)</b>		CLASS: Target organ effects. CLASS: Irritating substance.															
<b>ADR (Europe) (Pictograms)</b>		<b>DOT (U.S.A.) (Pictograms)</b>																	
<b>HMIS (U.S.A.)</b>		<b>NFPA (U.S.A.)</b>		<b>Rating</b>	<b>0 Insignificant</b>														
<table><tr><td>Health Hazard</td><td>2*</td></tr><tr><td>Fire Hazard</td><td>1</td></tr><tr><td>Reactivity</td><td>0</td></tr><tr><td>Personal Protection</td><td>H</td></tr></table>		Health Hazard	2*	Fire Hazard	1	Reactivity	0	Personal Protection	H	<table><tr><td>1 Fire Hazard</td><td></td></tr><tr><td>Health 2</td><td>0 Reactivity</td></tr><tr><td colspan="2">Specific hazard</td></tr></table>		1 Fire Hazard		Health 2	0 Reactivity	Specific hazard			<b>1 Slight</b>
Health Hazard	2*																		
Fire Hazard	1																		
Reactivity	0																		
Personal Protection	H																		
1 Fire Hazard																			
Health 2	0 Reactivity																		
Specific hazard																			
					<b>2 Moderate</b>														
					<b>3 High</b>														
					<b>4 Extreme</b>														

**Section 16. Other Information**

<b>References</b>	Available upon request. * Marque de commerce de Petro-Canada - Trademark
-------------------	---

**Glossary**

ACGIH - American Conference of Governmental Industrial Hygienists	IRIS - Integrated Risk Information System
ADR - Agreement on Dangerous goods by Road (Europe)	LD50/LC50 - Lethal Dose/Concentration kill 50%
ASTM - American Society for Testing and Materials	LDLo/TLCLo - Lowest Published Lethal Dose/Concentration
BOD5 - Biological Oxygen Demand in 5 days	NAERG'96 - North American Emergency Response Guide Book (1996)
CAN/CGA B149.2 Propane Installation Code	NFPA - National Fire Prevention Association
CAS - Chemical Abstract Services	NIOSH - National Institute for Occupational Safety & Health
CEPA - Canadian Environmental Protection Act	NPRI - National Pollutant Release Inventory
CERCLA - Comprehensive Environmental Response, Compensation and Liability Act	NSNR - New Substances Notification Regulations (Canada)
CFR - Code of Federal Regulations	NTP - National Toxicology Program
CHIP - Chemicals Hazard Information and Packaging Approved Supply List	OSHA - Occupational Safety & Health Administration
CNS - Central Nervous System	PEL - Permissible Exposure Limit
COD5 - Chemical Oxygen Demand in 5 days	RCRA - Resource Conservation and Recovery Act
CPR - Controlled Products Regulations	RTECS - Registry of Toxic Effects of Chemical Substances
DOT - Department of Transport	SARA - Superfund Amendments and Reorganization Act
DSCL - Dangerous Substances Classification and Labeling (Europe)	SD - Single Dose
DSD/DPD - Dangerous Substances or Dangerous Preparations Directives (Europe)	STEL - Short Term Exposure Limit (15 minutes)
DSL - Domestic Substance List	TDG - Transportation Dangerous Goods (Canada)
EEC/EU - European Economic Community/European Union	TDLo/TCLo - Lowest Published Toxic Dose/Concentration
EINECS - European Inventory of Existing Commercial Chemical Substances	TLM - Median Tolerance Limit
	TLV-TWA - Threshold Limit Value-Time Weighted Average
	TSCA - Toxic Substances Control Act
	USEPA - United States Environmental Protection Agency
	USP - United States Pharmacopoeia

EPA - Environmental Protection Agency  
EPCRA - Emergency Planning and Community Right to Know Act  
FDA - Food and Drug Administration  
FIFRA - Federal Insecticide, Fungicide and Rodenticide Act  
HCS - Hazard Communication Standard  
HMIS - Hazardous Material Information System  
IARC - International Agency for Research on Cancer

WHMIS - Workplace Hazardous Material Information System

**For Copy of MSDS**

Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)

Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228

For Product Safety Information: (905) 804-4752

Prepared by Product Safety - JDW on 5/11/2005.

Data entry by Product Safety - RS.

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*