



AIR LIQUIDE

MATERIAL SAFETY DATA SHEET

PRODUCT INFORMATION

PRODUCT: Oxygen, compressed

TRADE NAME: Oxygen

CHEMICAL NAME: Oxygen

SYNONYMS: Oxygen Compressed

FORMULA: O₂

CHEMICAL FAMILY: Gaseous oxidizer

MANUFACTURER'S NAME: Air Liquide Canada Inc.

MANUFACTURER'S ADDRESS: 1250 René-Lévesque Blvd. West Suite 1700

ADDRESS: Montréal (Québec) Canada H3B 5E6

SUPPLIER'S NAME: Air Liquide Canada Inc.

SUPPLIER'S ADDRESS: 1250 René-Lévesque Blvd. West Suite 1700

Montréal (Québec) Canada H3B 5E6

EMERGENCY PHONE NUMBER: (514) 878-1667

NUMBER:

MOLECULAR WEIGHT: 32.00

PRODUCT USE: Various

PRODUCT IDENTIFICATION UN 1072

NUMBER:

HAZARDOUS INGREDIENTS

CHEMICAL ID	CONCENTRATION	CAS #	LD(50)	LC(50)
Oxygen	>99.5%	7782-44-7	None	None


MSDS for: Oxygen, compressed / FaxBack Doc. # : 1132

PHYSICAL DATA

PHYSICAL STATE: Gas under pressure

APPEARANCE: Colorless gas

ODOR: Odorless



ODOR THRESHOLD: Not applicable
SPECIFIC GRAVITY (H₂O = 1): See Vapor Density (air = 1)
VAPOR PRESSURE: Not applicable (gas)
VAPOR DENSITY (air = 1): 1.11
EVAPORATION RATE: Not applicable (gas)
BOILING POINT: -182.97°C
FREEZING POINT: -218.57°C
pH: Not applicable (gas)
GAS DENSITY: 1.353 kg/m³ @ 15°C, 101.3 kPa
COEFFICIENT OF WATER/OIL @ 15°C, Bunsen Coefficient =
DISTRIBUTION: 0.0342

FIRE OR EXPLOSION HAZARD

CONDITIONS OF FLAMMABILITY:	Nonflammable gas
MEANS OF EXTINCTION:	Copious quantities of water for fires with oxygen as the oxidizer.
FLASHPOINT AND METHOD OF DETERMINATION:	Nonflammable gas
UPPER EXPLOSION LIMIT (% BY VOL):	Nonflammable gas
LOWER EXPLOSION LIMIT (% BY VOL):	Nonflammable gas
AUTO-IGNITION TEMPERATURE:	Nonflammable gas
FLAMMABILITY CLASSIFICATION:	Nonflammable gas
HAZARDOUS COMBUSTION PRODUCTS:	Nonflammable gas
EXPLOSION DATA:	Nonflammable gas
SENSITIVITY TO STATIC DISCHARGE:	None

MSDS for: Oxygen, compressed / FaxBack Doc. # : 1132

REACTIVITY DATA

CHEMICAL STABILITY: Stable as to decomposition
INCOMPATIBLE MATERIALS: All flammable materials, grease or oils
CONDITIONS OF REACTIVITY: Reactive under various conditions, temperature and pressure. All

elements, with the exception of the inert gases react directly with oxygen to form oxides. Reactivity increases with temperature.

HAZARDOUS DECOMPOSITION None

PRODUCTS:

TOXICOLOGICAL PROPERTIES

ROUTES OF ENTRY:

SKIN CONTACT: None

SKIN ABSORPTION: None

EYE: None

INHALATION: Breathing high concentrations greater than 75 molar per cent causes symptoms of hyperoxia which include cramps, nausea, dizziness, hypothermia, ambylopia, respiratory difficulties, bradycardia, fainting spells and convulsions capable of leading to death. For additional data on hyperoxia as it relates to oxygen pressure and exposure duration refer to L'Air Liquide's Gas Encyclopedia.

Also known as a central nervous system toxin at concentrations of 100% O₂ and at elevated atmospheric pressures.

INGESTION: None

ACUTE OVER EXPOSURE EFFECTS: The property is that of hyperoxia which leads to pneumonia. Concentrations between 25 and 75 molar percent present a risk of inflammation of organic matter in the body.

CHRONIC OVER EXPOSURE EFFECTS: None

EXPOSURE LIMITS: No TWA is established (ACGIH 1995-1996). Oxygen is the "vital element" in the atmosphere in which we live and breath (approximately 21 molar % of the atmosphere).

IRRITANCY OF PRODUCT: None

SENSITIZATION TO MATERIAL: None

CARCINOGENICITY, REPRODUCTIVE EFFECTS: None

TERATOGENICITY, MUTAGENICITY: None

TOXICOLOGICALLY SYNERGISTIC PRODUCTS: None

MSDS for: Oxygen, compressed / FaxBack Doc. # : 1132

PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Leather gloves. Safety goggles or glasses. Safety shoes

SPECIFIC ENGINEERING CONTROLS: Carbon steels and low alloy steels are acceptable for use at lower pressures. For high pressure applications use stainless steels, copper and its alloys, nickel and its alloys, brass, bronze, silicon alloys, Monel®, Inconel® or beryllium. Lead and silver or lead and tin alloys are good gasketing materials. Teflon® and Kel-F® are the preferred nonmetal gaskets.

Special Note: It should be recognized that the ignition temperature of metals and nonmetals in pure oxygen service decreases with increasing oxygen pressure. For additional information refer to L'Air Liquide's Gas Encyclopedia.

LEAK AND SPILL PROCEDURES: EVACUATE ALL PERSONNEL FROM AFFECTED AREA.

Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with an inert gas prior to attempting repairs. If leak is on container or container valve, contact the closest Air Liquide Canada location.

WASTE DISPOSAL: Do not attempt to dispose of waste or unused quantities. Return in the shipping container properly labeled, with any valve outlet plugs or caps secured and valve protection cap in place to Air Liquide Canada for proper disposal. For emergency disposal, contact the closest Air Liquide Canada location.

HANDLING PROCEDURES AND EQUIPMENT: USE ONLY IN WELL-VENTILATED AREAS.

Valve protection caps must remain in place unless container is secured with valve outlet piped to the point of use. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure reducing regulator when connecting cylinder to lower pressure piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous back flow into the cylinder. Do not tamper with valve (safety device). Close valve after each use and when empty.

STORAGE REQUIREMENTS: Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non combustible construction away from heavily trafficked areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 52°C. Cylinders must be stored upright and firmly

secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in - first out" inventory system to prevent full cylinders being stored for excessive periods of time.

TDG CLASSIFICATION: 2.2 (5.1)

WHMIS CLASSIFICATION: A, C

SPECIAL SHIPPING INFORMATION: Always secure cylinders in an upright position before transporting them. NEVER transport cylinders in trunks of vehicles, enclosed vans, truck cabs or in passenger compartments. Transport cylinders secured in open flatbed or in open pick-up type vehicles.

MSDS for: Oxygen, compressed / FaxBack Doc. # : 1132

FIRST AID MEASURES

SPECIFIC FIRST AID PROCEDURES: PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVER EXPOSURE TO OXYGEN. RESCUE PERSONNEL SHOULD BE COGNIZANT OF EXTREME FIRE HAZARD ASSOCIATED WITH OXYGEN-RICH ATMOSPHERES.

INHALATION: Conscious persons should be assisted to an uncontaminated area and breathe fresh air. They should be kept warm and quiet. The physician should be informed that the victim is experiencing (has experienced) hyperoxia.

Unconscious persons should be moved to an uncontaminated area and given assisted respiration. When breathing has been restored, treatment should be as above. Continued treatment should be symptomatic and supportive.

EYE CONTACT: Not applicable

SKIN CONTACT: Not applicable

MSDS for: Oxygen, compressed / FaxBack Doc. # : 1132

PREPARATION INFORMATION

PREPARED BY: Safety Department

DATE PREPARED: 09/01/88

LAST REVISION DATE: 04/19/2002

FOR INFORMATION OR MSDS, CONTACT YOUR LOCAL A.L.C. OFFICE OR DISTRIBUTOR.

MAIN ALC SALES LOCATIONS:

Newfoundland	St.John's	Tel : 709 758-2765	Fax : 709 758-2800
Nova Scotia	Dartmouth	Tel : 902 468-5152	Fax : 902 468-5782
New Brunswick	Moncton	Tel : 506 857-3280	Fax : 506 857-9734
New Brunswick	Saint John	Tel : 506 634-8960	Fax : 506-646-1021
Quebec	Vanier	Tel : 418 683-1917	Fax : 418 683-7088
Montreal	Anjou	Tel : 514 356-7600	Fax : 514 351-0531

Toronto	Bramalea	Tel : 905 793-2000	Fax : 905 793-9257
Eastern Ontario	Oshawa	Tel : 905 576-1860	Fax : 905 571-3779
Lake Ontario	Burlington	Tel : 905 335-4877	Fax : 905 335-0301
South West Ontario	London	Tel : 519 455-3990	Fax : 519 455-3828
Northern Ontario	Sudbury	Tel : 705 674-7777	Fax : 705 674-0517
Manitoba & N.W. Ont.	Winnipeg	Tel : 204 989-9353	Fax : 204 779-1047
Saskatchewan	Saskatoon	Tel : 306 933-2722	Fax : 306 931-6641
Calgary	Calgary	Tel : 403 777-4700	Fax : 403 777-4727
Edmonton	Edmonton	Tel : 780 438-5600	Fax : 780 438-2801
Vancouver	Vancouver	Tel : 604 606-4300	Fax : 604 606-4246
Vancouver Island	Nanaimo	Tel : 250 758-1761	Fax : 250 758-1911
Okanagan	Kelowna	Tel : 250 769-4222	Fax : 250 769-7224

THE INFORMATION, RECOMMENDATIONS AND DATA CONTAINED IN THIS DOCUMENT ARE INTENDED TO BE USED BY PROPERLY TRAINED AND QUALIFIED PERSONNEL ONLY AND AT THEIR SOLE RISKS AND DISCRETION. THE INFORMATION, RECOMMENDATIONS AND DATA HEREIN CONTAINED ARE DERIVED FROM SOURCES WHICH WE BELIEVE TO BE RELIABLE. HOWEVER, AIR LIQUIDE CANADA INC. MAKES NO REPRESENTATION AND GIVES NO WARRANTY OF ANY KIND WHATSOEVER WITH RESPECT TO THEIR ACCURACY OR COMPLETENESS AND ASSUMES NO LIABILITY FOR DAMAGES OR LOSS ARISING DIRECTLY OR INDIRECTLY FROM THEIR USE, WHETHER PROPER OR IMPROPER.