CITY OF IQALUIT

OPERATION AND MAINTNANCE MANUAL SEWAGE LAGOON

November, 24, 2004

INTRODUCTION


BACKGROUND

The sewage lagoon which serves the City of Iqaluit was built in 1978 on a tidal plain at the head of Koojesse Inlet (see figure 1).

In 1983 the dykes were upgraded which included lining the exterior slopes with filter cloth and rip-rap, constructing an overflow in the west dyke, adding a new section to the south end of the east dyke, and raising the west dyke by 1.5m. The exterior slopes were lined with filter cloth and rip-rap to prevent the dyke from tidal erosion.

In 1986 a manhole was installed in the west dyke to accommodate the installation of a control valve to regulate the continuous effluent discharge flow.

In 1991 a drainage channel was built adjacent to the lagoon in order to divert spring run off from entering the lagoon.



CITY OF IQALUIT CONTACT LIST

	CELL#	WORK#
DISPATCH	N/A	979- 5650
Director of Public Works	975-1877	975-8509
Operations Superintendent of Public Works	975-1774	979-5653
Utilidor Foreman	975-1443 Pager# 32	979-5648
	HOME #	WORK#
Utilidor Maintainer	979-6573	979-5648
Utilidor Technician	979-5821	979-5648
Utilidor Tech. Asst.	979-7742	979-5648
Utilidor Tech. Asst.	979-0346	979-5648

After hour calls will be dispatched through the Iqaluit Fire Department dispatch to the Public Works Utilidor Crew through and on call schedule posted at the Dispatch Office. The Utilidor crew is required to have one individual on call for after hour's emergencies.

OPERATIONS AND MAINTENANCE

The City sewage lagoon is monitored by the City of Iqaluit Utilidor crew. The crew consists of a Foreman and five other staff with various levels of training and experience.

The Utilidor crew monitors the Sewage Lagoon daily and records on there daily check sheet any activities that they are required to perform. (Attached daily check sheet)

DAILY CHECK

*Monitor and control sewage lagoon level through the regulating of a control valve located in manhole at the west end dyke (Attached, Safety, Confined Space Entry Procedures)

MONTHLY CHECK

* Perform a walk around inspection of lagoon checking all dykes for damage and seepage which might be early signs of a possible dyke breech. Staff are required to write any problems identified on the daily check sheet and bring it immediately to the attention of there supervisor.

YEARLY CHECK

*Assure that clearing of all snow from the drainage channel adjacent the sewage lagoon is performed prior to spring run off.

SEWAGE LAGOON SPILL

If the sewage lagoon were to breech and a spill were to occur the City of Iqaluit spill contingency plan would be put in to action (See attached City of Iqaluit Spill Contingency Plan).

網	S GENERAL CONTRACTOR SERVICE	FUNCTION	MONDAY	TUESDAY	WEDNESDAY	THURSDAY	FRIDAY
では、	Sewage Plant						
	AV. 208	FLOW#1					and a
	Figure 18	FLOW#2					
	37 马油	TEMP.#1			-		
		TEMP.#2					
	A.V. 207	FLOW					
u	FT STATION #1	PUMP#1				7	
ST. ST.		PUMP#2					
257	A.V. 404	FLOW	A. D	100			
	REHEAT # 222	SUPPLY TEMP.					
N. W. S. S.		RETURN TEMP.	The state of				
L	IFT STATION #2	PUMP#1					
の事が		PUMP#2	R.H.	17.37.51			
and the	AV. 223	FLOW#1	W		19 8 1 Egg		
6353	建制或制制	FLOW#2		in the second			1000
Nunactes .	AV. 224	FLOW	1000				
422/20	A.V. 225	FLOW		A STATE OF			1.00%
-	A.V. 226	FLOW	Kontrol				
_	AV. 234	FLOW	Andrews - Co.				· 1000
3	AV. 500	FLOW	张校道 。	· 通报条法	i hwe		
A CLUS	OOSTER STATIO		基度 。221	i Baktu			27.75
DAMES DAMES	HAPPY VALLEY			n likking			
THE PERSON ASSESSED AS NOT THE PERSON OF THE		RETURN TEMP.	他 经支持数据				
	ASTRO HILL	SUPPLY TEMP.	Barrie Barrier	· 教育的	5 - 10 - 1		1 70 5
SACASTANDARY	以智慧 证	RETURN TEMP	To be	张 精神饮食	多家的社		
X SAMPLE	W.T.P.	BOILERS	Mark to	16 (B. B. K.)	*29 PASSES 1 PASSES		
Separate Sep	TRIGRAM	SUPPLY TEMP		海 (草油) [19	建		1000
KARDO		RETURN TEMP	T REMEDIAL SERVICE	然 搜修学	8 200 200		- 177

DALUIT MUNICIPAL V	VORKS CHECKLIS	ST WEEK ENDING	Apt 2	3 2004		
0.005344645574547760555-15	DESCRIPTION OF SHORE OF SHORE AND ADDRESS OF SHORE OF SHORE AND ADDRESS		Control of the second s	WEDNESDAY	THURSDAY	33 FRIDAY
Sewage PINGGON		06	OK	ok	ok	Oh
A.V. 208	FLOW#1	5	5	4	4	7
	FLOW#2	5.0	50	50	50	50
Beach ROW WHITE ROW	TEMP.#1	0E	OK	OK	ok	ok
Middle School Jeanie School	TEMP.#2	OK.	OK	06	OK	ot
A.V. 207	FLOW	3	6.3	2	3	3
LIFT STATION#1	PUMP#1	OH	OK	ok	ok	ok
	PUMP#2	OH	oK	OK	ok	OH
120000 371	FLOW	ok	OK	OK	ok	ot
REHEAT # 222	SUPPLY TEMP.	9/59	8/54	9/55	9/54	956
	RETURN TEMP.	9	12	9	9	9
LIFT STATION #2	PUMP#1	17126	17128	17130	17132	17135
	PUMP#2	Oly	OK	OK	OK	ot
A.V. 223	FLOW#1	3	3	3	3	3
	FLOW#2	30	30	30	30	30
AV. 2000	FLOW	OK	oK	3K	OK	oh
AV. 28 503	FLOW	OK	OK	ok	OK	of
A.V. 008 509		OK	OK	OK	OK	8h
AV. 000 570	FLOW	ok	OK	OK	0K	ok
A.V. 500	FLOW					
BOOSTER STATION		OK	OK	OK	OK	ot
HAPPY VALLEY	SUPPLY TEMP.	18/33	17/33	18/34	17/34	18/3
	RETURN TEMP.	1	9	10	10	9
ASTRO HILL	SUPPLY TEMP.	20/24	20/29	20/15	19/24	10/1-
	RETURN TEMP	1 1	9	10	9	9
000/552	BOILERS	OK	OK.	ok	OK	0k
TRIGRAM	SUPPLY TEMP	8	8	9	9	9
	RETURN TEMP	. 18	18	18	17	17

Confined Entry Permit Hot Applications (post at all Entrances to Confined Space

Pern	nit #		
Natu	Welding Soldering Cutting Grinding Scraping Painting Unacceptable Air Monitoring Levels	}	Special Entry Procedure Checklists Forms II and III
Perso	Utilidor Foreman to Determine Appro Checklists to be Performed During Di Work. Onal Protective Equipment Require: Specific Determined by Utilidor Forem	sscus	

Location and Description of Confined Space					
Details of Work to be	Performed:				
Foreman in Charge of Additional Checklist to					
Authorized Entrants	All Perso	nal	Adequatly Trained		
	Yes □	No			
	Yes □	No			
	Yes 🗆	No			
Atmospheric Monitoria Instrument Used Calibrated	Yes 🗆				
Suction Test Yes	No No				

Time Date	Oxygen Must be 19.5%- 23.5%	H2S 10PPM	CO 30PPM	CH4 10%Lev
Prior to Venting				
1.				
2.				
3.				

4.			
Name and S	ignature of Tester		
		Print	
	Data	Sign	_
	Date		_
Permit Expir	res at Date and Time		_
Work Comp			
	Utilidor Foreman	Date	_
	Entrant	Date	_
	Stand By	Date	_
	Stand By Entrant	Date	_

Entry Procedures I Confined Space

Permit #		-		
Check When Com	pleted			
☐ All Persons Trained in C Stand By Persons and be Awa	s to E Confine erson I re of t	ed Space Acc Must Be Trai he Emergency	H Contess and index of the Contest o	nfined Space must be d in Use of Equipment a Confined Space Entry
Completed				
Lock Out and Isol	ation			
Electrical Energy		Lock Out		
Mechanical		Stops		Disconnect
Piping		Blank/Blind		Block/Bleed
Hyoraulic		Lock out		Disconnect
Pneumatic		Lock out		Disconnect
Gravity		Stops		

Secure Area Around A.V./M.H. Confined Space by
Installing Barricades
Ensure no Vehicle Exhaust can Enter A.V./M.H. Confined
Space When Opened * No Exhaust Near Fan Intake
Calibrate and Zero Air Monitoring Equipment (Enter Data
on Entry Permit)
Test for Vacuum on Air Monitoring Equipment (Enter Data
on Entry Permit)
Use Air Monitoring Equipment to Test Around the Opening
of A.V./M.H. Confined Space Prior to Opening
☐ Test Results Negative Enter Data on Entry Permit
and Continue with Entry Procedures
☐ Air Monitoring Equipment Shows Press H2S, CO
or Oxygen (Enter Data on Entry)
□ Divert Traffic and Clear Area of Passer By's
☐ Ventilate Area Until Air Monitor Levels Normal enter
Data on Entry Permit
☐ Proceed with Entry Procedures

☐ Unable to Obtain Acceptable Air Levels Contact Utilidor Forman (Hot Entry Permit Required)
☐ Barricade Off Area
Put Mechanical Winch and Tri-Pod in Place Un Lock and Open Confined Space
Ventilate Confined Space for 20 Minutes Extend Vent to Bottom of Space ☐ Ensure Air Intake Away From any Contaminating
Source
Lower Air Monitoring Equipment to Test for Acceptable Levels of O2, H2S CO and CH4 Perform Air Testing at Different Levels Over Entire Depth of Space and Enter Data on Entry Permit If Air Levels Not Acceptable Continue to Ventilate and Test Air quality Until within Acceptable Levels Unable to Obtain Acceptable Levels Contact Utilidor Foreman
(Hot Permit Required)
 □ Barricade OFF Area □ Re-Lock Confined space or put cover on M.H.

 Unable to Obtain Acceptable Air Levels Contact Utilidor Forman (Hot Entry Permit Required)
☐ Barricade Off Area
Put Mechanical Winch and Tri-Pod in Place
Un Lock and Open Confined Space
Ventilate Confined Space for 20 Minutes Extend Vent to Bottom of Space
☐ Ensure Air Intake Away From any Contaminating Source
Lower Air Monitoring Equipment to Test for Acceptable Levels of O2, H2S CO and CH4 Perform Air Testing at Different Levels Over Entire Depth of Space and Enter Data on Entry Permit If Air Levels Not Acceptable Continue to Ventilate and Test Air quality Until within Acceptable Levels Unable to Obtain Acceptable Levels Contact Utilidor Foreman
(Hot Permit Required)
 □ Barricade OFF Area □ Re-Lock Confined space or put cover on M.H.

Com	pletion and Reporting Procedures					
	Remove all Equipment Once Work Completed					
	Re-Lock A.V. or Confined Space Re Install Cover on M.H.					
	Notify Utilidor Foreman Upon Completion of Confined Space Entry					
	Complete Entry Permit Form and Checklists. Deliver a Copy of the Permit and Checklist to Utilidor Foreman to be Files (3-5 Years Keep Files)					
Entr	ant Date					
Stan	d By/Entrant Date					
Stan	d By Date					

Entry Procedure II Confined Space (Hot Application)

Pern	nit #	
Natu	are of Work to be Done	
	Welding Soldering Cutting Grinding Scrapping Painting	
(Check When Completed)		
	Obtain Entry Permit (Hot Application)	
	Completed Entry Procedures I	
Check List Additional Procedures		
	Installation of an Extractor Fan With Hoses will be Installed to Remove Fumes From the Confined Space	
	Locate Fan as Close to Practical to Activity Being	
	Performed Stand By Person will have Available Fire Extinguishers Type	

Note	
	Supply Air Hoses Welding Hoses/Cables will be Removed at Every Break
	If Confined Space is Vacant for Longer than 20 Minutes Confined Space Must Be Retested for Air Quality.
Com	pletion and Reporting
	Remove all Equipment Once Work Completed Re-Lock A.V. or Confined Space. Install Cover on M.H. Notify Utilidor Foreman Upon Completion Complete Entry Permit Form and Checklists, Deliver a Cop of the Permit and Checklist to Utilidor Foreman to be Filed. (3-5 Years Keep Files)
Entra Stand	By/Entrant Date

Entry Procedures III Confine Space Self Contained Breathing Apparatus Or Airline Entry.

	Permit #	
-	Check When Completed Obtain Hot Confined Space Entry Permit Utilidor Foreman 975-1443	
	f Clean Air Cannot Be Assured in an A.V./M.H. or Confined pace the Following Procedures will be Followed.	
	Notify Rescue Service Response of Location of Confined Space Access 979-5650	
	Install Tri-Pod and Mechanical Winch	
Entrant will Wear Following Protective Equipment		
	Self Contained Breathing Apparatus (Respirator)	

	Ensure Airline Compressor is Away from any Engine Exhaust to Prevent Contamination of Air Supply. All Sources of Ignition Eliminated or Controlled	
Note: Stand By Person Will Hold Rope and Remain in Communication With Entrant Until Work is Completed		
In Case of Emergency Stand by Person Will Start Rescue Service Response. He/She May attempt to Winch Entrant out of Confined Space. He will Not Enter Confined Space Under Any Circumstances.		
Completion and Reporting ☐ Remove All Equipment Once Work Complete ☐ Re-Lock A.V. or Confined Space Install Cover on M.H. ☐ Notify Utilidor Foreman Upon Completion as well as Rescue Service Response. ☐ Complete Entry Permit Form and Check List Deliver a Copy of the Entry Permit and Check List to Utilidor Forman to be Filed (3-5 Years)		
Sta	rant Date nd By/Entrant Date nd By Date	